



## Safety Data Sheet

Copyright, 2022, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document Group:** 30-7423-4  
**Issue Date:** 05/31/22

**Version Number:** 6.01  
**Supersedes Date:** 04/07/21

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ PB910 CA Compliant

#### Product Identification Numbers

70-0075-4559-6  
7100234121

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Adhesive

This chemical/product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal.

#### 1.3. Supplier's details

**MANUFACTURER:** 3M  
**DIVISION:** Industrial Adhesives and Tapes Division  
**ADDRESS:** 3M Center, St. Paul, MN 55144-1000, USA  
**Telephone:** 1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

#### 2.1. Hazard classification

Flammable Liquid: Category 2.  
Serious Eye Damage/Irritation: Category 2B.  
Skin Sensitizer: Category 1B.  
Reproductive Toxicity: Category 1B.  
Carcinogenicity: Category 2.  
Specific Target Organ Toxicity (single exposure): Category 3.

#### 2.2. Label elements

##### Signal word

Danger

**Symbols**

Flame | Exclamation mark | Health Hazard |

**Pictograms****Hazard Statements**

Highly flammable liquid and vapor.

Causes eye irritation.

May cause an allergic skin reaction.

May cause respiratory irritation.

May cause drowsiness or dizziness.

May damage fertility or the unborn child.

Suspected of causing cancer.

**Precautionary Statements****Prevention:**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Keep container tightly closed.

Use explosion-proof electrical/ventilating/lighting equipment.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves and eye/face protection.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

**Response:**

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

IF exposed or concerned: Get medical advice/attention.

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

**Storage:**

Keep cool.

Keep container tightly closed.

Store locked up in a well-ventilated place.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

### 2.3. Hazards not otherwise classified

Repeated exposure may cause skin dryness or cracking.

## SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Methyl Acetate	79-20-9	60 - 90 Trade Secret *
Rosin, polymer with isophthalic acid and pentaerythritol	68515-02-6	10 - 30 Trade Secret *
Non-hazardous Components	Trade Secret*	10 - 30 Trade Secret *
Nitrogen	7727-37-9	< 3 Trade Secret *
Toluene	108-88-3	< 1 Trade Secret *
Methyl Isobutyl Ketone	108-10-1	< 0.5 Trade Secret *
Talc	14807-96-6	< 0.2 Trade Secret *
Methylene Chloride	75-09-2	< 0.1 Trade Secret *

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Irritating to the respiratory tract (coughing, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain). Allergic skin reaction (redness, swelling, blistering, and itching). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness).

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### Hazardous Decomposition or By-Products

**Substance**

Aldehydes  
Hydrocarbons  
Methane  
Carbon monoxide  
Carbon dioxide  
Irritant Vapors or Gases  
Ketones  
Toxic Vapor, Gas, Particulate

**Condition**

During Combustion  
During Combustion  
During Combustion  
During Combustion  
During Combustion  
During Combustion  
During Combustion  
During Combustion

**5.3. Special protective actions for fire-fighters**

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

For industrial/occupational use only. Not for consumer sale or use. Do not use in a confined area with minimal air exchange. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (gloves, respirators, etc.) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

**7.2. Conditions for safe storage including any incompatibilities**

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Protect from sunlight. Store away from

heat. Store away from acids. Store away from oxidizing agents.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Methyl Isobutyl Ketone	108-10-1	ACGIH	TWA:20 ppm;STEL:75 ppm	A3: Confirmed animal carcin.
Methyl Isobutyl Ketone	108-10-1	OSHA	TWA:410 mg/m3(100 ppm)	
Toluene	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human carcin, Ototoxicant
Toluene	108-88-3	OSHA	TWA:200 ppm;CEIL:300 ppm	
Talc	14807-96-6	ACGIH	TWA(respirable fraction):2 mg/m3	A4: Not class. as human carcin
TALC	14807-96-6	OSHA	TWA - Use asbestos limits:	
Talc	14807-96-6	OSHA	TWA concentration(respirable):0.1 mg/m3(2.4 millions of particles/cu. ft.);TWA:20 millions of particles/cu. ft.	
Methylene Chloride	75-09-2	ACGIH	TWA:50 ppm	A3: Confirmed animal carcin.
Methylene Chloride	75-09-2	OSHA	TWA:25 ppm;STEL:125 ppm	29 CFR 1910.1052, SKIN
Nitrogen	7727-37-9	ACGIH	Limit value not established:	simple asphyxiant
Methyl Acetate	79-20-9	ACGIH	TWA:200 ppm;STEL:250 ppm	
Methyl Acetate	79-20-9	OSHA	TWA:610 mg/m3(200 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

#### 8.2.2. Personal protective equipment (PPE)

##### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

##### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

Half facepiece or full facepiece supplied-air respirator

Organic vapor respirators may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Appearance

Physical state

Liquid

Color

Red

Odor

Solvent

Odor threshold

No Data Available

pH

No Data Available

Melting point

No Data Available

Boiling Point

136 °F

Flash Point

8.6 °F [Test Method: Closed Cup]

Evaporation rate

No Data Available

Flammability (solid, gas)

Not Applicable

Flammable Limits(LEL)

3.1 % volume

Flammable Limits(UEL)

16 % volume

Vapor Pressure

163 mmHg

Vapor Density

2.8 [Ref Std: AIR=1]

Density

No Data Available

Specific Gravity

0.93 -

Solubility in Water

Nil

Solubility- non-water

No Data Available

Partition coefficient: n-octanol/ water

No Data Available

Autoignition temperature

No Data Available

Decomposition temperature

No Data Available

Viscosity

No Data Available

Hazardous Air Pollutants

No Data Available

Volatile Organic Compounds

535 g/l [Details: VOC for Europe only]

Percent volatile

No Data Available

VOC Less H2O & Exempt Solvents

< 35 g/l [Test Method: calculated SCAQMD rule 443.1]

VOC Less H2O & Exempt Solvents

< 0.21 lb/gal [Test Method: calculated SCAQMD rule 443.1]

VOC Less H2O & Exempt Solvents

1.2 % [Test Method: calculated per CARB title 2]

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Sparks and/or flames

Heat

### 10.5. Incompatible materials

Not determined

### 10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

May be harmful if inhaled.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

#### Skin Contact:

Prolonged or repeated exposure may cause: Dermal Defatting: Signs/symptoms may include localized redness, itching, drying and cracking of skin. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

**Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

**Additional Health Effects:****Single exposure may cause target organ effects:**

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

**Reproductive/Developmental Toxicity:**

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

**Carcinogenicity:**

Contains a chemical or chemicals which can cause cancer.

<b>Ingredient</b>	<b>CAS No.</b>	<b>Class Description</b>	<b>Regulation</b>
Dichloromethane (methylene chloride)	75-09-2	Grp. 2A: Probable human carc.	International Agency for Research on Cancer
Dichloromethane (Methylene Chloride)	75-09-2	Anticipated human carcinogen	National Toxicology Program Carcinogens
Methyl isobutyl ketone	108-10-1	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
METHYLENE CHLORIDE	75-09-2	Cancer hazard	OSHA Carcinogens

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

<b>Name</b>	<b>Route</b>	<b>Species</b>	<b>Value</b>
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >20 - =50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Methyl Acetate	Dermal	Rat	LD50 > 2,000 mg/kg
Methyl Acetate	Inhalation-Vapor (4 hours)	Rat	LC50 > 49 mg/l
Methyl Acetate	Ingestion	Rat	LD50 > 5,000 mg/kg
Non-hazardous Components	Dermal	Not available	LD50 > 2,000 mg/kg
Non-hazardous Components	Ingestion	Not available	LD50 > 2,000 mg/kg
Rosin, polymer with isophthalic acid and pentaerythritol	Ingestion	Rat	LD50 > 5,000 mg/kg
Nitrogen	Dermal		LD50 estimated to be > 5,000 mg/kg
Nitrogen	Inhalation-Gas		LC50 estimated to be > 50,000 ppm
Nitrogen	Ingestion		LD50 estimated to be > 5,000 mg/kg
Toluene	Dermal	Rat	LD50 12,000 mg/kg
Toluene	Inhalation-Vapor (4 hours)	Rat	LC50 30 mg/l
Toluene	Ingestion	Rat	LD50 5,550 mg/kg
Methyl Isobutyl Ketone	Dermal	Rabbit	LD50 > 16,000 mg/kg
Methyl Isobutyl Ketone	Inhalation-Vapor (4 hours)	Rat	LC50 11 mg/l
Methyl Isobutyl Ketone	Ingestion	Rat	LD50 3,038 mg/kg
Talc	Dermal		LD50 estimated to be > 5,000 mg/kg
Talc	Ingestion		LD50 estimated to be > 5,000 mg/kg
Methylene Chloride	Dermal	Rat	LD50 > 2,000 mg/kg
Methylene Chloride	Inhalation-	Rat	LC50 63.7 mg/l



	Vapor (4 hours)		
Methylene Chloride	Ingestion	Rat	LD50 1,410 mg/kg

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

Name	Species	Value
Methyl Acetate	Rabbit	No significant irritation
Non-hazardous Components	Professional judgement	No significant irritation
Rosin, polymer with isophthalic acid and pentaerythritol	Rabbit	No significant irritation
Nitrogen	Professional judgement	No significant irritation
Toluene	Rabbit	Irritant
Methyl Isobutyl Ketone	Rabbit	Mild irritant
Talc	Rabbit	No significant irritation
Methylene Chloride	Rabbit	Irritant

### Serious Eye Damage/Irritation

Name	Species	Value
Methyl Acetate	Rabbit	Moderate irritant
Non-hazardous Components	Professional judgement	No significant irritation
Rosin, polymer with isophthalic acid and pentaerythritol	Rabbit	Moderate irritant
Nitrogen	Professional judgement	No significant irritation
Toluene	Rabbit	Moderate irritant
Methyl Isobutyl Ketone	Rabbit	Mild irritant
Talc	Rabbit	No significant irritation
Methylene Chloride	Rabbit	Severe irritant

### Skin Sensitization

Name	Species	Value
Methyl Acetate	Human	Not classified
Non-hazardous Components		Not classified
Rosin, polymer with isophthalic acid and pentaerythritol	Mouse	Sensitizing
Toluene	Guinea pig	Not classified
Methyl Isobutyl Ketone	Guinea pig	Not classified

### Respiratory Sensitization

Name	Species	Value
Talc	Human	Not classified

### Germ Cell Mutagenicity

Name	Route	Value
Methyl Acetate	In Vitro	Not mutagenic
Methyl Acetate	In vivo	Not mutagenic
Rosin, polymer with isophthalic acid and pentaerythritol	In Vitro	Not mutagenic

Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic
Methyl Isobutyl Ketone	In Vitro	Not mutagenic
Talc	In Vitro	Not mutagenic
Talc	In vivo	Not mutagenic
Methylene Chloride	In vivo	Not mutagenic
Methylene Chloride	In Vitro	Some positive data exist, but the data are not sufficient for classification

### Carcinogenicity

Name	Route	Species	Value
Toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
Methyl Isobutyl Ketone	Inhalation	Multiple animal species	Carcinogenic
Talc	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Methylene Chloride	Inhalation	Multiple animal species	Carcinogenic

### Reproductive Toxicity

#### Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Rosin, polymer with isophthalic acid and pentaerythritol	Not Specified	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
Rosin, polymer with isophthalic acid and pentaerythritol	Not Specified	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
Toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse
Methyl Isobutyl Ketone	Inhalation	Not classified for female reproduction	Multiple animal species	NOAEL 8.2 mg/l	2 generation
Methyl Isobutyl Ketone	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Methyl Isobutyl Ketone	Inhalation	Not classified for male reproduction	Multiple animal species	NOAEL 8.2 mg/l	2 generation
Methyl Isobutyl Ketone	Inhalation	Not classified for development	Mouse	NOAEL 12.3 mg/l	during organogenesis
Talc	Ingestion	Not classified for development	Rat	NOAEL 1,600 mg/kg	during organogenesis
Methylene Chloride	Inhalation	Not classified for female reproduction	Rat	NOAEL 5.2 mg/l	2 generation
Methylene Chloride	Inhalation	Not classified for male reproduction	Rat	NOAEL 5.2 mg/l	2 generation
Methylene Chloride	Inhalation	Not classified for development	Multiple animal	NOAEL 4.3 mg/l	during gestation

			species		
--	--	--	---------	--	--

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Methyl Acetate	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Methyl Acetate	Inhalation	respiratory irritation	May cause respiratory irritation	Human and animal	NOAEL Not available	
Methyl Acetate	Inhalation	blindness	Not classified		NOAEL Not available	
Methyl Acetate	Ingestion	central nervous system depression	May cause drowsiness or dizziness		NOAEL Not available	
Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Methyl Isobutyl Ketone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	LOAEL 0.1 mg/l	2 hours
Methyl Isobutyl Ketone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Methyl Isobutyl Ketone	Inhalation	vascular system	Not classified	Dog	NOAEL Not available	not available
Methyl Isobutyl Ketone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	LOAEL 900 mg/kg	not applicable
Methylene Chloride	Dermal	blood	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	4 hours
Methylene Chloride	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	occupational exposure
Methylene Chloride	Inhalation	blood	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Methylene Chloride	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Methyl Acetate	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	28 days
Methyl Acetate	Inhalation	endocrine system   hematopoietic system   liver   immune system   kidney and/or bladder	Not classified	Rat	NOAEL 6.1 mg/l	28 days
Toluene	Inhalation	auditory system   eyes   olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	nervous system	May cause damage to organs though prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the	Rat	LOAEL 2.3	15 months

			data are not sufficient for classification		mg/l	
Toluene	Inhalation	heart   liver   kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
Toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic system   vascular system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	liver   kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks
Methyl Isobutyl Ketone	Inhalation	liver	Not classified	Rat	NOAEL 0.41 mg/l	13 weeks
Methyl Isobutyl Ketone	Inhalation	heart	Not classified	Multiple animal species	NOAEL 0.8 mg/l	2 weeks
Methyl Isobutyl Ketone	Inhalation	kidney and/or bladder	Not classified	Multiple animal species	NOAEL 0.4 mg/l	90 days
Methyl Isobutyl Ketone	Inhalation	respiratory system	Not classified	Multiple animal species	NOAEL 4.1 mg/l	14 weeks
Methyl Isobutyl Ketone	Inhalation	endocrine system   hematopoietic system	Not classified	Multiple animal species	NOAEL 0.41 mg/l	90 days
Methyl Isobutyl Ketone	Inhalation	nervous system	Not classified	Multiple animal species	NOAEL 0.41 mg/l	13 weeks
Methyl Isobutyl Ketone	Ingestion	endocrine system   hematopoietic system   liver   kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Methyl Isobutyl Ketone	Ingestion	heart   immune system   muscles   nervous system   respiratory system	Not classified	Rat	NOAEL 1,040 mg/kg/day	120 days
Talc	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Talc	Inhalation	pulmonary fibrosis   respiratory system	Not classified	Rat	NOAEL 18 mg/m3	113 weeks
Methylene Chloride	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 6.95 mg/l	2 years
Methylene Chloride	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.17 mg/l	2 years

Methylene Chloride	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	LOAEL 35 mg/l	8 weeks
Methylene Chloride	Inhalation	heart	Not classified	Human	NOAEL Not available	
Methylene Chloride	Inhalation	immune system	Not classified	Rat	NOAEL 18 mg/l	28 days
Methylene Chloride	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 1,200 mg/kg/day	3 months
Methylene Chloride	Ingestion	blood	Not classified	Rat	NOAEL 249 mg/kg/day	2 years
Methylene Chloride	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,469 mg/kg/day	3 months
Methylene Chloride	Ingestion	eyes	Not classified	Rat	NOAEL 249 mg/kg/day	104 weeks

**Aspiration Hazard**

Name	Value
Toluene	Aspiration hazard
Methyl Isobutyl Ketone	Some positive data exist, but the data are not sufficient for classification

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information****Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

**Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

**SECTION 13: Disposal considerations****13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

**EPA Hazardous Waste Number (RCRA):** D001 (Ignitable)

**SECTION 14: Transport Information**

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

**SECTION 15: Regulatory information**

**15.1. US Federal Regulations**

Contact manufacturer for more information

**EPCRA 311/312 Hazard Classifications:****Physical Hazards**

Flammable (gases, aerosols, liquids, or solids)

**Health Hazards**

Carcinogenicity

Hazard Not Otherwise Classified (HNOC)

Reproductive toxicity

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

**Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):****Ingredient**

Methyl Isobutyl Ketone

**C.A.S. No**

108-10-1

**% by Wt**

Trade Secret < 0.5

**This material contains a chemical which requires export notification under TSCA Section 12[b]:**

**Ingredient (Category if applicable)**

Methylene Chloride

**C.A.S. No**

75-09-2

**Regulation**

Toxic Substances Control Act (TSCA) 6  
Banned or Restricted Use Chemicals

**Status**

Applicable

**Additional TSCA Information**

This chemical/product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal.

**15.2. State Regulations**

Contact manufacturer for more information

**15.3. Chemical Inventories**

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact manufacturer for more information

**15.4. International Regulations**

Contact manufacturer for more information

**This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.**

**SECTION 16: Other information****NFPA Hazard Classification**

**Health:** 2 **Flammability:** 3 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include

the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

<b>Document Group:</b>	30-7423-4	<b>Version Number:</b>	6.01
<b>Issue Date:</b>	05/31/22	<b>Supersedes Date:</b>	04/07/21

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**