

# **Safety Data Sheet**

Copyright, 2022, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 30-8246-8
 Version Number:
 9.01

 Issue Date:
 08/05/22
 Supercedes Date:
 08/04/22

# **SECTION 1: Identification**

#### 1.1. Product identifier

3M<sup>TM</sup> Novec<sup>TM</sup> 2708 Electronic Grade Coating

### **Product Identification Numbers**

98-0212-3668-6, 98-0212-3669-4, 98-0212-3691-8 7100003813, 7100063983, 7100063821

#### 1.2. Recommended use and restrictions on use

#### Recommended use

Protective Barrier Coating. For Industrial Use Only. Not Intended for Use as a Medical Device or Drug.

Restrictions on use

Approved commercial use(s): Protective coating on electronic components.

3M Electronics Materials Solutions Division (EMSD) will not knowingly sample, support, or sell its products for incorporation in medical and pharmaceutical products and applications in which the 3M product will be temporarily or permanently implanted into humans or animals. The customer is responsible for evaluating and determining that a 3M EMSD product is suitable and appropriate for its particular use and intended application. The conditions of evaluation, selection, and use of a 3M product can vary widely and affect the use and intended application of a 3M product. Because many of these conditions are uniquely within the user's knowledge and control, it is essential that the user evaluate and determine whether the 3M product is suitable and appropriate for a particular use and intended application, and complies with all local applicable laws, regulations, standards, and guidance.

## 1.3. Supplier's details

MANUFACTURER: 3M

**DIVISION:** Electronics Materials Solutions Division **ADDRESS:** 3M Center, St. Paul, MN 55144-1000, USA **Telephone:** 1-888-3M HELPS (1-888-364-3577)

# 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

# **SECTION 2: Hazard identification**

#### 2.1. Hazard classification

Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### 2.2. Label elements

# Signal word

Not applicable.

### **Symbols**

Not applicable.

### **Pictograms**

Not applicable.

# 2.3. Hazards not otherwise classified

In use, may form flammable/explosive vapour-air mixture.

10% of the mixture consists of ingredients of unknown acute dermal toxicity.

# **SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
Ethyl nonafluoroisobutyl ether	163702-06-5	50 - 84
Ethyl nonafluorobutyl ether	163702-05-4	9 - 42
Fluorinated Polymer	Trade Secret*	5 - 9.5
1-methoxy-2-propyl acetate	108-65-6	3 - 5

<sup>\*</sup>The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

# **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

#### **Skin Contact:**

Wash with soap and water. If you feel unwell, get medical attention.

#### **Eye Contact:**

No need for first aid is anticipated.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

# 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

# 5.1. Suitable extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

# 5.2. Special hazards arising from the substance or mixture

Exposure to extreme heat can give rise to thermal decomposition. Material displays no closed-cup flash point but may form flammable/explosive vapor air mixture.

## 5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

# **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sparks, flames, and extreme heat. Evacuate area. Ventilate the area with fresh air. Observe precautions from other sections.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Eliminate all potential ignition sources when cleaning up spill. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

Refer to Section 15 for additional information

# **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

Do not breathe thermal decomposition products. Store work clothes separately from other clothing, food and tobacco products. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. No smoking: Smoking while using this product can result in contamination of the tobacco and/or smoke and lead to the formation of hazardous decomposition products. Keep away from sparks, flames, and extreme heat.

# 7.2. Conditions for safe storage including any incompatibilities

Store away from heat.

Refer to Section 15 for additional information

# **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	<b>Additional Comments</b>
1-methoxy-2-propyl acetate	108-65-6	AIHA	TWA:50 ppm	
Ethyl nonafluorobutyl ether			TWA(as total isomers):200 ppm(2160 mg/m3)	
Ethyl nonafluoroisobutyl ether	163702-06-	Manufacturer	TWA(as total isomers):200	
	5	determined	ppm(2160 mg/m3)	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

## 8.2. Exposure controls

## 8.2.1. Engineering controls

For those situations where the material might be exposed to extreme overheating due to misuse or equipment failure, use with appropriate local exhaust ventilation sufficient to maintain levels of thermal decomposition products below their exposure guidelines. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Provide ventilation adequate to maintain vapor concentration below lower explosive concentration.

#### 8.2.2. Personal protective equipment (PPE)

### Eye/face protection

None required.

### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl Rubber Neoprene

# Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

For those situations where the material might be exposed to extreme overheating due to misuse or equipment failure, use a positive pressure supplied-air respirator.

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors

For questions about suitability for a specific application, consult with your respirator manufacturer.

Refer to Section 15 for additional information

# **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Appearance

Physical state Liquid

Color Yellow-Orange

Odor Slight Ether

Odor thresholdNo Data AvailablepHNot ApplicableMelting pointNot Applicable

**Boiling Point** 76 °C

Flash Point No flash point [Test Method: Closed Cup] [Details: ASTM

D3278-96e1]

Evaporation rateNo Data AvailableFlammability (solid, gas)Not Applicable

Flammable Limits(LEL)

2.14 % [Details: ASTM E681 Method at 175 °C]

Flammable Limits(UEL)

2.14 % [Details: ASTM E681 Method at 175 °C]

Vapor Pressure109 mmHg [@ 25 °C]Vapor DensityNo Data AvailableDensity1.4 g/ml

Specific Gravity

1.4 [Ref Std:WATER=1]

Solubility In WaterNo Data AvailableSolubility- non-waterNo Data AvailablePartition coefficient: n-octanol/ waterNo Data Available

Autoignition temperature 375 °C

Decomposition temperatureNo Data AvailableViscosityNo Data AvailableMolecular weightNo Data Available

Percent volatile 89 - 92 %

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

# 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

# 10.4. Conditions to avoid

Heat

Sparks and/or flames

## 10.5. Incompatible materials

None known.

# 10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>	
Hydrocarbons	At Elevated Temperatures -	Extreme conditions
	of heat	
Carbon monoxide	At Elevated Temperatures -	Extreme conditions
	of heat	
Carbon dioxide	At Elevated Temperatures -	Extreme conditions
	of heat	
Hydrogen Fluoride	At Elevated Temperatures -	Extreme conditions
	of heat	
Perfluoroisobutylene (PFIB)	At Elevated Temperatures -	Extreme conditions
	of heat	
Toxic Vapor, Gas, Particulate	At Elevated Temperatures -	Extreme conditions
	of heat	

If the product is exposed to extreme condition of heat from misuse or equipment failure, toxic decomposition products that include hydrogen fluoride and perfluoroisobutylene can occur.

# **SECTION 11: Toxicological information**

.....

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

# 11.1. Information on Toxicological effects

# Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### **Inhalation:**

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

### **Skin Contact:**

May be harmful in contact with skin.

Contact with the skin during product use is not expected to result in significant irritation.

### **Eye Contact:**

Contact with the eyes during product use is not expected to result in significant irritation.

### **Ingestion:**

May be harmful if swallowed.

### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

## **Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >2,000 - =5,000
•			mg/kg
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000
			mg/kg
Ethyl nonafluoroisobutyl ether	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Ethyl nonafluoroisobutyl ether	Inhalation-	Rat	LC50 > 989 mg/l
	Vapor (4		
	hours)		
Ethyl nonafluoroisobutyl ether	Ingestion	Rat	LD50 > 2,000 mg/kg
Ethyl nonafluorobutyl ether	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Ethyl nonafluorobutyl ether	Inhalation-	Rat	LC50 > 989 mg/l
	Vapor (4		
	hours)		
Ethyl nonafluorobutyl ether	Ingestion	Rat	LD50 > 2,000  mg/kg
Fluorinated Polymer	Ingestion	Rat	LD50 > 2,000 mg/kg
1-methoxy-2-propyl acetate	Dermal	Rabbit	LD50 > 5,000 mg/kg
1-methoxy-2-propyl acetate	Inhalation-	Rat	LC50 > 28.8 mg/l
	Vapor (4		
	hours)		
1-methoxy-2-propyl acetate	Ingestion	Rat	LD50 8,532 mg/kg

ATE = acute toxicity estimate

# Skin Corrosion/Irritation

Name	Species	Value

**Page** 6 **of** 11

Ethyl nonafluoroisobutyl ether	Rabbit	No significant irritation
Ethyl nonafluorobutyl ether	Rabbit	No significant irritation
Fluorinated Polymer	Rabbit	No significant irritation
1-methoxy-2-propyl acetate	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name		Value
	D 11.7	N : : : : : : : : : : : : : : : : : : :
Ethyl nonafluoroisobutyl ether	Rabbit	No significant irritation
Ethyl nonafluorobutyl ether	Rabbit	No significant irritation
1-methoxy-2-propyl acetate	Rabbit	Mild irritant

# **Skin Sensitization**

Name	Species	Value
Ethyl nonafluoroisobutyl ether	Guinea	Not classified
	pig	
Ethyl nonafluorobutyl ether	Guinea	Not classified
	pig	
1-methoxy-2-propyl acetate	Guinea	Not classified
	pig	

# **Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity** 

Name	Route	Value
Ethyl nonafluoroisobutyl ether	In Vitro	Not mutagenic
Ethyl nonafluoroisobutyl ether	In vivo	Not mutagenic
Ethyl nonafluorobutyl ether	In Vitro	Not mutagenic
Ethyl nonafluorobutyl ether	In vivo	Not mutagenic
1-methoxy-2-propyl acetate	In Vitro	Not mutagenic

# Carcinogenicity

For the component/components, either no data are currently available or the data are not sufficient for classification.

# **Reproductive Toxicity**

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Ethyl nonafluoroisobutyl ether	Inhalation	Not classified for development	Rat	NOAEL 260 mg/l	during gestation
Ethyl nonafluorobutyl ether	Inhalation	Not classified for development	Rat	NOAEL 260 mg/l	during gestation
1-methoxy-2-propyl acetate	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
1-methoxy-2-propyl acetate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
1-methoxy-2-propyl acetate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
1-methoxy-2-propyl acetate	Inhalation	Not classified for development	Rat	NOAEL 21.6 mg/l	during organogenesi s

# Target Organ(s)

# **Specific Target Organ Toxicity - single exposure**

**Page** 7 **of** 11

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Ethyl nonafluoroisobutyl ether	Inhalation	cardiac sensitization	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL 204 mg/l	17 minutes
Ethyl nonafluoroisobutyl ether	Inhalation	respiratory irritation	Not classified	Rat	NOAEL 989 mg/l	4 hours
Ethyl nonafluorobutyl ether	Inhalation	cardiac sensitization	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL 204 mg/l	17 minutes
Ethyl nonafluorobutyl ether	Inhalation	respiratory irritation	Not classified	Rat	NOAEL 989 mg/l	4 hours
1-methoxy-2-propyl acetate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure** 

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Ethyl nonafluoroisobutyl ether	Inhalation	liver   kidney and/or bladder   respiratory system   heart   endocrine system   gastrointestinal tract   bone marrow   hematopoietic system   immune system   nervous system	Not classified	Rat	NOAEL 263.4 mg/l	4 weeks
Ethyl nonafluoroisobutyl ether	Ingestion	blood   liver   kidney and/or bladder   heart   endocrine system   bone marrow   hematopoietic system   immune system   nervous system   respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Ethyl nonafluorobutyl ether	Inhalation	liver   kidney and/or bladder   respiratory system   heart   endocrine system   gastrointestinal tract   bone marrow   hematopoietic system   immune system   nervous system	Not classified	Rat	NOAEL 263.4 mg/l	4 weeks
Ethyl nonafluorobutyl ether	Ingestion	blood   liver   kidney and/or bladder   heart   endocrine system   bone marrow   hematopoietic system   immune system   nervous system   respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
1-methoxy-2-propyl acetate	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 16.2 mg/l	9 days
1-methoxy-2-propyl acetate	Inhalation	olfactory system	Not classified	Mouse	LOAEL 1.62 mg/l	9 days
1-methoxy-2-propyl acetate	Inhalation	blood	Not classified	Multiple animal species	NOAEL 16.2 mg/l	9 days
1-methoxy-2-propyl acetate	Ingestion	endocrine system	Not classified	Rat	NOAEL 1,000	44 days

Page 8 of

3M <sup>TM</sup> Novec <sup>TM</sup> 2708 Electronic Grade Coating	08/05/22	

		mg/kg/day	

#### **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

# **Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

#### **Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

# **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include HF. Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

### EPA Hazardous Waste Number (RCRA): Not regulated

Refer to Section 15 for additional information

# **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

# **SECTION 15: Regulatory information**

# 15.1. US Federal Regulations

Contact 3M for more information.

# **EPCRA 311/312 Hazard Classifications:**

Physical Hazards	
Not applicable	

Health Hazards		
Not applicable		

# Additional TSCA Information

Components	CAS No	Additional Information
Fluorinated Polymer	Trade Secret	Allowed use: Protective coating. Required exposure controls
		when handling the LVE substance: Appropriate local exhaust
		ventilation; safety goggles with side shields or goggles;
		gloves; NIOSH-approved full face air-purifying respirator with
		organic vapor cartridges or a half facepiece/full face pressure
		demand self-contained breathing apparatus based on exposure
		assesment and potential particulate exposure risks; Use positive
		pressure supplied-air respirator if there is potential for
		uncontrolled release or unknown exposure levels. Required
		environmental release controls for the LVE substance:
		Incineration of wastes and cleanup materials at a permitted
		facility.

# 15.2. State Regulations

Contact 3M for more information.

#### 15.3. Chemical Inventories

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of the Korean Toxic Chemical Control Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the chemical notification requirements of TSCA. One or more of the components in this material is not listed on the TSCA inventory, but is approved for specific commercial use(s) under a US EPA low volume exemption.

Contact 3M for more information.

## 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

# **SECTION 16: Other information**

## NFPA Hazard Classification

Health: 3 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

The NFPA Health code of 3 is due to emergency situations where the material may thermally decompose and release Hydrogen Fluoride and Perfluoroisobutylene (PFIB). During normal use conditions, please reference Section 2 and Section 11 of the SDS for additional health hazard information.

### **HMIS Hazard Classification**

**Health:** 1 Flammability: 1 Physical Hazard: 0 Personal Protection: X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

 Document Group:
 30-8246-8
 Version Number:
 9.01

 Issue Date:
 08/05/22
 Supercedes Date:
 08/04/22

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com