

# Safety Data Sheet

Copyright, 2024, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:30-3770-2Version Number:3.00Issue Date:01/26/24Supercedes Date:05/22/23

# **SECTION 1: Identification**

### 1.1. Product identifier

3M<sup>TM</sup> Aerospace Sealant AC-730 B-1/2 PMF

### **Product Identification Numbers**

70-0052-0381-8, 70-0052-0385-9, 70-0052-0386-7, 75-0002-0568-4 7010295113, 7010371675, 7100319044

#### 1.2. Recommended use and restrictions on use

### Recommended use

For industrial or professional use only., Sealant

1.3. Supplier's details

MANUFACTURER: 3M

**DIVISION:** Automotive and Aerospace Solutions Division ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA Telephone: 1-888-3M HELPS (1-888-364-3577)

### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

# **SECTION 2: Hazard identification**

### 2.1. Hazard classification

Skin Sensitizer: Category 1.

Specific Target Organ Toxicity (repeated exposure): Category 1.

# 2.2. Label elements

### Signal word

Danger

**Symbols** 

Exclamation mark | Health Hazard |

# **Pictograms**





### **Hazard Statements**

May cause an allergic skin reaction.

Causes damage to organs through prolonged or repeated exposure: nervous system  $\ \mid$ 

respiratory system

# **Precautionary Statements**

### **Prevention:**

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

# **Response:**

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Get medical advice/attention if you feel unwell.

### Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

# **SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
POLYSULFIDE RUBBER	68611-50-7	55 - 65
CALCIUM CARBONATE	471-34-1	20 - 30
HYDROGENATED TERPHENYL	61788-32-7	1 - 5
MANGANESE DIOXIDE	1313-13-9	1 - 5 Trade Secret *
ZINC PHOSPHATE	7779-90-0	1 - 3
PHENOL-FORMALDEHYDE POLYMER	9003-35-4	0.1 - 0.5 Trade Secret *

<sup>\*</sup>The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

#### **Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

### **Eye Contact:**

If exposed, flush eyes with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms develop, get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### **Hazardous Decomposition or By-Products**

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Oxides of Nitrogen	During Combustion
Oxides of Sulfur	During Combustion

### 5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

**Page** 3 **of** 11

Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases.

# **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	<b>Additional Comments</b>
MANGANESE COMPOUNDS	1313-13-9	OSHA	CEIL(as Mn):5 mg/m3	
MANGANESE, INORGANIC	1313-13-9	ACGIH	TWA(as Mn, respirable	A4: Not class. as human
COMPOUNDS			fraction):0.02 mg/m3;TWA(as	carcin
			Mn, inhalable fraction):0.1	
			mg/m3	
DUST, INERT OR NUISANCE	471-34-1	OSHA	TWA(as total dust):15	
			mg/m3;TWA(as total dust):50	
			millions of particles/cu. ft.(15	
			mg/m3);TWA(respirable	
			fraction):5	
			mg/m3;TWA(respirable	
			fraction):15 millions of	
	451 04 1	A GOTT	particles/cu. ft.(5 mg/m3)	
Particles (insoluble or poorly	471-34-1	ACGIH	TWA(inhalable	
soluble) not otherwise specified,			particulates):10 mg/m3	
inhalable particles	471 24 1	A CCITI	TWA ( : 11 (: 1 ) 2	
Particles (insoluble or poorly	471-34-1	ACGIH	TWA(respirable particles):3	
soluble) not otherwise specified,			mg/m3	
respirable particles	(1700 22 7	A CCIII	TWA.O.5	
HYDROGENATED	61788-32-7	ACGIH	TWA:0.5 ppm	
TERPHENYL				

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

### 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

## Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

## Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Appearance

Physical stateLiquidColorDark Brown

OdorSlight OdorOdor thresholdNo Data AvailablepHNot ApplicableMelting pointNot Applicable

Boiling Point No Data Available

Flash Point >=200 °F [Test Method: Closed Cup]

Evaporation rateNo Data ĀvailableFlammability (solid, gas)Not ApplicableFlammable Limits(LEL)No Data AvailableFlammable Limits(UEL)No Data Available

Vapor Pressure Negligible

**Vapor Density** >=1 [Ref Std:AIR=1]

**Density** 1.58 g/ml

Specific Gravity >=1.58 [Ref Std:WATER=1]

Solubility in Water Nil

Solubility- non-waterNo Data AvailablePartition coefficient: n-octanol/ waterNo Data AvailableAutoignition temperatureNo Data AvailableDecomposition temperatureNo Data AvailableViscosityNo Data Available

**Volatile Organic Compounds**3.7 g/l [*Test Method*:calculated SCAQMD rule 443.1] **VOC Less H2O & Exempt Solvents**3.7 g/l [*Test Method*:calculated SCAQMD rule 443.1]

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Heat

### 10.5. Incompatible materials

Reducing agents Strong acids Strong bases

### 10.6. Hazardous decomposition products

### Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

### Inhalation:

May cause additional health effects (see below).

#### **Skin Contact:**

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

### **Eve Contact:**

Contact with the eyes during product use is not expected to result in significant irritation.

### **Ingestion:**

No known health effects.

### **Additional Health Effects:**

### Prolonged or repeated exposure may cause target organ effects:

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

## **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity** 

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
POLYSULFIDE RUBBER	Dermal	Rat	LD50 > 7,800 mg/kg
POLYSULFIDE RUBBER	Ingestion	Rat	LD50 > 5,000 mg/kg
CALCIUM CARBONATE	Dermal	Rat	LD50 > 2,000 mg/kg
CALCIUM CARBONATE	Inhalation- Dust/Mist (4 hours)	Rat	LC50 3 mg/l
CALCIUM CARBONATE	Ingestion	Rat	LD50 6,450 mg/kg
MANGANESE DIOXIDE	Dermal	Rat	LD50 2,000 mg/kg
MANGANESE DIOXIDE	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 1.5 mg/l
MANGANESE DIOXIDE	Ingestion	Rat	LD50 > 2,197 mg/kg
HYDROGENATED TERPHENYL	Dermal	Rabbit	LD50 > 2,000 mg/kg
HYDROGENATED TERPHENYL	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 4.7 mg/l
HYDROGENATED TERPHENYL	Ingestion	Rat	LD50 > 10,000 mg/kg
ZINC PHOSPHATE	Dermal		LD50 estimated to be > 5,000 mg/kg
ZINC PHOSPHATE	Ingestion	Rat	LD50 > 5,000 mg/kg
PHENOL-FORMALDEHYDE POLYMER	Dermal	Rat	LD50 > 2,000 mg/kg
PHENOL-FORMALDEHYDE POLYMER	Ingestion	Rat	LD50 > 2,900 mg/kg

ATE = acute toxicity estimate

## Skin Corrosion/Irritation

Name	Species	Value
DOLVCHI FIDE DUDDED	D 11.7	N · · · · · · · · · · · · · · · · · · ·
POLYSULFIDE RUBBER	Rabbit	No significant irritation
CALCIUM CARBONATE  MANGANESE DIOXIDE	Rabbit Rabbit	No significant irritation  No significant irritation
HYDROGENATED TERPHENYL	Rabbit	No significant irritation
PHENOL-FORMALDEHYDE POLYMER	Human	Mild irritant
	and	
	animal	

Serious Eye Damage/Irritation

Name	Species	Value
POLYSULFIDE RUBBER	Rabbit	No significant irritation
CALCIUM CARBONATE	Rabbit	No significant irritation
MANGANESE DIOXIDE	Rabbit	Mild irritant
HYDROGENATED TERPHENYL	Rabbit	No significant irritation
PHENOL-FORMALDEHYDE POLYMER	Human	Moderate irritant
	and	
	animal	

# **Skin Sensitization**

Name	Species	Value
POLYSULFIDE RUBBER		Not classified
MANGANESE DIOXIDE	Mouse	Not classified
HYDROGENATED TERPHENYL	Human	Not classified

Page 7 of 11

01/26/24

PHENOL-FORMALDEHYDE POLYMER	Human	Sensitizing
	and	
	animal	

**Respiratory Sensitization** 

Name	Species	Value
PHENOL-FORMALDEHYDE POLYMER	Human	Not classified

**Germ Cell Mutagenicity** 

Name	Route	Value
MANGANESE DIOXIDE	In Vitro	Some positive data exist, but the data are not sufficient for classification
MANGANESE DIOXIDE	In vivo	Some positive data exist, but the data are not sufficient for classification
HYDROGENATED TERPHENYL	In Vitro	Not mutagenic
HYDROGENATED TERPHENYL	In vivo	Not mutagenic

# Carcinogenicity

For the component/components, either no data are currently available or the data are not sufficient for classification.

# **Reproductive Toxicity**

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
CALCIUM CARBONATE	Ingestion	Not classified for development	Rat	NOAEL 625 mg/kg/day	premating & during gestation
MANGANESE DIOXIDE	Inhalation	Not classified for female reproduction	Rat	NOAEL 20 mg/m3	2 generation
MANGANESE DIOXIDE	Inhalation	Not classified for male reproduction	Rabbit	LOAEL 250 mg/kg	1 days
MANGANESE DIOXIDE	Ingestion	Not classified for development	Rat	LOAEL 354 mg/kg/day	premating into lactation
MANGANESE DIOXIDE	Inhalation	Not classified for development	Rat	LOAEL 61 mg/m3	gestation into lactation
HYDROGENATED TERPHENYL	Ingestion	Not classified for female reproduction	Rat	NOAEL 81 mg/kg/day	2 generation
HYDROGENATED TERPHENYL	Ingestion	Not classified for male reproduction	Rat	NOAEL 62 mg/kg/day	2 generation
HYDROGENATED TERPHENYL	Ingestion	Not classified for development	Rat	NOAEL 500 mg/kg/day	during organogenesi s

# Target Organ(s)

**Specific Target Organ Toxicity - single exposure** 

specific ranger organ rowerly single exposure						
Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure
						Duration
CALCIUM CARBONATE	Inhalation	respiratory system	Not classified	Rat	NOAEL	90 minutes
					0.812 mg/l	
PHENOL-	Inhalation	respiratory irritation	Some positive data exist, but the	Human	NOAEL Not	
FORMALDEHYDE			data are not sufficient for	and	available	
POLYMER			classification	animal		

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
CALCIUM CARBONATE	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure

Page 8 of 11

MANGANESE DIOXIDE	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Monkey	LOAEL 1.1 mg/m3	10 months
MANGANESE DIOXIDE	Inhalation	nervous system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
HYDROGENATED TERPHENYL	Dermal	skin	Not classified	Rabbit	NOAEL 500 mg/kg/day	3 weeks
HYDROGENATED TERPHENYL	Dermal	hematopoietic system	Not classified	Rabbit	NOAEL 2,000 mg/kg/day	3 weeks
HYDROGENATED TERPHENYL	Inhalation	liver   hematopoietic system   eyes	Not classified	Rat	NOAEL 0.5 mg/l	13 weeks
HYDROGENATED TERPHENYL	Ingestion	hematopoietic system   kidney and/or bladder   liver   eyes   respiratory system	Not classified	Rat	NOAEL 120 mg/kg/day	14 weeks
PHENOL- FORMALDEHYDE POLYMER	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure

### **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

# **Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

### Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

# **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

# **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

# **SECTION 15: Regulatory information**

# 15.1. US Federal Regulations

Contact 3M for more information.

### **EPCRA 311/312 Hazard Classifications:**

## Physical Hazards

Not applicable

### Health Hazards

Respiratory or Skin Sensitization

Specific target organ toxicity (single or repeated exposure)

## Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>	
MANGANESE DIOXIDE (MANGANESE	1313-13-9	Trade Secret	1 - 5
COMPOUNDS)			
ZINC PHOSPHATE (ZINC COMPOUNDS)	7779-90-0	1 - 3	

# 15.2. State Regulations

Contact 3M for more information.

### 15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

# 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

# **SECTION 16: Other information**

### NFPA Hazard Classification

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:30-3770-2Version Number:3.00Issue Date:01/26/24Supercedes Date:05/22/23

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness

or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com

\_\_\_\_