



## Safety Data Sheet

Copyright, 2024, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

This Safety Data Sheet has been prepared in accordance with the SS586 Specification for Hazard Communication for Hazardous Chemicals and Dangerous Goods.

<b>Document group:</b>	11-0058-5	<b>Version number:</b>	3.00
<b>Issue Date:</b>	30/08/2024	<b>Supersedes date:</b>	05/02/2024

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Hot Melt Adhesive 3764-AE, 3764-PG, 3764-TC, 3764-Q, 3764-B

#### Product Identification Numbers

62-3764-7230-4	62-3764-7231-2	62-3764-7232-0	62-3764-7233-8	62-3764-7234-6
62-3764-7235-3	62-3764-7236-1	62-3764-8530-6	62-3764-9030-6	62-3764-9130-4
62-3764-9132-0	62-3764-9135-3	62-3764-9136-1	62-3764-9230-2	62-3764-9231-0
62-3764-9232-8	62-3764-9330-0	62-3764-9333-4	62-3764-9335-9	62-3764-9336-7
62-3764-9337-5	62-3764-9338-3	62-3764-9339-1	62-3764-9395-3	62-3764-9399-5
62-3764-9530-5	62-3764-9531-3	62-3764-9536-2	62-3764-9537-0	62-3764-9830-9
62-3764-9835-8	62-3764-9836-6	62-3764-9930-7		

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Adhesive, Hot-melt adhesive

#### 1.3. Supplier's details

**Address:** 3M Technologies (S) Pte Ltd, 10 Ang Mo Kio Street 65, Singapore 569059  
**Telephone:** +65 6450 8888  
**Website:** www.3m.com.sg

#### 1.4. Emergency telephone number

+65 6591 6601 (8.15am - 5.00pm, Monday - Friday)

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

This product is not classified as hazardous per GHS criteria as implemented by Singapore Standard SS586: 2022.

#### 2.2. Label elements

##### SIGNAL WORD

Not applicable.

##### Symbols

Not applicable

**Pictograms**

Not applicable

**2.3. Other hazards**

May cause thermal burns. 3M Avoid contact with hot extruded material or applicator tip. Avoid direct eye exposure to vapours. 3M In case of skin contact with molten material, immediately flush with cold water and cover with a clean dressing. Do not attempt to remove adhesive. Have burn treated by a medical doctor.

**SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	CAS Nbr	% by Wt
Ethylene - vinyl acetate copolymer	24937-78-8	< 65
Naptha (Petroleum), Llight Steam-Cracked, Debenzenized, Polymers, Hydrogenated	68132-00-3	< 40
Hydrocarbon resin	Mixture	< 35
Polyethylene Polymer	9006-26-2	1 - 10
Polyolefin Wax	8002-74-2	1 - 10
Antioxidant	6683-19-8	< 2
Vinyl Acetate	108-05-4	< 0.5

**SECTION 4: First aid measures****4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you are concerned, get medical advice.

**Skin contact**

Immediately flush skin with large amounts of cold water for at least 15 minutes. DO NOT ATTEMPT TO REMOVE MOLTEN MATERIAL. Cover affected area with a clean dressing. Get immediate medical attention.

**Eye contact**

Immediately flush eyes with large amounts of water for at least 15 minutes. DO NOT ATTEMPT TO REMOVE MOLTEN MATERIAL. Get immediate medical attention.

**If swallowed**

Rinse mouth. If you are concerned, get medical advice.

**4.2. Most important symptoms and effects, both acute and delayed**

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

**SECTION 5: Fire-fighting measures****5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

**5.2. Special hazards arising from the substance or mixture**

None inherent in this product.

**Hazardous Decomposition or By-Products**

**Substance**

Carbon monoxide.  
Carbon dioxide.  
Irritant vapours or gases.

**Condition**

During combustion.  
During combustion.  
During combustion.

**5.3. Special protective actions for fire-fighters**

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. Observe precautions from other sections.

**6.2. Environmental precautions**

Avoid release to the environment.

**6.3. Methods and material for containment and cleaning up**

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

Avoid skin contact with hot material. For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Use personal protective equipment (eg. gloves, respirators...) as required.

**7.2. Conditions for safe storage including any incompatibilities**

Store away from heat.

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Vinyl Acetate	108-05-4	ACGIH	TWA:10 ppm;STEL:15 ppm	A3: Confirmed animal carcin.
Vinyl Acetate	108-05-4	Singapore PELs	TWA(8 hours):35 mg/m <sup>3</sup> (10 ppm);STEL(15 minutes):53 mg/m <sup>3</sup> (15 ppm)	
Polyolefin Wax	8002-74-2	ACGIH	TWA(as fume):2 mg/m <sup>3</sup>	
Polyolefin Wax	8002-74-2	Singapore PELs	TWA(as fume)(8 hours):2 mg/m <sup>3</sup>	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

Singapore PELs : Singapore. Workplace Safety and Health (Permissible Exposure Levels of Toxic Substances) Order

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

None required.

#### Skin/hand protection

No chemical protective gloves are required.

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

#### Thermal hazards

Wear heat insulating gloves, indirect vented goggles, and a full face shield when handling hot material to prevent thermal burns.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Solid.
Specific Physical Form:	Waxy Solid
Color	White
Odor	Odorless
Odour threshold	<i>No data available.</i>
pH	<i>Not applicable.</i>
Melting point/Freezing point	<i>No data available.</i>
Boiling point/Initial boiling point/Boiling range	<i>Not applicable.</i>
Flash point	267.8 °C [Test Method:Cleveland Open Cup] [Details:Conditions: ASTM D-92-72]
Evaporation rate	<i>Not applicable.</i>
Flammability	Not applicable.
Flammable Limits(LEL)	<i>Not applicable.</i>
Flammable Limits(UEL)	<i>Not applicable.</i>
Vapour pressure	<i>No data available.</i>
Vapor Density and/or Relative Vapor Density	<i>No data available.</i>
Density	0.95 g/cm <sup>3</sup>
Relative density	0.95 [Ref Std:WATER=1]
Water solubility	Nil
Solubility- non-water	<i>No data available.</i>

Partition coefficient: n-octanol/water	No data available.
Autoignition temperature	No data available.
Decomposition temperature	No data available.
Kinematic Viscosity	Not applicable.
Volatile organic compounds (VOC)	0 g/l [Test Method:calculated SCAQMD rule 443.1]
Percent volatile	0 % weight
VOC less H2O & exempt solvents	0 g/l [Test Method:calculated SCAQMD rule 443.1]
Molecular weight	No data available.
Solids content	100 %

Particle Characteristics	Not applicable.
--------------------------	-----------------

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material is considered to be non reactive under normal use conditions

### 10.2 Chemical stability

Stable.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.4 Conditions to avoid

None known.

### 10.5 Incompatible materials

None known.

### 10.6 Hazardous decomposition products

#### Substance

None known.

#### Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1 Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

May cause additional health effects (see below).

#### Skin contact

During heating: Thermal Burns: Signs/symptoms may include intense pain, redness and swelling, and tissue destruction.

**Eye contact**

During heating: Thermal Burns: Signs/symptoms may include severe pain, redness and swelling, and tissue destruction.

**Ingestion**

May cause additional health effects (see below).

**Additional Health Effects:**

**Carcinogenicity:**

Contains a chemical or chemicals which can cause cancer.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Ethylene - vinyl acetate copolymer	Dermal		LD50 estimated to be > 5,000 mg/kg
Ethylene - vinyl acetate copolymer	Ingestion	Rat	LD50 > 1,000 mg/kg
Naptha (Petroleum), Llight Steam-Cracked, Debenzenized, Polymers, Hydrogenated	Dermal		LD50 estimated to be > 5,000 mg/kg
Naptha (Petroleum), Llight Steam-Cracked, Debenzenized, Polymers, Hydrogenated	Ingestion		LD50 estimated to be > 5,000 mg/kg
Hydrocarbon resin	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
Hydrocarbon resin	Ingestion	Professional judgement	LD50 7,000 mg/kg
Polyethylene Polymer	Dermal	Rabbit	LD50 > 7,940 mg/kg
Polyethylene Polymer	Ingestion	Rat	LD50 > 10,000 mg/kg
Polyolefin Wax	Dermal	Rat	LD50 > 5,000 mg/kg
Polyolefin Wax	Ingestion	Rat	LD50 > 5,000 mg/kg
Antioxidant	Dermal	Rabbit	LD50 > 3,160 mg/kg
Antioxidant	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 1.95 mg/l
Antioxidant	Ingestion	Rat	LD50 > 10,250 mg/kg
Vinyl Acetate	Dermal	Rabbit	LD50 2,320 mg/kg
Vinyl Acetate	Inhalation-Vapor (4 hours)	Rat	LC50 11.3 mg/l
Vinyl Acetate	Ingestion	Rat	LD50 2,920 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Ethylene - vinyl acetate copolymer	Professional judgement	No significant irritation
Hydrocarbon resin	Professional judgement	No significant irritation
Naptha (Petroleum), Llight Steam-Cracked, Debenzenized, Polymers,	Professio	No significant irritation

Hydrogenated	nal judgement	
Polyethylene Polymer	Rabbit	No significant irritation
Polyolefin Wax	Rabbit	No significant irritation
Antioxidant	Rabbit	No significant irritation
Vinyl Acetate	Rabbit	Minimal irritation

### Serious Eye Damage/Irritation

Name	Species	Value
Ethylene - vinyl acetate copolymer	Professional judgement	No significant irritation
Naptha (Petroleum), Llight Steam-Cracked, Debenzenized, Polymers, Hydrogenated	Professional judgement	No significant irritation
Polyethylene Polymer	Rabbit	Mild irritant
Polyolefin Wax	Rabbit	No significant irritation
Antioxidant	Rabbit	Mild irritant
Vinyl Acetate	Rabbit	Mild irritant

### Sensitization:

#### Skin Sensitisation

Name	Species	Value
Polyolefin Wax	Guinea pig	Not classified
Antioxidant	Human and animal	Not classified
Vinyl Acetate	Guinea pig	Not classified

#### Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

#### Germ Cell Mutagenicity

Name	Route	Value
Hydrocarbon resin	In Vitro	Not mutagenic
Polyolefin Wax	In Vitro	Not mutagenic
Antioxidant	In Vitro	Not mutagenic
Antioxidant	In vivo	Not mutagenic
Vinyl Acetate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Vinyl Acetate	In vivo	Some positive data exist, but the data are not sufficient for classification

#### Carcinogenicity

Name	Route	Species	Value
Polyolefin Wax	Ingestion	Rat	Not carcinogenic
Antioxidant	Ingestion	Multiple animal species	Not carcinogenic
Vinyl Acetate	Ingestion	Multiple animal species	Carcinogenic.
Vinyl Acetate	Inhalation	Rat	Carcinogenic.

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Antioxidant	Ingestion	Not classified for female reproduction	Rat	NOAEL 688 mg/kg/day	2 generation
Antioxidant	Ingestion	Not classified for male reproduction	Rat	NOAEL 688 mg/kg/day	2 generation
Antioxidant	Ingestion	Not classified for development	Multiple animal species	NOAEL 1,000 mg/kg/day	during organogenesis
Vinyl Acetate	Ingestion	Not classified for female reproduction	Rat	NOAEL 140 mg/kg/day	2 generation
Vinyl Acetate	Ingestion	Not classified for male reproduction	Rat	NOAEL 140 mg/kg/day	2 generation
Vinyl Acetate	Ingestion	Not classified for development	Rat	NOAEL 700 mg/kg/day	2 generation
Vinyl Acetate	Inhalation	Not classified for development	Rat	NOAEL 0.7 mg/l	during organogenesis

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Vinyl Acetate	Inhalation	respiratory irritation	May cause respiratory irritation	Human and animal	NOAEL Not available	
Vinyl Acetate	Inhalation	central nervous system depression	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Ethylene - vinyl acetate copolymer	Ingestion	liver	Not classified	Rat	NOAEL 4,000 mg/kg/day	90 days
Polyolefin Wax	Ingestion	heart	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 15 mg/kg/day	90 days
Polyolefin Wax	Ingestion	hematopoietic system   liver   immune system   skin   endocrine system   bone, teeth, nails, and/or hair   muscles   nervous system   eyes   kidney and/or bladder   respiratory system   vascular system	Not classified	Rat	NOAEL 1,500 mg/kg/day	90 days
Antioxidant	Ingestion	endocrine system	Not classified	Rat	NOAEL 450 mg/kg/day	2 years
Antioxidant	Ingestion	liver	Not classified	Dog	NOAEL 302 mg/kg/day	90 days
Antioxidant	Ingestion	hematopoietic system   nervous system   kidney and/or bladder	Not classified	Rat	NOAEL 2,500 mg/kg/day	90 days
Antioxidant	Ingestion	auditory system   eyes	Not classified	Dog	NOAEL 302 mg/kg/day	90 days
Vinyl Acetate	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for	Multiple animal	NOAEL 0.2 mg/l	104 weeks



			classification	species		
Vinyl Acetate	Inhalation	heart   hematopoietic system   liver   kidney and/or bladder	Not classified	Rat	NOAEL 2.1 mg/l	104 weeks
Vinyl Acetate	Inhalation	endocrine system	Not classified	Rat	NOAEL 0.07 mg/l	120 days
Vinyl Acetate	Inhalation	immune system	Not classified	Multiple animal species	NOAEL 3.5 mg/l	3 months
Vinyl Acetate	Inhalation	nervous system	Not classified	Multiple animal species	NOAEL 2.1 mg/l	104 weeks
Vinyl Acetate	Inhalation	gastrointestinal tract	Not classified	Mouse	NOAEL 3.5 mg/l	3 months
Vinyl Acetate	Ingestion	liver	Not classified	Rat	LOAEL 684 mg/kg/day	3 months
Vinyl Acetate	Ingestion	hematopoietic system   nervous system   kidney and/or bladder	Not classified	Rat	NOAEL 235 mg/kg/day	104 weeks
Vinyl Acetate	Ingestion	immune system   respiratory system	Not classified	Mouse	NOAEL 950 mg/kg/day	3 months
Vinyl Acetate	Ingestion	heart	Not classified	Rat	NOAEL 235 mg/kg/day	104 weeks

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

**12.1. Toxicity**

**Acute aquatic hazard:**

Not acutely toxic to aquatic life by GHS criteria.

**Chronic aquatic hazard:**

Not chronically toxic to aquatic life by GHS criteria.

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
Ethylene - vinyl acetate copolymer	24937-78-8	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Naptha (Petroleum), Llight Steam-Cracked, Debenzenized, Polymers, Hydrogenated	68132-00-3	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Hydrocarbon resin	Mixture	N/A	Data not available	N/A	N/A	N/A

			or insufficient for classification			
Polyethylene Polymer	9006-26-2	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Polyolefin Wax	8002-74-2	Green algae	Analogous Compound	96 hours	EC50	>1,000 mg/l
Polyolefin Wax	8002-74-2	Rainbow trout	Analogous Compound	96 hours	LC50	>1,000 mg/l
Polyolefin Wax	8002-74-2	Water flea	Analogous Compound	48 hours	EC50	>10,000 mg/l
Antioxidant	6683-19-8	Water flea	Endpoint not reached	24 hours	EC50	>100 mg/l
Antioxidant	6683-19-8	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	>100 mg/l
Antioxidant	6683-19-8	Zebra Fish	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
Antioxidant	6683-19-8	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	>100 mg/l
Antioxidant	6683-19-8	Activated sludge	Experimental	3 hours	IC50	>100 mg/l
Antioxidant	6683-19-8	Redworm	Experimental	56 days	NOEC	>=1,000 mg/kg (Dry Weight)
Vinyl Acetate	108-05-4	Green algae	Experimental	72 hours	EC50	8.9 mg/l
Vinyl Acetate	108-05-4	Medaka	Experimental	96 hours	LC50	2.4 mg/l
Vinyl Acetate	108-05-4	Water flea	Experimental	48 hours	EC50	9.2 mg/l
Vinyl Acetate	108-05-4	Fathead minnow	Experimental	34 days	NOEC	0.551 mg/l
Vinyl Acetate	108-05-4	Green algae	Experimental	72 hours	NOEC	0.2 mg/l
Vinyl Acetate	108-05-4	Water flea	Experimental	21 days	NOEC	0.32 mg/l

**12.2. Persistence and degradability**

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Ethylene - vinyl acetate copolymer	24937-78-8	Data not available-insufficient	N/A	N/A	N/A	N/A
Naptha (Petroleum), Llight Steam-Cracked, Debenzenized, Polymers, Hydrogenated	68132-00-3	Modeled Biodegradation	28 days	BOD	0 %BOD/ThOD	Catalogic™
Hydrocarbon resin	Mixture	Data not available-insufficient	N/A	N/A	N/A	N/A
Polyethylene Polymer	9006-26-2	Data not available-insufficient	N/A	N/A	N/A	N/A
Polyolefin Wax	8002-74-2	Analogous Compound Biodegradation	28 days	BOD	40 %BOD/ThOD	OECD 301F - Manometric respirometry
Antioxidant	6683-19-8	Experimental Biodegradation	28 days	CO2 evolution	5 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
Antioxidant	6683-19-8	Experimental Biodegradation	26 days	Percent degraded	45.2 %removal of DOC	OECD 303A - Simulated Aerobic
Antioxidant	6683-19-8	Modeled Hydrolysis		Hydrolytic half-life (pH 7)	2.06 years (t 1/2)	Episuite™
Vinyl Acetate	108-05-4	Experimental Biodegradation	14 days	BOD	90 %BOD/ThOD	OECD 301C - MITI test (I)

**12.3 : Bioaccumulative potential**

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
----------	---------	-----------	----------	------------	-------------	----------

Ethylene - vinyl acetate copolymer	24937-78-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Naptha (Petroleum), Light Steam-Cracked, Debenzenized, Polymers, Hydrogenated	68132-00-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrocarbon resin	Mixture	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Polyethylene Polymer	9006-26-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Polyolefin Wax	8002-74-2	Modeled Bioconcentration		Log Kow	10.2	Episuite™
Antioxidant	6683-19-8	Experimental BCF - Fish	42 days	Bioaccumulation factor	<2.3	OECD305-Bioconcentration
Antioxidant	6683-19-8	Modeled Bioconcentration		Log Kow	22.7	
Vinyl Acetate	108-05-4	Experimental Bioconcentration		Log Kow	0.73	

**12.4. Mobility in soil**

Please contact manufacturer for more details

**12.5 Other adverse effects**

No information available.

**SECTION 13: Disposal considerations**

**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

**SECTION 14: Transport Information**

**International Regulations**

**UN No.:** Not restricted for transport.

**UN Proper shipping name:** Not restricted for transport.

**Transportation Class (IMO):** None assigned

**Transportation Class (IATA):** None assigned

**Other Dangerous Goods Descriptions (IMO):** None assigned

**Other Dangerous Goods Descriptions (IATA):** None assigned

**Packing Group:** None assigned

**Marine pollutant:** None assigned

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

### **Global inventory status**

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

### **This product may contain component(s) that are regulated by the following:**

Workplace Safety and Health Act & Workplace Safety and Health (General Provisions) Regulations: this product is subject to SDS, labelling, PEL and other requirements in the Act/Regulations.

Fire Safety (Petroleum and Flammable Materials) Regulations: This product is subject to the requirements in the Regulations

## **SECTION 16: Other information**

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

**3M Singapore SDSs are available at [www.3m.com.sg](http://www.3m.com.sg)**