



## Safety Data Sheet

Copyright,2024, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

This Safety Data Sheet has been prepared in accordance with the SS586 Specification for Hazard Communication for Hazardous Chemicals and Dangerous Goods.

<b>Document group:</b>	10-2460-3	<b>Version number:</b>	2.00
<b>Issue Date:</b>	29/08/2024	<b>Supersedes date:</b>	30/10/2023

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Scotch-Weld™ Fuel Resistant Coating EC-776

#### Product Identification Numbers

LC-B100-1065-4      62-0776-5530-6      62-0776-6530-5      62-0776-8530-3

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Fuel Resistant coating

#### 1.3. Supplier's details

**Address:** 3M Technologies (S) Pte Ltd, 10 Ang Mo Kio Street 65, Singapore 569059  
**Telephone:** +65 6450 8888  
**Website:** www.3m.com.sg

#### 1.4. Emergency telephone number

+65 6591 6601 (8.15am - 5.00pm, Monday - Friday)

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

Flammable Liquid: Category 2.  
Acute Toxicity (inhalation): Category 4.  
Skin Corrosion/Irritation: Category 1.  
Serious Eye Damage/Irritation: Category 1.  
Skin Sensitizer: Category 1.  
Carcinogenicity: Category 1A.  
Reproductive Toxicity: Category 1B.  
Specific Target Organ Toxicity (single exposure): Category 2.  
Specific Target Organ Toxicity (repeated exposure): Category 2.  
Specific Target Organ Toxicity (single exposure): Category 3.

#### 2.2. Label elements

**SIGNAL WORD**

DANGER!

**Symbols**

Flame |Corrosion | Exclamation mark |Health Hazard |

**Pictograms**



**HAZARD STATEMENTS**

- H225 Highly flammable liquid and vapour.
- H332 Harmful if inhaled.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H350 May cause cancer.
- H360 May damage fertility or the unborn child.
- H336 May cause drowsiness or dizziness.
- H371 May cause damage to organs: blood or blood-forming organs | cardiovascular system | kidney/urinary tract | nervous system | respiratory system.
- H373 May cause damage to organs through prolonged or repeated exposure: blood or blood-forming organs | cardiovascular system | kidney/urinary tract | liver | respiratory system.

**PRECAUTIONARY STATEMENTS**

**Prevention:**

- P201 Obtain special instructions before use.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P280J Wear protective gloves, protective clothing, respiratory protection, and eye/face protection.

**Response:**

- P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a POISON CENTER or doctor/physician.
- P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
- P370 + P378 In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

**2.3. Other hazards**

- May cause chemical gastrointestinal burns.

**SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	CAS Nbr	% by Wt
------------	---------	---------

4-Methylpentan-2-one	108-10-1	40 - 70
Acrylonitrile - butadiene polymer	9003-18-3	7 - 13
Phenolic resin	9039-25-2	7 - 13
Butanone	78-93-3	5 - 10
Ethanol	64-17-5	5 - 10
Phenol	108-95-2	1 - 5
Methanol	67-56-1	< 1

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

#### Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

#### If swallowed

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Skin burns (localized redness, swelling, itching, intense pain, blistering, and tissue destruction). Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness). Target organ effects. See Section 11 for additional details. Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### Hazardous Decomposition or By-Products

#### Substance

Hydrocarbons.  
Formaldehyde  
Carbon monoxide.  
Carbon dioxide.

#### Condition

During combustion.  
During combustion.  
During combustion.  
During combustion.

### 5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire extinguishing foam that is resistant to polar solvents. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (eg. gloves, respirators...) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from acids. Store away from oxidising agents.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
4-Methylpentan-2-one	108-10-1	ACGIH	TWA:20 ppm;STEL:75 ppm	A3: Confirmed animal carcin.
4-Methylpentan-2-one	108-10-1	Singapore PELs	TWA(8 hours):205 mg/m <sup>3</sup> (50 ppm);STEL(15 minutes):307 mg/m <sup>3</sup> (75 ppm)	

Phenol	108-95-2	ACGIH	TWA:5 ppm	A4: Not class. as human carcin, Danger of cutaneous absorption
Phenol	108-95-2	Singapore PELs	TWA(8 hours):19 mg/m3(5 ppm)	
Ethanol	64-17-5	ACGIH	STEL:1000 ppm	A3: Confirmed animal carcin.
Ethanol	64-17-5	Singapore PELs	TWA(8 hours):1880 mg/m3(1000 ppm)	
Methanol	67-56-1	ACGIH	TWA:200 ppm;STEL:250 ppm	Danger of cutaneous absorption
Methanol	67-56-1	Singapore PELs	TWA(8 hours):262 mg/m3(200 ppm);STEL(15 minutes):328 mg/m3(250 ppm)	
Butanone	78-93-3	ACGIH	TWA:75 ppm;STEL:150 ppm	Danger of cutaneous absorption
Butanone	78-93-3	Singapore PELs	TWA(8 hours):590 mg/m3(200 ppm);STEL(15 minutes):885 mg/m3(300 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

Singapore PELs : Singapore. Workplace Safety and Health (Permissible Exposure Levels of Toxic Substances) Order

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an Apron - polymer laminate

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for formaldehyde

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

Half facepiece or full facepiece supplied-air respirator

Organic vapor cartridges may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Color	Yellow
Odor	Mild Solvent
Odour threshold	No data available.
pH	No data available.
Melting point/Freezing point	No data available.
Boiling point/Initial boiling point/Boiling range	79.4 °C [ @ 101,325 Pa ] [ <i>Test Method: Estimated</i> ]
Flash point	10 °C [ @ 101,325 Pa ] [ <i>Test Method: Closed Cup</i> ]
Evaporation rate	2.7 [ <i>Ref Std: ETHER=1</i> ]
Flammability	Flammable Liquid: Category 2.
Flammable Limits(LEL)	1.8 % volume [ @ 20 °C ] [ <i>Test Method: Estimated</i> ]
Flammable Limits(UEL)	11.5 % volume [ @ 20 °C ] [ <i>Test Method: Estimated</i> ]
Vapour pressure	10,665.8 Pa [ @ 20 °C ] [ <i>Test Method: Estimated</i> ]
Vapor Density and/or Relative Vapor Density	2.5 [ <i>Ref Std: AIR=1</i> ]
Density	0.899 g/ml [ @ 20 °C ]
Relative density	0.899 [ <i>Ref Std: WATER=1</i> ]
Water solubility	Moderate
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Autoignition temperature	448.9 °C [ <i>Test Method: Estimated</i> ]
Decomposition temperature	No data available.
Kinematic Viscosity	1,557 mm <sup>2</sup> /sec
Volatile organic compounds (VOC)	<=690 g/l [ <i>Test Method: calculated SCAQMD rule 443.1</i> ]
Percent volatile	<=77 %
VOC less H <sub>2</sub> O & exempt solvents	<=695 g/l [ <i>Test Method: calculated SCAQMD rule 443.1</i> ]
Molecular weight	No data available.

Particle Characteristics	<i>Not applicable.</i>
--------------------------	------------------------

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material is considered to be non reactive under normal use conditions

### 10.2 Chemical stability

Stable.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

#### 10.4 Conditions to avoid

Sparks and/or flames.

#### 10.5 Incompatible materials

Strong acids.

Strong oxidising agents.

#### 10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1 Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

Harmful if inhaled. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic Respiratory Reaction in sensitive people: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest.

May cause additional health effects (see below).

#### Skin contact

Corrosive (skin burns): Signs/symptoms may include localised redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching. May cause additional health effects (see below).

#### Eye contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

#### Ingestion

May be harmful if swallowed.

Gastrointestinal corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain, nausea, vomiting, and diarrhea; blood in the faeces and/or vomitus may also be seen. May cause additional health effects (see below).

#### Additional Health Effects:

#### Single exposure may cause target organ effects:

Cardiac effects: Signs/symptoms may include irregular heartbeat (arrhythmia), changes in heart rate, damage to heart muscle, heart attack, and may be fatal. Hematopoietic effects: Signs/symptoms may include generalised weakness, fatigue and alterations in numbers of circulating blood cells. Central nervous system (CNS) depression: Signs/symptoms may include

headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness. Neurological effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and changes in blood pressure and heart rate. Respiratory effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and respiratory failure. Kidney/Bladder effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine, increased blood urea nitrogen (BUN), blood in urine, and painful urination.

**Prolonged or repeated exposure may cause target organ effects:**

Cardiac effects: Signs/symptoms may include irregular heartbeat (arrhythmia), changes in heart rate, damage to heart muscle, heart attack, and may be fatal. Hematopoietic effects: Signs/symptoms may include generalised weakness, fatigue and alterations in numbers of circulating blood cells. Liver effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice. Neurological effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and changes in blood pressure and heart rate. Respiratory effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and respiratory failure. Kidney/Bladder effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine, increased blood urea nitrogen (BUN), blood in urine, and painful urination.

**Reproductive/Developmental Toxicity:**

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

**Carcinogenicity:**

Contains a chemical or chemicals which can cause cancer.

**Additional information:**

This product contains ethanol. Alcoholic beverages and ethanol in alcoholic beverages have been classified by the International Agency for Research on Cancer as carcinogenic to humans. There are also data associating human consumption of alcoholic beverages with developmental toxicity and liver toxicity. Exposure to ethanol during the foreseeable use of this product is not expected to cause cancer, developmental toxicity, or liver toxicity.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >10 - =20 mg/l
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
4-Methylpentan-2-one	Dermal	Rabbit	LD50 > 16,000 mg/kg
4-Methylpentan-2-one	Inhalation-Vapor (4 hours)	Rat	LC50 11 mg/l
4-Methylpentan-2-one	Ingestion	Rat	LD50 3,038 mg/kg
Phenolic resin	Dermal		LD50 estimated to be > 5,000 mg/kg
Phenolic resin	Inhalation-Dust/Mist		LC50 estimated to be > 12.5 mg/l
Phenolic resin	Ingestion		LD50 estimated to be > 5,000 mg/kg
Acrylonitrile - butadiene polymer	Dermal	Rabbit	LD50 > 15,000 mg/kg
Acrylonitrile - butadiene polymer	Ingestion	Rat	LD50 > 30,000 mg/kg
Butanone	Dermal	Rabbit	LD50 > 8,050 mg/kg
Butanone	Inhalation-Vapor (4 hours)	Rat	LC50 34.5 mg/l
Butanone	Ingestion	Rat	LD50 2,737 mg/kg



Ethanol	Dermal	Rabbit	LD50 > 15,800 mg/kg
Ethanol	Inhalation-Vapor (4 hours)	Rat	LC50 124.7 mg/l
Ethanol	Ingestion	Rat	LD50 17,800 mg/kg
Phenol	Inhalation-Vapor		LC50 estimated to be 2 - 10 mg/l
Phenol	Dermal	Rat	LD50 670 mg/kg
Phenol	Ingestion	Rat	LD50 340 mg/kg
Methanol	Dermal		LD50 estimated to be 1,000 - 2,000 mg/kg
Methanol	Inhalation-Vapor		LC50 estimated to be 10 - 20 mg/l
Methanol	Ingestion		LD50 estimated to be 50 - 300 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
4-Methylpentan-2-one	Rabbit	Mild irritant
Phenolic resin	Professional judgement	No significant irritation
Acrylonitrile - butadiene polymer	Professional judgement	No significant irritation
Butanone	Rabbit	Minimal irritation
Ethanol	Rabbit	No significant irritation
Phenol	Rat	Corrosive
Methanol	Rabbit	Mild irritant

**Serious Eye Damage/Irritation**

Name	Species	Value
4-Methylpentan-2-one	Rabbit	Mild irritant
Phenolic resin	Professional judgement	Mild irritant
Acrylonitrile - butadiene polymer	Professional judgement	No significant irritation
Butanone	Rabbit	Severe irritant
Ethanol	Rabbit	Severe irritant
Phenol	Rabbit	Corrosive
Methanol	Rabbit	Moderate irritant

**Sensitization:**

**Skin Sensitisation**

Name	Species	Value
4-Methylpentan-2-one	Guinea pig	Not classified
Ethanol	Human	Not classified
Phenol	Guinea pig	Not classified
Methanol	Guinea pig	Not classified

**Respiratory Sensitisation**

For the component/components, either no data are currently available or the data are not sufficient for classification.

### Germ Cell Mutagenicity

Name	Route	Value
4-Methylpentan-2-one	In Vitro	Not mutagenic
Butanone	In Vitro	Not mutagenic
Ethanol	In Vitro	Some positive data exist, but the data are not sufficient for classification
Ethanol	In vivo	Some positive data exist, but the data are not sufficient for classification
Phenol	In Vitro	Some positive data exist, but the data are not sufficient for classification
Phenol	In vivo	Some positive data exist, but the data are not sufficient for classification
Methanol	In Vitro	Some positive data exist, but the data are not sufficient for classification
Methanol	In vivo	Some positive data exist, but the data are not sufficient for classification

### Carcinogenicity

Name	Route	Species	Value
4-Methylpentan-2-one	Inhalation	Multiple animal species	Carcinogenic.
Butanone	Inhalation	Human	Not carcinogenic
Ethanol	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Phenol	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Phenol	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Methanol	Inhalation	Multiple animal species	Not carcinogenic

### Reproductive Toxicity

#### Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
4-Methylpentan-2-one	Inhalation	Not classified for female reproduction	Multiple animal species	NOAEL 8.2 mg/l	2 generation
4-Methylpentan-2-one	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	13 weeks
4-Methylpentan-2-one	Inhalation	Not classified for male reproduction	Multiple animal species	NOAEL 8.2 mg/l	2 generation
4-Methylpentan-2-one	Inhalation	Not classified for development	Mouse	NOAEL 12.3 mg/l	during organogenesis
Butanone	Inhalation	Not classified for development	Rat	LOAEL 8.8 mg/l	during gestation
Ethanol	Inhalation	Not classified for development	Rat	NOAEL 38 mg/l	during gestation
Ethanol	Ingestion	Not classified for development	Rat	NOAEL 5,200 mg/kg/day	prematuring & during gestation
Phenol	Ingestion	Not classified for female reproduction	Rat	NOAEL 321 mg/kg/day	2 generation
Phenol	Ingestion	Not classified for male reproduction	Rat	NOAEL 321 mg/kg/day	2 generation
Phenol	Ingestion	Not classified for development	Rat	NOAEL 120	during

				mg/kg/day	organogenesis
Methanol	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,600 mg/kg/day	21 days
Methanol	Ingestion	Toxic to development	Mouse	LOAEL 4,000 mg/kg/day	during organogenesis
Methanol	Inhalation	Toxic to development	Mouse	NOAEL 1.3 mg/l	during organogenesis

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
4-Methylpentan-2-one	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	LOAEL 0.1 mg/l	2 hours
4-Methylpentan-2-one	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
4-Methylpentan-2-one	Inhalation	vascular system	Not classified	Dog	NOAEL Not available	not available
4-Methylpentan-2-one	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	LOAEL 900 mg/kg	not applicable
Butanone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	official classification	NOAEL Not available	
Butanone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Butanone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Butanone	Ingestion	liver	Not classified	Rat	NOAEL Not available	not applicable
Butanone	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 1,080 mg/kg	not applicable
Ethanol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	LOAEL 9.4 mg/l	not available
Ethanol	Inhalation	central nervous system depression	Not classified	Human and animal	NOAEL not available	
Ethanol	Ingestion	central nervous system depression	Not classified	Multiple animal species	NOAEL not available	
Ethanol	Ingestion	kidney and/or bladder	Not classified	Dog	NOAEL 3,000 mg/kg	
Phenol	Dermal	hematopoietic system	Causes damage to organs	Rat	LOAEL 108 mg/kg	not available
Phenol	Dermal	heart   nervous system   kidney and/or bladder	Causes damage to organs	Rat	LOAEL 107 mg/kg	24 hours
Phenol	Dermal	liver	Not classified	Human	NOAEL Not available	not available
Phenol	Inhalation	respiratory irritation	May cause respiratory irritation	Multiple animal species	NOAEL Not available	not available
Phenol	Ingestion	kidney and/or bladder	Causes damage to organs	Rat	NOAEL 120 mg/kg/day	not applicable
Phenol	Ingestion	respiratory system	Causes damage to organs	Human	NOAEL not available	poisoning and/or abuse
Phenol	Ingestion	endocrine system   liver	Not classified	Rat	NOAEL 224 mg/kg	not applicable
Phenol	Ingestion	heart	Not classified	Human	NOAEL Not available	poisoning and/or abuse

Methanol	Inhalation	blindness	Causes damage to organs	Human	NOAEL Not available	occupational exposure
Methanol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	not available
Methanol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	6 hours
Methanol	Ingestion	blindness	Causes damage to organs	Human	NOAEL Not available	poisoning and/or abuse
Methanol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
4-Methylpentan-2-one	Inhalation	liver	Not classified	Rat	NOAEL 0.41 mg/l	13 weeks
4-Methylpentan-2-one	Inhalation	heart	Not classified	Multiple animal species	NOAEL 0.8 mg/l	2 weeks
4-Methylpentan-2-one	Inhalation	kidney and/or bladder	Not classified	Multiple animal species	NOAEL 0.4 mg/l	90 days
4-Methylpentan-2-one	Inhalation	respiratory system	Not classified	Multiple animal species	NOAEL 4.1 mg/l	14 weeks
4-Methylpentan-2-one	Inhalation	endocrine system   hematopoietic system	Not classified	Multiple animal species	NOAEL 0.41 mg/l	90 days
4-Methylpentan-2-one	Inhalation	nervous system	Not classified	Multiple animal species	NOAEL 0.41 mg/l	13 weeks
4-Methylpentan-2-one	Ingestion	endocrine system   hematopoietic system   liver   kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
4-Methylpentan-2-one	Ingestion	heart   immune system   muscles   nervous system   respiratory system	Not classified	Rat	NOAEL 1,040 mg/kg/day	120 days
Butanone	Dermal	nervous system	Not classified	Guinea pig	NOAEL Not available	31 weeks
Butanone	Inhalation	liver   kidney and/or bladder   heart   endocrine system   gastrointestinal tract   bone, teeth, nails, and/or hair   hematopoietic system   immune system   muscles	Not classified	Rat	NOAEL 14.7 mg/l	90 days
Butanone	Ingestion	liver	Not classified	Rat	NOAEL Not available	7 days
Butanone	Ingestion	nervous system	Not classified	Rat	NOAEL 173 mg/kg/day	90 days
Ethanol	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Rabbit	LOAEL 124 mg/l	365 days
Ethanol	Inhalation	hematopoietic system   immune system	Not classified	Rat	NOAEL 25 mg/l	14 days
Ethanol	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 8,000 mg/kg/day	4 months
Ethanol	Ingestion	kidney and/or bladder	Not classified	Dog	NOAEL 3,000	7 days

					mg/kg/day	
Phenol	Dermal	nervous system	May cause damage to organs though prolonged or repeated exposure	Rabbit	LOAEL 260 mg/kg/day	18 days
Phenol	Inhalation	heart   liver   kidney and/or bladder   respiratory system	Causes damage to organs through prolonged or repeated exposure	Guinea pig	LOAEL 0.1 mg/l	41 days
Phenol	Inhalation	nervous system	May cause damage to organs though prolonged or repeated exposure	Multiple animal species	LOAEL 0.1 mg/l	14 days
Phenol	Inhalation	hematopoietic system	Not classified	Human	NOAEL Not available	occupational exposure
Phenol	Inhalation	immune system	Not classified	Rat	NOAEL 0.1 mg/l	2 weeks
Phenol	Ingestion	kidney and/or bladder	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 12 mg/kg/day	14 days
Phenol	Ingestion	hematopoietic system	Causes damage to organs through prolonged or repeated exposure	Mouse	LOAEL 1.8 mg/kg/day	28 days
Phenol	Ingestion	nervous system	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 308 mg/kg/day	13 weeks
Phenol	Ingestion	liver	Not classified	Rat	NOAEL 40 mg/kg/day	14 days
Phenol	Ingestion	respiratory system	Not classified	Rat	LOAEL 40 mg/kg/day	14 days
Phenol	Ingestion	immune system	Not classified	Mouse	NOAEL 1.8 mg/kg/day	28 days
Phenol	Ingestion	endocrine system	Not classified	Rat	NOAEL 120 mg/kg/day	14 days
Phenol	Ingestion	skin   bone, teeth, nails, and/or hair	Not classified	Multiple animal species	NOAEL 1,204 mg/kg/day	103 weeks
Methanol	Inhalation	liver	Not classified	Rat	NOAEL 6.55 mg/l	4 weeks
Methanol	Inhalation	respiratory system	Not classified	Rat	NOAEL 13.1 mg/l	6 weeks
Methanol	Ingestion	liver   nervous system	Not classified	Rat	NOAEL 2,500 mg/kg/day	90 days

**Aspiration Hazard**

Name	Value
4-Methylpentan-2-one	Some positive data exist, but the data are not sufficient for classification

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

**12.1. Toxicity**

**Acute aquatic hazard:**

GHS Acute 2: Toxic to aquatic life.

**Chronic aquatic hazard:**

GHS Chronic 3: Harmful to aquatic life with long lasting effects.

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
4-Methylpentan-2-one	108-10-1	Green algae	Experimental	96 hours	EC50	400 mg/l
4-Methylpentan-2-one	108-10-1	Water flea	Experimental	48 hours	EC50	>200 mg/l
4-Methylpentan-2-one	108-10-1	Zebra Fish	Experimental	96 hours	LC50	>179 mg/l
4-Methylpentan-2-one	108-10-1	Fathead minnow	Experimental	32 days	NOEC	56.2 mg/l
4-Methylpentan-2-one	108-10-1	Water flea	Experimental	21 days	NOEC	78 mg/l
4-Methylpentan-2-one	108-10-1	Activated sludge	Experimental	30 minutes	EC50	>1,000
Acrylonitrile - butadiene polymer	9003-18-3	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Phenolic resin	9039-25-2	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Ethanol	64-17-5	Fathead minnow	Experimental	96 hours	LC50	14,200 mg/l
Ethanol	64-17-5	Fish	Experimental	96 hours	LC50	11,000 mg/l
Ethanol	64-17-5	Green algae	Experimental	72 hours	EC50	275 mg/l
Ethanol	64-17-5	Water flea	Experimental	48 hours	LC50	5,012 mg/l
Ethanol	64-17-5	Green algae	Experimental	72 hours	ErC10	11.5 mg/l
Ethanol	64-17-5	Water flea	Experimental	10 days	NOEC	9.6 mg/l
Butanone	78-93-3	Fathead minnow	Experimental	96 hours	LC50	2,993 mg/l
Butanone	78-93-3	Green algae	Experimental	96 hours	ErC50	2,029 mg/l
Butanone	78-93-3	Water flea	Experimental	48 hours	EC50	308 mg/l
Butanone	78-93-3	Green algae	Experimental	96 hours	ErC10	1,289 mg/l
Butanone	78-93-3	Water flea	Experimental	21 days	NOEC	100 mg/l
Butanone	78-93-3	Bacteria	Experimental	16 hours	LOEC	1,150 mg/l
Phenol	108-95-2	Bacteria	Experimental	24 hours	IC50	21 mg/l
Phenol	108-95-2	Green algae	Experimental	96 hours	EC50	61.1 mg/l
Phenol	108-95-2	Rainbow trout	Experimental	96 hours	LC50	8.9 mg/l
Phenol	108-95-2	Water flea	Experimental	48 hours	EC50	3.1 mg/l
Phenol	108-95-2	Fish	Experimental	60 days	NOEC	0.077 mg/l
Phenol	108-95-2	Water flea	Experimental	16 days	NOEC	0.16 mg/l
Methanol	67-56-1	Algae or other aquatic plants	Experimental	96 hours	EC50	16.9 mg/l
Methanol	67-56-1	Bay mussel	Experimental	96 hours	LC50	15,900 mg/l
Methanol	67-56-1	Bluegill	Experimental	96 hours	LC50	15,400 mg/l
Methanol	67-56-1	Green algae	Experimental	96 hours	ErC50	22,000 mg/l
Methanol	67-56-1	Sediment organism	Experimental	96 hours	LC50	54,890 mg/l
Methanol	67-56-1	Water flea	Experimental	48 hours	LC50	3,289 mg/l
Methanol	67-56-1	Green algae	Experimental	96 hours	NOEC	9.96 mg/l
Methanol	67-56-1	Medaka	Experimental	8.33 days	NOEC	158,000 mg/l
Methanol	67-56-1	Water flea	Experimental	21 days	NOEC	122 mg/l
Methanol	67-56-1	Activated sludge	Experimental	3 hours	IC50	>1,000 mg/l
Methanol	67-56-1	Barley	Experimental	14 days	EC50	15,492 mg/kg (Dry Weight)
Methanol	67-56-1	Redworm	Experimental	63 days	EC50	26,646 mg/kg (Dry Weight)
Methanol	67-56-1	Springtail	Experimental	28 days	EC50	5,683 mg/kg (Dry Weight)

## 12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
4-Methylpentan-2-one	108-10-1	Experimental Biodegradation	28 days	BOD	83 %BOD/ThOD	OECD 301F - Manometric respirometry

4-Methylpentan-2-one	108-10-1	Experimental Photolysis		Photolytic half-life (in air)	2.3 days (t 1/2)	
Acrylonitrile - butadiene polymer	9003-18-3	Data not available-insufficient	N/A	N/A	N/A	N/A
Phenolic resin	9039-25-2	Data not available-insufficient	N/A	N/A	N/A	N/A
Ethanol	64-17-5	Experimental Biodegradation	14 days	BOD	89 %BOD/ThOD	OECD 301C - MITI test (I)
Butanone	78-93-3	Experimental Biodegradation	28 days	BOD	98 %BOD/ThOD	OECD 301D - Closed bottle test
Phenol	108-95-2	Experimental Biodegradation	100 hours	BOD	62 %BOD/ThOD	OECD 301C - MITI test (I)
Methanol	67-56-1	Experimental Biodegradation	3 days	Percent degraded	91 %degraded	
Methanol	67-56-1	Experimental Biodegradation	14 days	BOD	92 %BOD/ThOD	OECD 301C - MITI test (I)
Methanol	67-56-1	Experimental Photolysis		Photolytic half-life (in air)	35 days (t 1/2)	
Methanol	67-56-1	Experimental Soil Metabolism Aerobic	5 days	CO2 evolution	53.4 %CO2 evolution/THCO2 evolution	

**12.3 : Bioaccumulative potential**

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
4-Methylpentan-2-one	108-10-1	Experimental Bioconcentration		Log Kow	1.9	OECD 117 log Kow HPLC method
Acrylonitrile - butadiene polymer	9003-18-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Phenolic resin	9039-25-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Ethanol	64-17-5	Experimental Bioconcentration		Log Kow	-0.35	
Butanone	78-93-3	Experimental Bioconcentration		Log Kow	0.3	OECD 117 log Kow HPLC method
Phenol	108-95-2	Experimental Bioconcentration		Log Kow	1.47	
Methanol	67-56-1	Experimental BCF - Fish	3 days	Bioaccumulation factor	<4.5	
Methanol	67-56-1	Experimental Bioconcentration		Log Kow	-0.77	

**12.4. Mobility in soil**

Please contact manufacturer for more details

**12.5 Other adverse effects**

No information available.

**SECTION 13: Disposal considerations**

**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

## SECTION 14: Transport Information

### International Regulations

UN No.: UN1263

UN Proper shipping name: PAINTS

Transportation Class (IMO): 3-3 Flammable liquid

Transportation Class (IATA): 3-3 Flammable liquid

Other Dangerous Goods Descriptions (IMO): None assigned

Other Dangerous Goods Descriptions (IATA): None assigned

Packing Group: II

Marine pollutant: None assigned

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

#### This product may contain component(s) that are regulated by the following:

Workplace Safety and Health Act & Workplace Safety and Health (General Provisions) Regulations: this product is subject to SDS, labelling, PEL and other requirements in the Act/Regulations.

Fire Safety (Petroleum and Flammable Materials) Regulations: This product is subject to the requirements in the Regulations  
Sewerage & Drainage Act and Sewerage and Drainage (Trade Effluent) Regulations: This product is subject to the requirements in the act/regulation.

Environmental Protection and Management (Hazardous Substances) Regulations: This product is subject to the requirements in the Regulations

## SECTION 16: Other information

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M Singapore SDSs are available at [www.3m.com.sg](http://www.3m.com.sg)