

Safety Data Sheet

Copyright, 2024, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

This Safety Data Sheet has been prepared in accordance with the SS586 Specification for Hazard Communication for Hazardous Chemicals and Dangerous Goods.

Document group: 29-7430-1 Version number: 2.00

Issue Date: 19/03/2024 Supersedes date: 01/03/2023

IDENTIFICATION

1.1. Product identifier

3MTM RelyXTM U200 Automix Refill (56895, 56896, 56897, 56912)

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Dental cement

Restrictions on use

For use by dental professionals only.

1.3. Supplier's details

Address: 3M Technologies (S) Pte Ltd, 10 Ang Mo Kio Street 65, Singapore 569059

Telephone: +65 6450 8888 Website: www.3m.com.sg

1.4. Emergency telephone number

Company Emergency Hotline: +65 6591 6601 (8.15am - 5.00pm, Monday - Friday)

This product is a kit or a multipart product which consists of multiple, independently packaged components. An SDS for each of these components is included. Please do not separate the component SDSs from this cover page. The document numbers of the SDSs for components of this product are:

29-4789-3, 29-4856-0

TRANSPORT INFORMATION

International Regulations

UN No.: None assigned

UN Proper shipping name: None assigned Transportation Class (IMO): None assigned Transportation Class (IATA): None assigned

Other Dangerous Goods Descriptions (IMO): None assigned Other Dangerous Goods Descriptions (IATA): None assigned

3MTM RelyXTM U200 Automix Refill (56895, 56896, 56897, 56912)

Packing Group: None assigned Marine pollutant: None assigned

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M Singapore SDSs are available at www.3m.com.sg



Safety Data Sheet

Copyright, 2024, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

This Safety Data Sheet has been prepared in accordance with the SS586 Specification for Hazard Communication for Hazardous Chemicals and Dangerous Goods.

Document group: 29-4789-3 **Version number:** 3.00

Issue Date: 28/08/2024 **Supersedes date:** 19/03/2024

SECTION 1: Identification

1.1. Product identifier

3MTM RelyXTM U200 Automix Catalyst

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Cement

Restrictions on use

For use by dental professionals only.

1.3. Supplier's details

Address: 3M Technologies (S) Pte Ltd, 10 Ang Mo Kio Street 65, Singapore 569059

Telephone: +65 6450 8888 **Website:** www.3m.com.sg

1.4. Emergency telephone number

+65 6591 6601 (8.15am - 5.00pm, Monday - Friday)

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 2.

Skin Sensitizer: Category 1.

Acute Aquatic Toxicity: Category 1. Chronic Aquatic Toxicity: Category 2.

2.2. Label elements

SIGNAL WORD

WARNING!

Symbols

Exclamation mark |Environment |

Pictograms



HAZARD STATEMENTS

H319 Causes serious eye irritation. H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P273 Avoid release to the environment.

P280E Wear protective gloves.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P391 Collect spillage.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Wt
Glass powder (65997-17-3), surface	None	50 - 70
modified with 2-propenoic acid, 2		
methyl3-(trimethoxysilyl)propyl ester		
(2530-85-0), bulk material		
SUBSTITUTED DIMETHACRYLATE	27689-12-9	10 - 30
SILANE TREATED SILICA	68909-20-6	< 5
1,12-DODECANE DIMETHYCRYLATE	72829-09-5	< 5
2,4,6(1H,3H,5H)-Pyrimidinetrione, 5-	945012-02-2	< 5
phenyl-1-(phenylmethyl)-, calcium salt (2:1)		
[(3-methoxypropyl)imino]di-2,1-ethanediyl	93962-71-1	< 2
bismethacrylate		
Calcium dihydroxide	1305-62-0	< 2
Sodium toluene-4-sulphinate	824-79-3	< 2
NUC - Titanium Dioxide	13463-67-7	< 0.5

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

3MTM RelyXTM U200 Automix Catalyst

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide.

Carbon dioxide.

Irritant vapours or gases.

Condition

During combustion.

During combustion.

During combustion.

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Do not get in eyes. A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Calcium dihydroxide	1305-62-0	ACGIH	TWA:5 mg/m3	
Calcium dihydroxide	1305-62-0	Singapore PELs	TWA(8 hours):5 mg/m3	
NUC - Titanium Dioxide	13463-67-7		TWA(Respirable nanoscale particles):0.2 mg/m3;TWA(Respirable finescale particles):2.5 mg/m3	A3: Confirmed animal carcin.
NUC - Titanium Dioxide	13463-67-7	Singapore PELs	TWA(8 hours):10 mg/m3	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

Singapore PELs: Singapore. Workplace Safety and Health (Permissible Exposure Levels of Toxic Substances) Order

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid.	
Specific Physical Form:	Paste	
Color	Tooth	
Odor	Slight Acrylic	
Odour threshold	No data available.	
рН	Not applicable.	
Melting point/Freezing point	No data available.	

Boiling point/Initial boiling point/Boiling range	No data available.	
Flash point	No flash point	
Evaporation rate	No data available.	
Flammability	Not applicable.	
Flammable Limits(LEL)	No data available.	
Flammable Limits(UEL)	No data available.	
Vapour pressure	No data available.	
Vapor Density and/or Relative Vapor Density	No data available.	
Density	2 g/cm3 - 2.2 g/cm3	
Relative density	2 - 2.2 [<i>Ref Std</i> :WATER=1]	
Water solubility	Nil	
Solubility- non-water	No data available.	
Partition coefficient: n-octanol/water	No data available.	
Autoignition temperature	No data available.	
Decomposition temperature	No data available.	
Kinematic Viscosity	No data available.	
Percent volatile	No data available.	
Molecular weight	No data available.	

Particle Characteristics	Not applicable.
--------------------------	-----------------

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

Substance None known. **Condition**

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

This product may have a characteristic odour; however, no adverse health effects are anticipated.

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eve contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Additional Health Effects:

Carcinogenicity:

Exposures needed to cause the following health effect(s) are not expected during normal, intended use:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
Glass powder (65997-17-3), surface modified with 2-propenoic acid, 2 methyl3-(trimethoxysilyl)propyl ester (2530-85-0), bulk material	Dermal		LD50 estimated to be > 5,000 mg/kg
Glass powder (65997-17-3), surface modified with 2-propenoic acid, 2 methyl3-(trimethoxysilyl)propyl ester (2530-85-0), bulk material	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
SUBSTITUTED DIMETHACRYLATE	Dermal	Professio nal judgeme nt	LD50 estimated to be > 5,000 mg/kg
SUBSTITUTED DIMETHACRYLATE	Ingestion	Rat	LD50 > 17,600 mg/kg
1,12-DODECANE DIMETHYCRYLATE	Dermal	similar compoun ds	LD50 > 2,000 mg/kg
1,12-DODECANE DIMETHYCRYLATE	Ingestion	similar compoun ds	LD50 > 2,000 mg/kg
2,4,6(1H,3H,5H)-Pyrimidinetrione, 5-phenyl-1-(phenylmethyl)-, calcium salt (2:1)	Dermal	Professio nal judgeme nt	LD50 estimated to be 2,000 - 5,000 mg/kg
2,4,6(1H,3H,5H)-Pyrimidinetrione, 5-phenyl-1-(phenylmethyl)-, calcium salt (2:1)	Ingestion	Rat	LD50 > 2,000 mg/kg
SILANE TREATED SILICA	Ingestion	Rat	LD50 > 2,000 mg/kg

3MTM RelyXTM U200 Automix Catalyst

SILANE TREATED SILICA	Dermal	similar health	LD50 estimated to be > 5,000 mg/kg
		hazards	
Calcium dihydroxide	Dermal	Rabbit	LD50 > 2,500 mg/kg
Calcium dihydroxide	Ingestion	Rat	LD50 7,340 mg/kg
Sodium toluene-4-sulphinate	Ingestion	Rat	LD50 > 2,000 mg/kg
Sodium toluene-4-sulphinate	Dermal	similar	LD50 estimated to be > 5,000 mg/kg
		health hazards	
[(3-methoxypropyl)imino]di-2,1-ethanediyl bismethacrylate	Dermal	Professio nal	LD50 estimated to be > 5,000 mg/kg
		judgeme nt	
[(3-methoxypropyl)imino]di-2,1-ethanediyl bismethacrylate	Ingestion	Rat	LD50 > 1,600 mg/kg
NUC - Titanium Dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
NUC - Titanium Dioxide	Inhalation-	Rat	LC50 > 6.82 mg/l
	Dust/Mist		
	(4 hours)		
NUC - Titanium Dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Glass powder (65997-17-3), surface modified with 2-propenoic acid, 2 methyl3-(trimethoxysilyl)propyl ester (2530-85-0), bulk material	Professio nal judgemen t	No significant irritation
SUBSTITUTED DIMETHACRYLATE	Rabbit	No significant irritation
1,12-DODECANE DIMETHYCRYLATE	similar compoun ds	No significant irritation
SILANE TREATED SILICA	Rabbit	No significant irritation
Calcium dihydroxide	Human	Corrosive
Sodium toluene-4-sulphinate	In vitro data	No significant irritation
NUC - Titanium Dioxide	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Glass powder (65997-17-3), surface modified with 2-propenoic acid, 2 methyl3-(trimethoxysilyl)propyl ester (2530-85-0), bulk material	Professio nal judgemen t	No significant irritation
SUBSTITUTED DIMETHACRYLATE	Rabbit	Mild irritant
1,12-DODECANE DIMETHYCRYLATE	similar	Mild irritant
	compoun	
	ds	
SILANE TREATED SILICA	Rabbit	No significant irritation
Calcium dihydroxide	Rabbit	Corrosive
Sodium toluene-4-sulphinate	In vitro	Severe irritant
	data	
NUC - Titanium Dioxide	Rabbit	No significant irritation

Sensitization:

Skin Sensitisation

Name	Species	Value
SUBSTITUTED DIMETHACRYLATE	Guinea pig	Not classified
1,12-DODECANE DIMETHYCRYLATE	similar compoun	Sensitising

Page: 7 of 12

3MTM RelyXTM U200 Automix Catalyst

	ds	
2,4,6(1H,3H,5H)-Pyrimidinetrione, 5-phenyl-1-(phenylmethyl)-, calcium salt	Mouse	Not classified
(2:1)		
SILANE TREATED SILICA	Guinea	Not classified
	pig	
Sodium toluene-4-sulphinate	In vitro	Not classified
	data	
[(3-methoxypropyl)imino]di-2,1-ethanediyl bismethacrylate	Professio	Sensitising
	nal	
	judgemen	
	t	
NUC - Titanium Dioxide	Human	Not classified
	and	
	animal	

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
SUBSTITUTED DIMETHACRYLATE	In Vitro	Not mutagenic
1,12-DODECANE DIMETHYCRYLATE	In Vitro	Not mutagenic
2,4,6(1H,3H,5H)-Pyrimidinetrione, 5-phenyl-1-(phenylmethyl)-, calcium salt	In Vitro	Not mutagenic
(2:1)		
SILANE TREATED SILICA	In Vitro	Not mutagenic
Sodium toluene-4-sulphinate	In Vitro	Not mutagenic
NUC - Titanium Dioxide	In Vitro	Not mutagenic
NUC - Titanium Dioxide	In vivo	Not mutagenic

Carcinogenicity

cui emogeniery						
Name	Route	Species	Value			
NUC - Titanium Dioxide	Ingestion	Multiple	Not carcinogenic			
		animal				
		species				
NUC - Titanium Dioxide	Inhalation	Rat	Carcinogenic.			

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
SILANE TREATED SILICA	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
SILANE TREATED SILICA	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
2,4,6(1H,3H,5H)- Pyrimidinetrione, 5- phenyl-1-(phenylmethyl)-, calcium salt (2:1)	Ingestion	nervous system	Not classified	Rat	NOAEL 2,000 mg/kg	
Calcium dihydroxide	Inhalation	respiratory irritation	May cause respiratory irritation	Human	LOAEL 2.5 mg/m³	20 minutes
Sodium toluene-4- sulphinate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Page: 8 of 12

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
SILANE TREATED SILICA	Inhalation	respiratory system	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 0.035 mg/l	13 weeks
SILANE TREATED SILICA	Inhalation	hematopoietic system kidney and/or bladder	Not classified	Rat	NOAEL 0.035 mg/l	13 weeks
SILANE TREATED SILICA	Ingestion	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	5 weeks
NUC - Titanium Dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
NUC - Titanium Dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

GHS Acute 1: Very toxic to aquatic life.

Chronic aquatic hazard:

GHS Chronic 2: Toxic to aquatic life with long lasting effects.

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
Glass powder (65997-17-3), surface modified with 2-propenoic acid, 2 methyl3- (trimethoxysilyl)pr opyl ester (2530-	None	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
85-0), bulk material SUBSTITUTED	27689-12-9	Green algae	Experimental	72 hours	EC50	>100 mg/l
DIMETHACRYL ATE	27009 12 9	Green argue	Ехрегиненци	72 Hours	ECSO	roo mg/r
SUBSTITUTED DIMETHACRYL ATE	27689-12-9	Water flea	Experimental	48 hours	EC50	>100 mg/l
SUBSTITUTED DIMETHACRYL ATE	27689-12-9	Green algae	Experimental	72 hours	NOEC	>100 mg/l
1,12-DODECANE DIMETHYCRYL ATE	72829-09-5	Green algae	Experimental	72 hours	ErC50	0.017 mg/l

1,12-DODECANE DIMETHYCRYL ATE	72829-09-5	Water flea	Experimental	48 hours	EC50	>100 mg/l
1,12-DODECANE DIMETHYCRYL ATE	72829-09-5	Green algae	Experimental	72 hours	ErC10	0.0064 mg/l
2,4,6(1H,3H,5H)- Pyrimidinetrione, 5-phenyl-1- (phenylmethyl)-, calcium salt (2:1)	945012-02-2	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
SILANE TREATED SILICA	68909-20-6	Algae or other aquatic plants	Estimated	72 hours	EC50	>100 mg/l
[(3- methoxypropyl)imi no]di-2,1- ethanediyl bismethacrylate	93962-71-1	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Calcium dihydroxide	1305-62-0	Fathead minnow	Estimated	96 hours	LC50	4,630 mg/l
Calcium dihydroxide	1305-62-0	Green algae	Estimated	72 hours	EC50	>4,000 mg/l
Calcium dihydroxide	1305-62-0	Water flea	Estimated	48 hours	EC50	2,400 mg/l
Sodium toluene-4- sulphinate	824-79-3	Fathead minnow	Estimated	96 hours	LC50	>400 mg/l
Sodium toluene-4- sulphinate	824-79-3	Green algae	Estimated	96 hours	EC50	230 mg/l
Sodium toluene-4- sulphinate	824-79-3	Water flea	Estimated	48 hours	EC50	>400 mg/l
Sodium toluene-4- sulphinate	824-79-3	Green algae	Estimated	96 hours	NOEC	31 mg/l
NUC - Titanium Dioxide	13463-67-7	Activated sludge	Experimental	3 hours	NOEC	>=1,000 mg/l
NUC - Titanium Dioxide	13463-67-7	Diatom	Experimental	72 hours	EC50	>10,000 mg/l
NUC - Titanium Dioxide	13463-67-7	Fathead minnow	Experimental	96 hours	LC50	>100 mg/l
NUC - Titanium Dioxide	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
NUC - Titanium Dioxide	13463-67-7	Diatom	Experimental	72 hours	NOEC	5,600 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Glass powder (65997-17-3), surface modified with 2-propenoic acid, 2 methyl3- (trimethoxysilyl)pr opyl ester (2530- 85-0), bulk material	None	Data not available- insufficient	N/A	N/A	N/A	N/A
SUBSTITUTED DIMETHACRYL ATE	27689-12-9	Experimental Biodegradation	28 days	CO2 evolution	7-12 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
1,12-DODECANE DIMETHYCRYL ATE	72829-09-5	Experimental Biodegradation	28 days	CO2 evolution	97.3 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
2,4,6(1H,3H,5H)- Pyrimidinetrione,	945012-02-2	Data not available-	N/A	N/A	N/A	N/A

Page: 10 of 12

5-phenyl-1- (phenylmethyl)-, calcium salt (2:1)		insufficient				
SILANE TREATED SILICA	68909-20-6	Data not available- insufficient	N/A	N/A	N/A	N/A
[(3- methoxypropyl)imi no]di-2,1- ethanediyl bismethacrylate	93962-71-1	Modeled Biodegradation	28 days	BOD	70 %BOD/ThOD	Catalogic TM
Calcium dihydroxide	1305-62-0	Data not available- insufficient	N/A	N/A	N/A	N/A
Sodium toluene-4- sulphinate	824-79-3	Experimental Biodegradation	28 days	BOD	91 %BOD/ThOD	OECD 301C - MITI test (I)
NUC - Titanium Dioxide	13463-67-7	Data not available- insufficient	N/A	N/A	N/A	N/A

12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Glass powder (65997-17-3), surface modified with 2-propenoic acid, 2 methyl3-(trimethoxysilyl)pr opyl ester (2530-85-0), bulk material	None	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
SUBSTITUTED DIMETHACRYL ATE	27689-12-9	Modeled Bioconcentration		Log Kow	7.61	Episuite TM
1,12-DODECANE DIMETHYCRYL ATE	72829-09-5	Modeled Bioconcentration		Bioaccumulation factor	6.6	Catalogic™
1,12-DODECANE DIMETHYCRYL ATE	72829-09-5	Experimental Bioconcentration		Log Kow	>6.5	830.7570 Part. Coef by LC
2,4,6(1H,3H,5H)- Pyrimidinetrione, 5-phenyl-1- (phenylmethyl)-, calcium salt (2:1)	945012-02-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
SILANE TREATED SILICA	68909-20-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
[(3- methoxypropyl)imi no]di-2,1- ethanediyl bismethacrylate	93962-71-1	Modeled Bioconcentration		Bioaccumulation factor	3.6	Catalogic™
[(3-methoxypropyl)imi no]di-2,1- ethanediyl bismethacrylate	93962-71-1	Modeled Bioconcentration		Log Kow	1.7	ACD/Labs ChemSketch™
Calcium dihydroxide	1305-62-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Sodium toluene-4- sulphinate	824-79-3	Estimated Bioconcentration		Bioaccumulation factor	3.9	
NUC - Titanium Dioxide	13463-67-7	Experimental BCF - Fish	42 days	Bioaccumulation factor	9.6	

12.4. Mobility in soil

3MTM RelyXTM U200 Automix Catalyst

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility.

SECTION 14: Transport Information

International Regulations

UN No.: None assigned

UN Proper shipping name: None assigned

Transportation Class (IMO): None assigned Transportation Class (IATA): None assigned

Other Dangerous Goods Descriptions (IMO): None assigned Other Dangerous Goods Descriptions (IATA): None assigned

Packing Group: None assigned Marine pollutant: None assigned

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information.

SECTION 16: Other information

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M Singapore SDSs are available at www.3m.com.sg

D 12 c 12



Safety Data Sheet

Copyright, 2024, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

This Safety Data Sheet has been prepared in accordance with the SS586 Specification for Hazard Communication for Hazardous Chemicals and Dangerous Goods.

Document group: 29-4856-0 **Version number:** 2.00

Issue Date: 29/08/2024 **Supersedes date:** 24/07/2018

SECTION 1: Identification

1.1. Product identifier

3MTM RelyXTM U200 Automix Base Paste

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Cement

Restrictions on use

For use by dental professionals only.

1.3. Supplier's details

Address: 3M Technologies (S) Pte Ltd, 10 Ang Mo Kio Street 65, Singapore 569059

Telephone: +65 6450 8888 **Website:** www.3m.com.sg

1.4. Emergency telephone number

+65 6591 6601 (8.15am - 5.00pm, Monday - Friday)

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Skin Sensitizer: Category 1.

2.2. Label elements

SIGNAL WORD

WARNING!

Symbols

Exclamation mark |

Pictograms



HAZARD STATEMENTS

H317 May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

Prevention:

P280E Wear protective gloves.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

2.3. Other hazards

Eye damage/irritation class. not applied based on test data

This material has been tested for eye damage/irritation and the test results do not meet the criteria for classification.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Wt
Glass powder (65997-17-3), surface	None	45 - 55
modified with 2-propenoic acid, 2		
methyl3-(trimethoxysilyl)propyl ester		
(2530-85-0) and phenyltrimethoxy silane		
(2996-92-1), bulk material		
2-PROPENOIC ACID, 2-METHYL-, 1,1'-	1224866-76-5	20 - 30
[1-(HYDROXYMETHYL)-1,2-		
ETHANEDIYL] ESTER, REACTION		
PRODUCTS WITH 2-HYDROXY-1,3-		
PROPANEDIYL DIMETHACRYLATE		
AND PHOSPHORUS OXIDE		
2,2'-ethylenedioxydiethyl dimethacrylate	109-16-0	10 - 20
SILANE TREATED SILICA	68909-20-6	1 - 10
SODIUM PERSULFATE	7775-27-1	< 3
OXIDE GLASS CHEMICALS (non-	65997-17-3	< 3
fibrous)		
Tert-butyl 3,5,5-trimethylperoxyhexanoate	13122-18-4	< 0.5
Acetic acid, copper(2+) salt, monohydrate	6046-93-1	< 0.1

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

3MTM RelyXTM U200 Automix Base Paste

Eve contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a water extinguisher to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide.

Carbon dioxide.

Irritant vapours or gases.

Condition

During combustion.

During combustion.

During combustion.

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. Acrylates may penetrate commonly-used gloves. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Take any precaution to avoid mixing with combustibles. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Do not get in eyes.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Keep/store away from clothing and other combustible materials.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient		CAS Nbr	Agency	Limit type	Additional comments
COPPER C	COMPOUNDS	6046-93-1	ACGIH	TWA(as Cu, fume):0.2	
				mg/m3;TWA(as Cu dust or	
				mist):1 mg/m3	
PERSULFA	ATE COMPOUNDS	7775-27-1	ACGIH	TWA(as persulfate):0.1 mg/m3	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

Singapore PELs: Singapore. Workplace Safety and Health (Permissible Exposure Levels of Toxic Substances) Order

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid.
Specific Physical Form:	Paste
Color	Tooth
Odor	Slight Acrylic
Odour threshold	No data available.
pH	Not applicable.
Melting point/Freezing point	No data available.

Boiling point/Initial boiling point/Boiling range	No data available.
Flash point	No flash point
Evaporation rate	No data available.
Flammability	Not applicable.
Flammable Limits(LEL)	No data available.
Flammable Limits(UEL)	No data available.
Vapour pressure	No data available.
Vapor Density and/or Relative Vapor Density	No data available.
Density	2 g/cm3 - 2.2 g/cm3
Relative density	2 - 2.2 [<i>Ref Std</i> :WATER=1]
Water solubility	Negligible
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Autoignition temperature	No data available.
Decomposition temperature	No data available.
Kinematic Viscosity	No data available.
Volatile organic compounds (VOC)	No data available.
Percent volatile	No data available.
VOC less H2O & exempt solvents	No data available.
Molecular weight	No data available.

Particle Characteristics	Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

Substance None known. **Condition**

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be

relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

This product may have a characteristic odour; however, no adverse health effects are anticipated.

Skin contact

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eve contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
Glass powder (65997-17-3), surface modified with 2-propenoic acid, 2 methyl3-(trimethoxysilyl)propyl ester (2530-85-0) and phenyltrimethoxy silane (2996-92-1), bulk material	Dermal		LD50 estimated to be > 5,000 mg/kg
Glass powder (65997-17-3), surface modified with 2-propenoic acid, 2 methyl3-(trimethoxysilyl)propyl ester (2530-85-0) and phenyltrimethoxy silane (2996-92-1), bulk material	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
2-PROPENOIC ACID, 2-METHYL-, 1,1'-[1- (HYDROXYMETHYL)-1,2-ETHANEDIYL] ESTER, REACTION PRODUCTS WITH 2-HYDROXY-1,3- PROPANEDIYL DIMETHACRYLATE AND PHOSPHORUS OXIDE	Dermal		LD50 estimated to be > 5,000 mg/kg
2-PROPENOIC ACID, 2-METHYL-, 1,1'-[1- (HYDROXYMETHYL)-1,2-ETHANEDIYL] ESTER, REACTION PRODUCTS WITH 2-HYDROXY-1,3- PROPANEDIYL DIMETHACRYLATE AND PHOSPHORUS OXIDE	Ingestion	Rat	LD50 > 2,000 mg/kg
2,2'-ethylenedioxydiethyl dimethacrylate	Dermal	Mouse	LD50 > 2,000
2,2'-ethylenedioxydiethyl dimethacrylate	Ingestion	Rat	LD50 10,837 mg/kg
SILANE TREATED SILICA	Ingestion	Rat	LD50 > 2,000 mg/kg
SILANE TREATED SILICA	Dermal	similar health hazards	LD50 estimated to be > 5,000 mg/kg
OXIDE GLASS CHEMICALS (non-fibrous)	Dermal		LD50 estimated to be > 5,000 mg/kg
OXIDE GLASS CHEMICALS (non-fibrous)	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
SODIUM PERSULFATE	Dermal	Rabbit	LD50 > 10,000 mg/kg
SODIUM PERSULFATE	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 47.93 mg/l
SODIUM PERSULFATE	Ingestion	Rat	LD50 895 mg/kg
Tert-butyl 3,5,5-trimethylperoxyhexanoate	Dermal	Rat	LD50 > 2,000 mg/kg
Tert-butyl 3,5,5-trimethylperoxyhexanoate	Inhalation-	Rat	LC50 > 0.8 mg/l

Page: 6 of 14

3MTM RelyXTM U200 Automix Base Paste

	Dust/Mist		
	(4 hours)		
Tert-butyl 3,5,5-trimethylperoxyhexanoate	Ingestion	Rat	LD50 12,905 mg/kg
Acetic acid, copper(2+) salt, monohydrate	Dermal	Rat	LD50 > 2,000 mg/kg
Acetic acid, copper(2+) salt, monohydrate	Ingestion	Rat	LD50 > 300, < 2000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Glass powder (65997-17-3), surface modified with 2-propenoic acid, 2 methyl3-(trimethoxysilyl)propyl ester (2530-85-0) and phenyltrimethoxy silane (2996-92-1), bulk material	Professio nal judgemen t	No significant irritation
2-PROPENOIC ACID, 2-METHYL-, 1,1'-[1-(HYDROXYMETHYL)-1,2- ETHANEDIYL] ESTER, REACTION PRODUCTS WITH 2-HYDROXY-1,3- PROPANEDIYL DIMETHACRYLATE AND PHOSPHORUS OXIDE	Rabbit	Minimal irritation
2,2'-ethylenedioxydiethyl dimethacrylate	Rabbit	No significant irritation
SILANE TREATED SILICA	Rabbit	No significant irritation
OXIDE GLASS CHEMICALS (non-fibrous)	Professio nal judgemen t	No significant irritation
Tert-butyl 3,5,5-trimethylperoxyhexanoate	Rabbit	No significant irritation
Acetic acid, copper(2+) salt, monohydrate	In vitro data	Corrosive

Serious Eve Damage/Irritation

Name	Species	Value		
Overall product		No significant irritation		
Glass powder (65997-17-3), surface modified with 2-propenoic acid, 2 methyl3-(trimethoxysilyl)propyl ester (2530-85-0) and phenyltrimethoxy silane (2996-92-1), bulk material	Professio nal judgemen t	No significant irritation		
2-PROPENOIC ACID, 2-METHYL-, 1,1'-[1-(HYDROXYMETHYL)-1,2- ETHANEDIYL] ESTER, REACTION PRODUCTS WITH 2-HYDROXY-1,3- PROPANEDIYL DIMETHACRYLATE AND PHOSPHORUS OXIDE	Rabbit	Corrosive		
2,2'-ethylenedioxydiethyl dimethacrylate	Rabbit	No significant irritation		
SILANE TREATED SILICA	Rabbit	No significant irritation		
OXIDE GLASS CHEMICALS (non-fibrous)	Professio nal judgemen t	No significant irritation		
Tert-butyl 3,5,5-trimethylperoxyhexanoate	Rabbit	No significant irritation		
Acetic acid, copper(2+) salt, monohydrate	Rabbit	Corrosive		

Sensitization:

Skin Sensitisation

Name	Species	Value
2-PROPENOIC ACID, 2-METHYL-, 1,1'-[1-(HYDROXYMETHYL)-1,2-ETHANEDIYL] ESTER, REACTION PRODUCTS WITH 2-HYDROXY-1,3-PROPANEDIYL DIMETHACRYLATE AND PHOSPHORUS OXIDE	Guinea pig	Not classified
2,2'-ethylenedioxydiethyl dimethacrylate	Mouse	Sensitising
SILANE TREATED SILICA	Guinea pig	Not classified
Tert-butyl 3,5,5-trimethylperoxyhexanoate	Guinea pig	Sensitising
Acetic acid, copper(2+) salt, monohydrate	Guinea pig	Not classified

Page: 7 of 14

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
2-PROPENOIC ACID, 2-METHYL-, 1,1'-[1-(HYDROXYMETHYL)-1,2-	In Vitro	Not mutagenic
ETHANEDIYL] ESTER, REACTION PRODUCTS WITH 2-HYDROXY-1,3-		
PROPANEDIYL DIMETHACRYLATE AND PHOSPHORUS OXIDE		
2,2'-ethylenedioxydiethyl dimethacrylate	In Vitro	Some positive data exist, but the data are not
		sufficient for classification
SILANE TREATED SILICA	In Vitro	Not mutagenic
Acetic acid, copper(2+) salt, monohydrate	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
2,2'-ethylenedioxydiethyl dimethacrylate	Dermal	Mouse	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
2,2'-ethylenedioxydiethyl dimethacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
2,2'-ethylenedioxydiethyl dimethacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	5 weeks
2,2'-ethylenedioxydiethyl dimethacrylate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
SILANE TREATED SILICA	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
SILANE TREATED SILICA	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

specific ranger organ	promo rurgor organ romoty single enposure							
Name	Route	Target Organ(s)	Value	Species	Test result	Exposure		
						Duration		
Acetic acid, copper(2+)	Inhalation	respiratory irritation	Some positive data exist, but the	similar	NOAEL Not			
salt, monohydrate			data are not sufficient for	health	available			
			classification	hazards				

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
2,2'-ethylenedioxydiethyl dimethacrylate	Dermal	liver	Not classified	Mouse	NOAEL 2,000 mg/kg/day	13 weeks
2,2'-ethylenedioxydiethyl dimethacrylate	Dermal	skin	Not classified	Mouse	NOAEL 100 mg/kg/day	13 weeks
2,2'-ethylenedioxydiethyl dimethacrylate	Dermal	gastrointestinal tract hematopoietic system nervous system kidney and/or bladder respiratory system	Not classified	Mouse	NOAEL 2,000 mg/kg/day	13 weeks
2,2'-ethylenedioxydiethyl dimethacrylate	Ingestion	hematopoietic system liver nervous system	Not classified	Rat	NOAEL 3,849 mg/kg/day	13 weeks

		kidney and/or bladder eyes				
SILANE TREATED SILICA	Inhalation	respiratory system	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 0.035 mg/l	13 weeks
SILANE TREATED SILICA	Inhalation	hematopoietic system kidney and/or bladder	Not classified	Rat	NOAEL 0.035 mg/l	13 weeks
SILANE TREATED SILICA	Ingestion	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	5 weeks

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

GHS Acute 3: Harmful to aquatic life.

Chronic aquatic hazard:

GHS Chronic 3: Harmful to aquatic life with long lasting effects.

No product test data available.

Material	CAS Nbr	Organism	Туре	Exposure	Test endpoint	Test result
Glass powder (65997-17-3), surface modified with 2-propenoic acid, 2 methyl3-(trimethoxysilyl)pr opyl ester (2530-85-0) and phenyltrimethoxy silane (2996-92-1), bulk material	None	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
2-PROPENOIC ACID, 2- METHYL-, 1,1'-[1- (HYDROXYMET HYL)-1,2- ETHANEDIYL] ESTER, REACTION PRODUCTS WITH 2- HYDROXY-1,3- PROPANEDIYL DIMETHACRYL ATE AND	1224866-76-5	Green algae	Endpoint not reached	72 hours	EC50	>100 mg/l

D 0 C 14

PHOSPHORUS						
OXIDE 2-PROPENOIC	1224866-76-5	Water flea	Experimental	48 hours	EC50	>100 mg/l
ACID, 2-			r · · · · ·			
METHYL-, 1,1'-[1- (HYDROXYMET						
HYL)-1,2-						
ETHANEDIYL] ESTER,						
REACTION						
PRODUCTS						
WITH 2- HYDROXY-1,3-						
PROPANEDIYL						
DIMETHACRYL						
ATE AND PHOSPHORUS						
OXIDE						
2-PROPENOIC	1224866-76-5	Green algae	Experimental	72 hours	NOEC	56 mg/l
ACID, 2- METHYL-, 1,1'-[1- (HYDROXYMET						
HYL)-1,2-						
ETHANEDIYL] ESTER,						
REACTION						
PRODUCTS						
WITH 2- HYDROXY-1,3-						
PROPANEDIYL						
DIMETHACRYL ATE AND						
PHOSPHORUS						
OXIDE						
2,2'- ethylenedioxydieth	109-16-0	Green algae	Experimental	72 hours	ErC50	>100 mg/l
yl dimethacrylate						
2,2'- ethylenedioxydieth	109-16-0	Zebra Fish	Experimental	96 hours	LC50	16.4 mg/l
yl dimethacrylate						
2,2'-	109-16-0	Green algae	Experimental	72 hours	NOEC	18.6 mg/l
ethylenedioxydieth yl dimethacrylate						
2,2'-	109-16-0	Water flea	Experimental	21 days	NOEC	32 mg/l
ethylenedioxydieth				-		
yl dimethacrylate SILANE	68909-20-6	Algae or other	Estimated	72 hours	EC50	>100 mg/l
TREATED	20 0	aquatic plants	Estimated	72 Hours	Leso	100 mg/
SILICA OXIDE GLASS	(5007.17.2	NT/A	D-4	N/A	N/A	N/A
CHEMICALS	65997-17-3	N/A	Data not available or insufficient for	IN/A	IN/A	IN/A
(non-fibrous)			classification			
SODIUM PERSULFATE	7775-27-1	Algae or other aquatic plants	Estimated	72 hours	EC50	320 mg/l
SODIUM	7775-27-1	Copepod	Estimated	48 hours	EC50	21.22 mg/l
PERSULFATE						
SODIUM PERSULFATE	7775-27-1	Rainbow trout	Estimated	96 hours	LC50	76.3 mg/l
SODIUM PERSULFATE	7775-27-1	Algae or other aquatic plants	Estimated	72 hours	NOEC	32 mg/l
Tert-butyl 3,5,5-	13122-18-4	Green algae	Experimental	72 hours	ErC50	0.51 mg/l
trimethylperoxyhex anoate						
Tert-butyl 3,5,5-	13122-18-4	Rainbow trout	Experimental	96 hours	LC50	7.03 mg/l
trimethylperoxyhex						
anoate Tert-butyl 3,5,5-	13122-18-4	Water flea	Experimental	48 hours	EC50	>100 mg/l
trimethylperoxyhex	15122 10-7	, ator rica	Experimental	TO HOURS		100 mg/1
anoate						

Page: 10 of 14

Tert-butyl 3,5,5-	13122-18-4	Green algae	Experimental	72 hours	NOEC	0.125 mg/l
trimethylperoxyhex anoate						
Tert-butyl 3,5,5-	13122-18-4	Water flea	Experimental	21 days	NOEC	0.22 mg/l
trimethylperoxyhex		Water freu	Experimental	21 days	I TOLE	0.22 mg i
anoate						
Tert-butyl 3,5,5-	13122-18-4	Activated sludge	Experimental	3 hours	EC50	327.02 mg/l
trimethylperoxyhex			1			
anoate						
Acetic acid,	6046-93-1	Green algae	Estimated	72 hours	EC50	0.33 mg/l
copper(2+) salt,						
monohydrate						
Acetic acid,	6046-93-1	Water flea	Estimated	48 hours	EC50	0.04 mg/l
copper(2+) salt,						
monohydrate						
Acetic acid,	6046-93-1	Zebra Fish	Estimated	96 hours	LC50	0.037 mg/l
copper(2+) salt,						
monohydrate					12010	
Acetic acid,	6046-93-1	Fathead minnow	Estimated	32 days	EC10	0.019 mg/l
copper(2+) salt,						
monohydrate	50.45.00.4			27/	21070	10.050 #
Acetic acid,	6046-93-1	Green algae	Estimated	N/A	NOEC	0.069 mg/l
copper(2+) salt,						
monohydrate	6046.02.1	C II AWA	In a second	20.1	NOEG	57.5 / (D. W.: 1.)
Acetic acid,	6046-93-1	Sediment Worm	Estimated	28 days	NOEC	57.5 mg/kg (Dry Weight)
copper(2+) salt,						
monohydrate Acetic acid.	6046-93-1	Water flea	Estimated	7 days	NOEC	0.01 mg/l
copper(2+) salt,	0040-93-1	water frea	Estilliated	/ days	NOEC	0.01 mg/1
monohydrate						
Acetic acid,	6046-93-1	Activated sludge	Estimated	N/A	EC50	22 mg/l
copper(2+) salt,	0040-75-1	Activated studge	Limated	IV/A	LC30	22 mg/1
monohydrate						
Acetic acid,	6046-93-1	Barley	Estimated	4 days	NOEC	50 mg/kg (Dry Weight)
copper(2+) salt,				,	1	[* * * * * * * * * * * * * * * * * * *
monohydrate						
Acetic acid,	6046-93-1	Bobwhite quail	Estimated	14 days	LD50	4,402 mg per kg of
copper(2+) salt,		1				bodyweight
monohydrate						
Acetic acid,	6046-93-1	Redworm	Estimated	56 days	NOEC	31 mg/kg (Dry Weight)
copper(2+) salt,						
monohydrate						
Acetic acid,	6046-93-1	Soil microbes	Estimated	4 days	NOEC	38 mg/kg (Dry Weight)
copper(2+) salt,						
monohydrate						
Acetic acid,	6046-93-1	Springtail	Estimated	28 days	NOEC	87.7 mg/kg (Dry Weight)
copper(2+) salt,						
monohydrate						

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Glass powder	None		N/A	N/A	N/A	N/A
(65997-17-3),		available-				
surface modified		insufficient				
with 2-propenoic						
acid, 2 methyl3-						
(trimethoxysilyl)pr						
opyl ester (2530-						
85-0) and						
phenyltrimethoxy						
silane (2996-92-1),						
bulk material						

2-PROPENOIC	1224866-76-5	Experimental	28 days	BOD	82 %BOD/ThOD	OECD 301F - Manometric
ACID, 2-		Biodegradation	•			respirometry
METHYL-, 1,1'-[1-						
(HYDROXYMET						
HYL)-1,2-						
ETHANEDIYL]						
ESTER,						
REACTION						
PRODUCTS						
WITH 2-						
HYDROXY-1,3-						
PROPANEDIYL						
DIMETHACRYL						
ATE AND						
PHOSPHORUS						
OXIDE						
2,2'-	109-16-0	Experimental	28 days	CO2 evolution	85 %CO2	OECD 301B - Modified
ethylenedioxydieth		Biodegradation	•		evolution/THCO2	sturm or CO2
yl dimethacrylate					evolution	
SILANE	68909-20-6	Data not	N/A	N/A	N/A	N/A
TREATED		available-				
SILICA		insufficient				
OXIDE GLASS	65997-17-3	Data not	N/A	N/A	N/A	N/A
CHEMICALS		available-				
(non-fibrous)		insufficient				
SODIUM	7775-27-1	Data not	N/A	N/A	N/A	N/A
PERSULFATE		available-				
		insufficient				
Tert-butyl 3,5,5-	13122-18-4	Experimental	28 days	BOD	72 %BOD/ThOD	OECD 301D - Closed bottle
trimethylperoxyhex		Biodegradation	•			test
anoate						
Tert-butyl 3,5,5-	13122-18-4	Experimental	56 days	BOD	58 %BOD/ThOD	OECD 302A - Modified
trimethylperoxyhex		Aquatic Inherent	•			SCAS Test
anoate		Biodegrad.				
Tert-butyl 3,5,5-	13122-18-4	Experimental		Hydrolytic half-life	51 hours (t 1/2)	OECD 111 Hydrolysis func
trimethylperoxyhex		Hydrolysis		(pH 7)	` ′	of pH
anoate		'		- /		-
Acetic acid,	6046-93-1	Analogous	14 days	BOD	74 %BOD/ThOD	OECD 301C - MITI test (I)
copper(2+) salt,		Compound				
monohydrate		Biodegradation				
			•	•		

12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Glass powder (65997-17-3), surface modified with 2-propenoic acid, 2 methyl3-(trimethoxysilyl)pr opyl ester (2530-85-0) and phenyltrimethoxy silane (2996-92-1), bulk material	None	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
2-PROPENOIC ACID, 2- METHYL-, 1,1'-[1- (HYDROXYMET HYL)-1,2- ETHANEDIYL] ESTER, REACTION PRODUCTS WITH 2- HYDROXY-1,3- PROPANEDIYL DIMETHACRYL	1224866-76-5	Experimental Bioconcentration		Log Kow	-0.2	

ATE AND PHOSPHORUS OXIDE						
2,2'- ethylenedioxydieth yl dimethacrylate	109-16-0	Experimental Bioconcentration		Log Kow	2.3	EC A.8 Partition Coefficient
SILANE TREATED SILICA	68909-20-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
OXIDE GLASS CHEMICALS (non-fibrous)	65997-17-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
SODIUM PERSULFATE	7775-27-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Tert-butyl 3,5,5- trimethylperoxyhex anoate	13122-18-4	Modeled Bioconcentration		Bioaccumulation factor	380	Catalogic™
Tert-butyl 3,5,5- trimethylperoxyhex anoate	13122-18-4	Experimental Bioconcentration		Log Kow	5.16	OECD 117 log Kow HPLC method
Acetic acid, copper(2+) salt, monohydrate	6046-93-1	Analogous Compound Bioconcentration		Log Kow	-0.17	

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility.

SECTION 14: Transport Information

International Regulations

UN No.: None assigned

UN Proper shipping name: None assigned

Transportation Class (IMO): None assigned Transportation Class (IATA): None assigned

Other Dangerous Goods Descriptions (IMO): None assigned Other Dangerous Goods Descriptions (IATA): None assigned

Packing Group: None assigned Marine pollutant: None assigned

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this product are in compliance with the new substance notification requirements of CEPA.

This product may contain component(s) that are regulated by the following:

Workplace Safety and Health Act & Workplace Safety and Health (General Provisions) Regulations: this product is subject to SDS, labelling, PEL and other requirements in the Act/Regulations.

Fire Safety (Petroleum and Flammable Materials) Regulations: This product is subject to the requirements in the Regulations

SECTION 16: Other information

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M Singapore SDSs are available at www.3m.com.sg

D. . . 14 . C . 14