

Safety Data Sheet

Copyright,2024, 3M Company.All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

This Safety Data Sheet has been prepared in accordance with the SS586 Specification for Hazard Communication for Hazardous Chemicals and Dangerous Goods.

Document group:	40-6107-3	Version number:	3.00
Issue Date:	07/10/2024	Supersedes date:	25/03/2024

SECTION 1: Identification

1.1. Product identifier

3M Pavement Marking Thermoplastic Yellow

1.2. Recommended use and restrictions on use

Recommended use

Pavement Marking

1.3. Supplier's details

Address:	3M Technologies (S) Pte Ltd, 10 Ang Mo Kio Street 65, Singapore 569059
Telephone:	+65 6450 8888
Website:	www.3m.com.sg

1.4. Emergency telephone number

+65 6591 6601 (8.15am - 5.00pm, Monday - Friday)

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 2. Skin Sensitizer: Category 1. Carcinogenicity: Category 2.

2.2. Label elements SIGNAL WORD WARNING!

Symbols Exclamation mark |Health Hazard |

Pictograms



HAZARD STATEMENTS H319 H317 H351	Causes serious eye irritation. May cause an allergic skin reaction. Suspected of causing cancer.	
PRECAUTIONARY STATEMENT Prevention: P280K	Wear protective gloves and respiratory protection.	
Response: P305 + P351 + P338 P333 + P313 2 3 Other hazards	IF IN EYES: Rinse cautiously with water for several minutes. lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention.	Remove contact

May cause thermal burns.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Wt
Limestone	1317-65-3	30 - 60
Oxide glass chemicals	65997-17-3	15 - 40
Rosin, maleated, esters with glycerol	68038-41-5	10 - 30
Titanium dioxide	13463-67-7	5 - 10
Polyethylene	9002-88-4	1 - 5
Solvent dewaxed heavy paraffinic distillate	64742-65-0	< 1
(petroleum)		
Pigment	129423-54-7	< 1

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately flush skin with large amounts of cold water for at least 15 minutes. DO NOT ATTEMPT TO REMOVE MOLTEN MATERIAL. Cover affected area with a clean dressing. Get immediate medical attention.

Eye contact

Immediately flush eyes with large amounts of water for at least 15 minutes. DO NOT ATTEMPT TO REMOVE MOLTEN MATERIAL. Get immediate medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required Not applicable.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u> Carbon monoxide. Carbon dioxide. Irritant vapours or gases. <u>Condition</u> During combustion. During combustion. During combustion.

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Use wet sweeping compound or water to avoid dusting. Sweep up. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin contact with hot material. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Limestone	1317-65-3	Singapore PELs	TWA(8 hours):10 mg/m3	

Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles	1317-65-3	ACGIH	TWA(inhalable particulates):10 mg/m3	
Particles (insoluble or poorly soluble) not otherwise specified, respirable particles	1317-65-3	ACGIH	TWA(respirable particles):3 mg/m3	
Titanium dioxide	13463-67-7	ACGIH	TWA(Respirable nanoscale particles):0.2 mg/m3;TWA(Respirable finescale particles):2.5 mg/m3	A3: Confirmed animal carcin.
Titanium dioxide	13463-67-7	Singapore PELs	TWA(8 hours):10 mg/m3	
Oil mist mineral	64742-65-0	Singapore PELs	TWA(as mist)(8 hours):5 mg/m3;STEL(as mist)(15 minutes):10 mg/m3	
CERAMIC FIBERS	65997-17-3	ACGIH	TWA(as fiber):0.2 fiber/cc	A2: Suspected human carcin.
CONTINUOUS FILAMENT GLASS FIBERS	65997-17-3	ACGIH	TWA(as fiber):1 fiber/cc	A4: Not class. as human carcin
CONTINUOUS FILAMENT GLASS FIBERS, INHALABLE FRACTION	65997-17-3	ACGIH	TWA(inhalable fraction):5 mg/m3	A4: Not class. as human carcin
GLASS WOOL FIBERS	65997-17-3	ACGIH	TWA(as fiber):1 fiber/cc	A3: Confirmed animal carcin.
Oxide glass chemicals	65997-17-3	Manufacturer determined	TWA(as non-fibrous, respirable)(8 hours):3 mg/m3;TWA(as non-fibrous, inhalable fraction)(8 hours):10 mg/m3	
ROCK WOOL FIBERS	65997-17-3	ACGIH	TWA(as fiber):1 fiber/cc	A3: Confirmed animal carcin.
SLAG WOOL FIBERS	65997-17-3	ACGIH	TWA(as fiber):1 fiber/cc	A3: Confirmed animal carcin.
SPECIAL PURPOSE GLASS FIBERS	65997-17-3	ACGIH	TWA(as fiber):1 fiber/cc	A3: Confirmed animal carcin.
DUST, INERT OR NUISANCE	9002-88-4	Singapore PELs	TWA(as particulate)(8 hours):10 mg/m3	
Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles	9002-88-4	ACGIH	TWA(inhalable particulates):10 mg/m3	
Particles (insoluble or poorly soluble) not otherwise specified, respirable particles	9002-88-4	ACGIH	TWA(respirable particles):3 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

Singapore PELs : Singapore. Workplace Safety and Health (Permissible Exposure Levels of Toxic Substances) Order

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Full face shield. Indirect vented goggles.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Thermal hazards

Wear heat insulating gloves, indirect vented goggles, and a full face shield when handling hot material to prevent thermal burns.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid.		
Specific Physical Form:	Powder		
Color	Bright Yellow, Yellow		
Odor	Typical Odorless		
Odour threshold	No data available.		
рН	No data available.		
Melting point/Freezing point	85 - 105 °C		
Boiling point/Initial boiling point/Boiling range	> 260 °C		
Flash point	> 230 °C [Test Method:Open Cup]		
Evaporation rate	No data available.		
Flammability	Not applicable.		
Flammable Limits(LEL)	No data available.		
Flammable Limits(UEL)	No data available.		
Vapour pressure	Not applicable.		
apor Density and/or Relative Vapor Density > 1 [Ref Std:AIR=1]			

Relative density	2 [<i>Ref Std</i> :WATER=1]
Water solubility	Insoluble
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Autoignition temperature	No data available.
Decomposition temperature	No data available.
Kinematic Viscosity	No data available.

Particle Characteristics

Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid Heat.

пеаі.

10.5 Incompatible materials None known.

10.6 Hazardous decomposition products

Substance None known. **Condition**

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

During heating: Thermal Burns: Signs/symptoms may include intense pain, redness and swelling, and tissue destruction. Mechanical skin irritation: Signs/symptoms may include abrasion, redness, pain, and itching. Allergic skin reaction (non-

photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

During heating: Thermal Burns: Signs/symptoms may include severe pain, redness and swelling, and tissue destruction. Moderate eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision. Mechanical eye irritation: Signs/symptoms may include pain, redness, tearing and corneal abrasion.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Additional Health Effects:

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity			
Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Limestone	Dermal	Rat	LD50 > 2,000 mg/kg
Limestone	Inhalation-	Rat	LC50 3 mg/l
	Dust/Mist		
	(4 hours)		
Limestone	Ingestion	Rat	LD50 6,450 mg/kg
Oxide glass chemicals	Dermal		LD50 estimated to be $> 5,000 \text{ mg/kg}$
Oxide glass chemicals	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Rosin, maleated, esters with glycerol	Dermal	Professio	LD50 estimated to be $> 5,000 \text{ mg/kg}$
		nal	
		judgeme	
		nt	
Rosin, maleated, esters with glycerol	Ingestion	Rat	LD50 > 5,000 mg/kg
Titanium dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium dioxide	Inhalation-	Rat	LC50 > 6.82 mg/l
	Dust/Mist		
	(4 hours)		
Titanium dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
Polyethylene	Dermal		LD50 estimated to be $> 5,000 \text{ mg/kg}$
Polyethylene	Ingestion	Rat	LD50 > 2,000 mg/kg
Solvent dewaxed heavy paraffinic distillate (petroleum)	Dermal	Rabbit	LD50 > 5,000 mg/kg
Solvent dewaxed heavy paraffinic distillate (petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
Solvent dewaxed heavy paraffinic distillate (petroleum)	Inhalation-	similar	LC50 > 4 mg/l
	Dust/Mist	compoun	
	(4 hours)	ds	
Pigment	Dermal	Rat	LD50 > 2,000 mg/kg
Pigment	Ingestion	Rat	LD50 > 2,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Limestone	Rabbit	No significant irritation
Oxide glass chemicals	Professio	No significant irritation
	nal	
	judgemen	
	t	
Rosin, maleated, esters with glycerol	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation
Polyethylene	Professio	No significant irritation

	nal judgemen t	
Solvent dewaxed heavy paraffinic distillate (petroleum)	Rabbit	No significant irritation
Pigment	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Limestone	Rabbit	No significant irritation
Oxide glass chemicals	Professio	No significant irritation
	nal	
	judgemen	
	t	
Rosin, maleated, esters with glycerol	Rabbit	Moderate irritant
Titanium dioxide	Rabbit	No significant irritation
Solvent dewaxed heavy paraffinic distillate (petroleum)	Rabbit	No significant irritation
Pigment	Rabbit	No significant irritation

Sensitization:

Skin Sensitisation

Name	Species	Value
Rosin, maleated, esters with glycerol	Mouse	Sensitising
Titanium dioxide	Human	Not classified
	and	
	animal	
Solvent dewaxed heavy paraffinic distillate (petroleum)	Guinea	Not classified
	pig	
Pigment	Guinea	Not classified
	pig	

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Oxide glass chemicals	In Vitro	Some positive data exist, but the data are not
		sufficient for classification
Rosin, maleated, esters with glycerol	In Vitro	Not mutagenic
Titanium dioxide	In Vitro	Not mutagenic
Titanium dioxide	In vivo	Not mutagenic
Solvent dewaxed heavy paraffinic distillate (petroleum)	In Vitro	Not mutagenic
Pigment	In vivo	Not mutagenic
Pigment	In Vitro	Some positive data exist, but the data are not
		sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Oxide glass chemicals	Inhalation	Multiple	Some positive data exist, but the data are not
		animal	sufficient for classification
		species	
Titanium dioxide	Ingestion	Multiple	Not carcinogenic
	-	animal	
		species	
Titanium dioxide	Inhalation	Rat	Carcinogenic.
Polyethylene	Not	Multiple	Some positive data exist, but the data are not
	specified.	animal	sufficient for classification
		species	
Solvent dewaxed heavy paraffinic distillate (petroleum)	Dermal	Mouse	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Limestone	Ingestion	Not classified for development	Rat	NOAEL 625 mg/kg/day	premating & during gestation
Solvent dewaxed heavy paraffinic distillate (petroleum)	Dermal	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation
Pigment	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
Pigment	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
Pigment	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	1 generation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure
						Duration
Limestone	Inhalation	respiratory system	Not classified	Rat	NOAEL	90 minutes
					0.812 mg/l	
Rosin, maleated, esters	Inhalation	respiratory irritation	Some positive data exist, but the	similar	NOAEL Not	
with glycerol			data are not sufficient for	health	available	
			classification	hazards		

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Limestone	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Oxide glass chemicals	Inhalation	respiratory system	Not classified	Human	NOAEL not available	occupational exposure
Titanium dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Solvent dewaxed heavy paraffinic distillate (petroleum)	Dermal	skin liver hematopoietic system kidney and/or bladder	Not classified	Rat	NOAEL 2,000 mg/kg/day	13 weeks
Pigment	Ingestion	heart endocrine system gastrointestinal tract hematopoietic system liver immune system kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

Aspiration Hazard

hazard
<u>n l</u>

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

Not acutely toxic to aquatic life by GHS criteria.

Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available.

Material	CAS Nbr	Organism	Туре	Exposure	Test endpoint	Test result
Limestone	1317-65-3	Green algae	Estimated	72 hours	EC50	>100 mg/l
Limestone	1317-65-3	Rainbow trout	Estimated	96 hours	LC50	>100 mg/l
Limestone	1317-65-3	Water flea	Estimated	48 hours	EC50	>100 mg/l
Limestone	1317-65-3	Green algae	Estimated	72 hours	EC10	>100 mg/l
Oxide glass	65997-17-3	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
chemicals		6	1			, ,
Oxide glass chemicals	65997-17-3	Water flea	Experimental	72 hours	EC50	>1,000 mg/l
Oxide glass chemicals	65997-17-3	Zebra Fish	Experimental	96 hours	LC50	>1,000 mg/l
Oxide glass chemicals	65997-17-3	Green algae	Experimental	72 hours	NOEC	>=1,000 mg/l
Rosin, maleated, esters with glycerol	68038-41-5	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Activated sludge	Experimental	3 hours	NOEC	>=1,000 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	EC50	>10,000 mg/l
Titanium dioxide	13463-67-7	Fathead minnow	Experimental	96 hours	LC50	>100 mg/l
Titanium dioxide	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	NOEC	5,600 mg/l
Polyethylene	9002-88-4	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Pigment	129423-54-7	Activated sludge	Experimental	3 hours	NOEC	1,000 mg/l
Pigment	129423-54-7	Green algae	Experimental	72 hours	EC50	>39.8 mg/l
Pigment	129423-54-7	Water flea	Experimental	48 hours	EC50	750 mg/l
Pigment	129423-54-7	Zebra Fish	Experimental	96 hours	LC50	>500 mg/l
Pigment	129423-54-7	Water flea	Experimental	21 days	NOEC	1.88 mg/l
Pigment	129423-54-7	Zebra Fish	Experimental	28 days	NOEC	37.7 mg/l
Solvent dewaxed heavy paraffinic distillate (petroleum)	64742-65-0	Green algae	Analogous Compound	96 hours	EC50	>100 mg/l
Solvent dewaxed heavy paraffinic distillate (petroleum)	64742-65-0	Water flea	Analogous Compound	48 hours	EC50	>100 mg/l
Solvent dewaxed heavy paraffinic distillate (petroleum)	64742-65-0	Rainbow trout	Experimental	96 hours	LC50	>100 mg/l
Solvent dewaxed	64742-65-0	Water flea	Experimental	21 days	NOEC	100 mg/l

heavy paraffinic			
(petroleum)			

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Limestone	1317-65-3	Data not available- insufficient	N/A	N/A	N/A	N/A
Oxide glass chemicals	65997-17-3	Data not available- insufficient	N/A	N/A	N/A	N/A
Rosin, maleated, esters with glycerol	68038-41-5	Data not available- insufficient	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Data not available- insufficient	N/A	N/A	N/A	N/A
Polyethylene	9002-88-4	Data not available- insufficient	N/A	N/A	N/A	N/A
Pigment	129423-54-7	Estimated Biodegradation	28 days	BOD	8 %BOD/ThOD	OECD 301D - Closed bottle test
Solvent dewaxed heavy paraffinic distillate (petroleum)	64742-65-0	Experimental Biodegradation	28 days	CO2 evolution	23 %CO2 evolution/THCO2 evolution	similar to OECD 301B

12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Limestone	1317-65-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Oxide glass chemicals	65997-17-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Rosin, maleated, esters with glycerol	68038-41-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Experimental BCF - Fish	42 days	Bioaccumulation factor	9.6	
Polyethylene	9002-88-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Pigment	129423-54-7	Experimental BCF - Fish	14 days	Bioaccumulation factor	4	OECD305-Bioconcentration
Solvent dewaxed heavy paraffinic distillate (petroleum)	64742-65-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Dispose of waste product in a permitted industrial waste facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

International Regulations

UN No.: Not restricted for transport. UN Proper shipping name: Not restricted for transport.

Transportation Class (IMO): None assignedTransportation Class (IATA): None assignedOther Dangerous Goods Descriptions (IMO):None assignedOther Dangerous Goods Descriptions (IATA):None assignedPacking Group: None assignedMarine pollutant: None assigned

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information.

This product may contain component(s) that are regulated by the following:

Workplace Safety and Health Act & Workplace Safety and Health (General Provisions) Regulations: this product is subject to SDS, labelling, PEL and other requirements in the Act/Regulations.

Fire Safety (Petroleum and Flammable Materials) Regulations: This product is subject to the requirements in the Regulations

SECTION 16: Other information

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M Singapore SDSs are available at www.3m.com.sg