



## Safety Data Sheet

Copyright, 2024, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

This Safety Data Sheet has been prepared in accordance with the SS586 Specification for Hazard Communication for Hazardous Chemicals and Dangerous Goods.

<b>Document group:</b>	36-4098-4	<b>Version number:</b>	2.00
<b>Issue Date:</b>	20/03/2024	<b>Supersedes date:</b>	22/03/2023

## IDENTIFICATION

### 1.1. Product identifier

3M™ Scotchcast™ Inline Resin Power Cable Splice Kits (82-AN, 82-A1N, 82-A2N, 82-A3N), with 3M™ Scotchcast™ Resin 4N

### 1.2. Recommended use and restrictions on use

#### Recommended use

Electrical

### 1.3. Supplier's details

**Address:** 3M Technologies (S) Pte Ltd, 10 Ang Mo Kio Street 65, Singapore 569059  
**Telephone:** +65 6450 8888  
**Website:** www.3m.com.sg

### 1.4. Emergency telephone number

**Company Emergency Hotline:** +65 6591 6601 (8.15am - 5.00pm, Monday - Friday)

**This product is a kit or a multipart product which consists of multiple, independently packaged components. An SDS for each of these components is included. Please do not separate the component SDSs from this cover page. The document numbers of the SDSs for components of this product are:**

24-9848-3, 35-7972-9

## TRANSPORT INFORMATION

### International Regulations

**UN No.:** UN3267

**UN Proper shipping name:** CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.

**Transportation Class (IMO):** 8-8 Corrosives

**Transportation Class (IATA):** 8-8 Corrosives

**Other Dangerous Goods Descriptions (IMO):** None assigned

**Other Dangerous Goods Descriptions (IATA):** None assigned

**Packing Group:** III

**Marine pollutant:** None assigned

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

**3M Singapore SDSs are available at [www.3m.com.sg](http://www.3m.com.sg)**



## Safety Data Sheet

Copyright,2024, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

This Safety Data Sheet has been prepared in accordance with the SS586 Specification for Hazard Communication for Hazardous Chemicals and Dangerous Goods.

<b>Document group:</b>	35-7972-9	<b>Version number:</b>	3.00
<b>Issue Date:</b>	27/08/2024	<b>Supersedes date:</b>	17/07/2024

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Scotchcast™ Electrical Insulating Resin 4N, Part B

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Electrical, Part B of Resin 4N

#### 1.3. Supplier's details

**Address:** 3M Technologies (S) Pte Ltd,10 Ang Mo Kio Street 65, Singapore 569059  
**Telephone:** +65 6450 8888  
**Website:** www.3m.com.sg

#### 1.4. Emergency telephone number

+65 6591 6601 (8.15am - 5.00pm, Monday - Friday)

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

Acute Toxicity (oral): Category 4.  
Acute Toxicity (dermal): Category 4.  
Skin Corrosion/Irritation: Category 1.  
Serious Eye Damage/Irritation: Category 1.  
Skin Sensitizer: Category 1.  
Carcinogenicity: Category 1B.  
Reproductive Toxicity: Category 2.  
Specific Target Organ Toxicity (repeated exposure): Category 1.  
Chronic Aquatic Toxicity: Category 2.

#### 2.2. Label elements

##### SIGNAL WORD

DANGER!

##### Symbols

Corrosion | Exclamation mark | Health Hazard | Environment |

**Pictograms**



**HAZARD STATEMENTS**

H302	Harmful if swallowed.
H302 + H312	Harmful if swallowed or in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H350	May cause cancer.
H361	Suspected of damaging fertility or the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure: respiratory system.
H411	Toxic to aquatic life with long lasting effects.

**PRECAUTIONARY STATEMENTS**

**Prevention:**

P201	Obtain special instructions before use.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280J	Wear protective gloves, protective clothing, respiratory protection, and eye/face protection.

**Response:**

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.
P310	Immediately call a POISON CENTER or doctor/physician.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P391	Collect spillage.

**2.3. Other hazards**

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines. - May cause chemical gastrointestinal burns.

**SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	CAS Nbr	% by Wt
Phenol, Styrenated	61788-44-1	25 - 70
N-AMINOETHYLPIPERAZINE	140-31-8	5 - 22
HEAVY NAPHTHENIC DISTILLATE SOLVENT PETROLEUM EXTRACTS	64742-11-6	5 - 20
Alkyl Acids, Reaction Products With Triethylenetetramine	Trade Secret	5 - 17
Alykl Acids, Reaction Products With TETA And DGEBA	Trade Secret	4 - 10
Reaction product of cycloaliphatic amine with aromatic epoxy resin	Trade Secret	1 - 8

PETROLEUM DISTILLATES	Trade Secret	1 - 7
Thermal cracked residuum (petroleum)	64741-80-6	1 - 7
2,4,6-Tris(dimethylaminomethyl)-phenol	90-72-2	1 - 5
Triethylenetetramine	112-24-3	<= 2
Bis[(dimethylamino)methyl]phenol	71074-89-0	<= 1
Carbon black	1333-86-4	< 1

## **SECTION 4: First aid measures**

### **4.1. Description of first aid measures**

#### **Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

#### **Skin contact**

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

#### **Eye contact**

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

#### **If swallowed**

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

### **4.2. Most important symptoms and effects, both acute and delayed**

Skin burns (localized redness, swelling, itching, intense pain, blistering, and tissue destruction). Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

### **4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

## **SECTION 5: Fire-fighting measures**

### **5.1. Suitable extinguishing media**

Use a fire fighting agent suitable for the surrounding fire.

### **5.2. Special hazards arising from the substance or mixture**

None inherent in this product.

### **Hazardous Decomposition or By-Products**

#### **Substance**

Amine compounds.  
Carbon monoxide.  
Carbon dioxide.  
Oxides of nitrogen.

#### **Condition**

During combustion.  
During combustion.  
During combustion.  
During combustion.

### **5.3. Special protective actions for fire-fighters**

No special protective actions for fire-fighters are anticipated.

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for

information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

Contain spill. For large spills, if necessary, get assistance from professional spill clean up team. For small spills, carefully neutralise spill by adding appropriate dilute acid such as vinegar. Work slowly to avoid boiling or spattering. Continue to add neutralising agent until reaction stops. Let cool before collecting. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (eg. gloves, respirators...) as required.

### 7.2. Conditions for safe storage including any incompatibilities

Store away from acids.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Triethylenetetramine	112-24-3	AIHA	TWA:6 mg/m <sup>3</sup> (1 ppm)	SKIN
Carbon black	1333-86-4	ACGIH	TWA(inhalable fraction):3 mg/m <sup>3</sup>	A3: Confirmed animal carcin.
Carbon black	1333-86-4	Singapore PELs	TWA(8 hours):3.5 mg/m <sup>3</sup>	
Oil mist mineral	64742-11-6	Singapore PELs	TWA(as mist)(8 hours):5 mg/m <sup>3</sup> ;STEL(as mist)(15 minutes):10 mg/m <sup>3</sup>	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

Singapore PELs : Singapore. Workplace Safety and Health (Permissible Exposure Levels of Toxic Substances) Order

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

## 8.2.2. Personal protective equipment (PPE)

### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl rubber.

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an Apron – Butyl rubber

### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Liquid.
<b>Specific Physical Form:</b>	Resin
<b>Color</b>	Black
<b>Odor</b>	Moderate Amine
<b>Odour threshold</b>	<i>No data available.</i>
<b>pH</b>	10 - 12
<b>Melting point/Freezing point</b>	<i>No data available.</i>
<b>Boiling point/Initial boiling point/Boiling range</b>	319.4 °C
<b>Flash point</b>	No flash point
<b>Evaporation rate</b>	<i>No data available.</i>
<b>Flammability</b>	Not applicable.
<b>Flammable Limits(LEL)</b>	<i>No data available.</i>
<b>Flammable Limits(UEL)</b>	<i>No data available.</i>
<b>Vapour pressure</b>	533.3 Pa
<b>Vapor Density and/or Relative Vapor Density</b>	<i>No data available.</i>
<b>Density</b>	1.03 g/ml
<b>Relative density</b>	1.03 [Ref Std:WATER=1]
<b>Water solubility</b>	660 ppm [@ 77 °F]

<b>Solubility- non-water</b>	<i>No data available.</i>
<b>Partition coefficient: n-octanol/water</b>	<i>No data available.</i>
<b>Autoignition temperature</b>	<i>No data available.</i>
<b>Decomposition temperature</b>	<i>No data available.</i>
<b>Kinematic Viscosity</b>	4,369 mm <sup>2</sup> /sec
<b>Volatile organic compounds (VOC)</b>	<i>No data available.</i>
<b>Percent volatile</b>	3 - 5 %
<b>VOC less H<sub>2</sub>O &amp; exempt solvents</b>	<i>No data available.</i>
<b>Average particle size</b>	<i>No data available.</i>
<b>Bulk density</b>	<i>No data available.</i>
<b>Molecular weight</b>	<i>Not applicable.</i>

<b>Particle Characteristics</b>	<i>Not applicable.</i>
---------------------------------	------------------------

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

### 10.2 Chemical stability

Stable.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.4 Conditions to avoid

None known.

### 10.5 Incompatible materials

Strong acids.

No data available.

### 10.6 Hazardous decomposition products

#### Substance

None known.

#### Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1 Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:



**Inhalation**

May be harmful if inhaled. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

**Skin contact**

Harmful in contact with skin. Corrosive (skin burns): Signs/symptoms may include localised redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

**Eye contact**

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

**Ingestion**

Harmful if swallowed.

Gastrointestinal corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain, nausea, vomiting, and diarrhea; blood in the faeces and/or vomitus may also be seen. May cause additional health effects (see below).

**Additional Health Effects:**

**Prolonged or repeated exposure may cause target organ effects:**

Respiratory effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and respiratory failure.

**Reproductive/Developmental Toxicity:**

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

**Carcinogenicity:**

Contains a chemical or chemicals which can cause cancer.

**Additional information:**

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >1,000 - =2,000 mg/kg
Overall product	Inhalation-Dust/Mist(4 hr)		No data available; calculated ATE >5 - =12.5 mg/l
Overall product	Ingestion		No data available; calculated ATE >300 - =2,000 mg/kg
Phenol, Styrenated	Dermal	Rat	LD50 > 2,000 mg/kg
Phenol, Styrenated	Ingestion	Rat	LD50 > 2,000 mg/kg
N-AMINOETHYLPIPERAZINE	Dermal	Rabbit	LD50 865 mg/kg
N-AMINOETHYLPIPERAZINE	Ingestion	Rat	LD50 1,470 mg/kg
Alkyl Acids, Reaction Products With Triethylenetetramine	Ingestion	Rat	LD50 > 2,000 mg/kg
HEAVY NAPHTHENIC DISTILLATE SOLVENT PETROLEUM EXTRACTS	Dermal	similar compounds	LD50 > 3,000 mg/kg
HEAVY NAPHTHENIC DISTILLATE SOLVENT PETROLEUM EXTRACTS	Inhalation-Dust/Mist (4 hours)	similar compounds	LC50 > 5 mg/l
HEAVY NAPHTHENIC DISTILLATE SOLVENT PETROLEUM EXTRACTS	Ingestion	similar compound	LD50 > 5,000 mg/kg

**3M™ Scotchcast™ Electrical Insulating Resin 4N, Part B**

Alkyl Acids, Reaction Products With Triethylenetetramine	Dermal	ds similar health hazards	LD50 estimated to be > 5,000 mg/kg
PETROLEUM DISTILLATES	Dermal	similar compounds	LD50 > 2,000 mg/kg
PETROLEUM DISTILLATES	Inhalation-Dust/Mist (4 hours)	similar compounds	LC50 4.1 mg/l
PETROLEUM DISTILLATES	Ingestion	similar compounds	LD50 4,320 mg/kg
Thermal cracked residuum (petroleum)	Dermal	similar compounds	LD50 > 2,000 mg/kg
Thermal cracked residuum (petroleum)	Inhalation-Dust/Mist (4 hours)	similar compounds	LC50 4.1 mg/l
Thermal cracked residuum (petroleum)	Ingestion	similar compounds	LD50 4,320 mg/kg
2,4,6-Tris(dimethylaminomethyl)-phenol	Dermal	Rat	LD50 1,280 mg/kg
2,4,6-Tris(dimethylaminomethyl)-phenol	Ingestion	Rat	LD50 1,000 mg/kg
Triethylenetetramine	Dermal	Rat	LD50 1,465 mg/kg
Triethylenetetramine	Ingestion	Rat	LD50 1,591 mg/kg
Bis[(dimethylamino)methyl]phenol	Ingestion		LD50 estimated to be 300 - 2,000 mg/kg
Carbon black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon black	Ingestion	Rat	LD50 > 8,000 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Phenol, Styrenated	Rabbit	No significant irritation
N-AMINOETHYLPIPERAZINE	Rabbit	Corrosive
Alkyl Acids, Reaction Products With Triethylenetetramine	In vitro data	No significant irritation
HEAVY NAPHTHENIC DISTILLATE SOLVENT PETROLEUM EXTRACTS	similar compounds	Mild irritant
PETROLEUM DISTILLATES	similar compounds	No significant irritation
Thermal cracked residuum (petroleum)	similar compounds	No significant irritation
2,4,6-Tris(dimethylaminomethyl)-phenol	Rabbit	Corrosive
Triethylenetetramine	Rabbit	Corrosive
Bis[(dimethylamino)methyl]phenol	similar compounds	Corrosive
Carbon black	Rabbit	No significant irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
Phenol, Styrenated	Rabbit	Mild irritant
N-AMINOETHYLPIPERAZINE	Rabbit	Corrosive
Alkyl Acids, Reaction Products With Triethylenetetramine	In vitro data	Severe irritant
HEAVY NAPHTHENIC DISTILLATE SOLVENT PETROLEUM EXTRACTS	similar compounds	No significant irritation
PETROLEUM DISTILLATES	similar	Mild irritant

**3M™ Scotchcast™ Electrical Insulating Resin 4N, Part B**

	compounds	
Thermal cracked residuum (petroleum)	similar compounds	Mild irritant
2,4,6-Tris(dimethylaminomethyl)-phenol	Rabbit	Corrosive
Triethylenetetramine	Rabbit	Corrosive
Bis[(dimethylamino)methyl]phenol	similar compounds	Corrosive
Carbon black	Rabbit	No significant irritation

**Sensitization:****Skin Sensitisation**

Name	Species	Value
Phenol, Styrenated	Mouse	Sensitising
N-AMINOETHYLPIPERAZINE	Guinea pig	Sensitising
Alkyl Acids, Reaction Products With Triethylenetetramine	Guinea pig	Sensitising
HEAVY NAPHTHENIC DISTILLATE SOLVENT PETROLEUM EXTRACTS	similar compounds	Not classified
PETROLEUM DISTILLATES	Guinea pig	Not classified
Thermal cracked residuum (petroleum)	similar compounds	Not classified
2,4,6-Tris(dimethylaminomethyl)-phenol	Guinea pig	Not classified
Triethylenetetramine	Guinea pig	Sensitising

**Respiratory Sensitisation**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
N-AMINOETHYLPIPERAZINE	In vivo	Not mutagenic
N-AMINOETHYLPIPERAZINE	In Vitro	Some positive data exist, but the data are not sufficient for classification
Alkyl Acids, Reaction Products With Triethylenetetramine	In Vitro	Not mutagenic
HEAVY NAPHTHENIC DISTILLATE SOLVENT PETROLEUM EXTRACTS	In Vitro	Some positive data exist, but the data are not sufficient for classification
HEAVY NAPHTHENIC DISTILLATE SOLVENT PETROLEUM EXTRACTS	In vivo	Some positive data exist, but the data are not sufficient for classification
PETROLEUM DISTILLATES	In Vitro	Some positive data exist, but the data are not sufficient for classification
Thermal cracked residuum (petroleum)	In Vitro	Some positive data exist, but the data are not sufficient for classification
2,4,6-Tris(dimethylaminomethyl)-phenol	In Vitro	Not mutagenic
Triethylenetetramine	In vivo	Not mutagenic
Triethylenetetramine	In Vitro	Some positive data exist, but the data are not sufficient for classification
Carbon black	In Vitro	Not mutagenic
Carbon black	In vivo	Some positive data exist, but the data are not sufficient for classification

**Carcinogenicity**

Name	Route	Species	Value
HEAVY NAPHTHENIC DISTILLATE SOLVENT PETROLEUM	Dermal	similar	Carcinogenic.

EXTRACTS		compounds	
PETROLEUM DISTILLATES	Dermal	similar compounds	Carcinogenic.
Thermal cracked residuum (petroleum)	Dermal	similar compounds	Carcinogenic.
Triethylenetetramine	Dermal	Mouse	Not carcinogenic
Carbon black	Dermal	Mouse	Not carcinogenic
Carbon black	Ingestion	Mouse	Not carcinogenic
Carbon black	Inhalation	Rat	Carcinogenic.

**Reproductive Toxicity**

**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
N-AMINOETHYLPIPERAZINE	Ingestion	Not classified for female reproduction	Rat	NOAEL 598 mg/kg/day	prematuring & during gestation
N-AMINOETHYLPIPERAZINE	Ingestion	Not classified for male reproduction	Rat	NOAEL 409 mg/kg/day	32 days
N-AMINOETHYLPIPERAZINE	Ingestion	Toxic to development	Rabbit	NOAEL 75 mg/kg/day	during gestation
HEAVY NAPHTHENIC DISTILLATE SOLVENT PETROLEUM EXTRACTS	Ingestion	Not classified for male reproduction	similar compounds	NOAEL 125 mg/kg/day	13 weeks
HEAVY NAPHTHENIC DISTILLATE SOLVENT PETROLEUM EXTRACTS	Dermal	Toxic to development	similar compounds	NOAEL 5 mg/kg/day	during gestation
PETROLEUM DISTILLATES	Dermal	Toxic to development	similar compounds	NOAEL 0.05 mg/kg/day	during gestation
Thermal cracked residuum (petroleum)	Dermal	Toxic to development	similar compounds	NOAEL 0.05 mg/kg/day	during gestation
2,4,6-Tris(dimethylaminomethyl)-phenol	Ingestion	Not classified for male reproduction	Rat	NOAEL 150 mg/kg/day	2 generation
2,4,6-Tris(dimethylaminomethyl)-phenol	Ingestion	Not classified for female reproduction	Rat	NOAEL 50 mg/kg/day	2 generation
2,4,6-Tris(dimethylaminomethyl)-phenol	Ingestion	Not classified for development	Rabbit	NOAEL 15 mg/kg/day	during gestation
Triethylenetetramine	Dermal	Not classified for development	Rabbit	NOAEL 125 mg/kg/day	during organogenesis
Triethylenetetramine	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	during organogenesis

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
N-AMINOETHYLPIPERAZINE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Alkyl Acids, Reaction Products With Triethylenetetramine	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
HEAVY NAPHTHENIC DISTILLATE SOLVENT PETROLEUM EXTRACTS	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL not available	
2,4,6-Tris(dimethylaminomethyl)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for	similar health	NOAEL Not available	

-phenol			classification	hazards		
Triethylenetetramine	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
N-AMINOETHYLPIPERAZINE	Dermal	skin	Not classified	Rat	NOAEL 100 mg/kg/day	29 days
N-AMINOETHYLPIPERAZINE	Dermal	hematopoietic system   nervous system   kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	29 days
N-AMINOETHYLPIPERAZINE	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 0.2 mg/m <sup>3</sup>	13 weeks
N-AMINOETHYLPIPERAZINE	Inhalation	hematopoietic system   eyes   kidney and/or bladder	Not classified	Rat	NOAEL 53.8 mg/m <sup>3</sup>	13 weeks
N-AMINOETHYLPIPERAZINE	Ingestion	heart   endocrine system   hematopoietic system   liver   nervous system   kidney and/or bladder	Not classified	Rat	NOAEL 598 mg/kg/day	28 days
HEAVY NAPHTHENIC DISTILLATE SOLVENT PETROLEUM EXTRACTS	Dermal	endocrine system   gastrointestinal tract   hematopoietic system   liver   immune system   kidney and/or bladder	May cause damage to organs though prolonged or repeated exposure	similar compounds	LOAEL 30 mg/kg/day	90 days
PETROLEUM DISTILLATES	Dermal	hematopoietic system	Causes damage to organs through prolonged or repeated exposure	similar compounds	NOAEL 1.06 mg/kg/day	13 weeks
PETROLEUM DISTILLATES	Dermal	liver   immune system	May cause damage to organs though prolonged or repeated exposure	similar compounds	NOAEL 10.6 mg/kg/day	13 weeks
Thermal cracked residuum (petroleum)	Dermal	hematopoietic system	Causes damage to organs through prolonged or repeated exposure	similar compounds	NOAEL 1.06 mg/kg/day	13 weeks
Thermal cracked residuum (petroleum)	Dermal	liver   immune system	May cause damage to organs though prolonged or repeated exposure	similar compounds	NOAEL 10.6 mg/kg/day	13 weeks
2,4,6-Tris(dimethylaminomethyl)-phenol	Dermal	skin	Not classified	Rat	NOAEL 25 mg/kg/day	4 weeks
2,4,6-Tris(dimethylaminomethyl)-phenol	Dermal	liver   nervous system   auditory system   hematopoietic system   eyes	Not classified	Rat	NOAEL 125 mg/kg/day	4 weeks
2,4,6-Tris(dimethylaminomethyl)-phenol	Ingestion	heart   endocrine system   hematopoietic system   liver   muscles   nervous system   kidney and/or bladder   respiratory system   vascular system   auditory system   skin   gastrointestinal tract	Not classified	Rat	NOAEL 150 mg/kg/day	90 days

		bone, teeth, nails, and/or hair   immune system   eyes				
Carbon black	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure

**Aspiration Hazard**

Name	Value
PETROLEUM DISTILLATES	Aspiration hazard
Thermal cracked residuum (petroleum)	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

**12.1. Toxicity**

**Acute aquatic hazard:**

GHS Acute 2: Toxic to aquatic life.

**Chronic aquatic hazard:**

GHS Chronic 2: Toxic to aquatic life with long lasting effects.

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
Phenol, Styrenated	61788-44-1	Green algae	Experimental	72 hours	ErC50	1.35 mg/l
Phenol, Styrenated	61788-44-1	Medaka	Experimental	96 hours	LC50	5.6 mg/l
Phenol, Styrenated	61788-44-1	Water flea	Experimental	48 hours	EC50	4.6 mg/l
Phenol, Styrenated	61788-44-1	Zebra Fish	Analogous Compound	63 days	NOEC	0.0618 mg/l
Phenol, Styrenated	61788-44-1	Green algae	Experimental	72 hours	NOEC	0.42 mg/l
Phenol, Styrenated	61788-44-1	Water flea	Experimental	21 days	NOEC	0.2 mg/l
Phenol, Styrenated	61788-44-1	Activated sludge	Experimental	3 hours	EC50	362 mg/l
N-AMINOETHYLPIPERAZINE	140-31-8	Bacteria	Experimental	17 hours	EC10	100 mg/l
N-AMINOETHYLPIPERAZINE	140-31-8	Golden Orfe	Experimental	96 hours	LC50	368 mg/l
N-AMINOETHYLPIPERAZINE	140-31-8	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
N-AMINOETHYLPIPERAZINE	140-31-8	Water flea	Experimental	48 hours	EC50	58 mg/l
N-AMINOETHYLPIPERAZINE	140-31-8	Green algae	Experimental	72 hours	NOEC	31 mg/l
HEAVY NAPHTHENIC DISTILLATE SOLVENT	64742-11-6	Green algae	Analogous Compound	72 hours	EbC50	3.1 mg/l

**3M™ Scotchcast™ Electrical Insulating Resin 4N, Part B**

PETROLEUM EXTRACTS						
HEAVY NAPHTHENIC DISTILLATE SOLVENT PETROLEUM EXTRACTS	64742-11-6	Water flea	Analogous Compound	48 hours	EC50	1.4 mg/l
Alkyl Acids, Reaction Products With Triethylenetetramine	Trade Secret	Green algae	Experimental	72 hours	EC50	24 mg/l
Alkyl Acids, Reaction Products With Triethylenetetramine	Trade Secret	Water flea	Experimental	48 hours	EC50	31 mg/l
Alkyl Acids, Reaction Products With Triethylenetetramine	Trade Secret	Green algae	Experimental	72 hours	EC10	1.5 mg/l
Alkyl Acids, Reaction Products With TETA And DGEBA	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Reaction product of cycloaliphatic amine with aromatic epoxy resin	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
PETROLEUM DISTILLATES	Trade Secret	Green algae	Estimated	72 hours	EL50	0.32 mg/l
PETROLEUM DISTILLATES	Trade Secret	Rainbow trout	Estimated	96 hours	LL50	79 mg/l
PETROLEUM DISTILLATES	Trade Secret	Water flea	Estimated	48 hours	EL50	0.22 mg/l
PETROLEUM DISTILLATES	Trade Secret	Green algae	Estimated	72 hours	NOEL	0.05 mg/l
Thermal cracked residuum (petroleum)	64741-80-6	Green algae	Estimated	72 hours	EL50	0.32 mg/l
Thermal cracked residuum (petroleum)	64741-80-6	Rainbow trout	Estimated	96 hours	LL50	79 mg/l
Thermal cracked residuum (petroleum)	64741-80-6	Water flea	Estimated	48 hours	EL50	0.22 mg/l
Thermal cracked residuum (petroleum)	64741-80-6	Green algae	Estimated	72 hours	NOEL	0.05 mg/l
2,4,6-Tris(dimethylaminoethyl)-phenol	90-72-2	N/A	Experimental	96 hours	LC50	718 mg/l
2,4,6-Tris(dimethylaminoethyl)-phenol	90-72-2	Common Carp	Experimental	96 hours	LC50	>100 mg/l
2,4,6-Tris(dimethylaminoethyl)-phenol	90-72-2	Green algae	Experimental	72 hours	EC50	46.7 mg/l
2,4,6-Tris(dimethylaminoethyl)-phenol	90-72-2	Water flea	Experimental	48 hours	EC50	>100 mg/l
2,4,6-Tris(dimethylaminoethyl)-phenol	90-72-2	Green algae	Experimental	72 hours	NOEC	6.44 mg/l
Triethylenetetramine	112-24-3	Green algae	Experimental	72 hours	EC50	27.4 mg/l

**3M™ Scotchcast™ Electrical Insulating Resin 4N, Part B**

Triethylenetetramine	112-24-3	Guppy	Experimental	96 hours	LC50	570 mg/l
Triethylenetetramine	112-24-3	Water flea	Experimental	48 hours	EC50	37.4 mg/l
Triethylenetetramine	112-24-3	Green algae	Experimental	72 hours	NOEC	0.468 mg/l
Triethylenetetramine	112-24-3	Water flea	Experimental	21 days	NOEC	2.86 mg/l
Bis[(dimethylamino)methyl]phenol	71074-89-0	N/A	Data not available or insufficient for classification	N/A	N/A	NA
Carbon black	1333-86-4	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	>100 mg/l
Carbon black	1333-86-4	Zebra Fish	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
Carbon black	1333-86-4	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	100 mg/l
Carbon black	1333-86-4	Activated sludge	Experimental	3 hours	NOEC	>800 mg/l

**12.2. Persistence and degradability**

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Phenol, Styrenated	61788-44-1	Experimental Biodegradation	28 days	BOD	7 %BOD/ThOD	OECD 301F - Manometric respirometry
Phenol, Styrenated	61788-44-1	Analogous Compound Biodegradation		Half-life (t 1/2)	34.9 days (t 1/2)	
Phenol, Styrenated	61788-44-1	Analogous Compound Soil Metabolism Aerobic		Half-life (t 1/2)	12.5 days (t 1/2)	
N-AMINOETHYLPIPERAZINE	140-31-8	Experimental Biodegradation	28 days	BOD	0 %BOD/ThOD	OECD 301C - MITI test (I)
HEAVY NAPHTHENIC DISTILLATE SOLVENT PETROLEUM EXTRACTS	64742-11-6	Analogous Compound Biodegradation	28 days	BOD	0 %BOD/ThOD	
Alkyl Acids, Reaction Products With Triethylenetetramine	Trade Secret	Experimental Biodegradation	28 days	CO2 evolution	6 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
Alkyl Acids, Reaction Products With TETA And DGEBA	Trade Secret	Modeled Biodegradation	28 days	BOD	35 %BOD/ThOD	Catalogic™
Reaction product of cycloaliphatic amine with aromatic epoxy resin	Trade Secret	Data not available-insufficient	N/A	N/A	N/A	N/A
PETROLEUM DISTILLATES	Trade Secret	Data not available-insufficient	N/A	N/A	N/A	N/A
Thermal cracked residuum (petroleum)	64741-80-6	Data not available-insufficient	N/A	N/A	N/A	N/A
2,4,6-Tris(dimethylamino)	90-72-2	Experimental Biodegradation	28 days	BOD	4 %BOD/ThOD	OECD 301D - Closed bottle test



**3M™ Scotchcast™ Electrical Insulating Resin 4N, Part B**

omethyl)-phenol						
Triethylenetetramine	112-24-3	Experimental Biodegradation	20 days	BOD	0 %BOD/ThOD	OECD 301D - Closed bottle test
Bis[(dimethylamino)methyl]phenol	71074-89-0	Modeled Biodegradation	28 days	BOD	41 %CO2 evolution/THCO2 evolution	Catalogic™
Carbon black	1333-86-4	Data not available-insufficient	N/A	N/A	N/A	N/A

**12.3 : Bioaccumulative potential**

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Phenol, Styrenated	61788-44-1	Experimental BCF - Fish	10 days	Bioaccumulation factor	10395	
Phenol, Styrenated	61788-44-1	Experimental Bioconcentration		Log Kow	>4	
N-AMINOETHYLPIPERAZINE	140-31-8	Experimental Bioconcentration		Log Kow	0.3	
HEAVY NAPHTHENIC DISTILLATE SOLVENT PETROLEUM EXTRACTS	64742-11-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Alkyl Acids, Reaction Products With Triethylenetetramine	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Alkyl Acids, Reaction Products With TETA And DGEBA	Trade Secret	Modeled Bioconcentration		Bioaccumulation factor	7.4	Catalogic™
Reaction product of cycloaliphatic amine with aromatic epoxy resin	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
PETROLEUM DISTILLATES	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Thermal cracked residuum (petroleum)	64741-80-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
2,4,6-Tris(dimethylamino)methyl)-phenol	90-72-2	Experimental Bioconcentration		Log Kow	-0.66	830.7550 Part.Coef Shake Flask
Triethylenetetramine	112-24-3	Experimental BCF - Fish	42 days	Bioaccumulation factor	<5.0	OECD305-Bioconcentration
Bis[(dimethylamino)methyl]phenol	71074-89-0	Modeled Bioconcentration		Log Kow	-2.34	ACD/Labs ChemSketch™
Carbon black	1333-86-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

**12.4. Mobility in soil**

Please contact manufacturer for more details

**12.5 Other adverse effects**

No information available.

**SECTION 13: Disposal considerations**

### **13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

## **SECTION 14: Transport Information**

### **International Regulations**

**UN No.:** UN3267

**UN Proper shipping name:** CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.

**Transportation Class (IMO):** 8-8 Corrosives

**Transportation Class (IATA):** 8-8 Corrosives

**Other Dangerous Goods Descriptions (IMO):** None assigned

**Other Dangerous Goods Descriptions (IATA):** None assigned

**Packing Group:** III

**Marine pollutant:** None assigned

## **SECTION 15: Regulatory information**

### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

#### **Global inventory status**

Contact 3M for more information. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

#### **This product may contain component(s) that are regulated by the following:**

Workplace Safety and Health Act & Workplace Safety and Health (General Provisions) Regulations: this product is subject to SDS, labelling, PEL and other requirements in the Act/Regulations.

Environmental Protection and Management (Hazardous Substances) Regulations: This product is subject to the requirements in the Regulations

## **SECTION 16: Other information**

**DISCLAIMER:** The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

**3M Singapore SDSs are available at [www.3m.com.sg](http://www.3m.com.sg)**



## Safety Data Sheet

Copyright,2024, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

This Safety Data Sheet has been prepared in accordance with the SS586 Specification for Hazard Communication for Hazardous Chemicals and Dangerous Goods.

<b>Document group:</b>	24-9848-3	<b>Version number:</b>	4.00
<b>Issue Date:</b>	30/08/2024	<b>Supersedes date:</b>	19/03/2024

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Scotchcast™ Electrical Insulating Resin 4N, Part A and 3M™ Scotchcast™ Electrical Insulating Resin 4, Part A

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Electrical, Part A of Resin 4 & Resin 4N

#### 1.3. Supplier's details

**Address:** 3M Technologies (S) Pte Ltd,10 Ang Mo Kio Street 65, Singapore 569059  
**Telephone:** +65 6450 8888  
**Website:** www.3m.com.sg

#### 1.4. Emergency telephone number

+65 6591 6601 (8.15am - 5.00pm, Monday - Friday)

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 2.

Skin Sensitizer: Category 1.

Chronic Aquatic Toxicity: Category 2.

#### 2.2. Label elements

##### SIGNAL WORD

WARNING!

##### Symbols

Exclamation mark | Environment |

##### Pictograms



**HAZARD STATEMENTS**

H319 Causes serious eye irritation.  
 H317 May cause an allergic skin reaction.  
 H411 Toxic to aquatic life with long lasting effects.

**PRECAUTIONARY STATEMENTS**

**Prevention:**

P273 Avoid release to the environment.  
 P280E Wear protective gloves.

**Response:**

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.  
 P391 Collect spillage.

**2.3. Other hazards**

None known.

**SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	CAS Nbr	% by Wt
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	25085-99-8	80 - 100
Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives	68609-97-2	0 - 20

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin contact**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye contact**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

**If swallowed**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

Allergic skin reaction (redness, swelling, blistering, and itching).

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.
Toxic vapour, gas, particulate.	During combustion.

### 5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this Safety Data Sheet.

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an Apron - polymer laminate

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Liquid.
<b>Specific Physical Form:</b>	Resin
<b>Color</b>	Amber
<b>Odor</b>	Mild Epoxy
<b>Odour threshold</b>	<i>No data available.</i>
<b>pH</b>	<i>No data available.</i>
<b>Melting point/Freezing point</b>	<i>No data available.</i>
<b>Boiling point/Initial boiling point/Boiling range</b>	$\geq 93.9$ °C
<b>Flash point</b>	$\geq 93.9$ °C [Test Method: Closed Cup]
<b>Evaporation rate</b>	<i>No data available.</i>
<b>Flammability</b>	Not applicable.
<b>Flammable Limits(LEL)</b>	<i>No data available.</i>
<b>Flammable Limits(UEL)</b>	<i>No data available.</i>
<b>Vapour pressure</b>	$\leq 186,158.4$ Pa [ @ 55 °C ]

<b>Vapor Density and/or Relative Vapor Density</b>	<i>No data available.</i>
<b>Density</b>	1.16 g/ml
<b>Relative density</b>	1.16 [Ref Std: WATER=1]
<b>Water solubility</b>	Negligible
<b>Solubility- non-water</b>	<i>No data available.</i>
<b>Partition coefficient: n-octanol/water</b>	<i>No data available.</i>
<b>Autoignition temperature</b>	<i>No data available.</i>
<b>Decomposition temperature</b>	<i>No data available.</i>
<b>Kinematic Viscosity</b>	3,879 mm <sup>2</sup> /sec
<b>Volatile organic compounds (VOC)</b>	<i>No data available.</i>
<b>Percent volatile as Text</b>	Negligible
<b>VOC less H<sub>2</sub>O &amp; exempt solvents</b>	<i>No data available.</i>
<b>Average particle size</b>	<i>No data available.</i>
<b>Bulk density</b>	<i>No data available.</i>
<b>Molecular weight</b>	<i>No data available.</i>
<b>Softening point</b>	<i>No data available.</i>

<b>Particle Characteristics</b>	<i>Not applicable.</i>
---------------------------------	------------------------

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material is considered to be non reactive under normal use conditions

### 10.2 Chemical stability

Stable.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.4 Conditions to avoid

None known.

### 10.5 Incompatible materials

None known.

### 10.6 Hazardous decomposition products

#### Substance

None known.

#### Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1 Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

#### Skin contact

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eye contact

Moderate eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

#### Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	Dermal	Rat	LD50 > 1,600 mg/kg
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	Ingestion	Rat	LD50 > 1,000 mg/kg
Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives	Dermal	Rabbit	LD50 > 4,000 mg/kg
Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives	Ingestion	Rat	LD50 > 2,000 mg/kg

ATE = acute toxicity estimate

#### Skin Corrosion/Irritation

Name	Species	Value
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	Rabbit	Mild irritant
Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives	Rabbit	Mild irritant

#### Serious Eye Damage/Irritation

Name	Species	Value
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	Rabbit	Moderate irritant
Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives	Rabbit	No significant irritation

#### Sensitization:

##### Skin Sensitisation

Name	Species	Value
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	Human and animal	Sensitising
Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives	Guinea pig	Sensitising

##### Respiratory Sensitisation

Name	Species	Value
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	Human	Not classified



### Germ Cell Mutagenicity

Name	Route	Value
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	In vivo	Not mutagenic
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	In Vitro	Some positive data exist, but the data are not sufficient for classification
Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives	In vivo	Not mutagenic
Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives	In Vitro	Some positive data exist, but the data are not sufficient for classification

### Carcinogenicity

Name	Route	Species	Value
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification

### Reproductive Toxicity

#### Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives	Ingestion	Not classified for male reproduction	Rat	NOAEL 150 mg/kg/day	2 generation
Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives	Dermal	Not classified for development	Rat	NOAEL 200 mg/kg/day	during organogenesis
Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives	Ingestion	Not classified for development	Rabbit	NOAEL 375 mg/kg/day	during gestation
Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives	Ingestion	Toxic to female reproduction	Rat	NOAEL 10 mg/kg/day	2 generation

### Target Organ(s)

#### Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

#### Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	Ingestion	auditory system   heart   endocrine system   hematopoietic system   liver   eyes   kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Oxirane, mono[(C12-14-alkyloxy)methyl]	Dermal	nervous system   respiratory system	Not classified	Rat	NOAEL 100 mg/kg/day	14 weeks

derivatives						
Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives	Dermal	blood   liver   eyes   kidney and/or bladder	Not classified	Rat	NOAEL 100 mg/kg/day	13 weeks
Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives	Ingestion	immune system	Not classified	Rat	NOAEL 750 mg/kg/day	13 weeks
Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives	Ingestion	gastrointestinal tract	Not classified	Rat	NOAEL 100 mg/kg/day	13 weeks
Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives	Ingestion	hematopoietic system   nervous system   eyes	Not classified	Rat	NOAEL 750 mg/kg/day	13 weeks

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.**

**SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

**12.1. Toxicity**

**Acute aquatic hazard:**

GHS Acute 2: Toxic to aquatic life.

**Chronic aquatic hazard:**

GHS Chronic 2: Toxic to aquatic life with long lasting effects.

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	25085-99-8	Green algae	Estimated	72 hours	EC50	>11 mg/l
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	25085-99-8	Rainbow trout	Estimated	96 hours	LC50	2 mg/l
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	25085-99-8	Water flea	Estimated	48 hours	EC50	1.8 mg/l
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	25085-99-8	Green algae	Estimated	72 hours	NOEC	4.2 mg/l
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	25085-99-8	Water flea	Estimated	21 days	NOEC	0.3 mg/l
Oxirane, mono[(C12-14-alkyloxy)methyl]	68609-97-2	Green algae	Experimental	72 hours	IC50	843.75 mg/l

derivatives						
Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives	68609-97-2	Rainbow trout	Experimental	96 hours	LC50	>5,000 mg/l
Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives	68609-97-2	Water flea	Experimental	48 hours	EC50	7.2 mg/l
Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives	68609-97-2	Green algae	Experimental	72 hours	NOEC	500 mg/l

## 12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	25085-99-8	Estimated Biodegradation	28 days	BOD	5 %BOD/COD	OECD 301F - Manometric respirometry
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	25085-99-8	Estimated Hydrolysis		Hydrolytic half-life	4.9 days (t 1/2)	
Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives	68609-97-2	Experimental Biodegradation	28 days	BOD	34.7 % weight	OECD 301D - Closed bottle test

## 12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	25085-99-8	Estimated Bioconcentration		Log Kow	3.242	
Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives	68609-97-2	Experimental Bioconcentration		Log Kow	3.77	

## 12.4. Mobility in soil

Please contact manufacturer for more details

## 12.5 Other adverse effects

No information available.

# SECTION 13: Disposal considerations

## 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the

available treatment and disposal facilities.

## SECTION 14: Transport Information

### International Regulations

**UN No.:** None assigned

**UN Proper shipping name:** None assigned

**Transportation Class (IMO):** None assigned

**Transportation Class (IATA):** None assigned

**Other Dangerous Goods Descriptions (IMO):** Not restricted, as per IMDG code 2.10.2.7, marine pollutant exception.

**Other Dangerous Goods Descriptions (IATA):** Not restricted, as per Special Provision A197, environmentally hazardous substance exception.

**Packing Group:** None assigned

**Marine pollutant:** None assigned

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

#### This product may contain component(s) that are regulated by the following:

Workplace Safety and Health Act & Workplace Safety and Health (General Provisions) Regulations: this product is subject to SDS, labelling, PEL and other requirements in the Act/Regulations.

## SECTION 16: Other information

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M Singapore SDSs are available at [www.3m.com.sg](http://www.3m.com.sg)