

Safety Data Sheet

Copyright,2023, 3M Company.All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	28-8088-8	Version number:	4.01
Issue Date:	28/04/2023	Supersedes date:	17/02/2020

This Safety Data Sheet has been prepared in accordance with the South African National Standard SANS 10234:2008.

IDENTIFICATION

1.1. Product identifier

3M[™] Scotch-Weld[™] Acrylic Structural Adhesive DP-8005 Kit

Product Identification Numbers FS-9100-4048-4

1.2. Recommended use and restrictions on use

Structural adhesive.

1.3. Supplier's details

Address:	3M South Africa (Pty) Ltd, Private Bag X926, Rivonia 2128
Telephone:	011 806 2000
E Mail:	Not available.
Website:	www.3m.co.za

1.4. Emergency telephone number

011 806 2000

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the MSDSs for components of this product are:

28-8077-1, 28-8085-4

TRANSPORT INFORMATION

Compliance is required to South African Transport Information Road Traffic Act & Regulations and Railroad regulations, IATA Standards for airfreight and Maritime standards for ocean freight.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M South Africa SDSs are available at www.3m.co.za



Safety Data Sheet

Copyright,2020, 3M Company.All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	28-8085-4	Version number:	2.00
Issue Date:	17/02/2020	Supersedes date:	11/04/2018

This Safety Data Sheet has been prepared in accordance with the South African National Standard SANS 10234:2008.

SECTION 1: Identification

1.1. Product identifier

3MTM Scotch-WeldTM Acrylic Structural Adhesive DP-8005 (Part A)

1.2. Recommended use and restrictions on use

Recommended use

Part A of 2-Part Structural Adhesive, Structural adhesive.

1.3. Supplier's details

Address:	3M South Africa (Pty) Ltd, Private Bag X926, Rivonia 2128
Telephone:	011 806 2000
E Mail:	Not available.
Website:	www.3m.co.za

1.4. Emergency telephone number 011 806 2000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Acute Toxicity (oral): Category 4. Serious Eye Damage/Irritation: Category 1. Skin Corrosion/Irritation: Category 3. Respiratory Sensitizer: Category 1. Skin Sensitizer: Category 1. Carcinogenicity: Category 2. Germ Cell Mutagenicity: Category 2.

2.2. Label elements

Signal word DANGER!

Symbols Corrosion | Exclamation mark | Health Hazard |

Pictograms



HAZARD STATEMENTS:

H318 Causes serious eye damage.
Causes serious eye uallage.
H316 Causes mild skin irritation.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H341 Suspected of causing genetic defects.

PRECAUTIONARY STATEMENTS

Prevention: P261 P284A P280B P280E	Avoid breathing dust/fume/gas/mist/vapours/spray. In case of inadequate ventilation wear respiratory protection. Wear protective gloves and eye/face protection. Wear protective gloves.
Response:	
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P342 + P311	If experiencing respiratory symptoms: Call a POISON CENTER or
	doctor/physician.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact
	lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Wt
Polyester Plasticiser	Trade Secret	30 - 60
2-ethyl-2-[[3-(2-methylaziridin-1-	64265-57-2	15 - 40
yl)propionyl]methyl]propane-1,3-diyl bis(2- methylaziridine-1-propionate)		
Boron, hexamethyl [.mu(1,6- hexanediaminekappa. N1:.kappa. N6)]di-	223674-50-8	< 20
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	0.5 - 1.5
Titanium dioxide	13463-67-7	0.1 - 1

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Aldehydes.	During combustion.
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.
Irritant vapours or gases.	During combustion.
Oxides of nitrogen.	During combustion.

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not

remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not use in a confined area with minimal air exchange. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidising agents. Store away from amines.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Titanium dioxide	13463-67-7	ACGIH	TWA:10 mg/m ³	A4: Not class. as human
				carcin
Titanium dioxide	13463-67-7	South Africa	TWA(as respirable dust)(8	
		RELs	hours):5 mg/m3;TWA(Total	
			inhalable dust)(8 hours):10	
			mg/m3	
Silicon dioxide	67762-90-7	South Africa	TWA(as respirable dust)(8	
		RELs	hours):3 mg/m3;TWA(Total	
			inhalable dust)(8 hours):6	
			mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

South Africa CLs : South Africa. Control Limits. Regulations for Hazardous Chemical Substances, Table 1

South Africa RELs : South Africa. Recommended Exposure Limits (RELs) Regulations for Hazardous Chemical Substances, Table 2

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Provide appropriate local exhaust ventilation for cutting, grinding, sanding or machining. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Full face shield. Indirect vented goggles.

Indirect vented goggles.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

In case of inadequate ventilation wear respiratory protection. An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure: Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Paste
Colour	White
Odor	Mild Odor
Odour threshold	No data available.
рН	Not applicable.
Melting point/Freezing point	No data available.
Boiling point/Initial boiling point/Boiling range	>=181 °C [Details:758 mmHg]
Flash point	>=93,3 °C [<i>Test Method</i> :Closed Cup]
Evaporation rate	Not applicable.
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	Not applicable.
Flammable Limits(UEL)	Not applicable.
Vapour pressure	No data available.
Vapour density	No data available.
Density	1,05 - 1,09 g/ml
Relative density	1,05 - 1,09 [<i>Ref Std</i> :WATER=1]
Water solubility	Slight (less than 10%)
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Autoignition temperature	No data available.
Decomposition temperature	No data available.

Viscosity Volatile organic compounds (VOC) VOC less H2O & exempt solvents 35 - 65 Pa-s [@ 23 °C] 65 g/l [*Test Method*:EPA method 24A] 65 g/l [*Test Method*:EPA method 24A]

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid Heat.

10.5 Incompatible materials

Strong acids. Strong bases. Strong oxidising agents. Amines.

10.6 Hazardous decomposition products

<u>Substance</u>

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic respiratory reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest. May cause additional health effects (see below).

Skin contact

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision. Vapours released during curing may cause eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion

Harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Additional Health Effects:

Genotoxicity:

Genotoxicity and Mutagenicity: May interact with genetic material and possibly alter gene expression.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE300 - 2 000 mg/kg
2-ethyl-2-[[3-(2-methylaziridin-1-yl)propionyl]methyl]propane- 1,3-diyl bis(2-methylaziridine-1-propionate)	Dermal	Rabbit	LD50 > 3 000 mg/kg
2-ethyl-2-[[3-(2-methylaziridin-1-yl)propionyl]methyl]propane- 1,3-diyl bis(2-methylaziridine-1-propionate)	Inhalation- Dust/Mist (4 hours)	Rat	LC50 0,252 mg/l
2-ethyl-2-[[3-(2-methylaziridin-1-yl)propionyl]methyl]propane- 1,3-diyl bis(2-methylaziridine-1-propionate)	Ingestion	Rat	LD50 3 038 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Dermal	Rabbit	LD50 > 5 000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0,691 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Rat	LD50 > 5 110 mg/kg
Titanium dioxide	Dermal	Rabbit	LD50 > 10 000 mg/kg
Titanium dioxide	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 6,82 mg/l
Titanium dioxide	Ingestion	Rat	LD50 > 10 000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
2-ethyl-2-[[3-(2-methylaziridin-1-yl)propionyl]methyl]propane-1,3-diyl bis(2-methylaziridine-1-propionate)	Rabbit	Mild irritant
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
2-ethyl-2-[[3-(2-methylaziridin-1-yl)propionyl]methyl]propane-1,3-diyl bis(2-methylaziridine-1-propionate)	Rabbit	Corrosive
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation

Skin Sensitisation

Name	Species	Value
2-ethyl-2-[[3-(2-methylaziridin-1-yl)propionyl]methyl]propane-1,3-diyl bis(2-	Human	Sensitising
methylaziridine-1-propionate)	and animal	
Siloxanes and Silicones, di-Me, reaction products with silica	Human and	Not classified
	animal	
Titanium dioxide	Human	Not classified
	and	
	animal	

Respiratory Sensitisation

Name	Species	Value
2-ethyl-2-[[3-(2-methylaziridin-1-yl)propionyl]methyl]propane-1,3-diyl bis(2-methylaziridine-1-propionate)	Human	Sensitising

Germ Cell Mutagenicity

Name	Route	Value
2-ethyl-2-[[3-(2-methylaziridin-1-yl)propionyl]methyl]propane-1,3-diyl bis(2-methylaziridine-1-propionate)	In vivo	Mutagenic
Siloxanes and Silicones, di-Me, reaction products with silica	In Vitro	Not mutagenic
Titanium dioxide	In Vitro	Not mutagenic
Titanium dioxide	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Siloxanes and Silicones, di-Me, reaction products with silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Titanium dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium dioxide	Inhalation	Rat	Carcinogenic.

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for development	Rat	NOAEL 1 350 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
2-ethyl-2-[[3-(2- methylaziridin-1- yl)propionyl]methyl]propa ne-1,3-diyl bis(2- methylaziridine-1- propionate)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	4 hours

Specific Target Organ Toxicity - repeated exposure

	Name	Route	Target Organ(s)	Value	Species	Test result	Exposure
--	------	-------	-----------------	-------	---------	-------------	----------

						Duration
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Titanium dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0,01 mg/l	2 years
Titanium dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

Not acutely toxic to aquatic life by GHS criteria.

Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available.

Material	CAS Nbr	Organism	Туре	Exposure	Test endpoint	Test result
2-ethyl-2-[[3- (2- methylaziridin- 1- yl)propionyl]m ethyl]propane- 1,3-diyl bis(2- methylaziridine -1-propionate)	64265-57-2		Data not available or insufficient for classification			
Boron, hexamethyl [.mu(1,6- hexanediamine kappa. N1:.kappa. N6)]di-	223674-50-8		Data not available or insufficient for classification			
Siloxanes and Silicones, di- Me, reaction products with silica	67762-90-7		Data not available or insufficient for classification			
Titanium	13463-67-7	Diatom	Experimental	72 hours	EC50	>10 000 mg/l

dioxide						
Titanium	13463-67-7	Fathead	Experimental	96 hours	LC50	>100 mg/l
dioxide		minnow				
Titanium	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
dioxide						
Titanium	13463-67-7	Diatom	Experimental	72 hours	NOEC	5 600 mg/l
dioxide						

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
2-ethyl-2-[[3-	64265-57-2	Data not			N/A	
(2-		availbl-				
methylaziridin-		insufficient				
1-						
yl)propionyl]m						
ethyl]propane-						
1,3-diyl bis(2-						
methylaziridine						
-1-propionate)						
Boron,	223674-50-8	Data not			N/A	
hexamethyl		availbl-				
[.mu(1,6-		insufficient				
hexanediamine						
kappa.						
N1:.kappa.						
N6)]di-						
Siloxanes and	67762-90-7	Data not			N/A	
Silicones, di-		availbl-				
Me, reaction		insufficient				
products with						
silica						
Titanium	13463-67-7	Data not			N/A	
dioxide		availbl-				
		insufficient				

12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
2-ethyl-2-[[3-	64265-57-2	Data not	N/A	N/A	N/A	N/A
(2-		available or				
methylaziridin-		insufficient for				
1-		classification				
yl)propionyl]m						
ethyl]propane-						
1,3-diyl bis(2-						
methylaziridine						
-1-propionate)						
Boron,	223674-50-8	Data not	N/A	N/A	N/A	N/A
hexamethyl		available or				
[.mu(1,6-		insufficient for				
hexanediamine		classification				
kappa.						
N1:.kappa.						
N6)]di-						

Siloxanes and	67762-90-7	Data not	N/A	N/A	N/A	N/A
Silicones, di-		available or				
Me, reaction		insufficient for				
products with		classification				
silica						
Titanium	13463-67-7	Experimental	42 days	Bioaccumulatio	9.6	Other methods
dioxide		BCF-Carp		n factor		

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product must only be disposed of by an authorized/permitted waste disposal contractor or incinerated in an industrial or commercial facility in the presence of a combustible material.

SECTION 14: Transport Information

Compliance is required to South African Transport Information Road Traffic Act & Regulations and Railroad regulations, IATA Standards for airfreight and Maritime standards for ocean freight.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information.

SECTION 16: Other information

Revision information:

Section 5: Fire - Advice for fire fighters information information was modified.

- Section 7: Precautions safe handling information information was modified.
- Section 8: Occupational exposure limit table information was modified.
- Section 8: Skin protection protective clothing information information was modified.

Section 09: Color information was added.

Section 09: Odor information was added.

Sections 3 and 9: Odour, colour, grade information information was deleted.

Section 12: Component ecotoxicity information information was modified.

Sectio 16: UK disclaimer information was deleted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M South Africa SDSs are available at www.3m.co.za



Safety Data Sheet

Copyright,2020, 3M Company.All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	28-8077-1	Version number:	5.00
Issue Date:	17/02/2020	Supersedes date:	22/03/2019

This Safety Data Sheet has been prepared in accordance with the South African National Standard SANS 10234:2008.

SECTION 1: Identification

1.1. Product identifier

3MTM Scotch-WeldTM Acrylic Structural Adhesive DP-8005 (Part B)

1.2. Recommended use and restrictions on use

Recommended use

Bonding of low surface energy substrates, Structural adhesive.

1.3. Supplier's details

Address:	3M South Africa (Pty) Ltd, Private Bag X926, Rivonia 2128
Telephone:	011 806 2000
E Mail:	Not available.
Website:	www.3m.co.za

1.4. Emergency telephone number 011 806 2000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Acute Toxicity (oral): Category 5. Skin Corrosion/Irritation: Category 3. Respiratory Sensitizer: Category 1. Skin Sensitizer: Category 1. Reproductive Toxicity: Category 1B. Acute Aquatic Toxicity: Category 3. Chronic Aquatic Toxicity: Category 3.

2.2. Label elements

Signal word DANGER!

Symbols Health Hazard |

Pictograms



HAZARD STATEMEN	NTS:
H303	May be harmful if swallowed.
H316	Causes mild skin irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H360	May damage fertility or the unborn child.
H412	Harmful to acuatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:	
P201	Obtain special instructions before use.
P261A	Avoid breathing vapors.
P284A	In case of inadequate ventilation wear respiratory protection.
P280E	Wear protective gloves.
Response:	
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P342 + P311	If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
Disposal:	
P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Wt	
Tetrahydrofurfuryl methacrylate	2455-24-5	30 - 70	
Acrylate Polymer	Trade Secret	10 - 30	
2-Ethylhexyl methacrylate	688-84-6	< 20	
Butanoic acid, 3-oxo-, 2-[(2-methyl-1-oxo-	21282-97-3	1 - 15	
2-propenyl)oxy]ethyl ester			
[2-[(2-Methyl-1-oxoallyl)oxy]ethyl]	20882-04-6	< 10	
hydrogen succinate			
Ashes (residues), cenospheres	93924-19-7	1 - 5	
2-hydroxyethyl methacrylate	868-77-9	< 1	
Succinic Anhydride	108-30-5	< 1	

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance	Condition
Hydrocarbons.	During combustion.
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.
Hydrogen cyanide.	During combustion.
Oxides of nitrogen.	During combustion.

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

Page: 3 of 13

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Protect from sunlight. Store away from heat. Store away from acids. Store away from oxidising agents.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this Safety Data Sheet.

8.2. Exposure controls

8.2.1. Engineering controls

Provide appropriate local exhaust ventilation for cutting, grinding, sanding or machining. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Safety glasses with side shields.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then

use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

9.

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

•ties
Liquid.
Paste
Off-White
Acrylic
No data available.
Not applicable.
Not applicable.
>=110 °C [Details:CAS 688-84-6]
>=94 °C [Details:CAS 688-84-6]
Not applicable.
Not applicable.
No data available.
0,96 - 1 g/ml
0,96 - 1 [<i>Ref Std</i> :WATER=1]
Not applicable.
No data available.
17 - 36 Pa-s
1 %

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid Heat.

Sparks and/or flames. Light.

10.5 Incompatible materials

Strong acids. Strong oxidising agents.

10.6 Hazardous decomposition products

Substance None known. **Condition**

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic respiratory reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest. May cause additional health effects (see below).

Skin contact

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation. Vapours released during curing may cause eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Additional Health Effects:

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE2 000 - 5 000 mg/kg
Tetrahydrofurfuryl methacrylate	Ingestion	Rat	LD50 4 000 mg/kg
Tetrahydrofurfuryl methacrylate	Dermal	similar health hazards	LD50 estimated to be 2 000 - 5 000 mg/kg
2-Ethylhexyl methacrylate	Dermal		LD50 estimated to be > 5 000 mg/kg
2-Ethylhexyl methacrylate	Ingestion	Rat	LD50 > 2 000 mg/kg
[2-[(2-Methyl-1-oxoallyl)oxy]ethyl] hydrogen succinate	Dermal		LD50 estimated to be 2 000 - 5 000 mg/kg
[2-[(2-Methyl-1-oxoallyl)oxy]ethyl] hydrogen succinate	Ingestion		LD50 estimated to be 2 000 - 5 000 mg/kg
Succinic Anhydride	Dermal	Rat	LD50 > 2 000 mg/kg
Succinic Anhydride	Ingestion	Rat	LD50 1 510 mg/kg
2-hydroxyethyl methacrylate	Dermal	Rabbit	LD50 > 5 000 mg/kg
2-hydroxyethyl methacrylate	Ingestion	Rat	LD50 5 564 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Tetrahydrofurfuryl methacrylate	Rabbit	No significant irritation
2-Ethylhexyl methacrylate	Rabbit	Minimal irritation
[2-[(2-Methyl-1-oxoallyl)oxy]ethyl] hydrogen succinate	Not	Irritant
	applicabl	
	e	
Succinic Anhydride	In vitro	Corrosive
	data	
2-hydroxyethyl methacrylate	Rabbit	Minimal irritation

Serious Eye Damage/Irritation

Name	Species	Value
Tetrahydrofurfuryl methacrylate	Rabbit	No significant irritation
2-Ethylhexyl methacrylate	Rabbit	No significant irritation
[2-[(2-Methyl-1-oxoallyl)oxy]ethyl] hydrogen succinate	Not	Severe irritant
	available	
Succinic Anhydride	similar	Corrosive
	health	
	hazards	
2-hydroxyethyl methacrylate	Rabbit	Moderate irritant

Skin Sensitisation

Name	Species	Value
Tetrahydrofurfuryl methacrylate	In vitro	Sensitising
	data	
2-Ethylhexyl methacrylate	Guinea	Sensitising
	pig	
[2-[(2-Methyl-1-oxoallyl)oxy]ethyl] hydrogen succinate	similar	Sensitising
	compoun	
	ds	
Succinic Anhydride	Mouse	Sensitising
2-hydroxyethyl methacrylate	Human	Sensitising
	and	
	animal	

Respiratory Sensitisation

Name	Species	Value
Succinic Anhydride	similar compoun ds	Sensitising

Germ Cell Mutagenicity

Name	Route	Value
Tetrahydrofurfuryl methacrylate	In Vitro	Not mutagenic
[2-[(2-Methyl-1-oxoallyl)oxy]ethyl] hydrogen succinate	In Vitro	Not mutagenic
Succinic Anhydride	In Vitro	Not mutagenic
2-hydroxyethyl methacrylate	In vivo	Not mutagenic
2-hydroxyethyl methacrylate	In Vitro	Some positive data exist, but the data are not
		sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Succinic Anhydride	Ingestion	Multiple	Not carcinogenic
		animal	
		species	

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Tetrahydrofurfuryl methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 300 mg/kg/day	29 days
Tetrahydrofurfuryl methacrylate	Ingestion	Toxic to female reproduction	Rat	NOAEL 120 mg/kg/day	premating into lactation
Tetrahydrofurfuryl methacrylate	Ingestion	Toxic to development	Rat	NOAEL 120 mg/kg/day	premating into lactation
2-hydroxyethyl methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 1 000 mg/kg/day	premating & during gestation
2-hydroxyethyl methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1 000 mg/kg/day	49 days
2-hydroxyethyl methacrylate	Ingestion	Not classified for development	Rat	NOAEL 1 000 mg/kg/day	premating & during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
[2-[(2-Methyl-1- oxoallyl)oxy]ethyl] hydrogen succinate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Succinic Anhydride	Inhalation	respiratory irritation	May cause respiratory irritation	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Tetrahydrofurfuryl methacrylate	Ingestion	hematopoietic system nervous system	Not classified	Rat	NOAEL 300 mg/kg/day	29 days
Succinic Anhydride	Ingestion	heart skin endocrine system bone, teeth, nails, and/or hair hematopoietic system liver immune system nervous system kidney and/or	Not classified	Mouse	NOAEL 300 mg/kg/day	13 weeks

bladder respiratory		
system		

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

GHS Acute 3: Harmful to aquatic life.

Chronic aquatic hazard:

GHS Chronic 3: Harmful to aquatic life with long lasting effects.

No product test data available.

Material	CAS Nbr	Organism	Туре	Exposure	Test endpoint	Test result
Tetrahydrofurf uryl methacrylate	2455-24-5	Fathead minnow	Experimental	96 hours	LC50	34,7 mg/l
Tetrahydrofurf uryl methacrylate	2455-24-5	Green algae	Experimental	72 hours	EC50	>100 mg/l
Tetrahydrofurf uryl methacrylate	2455-24-5	Green algae	Experimental	72 hours	Effect Concentration 10%	>100 mg/l
Tetrahydrofurf uryl methacrylate	2455-24-5	Water flea	Experimental	21 days	NOEC	37,2 mg/l
2-Ethylhexyl methacrylate	688-84-6	Green Algae	Experimental	72 hours	EC50	5,3 mg/l
2-Ethylhexyl methacrylate	688-84-6	Ricefish	Experimental	96 hours	LC50	2,8 mg/l
2-Ethylhexyl methacrylate	688-84-6	Water flea	Experimental	48 hours	EC50	4,6 mg/l
2-Ethylhexyl methacrylate	688-84-6	Green Algae	Experimental	72 hours	NOEC	0,81 mg/l
2-Ethylhexyl methacrylate	688-84-6	Water flea	Experimental	21 days	NOEC	0,105 mg/l
Butanoic acid, 3-oxo-, 2-[(2- methyl-1-oxo- 2- propenyl)oxy]e	21282-97-3	Green Algae	Experimental	72 hours	EC50	>100 mg/l

thyl ester						
	21282-97-3	Rainbow trout	Experimental	96 hours	LC50	>100 mg/l
3-oxo-, 2-[(2-	21202 97 9	itumoow trout	Enperimental	y o nouis	Leve	100 mg/1
methyl-1-oxo-						
2-						
propenyl)oxy]e						
thyl ester						
	21282-97-3	Water flea	Experimental	48 hours	Effect Level	>100 mg/l
3-oxo-, 2-[(2-			1		50%	5
methyl-1-oxo-						
2-						
propenyl)oxy]e						
thyl ester						
Butanoic acid,	21282-97-3	Green Algae	Experimental	72 hours	NOEC	11,1 mg/l
3-oxo-, 2-[(2-						
methyl-1-oxo-						
2-						
propenyl)oxy]e						
thyl ester						
	20882-04-6	Green algae	Estimated	72 hours	EC50	710 mg/l
1-						
oxoallyl)oxy]et						
hyl] hydrogen						
succinate		D: 01				
	20882-04-6	Ricefish	Estimated	96 hours	LC50	227 mg/l
1-						
oxoallyl)oxy]et						
hyl] hydrogen						
succinate	20882-04-6	Water flea	Estimated	48 hours	EC50	290
[2-[(2-Methyl-	20882-04-0	water nea	Estimated	48 nours	EC30	380 mg/l
oxoallyl)oxy]et						
hyl] hydrogen						
succinate						
	20882-04-6	Green algae	Estimated	72 hours	NOEC	160 mg/l
1-	20002-04-0	Green argae	Lotinated	72 110013	NOLC	100 mg/1
oxoallyl)oxy]et						
hyl] hydrogen						
succinate						
	20882-04-6	Water flea	Estimated	21 days	NOEC	24,1 mg/l
1-						.,
oxoallyl)oxy]et						
hyl] hydrogen						
succinate						
	93924-19-7	Green Algae	Experimental	72 hours	Effect Level	>100 mg/l
(residues),					50%	
cenospheres						
	93924-19-7	Guppy	Experimental	96 hours	Lethal Level	>100 mg/l
(residues),					50%	
cenospheres				ļ		
	93924-19-7	Water flea	Experimental	48 hours	Effect Level	>100 mg/l
(residues),					50%	
cenospheres						
1	02024 10 7	Green Algae	Experimental	72 hours	No obs Effect	100 mg/l
Ashes (residues),	93924-19-7	Gleen Algae	Experimental	72 nours	Level	100 mg/1

cenospheres						
Ashes (residues), cenospheres	93924-19-7	Water flea	Experimental	21 days	No obs Effect Level	100 mg/l
2-hydroxyethyl methacrylate	868-77-9	Fathead minnow	Experimental	96 hours	LC50	227 mg/l
2-hydroxyethyl methacrylate	868-77-9	Green algae	Experimental	72 hours	EC50	710 mg/l
2-hydroxyethyl methacrylate	868-77-9	Water flea	Experimental	48 hours	EC50	380 mg/l
2-hydroxyethyl methacrylate	868-77-9	Green Algae	Experimental	72 hours	NOEC	160 mg/l
2-hydroxyethyl methacrylate	868-77-9	Water flea	Experimental	21 days	NOEC	24,1 mg/l
Succinic Anhydride	108-30-5	Green Algae	Estimated	72 hours	EC50	>100 mg/l
Succinic Anhydride	108-30-5	Water flea	Estimated	48 hours	EC50	>100 mg/l
Succinic Anhydride	108-30-5	Zebra Fish	Estimated	96 hours	LC50	>100 mg/l
Succinic Anhydride	108-30-5	Green Algae	Estimated	72 hours	NOEC	100 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Tetrahydrofurf uryl methacrylate	2455-24-5	Experimental Biodegradation	28 days	BOD	75 % BOD/ThBOD	OECD 301F - Manometric respirometry
2-Ethylhexyl methacrylate	688-84-6	Experimental Biodegradation	28 days	BOD	88 % BOD/ThBOD	OECD 301C - MITI test (I)
Butanoic acid, 3-oxo-, 2-[(2- methyl-1-oxo- 2- propenyl)oxy]e thyl ester	21282-97-3	Experimental Hydrolysis		Hydrolytic half-life	6.5 days (t 1/2)	Other methods
Butanoic acid, 3-oxo-, 2-[(2- methyl-1-oxo- 2- propenyl)oxy]e thyl ester	21282-97-3	Experimental Biodegradation	28 days	BOD	64 % BOD/ThBOD	OECD 301C - MITI test (I)
[2-[(2-Methyl- 1- oxoallyl)oxy]et hyl] hydrogen succinate	20882-04-6	Estimated Biodegradation	14 days	BOD	95 % weight	OECD 301C - MITI test (I)
Ashes (residues), cenospheres	93924-19-7	Data not availbl- insufficient			N/A	
2-hydroxyethyl methacrylate	868-77-9	Experimental Biodegradation	14 days	BOD	95 % BOD/ThBOD	OECD 301C - MITI test (I)
Succinic	108-30-5	Experimental		Hydrolytic	4.3 minutes (t	Other methods

Anhydride	Hydrolysis	half-life	1/2)	
Succinic Ambas derida	 	 o .	U U	OECD 301E - Modified
Anhydride	Biodegradation	Organic Carbon Deplet		OECD Scre

12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Tetrahydrofurf uryl methacrylate	2455-24-5	Estimated Bioconcentrati on		Bioaccumulatio n factor	3.42	Estimated: Bioconcentration factor
2-Ethylhexyl methacrylate	688-84-6	Experimental Bioconcentrati on	96 hours	Bioaccumulatio n factor	37	OECD 305C-Bioaccum degree fish
Butanoic acid, 3-oxo-, 2-[(2- methyl-1-oxo- 2- propenyl)oxy]e thyl ester	21282-97-3	Experimental Bioconcentrati on		Log Kow	0.9	Other methods
[2-[(2-Methyl- 1- oxoallyl)oxy]et hyl] hydrogen succinate	20882-04-6	Estimated Bioconcentrati on		Bioaccumulatio n factor	3.0	Estimated: Bioconcentration factor
Ashes (residues), cenospheres	93924-19-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
2-hydroxyethyl methacrylate	868-77-9	Experimental Bioconcentrati on		Log Kow	0.42	Other methods
Succinic Anhydride	108-30-5	Experimental Bioconcentrati on		Log Kow	2.44	Other methods

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product must only be disposed of by an authorized/permitted waste disposal contractor or incinerated in an industrial or commercial facility in the presence of a combustible material.

SECTION 14: Transport Information

Compliance is required to South African Transport Information Road Traffic Act & Regulations and Railroad regulations, IATA Standards for airfreight and Maritime standards for ocean freight.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information.

SECTION 16: Other information

Revision information:

Section 2: Ingredient table information was modified.

Section 4: First aid for eye contact information information was modified.

Section 8: Eye/face protection information information was modified.

Section 09: Color information was added.

Section 09: Odor information was added.

Sections 3 and 9: Odour, colour, grade information information was deleted.

Section 11: Acute Toxicity table information was modified.

Section 11: Germ Cell Mutagenicity Table information was modified.

Section 11: Reproductive Toxicity Table information was modified.

Section 11: Serious Eye Damage/Irritation Table information was modified.

Section 11: Skin Corrosion/Irritation Table information was modified.

Section 11: Skin Sensitization Table information was modified.

Section 12: Component ecotoxicity information information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12:Bioccumulative potential information information was modified.

Sectio 16: UK disclaimer information was deleted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M South Africa SDSs are available at www.3m.co.za