

Safety Data Sheet

Copyright, 2023, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group: 07-1664-7 Version number: 5.00 24/05/2023 **Issue Date:** Supersedes date: 17/08/2020

This Safety Data Sheet has been prepared in accordance with the South African National Standard SANS 10234:2008.

IDENTIFICATION

1.1. Product identifier

3M[™] Panel Bonding Adhesive PN 08115

Product Identification Numbers

60-9800-3093-0

1.2. Recommended use and restrictions on use

Automotive.

1.3. Supplier's details

Address: 3M South Africa (Pty) Ltd, Private Bag X926, Rivonia 2128

011 806 2000 **Telephone:** Not available. E Mail: Website: www.3m.co.za

1.4. Emergency telephone number

011 806 2000

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the MSDSs for components of this product are:

09-3599-9, 32-4327-6

TRANSPORT INFORMATION

Compliance is required to South African Transport Information Road Traffic Act & Regulations and Railroad regulations, IATA Standards for airfreight and Maritime standards for ocean freight.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M South Africa SDSs are available at www.3m.co.za

Page: 1 of 2

AMENIN I D. II. A. II. I. D.V. 00115		
3M [™] Panel Bonding Adhesive PN 08115		

Page: 2 of 2



Safety Data Sheet

Copyright, 2020, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 09-3599-9
 Version number:
 5.00

 Issue Date:
 13/08/2020
 Supersedes date:
 08/03/2019

This Safety Data Sheet has been prepared in accordance with the South African National Standard SANS 10234:2008.

SECTION 1: Identification

1.1. Product identifier

3MTM Panel Bonding (90 Minutes) Adhesive Part A (Accelerator) PN 08115, 38315, 58115

1.2. Recommended use and restrictions on use

Recommended use

Automotive., Use with Part B, MSDS 32-4327-6

1.3. Supplier's details

Address: 3M South Africa (Pty) Ltd, Private Bag X926, Rivonia 2128

Telephone: 011 806 2000 E Mail: Not available. Website: www.3m.co.za

1.4. Emergency telephone number

011 806 2000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Acute Toxicity (oral): Category 5.
Acute Toxicity (dermal): Category 5.
Acute Toxicity (inhalation): Category 5.
Serious Eye Damage/Irritation: Category 1.
Skin Corrosion/Irritation: Category 1B.

Skin Sensitizer: Category 1.

Reproductive Toxicity: Category 1B.

Specific Target Organ Toxicity (single exposure): Category 1. Specific Target Organ Toxicity (single exposure): Category 3. Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

Signal word

DANGER!

Symbols

Corrosion | Exclamation mark | Health Hazard |

Pictograms



HAZARD STATEMENTS:

H303 May be harmful if swallowed.
H313 May be harmful in contact with skin.
H333 May be harmful if inhaled.

H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.
H360 May damage fertility or the unborn child.

H370 Causes damage to organs:

blood or blood-forming organs

H372 Causes damage to organs through prolonged or repeated exposure:

respiratory system

PRECAUTIONARY STATEMENTS

General:

P102 Keep out of reach of children.

P101 If medical advice is needed, have product container or label at hand.

Prevention:

P201 Obtain special instructions before use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P271 Use only outdoors or in a well-ventilated area.

P280D Wear protective gloves, protective clothing, and eye/face protection.

P264 Wash thoroughly after handling.

Response:

P304 + P312 IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/physician.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P308 + P313 IF exposed or concerned: Get medical advice/attention.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/container in accordance with applicable

local/regional/national/international regulations.

2.3. Other hazards

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines. - May cause

chemical gastrointestinal burns. All or part of the classification is based on toxicity test data.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Wt
Fatty acids, C18-unsaturated, dimers,	68911-25-1	15 - 40
polymers with 3,3'-		
oxybis(ethyleneoxy)bis(propylamine)		
2-Propenenitrile, polymer with 1,3-	68683-29-4	9 - 30
butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-		
(1-piperazinyl)ethyl]amino]butyl-terminated		
Silica, vitreous	60676-86-0	10 - 30
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	3 - 13
Tris(2,4,6-	90-72-2	5 - 10
dimethylaminomonomethyl)phenol		
Imidazole	288-32-4	1 - 5
Siloxanes and Silicones, di-Me, reaction	67762-90-7	1 - 5
products with silica		
Calcium Nitrate	10124-37-5	1 - 2.5
Bis[(dimethylamino)methyl]phenol	71074-89-0	0.1 - 1.5
N-aminoethylpiperazine	140-31-8	0.1 - 1.5
Toluene	108-88-3	< 0.5

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eve contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If swallowed

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Overexposure to this product may result in methemoglobinemia. Methemoglobinemia may be clinically suspected by the presence of clinical "cyanosis" in the presence of a normal PaO2 (as obtained by arterial blood gases). Routine pulse oximetry may be inaccurate for monitoring oxygen saturation in the presence of methemoglobinemia, and should not be used to make the diagnosis of this disorder. If the patient is symptomatic or if the methemoglobin level is >20%, specific therapy with methylene blue should be considered as part of the medical management.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u> Carbon monoxide. Carbon dioxide.

Condition

During combustion. During combustion.

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store away from acids. Store away from oxidising agents.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Toluene	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human
				carcin
Toluene	108-88-3	South Africa	TWA(8 hours):188 mg/m3(50	SKIN
		RELs	ppm);STEL(15 minutes):560	
			mg/m3(150 ppm)	
Silica, vitreous	60676-86-0	South Africa	TWA(as respirable dust)(8	
		RELs	hours):0.1 mg/m3	
Silicon dioxide	67762-90-7	South Africa	TWA(Total inhalable dust)(8	
		RELs	hours):6 mg/m3;TWA(as	
			respirable dust)(8 hours):3	
			mg/m3	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

South Africa CLs: South Africa. Control Limits. Regulations for Hazardous Chemical Substances, Table 1

South Africa RELs : South Africa. Recommended Exposure Limits (RELs) Regulations for Hazardous Chemical Substances, Table 2

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Information on basic physical and chemical properties				
Physical state	Liquid.			
Specific Physical Form:	Viscous liquid			
Colour	Tan			
Odor	Slight Amine			
Odour threshold	No data available.			
pH	Not applicable.			
Melting point/Freezing point	Not applicable.			
Boiling point/Initial boiling point/Boiling range	>=110 °C			
Flash point	110 °C [Test Method:Closed Cup]			
Evaporation rate	<=1 [Ref Std:BUOAC=1]			
Flammability (solid, gas)	Not applicable.			
Flammable Limits(LEL)	No data available.			
Flammable Limits(UEL)	No data available.			
Vapour pressure	<=26 664,4 Pa [@ 20 °C]			
Vapor Density and/or Relative Vapor Density	No data available.			
Density	1,2 g/ml			
Relative density	1,2 [Ref Std:WATER=1]			
Water solubility	No data available.			
Solubility- non-water	No data available.			
Partition coefficient: n-octanol/water	No data available.			
Autoignition temperature	No data available.			
Decomposition temperature	No data available.			
Viscosity/Kinematic Viscosity	100 000 mPa-s - 225 000 mPa-s [Test Method: Brookfield]			
Volatile organic compounds (VOC)	4 g/l [Test Method:calculated SCAQMD rule 443.1]			
Volatile organic compounds (VOC)	0,4 % weight [Test Method:calculated per CARB title 2]			
Percent volatile	0,4 % weight			
VOC less H2O & exempt solvents	4 g/l [Test Method:calculated SCAQMD rule 443.1]			
Molecular weight	No data available.			

Nanoparticles

This material contains nanoparticles.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is considered to be non reactive under normal use conditions

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

Strong oxidising agents.

10.6 Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

May be harmful if inhaled. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

May be harmful in contact with skin. Corrosive (skin burns): Signs/symptoms may include localised redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion

May be harmful if swallowed.

Gastrointestinal corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain, nausea, vomiting, and diarrhea; blood in the faeces and/or vomitus may also be seen. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Methemoglobinemia: Signs/symptoms may include headache, dizziness, nausea, difficulty breathing, and generalised weakness. Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Prolonged or repeated exposure may cause target organ effects:

Respiratory effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and respiratory failure.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Additional information:

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE2 000 - 5 000 mg/kg
Overall product	Inhalation- Dust/Mist(4 hr)		No data available; calculated ATE5 - 12,5 mg/l
Overall product	Ingestion		No data available; calculated ATE2 000 - 5 000 mg/kg
Fatty acids, C18-unsaturated, dimers, polymers with 3,3'- oxybis(ethyleneoxy)bis(propylamine)	Dermal	Rat	LD50 > 2 000 mg/kg
Fatty acids, C18-unsaturated, dimers, polymers with 3,3'-oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Rat	LD50 > 2 000 mg/kg
Silica, vitreous	Dermal	Rabbit	LD50 > 5 000 mg/kg
Silica, vitreous	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0,691 mg/l
Silica, vitreous	Ingestion	Rat	LD50 > 5 110 mg/kg
2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated	Dermal	Rabbit	LD50 > 3 000 mg/kg
2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated	Ingestion	Rat	LD50 > 15 300 mg/kg
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Dermal	Rabbit	LD50 2 500 mg/kg
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Rat	LD50 3 160 mg/kg
Tris(2,4,6-dimethylaminomonomethyl)phenol	Dermal	Rat	LD50 1 280 mg/kg
Tris(2,4,6-dimethylaminomonomethyl)phenol	Ingestion	Rat	LD50 1 000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Dermal	Rabbit	LD50 > 5 000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0,691 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Rat	LD50 > 5 110 mg/kg
Imidazole	Ingestion	Rat	LD50 970 mg/kg
Imidazole	Dermal	similar compoun ds	LD50 400 mg/kg
Calcium Nitrate	Ingestion	Rat	LD50 >300, <2000 mg/kg
Calcium Nitrate	Dermal	similar compoun ds	LD50 > 2 000 mg/kg
Bis[(dimethylamino)methyl]phenol	Ingestion		LD50 estimated to be 300 - 2 000 mg/kg
N-aminoethylpiperazine	Dermal	Rabbit	LD50 865 mg/kg
N-aminoethylpiperazine	Ingestion	Rat	LD50 1 470 mg/kg
Toluene	Dermal	Rat	LD50 12 000 mg/kg
Toluene	Inhalation- Vapor (4 hours)	Rat	LC50 30 mg/l
Toluene	Ingestion	Rat	LD50 5 550 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Skin Corrosion/Irritation		
Name	Species	Value
Overall product	Rabbit	Corrosive
Fatty acids, C18-unsaturated, dimers, polymers with 3,3'-oxybis(ethyleneoxy)bis(propylamine)	Rat	Irritant
Silica, vitreous	Rabbit	No significant irritation
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Rabbit	Corrosive

Tris(2,4,6-dimethylaminomonomethyl)phenol	Rabbit	Corrosive
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
Imidazole	Rabbit	Corrosive
Calcium Nitrate	similar	No significant irritation
	compoun	
	ds	
Bis[(dimethylamino)methyl]phenol	similar	Corrosive
	compoun	
	ds	
N-aminoethylpiperazine	Rabbit	Corrosive
Toluene	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
Overall product	similar	Corrosive
	health	
	hazards	
Fatty acids, C18-unsaturated, dimers, polymers with 3,3'-	In vitro	Severe irritant
oxybis(ethyleneoxy)bis(propylamine)	data	
Silica, vitreous	Rabbit	No significant irritation
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	similar	Corrosive
	health	
	hazards	
Tris(2,4,6-dimethylaminomonomethyl)phenol	Rabbit	Corrosive
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
Imidazole	Rabbit	Corrosive
Calcium Nitrate	Rabbit	Corrosive
Bis[(dimethylamino)methyl]phenol	similar	Corrosive
	compoun	
	ds	
N-aminoethylpiperazine	Rabbit	Corrosive
Toluene	Rabbit	Moderate irritant

Sensitization:

Skin Sensitisation

SKIII SCIISIUSAUOII	- C ·	X7.1
Name	Species	Value
Overall product	Guinea	Sensitising
•	pig	
Fatty acids, C18-unsaturated, dimers, polymers with 3,3'-	Guinea	Sensitising
oxybis(ethyleneoxy)bis(propylamine)	pig	
Silica, vitreous	Human	Not classified
	and	
	animal	
2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-	Guinea	Not classified
piperazinyl)ethyl]amino]butyl-terminated	pig	
Tris(2,4,6-dimethylaminomonomethyl)phenol	Guinea	Not classified
	pig	
Siloxanes and Silicones, di-Me, reaction products with silica	Human	Not classified
	and	
	animal	
Calcium Nitrate	similar	Not classified
	compoun	
	ds	
N-aminoethylpiperazine	Guinea	Sensitising
	pig	
Toluene	Guinea	Not classified
	pig	

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Fatty acids, C18-unsaturated, dimers, polymers with 3,3'-oxybis(ethyleneoxy)bis(propylamine)	In Vitro	Not mutagenic
Silica, vitreous	In Vitro	Not mutagenic
Tris(2,4,6-dimethylaminomonomethyl)phenol	In Vitro	Not mutagenic
Siloxanes and Silicones, di-Me, reaction products with silica	In Vitro	Not mutagenic
Imidazole	In Vitro	Not mutagenic
Imidazole	In vivo	Not mutagenic
Calcium Nitrate	In Vitro	Not mutagenic
N-aminoethylpiperazine	In vivo	Not mutagenic
N-aminoethylpiperazine	In Vitro	Some positive data exist, but the data are not sufficient for classification
Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Silica, vitreous	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Siloxanes and Silicones, di-Me, reaction products with silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Silica, vitreous	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silica, vitreous	Inhalation	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Silica, vitreous	Ingestion	Not classified for development	Rat	NOAEL 1 350 mg/kg/day	during organogenesis
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for development	Rat	NOAEL 1 350 mg/kg/day	during organogenesis
Imidazole	Ingestion	Toxic to development	Rat	NOAEL 60 mg/kg/day	during organogenesis
Calcium Nitrate	Ingestion	Not classified for female reproduction	similar compoun ds	NOAEL 1 500 mg/kg/day	premating into lactation
Calcium Nitrate	Ingestion	Not classified for male reproduction	similar compoun ds	NOAEL 1 500 mg/kg/day	28 days
Calcium Nitrate	Ingestion	Not classified for development	similar compoun ds	NOAEL 1 500 mg/kg/day	premating into lactation
N-aminoethylpiperazine	Ingestion	Not classified for female reproduction	Rat	NOAEL 598 mg/kg/day	premating & during gestation
N-aminoethylpiperazine	Ingestion	Not classified for male reproduction	Rat	NOAEL 409 mg/kg/day	32 days

N-aminoethylpiperazine	Ingestion	Toxic to development	Rabbit	NOAEL 75	during
				mg/kg/day	gestation
Toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not	occupational
				available	exposure
Toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2,3	1 generation
				mg/l	
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520	during
				mg/kg/day	gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not	poisoning
				available	and/or abuse

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Fatty acids, C18- unsaturated, dimers, polymers with 3,3'- oxybis(ethyleneoxy)bis(pro pylamine)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	Irritation Positive	
Fatty acids, C18- unsaturated, dimers, polymers with 3,3'- oxybis(ethyleneoxy)bis(pro pylamine)	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	NOAEL Not available	
3,3'- Oxybis(ethyleneoxy)bis(pr opylamine)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Tris(2,4,6-dimethylaminomonomethyl)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Imidazole	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Calcium Nitrate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Calcium Nitrate	Ingestion	methemoglobinemi a	Causes damage to organs	Human	NOAEL Not available	environmental exposure
N-aminoethylpiperazine	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0,004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Silica, vitreous	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Tris(2,4,6-dimethylaminomonomethy l)phenol	Dermal	skin liver nervous system auditory system hematopoietic system eyes	Not classified	Rat	NOAEL 125 mg/kg/day	28 days
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure

Imidazole	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 60 mg/kg/day	90 days
Imidazole	Ingestion	heart liver blood nervous system eyes	Not classified	Rat	NOAEL 180 mg/kg/day	90 days
Calcium Nitrate	Ingestion	heart skin endocrine system bone, teeth, nails, and/or hair hematopoietic system liver immune system nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	similar compoun ds	NOAEL 1 500 mg/kg/day	28 days
N-aminoethylpiperazine	Dermal	skin	Not classified	Rat	NOAEL 100 mg/kg/day	29 days
N-aminoethylpiperazine	Dermal	hematopoietic system nervous system kidney and/or bladder	Not classified	Rat	NOAEL 1 000 mg/kg/day	29 days
N-aminoethylpiperazine	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 0,2 mg/m3	13 weeks
N-aminoethylpiperazine	Inhalation	hematopoietic system eyes kidney and/or bladder	Not classified	Rat	NOAEL 53,8 mg/m3	13 weeks
N-aminoethylpiperazine	Ingestion	heart endocrine system hematopoietic system liver nervous system kidney and/or bladder	Not classified	Rat	NOAEL 598 mg/kg/day	28 days
Toluene	Inhalation	auditory system eyes olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	nervous system	May cause damage to organs though prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2,3 mg/l	15 months
Toluene	Inhalation	heart liver kidney and/or bladder	Not classified	Rat	NOAEL 11,3 mg/l	15 weeks
Toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1,1 mg/l	4 weeks
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
Toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1,1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic system vascular system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11,3 mg/l	15 weeks
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2 500 mg/kg/day	13 weeks
Toluene	Ingestion	liver kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2 500 mg/kg/day	13 weeks

Toluene	Ingestion	hematopoietic	Not classified	Mouse	NOAEL 600	14 days
		system			mg/kg/day	
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105	28 days
					mg/kg/day	
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105	4 weeks
	_				mg/kg/day	

Aspiration Hazard

Name	Value
Toluene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

Not acutely toxic to aquatic life by GHS criteria.

Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available.

Material	CAS Nbr	Organism	Туре	Exposure	Test endpoint	Test result
Fatty acids,	68911-25-1		Data not			
C18-			available or			
unsaturated,			insufficient for			
dimers,			classification			
polymers with						
3,3'-						
oxybis(ethylen						
eoxy)bis(propy						
lamine)						
2-	68683-29-4		Data not			
Propenenitrile,			available or			
polymer with			insufficient for			
1,3-butadiene,			classification			
1-cyano-1-						
methyl-4-oxo-						
4-[[2-(1-						
piperazinyl)eth						
yl]amino]butyl-						
terminated	(0(7(9(0	C	F	70 1	1.050	> 10,000 /1
	60676-86-0	·	Experimental	72 hours	LC50	>10 000 mg/l
3,3'-	4246-51-9	Water flea	Experimental	48 hours	EC50	218,16 mg/l
Oxybis(ethylen						
eoxy)bis(propy						

lamine)		1	1	1	1	
3,3'-	4246-51-9	Green algae	Experimental	72 hours	EC50	>500 mg/l
Oxybis(ethylen	1210317	Green argue	Emperimentar	/2 Hours		500 mg/r
eoxy)bis(propy						
lamine)						
3,3'-	4246-51-9	Golden Orfe	Experimental	96 hours	LC50	>1 000 mg/l
Oxybis(ethylen						
eoxy)bis(propy						
lamine)						
3,3'-	4246-51-9	Green algae	Experimental	72 hours	Effect	5,4 mg/l
Oxybis(ethylen				, = ===================================	Concentration	, , , , , , , , , , , , , , , , , , , ,
eoxy)bis(propy					10%	
lamine)						
Tris(2,4,6-	90-72-2	Grass Shrimp	Experimental	96 hours	LC50	718 mg/l
dimethylamino		l · · · · · · · · · · · · · · ·	F			
monomethyl)p						
henol						
Tris(2,4,6-	90-72-2	Common Carp	Experimental	96 hours	LC50	175 mg/l
dimethylamino						
monomethyl)p						
henol						
Tris(2,4,6-	90-72-2	Green algae	Experimental	72 hours	EC50	84 mg/l
dimethylamino			1			
monomethyl)p						
henol						
Tris(2,4,6-	90-72-2	Green algae	Experimental	72 hours	NOEC	6,25 mg/l
dimethylamino						
monomethyl)p						
henol						
Imidazole	288-32-4	Green algae	Experimental	72 hours	EC50	133 mg/l
Imidazole	288-32-4	Water flea	Experimental	48 hours	EC50	341,5 mg/l
Imidazole	288-32-4	Green algae	Experimental	72 hours	NOEC	25 mg/l
Siloxanes and	67762-90-7		Data not			
Silicones, di-			available or			
Me, reaction			insufficient for			
products with			classification			
silica						
Calcium	10124-37-5	Guppy	Estimated	96 hours	LC50	1 378 mg/l
Nitrate						
Calcium	10124-37-5	Fathead	Estimated	30 days	NOEC	58 mg/l
Nitrate		minnow				
Bis[(dimethyla	71074-89-0		Data not			
mino)methyl]p			available or			
henol			insufficient for			
			classification			
N-	140-31-8	Water flea	Experimental	48 hours	EC50	58 mg/l
aminoethylpipe						
razine						
N-	140-31-8	Green Algae	Experimental	72 hours	EC50	>1 000 mg/l
aminoethylpipe						
razine						
N-	140-31-8	Golden Orfe	Experimental	96 hours	LC50	368 mg/l
aminoethylpipe						
razine						
N-	140-31-8	Green Algae	Experimental	72 hours	NOEC	31 mg/l

Page: 14 of 18

aminoethylpipe						
razine						
Toluene	108-88-3	Green Algae	Experimental	72 hours	EC50	12,5 mg/l
Toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5,5 mg/l
Toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3,78 mg/l
Toluene	108-88-3	Fish other	Experimental	96 hours	LC50	6,41 mg/l
Toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0,74 mg/l
Toluene	108-88-3	Coho salmon	Experimental	40 days	NOEC	3,2 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Fatty acids, C18- unsaturated, dimers, polymers with	68911-25-1	Data not availbl- insufficient			N/A	
3,3'- oxybis(ethylen eoxy)bis(propy lamine)						
Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)eth yl]amino]butyl-terminated		Data not availbl-insufficient			N/A	
Silica, vitreous	60676-86-0	Data not availbl-insufficient			N/A	
3,3'- Oxybis(ethylen eoxy)bis(propy lamine)	4246-51-9	Estimated Photolysis		Photolytic half- life (in air)	2.96 hours (t 1/2)	Other methods
3,3'- Oxybis(ethylen eoxy)bis(propy lamine)	4246-51-9	Experimental Biodegradation	25 days	CO2 evolution	-8 %CO2 evolution/THC O2 evolution	OECD 301B - Modified sturm or CO2
Tris(2,4,6-dimethylamino monomethyl)p henol	90-72-2	Experimental Biodegradation	28 days	BOD	4 % weight	OECD 301D - Closed bottle test
Imidazole	288-32-4	Experimental Biodegradation	18 days	Dissolv. Organic Carbon Deplet	98 % weight	OECD 301A - DOC Die Away Test
Siloxanes and Silicones, di- Me, reaction products with silica	67762-90-7	Data not availbl- insufficient			N/A	
Calcium	10124-37-5	Data not			N/A	

Nitrate		availbl- insufficient				
Bis[(dimethyla mino)methyl]p henol	71074-89-0	Estimated Biodegradation	28 days	BOD	20 % weight	OECD 301C - MITI test (I)
N- aminoethylpipe razine	140-31-8	Experimental Biodegradation	28 days			OECD 301C - MITI test (I)
Toluene	108-88-3	Experimental Photolysis		Photolytic half- life (in air)	5.2 days (t 1/2)	Other methods
Toluene	108-88-3	Experimental Biodegradation	20 days	BOD	80 % weight	

12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Fatty acids, C18- unsaturated, dimers, polymers with 3,3'-	68911-25-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
oxybis(ethylen eoxy)bis(propy lamine)						
Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)eth yl]amino]butyl-terminated	68683-29-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Silica, vitreous	60676-86-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
3,3'- Oxybis(ethylen eoxy)bis(propy lamine)	4246-51-9	Experimental Bioconcentrati on		Log Kow	-1.25	Other methods
Tris(2,4,6-dimethylamino monomethyl)p henol	90-72-2	Experimental Bioconcentrati on		Log Kow	-0.66	Other methods
Imidazole	288-32-4	Experimental Bioconcentrati on		Log Kow	-0.08	Other methods
Siloxanes and Silicones, di- Me, reaction products with silica	67762-90-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

Calcium	10124-37-5	Data not	N/A	N/A	N/A	N/A
Nitrate		available or				
		insufficient for				
		classification				
Bis[(dimethyla	71074-89-0	Estimated		Log Kow	-2.34	Estimated: Octanol-
mino)methyl]p		Bioconcentrati				water partition
henol		on				coefficient
N-	140-31-8	Experimental		Log Kow	0.3	Other methods
aminoethylpipe		Bioconcentrati				
razine		on				
Toluene	108-88-3	Experimental		Log Kow	2.73	Other methods
		Bioconcentrati				
		on				

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product must only be disposed of by an authorized/permitted waste disposal contractor or incinerated in an industrial or commercial facility in the presence of a combustible material.

SECTION 14: Transport Information

Compliance is required to South African Transport Information Road Traffic Act & Regulations and Railroad regulations, IATA Standards for airfreight and Maritime standards for ocean freight.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

Revision information:

Section 2: Hazard - Other information was modified.

Label: GHS Classification information was modified.

Label: GHS Precautionary - Prevention information was modified.

Label: GHS Precautionary - Response information was modified.

Label: GHS Target Organ Hazard Statement information was added.

3MTM Panel Bonding (90 Minutes) Adhesive Part A (Accelerator) PN 08115, 38315, 58115

- Section 2: Ingredient table information was modified.
- Section 4: First Aid notes to physician (REACH/GHS) information was modified.
- Section 7: Precautions safe handling information information was modified.
- Section 8: Occupational exposure limit table information was modified.
- Section 09: Color information was added.
- Section 09: Nanoparticle information was added.
- Section 09: Odor information was added.
- Sections 3 and 9: Odour, colour, grade information information was deleted.
- Section 09: Percent Volatile information was added.
- Section 9: Property description for optional properties information was added.
- Section 9: Property description for optional properties information was deleted.
- Section 09: Vapor Density Value information was added.
- Section 9: Vapour density value information was deleted.
- Section 9: Viscosity information information was deleted.
- Section 09: Viscosity information was added.
- Section 09: VOC Less H2O & Exempt Solvents information was added.
- Section 09: Volatile Organic Compounds information was added.
- Section 11: Acute Toxicity table information was modified.
- Section 11: Germ Cell Mutagenicity Table information was modified.
- Section 11: Prolonged or repeated exposure may cause standard phrases information was added.
- Section 11: Reproductive Toxicity Table information was modified.
- Section 11: Serious Eye Damage/Irritation Table information was modified.
- Section 11: Single exposure may cause standard phrases information was modified.
- Section 11: Skin Corrosion/Irritation Table information was modified.
- Section 11: Skin Sensitization Table information was modified.
- Section 11: Target Organs Repeated Table information was modified.
- Section 11: Target Organs Single Table information was modified.
- Section 12: Component ecotoxicity information information was modified.
- Section 12: Persistence and Degradability information information was modified.
- Section 12:Bioccumulative potential information information was modified.
- Sectio 16: UK disclaimer information was deleted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M South Africa SDSs are available at www.3m.co.za



Safety Data Sheet

Copyright, 2024, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 32-4327-6
 Version number:
 2.05

 Issue Date:
 06/03/2024
 Supersedes date:
 25/01/2024

This Safety Data Sheet has been prepared in accordance with the South African National Standard SANS 10234:2008.

SECTION 1: Identification

1.1. Product identifier

3MTM Panel Bonding Adhesive Part B PNs 08115, 38315, 38515, 58115

1.2. Recommended use and restrictions on use

Recommended use

Automotive., Structural Panel Bonding Adhesive

NPEL priemerná (respirabilná frakcia)(8 hodín): 1 mg/m3; NPEL krátkodobá (respirabilná frakcia) (15 minút): 4 mg/m3

1.3. Supplier's details

Address: 3M South Africa (Pty) Ltd, Private Bag X926, Rivonia 2128

Telephone: 011 806 2000 E Mail: Not available. Website: www.3m.co.za

1.4. Emergency telephone number

011 806 2000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Acute Toxicity (inhalation): Category 5. Skin Corrosion/Irritation: Category 2. Serious Eye Damage/Irritation: Category 2A

Skin Sensitizer: Category 1.

Germ Cell Mutagenicity: Category 2.

Carcinogenicity: Category 2.

Reproductive Toxicity: Category 1B. Acute Aquatic Toxicity: Category 2. Chronic Aquatic Toxicity: Category 2.

2.2. Label elements

Signal word

Danger

Symbols

Exclamation mark | Health Hazard | Environment |

Pictograms







HAZARD STATEMENTS:

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H333 May be harmful if inhaled.

H317 May cause an allergic skin reaction.
H341 Suspected of causing genetic defects.
H351 Suspected of causing cancer.

H360 May damage fertility or the unborn child.

H411 Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

General:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Prevention:

P201 Obtain special instructions before use.
P273 Avoid release to the environment.

P280E Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P312 IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/attention.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/container in accordance with applicable

local/regional/national/international regulations.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Wt
4,4'-isopropylidenediphenol-	25068-38-6	30 - 60

epichlorohydrin polymer		
Glass, oxide, chemicals	65997-17-3	10 - 30
1,4-Bis[(2,3-	14228-73-0	7 - 13
epoxypropoxy)methyl]cyclohexane		
Silica, vitreous	60676-86-0	7 - 13
Acrylate Polymer	Trade Secret	5 - 10
Silicon dioxide	7631-86-9	1 - 5
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	0.5 - 1.5
[3-(2,3-Epoxypropoxy)propyl]	2530-83-8	0.5 - 1.5
trimethoxysilane		
Carbon black	1333-86-4	< 0.5
Toluene	108-88-3	< 0.3

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eve contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

5.3. Special protective actions for fire-fighters

When fire fighting conditions are severe and total thermal decomposition of the product is possible, wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, tunic and trousers (leggings), bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for

information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from strong bases. Store away from oxidising agents. Store away from amines.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Toluene	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human carcin, Ototoxicant
Toluene	108-88-3	South Africa RELs	TWA(8 hours):40 ppm	SKIN
Carbon black	1333-86-4	ACGIH	TWA(inhalable fraction):3 mg/m3	A3: Confirmed animal carcin.
Carbon black	1333-86-4	South Africa RELs	TWA(inhalable fraction)(8 hours):6 mg/m3	
Silicon Carbide	60676-86-0	South Africa RELs	TWA(as total dust)(8 hours):10 mg/m3;TWA(as respirable dust)(8 hours):5 mg/m3	
CERAMIC FIBERS	65997-17-3	ACGIH	TWA(as fiber):0.2 fiber/cc	A2: Suspected human carcin.
CERAMIC FIBERS	65997-17-3	South Africa RELs	TWA(8 hours):0.4 fiber/cc	
Glass, oxide, chemicals	65997-17-3	Manufacturer determined	TWA(as non-fibrous, respirable)(8 hours):3 mg/m3;TWA(as non-fibrous,	

			inhalable fraction)(8 hours):10	
			mg/m3	
SPECIAL PURPOSE GLASS	65997-17-3	ACGIH	TWA(as fiber):1 fiber/cc	A3: Confirmed animal
FIBERS				carcin.
SPECIAL PURPOSE GLASS	65997-17-3	South Africa	TWA(8 hours):2 fiber/cc	
FIBERS		RELs		
Silicon Carbide	7631-86-9	South Africa	TWA(as total dust)(8	
		RELs	hours):10 mg/m3;TWA(as	
			respirable dust)(8 hours):5	
			mg/m3	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

South Africa CLs: South Africa. Control Limits. Regulations for Hazardous Chemical Substances, Table 1

South Africa RELs: South Africa. Recommended Exposure Limits (RELs) Regulations for Hazardous Chemical Substances, Table 2

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.		
Colour	Black		
Odor	Acrylic		
Odour threshold	No data available.		
рН	No data available.		
Melting point/Freezing point	No data available.		
Boiling point/Initial boiling point/Boiling range	>= 35 °C		
Flash point	>= 104,4 °C [Test Method:Closed Cup]		
Evaporation rate	<= 1 Units not available or not applicable. [Ref Std:BUOAC=1]		
Flammability (solid, gas)	Not applicable.		
Flammable Limits(LEL)	No data available.		
Flammable Limits(UEL)	No data available.		
Vapour pressure	<= 186 158,4 Pa		
Vapor Density and/or Relative Vapor Density	No data available.		
Density	1 kg/l		
Density	0,96 g/ml		
Relative density	0,96 [Ref Std:WATER=1]		
Water solubility	Negligible		
Solubility- non-water	No data available.		
Partition coefficient: n-octanol/water	No data available.		
Autoignition temperature	No data available.		
Decomposition temperature	No data available.		
Viscosity/Kinematic Viscosity	100 000 mPa-s - 225 000 mPa-s [Test Method: Brookfield]		
Volatile organic compounds (VOC)	15 g/l [Test Method:calculated SCAQMD rule 443.1]		
Volatile organic compounds (VOC)	1,6 % weight [Test Method:calculated per CARB title 2]		
Percent volatile	1,6 % weight		
VOC less H2O & exempt solvents	15 g/l [Test Method:calculated SCAQMD rule 443.1]		
Molecular weight	No data available.		

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Sparks and/or flames.

10.5 Incompatible materials

Amines.

Strong acids.

Strong bases.

Strong oxidising agents.

10.6 Hazardous decomposition products

SubstanceConditionAldehydes.Not specified.Carbon monoxide.Not specified.

Carbon dioxide. Not specified. Hydrogen Chloride Not specified.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

May be harmful if inhaled. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching. May cause additional health effects (see below).

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Genotoxicity:

Genotoxicity and Mutagenicity: May interact with genetic material and possibly alter gene expression.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5 000 mg/kg
Overall product	Inhalation- Dust/Mist(4 hr)		No data available; calculated ATE >5 - =12,5 mg/l

Overall product	Ingestion		No data available; calculated ATE >5 000 mg/kg
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Dermal	Rat	LD50 > 1 600 mg/kg
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Ingestion	Rat	LD50 > 1 000 mg/kg
Glass, oxide, chemicals	Dermal		LD50 estimated to be > 5 000 mg/kg
Glass, oxide, chemicals	Ingestion		LD50 estimated to be 2 000 - 5 000 mg/kg
Silica, vitreous	Dermal	Rabbit	LD50 > 5 000 mg/kg
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	Ingestion	Rat	LD50 1 000 mg/kg
Silica, vitreous	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0,691 mg/l
Silica, vitreous	Ingestion	Rat	LD50 > 5 110 mg/kg
Acrylate Polymer	Dermal	Rabbit	LD50 > 5~000 mg/kg
Acrylate Polymer	Ingestion	Rat	LD50 > 5 000 mg/kg
Silicon dioxide	Dermal	Rabbit	LD50 > 5000 mg/kg
Silicon dioxide	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0,691 mg/l
Silicon dioxide	Ingestion	Rat	LD50 > 5 110 mg/kg
[3-(2,3-Epoxypropoxy)propyl] trimethoxysilane	Dermal	Rabbit	LD50 4 000 mg/kg
[3-(2,3-Epoxypropoxy)propyl] trimethoxysilane	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 5,3 mg/l
[3-(2,3-Epoxypropoxy)propyl] trimethoxysilane	Ingestion	Rat	LD50 7 010 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Dermal	Rabbit	LD50 > 5 000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0,691 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Rat	LD50 > 5 110 mg/kg
Carbon black	Dermal	Rabbit	LD50 > 3 000 mg/kg
Carbon black	Ingestion	Rat	LD50 > 8 000 mg/kg
Toluene	Dermal	Rat	LD50 12 000 mg/kg
Toluene	Inhalation- Vapor (4 hours)	Rat	LC50 30 mg/l
Toluene	Ingestion	Rat	LD50 5 550 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Rabbit	Mild irritant
Glass, oxide, chemicals	Professio	No significant irritation
	nal	
	judgemen	
	t	
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	In vitro	Irritant
	data	
Silica, vitreous	Rabbit	No significant irritation
Acrylate Polymer	Professio	Minimal irritation
	nal	
	judgemen	
	t	
Silicon dioxide	Rabbit	No significant irritation
[3-(2,3-Epoxypropoxy)propyl] trimethoxysilane	Rabbit	Mild irritant
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
Carbon black	Rabbit	No significant irritation
Toluene	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Rabbit	Moderate irritant
Glass, oxide, chemicals	Professio	No significant irritation
	nal	

	judgemen t	
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	In vitro data	No significant irritation
Silica, vitreous	Rabbit	No significant irritation
Acrylate Polymer	Professio nal judgemen t	Mild irritant
Silicon dioxide	Rabbit	No significant irritation
[3-(2,3-Epoxypropoxy)propyl] trimethoxysilane	Rabbit	Corrosive
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
Carbon black	Rabbit	No significant irritation
Toluene	Rabbit	Moderate irritant

Sensitization:

Skin Sensitisation

Name	Species	Value
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Human and animal	Sensitising
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	similar compoun ds	Sensitising
Silica, vitreous	Human and animal	Not classified
Silicon dioxide	Human and animal	Not classified
[3-(2,3-Epoxypropoxy)propyl] trimethoxysilane	Guinea pig	Not classified
Siloxanes and Silicones, di-Me, reaction products with silica	Human and animal	Not classified
Toluene	Guinea pig	Not classified

Respiratory Sensitisation

Name	Species	Value
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
4,4'-isopropylidenediphenol-epichlorohydrin polymer	In vivo	Not mutagenic
4,4'-isopropylidenediphenol-epichlorohydrin polymer	In Vitro	Some positive data exist, but the data are not sufficient for classification
Glass, oxide, chemicals	In Vitro	Some positive data exist, but the data are not sufficient for classification
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	In Vitro	Mutagenic; structurally related to germ cell mutagens
Silica, vitreous	In Vitro	Not mutagenic
Silicon dioxide	In Vitro	Not mutagenic
[3-(2,3-Epoxypropoxy)propyl] trimethoxysilane	In vivo	Not mutagenic
[3-(2,3-Epoxypropoxy)propyl] trimethoxysilane	In Vitro	Some positive data exist, but the data are not sufficient for classification
Siloxanes and Silicones, di-Me, reaction products with silica	In Vitro	Not mutagenic
Carbon black	In Vitro	Not mutagenic
Carbon black	In vivo	Some positive data exist, but the data are not sufficient for classification

D 0.5.16

Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Glass, oxide, chemicals	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Silica, vitreous	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Silicon dioxide	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
[3-(2,3-Epoxypropoxy)propyl] trimethoxysilane	Dermal	Mouse	Not carcinogenic
Siloxanes and Silicones, di-Me, reaction products with silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Carbon black	Dermal	Mouse	Not carcinogenic
Carbon black	Ingestion	Mouse	Not carcinogenic
Carbon black	Inhalation	Rat	Carcinogenic.
Toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
4,4'-isopropylidenediphenol- epichlorohydrin polymer	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
4,4'-isopropylidenediphenol- epichlorohydrin polymer	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
4,4'-isopropylidenediphenol- epichlorohydrin polymer	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
4,4'-isopropylidenediphenol- epichlorohydrin polymer	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
Silica, vitreous	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silica, vitreous	Inhalation	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Silica, vitreous	Ingestion	Not classified for development	Rat	NOAEL 1 350 mg/kg/day	during organogenesis
Silicon dioxide	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silicon dioxide	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Silicon dioxide	Ingestion	Not classified for development	Rat	NOAEL 1 350 mg/kg/day	during organogenesis
[3-(2,3-Epoxypropoxy)propyl] trimethoxysilane	Ingestion	Not classified for female reproduction	Rat	NOAEL 1 000 mg/kg/day	1 generation
[3-(2,3-Epoxypropoxy)propyl] trimethoxysilane	Ingestion	Not classified for male reproduction	Rat	NOAEL 1 000 mg/kg/day	1 generation
[3-(2,3-Epoxypropoxy)propyl] trimethoxysilane	Ingestion	Not classified for development	Rat	NOAEL 3 000 mg/kg/day	during organogenesis
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction	Ingestion	Not classified for male reproduction	Rat	NOAEL 497	1 generation

P 40 0 4

products with silica				mg/kg/day	
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for development	Rat	NOAEL 1 350 mg/kg/day	during organogenesis
Toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2,3 mg/l	1 generation
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
1,4-Bis[(2,3- epoxypropoxy)methyl]cycl ohexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0,004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
4,4'- isopropylidenediphenol- epichlorohydrin polymer	Dermal	liver	Not classified	Rat	NOAEL 1 000 mg/kg/day	2 years
4,4'- isopropylidenediphenol- epichlorohydrin polymer	Dermal	nervous system	Not classified	Rat	NOAEL 1 000 mg/kg/day	13 weeks
4,4'- isopropylidenediphenol- epichlorohydrin polymer	Ingestion	auditory system heart endocrine system hematopoietic system liver eyes kidney and/or bladder	Not classified	Rat	NOAEL 1 000 mg/kg/day	28 days
Glass, oxide, chemicals	Inhalation	respiratory system	Not classified	Human	NOAEL not available	occupational exposure
Silica, vitreous	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Silicon dioxide	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
[3-(2,3- Epoxypropoxy)propyl] trimethoxysilane	Ingestion	heart endocrine system bone, teeth, nails, and/or hair hematopoietic system liver immune system nervous system kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 1 000 mg/kg/day	28 days
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure

Carbon black	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	auditory system nervous system eyes olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2,3 mg/l	15 months
Toluene	Inhalation	heart liver kidney and/or bladder	Not classified	Rat	NOAEL 11,3 mg/l	15 weeks
Toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1,1 mg/l	4 weeks
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
Toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1,1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic system vascular system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11,3 mg/l	15 weeks
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2 500 mg/kg/day	13 weeks
Toluene	Ingestion	liver kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2 500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks

Aspiration Hazard

ispiration mazara						
Name	Value					
Toluene	Aspiration hazard					

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient—is present below the threshold for labelling, an ingredient—is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

GHS Acute 2: Toxic to aquatic life.

Chronic aquatic hazard:

GHS Chronic 2: Toxic to aquatic life with long lasting effects.

No product test data available.

Material	CAS Nbr	Organism	Туре	Exposure	Test endpoint	Test result
4,4'-	25068-38-6	Activated sludge	Estimated	3 hours	IC50	>100 mg/l
isopropylidenediph enol-						
epichlorohydrin polymer						
4,4'- isopropylidenediph	25068-38-6	Green algae	Estimated	72 hours	EC50	>11 mg/l
enol- epichlorohydrin polymer						
4,4'-	25068-38-6	Rainbow trout	Estimated	96 hours	LC50	2 mg/l
isopropylidenediph enol-	23000 30 0	Rumoow trout	Estimated	70 nours	ECSO	Z mg/i
epichlorohydrin polymer						
4,4'- isopropylidenediph enol- epichlorohydrin	25068-38-6	Water flea	Estimated	48 hours	EC50	1,8 mg/l
polymer 4,4'- isopropylidenediph	25068-38-6	Green algae	Estimated	72 hours	NOEC	4,2 mg/l
enol- epichlorohydrin polymer						
4,4'- isopropylidenediph enol- epichlorohydrin polymer	25068-38-6	Water flea	Estimated	21 days	NOEC	0,3 mg/l
Glass, oxide, chemicals	65997-17-3	Green algae	Experimental	72 hours	EC50	>1 000 mg/l
Glass, oxide, chemicals	65997-17-3	Water flea	Experimental	72 hours	EC50	>1 000 mg/l
Glass, oxide, chemicals	65997-17-3	Zebra Fish	Experimental	96 hours	LC50	>1 000 mg/l
Glass, oxide, chemicals	65997-17-3	Green algae	Experimental	72 hours	NOEC	>=1 000 mg/l
1,4-Bis[(2,3- epoxypropoxy)met hyl]cyclohexane	14228-73-0	Bacteria	Estimated	18 hours	EC50	10 264 mg/l
1,4-Bis[(2,3- epoxypropoxy)met hyl]cyclohexane	14228-73-0	N/A	Experimental	72 hours	EC50	38 mg/l
1,4-Bis[(2,3- epoxypropoxy)met hyl]cyclohexane	14228-73-0	Water flea	Experimental	48 hours	EC50	71 mg/l
1,4-Bis[(2,3- epoxypropoxy)met hyl]cyclohexane	14228-73-0	N/A	Experimental	72 hours	EC10	18 mg/l
Silica, vitreous	60676-86-0	Common Carp	Experimental	72 hours	LC50	>10 000 mg/l
Acrylate Polymer	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Silicon dioxide	7631-86-9	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
[3-(2,3- Epoxypropoxy)pro pyl] trimethoxysilane	2530-83-8	Common Carp	Experimental	96 hours	LC50	55 mg/l
[3-(2,3- Epoxypropoxy)pro pyl]	2530-83-8	Green algae	Experimental	96 hours	ErC50	350 mg/l

trimethoxysilane						
[3-(2,3-	2530-83-8	Invertebrate	Experimental	48 hours	LC50	324 mg/l
Epoxypropoxy)pro			•			
pyl]						
trimethoxysilane						
[3-(2,3-	2530-83-8	Green algae	Experimental	96 hours	NOEC	130 mg/l
Epoxypropoxy)pro						
pyl]						
trimethoxysilane						
[3-(2,3-	2530-83-8	Water flea	Experimental	21 days	NOEC	100 mg/l
Epoxypropoxy)pro						
pyl]						
trimethoxysilane					7.7.	1 100 //
[3-(2,3-	2530-83-8	Activated sludge	Experimental	3 hours	EC50	>100 mg/l
Epoxypropoxy)pro						
pyl] trimethoxysilane						
Siloxanes and	67762-90-7	N/A	Data not available	N/A	N/A	N/A
Silicones, di-Me,	0//02-90-/	IN/A	or insufficient for	IN/A	IN/A	IN/A
reaction products			classification			
with silica			Classification			
Carbon black	1333-86-4	Green algae	Experimental	72 hours	No tox obs at lmt	>100 mg/l
Curbon black	1333 00 4	Green argue	Experimental	72 Hours	of water sol	100 mg/1
Carbon black	1333-86-4	Zebra Fish	Experimental	96 hours	No tox obs at lmt	>100 mg/l
Curbon black	1333 00 1	20014 1 1511	Experimental	yo nours	of water sol	i roo mg r
Carbon black	1333-86-4	Green algae	Experimental	72 hours	No tox obs at lmt	100 mg/l
				1 = 330 033	of water sol	
Carbon black	1333-86-4	Activated sludge	Experimental	3 hours	NOEC	>800 mg/l
Toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5,5 mg/l
Toluene	108-88-3	Grass Shrimp	Experimental	96 hours	LC50	9,5 mg/l
Toluene	108-88-3	Green algae	Experimental	72 hours	EC50	12,5 mg/l
Toluene	108-88-3	Leopard frog	Experimental	9 days	LC50	0,39 mg/l
Toluene	108-88-3	Pink Salmon	Experimental	96 hours	LC50	6,41 mg/l
Toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3,78 mg/l
Toluene	108-88-3	Coho Salmon	Experimental	40 days	NOEC	1,39 mg/l
Toluene	108-88-3	Diatom	Experimental	72 hours	NOEC	10 mg/l
Toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0,74 mg/l
Toluene	108-88-3	Activated sludge	Experimental	12 hours	IC50	292 mg/l
Toluene	108-88-3	Bacteria	Experimental	16 hours	NOEC	29 mg/l
Toluene	108-88-3	Bacteria	Experimental	24 hours	EC50	84 mg/l
Toluene	108-88-3	Redworm	Experimental	28 days	LC50	>150 mg per kg of
1			1			bodyweight
Toluene	108-88-3	Soil microbes	Experimental	28 days	NOEC	<26 mg/kg (Dry Weight)

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
4,4'- isopropylidenediph enol- epichlorohydrin polymer	25068-38-6	Estimated Biodegradation	28 days	BOD	5 %BOD/COD	OECD 301F - Manometric respirometry
4,4'- isopropylidenediph enol- epichlorohydrin polymer	25068-38-6	Estimated Hydrolysis		Hydrolytic half-life	117 hours (t 1/2)	
Glass, oxide, chemicals	65997-17-3	Data not availbl- insufficient	N/A	N/A	N/A	N/A
1,4-Bis[(2,3- epoxypropoxy)met hyl]cyclohexane	14228-73-0	Experimental Biodegradation	28 days	CO2 evolution	1.3 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
Silica, vitreous	60676-86-0	Data not availbl-	N/A	N/A	N/A	N/A

		insufficient				
Acrylate Polymer	Trade Secret	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Silicon dioxide	7631-86-9	Data not availblinsufficient	N/A	N/A	N/A	N/A
[3-(2,3- Epoxypropoxy)pro pyl] trimethoxysilane	2530-83-8	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	37 %removal of DOC	EC C.4.A. DOC Die-Away Test
[3-(2,3- Epoxypropoxy)pro pyl] trimethoxysilane	2530-83-8	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	6.5 hours (t 1/2)	OECD 111 Hydrolysis func of pH
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Data not availblinsufficient	N/A	N/A	N/A	N/A
Carbon black	1333-86-4	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Toluene	108-88-3	Experimental Biodegradation	20 days	BOD	80 %BOD/ThOD	APHA Std Meth Water/Wastewater
Toluene	108-88-3	Experimental Photolysis		Photolytic half-life (in air)	5.2 days (t 1/2)	

12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
4,4'- isopropylidenediph enol- epichlorohydrin polymer	25068-38-6	Estimated Bioconcentration		Log Kow	3.242	
Glass, oxide, chemicals	65997-17-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
1,4-Bis[(2,3- epoxypropoxy)met hyl]cyclohexane	14228-73-0	Experimental Bioconcentration		Log Kow	2.05	
Silica, vitreous	60676-86-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Acrylate Polymer	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Silicon dioxide	7631-86-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
[3-(2,3- Epoxypropoxy)pro pyl] trimethoxysilane	2530-83-8	Experimental Bioconcentration		Log Kow	0.5	Episuite TM
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Carbon black	1333-86-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Toluene	108-88-3	Experimental BCF - Other	72 hours	Bioaccumulation factor	90	
Toluene	108-88-3	Experimental Bioconcentration		Log Kow	2.73	

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product must only be disposed of by an authorized/permitted waste disposal contractor or incinerated in an industrial or commercial facility in the presence of a combustible material.

SECTION 14: Transport Information

Compliance is required to South African Transport Information Road Traffic Act & Regulations and Railroad regulations, IATA Standards for airfreight and Maritime standards for ocean freight.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Industrial Safety and Health Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

Revision information:

Section 12: Component ecotoxicity information information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M South Africa SDSs are available at www.3m.co.za