



Safety Data Sheet

Copyright, 2021, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	16-3092-0	Version number:	7.00
Issue Date:	25/10/2021	Supersedes date:	02/05/2021

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

SECTION 1: Identification

1.1. Product identifier

3M™ Marine Adhesive Sealant 5200, White, PN 06500

Product Identification Numbers

60-9800-4300-8

1.2. Recommended use and restrictions on use

Recommended use

Marine Adhesive Sealant, One-part Polyurethane Adhesive for Marine Applications.

For Industrial or Professional use only.

1.3. Supplier's details

Address: 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113
Telephone: 136 136
E Mail: productinfo.au@mmm.com
Website: www.3m.com.au

1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

Acute Toxicity (inhalation): Category 4.
Respiratory Sensitizer: Category 1A.
Skin Sensitizer: Category 1A.
Carcinogenicity: Category 1B.

2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

Signal word

Danger

Symbols

Exclamation mark | Health Hazard |

Pictograms



Hazard statements

H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H350	May cause cancer.

Precautionary statements

General:

P102	Keep out of reach of children.
------	--------------------------------

Prevention:

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280E	Wear protective gloves.
P284	Wear respiratory protection.

Response:

P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a POISON CENTRE or doctor/physician if you feel unwell.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P342 + P311	If experiencing respiratory symptoms: Call a POISON CENTRE or doctor/physician.
P362 + P364	Take off contaminated clothing and wash it before reuse.

Storage:

P405	Store locked up.
------	------------------

Disposal:

P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.
------	--

2.3. Other assigned/identified product hazards

Persons previously sensitised to isocyanates may develop a cross-sensitisation reaction to other isocyanates. Although titanium dioxide is classified as a carcinogen, exposures associated with this health effect are not expected during normal,

intended use of this product.

2.4. Other hazards which do not result in classification

Toxic to aquatic life with long lasting effects.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
Urethane Polymer	68611-34-7	30 - 60
Talc	14807-96-6	15 - 40
Titanium dioxide	13463-67-7	5 - 10
2-(2-Ethoxyethoxy)ethyl acetate	112-15-2	1 - 5
Fumed silica	112945-52-5	0.5 - 5
Zinc Oxide	1314-13-2	< 2.5
Alkyl Isocyanate Silane	85702-90-5	0.5 - 1.5
m-tolylidene diisocyanate	26471-62-5	< 1
Heptane	142-82-5	< 0.23
(Gamma-Mercaptopropyl)trimethoxysilane	4420-74-0	< 0.19
Hexamethylene Diisocyanate	822-06-0	< 0.015

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic respiratory reaction (difficulty breathing, wheezing, cough, and tightness of chest). Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a carbon dioxide or dry chemical extinguisher to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products**Substance**

Isocyanates
Carbon monoxide.
Carbon dioxide.
Hydrogen cyanide.
Irritant vapours or gases.
Oxides of nitrogen.
Oxides of sulphur.

Condition

During combustion.
During combustion.
During combustion.
During combustion.
During combustion.
During combustion.
During combustion.

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

Hazchem Code: 2Z

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Pour isocyanate decontaminant solution (90% water, 8% concentrated ammonia, 2% detergent) on spill and allow to react for 10 minutes. Or pour water on spill and allow to react for more than 30 minutes. Cover with absorbent material. Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Keep cool. Protect from sunlight. Store away from heat. Store away from amines.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Silicon dioxide	112945-52-	Australia OELs	TWA(respirable fraction)(8	

	5		hours):2 mg/m ³	
Zinc Oxide	1314-13-2	ACGIH	TWA(respirable fraction):2 mg/m ³ ;STEL(respirable fraction):10 mg/m ³	
Zinc Oxide	1314-13-2	Australia OELs	TWA(Inspirable dust)(8 hours):10 mg/m ³ ;TWA(as fume)(8 hours):5 mg/m ³ ;STEL(as fume)(15 minutes):10 mg/m ³	
Titanium dioxide	13463-67-7	ACGIH	TWA:10 mg/m ³	A4: Not class. as human carcin
Titanium dioxide	13463-67-7	Australia OELs	TWA(Inspirable dust)(8 hours):10 mg/m ³	
Heptane	142-82-5	ACGIH	TWA:400 ppm;STEL:500 ppm	
Heptane	142-82-5	Australia OELs	TWA(8 hours):1640 mg/m ³ (400 ppm);STEL(15 minutes):2050 mg/m ³ (500 ppm)	
Talc	14807-96-6	ACGIH	TWA(respirable fraction):2 mg/m ³	A4: Not class. as human carcin
Talc	14807-96-6	Australia OELs	TWA(8 hours):2.5 mg/m ³	
Free isocyanates	26471-62-5	Australia OELs	TWA(as NCO)(8 hours):0.02 mg/m ³ ;STEL(as NCO)(15 minutes):0.07 mg/m ³	
m-tolylidene diisocyanate	26471-62-5	ACGIH	TWA(inhalable fraction and vapor):0.001 ppm;STEL(inhalable fraction and vapor):0.005 ppm	A3: Confirmed animal carcin., Dermal/Respiratory Sensitizer
Free isocyanates	68611-34-7	Australia OELs	TWA(as NCO)(8 hours):0.02 mg/m ³ ;STEL(as NCO)(15 minutes):0.07 mg/m ³	
Hexamethylene Diisocyanate	822-06-0	ACGIH	TWA:0.005 ppm	
Hexamethylene Diisocyanate	822-06-0	Australia OELs	TWA(8 hours):0.02 mg/m ³ ;STEL(15 minutes):0.07 mg/m ³	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

Select and use gloves according to AS/NZ 2161.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

Half facepiece or full facepiece supplied-air respirator.

For questions about suitability for a specific application, consult with your respirator manufacturer.

Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid.
Specific Physical Form:	Paste
Colour	White
Odour	Urethane
Odour threshold	No data available.
pH	No data available.
Melting point/Freezing point	No data available.
Boiling point/Initial boiling point/Boiling range	No data available.
Flash point	No flash point
Evaporation rate	No data available.
Flammability (solid, gas)	Not classified
Flammable Limits(LEL)	No data available.
Flammable Limits(UEL)	No data available.
Vapour pressure	No data available.
Vapor Density and/or Relative Vapor Density	No data available.
Density	1.36 g/ml
Relative density	1.36 [Ref Std: WATER=1]
Water solubility	No data available.
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Autoignition temperature	Not applicable.
Decomposition temperature	No data available.
Viscosity/Kinematic Viscosity	100,000 - 500,000 mPa-s

Volatile organic compounds (VOC)	
Percent volatile	2.9 % weight
VOC less H2O & exempt solvents	40 g/l [<i>Test Method</i> : tested per EPA method 24]
Molecular weight	<i>No data available.</i>

Nanoparticles

This material contains nanoparticles.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3. Conditions to avoid

Heat.

10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.5 Incompatible materials

Reaction with water, alcohols, and amines is not hazardous if container can vent to the atmosphere to prevent pressure buildup.

Amines.

Alcohols.

Water

10.6 Hazardous decomposition products**Substance****Condition**

None known.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects**Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Harmful if inhaled. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic respiratory reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest.

Skin contact

Contact with the skin during product use is not expected to result in significant irritation. Allergic skin reaction (non-photo

induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Additional information:

Persons previously sensitised to isocyanates may develop a cross-sensitisation reaction to other isocyanates.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE10 - 20 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Talc	Dermal		LD50 estimated to be > 5,000 mg/kg
Talc	Ingestion		LD50 estimated to be > 5,000 mg/kg
Titanium dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
Fumed silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Fumed silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Fumed silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Zinc Oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Zinc Oxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.7 mg/l
Zinc Oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
2-(2-Ethoxyethoxy)ethyl acetate	Dermal	Rabbit	LD50 15,000 mg/kg
2-(2-Ethoxyethoxy)ethyl acetate	Ingestion	Rat	LD50 11,000 mg/kg
m-tolylidene diisocyanate	Inhalation-Vapour (4 hours)	Mouse	LC50 0.12 mg/l
m-tolylidene diisocyanate	Dermal	Rabbit	LD50 > 9,400 mg/kg
m-tolylidene diisocyanate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.35 mg/l
m-tolylidene diisocyanate	Ingestion	Rat	LD50 > 5,000 mg/kg
Heptane	Dermal	Rabbit	LD50 3,000 mg/kg
Heptane	Inhalation-Vapour (4 hours)	Rat	LC50 103 mg/l
Heptane	Ingestion	Rat	LD50 > 15,000 mg/kg
(Gamma-Mercaptopropyl)trimethoxysilane	Dermal	Rabbit	LD50 2,270 mg/kg
(Gamma-Mercaptopropyl)trimethoxysilane	Ingestion	Rat	LD50 770 mg/kg

Hexamethylene Diisocyanate	Dermal	Rat	LD50 > 7,000 mg/kg
Hexamethylene Diisocyanate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.124 mg/l
Hexamethylene Diisocyanate	Inhalation-Vapour (4 hours)	Rat	LC50 0.124 mg/l
Hexamethylene Diisocyanate	Ingestion	Rat	LD50 710 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Talc	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation
Fumed silica	Rabbit	No significant irritation
Zinc Oxide	Human and animal	No significant irritation
2-(2-Ethoxyethoxy)ethyl acetate	Human and animal	Minimal irritation
m-tolylidene diisocyanate	Rabbit	Irritant
Heptane	Human	Mild irritant
(Gamma-Mercaptopropyl)trimethoxysilane	Rabbit	No significant irritation
Hexamethylene Diisocyanate	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
Talc	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation
Fumed silica	Rabbit	No significant irritation
Zinc Oxide	Rabbit	Mild irritant
2-(2-Ethoxyethoxy)ethyl acetate	Rabbit	Severe irritant
m-tolylidene diisocyanate	Rabbit	Corrosive
Heptane	Professional judgement	Moderate irritant
(Gamma-Mercaptopropyl)trimethoxysilane	Rabbit	No significant irritation
Hexamethylene Diisocyanate	Rabbit	Corrosive

Skin Sensitisation

Name	Species	Value
Titanium dioxide	Human and animal	Not classified
Fumed silica	Human and animal	Not classified
Zinc Oxide	Guinea pig	Not classified
2-(2-Ethoxyethoxy)ethyl acetate	Human and animal	Not classified
m-tolylidene diisocyanate	Human and animal	Sensitising
(Gamma-Mercaptopropyl)trimethoxysilane	Guinea pig	Sensitising
Hexamethylene Diisocyanate	Multiple animal species	Sensitising

Respiratory Sensitisation

Name	Species	Value
Talc	Human	Not classified
m-tolylidene diisocyanate	Human	Sensitising
Hexamethylene Diisocyanate	Human and animal	Sensitising

Germ Cell Mutagenicity

Name	Route	Value
Talc	In Vitro	Not mutagenic
Talc	In vivo	Not mutagenic

Titanium dioxide	In Vitro	Not mutagenic
Titanium dioxide	In vivo	Not mutagenic
Fumed silica	In Vitro	Not mutagenic
Zinc Oxide	In Vitro	Some positive data exist, but the data are not sufficient for classification
Zinc Oxide	In vivo	Some positive data exist, but the data are not sufficient for classification
2-(2-Ethoxyethoxy)ethyl acetate	In Vitro	Not mutagenic
m-tolylidene diisocyanate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Heptane	In Vitro	Not mutagenic
(Gamma-Mercaptopropyl)trimethoxysilane	In Vitro	Not mutagenic
Hexamethylene Diisocyanate	In Vitro	Not mutagenic
Hexamethylene Diisocyanate	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Talc	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Titanium dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium dioxide	Inhalation	Rat	Carcinogenic.
Fumed silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
m-tolylidene diisocyanate	Inhalation	Human and animal	Not carcinogenic
m-tolylidene diisocyanate	Ingestion	Multiple animal species	Carcinogenic.
Hexamethylene Diisocyanate	Inhalation	Rat	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Talc	Ingestion	Not classified for development	Rat	NOAEL 1,600 mg/kg	during organogenesis
Fumed silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Fumed silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Fumed silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Zinc Oxide	Ingestion	Not classified for reproduction and/or development	Multiple animal species	NOAEL 125 mg/kg/day	premating & during gestation
m-tolylidene diisocyanate	Inhalation	Not classified for female reproduction	Rat	NOAEL 0.002 mg/l	2 generation
m-tolylidene diisocyanate	Inhalation	Not classified for male reproduction	Rat	NOAEL 0.002 mg/l	2 generation
m-tolylidene diisocyanate	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis
Hexamethylene Diisocyanate	Inhalation	Not classified for female reproduction	Rat	NOAEL 0.002 mg/l	7 weeks
Hexamethylene Diisocyanate	Inhalation	Not classified for development	Rat	NOAEL 0.002 mg/l	7 weeks
Hexamethylene Diisocyanate	Inhalation	Not classified for male reproduction	Rat	NOAEL 0.014 mg/l	4 weeks

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
2-(2-Ethoxyethoxy)ethyl acetate	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	not applicable
2-(2-Ethoxyethoxy)ethyl acetate	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	not applicable
m-tolylidene diisocyanate	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	occupational exposure
Heptane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Heptane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Heptane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Hexamethylene Diisocyanate	Inhalation	respiratory irritation	May cause respiratory irritation	Human and animal	NOAEL Not available	
Hexamethylene Diisocyanate	Inhalation	blood	Not classified	Human	NOAEL Not available	occupational exposure

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Talc	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Talc	Inhalation	pulmonary fibrosis respiratory system	Not classified	Rat	NOAEL 18 mg/m ³	113 weeks
Titanium dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Fumed silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Zinc Oxide	Ingestion	nervous system	Not classified	Rat	NOAEL 600 mg/kg/day	10 days
Zinc Oxide	Ingestion	endocrine system hematopoietic system kidney and/or bladder	Not classified	Other	NOAEL 500 mg/kg/day	6 months
2-(2-Ethoxyethoxy)ethyl acetate	Inhalation	respiratory system liver immune system	Not classified	Rat	NOAEL 0.48 mg/l	2 weeks

		kidney and/or bladder				
m-tolylidene diisocyanate	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL 0 mg/l	occupational exposure
Heptane	Inhalation	liver nervous system kidney and/or bladder	Not classified	Rat	NOAEL 12 mg/l	26 weeks
Hexamethylene Diisocyanate	Inhalation	liver kidney and/or bladder	Not classified	Rat	NOAEL 0.002 mg/l	3 weeks
Hexamethylene Diisocyanate	Inhalation	endocrine system	Not classified	Rat	NOAEL 0.0014 mg/l	4 weeks
Hexamethylene Diisocyanate	Inhalation	blood	Not classified	Rat	NOAEL 0.0012 mg/l	2 years
Hexamethylene Diisocyanate	Inhalation	nervous system	Not classified	Rat	NOAEL 0.002 mg/l	7 weeks
Hexamethylene Diisocyanate	Inhalation	heart	Not classified	Rat	NOAEL 0.001 mg/l	90 days

Aspiration Hazard

Name	Value
Heptane	Aspiration hazard

Exposure Levels

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

Interactive Effects

Not determined.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity**Chronic aquatic hazard:**

GHS Chronic 2: Toxic to aquatic life with long lasting effects.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Urethane Polymer	68611-34-7		Data not available or insufficient for classification			N/A
Talc	14807-96-6		Data not available or insufficient for classification			N/A
Titanium dioxide	13463-67-7	Activated sludge	Experimental	3 hours	NOEC	>=1,000 mg/l

Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	EC50	>10,000 mg/l
Titanium dioxide	13463-67-7	Fathead minnow	Experimental	96 hours	LC50	>100 mg/l
Titanium dioxide	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	NOEC	5,600 mg/l
2-(2-Ethoxyethoxy) ethyl acetate	112-15-2	Fathead minnow	Experimental	96 hours	LC50	110 mg/l
2-(2-Ethoxyethoxy) ethyl acetate	112-15-2	Green algae	Experimental	72 hours	EC50	>100 mg/l
2-(2-Ethoxyethoxy) ethyl acetate	112-15-2	Water flea	Experimental	48 hours	EC50	>100 mg/l
2-(2-Ethoxyethoxy) ethyl acetate	112-15-2	Green algae	Experimental	72 hours	NOEC	100 mg/l
Fumed silica	112945-52-5	Green Algae	Experimental	72 hours	EC50	>100 mg/l
Fumed silica	112945-52-5	Water flea	Experimental	24 hours	EC50	>100 mg/l
Fumed silica	112945-52-5	Zebra Fish	Experimental	96 hours	LC50	>100 mg/l
Fumed silica	112945-52-5	Green Algae	Experimental	72 hours	NOEC	60 mg/l
Zinc Oxide	1314-13-2	Activated sludge	Estimated	3 hours	EC50	6.5 mg/l
Zinc Oxide	1314-13-2	Green Algae	Estimated	72 hours	EC50	0.052 mg/l
Zinc Oxide	1314-13-2	Rainbow trout	Estimated	96 hours	LC50	0.21 mg/l
Zinc Oxide	1314-13-2	Water flea	Estimated	48 hours	EC50	0.07 mg/l
Zinc Oxide	1314-13-2	Green Algae	Estimated	72 hours	NOEC	0.006 mg/l
Zinc Oxide	1314-13-2	Water flea	Estimated	7 days	NOEC	0.02 mg/l
Alkyl Isocyanate Silane	85702-90-5		Data not available or insufficient for classification			N/A
m-tolylidene diisocyanate	26471-62-5	Green Algae	Estimated	96 hours	EC50	9.54 mg/l
m-tolylidene diisocyanate	26471-62-5	Water flea	Estimated	48 hours	EC50	1.6 mg/l
m-tolylidene diisocyanate	26471-62-5	Zebra Fish	Estimated	96 hours	LC50	392 mg/l
m-tolylidene diisocyanate	26471-62-5	Crustacea other	Estimated	14 days	NOEC	0.8 mg/l
m-tolylidene diisocyanate	26471-62-5	Medaka	Estimated	28 days	NOEC	40.3 mg/l
Heptane	142-82-5	Water flea	Experimental	48 hours	EC50	1.5 mg/l
Heptane	142-82-5	Water flea	Estimated	21 days	NOEC	0.17 mg/l
(Gamma-Mercaptopropyl)trimethoxysilane	4420-74-0	Green algae	Experimental	72 hours	EC50	267 mg/l
(Gamma-Mercaptopropyl)trimethoxysilane	4420-74-0	Water flea	Experimental	48 hours	EC50	6.7 mg/l

ane						
(Gamma-Mercaptopropyl)trimethoxysilane	4420-74-0	Zebra Fish	Experimental	96 hours	LC50	439 mg/l
Hexamethylene Diisocyanate	822-06-0	Green Algae	Estimated	96 hours	EC50	14.8 mg/l
Hexamethylene Diisocyanate	822-06-0	Medaka	Estimated	96 hours	LC50	71 mg/l
Hexamethylene Diisocyanate	822-06-0	Water flea	Estimated	48 hours	EC50	27 mg/l
Hexamethylene Diisocyanate	822-06-0	Activated sludge	Experimental	3 hours	EC50	842 mg/l
Hexamethylene Diisocyanate	822-06-0	Green Algae	Estimated	72 hours	NOEC	10 mg/l
Hexamethylene Diisocyanate	822-06-0	Water flea	Estimated	21 days	NOEC	4.2 mg/l

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Urethane Polymer	68611-34-7	Data not available-insufficient			N/A	
Talc	14807-96-6	Data not available-insufficient			N/A	
Titanium dioxide	13463-67-7	Data not available-insufficient			N/A	
2-(2-Ethoxyethoxy)ethyl acetate	112-15-2	Experimental Biodegradation	28 days	BOD	100 % BOD/ThBOD	OECD 301C - MITI test (I)
Fumed silica	112945-52-5	Data not available-insufficient			N/A	
Zinc Oxide	1314-13-2	Data not available-insufficient			N/A	
Alkyl Isocyanate Silane	85702-90-5	Data not available-insufficient			N/A	
m-tolylidene diisocyanate	26471-62-5	Experimental Photolysis		Photolytic half-life (in air)	4.27 days (t 1/2)	Non-standard method
m-tolylidene diisocyanate	26471-62-5	Estimated Hydrolysis		Hydrolytic half-life	5 days (t 1/2)	Non-standard method
m-tolylidene diisocyanate	26471-62-5	Estimated Biodegradation	14 days	BOD	0 % weight	OECD 301C - MITI test (I)
Heptane	142-82-5	Experimental Photolysis		Photolytic half-life (in air)	4.24 days (t 1/2)	Non-standard method
Heptane	142-82-5	Experimental Biodegradation	28 days	BOD	101 % BOD/ThBOD	OECD 301C - MITI test (I)
(Gamma-Mercaptopropyl)	4420-74-0	Estimated Hydrolysis		Hydrolytic half-life	53.3 minutes (t 1/2)	Non-standard method

l)trimethoxysilane						
Hexamethylene Diisocyanate	822-06-0	Experimental Hydrolysis		Hydrolytic half-life	5 minutes (t _{1/2})	Non-standard method
Hexamethylene Diisocyanate	822-06-0	Estimated Biodegradation	28 days	BOD	82 % BOD/ThBOD	OECD 301D - Closed bottle test

12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Urethane Polymer	68611-34-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Talc	14807-96-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Experimental BCF-Carp	42 days	Bioaccumulation factor	9.6	Non-standard method
2-(2-Ethoxyethoxy)ethyl acetate	112-15-2	Experimental Bioconcentration		Log Kow	0.74	Non-standard method
Fumed silica	112945-52-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Zinc Oxide	1314-13-2	Experimental BCF-Carp	56 days	Bioaccumulation factor	≤217	OECD 305E - Bioaccumulation flow-through fish test
Alkyl Isocyanate Silane	85702-90-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
m-tolylidene diisocyanate	26471-62-5	Estimated BCF-Carp	42 days	Bioaccumulation factor	<50	OECD 305C-Bioaccumulation degree fish
Heptane	142-82-5	Estimated Bioconcentration		Bioaccumulation factor	105	Estimated: Bioconcentration factor
(Gamma-Mercaptopropyl)trimethoxysilane	4420-74-0	Estimated Bioconcentration		Log Kow	0.25	Estimated: Octanol-water partition coefficient
Hexamethylene Diisocyanate	822-06-0	Estimated Bioconcentration		Log Kow	0.02	Non-standard method

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

Material	CAS Number	Ozone Depletion Potential	Global Warming Potential
(gamma-	4420-74-0	0	

mercaptopropyl)trimethoxy silane			
-------------------------------------	--	--	--

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes.

SECTION 14: Transport Information

Australian Dangerous Goods Code (ADG) - Road/Rail Transport

UN No.: UN3077

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. , (Zinc Oxide)

Class/Division: 9

Sub Risk: Not applicable.

Packing Group: III

Special Instructions: Not restricted, environmentally hazardous substance exception.

Hazchem Code: 2Z

IERG: 47

International Air Transport Association (IATA) - Air Transport

UN No.: UN3077

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. , (Zinc Oxide)

Class/Division: 9

Sub Risk: Not applicable.

Packing Group: III

Special Instructions: Not restricted, as per Special Provision A197, environmentally hazardous substance exception.

International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: UN3077

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. , (Zinc Oxide)

Class/Division: 9

Sub Risk: Not applicable.

Packing Group: III

Marine Pollutant: Not applicable.

Special Instructions: Not restricted, as per IMDG code 2.10.2.7, marine pollutant exception.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Australian Inventory Status:

An ingredient(s) in this product is being introduced under the no unreasonable risk non-cosmetic (<100 Kg) exemption provisions specified in Section 21(4) of the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

Poison Schedule: This product is intended for Industrial or Professional Use only and therefore is not packaged and labelled in accordance with the requirements of the Standard for the Uniform Scheduling of Medicines and Poisons.

SECTION 16: Other information

Revision information:

Complete document review.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au