



## Safety Data Sheet

Copyright, 2021, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	18-5135-1	<b>Version number:</b>	5.00
<b>Issue Date:</b>	16/06/2021	<b>Supersedes date:</b>	03/08/2016

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Notebook Screen Cleaning Wipes #CL630

#### Product Identification Numbers

70-0051-5279-1

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Office cleaner, Premoistened wipes for cleaning computer equipment

For Industrial or Consumer Use.

#### 1.3. Supplier's details

**Address:** 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113  
**Telephone:** 136 136  
**E Mail:** productinfo.au@mmm.com  
**Website:** www.3m.com.au

#### 1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

### SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

#### 2.1. Classification of the substance or mixture

Flammable liquid: Category 3.

Serious Eye Damage/Irritation: Category 2.

#### 2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product

label.

**Signal word**

Warning

**Symbols**

Flame | Exclamation mark |

**Pictograms**



**Hazard statements**

H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

**Precautionary statements**

**Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical, ventilating and lighting equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P264 Wash thoroughly after handling.

P280E Wear protective gloves.

**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 IF eye irritation persists: Get medical advice/attention.

P370 + P378 In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

**Storage:**

P403 + P235 Store in a well-ventilated place. Keep cool.

**Disposal:**

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**2.3. Other assigned/identified product hazards**

Repeated exposure may cause skin dryness or cracking.

**2.4. Other hazards which do not result in classification**

None known.

**SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
Water	7732-18-5	80 - 95
Isopropyl Alcohol	67-63-0	10 - 20
2-Methoxymethylethoxypropanol	34590-94-8	0 - 2
Ammonia	7664-41-7	0 - 2
Ethoxylated C12-C14 Alcohols	68439-50-9	0 - 2

**SECTION 4: First aid measures****4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin contact**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye contact**

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

**If swallowed**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

**SECTION 5: Fire-fighting measures****5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

**5.2. Special hazards arising from the substance or mixture**

Closed containers exposed to heat from fire may build pressure and explode.

**5.3. Special protective actions for fire-fighters**

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

**Hazchem Code:** 1Z

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. **WARNING!** A motor could be an ignition source and

could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

## 6.2. Environmental precautions

Avoid release to the environment.

## 6.3. Methods and material for containment and cleaning up

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Avoid eye contact. Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapour accumulation.

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Protect from sunlight. Store away from heat. Store away from acids. Store away from oxidising agents.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
2-Methoxymethylethoxypropanol	34590-94-8	ACGIH	TWA:100 ppm;STEL:150 ppm	Danger of cutaneous absorption
2-Methoxymethylethoxypropanol	34590-94-8	Australia OELs	TWA(8 hours):308 mg/m3(50 ppm)	SKIN
Isopropyl Alcohol	67-63-0	ACGIH	TWA:200 ppm;STEL:400 ppm	A4: Not class. as human carcin
Isopropyl Alcohol	67-63-0	Australia OELs	TWA(8 hours):983 mg/m3(400 ppm);STEL(15 minutes):1230 mg/m3(500 ppm)	
Ammonia	7664-41-7	ACGIH	TWA:25 ppm;STEL:35 ppm	
Ammonia	7664-41-7	Australia OELs	TWA(8 hours):17 mg/m3(25 ppm);STEL(15 minutes):24 mg/m3(35 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling  
 Sen: Sensitiser  
 Sk: Absorption through the skin may be a significant source of exposure.

**8.2. Exposure controls**

**8.2.1. Engineering controls**

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

**8.2.2. Personal protective equipment (PPE)**

**Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:  
 Indirect vented goggles.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

**Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Nitrile rubber.

Select and use gloves according to AS/NZ 2161.

**Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours

For questions about suitability for a specific application, consult with your respirator manufacturer.

Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

<b>Physical state</b>	Liquid.
<b>Specific Physical Form:</b>	paper tissues saturated with liquid
<b>Colour</b>	White
<b>Odour</b>	Alcohol
<b>Odour threshold</b>	<i>No data available.</i>
<b>pH</b>	<i>No data available.</i>
<b>Melting point/Freezing point</b>	<i>No data available.</i>
<b>Boiling point/Initial boiling point/Boiling range</b>	100 °C
<b>Flash point</b>	56 °C [ <i>Test Method:Estimated</i> ]

Evaporation rate	<i>No data available.</i>
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	2 % volume
Flammable Limits(UEL)	12 % volume
Vapour pressure	5,732.8 Pa [ @ 20 °C ]
Vapor Density and/or Relative Vapor Density	<i>No data available.</i>
Density	<i>No data available.</i>
Relative density	1 [Ref Std: WATER=1]
Water solubility	Complete
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
Viscosity/Kinematic Viscosity	<i>No data available.</i>
Volatile organic compounds (VOC)	
Percent volatile	
VOC less H2O & exempt solvents	

**Nanoparticles**

This material does not contain nanoparticles.

## SECTION 10: Stability and reactivity

**10.1 Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

**10.2 Chemical stability**

Stable.

**10.3. Conditions to avoid**

Sparks and/or flames.

**10.4. Possibility of hazardous reactions**

Hazardous polymerisation will not occur.

**10.5 Incompatible materials**

Not determined

**10.6 Hazardous decomposition products****Substance**

Carbon monoxide.

Carbon dioxide.

**Condition**

Not specified.

Not specified.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

**11.1 Information on Toxicological effects****Signs and Symptoms of Exposure**

**Based on test data and/or information on the components, this material may produce the following health effects:**

#### **Inhalation**

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

#### **Skin contact**

Dermal Defatting Prolonged or repeated exposure may cause: Dermal Defatting: Signs/symptoms may include localized redness, itching, drying and cracking of skin. Dermal Defatting: Signs/symptoms may include localised redness, itching, drying and cracking of skin.

#### **Eye contact**

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

#### **Ingestion**

Physical Blockage: Signs/symptoms may include cramping, abdominal pain, and constipation. Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

#### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### **Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Isopropyl Alcohol	Dermal	Rabbit	LD50 12,870 mg/kg
Isopropyl Alcohol	Inhalation-Vapour (4 hours)	Rat	LC50 72.6 mg/l
Isopropyl Alcohol	Ingestion	Rat	LD50 4,710 mg/kg
Ammonia	Inhalation-Gas (4 hours)	Rat	LC50 2,000 ppm
ETHOXYLATED C12-C14 ALCOHOLS	Dermal	Rabbit	LD50 491 mg/kg
ETHOXYLATED C12-C14 ALCOHOLS	Ingestion	Rat	LD50 687 mg/kg
2-Methoxymethylethoxypropanol	Dermal	Rabbit	LD50 > 19,000 mg/kg
2-Methoxymethylethoxypropanol	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 50 mg/l
2-Methoxymethylethoxypropanol	Ingestion	Rat	LD50 5,180 mg/kg

ATE = acute toxicity estimate

#### **Skin Corrosion/Irritation**

Name	Species	Value
Isopropyl Alcohol	Multiple animal species	No significant irritation
Ammonia	Human and animal	Corrosive
2-Methoxymethylethoxypropanol	Human and animal	No significant irritation

#### **Serious Eye Damage/Irritation**

Name	Species	Value
------	---------	-------

Isopropyl Alcohol	Rabbit	Severe irritant
Ammonia	Human and animal	Corrosive
2-Methoxymethylethoxypropanol	Rabbit	Mild irritant

**Skin Sensitisation**

Name	Species	Value
Isopropyl Alcohol	Guinea pig	Not classified
2-Methoxymethylethoxypropanol	Human	Not classified

**Respiratory Sensitisation**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
Isopropyl Alcohol	In Vitro	Not mutagenic
Isopropyl Alcohol	In vivo	Not mutagenic
2-Methoxymethylethoxypropanol	In Vitro	Not mutagenic

**Carcinogenicity**

Name	Route	Species	Value
Isopropyl Alcohol	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Isopropyl Alcohol	Ingestion	Not classified for development	Rat	NOAEL 400 mg/kg/day	during organogenesis
Isopropyl Alcohol	Inhalation	Not classified for development	Rat	LOAEL 9 mg/l	during gestation
2-Methoxymethylethoxypropanol	Inhalation	Not classified for development	Multiple animal species	NOAEL 1.82 mg/l	during organogenesis

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Isopropyl Alcohol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Isopropyl Alcohol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Isopropyl Alcohol	Inhalation	auditory system	Not classified	Guinea pig	NOAEL 13.4 mg/l	24 hours
Isopropyl Alcohol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Ammonia	Inhalation	respiratory	May cause	Human	NOAEL not	



		irritation	respiratory irritation		available	
2-Methoxymethylethoxypropyl alcohol	Dermal	central nervous system depression	Not classified	Rabbit	NOAEL 2,850 mg/kg	
2-Methoxymethylethoxypropyl alcohol	Inhalation	central nervous system depression	Not classified	Rat	LOAEL 3.07 mg/l	7 hours
2-Methoxymethylethoxypropyl alcohol	Ingestion	central nervous system depression	Not classified	Rat	LOAEL 5,000 mg/kg	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Isopropyl Alcohol	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 12.3 mg/l	24 months
Isopropyl Alcohol	Inhalation	nervous system	Not classified	Rat	NOAEL 12 mg/l	13 weeks
Isopropyl Alcohol	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 400 mg/kg/day	12 weeks
2-Methoxymethylethoxypropyl alcohol	Dermal	kidney and/or bladder   heart   endocrine system   hematopoietic system   liver   respiratory system	Not classified	Rabbit	NOAEL 9,500 mg/kg/day	90 days
2-Methoxymethylethoxypropyl alcohol	Inhalation	heart   hematopoietic system   liver   immune system   nervous system   eyes   kidney and/or bladder	Not classified	Rat	NOAEL 1.21 mg/l	90 days
2-Methoxymethylethoxypropyl alcohol	Ingestion	liver   heart   endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   immune system   nervous system   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Exposure Levels**

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

**Interactive Effects**

Not determined.

## SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

### 12.1. Toxicity

#### Acute aquatic hazard:

Not acutely toxic to aquatic life by GHS criteria.

#### Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Isopropyl Alcohol	67-63-0	Bacteria	Experimental	16 hours	LOEC	1,050 mg/l
Isopropyl Alcohol	67-63-0	Crustacea	Experimental	24 hours	LC50	>10,000 mg/l
Isopropyl Alcohol	67-63-0	Green Algae	Experimental	72 hours	EC50	>1,000 mg/l
Isopropyl Alcohol	67-63-0	Medaka	Experimental	96 hours	LC50	>100 mg/l
Isopropyl Alcohol	67-63-0	Water flea	Experimental	48 hours	EC50	>1,000 mg/l
Isopropyl Alcohol	67-63-0	Green algae	Experimental	72 hours	NOEC	1,000 mg/l
Isopropyl Alcohol	67-63-0	Water flea	Experimental	21 days	NOEC	100 mg/l
2-Methoxymethyl ethoxypropanol	34590-94-8	Bacteria	Experimental	18 hours	EC10	4,168 mg/l
2-Methoxymethyl ethoxypropanol	34590-94-8	Fathead minnow	Experimental	96 hours	LC50	>10,000 mg/l
2-Methoxymethyl ethoxypropanol	34590-94-8	Green Algae	Experimental	72 hours	EC50	>969 mg/l
2-Methoxymethyl ethoxypropanol	34590-94-8	Water flea	Experimental	48 hours	LC50	1,919 mg/l
2-Methoxymethyl ethoxypropanol	34590-94-8	Green Algae	Experimental	72 hours	EC10	133 mg/l

Ammonia	7664-41-7	Algae or other aquatic plants	Estimated	72 days	IC50	10.4 mg/l
Ammonia	7664-41-7	Fish	Estimated	96 hours	LC50	1.7 mg/l
Ammonia	7664-41-7	Grass Shrimp	Estimated	48 hours	EC50	9.69 mg/l
Ammonia	7664-41-7	Algae or other aquatic plants	Estimated	72 hours	NOEC	0.73 mg/l
Ammonia	7664-41-7	Bluegill	Estimated	32 days	NOEC	1.56 mg/l
Ammonia	7664-41-7	Water flea	Estimated	21 days	NOEC	18.6 mg/l
ETHOXYLATED C12-C14 ALCOHOLS	68439-50-9	Bacteria	Experimental	16.9 hours	EC50	>10,000 mg/l
ETHOXYLATED C12-C14 ALCOHOLS	68439-50-9	Common Carp	Experimental	96 hours	LC50	0.8 mg/l
ETHOXYLATED C12-C14 ALCOHOLS	68439-50-9	Green algae	Experimental	72 hours	EC50	0.57 mg/l
ETHOXYLATED C12-C14 ALCOHOLS	68439-50-9	Water flea	Experimental	48 hours	EC50	0.53 mg/l
ETHOXYLATED C12-C14 ALCOHOLS	68439-50-9	Water flea	Estimated	21 days	NOEC	0.77 mg/l
ETHOXYLATED C12-C14 ALCOHOLS	68439-50-9	Green algae	Experimental	72 hours	NOEC	0.035 mg/l

## 12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Isopropyl Alcohol	67-63-0	Experimental Biodegradation	14 days	BOD	86 % BOD/ThBOD	OECD 301C - MITI test (I)
2-Methoxymethyl ethoxypropanol	34590-94-8	Experimental Biodegradation	28 days	BOD	75 % BOD/ThBOD	OECD 301F - Manometric respirometry
Ammonia	7664-41-7	Experimental Photolysis		Photolytic half-life (in air)	201 days (t 1/2)	Non-standard method
ETHOXYLATED C12-C14 ALCOHOLS	68439-50-9	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	100 % weight	Non-standard method

## 12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Isopropyl Alcohol	67-63-0	Experimental Bioconcentration		Log Kow	0.05	Non-standard method
2-Methoxymethyl ethoxypropanol	34590-94-8	Experimental Bioconcentration		Log Kow	0.0061	Non-standard method
Ammonia	7664-41-7	Experimental Bioconcentration		Log Kow	-1.14	Non-standard method

		on				
ETHOXYLAT ED C12-C14 ALCOHOLS	68439-50-9	Experimental BCF-Carp	72 hours	Bioaccumulatio n factor	310	Non-standard method

**12.4. Mobility in soil**

Please contact manufacturer for more details

**12.5 Other adverse effects**

No information available.

## SECTION 13: Disposal considerations

**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility.

## SECTION 14: Transport Information

**Australian Dangerous Goods Code (ADG) - Road/Rail Transport**

UN No.: UN3175

**Proper shipping name:** SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. , ( Isopropyl Alcohol )

**Class/Division:** 4.1

**Sub Risk:** Not applicable.

**Packing Group:** II

**Special Instructions:** Australian Dangerous Goods Code: Not subject to this code as per Special Provision 216

**Hazchem Code:** 1Z

**IERG:** 20

**International Air Transport Association (IATA) - Air Transport**

UN No.: UN3175

**Proper shipping name:** SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. , ( Isopropyl Alcohol )

**Class/Division:** 4.1

**Sub Risk:** Not applicable.

**Packing Group:** II

**Special Instructions:** Not restricted, as per Special Provision A46.

**International Maritime Dangerous Goods Code (IMDG)- Marine Transport**

UN No.: UN3175

**Proper shipping name:** SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. , ( Isopropyl Alcohol )

**Class/Division:** 4.1

**Sub Risk:** Not applicable.

**Packing Group:** II

**Marine Pollutant:** Not applicable.

**Special Instructions:** Not restricted, as per Special Provision 216.

## SECTION 15: Regulatory information

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Australian Inventory Status:**

The chemical components contained within this product are listed on the Australian Inventory of Chemical Substances and are in compliance with the requirements of the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

**Poison Schedule:** This product is not a scheduled poison according to the criteria of the Standard for the Uniform Scheduling of Medicines and Poisons.

## **SECTION 16: Other information**

**Revision information:**

Complete document review.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

**3M Australia SDSs are available at [www.3m.com.au](http://www.3m.com.au)**