

# Safety Data Sheet

Copyright,2024, 3M Company.All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	18-1161-1	Version number:	5.04
Issue Date:	11/03/2024	Supersedes date:	03/03/2024

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

# **IDENTIFICATION:**

### 1.1. Product identifier

3M<sup>™</sup> RELYX<sup>™</sup> UNICEM<sup>™</sup> Aplicap/Maxicap

### **Product Identification Numbers**

70-2011-1559-2	70-2011-1562-6	70-2011-1563-4	70-2011-1564-2	70-2011-1565-9
70-2011-1566-7	70-2011-1567-5	70-2011-1568-3	70-2011-1980-0	70-2011-1981-8
70-2011-1982-6	70-2011-1983-4	UU-0104-3488-2	UU-0104-3489-0	UU-0104-3490-8
UU-0104-3493-2	UU-0104-3520-2	UU-0104-3521-0	UU-0104-3522-8	UU-0104-3523-6
UU-0104-3525-1	UU-0104-3526-9			

### 1.2. Recommended use and restrictions on use

### **Recommended use**

Dental Product, Dental univeral luting material.

### Restrictions on use

For use by dental professionals only.

### 1.3. Supplier's details

Address:	3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113
Telephone:	136 136
E Mail:	productinfo.au@mmm.com
Website:	www.3m.com.au

**1.4. Emergency telephone number Company Emergency Hotline:**EMERGENCY: 1800 097 146 (Australia only)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the SDSs for components of this product are:

17-9608-5, 18-0262-8

One or more components of this KIT is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

# **TRANSPORT INFORMATION**

The Dangerous Goods Classification for the complete Kit is provided below.

UN No.: UN3082 Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., (Acetic Acid, Copper (2+) Salt, Monohydrate) Class/Division: 9 Packing Group: III Marine Pollutant:Not applicable.

Hazchem Code: -3Z IERG: 47

Australian Dangerous Goods Code (ADG) - Road/Rail Transport Special Instructions: Not restricted, environmentally hazardous substance exception.

# International Air Transport Association (IATA)- Air Transport

Special Instructions: Not restricted, as per Special Provision A197, environmentally hazardous substance exception.

# International Maritime Dangerous Goods Code (IMDG)- Marine Transport

Special Instructions: Not restricted, as per IMDG code 2.10.2.7, marine pollutant exception.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

## 3M Australia SDSs are available at www.3m.com.au



# Safety Data Sheet

Copyright,2021, 3M Company.All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	18-0262-8	Version number:	5.00
Issue Date:	15/09/2021	Supersedes date:	01/02/2021

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

# **SECTION 1: Identification**

### 1.1. Product identifier

3M<sup>™</sup> RelyX<sup>™</sup> Unicem Aplicap<sup>™</sup>/Maxicap<sup>™</sup> Powder

### 1.2. Recommended use and restrictions on use

### **Recommended use**

Dental Product, Universal luting material.

### Restrictions on use

For use by dental professionals only.

### 1.3. Supplier's details

Address:3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113Telephone:136 136E Mail:productinfo.au@mmm.comWebsite:www.3m.com.au

## **1.4. Emergency telephone number**

EMERGENCY: 1800 097 146 (Australia only)

# **SECTION 2: Hazard identification**

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

## 2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 2.

## 2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

### Signal word

Warning

**Symbols** Exclamation mark |

### **Pictograms**



Hazard statements H319

Causes serious eye irritation.

### **Precautionary statements**

**Prevention:** P264

Wash thoroughly after handling.

#### **Response:** P305 + P351 + P338

P337 + P313

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF eye irritation persists: Get medical advice/attention.

# 2.3. Other assigned/identified product hazards

None known.

### 2.4. Other hazards which do not result in classification

May be harmful if swallowed. Causes mild skin irritation.

# **SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
Glass powder (65997-17-3), surface	None	85 - 95
modified with 2-propenoic acid, 2		
methyl3-(trimethoxysilyl)propyl ester		
(2530-85-0), bulk material		
2-Propenoic acid, 2-methyl-, 3-	122334-95-6	1 - 10
(trimetoxysilyl)propyl ester, hydrolysis		
products with silica		
Subtituted pyrimidine	72846-00-5	1 - 5
Calcium dihydroxide	1305-62-0	< 3
Sodium Persulphate	7775-27-1	< 1
Titanium dioxide	13463-67-7	< 0.5

# **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

### Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

### Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

#### **4.3. Indication of any immediate medical attention and special treatment required** Not applicable

Not applicable

# **SECTION 5: Fire-fighting measures**

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

## Hazardous Decomposition or By-Products

<u>Substance</u> None known. <u>Condition</u> During combustion.

### 5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

# **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

## **6.2.** Environmental precautions

Avoid release to the environment.

# 6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Avoid breathing

dust/fume/gas/mist/vapours/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not get in eyes. Use personal protective equipment (eg. gloves, respirators...) as required. A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. If product contacts glove, remove and discard glove,

wash hands immediately with soap and water and then re-glove.

### 7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

# **SECTION 8: Exposure controls/personal protection**

### **8.1 Control parameters**

### **Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Calcium dihydroxide	1305-62-0	ACGIH	TWA:5 mg/m3	
Calcium dihydroxide	1305-62-0	Australia OELs	TWA(8 hours):5 mg/m3	
Titanium dioxide	13463-67-7	ACGIH	TWA:10 mg/m <sup>3</sup>	A4: Not class. as human
				carcin
Titanium dioxide	13463-67-7	Australia OELs	TWA(Inspirable dust)(8	
			hours):10 mg/m3	
PERSULFATE COMPOUNDS	7775-27-1	ACGIH	TWA(as persulfate):0.1 mg/m3	
Sodium Persulphate	7775-27-1	Australia OELs	Peak limit:0.01 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

## 8.2. Exposure controls

## 8.2.1. Engineering controls

Use in a well-ventilated area.

## 8.2.2. Personal protective equipment (PPE)

## Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Safety glasses with side shields.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

## Skin/hand protection

See Section 7.1 for additional information on skin protection.

## **Respiratory protection**

None required.

# **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state	Solid.
Specific Physical Form:	Powder
Colour	White-Beige
Odour	Odourless
Odour threshold	No data available.
рН	Not applicable.
Melting point/Freezing point	No data available.
Boiling point/Initial boiling point/Boiling range	Not applicable.
Flash point	No flash point
Evaporation rate	Not applicable.
Flammability (solid, gas)	Not classified
Flammable Limits(LEL)	No data available.
Flammable Limits(UEL)	No data available.
Vapour pressure	Not applicable.
Vapor Density and/or Relative Vapor Density	Not applicable.
Density	> 1 g/ml
Relative density	No data available.
Water solubility	Negligible
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Autoignition temperature	Not applicable.
Decomposition temperature	No data available.
Viscosity/Kinematic Viscosity	Not applicable.
Volatile organic compounds (VOC)	Not applicable.
Percent volatile	No data available.
VOC less H2O & exempt solvents	No data available.
Molecular weight	No data available.

# Nanoparticles

This material does not contain nanoparticles.

# **SECTION 10: Stability and reactivity**

## **10.1 Reactivity**

This material is considered to be non reactive under normal use conditions

# 10.2 Chemical stability

Stable.

# 10.3. Conditions to avoid

None known.

**10.4. Possibility of hazardous reactions** Hazardous polymerisation will not occur.

### **10.5 Incompatible materials** None known.

10.6 Hazardous decomposition products <u>Substance</u>

**Condition** 

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

**11.1 Information on Toxicological effects** 

### Signs and Symptoms of Exposure

### Based on test data and/or information on the components, this material may produce the following health effects:

### Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic respiratory reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest. May cause additional health effects (see below).

### Skin contact

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

### Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

### Ingestion

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

## **Additional Health Effects:**

## **Carcinogenicity:**

Contains a chemical or chemicals which can cause cancer.

### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

### Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE2,000 - 5,000 mg/kg
Glass powder (65997-17-3), surface modified with 2-propenoic acid, 2 methyl3-(trimethoxysilyl)propyl ester (2530-85-0), bulk material	Dermal		LD50 estimated to be > 5,000 mg/kg
Glass powder (65997-17-3), surface modified with 2-propenoic acid, 2 methyl3-(trimethoxysilyl)propyl ester (2530-85-0), bulk material	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
2-Propenoic acid, 2-methyl-, 3- (trimetoxysilyl)propyl ester,	Dermal	Rabbit	LD50 > 5,000 mg/kg

hydrolysis products with silica			
2-Propenoic acid, 2-methyl-, 3- (trimetoxysilyl)propyl ester, hydrolysis products with silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
2-Propenoic acid, 2-methyl-, 3- (trimetoxysilyl)propyl ester, hydrolysis products with silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Calcium dihydroxide	Dermal	Rabbit	LD50 > 2,500 mg/kg
Calcium dihydroxide	Ingestion	Rat	LD50 7,340 mg/kg
Subtituted pyrimidine	Dermal	Professional judgement	LD50 estimated to be 2,000 - 5,000 mg/kg
Subtituted pyrimidine	Ingestion	Rat	LD50 > 2,000 mg/kg
Sodium Persulphate	Dermal	Rabbit	LD50 > 10,000 mg/kg
Sodium Persulphate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 47.93 mg/l
Sodium Persulphate	Ingestion	Rat	LD50 895 mg/kg
Titanium dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg

 $\overline{\text{ATE}}$  = acute toxicity estimate

## **Skin Corrosion/Irritation**

Name	Species	Value
Glass powder (65997-17-3), surface modified with 2-propenoic acid, 2 methyl3- (trimethoxysilyl)propyl ester (2530-85-0), bulk material	Professional judgement	No significant irritation
2-Propenoic acid, 2-methyl-, 3- (trimetoxysilyl)propyl ester, hydrolysis products with silica	Rabbit	No significant irritation
Calcium dihydroxide	Human	Corrosive
Titanium dioxide	Rabbit	No significant irritation

# Serious Eye Damage/Irritation

Name	Species	Value
Glass powder (65997-17-3), surface modified with	Professional judgement	No significant irritation
2-propenoic acid, 2 methyl3-		
(trimethoxysilyl)propyl ester (2530-85-0), bulk		
material		
2-Propenoic acid, 2-methyl-, 3-	Rabbit	No significant irritation
(trimetoxysilyl)propyl ester, hydrolysis products		
with silica		
Calcium dihydroxide	Rabbit	Corrosive
Titanium dioxide	Rabbit	No significant irritation

## **Skin Sensitisation**

Name	Species	Value
2-Propenoic acid, 2-methyl-, 3- (trimetoxysilyl)propyl ester, hydrolysis products with silica	Human and animal	Not classified
Subtituted pyrimidine	Mouse	Not classified
Titanium dioxide	Human and animal	Not classified

# **Respiratory Sensitisation**

For the component/components, either no data are currently available or the data are not sufficient for classification.

### Germ Cell Mutagenicity

Name	Route	Value
2-Propenoic acid, 2-methyl-, 3- (trimetoxysilyl)propyl ester, hydrolysis products with silica	In Vitro	Not mutagenic
Subtituted pyrimidine	In Vitro	Not mutagenic
Titanium dioxide	In Vitro	Not mutagenic
Titanium dioxide	In vivo	Not mutagenic

## Carcinogenicity

Name	Route	Species	Value
2-Propenoic acid, 2-methyl-, 3- (trimetoxysilyl)propyl ester, hydrolysis products with silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Titanium dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium dioxide	Inhalation	Rat	Carcinogenic.

# **Reproductive Toxicity**

# **Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	<b>Exposure Duration</b>
2-Propenoic acid, 2- methyl-, 3- (trimetoxysilyl)propy l ester, hydrolysis products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
2-Propenoic acid, 2- methyl-, 3- (trimetoxysilyl)propy l ester, hydrolysis products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
2-Propenoic acid, 2- methyl-, 3- (trimetoxysilyl)propy l ester, hydrolysis products with silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

# Target Organ(s)

# Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Calcium dihydroxide	Inhalation	respiratory irritation	May cause respiratory irritation	Human	LOAEL 2.5 mg/m3	20 minutes
Subtituted pyrimidine	Ingestion	nervous system	Not classified	Rat	NOAEL 2,000 mg/kg	

# Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
2-Propenoic acid, 2- methyl-, 3- (trimetoxysily	Inhalation	respiratory system   silicosis	Not classified	Human	NOAEL Not available	occupational exposure

l)propyl ester, hydrolysis products with silica						
Titanium dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure

## Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

### **Exposure Levels**

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

## Interactive Effects

Not determined.

# **SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

### Acute aquatic hazard:

Not acutely toxic to aquatic life by GHS criteria.

## Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available.

Material	CAS Number	Organism	Туре	Exposure	Test endpoint	Test result
Glass powder	None		Data not			N/A
(65997-17-3),			available or			
surface			insufficient for			
modified with			classification			
2-propenoic						
acid, 2						
methyl3-						
(trimethoxysily						
l)propyl ester						
(2530-85-0),						
bulk material						
2-Propenoic	122334-95-6	Activated	Estimated	3 hours	NOEC	>=1,000 mg/l
acid, 2-methyl-,		sludge				
3-		_				
(trimetoxysilyl)						
propyl ester,						

hydrolysis						
products with						
silica						
2-Propenoic	122334-95-6		Data not			N/A
acid, 2-methyl-,			available or			
3-			insufficient for			
(trimetoxysilyl)			classification			
propyl ester,						
hydrolysis						
products with						
silica						
Subtituted	72846-00-5		Data not			N/A
pyrimidine			available or			
			insufficient for			
			classification			
Calcium	1305-62-0	Fathead	Estimated	96 hours	LC50	4,630 mg/l
dihydroxide		minnow				
Calcium	1305-62-0	Green Algae	Estimated	72 hours	EC50	>4,000 mg/l
dihydroxide						
Calcium	1305-62-0	Water flea	Estimated	48 hours	EC50	2,400 mg/l
dihydroxide						
Sodium	7775-27-1	Algae other	Estimated	72 hours	EC50	320 mg/l
Persulphate						
Sodium	7775-27-1	Copepods	Estimated	48 hours	EC50	21.22 mg/l
Persulphate						
Sodium	7775-27-1	Rainbow trout	Estimated	96 hours	LC50	76.3 mg/l
Persulphate						
Sodium	7775-27-1	Algae other	Estimated	72 hours	NOEC	32 mg/l
Persulphate						
Titanium	13463-67-7	Activated	Experimental	3 hours	NOEC	>=1,000 mg/l
dioxide		sludge				
Titanium	13463-67-7	Diatom	Experimental	72 hours	EC50	>10,000 mg/l
dioxide						
Titanium	13463-67-7	Fathead	Experimental	96 hours	LC50	>100 mg/l
dioxide		minnow				
Titanium	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
dioxide						
Titanium	13463-67-7	Diatom	Experimental	72 hours	NOEC	5,600 mg/l
dioxide						

# 12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Glass powder	None	Data not			N/A	
(65997-17-3),		available-				
surface		insufficient				
modified with						
2-propenoic						
acid, 2						
methyl3-						
(trimethoxysily						
l)propyl ester						
(2530-85-0),						
bulk material						
2-Propenoic	122334-95-6	Data not			N/A	

acid, 2-methyl-, 3- (trimetoxysilyl) propyl ester, hydrolysis products with silica		available- insufficient				
Subtituted pyrimidine	72846-00-5	Estimated Photolysis		Photolytic half- life (in air)	1.48 days (t 1/2)	Non-standard method
Subtituted pyrimidine	72846-00-5	Experimental Biodegradation	28 days	CO2 evolution		OECD 301B - Modified sturm or CO2
Calcium dihydroxide	1305-62-0	Data not available- insufficient			N/A	
Sodium Persulphate	7775-27-1	Data not available- insufficient			N/A	
Titanium dioxide	13463-67-7	Data not available- insufficient			N/A	

# 12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Glass powder (65997-17-3), surface modified with 2-propenoic acid, 2 methyl3- (trimethoxysily l)propyl ester (2530-85-0), bulk material	None	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
2-Propenoic acid, 2-methyl-, 3- (trimetoxysilyl) propyl ester, hydrolysis products with silica		Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Subtituted pyrimidine	72846-00-5	Experimental Bioconcentrati on		Log Kow	2.57	Non-standard method
Calcium dihydroxide	1305-62-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Sodium Persulphate	7775-27-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

Titanium	13463-67-7	Experimental	42 days	Bioaccumulatio	9.6	Non-standard method
dioxide		BCF-Carp	-	n factor		

# 12.4. Mobility in soil

Please contact manufacturer for more details

# 12.5 Other adverse effects

No information available.

# **SECTION 13: Disposal considerations**

## 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate uncured product in a permitted waste incineration facility. Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste.

# **SECTION 14: Transport Information**

# Australian Dangerous Goods Code (ADG) - Road/Rail Transport UN No.: Not applicable. Proper shipping name: Not applicable. Class/Division: Not applicable. Sub Risk: Not applicable. Packing Group: Not applicable.

Hazchem Code: Not applicable IERG: Not applicable.

## International Air Transport Association (IATA) - Air Transport UN No.: Not applicable. Proper shipping name: Not applicable. Class/Division: Not applicable. Sub Risk: Not applicable. Packing Group: Not applicable.

# International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: Not applicable.
Proper shipping name: Not applicable.
Class/Division: Not applicable.
Sub Risk: Not applicable.
Packing Group: Not applicable.
Marine Pollutant: Not applicable.

# **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## Australian Inventory Status:

This product is regulated by the Therapeutics Goods Administration and is exempt from compliance with the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

# **SECTION 16: Other information**

### **Revision information:**

Complete document review.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au



# Safety Data Sheet

Copyright,2022, 3M Company.All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	17-9608-5	Version number:	5.00
Issue Date:	01/05/2022	Supersedes date:	01/02/2021

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

# **SECTION 1: Identification**

### 1.1. Product identifier

3M<sup>™</sup> RELYX<sup>™</sup> Unicem Aplicap<sup>™</sup>/Maxicap<sup>™</sup> Liquid

### 1.2. Recommended use and restrictions on use

### Recommended use

Dental Product, For use by dental professionals.

### 1.3. Supplier's details

Address:	3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113
Telephone:	136 136
E Mail:	productinfo.au@mmm.com
Website:	www.3m.com.au

### 1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

# **SECTION 2: Hazard identification**

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

### **2.1.** Classification of the substance or mixture

Flammable Liquid: Category 4. Serious Eye Damage/Irritation: Category 1. Skin Sensitizer: Category 1.

### 2.2. Label elements


The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

Signal word

Danger

### Symbols

Corrosion |Exclamation mark |



None known.

2.4. Other hazards which do not result in classification

Causes mild skin irritation.

Toxic to aquatic life with long lasting effects.

# **SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	CAS Nbr	% by Weight

mixture of mono-, di- and tri-glycerin-	1224866-76-5	40 - 50
dimethacrylate-ester of phosphoric acid		
2,2'-Ethylenedioxydiethyl dimethacrylate	109-16-0	20 - 35
(1-Methylethylidene)bis(4, 1-phenyleneoxy-	27689-12-9	20 - 30
3, 1-propanediyl) bismethacrylate		
2,6-Di-tert-butyl-p-cresol	128-37-0	< 0.5
Methyl Methacrylate	80-62-6	< 0.5
Acetic acid, copper(2+) salt, monohydrate	6046-93-1	< 0.2

# **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

#### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

#### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### **Hazardous Decomposition or By-Products**

<u>Substance</u>	<b>Condition</b>
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.

### 5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## Hazchem Code: •3Z

# **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. WARNING ! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment.

## 6.3. Methods and material for containment and cleaning up

Contain spill. Collect as much of the spilled material as possible using non-sparking tools. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

This product is classified as a C1 COMBUSTIBLE LIQUID. For more information please refer to AS 1940

## 7.1. Precautions for safe handling

A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. Acrylates may penetrate commonly-used gloves. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Do not get in eyes.

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Store away from heat. Store away from acids. Store away from oxidising agents.

# **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters

## **Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
2,6-Di-tert-butyl-p-cresol	128-37-0	ACGIH	TWA(inhalable fraction and	A4: Not class. as human
			vapour):2 mg/m3	carcin
2,6-Di-tert-butyl-p-cresol	128-37-0	Australia OELs	TWA(8 hours):10 mg/m3	
COPPER COMPOUNDS	6046-93-1	ACGIH	TWA(as Cu, fume):0.2	
			mg/m3;TWA(as Cu dust or	
			mist):1 mg/m3	
Methyl Methacrylate	80-62-6	ACGIH	TWA:50 ppm;STEL:100 ppm	A4: Not class. as human
				carcin, Dermal
				Sensitizer
Methyl Methacrylate	80-62-6	Australia OELs	TWA(8 hours):208 mg/m3(50	SKIN
			ppm);STEL(15 minutes):416	
			mg/m3(100 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit CEIL: Ceiling Sen: Sensitiser Sk: Absorption through the skin may be a significant source of exposure.

### 8.2. Exposure controls

### **8.2.1.** Engineering controls

Use in a well-ventilated area.

### 8.2.2. Personal protective equipment (PPE)

### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Safety glasses with side shields.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

### Skin/hand protection

See Section 7.1 for additional information on skin protection.

### **Respiratory protection**

None required.

# **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Liquid.	
Liquid.	
Yellow	
Acrylate	
No data available.	
2.3	
No data available.	
> 93.3 °C	
64 °C [Test Method: Tagliabue closed cup]	
No data available.	
Not applicable.	
No data available.	
1.14 g/ml	
1.14 [ <i>Ref Std</i> :WATER=1]	
< 63 g/l	
No data available.	

Volatile organic compounds (VOC)	No data available.
Percent volatile	No data available.
VOC less H2O & exempt solvents	No data available.
Molecular weight	No data available.

# **SECTION 10: Stability and reactivity**

### **10.1 Reactivity**

This material is considered to be non reactive under normal use conditions

# 10.2 Chemical stability

Stable.

# 10.3. Conditions to avoid

Heat.

# 10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

# **10.5 Incompatible materials**

None known.

## 10.6 Hazardous decomposition products

<u>Substance</u>

None known.

Condition

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

**11.1 Information on Toxicological effects** 

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

## Inhalation

This product may have a characteristic odour; however, no adverse health effects are anticipated.

# Skin contact

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

## Eye contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

## Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

# **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

### **Acute Toxicity**

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
mixture of mono-, di- and tri- glycerin-dimethacrylate-ester of phosphoric acid	Dermal		LD50 estimated to be > 5,000 mg/kg
mixture of mono-, di- and tri- glycerin-dimethacrylate-ester of phosphoric acid	Ingestion	Rat	LD50 > 2,000 mg/kg
2,2'-Ethylenedioxydiethyl dimethacrylate	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
2,2'-Ethylenedioxydiethyl dimethacrylate	Ingestion	Rat	LD50 10,837 mg/kg
(1-Methylethylidene)bis(4, 1- phenyleneoxy- 3, 1-propanediyl) bismethacrylate	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
(1-Methylethylidene)bis(4, 1- phenyleneoxy- 3, 1-propanediyl) bismethacrylate	Ingestion	Rat	LD50 > 17,600 mg/kg
2,6-Di-tert-butyl-p-cresol	Dermal	Rat	LD50 > 2,000 mg/kg
2,6-Di-tert-butyl-p-cresol	Ingestion	Rat	LD50 > 2,930 mg/kg
Methyl Methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
Methyl Methacrylate	Inhalation-Vapour (4 hours)	Rat	LC50 29 mg/l
Methyl Methacrylate	Ingestion	Rat	LD50 7,900 mg/kg

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

Name	Species	Value
mixture of mono-, di- and tri-glycerin- dimethacrylate-ester of phosphoric acid	Rabbit	Minimal irritation
2,2'-Ethylenedioxydiethyl dimethacrylate	Guinea pig	Mild irritant
(1-Methylethylidene)bis(4, 1-phenyleneoxy- 3, 1- propanediyl) bismethacrylate	Rabbit	No significant irritation
2,6-Di-tert-butyl-p-cresol	Human and animal	Minimal irritation
Methyl Methacrylate	Human and animal	Mild irritant

# Serious Eye Damage/Irritation

Name	Species	Value
mixture of mono-, di- and tri-glycerin-	Rabbit	Corrosive
dimethacrylate-ester of phosphoric acid		
2,2'-Ethylenedioxydiethyl dimethacrylate	Professional judgement	Moderate irritant
(1-Methylethylidene)bis(4, 1-phenyleneoxy- 3, 1-	Rabbit	Mild irritant
propanediyl) bismethacrylate		
2,6-Di-tert-butyl-p-cresol	Rabbit	Mild irritant
Methyl Methacrylate	Rabbit	Moderate irritant

## **Skin Sensitisation**

Name	Species	Value
mixture of mono-, di- and tri-glycerin-	Guinea pig	Not classified

dimethacrylate-ester of phosphoric acid		
2,2'-Ethylenedioxydiethyl dimethacrylate	Human and animal	Sensitising
(1-Methylethylidene)bis(4, 1-phenyleneoxy- 3, 1- propanediyl) bismethacrylate	Guinea pig	Not classified
2,6-Di-tert-butyl-p-cresol	Human	Not classified
Methyl Methacrylate	Human and animal	Sensitising

# **Respiratory Sensitisation**

Name	Species	Value
Methyl Methacrylate	Human	Not classified

# Germ Cell Mutagenicity

Name	Route	Value
mixture of mono-, di- and tri-glycerin- dimethacrylate-ester of phosphoric acid	In Vitro	Not mutagenic
2,2'-Ethylenedioxydiethyl dimethacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
(1-Methylethylidene)bis(4, 1-phenyleneoxy- 3, 1- propanediyl) bismethacrylate	In Vitro	Not mutagenic
2,6-Di-tert-butyl-p-cresol	In Vitro	Not mutagenic
2,6-Di-tert-butyl-p-cresol	In vivo	Not mutagenic
Methyl Methacrylate	In vivo	Not mutagenic
Methyl Methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification

# Carcinogenicity

Name	Route	Species	Value
2,2'-Ethylenedioxydiethyl	Dermal	Mouse	Not carcinogenic
dimethacrylate			
2,6-Di-tert-butyl-p-cresol	Ingestion	Multiple animal	Some positive data exist, but the data
		species	are not sufficient for classification
Methyl Methacrylate	Ingestion	Rat	Not carcinogenic
Methyl Methacrylate	Inhalation	Human and animal	Not carcinogenic

# **Reproductive Toxicity**

# **Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	<b>Exposure Duration</b>
2,2'- Ethylenedioxydiethyl dimethacrylate	Ingestion	Not classified for female reproduction	Mouse	NOAEL 1 mg/kg/day	1 generation
2,2'- Ethylenedioxydiethyl dimethacrylate	Ingestion	Not classified for male reproduction	Mouse	NOAEL 1 mg/kg/day	1 generation
2,2'- Ethylenedioxydiethyl dimethacrylate	Ingestion	Not classified for development	Mouse	NOAEL 1 mg/kg/day	1 generation
2,6-Di-tert-butyl-p- cresol	Ingestion	Not classified for female reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
2,6-Di-tert-butyl-p- cresol	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
2,6-Di-tert-butyl-p- cresol	Ingestion	Not classified for development	Rat	NOAEL 100 mg/kg/day	2 generation
Methyl Methacrylate	Inhalation	Not classified for male reproduction	Mouse	NOAEL 36.9 mg/l	
Methyl Methacrylate	Inhalation	Not classified for	Rat	NOAEL 8.3	during

development	mg/l	organogenesis

# Target Organ(s)

# Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Methyl Methacrylate	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	occupational exposure

## Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
2,2'- Ethylenedioxy diethyl dimethacrylat e	Dermal	kidney and/or bladder   blood	Not classified	Mouse	NOAEL 833 mg/kg/day	78 weeks
2,6-Di-tert- butyl-p-cresol	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 250 mg/kg/day	28 days
2,6-Di-tert- butyl-p-cresol	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 500 mg/kg/day	2 generation
2,6-Di-tert- butyl-p-cresol	Ingestion	blood	Not classified	Rat	LOAEL 420 mg/kg/day	40 days
2,6-Di-tert- butyl-p-cresol	Ingestion	endocrine system	Not classified	Rat	NOAEL 25 mg/kg/day	2 generation
2,6-Di-tert- butyl-p-cresol	Ingestion	heart	Not classified	Mouse	NOAEL 3,480 mg/kg/day	10 weeks
Methyl Methacrylate	Dermal	peripheral nervous system	Not classified	Human	NOAEL Not available	occupational exposure
Methyl Methacrylate	Inhalation	olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Methyl Methacrylate	Inhalation	kidney and/or bladder	Not classified	Multiple animal species	NOAEL Not available	14 weeks
Methyl Methacrylate	Inhalation	liver	Not classified	Mouse	NOAEL 12.3 mg/l	14 weeks
Methyl Methacrylate	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure

## Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

## **Exposure Levels**

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

# Interactive Effects

Not determined.

# **SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in

Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

## Acute aquatic hazard:

GHS Acute 2: Toxic to aquatic life.

## Chronic aquatic hazard:

GHS Chronic 2: Toxic to aquatic life with long lasting effects.

No product test data available.

Material	CAS Number	Organism	Туре	Exposure	Test endpoint	Test result
mixture of	1224866-76-5	Green algae	Endpoint not	72 hours	EC50	>100 mg/l
mono-, di- and		_	reached			
tri-glycerin-						
dimethacrylate-						
ester of						
phosphoric acid						
mixture of	1224866-76-5	Water flea	Experimental	48 hours	EC50	>100 mg/l
mono-, di- and			-			
tri-glycerin-						
dimethacrylate-						
ester of						
phosphoric acid						
	1224866-76-5	Green algae	Experimental	72 hours	NOEC	56 mg/l
mono-, di- and						
tri-glycerin-						
dimethacrylate-						
ester of						
phosphoric acid						
	109-16-0	Green algae	Experimental	72 hours	EC50	>100 mg/l
Ethylenedioxyd			1			
iethyl						
dimethacrylate						
	109-16-0	Zebra Fish	Experimental	96 hours	LC50	16.4 mg/l
Ethylenedioxyd			1			
iethyl						
dimethacrylate						
	109-16-0	Green algae	Experimental	72 hours	NOEC	18.6 mg/l
Ethylenedioxyd			1			
iethyl						
dimethacrylate						
	109-16-0	Water flea	Experimental	21 days	NOEC	32 mg/l
Ethylenedioxyd	-		1	5-		
iethyl						
dimethacrylate						
	27689-12-9	Green algae	Experimental	72 hours	EC50	>100 mg/l
Methylethylide			I			
ne)bis(4, 1-						
phenyleneoxy-						
3, 1-						
propanediyl)						

bismethacrylate						
(1-	27689-12-9	Water flea	Experimental	48 hours	EC50	>100 mg/l
Methylethylide	27009-12-9	water nea	Experimental	40 110015	LC30	> 100 mg/1
ne)bis(4, 1-						
phenyleneoxy-						
3, 1-						
propanediyl)						
bismethacrylate	27/00 10 0			50.1	NOEG	100 /
(1-	27689-12-9	Green algae	Experimental	72 hours	NOEC	>100 mg/l
Methylethylide						
ne)bis(4, 1-						
phenyleneoxy-						
3, 1-						
propanediyl)						
bismethacrylate						
2,6-Di-tert-	128-37-0	Activated	Experimental	3 hours	EC50	>10,000 mg/l
butyl-p-cresol		sludge	-			
2,6-Di-tert-	128-37-0	Green algae	Experimental	72 hours	EC50	>0.4 mg/l
butyl-p-cresol	-					
2,6-Di-tert-	128-37-0	Water flea	Experimental	48 hours	EC50	0.48 mg/l
butyl-p-cresol		,,				······································
2,6-Di-tert-	128-37-0	Zebra Fish	Experimental	96 hours	No tox obs at	>100 mg/l
butyl-p-cresol	128-37-0		Experimental	90 nours	lmt of water sol	>100 mg/1
2,6-Di-tert-	129 27 0		E-m oning on tol	72 h aure		$0.4 m \alpha / 1$
· ·	128-37-0	Green algae	Experimental	72 hours	EC10	0.4 mg/l
butyl-p-cresol	120.27.0			40.1	NOEG	0.052 //
2,6-Di-tert-	128-37-0	Medaka	Experimental	42 days	NOEC	0.053 mg/l
butyl-p-cresol						
2,6-Di-tert-	128-37-0	Water flea	Experimental	21 days	NOEC	0.023 mg/l
butyl-p-cresol						
Methyl	80-62-6	Green algae	Experimental	72 hours	EC50	>110 mg/l
Methacrylate						
Methyl	80-62-6	Rainbow trout	Experimental	96 hours	LC50	>79 mg/l
Methacrylate						
Methyl	80-62-6	Water flea	Experimental	48 hours	EC50	69 mg/l
Methacrylate			1			e
Methyl	80-62-6	Green algae	Experimental	72 hours	NOEC	110 mg/l
Methacrylate			Linperintental	/ _ 110 01 0	11020	· · · · · · · · · · · · · · · · · · ·
Methyl	80-62-6	Water flea	Experimental	21 days	NOEC	37 mg/l
Methacrylate				21 auy5		5 , 111 <del>5</del> /1
Methyl	80-62-6	Activated	Experimental	30 minutes	EC20	150 mg/l
Methacrylate	00-02-0			50 minutes		150 IIIg/1
	80.62.6	sludge	E	20 4		> 1 000 m - /l /D
Methyl Methe amalata	80-62-6	Soil microbes	Experimental	28 days	NOEC	>1,000 mg/kg (Dry
Methacrylate	6046.02.1			170.1	- East	Weight)
Acetic acid,	6046-93-1	Green algae	Estimated	72 hours	EC50	0.33 mg/l
copper(2+) salt,						
monohydrate						
Acetic acid,	6046-93-1	Water flea	Estimated	48 hours	EC50	0.04 mg/l
copper(2+) salt,						
monohydrate						
Acetic acid,	6046-93-1	Zebra Fish	Estimated	96 hours	LC50	0.037 mg/l
copper(2+) salt,						
monohydrate						
Acetic acid,	6046-93-1	Fathead	Estimated	32 days	EC10	0.019 mg/l
copper(2+) salt,		minnow		J ~		
	1		1	1	1	1

monohydrate						
Acetic acid, copper(2+) salt, monohydrate	6046-93-1	Green algae	Estimated		NOEC	0.069 mg/l
Acetic acid, copper(2+) salt, monohydrate	6046-93-1	Water flea	Estimated	7 days	NOEC	0.01 mg/l
Acetic acid, copper(2+) salt, monohydrate	6046-93-1	Activated sludge	Estimated		EC50	22 mg/l
Acetic acid, copper(2+) salt, monohydrate	6046-93-1	Barley	Estimated	4 days	NOEC	50 mg/kg (Dry Weight)
Acetic acid, copper(2+) salt, monohydrate	6046-93-1	Bobwhite quail	Estimated	14 days	LD50	4,402 mg per kg of bodyweight
Acetic acid, copper(2+) salt, monohydrate	6046-93-1	Redworm	Estimated	56 days	NOEC	31 mg/kg (Dry Weight)
Acetic acid, copper(2+) salt, monohydrate	6046-93-1	Sediment Worm	Estimated	28 days	NOEC	57.5 mg/kg (Dry Weight)
Acetic acid, copper(2+) salt, monohydrate	6046-93-1	Soil microbes	Estimated	4 days	NOEC	38 mg/kg (Dry Weight)
Acetic acid, copper(2+) salt, monohydrate	6046-93-1	Springtail	Estimated	28 days	NOEC	87.7 mg/kg (Dry Weight)

# 12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
mixture of	1224866-76-5	Experimental	28 days	BOD	82 %BOD/ThB	OECD 301F -
mono-, di- and		Biodegradation			OD	Manometric
tri-glycerin-						respirometry
dimethacrylate-						
ester of						
phosphoric acid						
2,2'-	109-16-0	Experimental	28 days	CO2 evolution	85 % weight	OECD 301B - Modified
Ethylenedioxyd		Biodegradation				sturm or CO2
iethyl						
dimethacrylate						
(1-	27689-12-9	Experimental	28 days	CO2 evolution	7-12 % weight	OECD 301B - Modified
Methylethylide		Biodegradation				sturm or CO2
ne)bis(4, 1-						
phenyleneoxy-						
3, 1-						
propanediyl)						
bismethacrylate						
2,6-Di-tert-	128-37-0	Data not	N/A	N/A	N/A	N/A
butyl-p-cresol		available-				
		insufficient				
Methyl	80-62-6	Experimental	14 days	BOD	94 %BOD/ThB	OECD 301C - MITI
Methacrylate		Biodegradation			OD	test (I)
Acetic acid,	6046-93-1	Analogous	14 days	BOD	74 %BOD/ThB	OECD 301C - MITI

copper(2+) salt,	Compound	1	OD	test (I)
monohydrate	Biodegrad	ation		

## **12.3 : Bioaccumulative potential**

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
mixture of	1224866-76-5	Experimental		Log Kow	-0.2	Non-standard method
mono-, di- and		Bioconcentrati				
tri-glycerin-		on				
dimethacrylate-						
ester of						
phosphoric acid						
2,2'-	109-16-0	Experimental		Log Kow	2.3	Non-standard method
Ethylenedioxyd		Bioconcentrati		_		
iethyl		on				
dimethacrylate						
(1-	27689-12-9	Estimated		Log Kow	7.61	Estimated: Octanol-
Methylethylide		Bioconcentrati		C		water partition
ne)bis(4, 1-		on				coefficient
phenyleneoxy-						
3, 1-						
propanediyl)						
bismethacrylate						
2,6-Di-tert-	128-37-0	Experimental	56 days	Bioaccumulatio	1277	OECD 305E -
butyl-p-cresol		BCF - Carp		n factor		Bioaccumulation flow-
		_				through fish test
Methyl	80-62-6	Experimental		Log Kow	1.38	OECD 107 log Kow
Methacrylate		Bioconcentrati		_		shke flsk mtd
-		on				
Acetic acid,	6046-93-1	Analogous		Log Kow	-0.17	
copper(2+) salt,		Compound				
monohydrate		Bioconcentrati				
		on				

## 12.4. Mobility in soil

Please contact manufacturer for more details

# 12.5 Other adverse effects

No information available.

# **SECTION 13: Disposal considerations**

## 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate uncured product in a permitted waste incineration facility. Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste.

# **SECTION 14: Transport Information**

Australian Dangerous Goods Code (ADG) - Road/Rail Transport

UN No.: UN3082 Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. , (Acetic Acid, Copper (2+) Salt, Monohydrate ) Class/Division: 9 Sub Risk: Not applicable. Packing Group: III Special Instructions: Not restricted, environmentally hazardous substance exception. Hazchem Code: •3Z IERG: 47

International Air Transport Association (IATA) - Air Transport UN No.: UN3082 Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. , (Acetic Acid, Copper (2+) Salt, Monohydrate ) Class/Division: 9 Sub Risk: Not applicable. Packing Group: III Special Instructions: Not restricted, as per Special Provision A197, environmentally hazardous substance exception.

International Maritime Dangerous Goods Code (IMDG)- Marine Transport UN No.: UN3082 Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. , ( Acetic Acid, Copper (2+) Salt, Monohydrate ) Class/Division: 9 Sub Risk: Not applicable. Packing Group: III Marine Pollutant: Acetic Acid, Copper (2+) Salt, Monohydrate Special Instructions: Not restricted, as per IMDG code 2.10.2.7, marine pollutant exception.

# **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## Australian Inventory Status:

This product is regulated by the Therapeutics Goods Administration and is exempt from compliance with the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

# **SECTION 16: Other information**

## **Revision information:**

Complete document review.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

### 3M Australia SDSs are available at www.3m.com.au