



## Safety Data Sheet

Copyright, 2016, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	18-3229-4	<b>Version number:</b>	5.00
<b>Issue Date:</b>	18/11/2016	<b>Supersedes date:</b>	14/11/2016

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

### SECTION 1: Identification

#### 1.1. Product identifier

3M(TM) 5-Way Spray

#### Product Identification Numbers

62-4978-4930-7      62-4978-4935-6

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Penetrant, Lubricant and Demoisurizer

For Industrial or Professional use only.

#### 1.3. Supplier's details

**Address:** 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113  
**Telephone:** 136 136  
**E Mail:** productinfo.au@mmm.com  
**Website:** www.3m.com.au

#### 1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

### SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

#### 2.1. Classification of the substance or mixture

Flammable Aerosol: Category 1.

Gas under pressure: Liquefied gas.

Specific Target Organ Toxicity (single exposure): Category 1.

Specific Target Organ Toxicity (single exposure): Category 3.

#### 2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for

Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

**Signal word**

DANGER!

**Symbols**

Flame | Gas cylinder | Exclamation mark | Health Hazard |

**Pictograms**



**Hazard statements**

H222	Extremely flammable aerosol.
H280	Contains gas under pressure; may explode if heated.
H336	May cause drowsiness or dizziness.
H370	Causes damage to organs: cardiovascular system

**Precautionary statements**

**Prevention:**

P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P270	Do not eat, drink or smoke when using this product.
P264	Wash thoroughly after handling.

**Response:**

P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P307 + P311	IF exposed: Call a POISON CENTRE or doctor/physician.
P321	Specific treatment (see Notes to Physician on this label).
P312	Call a POISON CENTRE or doctor/physician if you feel unwell.

**Storage:**

P410 + P403	Protect from sunlight. Store in a well-ventilated place.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.

**Disposal:**

P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.
------	--

**2.3. Other assigned/identified product hazards**

3M Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal.

### 3M(TM) 5-Way Spray

#### 2.4. Other hazards which do not result in classification

Causes mild skin irritation.

### SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
ALIPHATIC HYDROCARBON	64742-47-8	50 - 60
Butane	106-97-8	10 - 20
Propane	74-98-6	10 - 20
PETROLEUM OIL	64742-52-5	3 - 7
HEAVY PARAFFINIC OIL	64742-54-7	1 - 5
Petrolatum	8009-03-8	1 - 5

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### Inhalation

Remove person to fresh air. Get medical attention.

##### Skin contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

##### Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

##### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

#### 4.3. Indication of any immediate medical attention and special treatment required

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

#### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

#### Hazardous Decomposition or By-Products

##### Substance

Carbon monoxide.

Carbon dioxide.

##### Condition

During combustion.

During combustion.

#### 5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and

## 3M(TM) 5-Way Spray

prevent explosive rupture.

**Hazchem Code:** 2YE

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. **WARNING !** A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. Cover spill area with a fire-extinguishing foam. An appropriate aqueous film forming foam (AFFF) is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

For industrial or professional use only. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store away from acids. Store away from oxidising agents.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Natural gas	106-97-8	ACGIH	Limit value not established:	
Butane	106-97-8	Australia OELs	TWA(8 hours):1900 mg/m3(800 ppm)	
Butane	106-97-8	ACGIH	STEL:1000 ppm	
Kerosine (petroleum)	64742-47-8	ACGIH	TWA(as total hydrocarbon	A3: Confirmed animal

**3M(TM) 5-Way Spray**

			vapour, non-aerosol):200 mg/m3	carcin., SKIN
JET FUELS (NON-AEROSOL), AS TOTAL HYDROCARBON VAPOUR	64742-47-8	ACGIH	TWA(as total hydrocarbon vapour, non-aerosol):200 mg/m3	A3: Confirmed animal carcin., SKIN
Paraffin oil	64742-52-5	Australia OELs	TWA(as mist)(8 hours):5 mg/m3	
MINERAL OILS, HIGHLY-REFINED OILS	64742-54-7	ACGIH	TWA(inhalable fraction):5 mg/m3	A4: Not class. as human carcin
Propane	74-98-6	ACGIH	Limit value not established:	
Propane	74-98-6	Australia OELs	Limit value not established:	Explosion hazard, asphyxiant
MINERAL OILS, HIGHLY-REFINED OILS	8009-03-8	ACGIH	TWA(inhalable fraction):5 mg/m3	A4: Not class. as human carcin
Mineral oils (untreated and mildly treated)	8009-03-8	ACGIH	Limit value not established:	A2: Suspected human carcin., Cntrl all expos-low as possib
Paraffin oil	8009-03-8	Australia OELs	TWA(as mist)(8 hours):5 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Do not remain in area where available oxygen may be reduced. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Nitrile rubber.

Select and use gloves according to AS/NZ 2161.

**Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece supplied-air respirator.

Organic vapour respirators may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

<b>Physical state</b>	Liquid.
<b>Appearance/Odour</b>	amber coloured liquid, strong solvent odour
<b>Odour threshold</b>	<i>No data available.</i>
<b>pH</b>	<i>No data available.</i>
<b>Melting point/Freezing point</b>	<i>Not applicable.</i>
<b>Boiling point/Initial boiling point/Boiling range</b>	<=458 °C
<b>Flash point</b>	-17.8 °C
<b>Evaporation rate</b>	<i>No data available.</i>
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Flammable Limits(LEL)</b>	0.6
<b>Flammable Limits(UEL)</b>	9.5
<b>Vapour pressure</b>	<i>No data available.</i>
<b>Vapour density</b>	2 [Ref Std: AIR=1]
<b>Density</b>	0.72 g/ml
<b>Relative density</b>	0.72 [Ref Std: WATER=1]
<b>Water solubility</b>	<i>No data available.</i>
<b>Solubility- non-water</b>	<i>No data available.</i>
<b>Partition coefficient: n-octanol/water</b>	<i>No data available.</i>
<b>Autoignition temperature</b>	<i>No data available.</i>
<b>Decomposition temperature</b>	<i>Not applicable.</i>
<b>Viscosity</b>	<i>No data available.</i>
<b>VOC less H2O &amp; exempt solvents</b>	<=30 % [Test Method:calculated per CARB title 2]
<b>Solids content</b>	15 %

**SECTION 10: Stability and reactivity****10.1 Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

**10.2 Chemical stability**

Stable.

**10.3. Conditions to avoid**

Sparks and/or flames.

**10.4. Possibility of hazardous reactions**

Hazardous polymerisation will not occur.

**10.5 Incompatible materials**

Strong oxidising agents.

**10.6 Hazardous decomposition products****Substance****Condition**

None known.

**SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

**11.1 Information on Toxicological effects****Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

**Inhalation**

Intentional concentration and inhalation may be harmful or fatal. Simple asphyxiation: Signs/symptoms may include increased heart rate, rapid respirations, drowsiness, headache, incoordination, altered judgement, nausea, vomiting, lethargy, seizures, coma, and may be fatal. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

**Skin contact**

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

**Eye contact**

Contact with the eyes during product use is not expected to result in significant irritation.

**Ingestion**

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

**Additional Health Effects:****Single exposure may cause target organ effects:**

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Single exposure, above recommended guidelines, may cause:

Cardiac sensitisation: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000

**3M(TM) 5-Way Spray**

			mg/kg
ALIPHATIC HYDROCARBON	Dermal	Rabbit	LD50 > 3,160 mg/kg
ALIPHATIC HYDROCARBON	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 3 mg/l
ALIPHATIC HYDROCARBON	Ingestion	Rat	LD50 > 5,000 mg/kg
Propane	Inhalation-Gas (4 hours)	Rat	LC50 > 200,000 ppm
Butane	Inhalation-Gas (4 hours)	Rat	LC50 277,000 ppm
PETROLEUM OIL	Dermal	Rabbit	LD50 > 2,000 mg/kg
PETROLEUM OIL	Ingestion	Rat	LD50 > 5,000 mg/kg
Petrolatum	Dermal		LD50 estimated to be > 5,000 mg/kg
Petrolatum	Ingestion	Rat	LD50 > 5,000 mg/kg
HEAVY PARAFFINIC OIL	Dermal	Rabbit	LD50 > 5,000 mg/kg
HEAVY PARAFFINIC OIL	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
ALIPHATIC HYDROCARBON	Rabbit	Mild irritant
Propane	Rabbit	Minimal irritation
Butane	Professional judgement	No significant irritation
PETROLEUM OIL	Rabbit	Minimal irritation
HEAVY PARAFFINIC OIL	Rabbit	Minimal irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
ALIPHATIC HYDROCARBON	Rabbit	Mild irritant
Propane	Rabbit	Mild irritant
Butane	Rabbit	No significant irritation
PETROLEUM OIL	Rabbit	Mild irritant
HEAVY PARAFFINIC OIL	Rabbit	Mild irritant

**Skin Sensitisation**

Name	Species	Value
ALIPHATIC HYDROCARBON	Guinea pig	Not sensitizing
PETROLEUM OIL	Guinea pig	Not sensitizing
HEAVY PARAFFINIC OIL	Guinea pig	Not sensitizing

**Respiratory Sensitisation**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
ALIPHATIC HYDROCARBON	In Vitro	Not mutagenic
Propane	In Vitro	Not mutagenic
Butane	In Vitro	Not mutagenic
HEAVY PARAFFINIC OIL	In Vitro	Some positive data exist, but the data are not sufficient for classification

**Carcinogenicity**

Name	Route	Species	Value
ALIPHATIC HYDROCARBON	Dermal	Mouse	Some positive data exist, but the data



**3M(TM) 5-Way Spray**

			are not sufficient for classification
PETROLEUM OIL	Ingestion	Rat	Not carcinogenic
PETROLEUM OIL	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
HEAVY PARAFFINIC OIL	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification

**Reproductive Toxicity**

**Reproductive and/or Developmental Effects**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
ALIPHATIC HYDROCARBON	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
ALIPHATIC HYDROCARBON	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
ALIPHATIC HYDROCARBON	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Propane	Inhalation	cardiac sensitization	Causes damage to organs	Human	NOAEL Not available	
Propane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Propane	Inhalation	respiratory irritation	All data are negative	Human	NOAEL Not available	
Butane	Inhalation	cardiac sensitization	Causes damage to organs	Human	NOAEL Not available	
Butane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Butane	Inhalation	heart	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL 5,000 ppm	25 minutes
Butane	Inhalation	respiratory irritation	All data are negative	Rabbit	NOAEL Not available	
PETROLEUM OIL	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
HEAVY PARAFFINIC OIL	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
HEAVY PARAFFINIC OIL	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	

**3M(TM) 5-Way Spray****Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Butane	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 4,489 ppm	90 days
Butane	Inhalation	blood	All data are negative	Rat	NOAEL 4,489 ppm	90 days
HEAVY PARAFFINI C OIL	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.21 mg/l	28 days

**Aspiration Hazard**

Name	Value
ALIPHATIC HYDROCARBON	Aspiration hazard

**Exposure Levels**

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

**Interactive Effects**

Not determined.

**SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

**12.1. Toxicity****Acute aquatic hazard:**

Not acutely toxic to aquatic life by GHS criteria.

**Chronic aquatic hazard:**

Not chronically toxic to aquatic life by GHS criteria.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Propane	74-98-6		Data not available or insufficient for classification			
Petrolatum	8009-03-8	Rainbow trout	Estimated	96 hours	LC50	>1,000 mg/l
HEAVY PARAFFINIC OIL	64742-54-7		Data not available or insufficient for classification			
PETROLEUM OIL	64742-52-5	Rainbow trout	Estimated	96 hours	LC50	>100 mg/l

**3M(TM) 5-Way Spray**

PETROLEUM OIL	64742-52-5	Green algae	Estimated	96 hours	EC50	>100 mg/l
PETROLEUM OIL	64742-52-5	Water flea	Estimated	48 hours	EC50	>100 mg/l
Butane	106-97-8		Data not available or insufficient for classification			
ALIPHATIC HYDROCARBON	64742-47-8		Data not available or insufficient for classification			

**12.2. Persistence and degradability**

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Butane	106-97-8	Experimental Photolysis		Photolytic half-life (in air)	12.3 days (t 1/2)	Other methods
ALIPHATIC HYDROCARBON	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
PETROLEUM OIL	64742-52-5	Experimental Biodegradation	28 days	CO2 evolution	6 % weight	OECD 301B - Modified sturm or CO2
HEAVY PARAFFINIC OIL	64742-54-7	Experimental Biodegradation	28 days	BOD	31 % weight	OECD 301F - Manometric respirometry
Propane	74-98-6	Experimental Photolysis		Photolytic half-life (in air)	27.5 days (t 1/2)	Other methods
Petrolatum	8009-03-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

**12.3 : Bioaccumulative potential**

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Butane	106-97-8	Experimental Bioconcentration		Log Kow	2.89	Other methods
ALIPHATIC HYDROCARBON	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
PETROLEUM OIL	64742-52-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
HEAVY PARAFFINIC OIL	64742-54-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Propane	74-98-6	Data not available or insufficient for	N/A	N/A	N/A	N/A

**3M(TM) 5-Way Spray**

		classification				
Petrolatum	8009-03-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

**12.4. Mobility in soil**

Please contact manufacturer for more details

**12.5 Other adverse effects**

No information available.

**SECTION 13: Disposal considerations****13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility.

**SECTION 14: Transport Information****Australian Dangerous Goods Code (ADG) - Road/Rail Transport**

**UN No.:** UN1950

**Proper shipping name:** AEROSOLS

**Class/Division:** 2.1

**Sub Risk:** Not applicable.

**Packing Group:** Not applicable.

**Hazchem Code:** 2YE

**IERG:** 49

**International Air Transport Association (IATA) - Air Transport**

**UN No.:** UN1950

**Proper shipping name:** AEROSOLS, FLAMMABLE

**Class/Division:** 2.1

**Sub Risk:** Not applicable.

**Packing Group:** Not applicable.

**International Maritime Dangerous Goods Code (IMDG)- Marine Transport**

**UN No.:** UN1950

**Proper shipping name:** AEROSOLS

**Class/Division:** 2.1

**Sub Risk:** Not applicable.

**Packing Group:** Not applicable.

**Marine Pollutant:** Not applicable.

**Special Instructions:** Limited quantity may apply

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Australian Inventory Status:**

The chemical components contained within this product are listed on the Australian Inventory of Chemical Substances and

## 3M(TM) 5-Way Spray

are in compliance with the requirements of the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

**Poison Schedule:** This product has not been assessed for poisons scheduling as the product is intended for industrial and professional use only.

## SECTION 16: Other information

### **Revision information:**

Conversion to GHS format SDS.

**DISCLAIMER:** The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

**3M Australia SDSs are available at [www.3m.com.au](http://www.3m.com.au)**