



## Safety Data Sheet

Copyright, 2016, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	11-2664-8	<b>Version number:</b>	5.00
<b>Issue Date:</b>	18/11/2016	<b>Supersedes date:</b>	14/11/2016

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Scotch-Weld™ Instant Adhesive CA100 Clear 3M™ Scotch-Weld™ Instant Adhesive CA100 Clear

#### Product Identification Numbers

62-3873-0330-8      62-3873-0335-7      62-3873-3830-4

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Structural Strength Instant Adhesive.

For Industrial or Professional use only.

#### 1.3. Supplier's details

**Address:** 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113  
**Telephone:** 136 136  
**E Mail:** productinfo.au@mmm.com  
**Website:** www.3m.com.au

#### 1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

### SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

#### 2.1. Classification of the substance or mixture

Flammable Liquid: Category 4.  
Serious Eye Damage/Irritation: Category 2.  
Skin Sensitizer: Category 1B.  
Specific Target Organ Toxicity (single exposure): Category 3.

#### 2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for

Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

**Signal word**

WARNING!

**Symbols**

Exclamation mark |

**Pictograms**



**Hazard statements**

H227	Combustible liquid.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.

**Precautionary statements**

**Prevention:**

P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P280B	Wear protective gloves and eye/face protection.
P264	Wash thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.

**Response:**

P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.
P312	Call a POISON CENTRE or doctor/physician if you feel unwell.
P370 + P378G	In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

**Storage:**

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

**Disposal:**

P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.
------	--

**2.3. Other assigned/identified product hazards**

May bond tissue rapidly. Avoid eye and skin contact. If eyelids are bonded, do not force open. In case of skin bonding,

## 3M™ Scotch-Weld™ Instant Adhesive CA100 Clear 3M™ Scotch-Weld™ Instant Adhesive CA100 Clear

quickly soak in warm water and avoid excessive force to free bonded area. Contact through clothing may cause thermal burns.

### 2.4. Other hazards which do not result in classification

Causes mild skin irritation. Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

## SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
Ethyl 2-cyanoacrylate	7085-85-0	60 - 100
Poly(methyl methacrylate)	9011-14-7	10 - 30
Hydroquinone	123-31-9	0.1 - 1

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

For skin bonds: Quickly soak in warm water and avoid use of excessive force to free bonded area. If unable to free bonded area, or if lips or mouth are bonded, get medical attention. If irritation persists, get medical attention.

#### Eye contact

Immediately flush eyes with large amounts of water for at least 15 minutes. Get immediate medical attention. DO NOT force eyelids open.

#### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### Hazardous Decomposition or By-Products

#### Substance

Carbon monoxide.  
Carbon dioxide.  
Oxides of nitrogen.

#### Condition

During combustion.  
During combustion.  
During combustion.

**5.3. Special protective actions for fire-fighters**

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. **WARNING!** A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

**SECTION 7: Handling and storage**

This product is classified as a C1 COMBUSTIBLE LIQUID. For more information please refer to AS 1940

**7.1. Precautions for safe handling**

For industrial or professional use only. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

**7.2. Conditions for safe storage including any incompatibilities**

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from acids. Store away from strong bases. Store away from oxidising agents. Store away from amines.

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Hydroquinone	123-31-9	Australia OELs	TWA(8 hours): 2 mg/m <sup>3</sup>	
Hydroquinone	123-31-9	ACGIH	TWA:1 mg/m <sup>3</sup>	A3: Confirmed animal carcin., Dermal Sensitizer
Ethyl 2-cyanoacrylate	7085-85-0	ACGIH	TWA:0.2 ppm	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG : Chemical Manufacturer's Recommended Guidelines  
TWA: Time-Weighted-Average  
STEL: Short Term Exposure Limit  
CEIL: Ceiling  
Sen: Sensitiser  
Sk: Absorption through the skin may be a significant source of exposure.

## **8.2. Exposure controls**

### **8.2.1. Engineering controls**

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

### **8.2.2. Personal protective equipment (PPE)**

#### **Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

#### **Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Do not wear cotton gloves.

Gloves made from the following material(s) are recommended: Neoprene.

Nitrile rubber.

Natural rubber.

Select and use gloves according to AS/NZ 2161.

#### **Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

## **SECTION 9: Physical and chemical properties**

### **9.1. Information on basic physical and chemical properties**

<b>Physical state</b>	Liquid.
<b>Specific Physical Form:</b>	Viscous Liquid
<b>Appearance/Odour</b>	Clear, colourless; sharp irritating odour.
<b>Odour threshold</b>	<i>No data available.</i>
<b>Boiling point/Initial boiling point/Boiling range</b>	> 98.9 °C [ @ 799.932 Pa ]
<b>Flash point</b>	85 °C [ <i>Test Method:</i> Tagliabue closed cup ]
<b>Evaporation rate</b>	Negligible

Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Vapour pressure	133.3 Pa [ <i>@ 20 °C</i> ]
Vapour density	<i>No data available.</i>
Density	1.05 g/ml
Relative density	1.05 [ <i>Ref Std: WATER=1</i> ]
Water solubility	Nil
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
Viscosity	2,500 - 4,500 mPa-s
VOC less H2O & exempt solvents	<= 6 g/l
VOC less H2O & exempt solvents	<= 0.6 %

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

### 10.2 Chemical stability

Stable.

### 10.3. Conditions to avoid

None known.

### 10.4. Possibility of hazardous reactions

Hazardous polymerisation may occur. May occur in large quantities only.

### 10.5 Incompatible materials

Strong bases.

Amines.

### 10.6 Hazardous decomposition products

#### Substance

None known.

#### Condition

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1 Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

**3M™ Scotch-Weld™ Instant Adhesive CA100 Clear 3M™ Scotch-Weld™ Instant Adhesive CA100 Clear**

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

**Skin contact**

Bonds skin rapidly. Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching. May cause additional health effects (see below). Contact through clothing may cause thermal burns.

**Eye contact**

Bonds eyelids rapidly. Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

**Ingestion**

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

**Additional Health Effects:****Single exposure may cause target organ effects:**

Dermal effects: Signs/symptoms may include changes in skin pigmentation and/or colouration. Neurological effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and changes in blood pressure and heart rate.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Ethyl 2-cyanoacrylate	Dermal	Rabbit	LD50 > 2,000 mg/kg
Ethyl 2-cyanoacrylate	Ingestion	Rat	LD50 > 5,000 mg/kg
Poly(methyl methacrylate)	Dermal		LD50 estimated to be > 5,000 mg/kg
Poly(methyl methacrylate)	Ingestion	Rat	LD50 > 5,000 mg/kg
Hydroquinone	Dermal	Rat	LD50 > 4,800 mg/kg
Hydroquinone	Ingestion	Rat	LD50 302 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Ethyl 2-cyanoacrylate	Rabbit	Mild irritant
Poly(methyl methacrylate)	Rabbit	No significant irritation
Hydroquinone	Human and animal	Minimal irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
Ethyl 2-cyanoacrylate	Rabbit	Severe irritant
Poly(methyl methacrylate)	Rabbit	Mild irritant
Hydroquinone	Human	Corrosive

**Skin Sensitisation**

Name	Species	Value
------	---------	-------

**3M™ Scotch-Weld™ Instant Adhesive CA100 Clear 3M™ Scotch-Weld™ Instant Adhesive CA100 Clear**

Ethyl 2-cyanoacrylate	Human	Some positive data exist, but the data are not sufficient for classification
Hydroquinone	Guinea pig	Sensitising

**Respiratory Sensitisation**

Name	Species	Value
Ethyl 2-cyanoacrylate	Human	Some positive data exist, but the data are not sufficient for classification

**Germ Cell Mutagenicity**

Name	Route	Value
Ethyl 2-cyanoacrylate	In Vitro	Not mutagenic
Hydroquinone	In Vitro	Some positive data exist, but the data are not sufficient for classification
Hydroquinone	In vivo	Some positive data exist, but the data are not sufficient for classification

**Carcinogenicity**

Name	Route	Species	Value
Hydroquinone	Dermal	Mouse	Not carcinogenic
Hydroquinone	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification

**Reproductive Toxicity**

**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Hydroquinone	Ingestion	Not toxic to female reproduction	Rat	NOAEL 150 mg/kg/day	2 generation
Hydroquinone	Ingestion	Not toxic to male reproduction	Rat	NOAEL 150 mg/kg/day	2 generation
Hydroquinone	Ingestion	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 100 mg/kg/day	during organogenesis

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Ethyl 2-cyanoacrylate	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	occupational exposure
Hydroquinone	Ingestion	nervous system	May cause damage to organs	Rat	NOAEL Not available	not applicable
Hydroquinone	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 400 mg/kg	not applicable

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
------	-------	-----------------	-------	---------	-------------	-------------------



**3M™ Scotch-Weld™ Instant Adhesive CA100 Clear 3M™ Scotch-Weld™ Instant Adhesive CA100 Clear**

Hydroquinone	Ingestion	blood	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	40 days
Hydroquinone	Ingestion	bone marrow   liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	9 weeks
Hydroquinone	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 50 mg/kg/day	15 months
Hydroquinone	Ocular	eyes	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Exposure Levels**

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

**Interactive Effects**

Not determined.

**SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

**12.1. Toxicity**

**Acute aquatic hazard:**

GHS Acute 2: Toxic to aquatic life.

**Chronic aquatic hazard:**

GHS Chronic 3: Harmful to aquatic life with long lasting effects.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Poly(methyl methacrylate)	9011-14-7		Data not available or insufficient for classification			
Hydroquinone	123-31-9	Rainbow trout	Experimental	96 hours	LC50	0.044 mg/l
Hydroquinone	123-31-9	Green Algae	Experimental	72 hours	EC50	0.053 mg/l
Hydroquinone	123-31-9	Water flea	Experimental	48 hours	EC50	0.061 mg/l
Hydroquinone	123-31-9	Water flea	Experimental	21 days	NOEC	0.0029 mg/l

**3M™ Scotch-Weld™ Instant Adhesive CA100 Clear 3M™ Scotch-Weld™ Instant Adhesive CA100 Clear**

Hydroquinone	123-31-9	Green Algae	Experimental	72 hours	NOEC	0.0015 mg/l
Ethyl 2-cyanoacrylate	7085-85-0		Data not available or insufficient for classification			

**12.2. Persistence and degradability**

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Hydroquinone	123-31-9	Experimental Biodegradation	14 days	BOD	70 % weight	OECD 301C - MITI test (I)
Ethyl 2-cyanoacrylate	7085-85-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Poly(methyl methacrylate)	9011-14-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

**12.3 : Bioaccumulative potential**

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Hydroquinone	123-31-9	Experimental Bioconcentration		Log Kow	0.59	Other methods
Ethyl 2-cyanoacrylate	7085-85-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Poly(methyl methacrylate)	9011-14-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

**12.4. Mobility in soil**

Please contact manufacturer for more details

**12.5 Other adverse effects**

No information available.

**SECTION 13: Disposal considerations****13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste.

**SECTION 14: Transport Information****Australian Dangerous Goods Code (ADG) - Road/Rail Transport**

**UN No.:** Not applicable.

**Proper shipping name:** Not applicable.

**Class/Division:** Not applicable.

**Sub Risk:** Not applicable.

**Packing Group:** Not applicable.

**Hazchem Code:** Not applicable

**IERG:** Not applicable.

#### **International Air Transport Association (IATA) - Air Transport**

**UN No.:** Not applicable.

**Proper shipping name:** Not applicable.

**Class/Division:** Not applicable.

**Sub Risk:** Not applicable.

**Packing Group:** Not applicable.

#### **International Maritime Dangerous Goods Code (IMDG)- Marine Transport**

**UN No.:** Not applicable.

**Proper shipping name:** Not applicable.

**Class/Division:** Not applicable.

**Sub Risk:** Not applicable.

**Packing Group:** Not applicable.

**Marine Pollutant:** Not applicable.

## **SECTION 15: Regulatory information**

### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

#### **Australian Inventory Status:**

The chemical components contained within this product are listed on the Australian Inventory of Chemical Substances and are in compliance with the requirements of the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

**Poison Schedule:** This product has not been assessed for poisons scheduling as the product is intended for industrial and professional use only.

## **SECTION 16: Other information**

#### **Revision information:**

Conversion to GHS format SDS.

**DISCLAIMER:** The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

**3M Australia SDSs are available at [www.3m.com.au](http://www.3m.com.au)**