



## Safety Data Sheet

Copyright, 2018, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	11-3180-4	<b>Version number:</b>	7.00
<b>Issue Date:</b>	30/04/2018	<b>Supersedes date:</b>	08/04/2018

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

### IDENTIFICATION:

#### 1.1. Product identifier

3M™ Scotch-Weld™ Epoxy Adhesive DP100, Clear

#### Product Identification Numbers

62-3575-1435-5      62-3575-1437-1

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Structural adhesive.

For Industrial or Professional use only.

#### 1.3. Supplier's details

**Address:** 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113  
**Telephone:** 136 136  
**E Mail:** productinfo.au@mmm.com  
**Website:** www.3m.com.au

#### 1.4. Emergency telephone number

**Company Emergency Hotline:** EMERGENCY: 1800 097 146 (Australia only)

**This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the SDSs for components of this product are:**

10-3341-4, 10-3337-2

One or more components of this KIT is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

### TRANSPORT INFORMATION

The Components of this KIT have various Dangerous Goods Transportation Classifications. Please refer to the attached component Safety Data Sheets for individual Transportation Classifications.

**UN No.:** UN3082

**Proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

**Class/Division:** 9

**Packing Group:** III

**Marine Pollutant:**Epoxy Resin

**Hazchem Code:** -3Z

**IERG:** 47

**Australian Dangerous Goods Code (ADG) - Road/Rail Transport**

**Special Instructions:**Australian Dangerous Goods Code: Not subject to this code as per Special Provision AU01

**International Air Transport Association (IATA)- Air Transport**

**Special Instructions:**Not restricted, as per Special Provision A197, environmentally hazardous substance exception.

**International Maritime Dangerous Goods Code (IMDG)- Marine Transport**

**Special Instructions:**Not restricted, as per IMDG code 2.10.2.7, marine pollutant exception.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

**3M Australia SDSs are available at [www.3m.com.au](http://www.3m.com.au)**



## Safety Data Sheet

Copyright, 2018, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	10-3337-2	<b>Version number:</b>	6.00
<b>Issue Date:</b>	06/04/2018	<b>Supersedes date:</b>	07/04/2016

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Scotch-Weld™ Epoxy Adhesive DP100 Clear, Part B

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Structural adhesive.

For Industrial or Professional use only.

#### 1.3. Supplier's details

**Address:** 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113  
**Telephone:** 136 136  
**E Mail:** productinfo.au@mmm.com  
**Website:** www.3m.com.au

#### 1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

### SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

#### 2.1. Classification of the substance or mixture

Skin Sensitizer: Category 1.

#### 2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

##### Signal word

WARNING!

## 3M™ Scotch-Weld™ Epoxy Adhesive DP100 Clear, Part B

### Symbols

Exclamation mark |

### Pictograms



### Hazard statements

H317 May cause an allergic skin reaction.

### Precautionary statements

#### Prevention:

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P280E Wear protective gloves.  
P272 Contaminated work clothing should not be allowed out of the workplace.

#### Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.  
P363 Wash contaminated clothing before reuse.  
P321 Specific treatment (see Notes to Physician on this label).

#### Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

### 2.3. Other assigned/identified product hazards

None known.

### 2.4. Other hazards which do not result in classification

Causes mild skin irritation. Causes eye irritation. Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.

## SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
Epoxy resin	25068-38-6	100

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye contact**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

**If swallowed**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

See Section 11.1. Information on toxicological effects.

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

**SECTION 5: Fire-fighting measures**

**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

**5.2. Special hazards arising from the substance or mixture**

None inherent in this product.

**Hazardous Decomposition or By-Products**

**Substance**

Aldehydes.  
Carbon monoxide.  
Carbon dioxide.  
Hydrogen Chloride  
Ketones.

**Condition**

During combustion.  
During combustion.  
During combustion.  
During combustion.  
During combustion.

**5.3. Special protective actions for fire-fighters**

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

**Hazchem Code:** •3Z

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in

accordance with applicable local/regional/national/international regulations.

## **SECTION 7: Handling and storage**

### **7.1. Precautions for safe handling**

Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

### **7.2. Conditions for safe storage including any incompatibilities**

Store away from heat. Store away from acids. Store away from oxidising agents.

## **SECTION 8: Exposure controls/personal protection**

### **8.1 Control parameters**

#### **Occupational exposure limits**

No occupational exposure limit values exist for any of the components listed in Section 3 of this Safety Data Sheet.

### **8.2. Exposure controls**

#### **8.2.1. Engineering controls**

No engineering controls required.

#### **8.2.2. Personal protective equipment (PPE)**

##### **Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

##### **Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

Select and use gloves according to AS/NZ 2161.

##### **Respiratory protection**

None required.

## **SECTION 9: Physical and chemical properties**

### **9.1. Information on basic physical and chemical properties**

<b>Physical state</b>	Liquid.
<b>Specific Physical Form:</b>	Viscous.
<b>Appearance/Odour</b>	light straw coloured, epoxy odour

## 3M™ Scotch-Weld™ Epoxy Adhesive DP100 Clear, Part B

Odour threshold	No data available.
pH	Not applicable.
Melting point/Freezing point	Not applicable.
Boiling point/Initial boiling point/Boiling range	>=249 °C
Flash point	249 °C [Test Method:Pensky-Martens Closed Cup]
Evaporation rate	Not applicable.
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	Not applicable.
Flammable Limits(UEL)	Not applicable.
Vapour pressure	<=4 Pa [@ 70 °C ]
Vapour density	Not applicable.
Density	1.17 g/ml
Relative density	1.17
Water solubility	Nil
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Autoignition temperature	No data available.
Decomposition temperature	No data available.
Viscosity	10,000 - 30,000 mPa-s [@ 23 °C ] [Details:MIT data]
Molecular weight	No data available.
VOC less H2O & exempt solvents	0 g/l [Test Method:calculated SCAQMD rule 443.1] [Details:when used as intended with Part A]
VOC less H2O & exempt solvents	0 g/l [Test Method:calculated SCAQMD rule 443.1] [Details:as supplied]
VOC less H2O & exempt solvents	0 % [Test Method:calculated SCAQMD rule 443.1] [Details:when used as intended with Part A]

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

### 10.2 Chemical stability

Stable.

### 10.3. Conditions to avoid

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

Heat.

### 10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.5 Incompatible materials

Strong acids.

Strong oxidising agents.

### 10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
------------------	------------------

None known.	
-------------	--

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1 Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

No health effects are expected.

#### Skin contact

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eye contact

Moderate eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

#### Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

Name	Route	Species	Value
Epoxy resin	Dermal	Rat	LD50 > 1,600 mg/kg
Epoxy resin	Ingestion	Rat	LD50 > 1,000 mg/kg

ATE = acute toxicity estimate

#### Skin Corrosion/Irritation

Name	Species	Value
Epoxy resin	Rabbit	Mild irritant

#### Serious Eye Damage/Irritation

Name	Species	Value
Epoxy resin	Rabbit	Moderate irritant

#### Skin Sensitisation

Name	Species	Value
Epoxy resin	Human and animal	Sensitising

#### Respiratory Sensitisation

Name	Species	Value
Epoxy resin	Human	Not classified

#### Germ Cell Mutagenicity



**3M™ Scotch-Weld™ Epoxy Adhesive DP100 Clear, Part B**

Name	Route	Value
Epoxy resin	In vivo	Not mutagenic
Epoxy resin	In Vitro	Some positive data exist, but the data are not sufficient for classification

**Carcinogenicity**

Name	Route	Species	Value
Epoxy resin	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Epoxy resin	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
Epoxy resin	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
Epoxy resin	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
Epoxy resin	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Epoxy resin	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
Epoxy resin	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Epoxy resin	Ingestion	auditory system   heart   endocrine system   hematopoietic system   liver   eyes   kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Exposure Levels**

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

**Interactive Effects**

Not determined.

**SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient

## 3M™ Scotch-Weld™ Epoxy Adhesive DP100 Clear, Part B

classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

### 12.1. Toxicity

#### Acute aquatic hazard:

GHS Acute 1: Very toxic to aquatic life.

#### Chronic aquatic hazard:

GHS Chronic 2: Toxic to aquatic life with long lasting effects.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Epoxy resin	25068-38-6	Water flea	Estimated	48 hours	LC50	0.95 mg/l
Epoxy resin	25068-38-6	Green Algae	Experimental	72 hours	EC50	>11 mg/l
Epoxy resin	25068-38-6	Rainbow trout	Experimental	96 hours	LC50	1.2 mg/l
Epoxy resin	25068-38-6	Water flea	Experimental	21 days	NOEC	0.3 mg/l
Epoxy resin	25068-38-6	Green Algae	Experimental	72 hours	NOEC	4.2 mg/l

### 12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Epoxy resin	25068-38-6	Experimental Biodegradation	28 days	BOD	0 % BOD/ThBOD	OECD 301C - MITI test (I)
Epoxy resin	25068-38-6	Estimated Hydrolysis		Hydrolytic half-life	<2 days (t 1/2)	Other methods

### 12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Epoxy resin	25068-38-6	Experimental BCF-Carp	28 days	Bioaccumulation factor	<=42	OECD 305E - Bioaccumulation flow-through fish test

### 12.4. Mobility in soil

Please contact manufacturer for more details

### 12.5 Other adverse effects

No information available.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate uncured product in a permitted waste incineration facility. Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste.

## SECTION 14: Transport Information

### Australian Dangerous Goods Code (ADG) - Road/Rail Transport

UN No.: UN3082

**Proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. , ( Epoxy resin )

**Class/Division:** 9

**Sub Risk:** Not applicable.

**Packing Group:** III

**Special Instructions:** Australian Dangerous Goods Code: Not subject to this code as per Special Provision AU01

**Hazchem Code:** •3Z

**IERG:** 47

### International Air Transport Association (IATA) - Air Transport

UN No.: UN3082

**Proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. , ( Epoxy resin )

**Class/Division:** 9

**Sub Risk:** Not applicable.

**Packing Group:** III

**Special Instructions:** Not restricted, as per Special Provision A197, environmentally hazardous substance exception.

### International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: UN3082

**Proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. , ( Epoxy resin )

**Class/Division:** 9

**Sub Risk:** Not applicable.

**Packing Group:** III

**Marine Pollutant:** Epoxy resin

**Special Instructions:** Not restricted, as per IMDG code 2.10.2.7, marine pollutant exception.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Australian Inventory Status:

The chemical components contained within this product are listed on the Australian Inventory of Chemical Substances and are in compliance with the requirements of the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

## SECTION 16: Other information

#### Revision information:

Complete document review.

**DISCLAIMER:** The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

**3M Australia SDSs are available at [www.3m.com.au](http://www.3m.com.au)**



## Safety Data Sheet

Copyright, 2018, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	10-3341-4	<b>Version number:</b>	6.00
<b>Issue Date:</b>	05/04/2018	<b>Supersedes date:</b>	11/04/2016

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Scotch-Weld™ Epoxy Adhesive DP100 Clear, Part A

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Accelerator for 2 part epoxy adhesive, Structural adhesive.

For Industrial or Professional use only.

#### 1.3. Supplier's details

**Address:** 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113  
**Telephone:** 136 136  
**E Mail:** productinfo.au@mmm.com  
**Website:** www.3m.com.au

#### 1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

### SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

#### 2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 2.

Skin Corrosion/Irritation: Category 2.

#### 2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

#### Signal word

## 3M™ Scotch-Weld™ Epoxy Adhesive DP100 Clear, Part A

WARNING!

### Symbols

Exclamation mark |

### Pictograms



### Hazard statements

H319 Causes serious eye irritation.  
H315 Causes skin irritation.

### Precautionary statements

#### Prevention:

P280A Wear eye/face protection.  
P280E Wear protective gloves.  
P264 Wash thoroughly after handling.

#### Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 If eye irritation persists: Get medical advice/attention.  
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
P332 + P313 If skin irritation occurs: Get medical advice/attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P321 Specific treatment (see Notes to Physician on this label).

### 2.3. Other assigned/identified product hazards

None known.

### 2.4. Other hazards which do not result in classification

May be harmful if swallowed.

## SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
Mercaptan Polymer	Trade Secret	80 - 95
2,4,6-tris(Dimethylamino)methylphenol	90-72-2	5 - 15
bis(Dimethylamino)methylphenol	71074-89-0	0.1 - 1.5

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin contact**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye contact**

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

**If swallowed**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

See Section 11.1. Information on toxicological effects.

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

**SECTION 5: Fire-fighting measures**

**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

**5.2. Special hazards arising from the substance or mixture**

None inherent in this product.

**Hazardous Decomposition or By-Products**

**Substance**

Carbon monoxide.  
Carbon dioxide.  
Hydrogen Sulfide  
Oxides of nitrogen.  
Oxides of sulphur.

**Condition**

During combustion.  
During combustion.  
During combustion.  
During combustion.  
During combustion.

**5.3. Special protective actions for fire-fighters**

No special protective actions for fire-fighters are anticipated.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

### 7.2. Conditions for safe storage including any incompatibilities

Store away from oxidising agents.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this Safety Data Sheet.

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

#### 8.2.2. Personal protective equipment (PPE)

##### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

##### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl rubber.

Neoprene.

Nitrile rubber.

Select and use gloves according to AS/NZ 2161.

##### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

## **SECTION 9: Physical and chemical properties**

### **9.1. Information on basic physical and chemical properties**

<b>Physical state</b>	Liquid.
<b>Specific Physical Form:</b>	Viscous.
<b>Appearance/Odour</b>	dark amber, strong mercaptan odor
<b>Odour threshold</b>	<i>No data available.</i>
<b>pH</b>	<i>Not applicable.</i>
<b>Melting point/Freezing point</b>	<i>Not applicable.</i>
<b>Boiling point/Initial boiling point/Boiling range</b>	$\geq 257$ °C
<b>Flash point</b>	257 °C [ <i>Test Method</i> :Closed Cup]
<b>Evaporation rate</b>	<i>Not applicable.</i>
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Flammable Limits(LEL)</b>	<i>Not applicable.</i>
<b>Flammable Limits(UEL)</b>	<i>Not applicable.</i>
<b>Vapour density</b>	<i>Not applicable.</i>
<b>Density</b>	1.15 g/ml
<b>Relative density</b>	1.15 [ <i>Ref Std</i> :WATER=1]
<b>Water solubility</b>	Negligible
<b>Solubility- non-water</b>	<i>No data available.</i>
<b>Partition coefficient: n-octanol/water</b>	<i>No data available.</i>
<b>Autoignition temperature</b>	<i>No data available.</i>
<b>Decomposition temperature</b>	<i>No data available.</i>
<b>Viscosity</b>	8,000 - 15,000 mPa-s [ <i>@ 22.8 °C</i> ]
<b>Molecular weight</b>	<i>No data available.</i>
<b>VOC less H2O &amp; exempt solvents</b>	0 g/l [ <i>Test Method</i> :calculated SCAQMD rule 443.1] [ <i>Details</i> :when used as intended with Part B]
<b>VOC less H2O &amp; exempt solvents</b>	0 g/l [ <i>Test Method</i> :calculated SCAQMD rule 443.1] [ <i>Details</i> :as supplied]
<b>VOC less H2O &amp; exempt solvents</b>	0 % [ <i>Test Method</i> :calculated SCAQMD rule 443.1] [ <i>Details</i> :when used as intended with Part B]

## **SECTION 10: Stability and reactivity**

### **10.1 Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

### **10.2 Chemical stability**

Stable.

### **10.3. Conditions to avoid**

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

### **10.4. Possibility of hazardous reactions**

Hazardous polymerisation will not occur.

### **10.5 Incompatible materials**

Strong oxidising agents.



**10.6 Hazardous decomposition products****Substance**

None known.

**Condition****SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

**11.1 Information on Toxicological effects****Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

**Inhalation**

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

**Skin contact**

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

**Eye contact**

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

**Ingestion**

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE2,000 - 5,000 mg/kg
Mercaptan Polymer	Dermal	Rabbit	LD50 > 10,200 mg/kg
Mercaptan Polymer	Ingestion	Rat	LD50 2,600 mg/kg
2,4,6-tris(Dimethylamino)methylphenol	Dermal	Rat	LD50 1,280 mg/kg
2,4,6-tris(Dimethylamino)methylphenol	Ingestion	Rat	LD50 1,000 mg/kg
bis(Dimethylamino)methylphenol	Ingestion		LD50 estimated to be 300 - 2,000 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Overall product	In vitro data	Irritant
Mercaptan Polymer	Rabbit	No significant irritation

**3M™ Scotch-Weld™ Epoxy Adhesive DP100 Clear, Part A**

2,4,6-tris(Dimethylamino)methyl)phenol	Rabbit	Corrosive
bis(Dimethylamino)methyl)phenol	similar compounds	Corrosive

**Serious Eye Damage/Irritation**

Name	Species	Value
Overall product	In vitro data	Severe irritant
Mercaptan Polymer	Rabbit	Mild irritant
2,4,6-tris(Dimethylamino)methyl)phenol	Rabbit	Corrosive
bis(Dimethylamino)methyl)phenol	similar compounds	Corrosive

**Skin Sensitisation**

Name	Species	Value
Mercaptan Polymer	Mouse	Sensitising
2,4,6-tris(Dimethylamino)methyl)phenol	Guinea pig	Not classified

**Respiratory Sensitisation**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
Mercaptan Polymer	In Vitro	Not mutagenic
2,4,6-tris(Dimethylamino)methyl)phenol	In Vitro	Not mutagenic

**Carcinogenicity**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
2,4,6-tris(Dimethylamino)methyl)phenol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Mercaptan Polymer	Ingestion	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 75 mg/kg/day	90 days
Mercaptan Polymer	Ingestion	liver	Some positive data exist, but the data are not sufficient for	Rat	NOAEL 250 mg/kg/day	90 days

**3M™ Scotch-Weld™ Epoxy Adhesive DP100 Clear, Part A**

			classification			
Mercaptan Polymer	Ingestion	endocrine system   heart   skin   immune system   nervous system   eyes   kidney and/or bladder   respiratory system   vascular system	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
2,4,6-tris(Dimethylamino)methylphenol	Dermal	skin   liver   nervous system   auditory system   hematopoietic system   eyes	Not classified	Rat	NOAEL 125 mg/kg/day	28 days

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Exposure Levels**

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

**Interactive Effects**

Not determined.

**SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

**12.1. Toxicity**

**Acute aquatic hazard:**

Not acutely toxic to aquatic life by GHS criteria.

**Chronic aquatic hazard:**

Not chronically toxic to aquatic life by GHS criteria.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Mercaptan Polymer	Trade Secret		Data not available or insufficient for classification			
2,4,6-tris(Dimethylamino)methylphenol	90-72-2	Common Carp	Experimental	96 hours	LC50	175 mg/l
2,4,6-tris(Dimethylamino)methylphenol	90-72-2	Grass Shrimp	Experimental	96 hours	LC50	718 mg/l

**3M™ Scotch-Weld™ Epoxy Adhesive DP100 Clear, Part A**

2,4,6-tris(Dimethylamino)methylphenol	90-72-2	Green algae	Experimental	72 hours	EC50	84 mg/l
2,4,6-tris(Dimethylamino)methylphenol	90-72-2	Green algae	Experimental	72 hours	NOEC	6.25 mg/l
bis(Dimethylamino)methylphenol	71074-89-0		Data not available or insufficient for classification			

**12.2. Persistence and degradability**

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Mercaptan Polymer	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
2,4,6-tris(Dimethylamino)methylphenol	90-72-2	Experimental Biodegradation	28 days	BOD	4 % weight	OECD 301D - Closed bottle test
bis(Dimethylamino)methylphenol	71074-89-0	Estimated Biodegradation	28 days	BOD	20 % weight	OECD 301C - MITI test (I)

**12.3 : Bioaccumulative potential**

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Mercaptan Polymer	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
2,4,6-tris(Dimethylamino)methylphenol	90-72-2	Experimental Bioconcentration		Log Kow	-0.66	Other methods
bis(Dimethylamino)methylphenol	71074-89-0	Estimated Bioconcentration		Log Kow	-2.34	Estimated: Octanol-water partition coefficient

**12.4. Mobility in soil**

Please contact manufacturer for more details

**12.5 Other adverse effects**

No information available.

**SECTION 13: Disposal considerations****13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

## 3M™ Scotch-Weld™ Epoxy Adhesive DP100 Clear, Part A

Incinerate uncured product in a permitted waste incineration facility. Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste.

## SECTION 14: Transport Information

### Australian Dangerous Goods Code (ADG) - Road/Rail Transport

**UN No.:** Not applicable.

**Proper shipping name:** Not applicable.

**Class/Division:** Not applicable.

**Sub Risk:** Not applicable.

**Packing Group:** Not applicable.

**Hazchem Code:** Not applicable

**IERG:** Not applicable.

### International Air Transport Association (IATA) - Air Transport

**UN No.:** Not applicable.

**Proper shipping name:** Not applicable.

**Class/Division:** Not applicable.

**Sub Risk:** Not applicable.

**Packing Group:** Not applicable.

### International Maritime Dangerous Goods Code (IMDG)- Marine Transport

**UN No.:** Not applicable.

**Proper shipping name:** Not applicable.

**Class/Division:** Not applicable.

**Sub Risk:** Not applicable.

**Packing Group:** Not applicable.

**Marine Pollutant:** Not applicable.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Australian Inventory Status:

The chemical components contained within this product are listed on the Australian Inventory of Chemical Substances and are in compliance with the requirements of the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

**Poison Schedule:** This product has not been assessed for poisons scheduling as the product is intended for industrial and professional use only.

## SECTION 16: Other information

#### Revision information:

Complete document review.

**DISCLAIMER:** The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to

**3M™ Scotch-Weld™ Epoxy Adhesive DP100 Clear, Part A**

satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

**3M Australia SDSs are available at [www.3m.com.au](http://www.3m.com.au)**