

# Safety Data Sheet

Copyright, 2021, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 11-3432-9
 Version number:
 5.00

 Issue Date:
 08/08/2021
 Supersedes date:
 14/06/2016

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

# **SECTION 1: Identification**

#### 1.1. Product identifier

3M<sup>™</sup> Hot Melt Adhesive 3792LM Q

#### **Product Identification Numbers**

62-3760-9132-8

#### 1.2. Recommended use and restrictions on use

## Recommended use

Adhesive, hot-melt adhesive for bonding heat sensitive materials such as wood and coated paper

For Industrial or Professional use only.

# 1.3. Supplier's details

Address: 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113

**Telephone:** 136 136

E Mail: productinfo.au@mmm.com

Website: www.3m.com.au

### 1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

# **SECTION 2: Hazard identification**

This product is NOT classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

### 2.1. Classification of the substance or mixture

Not applicable.

### 2.2. Label elements

#### Signal word

Not applicable.

#### **Symbols**

Not applicable.

#### **Pictograms**

Not applicable

#### 2.3. Other assigned/identified product hazards

May cause thermal burns. 3M Avoid contact with hot extruded material or applicator tip. Avoid direct eye exposure to vapours. In case of eye/skin contact with molten material, immediately flush with cold water

#### 2.4. Other hazards which do not result in classification

None known.

# **SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
Ethylene-Vinyl Acetate Polymer	Mixture	40 - 70
Hydrocarbon resin	Mixture	10 - 30
Hydrocarbons, C6-20, Polymers,	69430-35-9	10 - 20
Hydrogenated		
Vinyl Acetate	108-05-4	< 0.5

# **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you are concerned, get medical advice.

#### Skin contact

Immediately flush skin with large amounts of cold water for at least 15 minutes. DO NOT ATTEMPT TO REMOVE MOLTEN MATERIAL. Cover affected area with a clean dressing. Get immediate medical attention.

### Eye contact

Immediately flush eyes with large amounts of water for at least 15 minutes. DO NOT ATTEMPT TO REMOVE MOLTEN MATERIAL. Get immediate medical attention.

## If swallowed

Rinse mouth. If you are concerned, get medical advice.

#### 4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

#### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

## 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

#### **Hazardous Decomposition or By-Products**

Substance

Carbon monoxide. Carbon dioxide.

#### Condition

During combustion.

During combustion.

#### 5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

# **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

# 7.2. Conditions for safe storage including any incompatibilities

Store away from oxidising agents.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Vinyl Acetate	108-05-4	ACGIH	TWA:10 ppm;STEL:15 ppm	A3: Confirmed animal
				carcinogen.
Vinyl Acetate	108-05-4	Australia OELs	TWA(8 hours): 35 mg/m3 (10	
			ppm); STEL(15 minutes): 70	
			mg/m3(20 ppm)	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

Australia OELs: Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling Sen: Sensitiser

## 3M™ Hot Melt Adhesive 3792LM Q

Sk: Absorption through the skin may be a significant source of exposure.

#### 8.2. Exposure controls

#### 8.2.1. Engineering controls

No engineering controls required.

# 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

## Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Butyl rubber.

Polymer laminate

Select and use gloves according to AS/NZ 2161.

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer. Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

#### Thermal hazards

Wear heat insulating gloves when handling hot material to prevent thermal burns.

# **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

Physical state	Solid.
Specific Physical Form:	Waxy Solid
Colour	Colourless
Odour	Odourless
Odour threshold	No data available.
pH	Not applicable.
Melting point/Freezing point	No data available.

Boiling point/Initial boiling point/Boiling range	Not applicable.			
Flash point	>=232.2 °C [Test Method:Cleveland Open Cup]			
	[Details:Conditions: ASTM D-92-72]			
Evaporation rate	Not applicable.			
Flammability (solid, gas)	Not classified			
Flammable Limits(LEL)	Not applicable.			
Flammable Limits(UEL)	Not applicable.			
Vapor Density and/or Relative Vapor Density	Nil			
Density	1.01 g/cm3			
Relative density	1.01 [Ref Std:WATER=1]			
Water solubility	Nil			
Solubility- non-water	No data available.			
Partition coefficient: n-octanol/water	No data available.			
Autoignition temperature	No data available.			
Decomposition temperature	No data available.			
Viscosity/Kinematic Viscosity	Not applicable.			
Volatile organic compounds (VOC)	0 g/l [Test Method:calculated SCAQMD rule 443.1]			
Percent volatile	0 % weight			
VOC less H2O & exempt solvents	0 g/l [Test Method:calculated SCAQMD rule 443.1]			
Molecular weight	No data available.			
Solids content	100 %			

# Nanoparticles

This material does not contain nanoparticles.

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

# 10.2 Chemical stability

Stable.

# 10.3. Conditions to avoid

None known.

## 10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

#### 10.5 Incompatible materials

Strong oxidising agents.

## 10.6 Hazardous decomposition products

Substance
None known.

Condition

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

#### 11.1 Information on Toxicological effects

#### Signs and Symptoms of Exposure

## Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

May cause additional health effects (see below).

#### Skin contact

During heating: Thermal Burns: Signs/symptoms may include intense pain, redness and swelling, and tissue destruction. May cause additional health effects (see below).

## Eye contact

During heating: Thermal Burns: Signs/symptoms may include severe pain, redness and swelling, and tissue destruction.

## Ingestion

May cause additional health effects (see below).

#### **Additional Health Effects:**

## Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

## **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity** 

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Ethylene-Vinyl Acetate Polymer	Dermal		LD50 estimated to be > 5,000 mg/kg
Ethylene-Vinyl Acetate Polymer	Ingestion	Rat	LD50 > 1,000 mg/kg
Hydrocarbon resin	Dermal		LD50 estimated to be > 5,000 mg/kg
Hydrocarbon resin	Ingestion		LD50 estimated to be > 5,000 mg/kg
Hydrocarbons, C6-20, Polymers, Hydrogenated	Dermal	Rat	LD50 > 2,000 mg/kg
Hydrocarbons, C6-20, Polymers, Hydrogenated	Ingestion	Ingestion Rat LD50 > 5,000 mg/kg	
Vinyl Acetate	Dermal	Rabbit	LD50 2,320 mg/kg
Vinyl Acetate	Inhalation-Vapour (4 hours)	a-Vapour (4 Rat LC50 11.3 mg/l	
Vinyl Acetate	Ingestion	Rat	LD50 2,920 mg/kg

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

Name	Species	Value
Ethylene-Vinyl Acetate Polymer	Professional judgement	No significant irritation
Hydrocarbon resin	Professional judgement	No significant irritation
Vinyl Acetate	Rabbit	Minimal irritation

Serious Eye Damage/Irritation

Name	Species	Value
Ethylene-Vinyl Acetate Polymer	Professional judgement	No significant irritation
Hydrocarbon resin	Professional judgement	No significant irritation
Vinyl Acetate	Rabbit	Mild irritant

# **Skin Sensitisation**

Name	Species	Value
Vinyl Acetate	Guinea pig	Not classified

# **Respiratory Sensitisation**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Vinyl Acetate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Vinyl Acetate	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Vinyl Acetate	Ingestion	Multiple animal	Carcinogenic.
		species	
Vinyl Acetate	Inhalation	Rat	Carcinogenic.

# **Reproductive Toxicity**

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	<b>Exposure Duration</b>
Vinyl Acetate	Ingestion	Not classified for	Rat	NOAEL 140	2 generation
-		female reproduction		mg/kg/day	
Vinyl Acetate	Ingestion	Not classified for	Rat	NOAEL 140	2 generation
	-	male reproduction		mg/kg/day	
Vinyl Acetate	Ingestion	Not classified for	Rat	NOAEL 700	2 generation
		development		mg/kg/day	
Vinyl Acetate	Inhalation	Not classified for	Rat	NOAEL 0.7	during
- 		development		mg/l	organogenesis

# Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Vinyl Acetate	Inhalation	respiratory irritation	May cause respiratory irritation	Human and animal	NOAEL Not available	
Vinyl Acetate	Inhalation	central nervous system depression	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	

# Specific Target Organ Toxicity - repeated exposure

\_\_\_\_\_

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Ethylene- Vinyl Acetate Polymer	Ingestion	liver	Not classified	Rat	NOAEL 4,000 mg/kg/day	90 days
Vinyl Acetate	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL 0.2 mg/l	104 weeks
Vinyl Acetate	Inhalation	heart   hematopoietic system   liver   kidney and/or bladder	Not classified	Rat	NOAEL 2.1 mg/l	104 weeks
Vinyl Acetate	Inhalation	endocrine system	Not classified	Rat	NOAEL 0.07 mg/l	120 days
Vinyl Acetate	Inhalation	immune system	Not classified	Multiple animal species	NOAEL 3.5 mg/l	3 months
Vinyl Acetate	Inhalation	nervous system	Not classified	Multiple animal species	NOAEL 2.1 mg/l	104 weeks
Vinyl Acetate	Inhalation	gastrointestinal tract	Not classified	Mouse	NOAEL 3.5 mg/l	3 months
Vinyl Acetate	Ingestion	liver	Not classified	Rat	LOAEL 684 mg/kg/day	3 months
Vinyl Acetate	Ingestion	hematopoietic system   nervous system   kidney and/or bladder	Not classified	Rat	NOAEL 235 mg/kg/day	104 weeks
Vinyl Acetate	Ingestion	immune system   respiratory   system	Not classified	Mouse	NOAEL 950 mg/kg/day	3 months
Vinyl Acetate	Ingestion	heart	Not classified	Rat	NOAEL 235 mg/kg/day	104 weeks

#### **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

#### **Exposure Levels**

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

#### **Interactive Effects**

Not determined.

# **SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

## 12.1. Toxicity

## Acute aquatic hazard:

Not acutely toxic to aquatic life by GHS criteria.

## Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Ethylene-Vinyl	Mixture		Data not			N/A
Acetate			available or			
Polymer			insufficient for			
			classification			
Hydrocarbon	Mixture		Data not			N/A
resin			available or			
			insufficient for			
			classification			
Hydrocarbons,	69430-35-9		Data not			N/A
C6-20,			available or			
Polymers,			insufficient for			
Hydrogenated			classification			
Vinyl Acetate	108-05-4	Green Algae	Experimental	72 hours	EC50	8.9 mg/l
Vinyl Acetate	108-05-4	Medaka	Experimental	96 hours	LC50	2.4 mg/l
Vinyl Acetate	108-05-4	Water flea	Experimental	48 hours	EC50	9.2 mg/l
Vinyl Acetate	108-05-4	Fathead	Experimental	34 days	NOEC	0.551 mg/l
		minnow	_	-		
Vinyl Acetate	108-05-4	Green Algae	Experimental	72 hours	NOEC	0.2 mg/l
Vinyl Acetate	108-05-4	Water flea	Experimental	21 days	NOEC	0.32 mg/l

# 12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Ethylene-Vinyl	Mixture	Data not			N/A	
Acetate		available-				
Polymer		insufficient				
Hydrocarbon	Mixture	Estimated	28 days	BOD	0 %	Non-standard method
resin		Biodegradation			BOD/ThBOD	
Hydrocarbons,	69430-35-9	Data not			N/A	
C6-20,		available-				
Polymers,		insufficient				
Hydrogenated						
Vinyl Acetate	108-05-4	Experimental	14 days	BOD	90 %	OECD 301C - MITI
		Biodegradation			BOD/ThBOD	test (I)

# 12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Ethylene-Vinyl	Mixture	Data not	N/A	N/A	N/A	N/A
Acetate		available or				
Polymer		insufficient for				
		classification				
Hydrocarbon	Mixture	Data not	N/A	N/A	N/A	N/A
resin		available or				
		insufficient for				
		classification				
Hydrocarbons,	69430-35-9	Data not	N/A	N/A	N/A	N/A
C6-20,		available or				
Polymers,		insufficient for				

Hydrogenated	classification			
Vinyl Acetate	Experimental Bioconcentrati	Log Kow	0.73	Non-standard method
	on			

#### 12.4. Mobility in soil

Please contact manufacturer for more details

#### 12.5 Other adverse effects

No information available.

# **SECTION 13: Disposal considerations**

#### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. Proper destruction may require the use of additional fuel during incineration processes. As a disposal alternative, incinerate in a permitted waste incineration facility.

# **SECTION 14: Transport Information**

Australian Dangerous Goods Code (ADG) - Road/Rail Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable. Sub Risk: Not applicable. Packing Group: Not applicable.

Hazchem Code: Not applicable

IERG: Not applicable.

International Air Transport Association (IATA) - Air Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable. Sub Risk: Not applicable. Packing Group: Not applicable.

#### International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable. Sub Risk: Not applicable. Packing Group: Not applicable. Marine Pollutant: Not applicable.

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **Australian Inventory Status:**

The chemical components contained within this product are listed on the Australian Inventory of Chemical Substances and are in compliance with the requirements of the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

**Poison Schedule:** This product is intended for Industrial or Professional Use only and therefore is not packaged and labelled in accordance with the requirements of the Standard for the Uniform Scheduling of Medicines and Poisons.

# **SECTION 16: Other information**

#### **Revision information:**

Complete document review.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au