

## Safety Data Sheet

Copyright,2022, 3M Company.All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	10-7828-6	Version number:	7.00
Issue Date:	26/04/2022	Supersedes date:	15/02/2021

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

## **SECTION 1: Identification**

**1.1. Product identifier** 3M CGS-30 Thinner

**Product Identification Numbers** 75-3465-0420-4

### 1.2. Recommended use and restrictions on use

Recommended use Solvent

For Industrial or Professional use only.

#### 1.3. Supplier's details

Address:	3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113
Telephone:	136 136
E Mail:	productinfo.au@mmm.com
Website:	www.3m.com.au

**1.4. Emergency telephone number** EMERGENCY: 1800 097 146 (Australia only)

## **SECTION 2: Hazard identification**

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

### 2.1. Classification of the substance or mixture

Flammable liquid: Category 3.

#### 2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

## Signal word Warning

Symbols Flame |

### **Pictograms**



Hazard statements H226

Flammable liquid and vapour.

### **Precautionary statements**

Prevention:	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
	No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P280E	Wear protective gloves.
Response:	
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P370 + P378	In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.
Storage:	
P403 + P235	Store in a well-ventilated place. Keep cool.
Disposal:	
P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**2.3. Other assigned/identified product hazards** None known.

**2.4. Other hazards which do not result in classification** May be harmful if swallowed. May be harmful in contact with skin. Harmful to aquatic life.

# **SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	CAS Nbr	% by Weight

Ethyl 3-ethoxypropionate

763-69-9

> 99

## **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

#### Eye contact

No need for first aid is anticipated.

#### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

#### 4.3. Indication of any immediate medical attention and special treatment required Not applicable

## **SECTION 5: Fire-fighting measures**

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

#### **Hazardous Decomposition or By-Products**

<u>Substance</u>	<u>Condition</u>
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.

#### 5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

#### Hazchem Code: •3Y

## **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. WARNING ! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

## **6.2.** Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or

Page: 3 of 10

bodies of water.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire extinguishing foam that is resistant to polar solvents. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

Avoid eye contact. For industrial/occupational use only. Not for consumer sale or use. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapour accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer. Vapours may travel long distances along the ground or floor to an ignition source and flash back.

## 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidising agents.

## **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters

## **Occupational exposure limits**

No occupational exposure limit values exist for any of the components listed in Section 3 of this Safety Data Sheet.

## 8.2. Exposure controls

## 8.2.1. Engineering controls

Use explosion-proof ventilation equipment.

## **8.2.2.** Personal protective equipment (PPE)

## **Eye/face protection**

Eye protection not required.

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl rubber.

Select and use gloves according to AS/NZ 2161.

### **Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours

For questions about suitability for a specific application, consult with your respirator manufacturer. Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

## **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state	Liquid.	
Specific Physical Form:	Liquid.	
Colour	Colourless	
Odour	Solvent	
Odour threshold	No data available.	
рН	Not applicable.	
Melting point/Freezing point	Not applicable.	
Boiling point/Initial boiling point/Boiling range	165 °C	
Flash point	58.9 °C [Test Method:Closed Cup]	
Evaporation rate	No data available.	
Flammability (solid, gas)	Not applicable.	
Flammable Limits(LEL)	1.05 %	
Flammable Limits(UEL)	No data available.	
Vapour pressure	< 133.3 Pa [@ 20 °C ]	
Vapor Density and/or Relative Vapor Density	> 1 [ <i>Ref Std</i> :AIR=1]	
Density	0.95 g/ml	
Relative density	0.95 [ <i>Ref Std</i> :WATER=1]	
Water solubility	Moderate	
Solubility- non-water	No data available.	
Partition coefficient: n-octanol/water	No data available.	
Autoignition temperature	376.7 °C	
Decomposition temperature	No data available.	
Viscosity/Kinematic Viscosity	No data available.	
Volatile organic compounds (VOC)	950 g/l	
Percent volatile	100 %	
VOC less H2O & exempt solvents	950 g/l	
Molecular weight	No data available.	

## **SECTION 10: Stability and reactivity**

## 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

## 10.2 Chemical stability

Stable.

## 10.3. Conditions to avoid

Heat. Sparks and/or flames.

#### 10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

## **10.5 Incompatible materials**

Strong oxidising agents.

## 10.6 Hazardous decomposition products

<u>Substance</u>

None known.

Condition

## **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

**11.1 Information on Toxicological effects** 

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

### Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

#### Skin contact

May be harmful in contact with skin.

#### Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

#### Ingestion

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

#### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### **Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >2,000 - =5,000 mg/kg
	T (:		
Overall product	Ingestion		No data available; calculated ATE >2,000 -
			=5,000 mg/kg
Ethyl 3-ethoxypropionate	Dermal	Rabbit	LD50 4,080 mg/kg
Ethyl 3-ethoxypropionate	Inhalation-Vapour (4	Rat	LC50 > 14.4  mg/l
	hours)		_

Ethyl 3-ethoxypropionate	Ingestion	Rat	LD50 3,200 mg/kg
ATE = acute toxicity estimate			

### Skin Corrosion/Irritation

Name	Species	Value
Ethyl 3-ethoxypropionate	Rabbit	No significant irritation

#### Serious Eye Damage/Irritation

Name	Species	Value
Ethyl 3-ethoxypropionate	Rabbit	Mild irritant

#### **Skin Sensitisation**

Name	Species	Value
Ethyl 3-ethoxypropionate	Guinea pig	Not classified

#### **Respiratory Sensitisation**

For the component/components, either no data are currently available or the data are not sufficient for classification.

#### Germ Cell Mutagenicity

Name	Route	Value
Ethyl 3-ethoxypropionate	In Vitro	Not mutagenic

### Carcinogenicity

For the component/components, either no data are currently available or the data are not sufficient for classification.

#### **Reproductive Toxicity**

#### **Reproductive and/or Developmental Effects**

For the component/components, either no data are currently available or the data are not sufficient for classification.

### Target Organ(s)

#### Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

#### Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Ethyl 3- ethoxypropion ate	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 6 mg/l	90 days
Ethyl 3- ethoxypropion ate	Inhalation	nervous system   heart   liver   immune system   kidney and/or bladder	Not classified	Rat	NOAEL 6 mg/l	17 days
Ethyl 3- ethoxypropion ate	Ingestion	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	17 days
Ethyl 3- ethoxypropion ate	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

Ethyl 3- ethoxypropion	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	17 days
ethoxypropion					iiig/kg/uay	
ate		respiratory				
		system				

## Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

### **Exposure Levels**

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

#### **Interactive Effects**

Not determined.

## **SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

### Acute aquatic hazard:

GHS Acute 3: Harmful to aquatic life.

### Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available.

Material	CAS Number	Organism	Туре	Exposure	Test endpoint	Test result
Ethyl 3- ethoxypropiona te	763-69-9	Activated sludge	Experimental	5 hours	EC50	>5,000 mg/l
Ethyl 3- ethoxypropiona te	763-69-9	Fathead minnow	Experimental	96 hours	LC50	45.3 mg/l
Ethyl 3- ethoxypropiona te	763-69-9	Green Algae	Experimental	72 hours	EC50	>86 mg/l
Ethyl 3- ethoxypropiona te	763-69-9	Water flea	Experimental	48 hours	EC50	>92 mg/l
Ethyl 3- ethoxypropiona te	763-69-9	Green Algae	Experimental	72 hours	NOEC	86 mg/l

## 12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Ethyl 3-	763-69-9	Experimental		Photolytic half-	1.2 days (t 1/2)	Non-standard method
ethoxypropiona		Photolysis		life (in air)		
te						

#### 3M CGS-30 Thinner

Ethyl 3-	763-69-9	Experimental	18 days	% CO2	100 % weight	OECD 301B - Modified
ethoxypropiona		Biodegradation		produced		sturm or CO2
te						

### **12.3 : Bioaccumulative potential**

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Ethyl 3-	763-69-9	Experimental		Log Kow	1.35	Non-standard method
ethoxypropiona		Bioconcentrati				
te		on				

### 12.4. Mobility in soil

Please contact manufacturer for more details

## 12.5 Other adverse effects

No information available.

## **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility.

## **SECTION 14: Transport Information**

Australian Dangerous Goods Code (ADG) - Road/Rail Transport UN No.: UN1263 Proper shipping name: PAINT RELATED MATERIAL Class/Division: 3

Sub Risk: Not applicable. Packing Group: III Special Instructions: Limited quantity may apply Hazchem Code: •3Y IERG: 14

International Air Transport Association (IATA) - Air Transport UN No.: UN1263 Proper shipping name: PAINT RELATED MATERIAL Class/Division: 3 Sub Risk: Not applicable. Packing Group: III

International Maritime Dangerous Goods Code (IMDG)- Marine Transport UN No.: UN1263 Proper shipping name: PAINT RELATED MATERIAL Class/Division: 3 Sub Risk: Not applicable. Packing Group: III Marine Pollutant: Not applicable. Special Instructions: Limited quantity may apply

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **Australian Inventory Status:**

All components of this product are listed on or exempt from the Australian Inventory of Industrial Chemicals (AIIC). Conditions may apply prior to introduction for direct importers of this product, Please contact 3M Australia on 136 136 for further details.

**Poison Schedule:** This product is intended for Industrial or Professional Use only and therefore is not packaged and labelled in accordance with the requirements of the Standard for the Uniform Scheduling of Medicines and Poisons.

## **SECTION 16: Other information**

## **Revision information:**

Complete document review.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

### 3M Australia SDSs are available at www.3m.com.au