



Safety Data Sheet

Copyright,2022, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|------------------------|------------|-------------------------|------------|
| Document group: | 26-6728-5 | Version number: | 3.00 |
| Issue Date: | 15/05/2022 | Supersedes date: | 14/06/2020 |

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

SECTION 1: Identification

1.1. Product identifier

3M™ Scotch-Brite™ Products, EXL Unitized AMED, Products, Wheels, Blocks, Discs, Roloc™ TR; TS

1.2. Recommended use and restrictions on use

Recommended use

Abrasive Product

For Industrial or Professional use only.

1.3. Supplier's details

Address: 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113
Telephone: 136 136
E Mail: productinfo.au@mmm.com
Website: www.3m.com.au

1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

SECTION 2: Hazard identification

This product is NOT classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

Not applicable.

2.2. Label elements

Signal word

Not applicable.

Symbols

Not applicable.

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide.

Carbon dioxide.

Condition

During combustion.

During combustion.

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Observe precautions from other sections.

6.2. Environmental precautions

Not applicable.

6.3. Methods and material for containment and cleaning up

Not applicable.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Avoid breathing of dust created by sanding, grinding or machining. Damaged product can break apart during use and cause serious injury to face or eyes. Check product for damage such as cracks or nicks prior to use. Replace if damaged. Always wear eye and face protection when working at sanding or grinding operations or when near such operations. Combustible dust may form by action of this product on another material (substrate). Dust generated from the substrate during use of this product may be explosive if in sufficient concentration with an ignition source. Dust deposits should not be allowed to accumulate on surfaces because of the potential for secondary explosions.

7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | CAS Nbr | Agency | Limit type | Additional comments |
|--------------------------------------|------------|----------------|--|--------------------------------|
| Aluminum Oxide Mineral (non-fibrous) | 1344-28-1 | Australia OELs | TWA(Inspirable dust)(8 hours):10 mg/m ³ | |
| Aluminum, insoluble compounds | 1344-28-1 | ACGIH | TWA(respirable fraction):1 mg/m ³ | A4: Not class. as human carcin |
| Titanium dioxide | 13463-67-7 | ACGIH | TWA:10 mg/m ³ | A4: Not class. as human |

| | | | | |
|------------------|------------|----------------|--|--------------------------------|
| | | | | carcin |
| Titanium dioxide | 13463-67-7 | Australia OELs | TWA(Inspirable dust)(8 hours):10 mg/m ³ | |
| Talc | 14807-96-6 | ACGIH | TWA(respirable fraction):2 mg/m ³ | A4: Not class. as human carcin |
| Talc | 14807-96-6 | Australia OELs | TWA(8 hours):2.5 mg/m ³ | |
| Stearates | 4485-12-5 | ACGIH | TWA(respirable fraction):3 mg/m ³ ;TWA(inhalable fraction):10 mg/m ³ | A4: Not class. as human carcin |
| Stearates | 4485-12-5 | Australia OELs | TWA(Inspirable dust)(8 hours):10 mg/m ³ | |
| Paraffin oil | 64742-52-5 | Australia OELs | TWA(as mist)(8 hours):5 mg/m ³ | |

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

8.2. Exposure controls

8.2.1. Engineering controls

Provide appropriate local exhaust ventilation for sanding, grinding or machining. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Warning: Excessive operating speed or generation of extreme heat may result in harmful emissions. Use local exhaust ventilation. Provide local exhaust at process emission sources to control exposure near the source and to prevent the escape of dust into the work area. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

8.2.2. Personal protective equipment (PPE)

Eye/face protection

To minimise the risk of injury to face and eyes, always wear eye and face protection when working at sanding or grinding operations or when near such operations. Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

Skin/hand protection

Wear appropriate gloves to minimise risk of injury to skin from contact with dust or physical abrasion from grinding or sanding.

Respiratory protection

Assess exposure concentrations of all materials involved in the work process. Consider material being abraded when determining the appropriate respiratory protection. Select and use appropriate respirators to prevent inhalation overexposure.

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following

respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for particulates.

For questions about suitability for a specific application, consult with your respirator manufacturer.
Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|---------------------------|
| Physical state | Solid. |
| Colour | Brown |
| Odour | Slight Polymeric |
| Odour threshold | <i>Not applicable.</i> |
| pH | <i>Not applicable.</i> |
| Melting point/Freezing point | <i>Not applicable.</i> |
| Boiling point/Initial boiling point/Boiling range | <i>Not applicable.</i> |
| Flash point | <i>Not applicable.</i> |
| Evaporation rate | <i>Not applicable.</i> |
| Flammability (solid, gas) | Not classified |
| Flammable Limits(LEL) | <i>Not applicable.</i> |
| Flammable Limits(UEL) | <i>Not applicable.</i> |
| Vapour pressure | <i>Not applicable.</i> |
| Vapor Density and/or Relative Vapor Density | <i>Not applicable.</i> |
| Density | <i>Not applicable.</i> |
| Relative density | <i>Not applicable.</i> |
| Water solubility | <i>Not applicable.</i> |
| Solubility- non-water | <i>Not applicable.</i> |
| Partition coefficient: n-octanol/water | <i>Not applicable.</i> |
| Autoignition temperature | <i>Not applicable.</i> |
| Decomposition temperature | <i>Not applicable.</i> |
| Viscosity/Kinematic Viscosity | <i>Not applicable.</i> |
| Volatile organic compounds (VOC) | <i>No data available.</i> |
| Percent volatile | <i>No data available.</i> |
| VOC less H ₂ O & exempt solvents | <i>No data available.</i> |
| Molecular weight | <i>No data available.</i> |

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is considered to be non reactive under normal use conditions

10.2 Chemical stability

Stable.

10.3. Conditions to avoid

None known.

10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products**Substance**

None known.

Condition**SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects**Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Dust created by grinding, sanding, or machining may cause irritation of the respiratory system. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Skin contact

Mechanical skin irritation: Signs/symptoms may include abrasion, redness, pain, and itching.

Eye contact

Mechanical eye irritation: Signs/symptoms may include pain, redness, tearing and corneal abrasion. Dust created by grinding, sanding, or machining may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion

No known health effects.

Additional information:

- This document covers only the 3M product. For complete assessment, when determining the degree of hazard, the material being abraded must also be considered. Dust created by grinding, sanding, or machining may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|--------------------------------------|--------------------------------|---------|--|
| Overall product | Ingestion | | No data available; calculated ATE >5,000 mg/kg |
| Aluminum Oxide Mineral (non-fibrous) | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| Aluminum Oxide Mineral (non-fibrous) | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 2.3 mg/l |
| Aluminum Oxide Mineral (non-fibrous) | Ingestion | Rat | LD50 > 5,000 mg/kg |
| Potassium tetrafluoroborate | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| Potassium tetrafluoroborate | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 5.3 mg/l |

| | | | |
|---|-----------------------------------|--------|------------------------------------|
| Potassium tetrafluoroborate | Ingestion | Rat | LD50 5,854 mg/kg |
| Talc | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| Talc | Ingestion | | LD50 estimated to be > 5,000 mg/kg |
| Lithium Stearate | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| Lithium Stearate | Ingestion | Rat | LD50 > 5,000 mg/kg |
| Titanium dioxide | Dermal | Rabbit | LD50 > 10,000 mg/kg |
| Titanium dioxide | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 6.82 mg/l |
| Titanium dioxide | Ingestion | Rat | LD50 > 10,000 mg/kg |
| Hydrotreated heavy naphthenic petroleum distillates | Dermal | Rabbit | LD50 > 2,000 mg/kg |
| Hydrotreated heavy naphthenic petroleum distillates | Ingestion | Rat | LD50 > 5,000 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|---|-------------------|---------------------------|
| Aluminum Oxide Mineral (non-fibrous) | Rabbit | No significant irritation |
| Potassium tetrafluoroborate | Rabbit | No significant irritation |
| Talc | Rabbit | No significant irritation |
| Lithium Stearate | similar compounds | No significant irritation |
| Titanium dioxide | Rabbit | No significant irritation |
| Hydrotreated heavy naphthenic petroleum distillates | Rabbit | Minimal irritation |

Serious Eye Damage/Irritation

| Name | Species | Value |
|---|-------------------|---------------------------|
| Aluminum Oxide Mineral (non-fibrous) | Rabbit | No significant irritation |
| Potassium tetrafluoroborate | Rabbit | No significant irritation |
| Talc | Rabbit | No significant irritation |
| Lithium Stearate | similar compounds | Mild irritant |
| Titanium dioxide | Rabbit | No significant irritation |
| Hydrotreated heavy naphthenic petroleum distillates | Rabbit | Mild irritant |

Skin Sensitisation

| Name | Species | Value |
|---|------------------|----------------|
| Titanium dioxide | Human and animal | Not classified |
| Hydrotreated heavy naphthenic petroleum distillates | Guinea pig | Not classified |

Respiratory Sensitisation

| Name | Species | Value |
|------|---------|----------------|
| Talc | Human | Not classified |

Germ Cell Mutagenicity

| Name | Route | Value |
|--------------------------------------|----------|---------------|
| Aluminum Oxide Mineral (non-fibrous) | In Vitro | Not mutagenic |
| Talc | In Vitro | Not mutagenic |
| Talc | In vivo | Not mutagenic |
| Titanium dioxide | In Vitro | Not mutagenic |
| Titanium dioxide | In vivo | Not mutagenic |

Carcinogenicity

| Name | Route | Species | Value |
|------|-------|---------|-------|
|------|-------|---------|-------|

| | | | |
|---|------------|-------------------------|--|
| Aluminum Oxide Mineral (non-fibrous) | Inhalation | Rat | Not carcinogenic |
| Talc | Inhalation | Rat | Some positive data exist, but the data are not sufficient for classification |
| Titanium dioxide | Ingestion | Multiple animal species | Not carcinogenic |
| Titanium dioxide | Inhalation | Rat | Carcinogenic. |
| Hydrotreated heavy naphthenic petroleum distillates | Ingestion | Rat | Not carcinogenic |
| Hydrotreated heavy naphthenic petroleum distillates | Dermal | Mouse | Some positive data exist, but the data are not sufficient for classification |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test result | Exposure Duration |
|------|-----------|--------------------------------|---------|----------------------|----------------------|
| Talc | Ingestion | Not classified for development | Rat | NOAEL 1,600 mg/kg | during organogenesis |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|---|------------|------------------------|--|---------|---------------------|-------------------|
| Hydrotreated heavy naphthenic petroleum distillates | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | | NOAEL Not available | |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|--------------------------------------|------------|---|--|---------|---------------------|-----------------------|
| Aluminum Oxide Mineral (non-fibrous) | Inhalation | pneumoconiosis | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | occupational exposure |
| Aluminum Oxide Mineral (non-fibrous) | Inhalation | pulmonary fibrosis | Not classified | Human | NOAEL Not available | occupational exposure |
| Talc | Inhalation | pneumoconiosis | Causes damage to organs through prolonged or repeated exposure | Human | NOAEL Not available | occupational exposure |
| Talc | Inhalation | pulmonary fibrosis respiratory system | Not classified | Rat | NOAEL 18 mg/m3 | 113 weeks |
| Titanium dioxide | Inhalation | respiratory system | Some positive data exist, but the data are not sufficient for classification | Rat | LOAEL 0.01 mg/l | 2 years |
| Titanium dioxide | Inhalation | pulmonary fibrosis | Not classified | Human | NOAEL Not available | occupational exposure |

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Exposure Levels

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

Interactive Effects

Not determined.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

Not acutely toxic to aquatic life by GHS criteria.

Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available.

| Material | CAS Number | Organism | Type | Exposure | Test endpoint | Test result |
|--------------------------------------|------------|-------------|--------------|----------|---------------|-------------|
| Aluminum Oxide Mineral (non-fibrous) | 1344-28-1 | | Experimental | 96 hours | LC50 | >100 mg/l |
| Aluminum Oxide Mineral (non-fibrous) | 1344-28-1 | Green algae | Experimental | 72 hours | EC50 | >100 mg/l |
| Aluminum Oxide Mineral (non-fibrous) | 1344-28-1 | Water flea | Experimental | 48 hours | LC50 | >100 mg/l |
| Aluminum Oxide Mineral (non-fibrous) | 1344-28-1 | Green algae | Experimental | 72 hours | NOEC | >100 mg/l |
| Potassium tetrafluoroborate | 14075-53-7 | Bacteria | Experimental | 18 hours | EC50 | 550 mg/l |
| Potassium tetrafluoroborate | 14075-53-7 | Golden Orfe | Experimental | 96 hours | LC50 | 760 mg/l |
| Potassium tetrafluoroborate | 14075-53-7 | Green algae | Experimental | 72 hours | EC50 | >100 mg/l |
| Potassium tetrafluoroborate | 14075-53-7 | Water flea | Experimental | 48 hours | EC50 | >100 mg/l |
| Potassium tetrafluoroborate | 14075-53-7 | Water flea | Estimated | 21 days | NOEC | 188 mg/l |
| Potassium | 14075-53-7 | Green algae | Experimental | 72 hours | NOEC | 100 mg/l |

| | | | | | | |
|---|------------|------------------|---|----------|--------------------------------|--------------|
| tetrafluoroborate | | | | | | |
| Talc | 14807-96-6 | | Data not available or insufficient for classification | | | N/A |
| Lithium Stearate | 4485-12-5 | Green algae | Estimated | 72 hours | No tox obs at lmt of water sol | >100 mg/l |
| Lithium Stearate | 4485-12-5 | Rainbow trout | Estimated | 96 hours | No tox obs at lmt of water sol | >100 mg/l |
| Lithium Stearate | 4485-12-5 | Water flea | Estimated | 48 hours | No tox obs at lmt of water sol | >100 mg/l |
| Lithium Stearate | 4485-12-5 | Green algae | Estimated | 72 hours | No tox obs at lmt of water sol | >100 mg/l |
| Titanium dioxide | 13463-67-7 | Activated sludge | Experimental | 3 hours | NOEC | >=1,000 mg/l |
| Titanium dioxide | 13463-67-7 | Diatom | Experimental | 72 hours | EC50 | >10,000 mg/l |
| Titanium dioxide | 13463-67-7 | Fathead minnow | Experimental | 96 hours | LC50 | >100 mg/l |
| Titanium dioxide | 13463-67-7 | Water flea | Experimental | 48 hours | EC50 | >100 mg/l |
| Titanium dioxide | 13463-67-7 | Diatom | Experimental | 72 hours | NOEC | 5,600 mg/l |
| Hydrotreated heavy naphthenic petroleum distillates | 64742-52-5 | Green algae | Estimated | 96 hours | EC50 | >100 mg/l |
| Hydrotreated heavy naphthenic petroleum distillates | 64742-52-5 | Water flea | Estimated | 48 hours | EC50 | >100 mg/l |

12.2. Persistence and degradability

| Material | CAS Number | Test type | Duration | Study Type | Test result | Protocol |
|--------------------------------------|------------|---------------------------------|----------|------------|---------------|---------------------------|
| Aluminum Oxide Mineral (non-fibrous) | 1344-28-1 | Data not available-insufficient | N/A | N/A | N/A | N/A |
| Potassium tetrafluoroborate | 14075-53-7 | Data not available-insufficient | N/A | N/A | N/A | N/A |
| Talc | 14807-96-6 | Data not available-insufficient | N/A | N/A | N/A | N/A |
| Lithium Stearate | 4485-12-5 | Estimated Biodegradation | 28 days | BOD | 78 %BOD/ThBOD | OECD 301C - MITI test (I) |
| Titanium dioxide | 13463-67-7 | Data not available-insufficient | N/A | N/A | N/A | N/A |
| Hydrotreated heavy | 64742-52-5 | Data not available- | N/A | N/A | N/A | N/A |

| | | | | | | |
|----------------------------------|--|--------------|--|--|--|--|
| naphthenic petroleum distillates | | insufficient | | | | |
|----------------------------------|--|--------------|--|--|--|--|

12.3 : Bioaccumulative potential

| Material | CAS Number | Test type | Duration | Study Type | Test result | Protocol |
|---|------------|---|----------|------------------------|-------------|---------------------|
| Aluminum Oxide Mineral (non-fibrous) | 1344-28-1 | Data not available or insufficient for classification | N/A | N/A | N/A | N/A |
| Potassium tetrafluoroborate | 14075-53-7 | Data not available or insufficient for classification | N/A | N/A | N/A | N/A |
| Talc | 14807-96-6 | Data not available or insufficient for classification | N/A | N/A | N/A | N/A |
| Lithium Stearate | 4485-12-5 | Estimated BCF - Other | 4 days | Bioaccumulation factor | 8 | Non-standard method |
| Titanium dioxide | 13463-67-7 | Experimental BCF - Carp | 42 days | Bioaccumulation factor | 9.6 | Non-standard method |
| Hydrotreated heavy naphthenic petroleum distillates | 64742-52-5 | Data not available or insufficient for classification | N/A | N/A | N/A | N/A |

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. If no other disposal options are available, waste product may be placed in a landfill properly designed for industrial waste.

SECTION 14: Transport Information

Australian Dangerous Goods Code (ADG) - Road/Rail Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

Hazchem Code: Not applicable

IERG: Not applicable.

International Air Transport Association (IATA) - Air Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

Marine Pollutant: Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Australian Inventory Status:

Not applicable, as this product/s aligns with the AICIS definition of an article.

Poison Schedule: This product is intended for Industrial or Professional Use only and therefore is not packaged and labelled in accordance with the requirements of the Standard for the Uniform Scheduling of Medicines and Poisons.

SECTION 16: Other information

Revision information:

Complete document review.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au