

## Safety Data Sheet

Copyright, 2021, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 26-9510-4
 Version number:
 2.00

 Issue Date:
 15/08/2021
 Supersedes date:
 08/05/2017

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

### **SECTION 1: Identification**

### 1.1. Product identifier

3M<sup>™</sup> Blue Cream Hardener

#### **Product Identification Numbers**

70-0080-0380-1

#### 1.2. Recommended use and restrictions on use

### Recommended use

Automotive., Hardener for Body Fillers

For Industrial or Professional use only.

### 1.3. Supplier's details

Address: 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113

**Telephone:** 136 136

E Mail: productinfo.au@mmm.com

Website: www.3m.com.au

### 1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

### **SECTION 2: Hazard identification**

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

### 2.1. Classification of the substance or mixture

Organic Peroxide: Type E.

Serious Eye Damage/Irritation: Category 2.

Skin Sensitizer: Category 1B.

### 2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for

Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

### Signal word

Warning

### **Symbols**

Flame |Exclamation mark |





#### Hazard statements

H242 Heating may cause a fire.

H319 Causes serious eye irritation. H317 May cause an allergic skin reaction.

### **Precautionary statements**

General:

P102 Keep out of reach of children.

**Prevention:** 

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

Keep only in original packaging. P234

P235 Keep cool.

Ground and bond container and receiving equipment. P240

P264 Wash thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280B Wear protective gloves and eye/face protection.

**Response:** 

P302 + P352IF ON SKIN: Wash with plenty of soap and water.

P305 + P351 + P338IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

If skin irritation or rash occurs: Get medical advice/attention. P333 + P313P337 + P313IF eye irritation persists: Get medical advice/attention. P362 + P364Take off contaminated clothing and wash it before reuse.

Storage:

P403 Store in a well-ventilated place.

P410 Protect from sunlight.

P411 Store at temperatures not exceeding 5C/40F.

P420 Store separately.

Disposal:

P501 Dispose of contents/container in accordance with applicable

local/regional/national/international regulations.

### 2.3. Other assigned/identified product hazards

None known.

#### 2.4. Other hazards which do not result in classification

May be harmful in contact with skin.

Very toxic to aquatic life with long lasting effects.

## **SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
Benzoyl Peroxide	94-36-0	30 - 60
Benzoic Acid, C9-11-Branched Alkyl Esters	131298-44-7	10 - 30
Water	7732-18-5	10 - 30
Zinc Stearate	557-05-1	5 - 10
Calcium Sulfate	7778-18-9	3 - 7
Oxirane, Polymer with Methyloxirane,	9038-95-3	1 - 5
Monobutyl Ether		
Ferric Ammonium Ferrocyanide	25869-00-5	< 1
Ferric Ferrocyanide	14038-43-8	<1

## **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

#### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

#### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode. Part of the oxygen for combustion is supplied by the peroxide itself.

### **Hazardous Decomposition or By-Products**

**Substance** 

Condition

Carbon monoxide.

During combustion.

Page: 3 of 14

Carbon dioxide.
Toxic vapour, gas, particulate.

During combustion. During combustion.

### 5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

Hazchem Code: 1W

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. WARNING! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

#### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage including any incompatibilities

Protect from sunlight. Store at temperatures not exceeding 32C. Keep cool. Keep only in original container. Store away from other materials. Keep/store away from clothing and other combustible materials.

# **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Calcium Sulfate	7778-18-9	ACGIH	TWA(inhalable fraction):10	
			mg/m3	
Calcium Sulfate	7778-18-9	Australia OELs	TWA(Inspirable dust)(8	
			hours):10 mg/m3	
Benzoyl Peroxide	94-36-0	ACGIH	TWA:5 mg/m3	A4: Not class. as human
				carcin
Benzoyl Peroxide	94-36-0	Australia OELs	TWA(8 hours):5 mg/m3	

### 3M<sup>™</sup> Blue Cream Hardener

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

Australia OELs: Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG: Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

### 8.2. Exposure controls

### 8.2.1. Engineering controls

No engineering controls required.

#### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

if this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Select and use gloves according to AS/NZ 2161.

### Respiratory protection

Wear respiratory protection if ventilation is inadequate to prevent overexposure.

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer. Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

# **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state	Solid.
----------------	--------

Specific Physical Form:	Paste
Colour	Blue
Odour	Slight Ester
Odour threshold	No data available.
pH	No data available.
Melting point/Freezing point	No data available.
Boiling point/Initial boiling point/Boiling range	Not applicable.
Flash point	111 °C [Test Method: Estimated]
Evaporation rate	No data available.
Flammability (solid, gas)	Organic Peroxide: Type E.
Flammable Limits(LEL)	Not applicable.
Flammable Limits(UEL)	Not applicable.
Vapour pressure	No data available.
Vapor Density and/or Relative Vapor Density	No data available.
Density	1.2 g/ml
Relative density	1.2 [Ref Std:WATER=1] [Details:@ 25 C]
Water solubility	Negligible
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Autoignition temperature	410 °C [Test Method: Estimated]
Decomposition temperature	No data available.
Viscosity/Kinematic Viscosity	70,000 mPa-s - 150,000 mPa-s
Volatile organic compounds (VOC)	0 % weight [Test Method:calculated per CARB title 2]
Volatile organic compounds (VOC)	0 g/l [Test Method:calculated SCAQMD rule 443.1]
Percent volatile	
VOC less H2O & exempt solvents	0 g/l [Test Method:calculated SCAQMD rule 443.1]
Molecular weight	No data available.

### Nanoparticles

This material does not contain nanoparticles.

# **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

### 10.2 Chemical stability

Stable.

### 10.3. Conditions to avoid

None known.

### 10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.5 Incompatible materials

Accelerators

### 10.6 Hazardous decomposition products

**Substance** Condition

None known.

## **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1 Information on Toxicological effects

### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

#### Skin contact

May be harmful in contact with skin.

Contact with the skin during product use is not expected to result in significant irritation. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eve contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

#### Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

### **Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE2,000 - 5,000 mg/kg
Overall product	Inhalation- Dust/Mist(4 hr)		No data available; calculated ATE >12.5 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Benzoyl Peroxide	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Benzoyl Peroxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 24.3 mg/l
Benzoyl Peroxide	Ingestion	Rat	LD50 > 5,000  mg/kg
Benzoic Acid, C9-11-Branched Alkyl Esters	Dermal	Rabbit	LD50 > 2,000 mg/kg
Benzoic Acid, C9-11-Branched Alkyl Esters	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5 mg/l
Benzoic Acid, C9-11-Branched Alkyl Esters	Ingestion	Rat	LD50 > 5,000 mg/kg
Zinc Stearate	Dermal	Rabbit	LD50 > 2,000  mg/kg
Zinc Stearate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 50 mg/l
Zinc Stearate	Ingestion	Rat	LD50 > 5,000  mg/kg

Page: 7 of 14

Calcium Sulfate	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
Calcium Sulfate	Ingestion	Rat	LD50 > 5,000 mg/kg
Oxirane, Polymer with	Dermal	Rabbit	LD50 > 16,960 mg/kg
Methyloxirane, Monobutyl Ether			
Oxirane, Polymer with	Inhalation-Dust/Mist	Rat	LC50 > 5  mg/l
Methyloxirane, Monobutyl Ether	(4 hours)		
Oxirane, Polymer with	Ingestion	Rat	LD50 4,240 mg/kg
Methyloxirane, Monobutyl Ether			
Ferric Ammonium Ferrocyanide	Dermal		LD50 estimated to be > 5,000 mg/kg
Ferric Ferrocyanide	Dermal		LD50 estimated to be > 5,000 mg/kg
Ferric Ammonium Ferrocyanide	Ingestion	Rat	LD50 > 5,110 mg/kg
Ferric Ferrocyanide	Ingestion	Rat	LD50 > 8,000 mg/kg

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

Name	Species	Value
Benzoyl Peroxide	Rabbit	Minimal irritation
Zinc Stearate	Rabbit	No significant irritation
Oxirane, Polymer with Methyloxirane, Monobutyl	Rabbit	Minimal irritation
Ether		

Serious Eye Damage/Irritation

Name	Species	Value
Benzoyl Peroxide	Rabbit	Severe irritant
Zinc Stearate	Rabbit	No significant irritation
Oxirane, Polymer with Methyloxirane, Monobutyl	Rabbit	No significant irritation
Ether		

### **Skin Sensitisation**

Name	Species	Value		
Benzoyl Peroxide	Guinea pig	Sensitising		

## **Respiratory Sensitisation**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity** 

Germ Cen Mutagementy				
Name	Route	Value		
Benzoyl Peroxide	In Vitro	Not mutagenic		
Benzoyl Peroxide	In vivo	Not mutagenic		

Carcinogenicity

Name	Route	Species	Value
Benzoyl Peroxide	Ingestion	Multiple animal	Not carcinogenic
		species	
Benzoyl Peroxide	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Ingestion	Rat	Not carcinogenic

## **Reproductive Toxicity**

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	<b>Exposure Duration</b>
Benzoyl Peroxide	Ingestion	Not classified for	Rat	NOAEL	premating & during
		female reproduction		1,000	gestation
				mg/kg/day	
Benzoyl Peroxide	Ingestion	Not classified for	Rat	NOAEL 500	premating & during
		male reproduction		mg/kg/day	gestation
Benzoyl Peroxide	Ingestion	Not classified for	Rat	NOAEL 500	premating & during
		development		mg/kg/day	gestation
Oxirane, Polymer	Inhalation	Not classified for	Rat	NOAEL 1	2 weeks
with Methyloxirane,		male reproduction		mg/l	
Monobutyl Ether					

## Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Oxirane, Polymer with Methyloxiran e, Monobutyl Ether	Ingestion	nervous system	Not classified	Rat	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure** 

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Oxirane, Polymer with Methyloxiran e, Monobutyl Ether	Inhalation	endocrine system   hematopoietic system   liver   nervous system	Not classified	Rat	NOAEL 1 mg/l	2 weeks
Oxirane, Polymer with Methyloxiran e, Monobutyl Ether	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 0.005 mg/l	2 weeks
Oxirane, Polymer with Methyloxiran e, Monobutyl Ether	Inhalation	respiratory system	Not classified	Rat	LOAEL 0.001 mg/l	2 weeks
Oxirane, Polymer with Methyloxiran e, Monobutyl Ether	Inhalation	heart	Not classified	Rat	NOAEL 0.5 mg/l	2 weeks
Oxirane, Polymer with Methyloxiran e, Monobutyl Ether	Ingestion	liver   kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 145 mg/kg/day	90 days
Oxirane, Polymer with Methyloxiran e, Monobutyl Ether	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 500 mg/kg/day	2 years
Oxirane, Polymer with Methyloxiran	Ingestion	heart   endocrine system   respiratory	Not classified	Rat	NOAEL 3,770 mg/kg/day	90 days

\_\_\_\_\_

31	TM	Rlue	Cream	Hard	lener

e, Monobutyl	system		
Ether			

### **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

### **Exposure Levels**

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

### **Interactive Effects**

Not determined.

## **SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

### 12.1. Toxicity

### Acute aquatic hazard:

GHS Acute 1: Very toxic to aquatic life.

### Chronic aquatic hazard:

GHS Chronic 1: Very toxic to aquatic life with long lasting effects.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Benzoyl	94-36-0	Green Algae	Experimental	72 hours	EC50	0.071 mg/l
Peroxide						
Benzoyl	94-36-0	Rainbow trout	Experimental	96 hours	LC50	0.06 mg/l
Peroxide						
Benzoyl	94-36-0	Water flea	Experimental	48 hours	EC50	0.11 mg/l
Peroxide						
Benzoyl	94-36-0	Green Algae	Experimental	72 hours	NOEC	0.02 mg/l
Peroxide						
Benzoyl	94-36-0	Water flea	Experimental	21 days	EC10	0.001 mg/l
Peroxide						
Benzoyl	94-36-0	Activated	Experimental	30 minutes	EC50	35 mg/l
Peroxide		sludge				
Benzoyl	94-36-0	Redworm	Experimental	14 days	LC50	>1,000 mg/kg (Dry
Peroxide						Weight)
Benzoyl	94-36-0	Soil microbes	Experimental	28 days	EC50	2,300 mg/kg (Dry
Peroxide						Weight)
Benzoic Acid,	131298-44-7	Activated	Experimental	3 hours	EC50	>100 mg/l
C9-11-		sludge				
Branched Alkyl						
Esters						
Benzoic Acid,	131298-44-7		Data not			N/A
C9-11-			available or			
Branched Alkyl			insufficient for			
Esters			classification			

Zinc Stearate	557-05-1	Water flea	Experimental	48 hours	EC50	>100 mg/l
Zinc Stearate	557-05-1	Zebra Fish	Experimental	96 hours	No tox obs at	>100 mg/l
			1		lmt of water sol	
Calcium	7778-18-9	Activated	Estimated	3 hours	NOEC	1,000 mg/l
Sulfate		sludge				
Calcium	7778-18-9	Algae or other	Experimental	96 hours	EC50	3,200 mg/l
Sulfate		aquatic plants				
Calcium	7778-18-9	Bluegill	Experimental	96 hours	LC50	>2,980 mg/l
Sulfate						
Calcium	7778-18-9	Water flea	Experimental	48 hours	LC50	>1,970 mg/l
Sulfate			1			
Calcium	7778-18-9	Water flea	Estimated	21 days	NOEC	1,270 mg/l
Sulfate						
Oxirane,	9038-95-3	Inland	Analogous	96 hours	LC50	650 mg/l
Polymer with		Silverside	Compound			
Methyloxirane,			1			
Monobutyl						
Ether						
Oxirane,	9038-95-3	Activated	Experimental	16 hours	IC50	32,000 mg/l
Polymer with		sludge				
Methyloxirane,						
Monobutyl						
Ether						
Ferric	25869-00-5	Water flea	Endpoint not	24 hours	EC50	>100 mg/l
Ammonium			reached			
Ferrocyanide						
Ferric	25869-00-5	Activated	Experimental	3 hours	NOEC	100 mg/l
Ammonium		sludge				
Ferrocyanide						
Ferric	25869-00-5	Common Carp	Experimental	96 hours	LC50	>100 mg/l
Ammonium						
Ferrocyanide						
Ferric	25869-00-5	Green Algae	Experimental	72 hours	EC50	9.7 mg/l
Ammonium						
Ferrocyanide						
Ferric	25869-00-5	Green Algae	Experimental	72 hours	NOEC	8 mg/l
Ammonium						
Ferrocyanide						
Ferric	25869-00-5	Water flea	Experimental	21 days	EC10	0.168 mg/l
Ammonium						
Ferrocyanide						
Ferric	14038-43-8	Golden Orfe	Estimated	96 hours	LC50	>100 mg/l
Ferrocyanide						

## 12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Benzoyl	94-36-0	Experimental		Hydrolytic	5.2 hours (t	OECD 111 Hydrolysis
Peroxide		Hydrolysis		half-life	1/2)	func of pH
Benzoyl	94-36-0	Experimental	28 days	BOD	71 %	OECD 301D - Closed
Peroxide		Biodegradation			BOD/ThBOD	bottle test
Benzoic Acid,	131298-44-7	Data not			N/A	
C9-11-		available-				
Branched Alkyl		insufficient				

Esters						
Zinc Stearate	557-05-1	Experimental Biodegradation	28 days	BOD	14.6 % BOD/ThBOD	OECD 301D - Closed bottle test
Calcium Sulfate	7778-18-9	Data not available-insufficient			N/A	
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	9038-95-3	Data not available- insufficient			N/A	
Ferric Ammonium Ferrocyanide	25869-00-5	Data not available-insufficient			N/A	
Ferric Ferrocyanide	14038-43-8	Data not available-insufficient			N/A	

## 12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Benzoyl Peroxide	94-36-0	Experimental Bioconcentrati on		Log Kow	3.2	OECD 117 log Kow HPLC method
Benzoic Acid, C9-11- Branched Alkyl Esters	131298-44-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Zinc Stearate	557-05-1	Experimental Bioconcentrati on		Log Kow	4.64	OECD 117 log Kow HPLC method
Calcium Sulfate	7778-18-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	9038-95-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Ferric Ammonium Ferrocyanide	25869-00-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Ferric Ferrocyanide	14038-43-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

**12.4. Mobility in soil** Please contact manufacturer for more details

### 12.5 Other adverse effects

No information available.

## **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes.

## **SECTION 14: Transport Information**

### Australian Dangerous Goods Code (ADG) - Road/Rail Transport

UN No.: UN3108

Proper shipping name: ORGANIC PEROXIDE TYPE E, SOLID, (DIBENZOYL PEROXIDE (As a Paste), <= 52%)

Class/Division: 5.2
Sub Risk: Not applicable.
Packing Group: Not applicable.

**Special Instructions:** Limited quantity may apply

Hazchem Code: 1W

**IERG: 32** 

### International Air Transport Association (IATA) - Air Transport

UN No.: UN3108

Proper shipping name: ORGANIC PEROXIDE TYPE E, SOLID, (DIBENZOYL PEROXIDE (As a Paste), <= 52%)

Class/Division: 5.2 Sub Risk: Not applicable. Packing Group: Not applicable.

**Special Instructions:** Forbidden packaging does not meet requirements for this mode of transport

### International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: UN3108

Proper shipping name: ORGANIC PEROXIDE TYPE E, SOLID, (DIBENZOYL PEROXIDE (As a Paste), <= 52%)

Class/Division: 5.2
Sub Risk: Not applicable.
Packing Group: Not applicable.
Marine Pollutant: Not applicable.

**Special Instructions:** Limited quantity may apply

## **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### **Australian Inventory Status:**

The chemical components contained within this product are listed on the Australian Inventory of Chemical Substances and are in compliance with the requirements of the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

**Poison Schedule:** This product is intended for Industrial or Professional Use only and therefore is not packaged and labelled in accordance with the requirements of the Standard for the Uniform Scheduling of Medicines and Poisons.

### **SECTION 16: Other information**

### **Revision information:**

Complete document review.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our

### 3M<sup>TM</sup> Blue Cream Hardener

knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au

Page: 14 of 14