



Safety Data Sheet

Copyright, 2015, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group: 24-3532-9 **Version number:** 1.00
Issue Date: 13/08/2015 **Supersedes date:** Initial issue.

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

SECTION 1: Identification

1.1. Product identifier

3M™ Scotch-Brite™ Products, EXL Unitized Wheels, Blocks, Slabs A-XCRS, CRS

Product Identification Numbers

41-1510-4544-4	41-1510-4645-9	41-1510-4646-7	41-1510-4647-5	41-1510-4648-3
41-1510-4649-1	41-1510-4650-9	41-1510-4651-7	41-1510-4652-5	41-1510-4741-6
41-1510-4742-4	41-1510-4743-2	41-1510-4759-8	41-1510-4851-3	41-1510-4852-1
41-1510-4853-9	41-1510-4866-1	41-1510-4869-5	41-1510-4874-5	41-1510-5509-6
41-1510-5720-9	41-1510-5749-8	42-0016-9788-9	61-0000-1454-0	61-0000-1520-8
61-0000-1560-4	61-0000-1944-0	61-0000-2426-7	61-0000-2483-8	61-0000-2486-1
61-0000-2490-3	61-0000-2492-9	61-0000-3745-9	61-0000-3937-2	61-0000-3969-5
61-0000-3970-3	61-0000-3981-0	61-0000-3982-8	61-0000-3991-9	61-0000-3994-3
61-0000-3996-8	61-0000-4031-3	61-0000-4033-9	61-0000-4046-1	61-0000-4047-9
61-0000-4049-5	61-0000-4052-9	61-0000-4059-4	61-0000-4061-0	61-0000-4062-8
61-0000-4066-9	61-5000-5783-3	61-5000-5786-6	61-5000-5788-2	61-5000-5794-0
61-5000-5797-3	61-5000-5798-1	61-5000-5805-4	61-5000-5807-0	61-5000-5808-8
61-5000-5812-0	61-5000-5818-7	61-5000-7036-4	61-5000-7769-0	61-5000-7938-1
61-5000-7941-5	61-5000-8185-8	61-5000-9931-4	61-5000-9932-2	61-5000-9935-5
61-5000-9936-3	61-5001-0818-0	61-5001-1191-1	61-5001-2256-1	61-5001-2258-7
61-5001-2826-1	61-5001-2835-2	61-5001-2837-8	61-5001-2839-4	61-5001-2869-1
61-5001-3511-8	61-5001-5236-0	61-5001-5582-7	61-5001-5584-3	61-5001-5763-3
61-5001-5765-8	61-5001-5767-4	61-5001-5769-0	61-5001-5770-8	61-5001-5771-6
61-5001-5773-2	61-5001-5774-0	61-5001-5776-5	61-5001-5777-3	61-5001-7029-7
61-5001-7478-6	61-5001-7517-1	61-5001-8723-4	61-5003-0163-7	RN-0009-5894-2
RN-0009-7602-7	RN-0009-8283-5			

1.2. Recommended use and restrictions on use

Recommended use

Abrasive Product

For Industrial or Professional use only.

1.3. Supplier's details

Address: 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113

Telephone: 136 136

E Mail: productinfo.au@mmm.com

Website: www.3m.com.au

1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

SECTION 2: Hazard identification

This product is NOT classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

Not applicable.

2.2. Label elements

Signal word

Not applicable.

Symbols

Not applicable.

Pictograms

Not applicable.

2.3. Other assigned/identified product hazards

None known.

2.4. Other hazards which do not result in classification

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
Aluminum Oxide Mineral (non-fibrous)	1344-28-1	50 - 75
Titanium dioxide	13463-67-7	0.4 - 2.4
Cloth Backing	25038-59-9	0.5 - 1
Nylon Fiber	Mixture	2 - 10
Cured resin	Mixture	20 - 35
Attachment Button	Mixture	0 - 5

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

No need for first aid is anticipated.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide.

Carbon dioxide.

Condition

During combustion.

During combustion.

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Observe precautions from other sections.

6.2. Environmental precautions

Not applicable.

6.3. Methods and material for containment and cleaning up

Not applicable.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial or professional use only. Avoid breathing of dust created by sanding, grinding or machining. Damaged product can break apart during use and cause serious injury to face or eyes. Check product for damage such as cracks or nicks prior to use. Replace if damaged. Always wear eye and face protection when working at sanding or grinding operations or when near such operations. Combustible dust may form by action of this product on another material (substrate). Dust generated from the substrate during use of this product may be explosive if in sufficient concentration with an ignition source. Dust deposits should not be allowed to accumulate on surfaces because of the potential for secondary explosions.

7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Aluminum Oxide Mineral (non-fibrous)	1344-28-1	Australia OELs	TWA(Inspirable dust)(8 hours):10 mg/m ³	
Aluminum, insoluble compounds	1344-28-1	ACGIH	TWA(respirable fraction):1 mg/m ³	A4: Not class. as human carcin
Aluminum Oxide Mineral (non-fibrous)	1344-28-1	CMRG	TWA:1 fiber/cc	
Titanium dioxide	13463-67-7	CMRG	TWA(as respirable dust):5 mg/m ³	
Titanium dioxide	13463-67-7	ACGIH	TWA:10 mg/m ³	A4: Not class. as human carcin
Titanium dioxide	13463-67-7	Australia OELs	TWA(Inspirable dust)(8 hours):10 mg/m ³	
Cloth Backing	25038-59-9	CMRG	TWA(as respirable dust):5 mg/m ³ ;TWA(as total dust):10 mg/m ³	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CELL: Ceiling

Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

8.2. Exposure controls

8.2.1. Engineering controls

Provide appropriate local exhaust ventilation for sanding, grinding or machining. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Warning: Excessive operating speed or generation of extreme heat may result in harmful emissions. Use local exhaust ventilation. Provide local exhaust at process emission sources to control exposure near the source and to prevent the escape of dust into the work area. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

8.2.2. Personal protective equipment (PPE)

Eye/face protection

To minimise the risk of injury to face and eyes, always wear eye and face protection when working at sanding or grinding operations or when near such operations. Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

Skin/hand protection

Wear appropriate gloves to minimise risk of injury to skin from contact with dust or physical abrasion from grinding or

sanding.

Respiratory protection

Assess exposure concentrations of all materials involved in the work process. Consider material being abraded when determining the appropriate respiratory protection. Select and use appropriate respirators to prevent inhalation overexposure. An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for particulates.

For questions about suitability for a specific application, consult with your respirator manufacturer.

Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid.
Appearance/Odour	Solid abrasive product
Odour threshold	<i>Not applicable.</i>
pH	<i>Not applicable.</i>
Melting point/Freezing point	<i>Not applicable.</i>
Boiling point/Initial boiling point/Boiling range	<i>Not applicable.</i>
Flash point	<i>Not applicable.</i>
Evaporation rate	<i>Not applicable.</i>
Flammability (solid, gas)	Not classified
Flammable Limits(LEL)	<i>Not applicable.</i>
Flammable Limits(UEL)	<i>Not applicable.</i>
Vapour pressure	<i>Not applicable.</i>
Vapour density	<i>Not applicable.</i>
Density	<i>Not applicable.</i>
Relative density	<i>Not applicable.</i>
Water solubility	<i>Not applicable.</i>
Solubility- non-water	<i>Not applicable.</i>
Autoignition temperature	<i>Not applicable.</i>
Decomposition temperature	<i>Not applicable.</i>
Viscosity	<i>Not applicable.</i>

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is considered to be non reactive under normal use conditions

10.2 Chemical stability

Stable.

10.3. Conditions to avoid

None known.

10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

Substance

Condition

None known.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Dust created by grinding, sanding, or machining may cause irritation of the respiratory system. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Skin contact

Mechanical skin irritation: Signs/symptoms may include abrasion, redness, pain, and itching.

Eye contact

Mechanical eye irritation: Signs/symptoms may include pain, redness, tearing and corneal abrasion. Dust created by grinding, sanding, or machining may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion

No known health effects.

Additional information:

- This document covers only the 3M product. For complete assessment, when determining the degree of hazard, the material being abraded must also be considered. Dust created by grinding, sanding, or machining may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Aluminum Oxide Mineral (non-fibrous)	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminum Oxide Mineral (non-fibrous)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminum Oxide Mineral (non-fibrous)	Ingestion	Rat	LD50 > 5,000 mg/kg

3M™ Scotch-Brite™ Products, EXL Unitized Wheels, Blocks, Slabs A-XCRS, CRS

Titanium dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
Cloth Backing	Dermal		LD50 estimated to be > 5,000 mg/kg
Cloth Backing	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Aluminum Oxide Mineral (non-fibrous)	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Aluminum Oxide Mineral (non-fibrous)	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation

Skin Sensitisation

Name	Species	Value
Titanium dioxide	Human and animal	Not sensitizing

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Aluminum Oxide Mineral (non-fibrous)	In Vitro	Not mutagenic
Titanium dioxide	In Vitro	Not mutagenic
Titanium dioxide	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Aluminum Oxide Mineral (non-fibrous)	Inhalation	Rat	Not carcinogenic
Titanium dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium dioxide	Inhalation	Rat	Carcinogenic.

Reproductive Toxicity**Reproductive and/or Developmental Effects**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Aluminum	Inhalation	pneumoconiosis	Some positive	Human	NOAEL Not	occupational

3M™ Scotch-Brite™ Products, EXL Unitized Wheels, Blocks, Slabs A-XCRS, CRS

Oxide Mineral (non-fibrous)		pulmonary fibrosis	data exist, but the data are not sufficient for classification		available	exposure
Titanium dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium dioxide	Inhalation	pulmonary fibrosis	All data are negative	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Exposure Levels

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

Interactive Effects

Not determined.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

Not acutely toxic to aquatic life by GHS criteria.

Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Cloth Backing	25038-59-9		Data not available or insufficient for classification			
Aluminum Oxide Mineral (non-fibrous)	1344-28-1	Water flea	Experimental	48 hours	EC50	>100 mg/l
Aluminum Oxide Mineral (non-fibrous)	1344-28-1	Fish	Experimental	96 hours	LC50	>100 mg/l
Aluminum Oxide Mineral (non-fibrous)	1344-28-1	Green algae	Experimental	72 hours	NOEC	>100 mg/l
Aluminum Oxide Mineral (non-fibrous)	1344-28-1	Green algae	Experimental	72 hours	EC50	>100 mg/l

3M™ Scotch-Brite™ Products, EXL Unitized Wheels, Blocks, Slabs A-XCRS, CRS

Titanium dioxide	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
Titanium dioxide	13463-67-7	Crustacea other	Experimental	96 hours	EC50	>300 mg/l
Titanium dioxide	13463-67-7	Water flea	Experimental	30 days	NOEC	3 mg/l
Titanium dioxide	13463-67-7	Fish	Experimental	30 days	NOEC	>=1,000 mg/l
Titanium dioxide	13463-67-7	Sheepshead Minnow	Experimental	96 hours	LC50	>240 mg/l

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Titanium dioxide	13463-67-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Aluminum Oxide Mineral (non-fibrous)	1344-28-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Cloth Backing	25038-59-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Aluminum Oxide Mineral (non-fibrous)	1344-28-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Cloth Backing	25038-59-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Experimental BCF - Other	42 days	Bioaccumulation factor	9.6	Other methods

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility.

SECTION 14: Transport Information

Australian Dangerous Goods Code (ADG) - Road/Rail Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

Hazchem Code: Not applicable

IERG: Not applicable.

International Air Transport Association (IATA) - Air Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

Marine Pollutant: Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Australian Inventory Status:

This product is defined as an article under the Industrial Chemicals (Notification and Assessment) Act 1989, as amended, and is exempt from inventory requirements under the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

Poison Schedule: This product has not been assessed for poisons scheduling as the product is intended for industrial and professional use only.

SECTION 16: Other information

Revision information:

Conversion to GHS format SDS.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au

