



Safety Data Sheet

Copyright, 2016, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	29-9413-5	Version number:	3.00
Issue Date:	16/10/2016	Supersedes date:	14/10/2014

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

IDENTIFICATION:

1.1. Product identifier

3M™ ESPE™ RelyX™ Ultimate Trial Kit

Product Identification Numbers

70-2011-3871-9 70-2011-3873-5

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Adhesive Resin cement

For use only by dental professionals.

Restrictions on use

For use by dental professionals only.

1.3. Supplier's details

Address: 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113
Telephone: 136 136
E Mail: productinfo.au@mmm.com
Website: www.3m.com.au

1.4. Emergency telephone number

Company Emergency Hotline: EMERGENCY: 1800 097 146 (Australia only)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the SDSs for components of this product are:

29-9001-8, 29-9002-6, 29-8286-6, 29-8287-4

One or more components of this KIT is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011.

TRANSPORT INFORMATION

The Components of this KIT have various Dangerous Goods Transportation Classifications. Please refer to the attached component Safety Data Sheets for individual Transportation Classifications.

Marine Pollutant:Not applicable.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au



Safety Data Sheet

Copyright, 2017, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	29-8287-4	Version number:	3.00
Issue Date:	02/08/2017	Supersedes date:	13/10/2014

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

SECTION 1: Identification

1.1. Product identifier

3M™ ESPE™ Scotchbond™ Universal

Product Identification Numbers

70-2011-3903-0

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, ADHESIVE

Restrictions on use

For use by dental professionals only.

1.3. Supplier's details

Address: 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113
Telephone: 136 136
E Mail: productinfo.au@mmm.com
Website: www.3m.com.au

1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

Flammable liquid: Category 3.

Serious Eye Damage/Irritation: Category 1.

Skin Sensitizer: Category 1.

2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

Signal word

DANGER!

Symbols

Flame | Corrosion | Exclamation mark |

Pictograms



Hazard statements

H226	Flammable liquid and vapour.
H318	Causes serious eye damage.
H317	May cause an allergic skin reaction.

Precautionary statements

Prevention:

P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P240	Ground/bond container and receiving equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P233	Keep container tightly closed.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280B	Wear protective gloves and eye/face protection.
P280E	Wear protective gloves.
P272	Contaminated work clothing should not be allowed out of the workplace.

Response:

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P310	Immediately call a POISON CENTRE or doctor/physician.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.
P321	Specific treatment (see Notes to Physician on this label).
P370 + P378G	In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage:

P403 + P235	Store in a well-ventilated place. Keep cool.
-------------	----------------------------------------------

Disposal:

P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.
------	----------------------------------------------------------------------------------------------------------------

2.3. Other assigned/identified product hazards

None known.

2.4. Other hazards which do not result in classification

Harmful to aquatic life.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
2-Hydroxyethyl methacrylate	868-77-9	15 - 25
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	1565-94-2	15 - 25
Decamethylene dimethacrylate	6701-13-9	5 - 15
Ethanol	64-17-5	10 - 15
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	122334-95-6	5 - 15
Water	7732-18-5	10 - 15
1,10-Decanediol methacrylated phosphates	1207736-18-2	1 - 10
Copolymer of acrylic and itaconic acid	25948-33-8	1 - 5
Camphorquinone	10373-78-1	< 2
Ethyl 4-dimethylaminobenzoate	10287-53-3	< 2

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If swallowed

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Formaldehyde	During combustion.
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.
Irritant vapours or gases.	During combustion.
Oxides of nitrogen.	During combustion.

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

Hazchem Code: •3Y

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. **WARNING !** A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam designed for use on solvents, such as alcohols and acetone, that can dissolve in water. An Alcohol Resistant foam is recommended. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. Acrylates may penetrate commonly-used gloves. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Do not get in eyes.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidising agents.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Ethanol	64-17-5	ACGIH	STEL:1000 ppm	A3: Confirmed animal carcinogen.
Ethanol	64-17-5	Australia OELs	TWA(8 hours):1880 mg/m3(1000 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety glasses with side shields.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Viscous Liquid
Appearance/Odour	Characteristic odour, yellow liquid.
Odour threshold	<i>No data available.</i>
pH	<i>Not applicable.</i>
Melting point/Freezing point	<i>No data available.</i>
Boiling point/Initial boiling point/Boiling range	>= 78 °C
Flash point	30.5 °C [<i>Test Method:Closed Cup</i>]

Evaporation rate	<i>No data available.</i>
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Vapour pressure	<i>No data available.</i>
Vapour density	<i>No data available.</i>
Density	1 - 1.2 g/cm ³
Relative density	1 - 1.2 [Ref Std: WATER=1]
Water solubility	Appreciable
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
Viscosity	<i>Not applicable.</i>
Molecular weight	<i>No data available.</i>
Volatile organic compounds (VOC)	<i>No data available.</i>

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is considered to be non reactive under normal use conditions

10.2 Chemical stability

Stable.

10.3. Conditions to avoid

Heat.

10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

Substance

None known.

Condition

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin contact

Contact with the skin during product use is not expected to result in significant irritation. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Additional information:

This product contains ethanol. Alcoholic beverages and ethanol in alcoholic beverages have been classified by the International Agency for Research on Cancer as carcinogenic to humans. There are also data associating human consumption of alcoholic beverages with developmental toxicity and liver toxicity. Exposure to ethanol during the foreseeable use of this product is not expected to cause cancer, developmental toxicity, or liver toxicity.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
2-Hydroxyethyl methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
2-Hydroxyethyl methacrylate	Ingestion	Rat	LD50 5,564 mg/kg
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	Dermal	Professional judgement	LD50 estimated to be 2,000 - 5,000 mg/kg
Ethanol	Dermal	Rabbit	LD50 > 15,800 mg/kg
Ethanol	Inhalation-Vapour (4 hours)	Rat	LC50 124.7 mg/l
Ethanol	Ingestion	Rat	LD50 17,800 mg/kg
Decamethylene dimethacrylate	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Decamethylene dimethacrylate	Dermal	Professional judgement	LD50 estimated to be 2,000 - 5,000 mg/kg
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Ingestion	Rat	LD50 > 5,110 mg/kg
1,10-Decanediol methacrylated phosphates	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg

3M™ ESPE™ Scotchbond™ Universal

1,10-Decanediol methacrylated phosphates	Ingestion	Rat	LD50 > 1,380 mg/kg
Copolymer of acrylic and itaconic acid	Ingestion	Rat	LD50 > 5,000 mg/kg
Copolymer of acrylic and itaconic acid	Dermal	similar health hazards	LD50 estimated to be > 5,000 mg/kg
Camphorquinone	Dermal	Professional judgement	LD50 estimated to be 2,000 - 5,000 mg/kg
Camphorquinone	Ingestion	Rat	LD50 > 2,000 mg/kg
Ethyl 4-dimethylaminobenzoate	Dermal	Rat	LD50 > 2,000 mg/kg
Ethyl 4-dimethylaminobenzoate	Ingestion	Rat	LD50 > 2,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Overall product	Rabbit	No significant irritation
2-Hydroxyethyl methacrylate	Rabbit	Minimal irritation
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	Not available	Minimal irritation
Ethanol	Rabbit	No significant irritation
Decamethylene dimethacrylate	Professional judgement	Irritant
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Rabbit	No significant irritation
Ethyl 4-dimethylaminobenzoate	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Overall product	In vitro data	Corrosive
2-Hydroxyethyl methacrylate	Rabbit	Moderate irritant
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	Not available	Moderate irritant
Ethanol	Rabbit	Severe irritant
Decamethylene dimethacrylate	Professional judgement	Severe irritant
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Rabbit	No significant irritation
Ethyl 4-dimethylaminobenzoate	Rabbit	Mild irritant

Skin Sensitisation

Name	Species	Value
2-Hydroxyethyl methacrylate	Human and animal	Sensitising
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	Guinea pig	Sensitising
Ethanol	Human	Not classified
Decamethylene dimethacrylate		Sensitising
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Human and animal	Not classified

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

3M™ ESPE™ Scotchbond™ Universal

Name	Route	Value
2-Hydroxyethyl methacrylate	In vivo	Not mutagenic
2-Hydroxyethyl methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Ethanol	In Vitro	Some positive data exist, but the data are not sufficient for classification
Ethanol	In vivo	Some positive data exist, but the data are not sufficient for classification
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Ethanol	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
2-Hydroxyethyl methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	prematuring & during gestation
2-Hydroxyethyl methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	49 days
2-Hydroxyethyl methacrylate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	prematuring & during gestation
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	Ingestion	Not classified for female reproduction	Mouse	NOAEL 0.8 mg/kg/day	prematuring & during gestation
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	Ingestion	Not classified for male reproduction	Mouse	NOAEL 0.8 mg/kg/day	prematuring & during gestation
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	Ingestion	Not classified for development	Mouse	NOAEL 0.8 mg/kg/day	prematuring & during gestation
Ethanol	Inhalation	Not classified for development	Rat	NOAEL 38 mg/l	during gestation
Ethanol	Ingestion	Not classified for development	Rat	NOAEL 5,200 mg/kg/day	prematuring & during gestation

2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Ethanol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	LOAEL 2.6 mg/l	30 minutes
Ethanol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	LOAEL 9.4 mg/l	not available
Ethanol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL not available	
Ethanol	Ingestion	kidney and/or bladder	Not classified	Dog	NOAEL 3,000 mg/kg	
Decamethylene dimethacrylate	Inhalation	respiratory irritation	May cause respiratory irritation		NOAEL Not available	
Copolymer of acrylic and itaconic acid	Ingestion	nervous system	Not classified	Rat	NOAEL 5,000 mg/kg	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
(1-methylethylidene)bis[4,1-phenyleneoxy (2-hydroxy-3,1-propanediyl)] bismethacrylate	Ingestion	endocrine system liver nervous system kidney and/or bladder	Not classified	Mouse	NOAEL 0.8 mg/kg/day	prematuring & during gestation
Ethanol	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Rabbit	LOAEL 124 mg/l	365 days
Ethanol	Inhalation	hematopoietic	Not classified	Rat	NOAEL 25 mg/l	14 days

		system immune system				
Ethanol	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 8,000 mg/kg/day	4 months
Ethanol	Ingestion	kidney and/or bladder	Not classified	Dog	NOAEL 3,000 mg/kg/day	7 days
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Copolymer of acrylic and itaconic acid	Ingestion	endocrine system hematopoietic system liver	Not classified	Rat	NOAEL 200 mg/kg/day	28 days
Copolymer of acrylic and itaconic acid	Ingestion	heart bone, teeth, nails, and/or hair immune system muscles nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	Rat	NOAEL 2,000 mg/kg/day	28 days

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Exposure Levels

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

Interactive Effects

Not determined.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

GHS Acute 3: Harmful to aquatic life.

Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

3M™ ESPE™ Scotchbond™ Universal

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
2-Hydroxyethyl methacrylate	868-77-9	Green algae	Experimental	72 hours	EC50	710 mg/l
2-Hydroxyethyl methacrylate	868-77-9	Water flea	Experimental	48 hours	EC50	380 mg/l
2-Hydroxyethyl methacrylate	868-77-9	Fathead minnow	Experimental	96 hours	LC50	227 mg/l
2-Hydroxyethyl methacrylate	868-77-9	Water flea	Experimental	21 days	NOEC	24.1 mg/l
2-Hydroxyethyl methacrylate	868-77-9	Green Algae	Experimental	72 hours	NOEC	160 mg/l
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	1565-94-2		Data not available or insufficient for classification			
Decamethylene dimethacrylate	6701-13-9		Data not available or insufficient for classification			
Ethanol	64-17-5	Rainbow trout	Experimental	96 hours	LC50	42 mg/l
Ethanol	64-17-5	Water flea	Experimental	48 hours	LC50	5,012 mg/l
Ethanol	64-17-5	Water flea	Experimental	10 days	NOEC	9.6 mg/l
Ethanol	64-17-5	Algae other	Experimental	96 hours	NOEC	1,580 mg/l
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl) propyl ester, hydrolysis products with silica	122334-95-6		Data not available or insufficient for classification			
1,10-Decanediol methacrylated phosphates	1207736-18-2		Data not available or insufficient for classification			
Copolymer of acrylic and itaconic acid	25948-33-8		Data not available or insufficient for classification			
Camphorquinone	10373-78-1		Data not available or insufficient for classification			
Ethyl 4-dimethylamino	10287-53-3		Data not available or			% weight

3M™ ESPE™ Scotchbond™ Universal

benzoate			insufficient for classification			
----------	--	--	---------------------------------	--	--	--

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
2-Hydroxyethyl methacrylate	868-77-9	Experimental Biodegradation	14 days	BOD	95 % weight	OECD 301C - MITI test (I)
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	1565-94-2	Estimated Biodegradation	28 days	BOD	32 % weight	OECD 301C - MITI test (I)
Decamethylene dimethacrylate	6701-13-9	Estimated Biodegradation	28 days	BOD	89 % weight	OECD 301C - MITI test (I)
Ethanol	64-17-5	Experimental Biodegradation	14 days	BOD	89 % BOD/ThBOD	OECD 301C - MITI test (I)
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl) propyl ester, hydrolysis products with silica	122334-95-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
1,10-Decanediol methacrylated phosphates	1207736-18-2	Estimated Biodegradation	28 days	BOD	91 % weight	OECD 301C - MITI test (I)
Copolymer of acrylic and itaconic acid	25948-33-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
2-Hydroxyethyl methacrylate	868-77-9	Experimental Bioconcentration		Log Kow	0.47	Other methods
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	1565-94-2	Estimated Bioconcentration		Bioaccumulation factor	5.8	Estimated: Bioconcentration factor
Decamethylene dimethacrylate	6701-13-9	Estimated Bioconcentration		Bioaccumulation factor	6.6	Estimated: Bioconcentration factor
Ethanol	64-17-5	Experimental Bioconcentration		Log Kow	-0.35	Other methods

3M™ ESPE™ Scotchbond™ Universal

		on				
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl) propyl ester, hydrolysis products with silica	122334-95-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
1,10-Decanediol methacrylated phosphates	1207736-18-2	Estimated Bioconcentration		Bioaccumulation factor	4.5	Other methods
Copolymer of acrylic and itaconic acid	25948-33-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste.

SECTION 14: Transport Information**Australian Dangerous Goods Code (ADG) - Road/Rail Transport**

UN No.: UN1133

Proper shipping name: ADHESIVES

Class/Division: 3

Sub Risk: Not applicable.

Packing Group: III

Hazchem Code: •3Y

IERG: 14

International Air Transport Association (IATA) - Air Transport

UN No.: UN1133

Proper shipping name: ADHESIVES

Class/Division: 3

Sub Risk: Not applicable.

Packing Group: III

Special Instructions: Excepted Quantity may apply

International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: UN1133

Proper shipping name: ADHESIVES

Class/Division: 3

Sub Risk: Not applicable.

Packing Group: III

Marine Pollutant: Not applicable.

Special Instructions: Forbidden due to internal policy

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Australian Inventory Status:

This product is regulated by the Therapeutics Goods Administration and is exempt from compliance with the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

Poison Schedule: This product is intended for Industrial or Professional Use only and therefore is not packaged and labelled in accordance with the requirements of the Standard for the Uniform Scheduling of Medicines and Poisons.

SECTION 16: Other information

Revision information:

Complete document review.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au



Safety Data Sheet

Copyright, 2019, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	29-9001-8	Version number:	4.00
Issue Date:	04/08/2019	Supersedes date:	03/08/2016

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

SECTION 1: Identification

1.1. Product identifier

3M™ ESPE™ RelyX™ Ultimate Base Paste

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Adhesive resin cement.

Restrictions on use

For use by dental professionals only.

1.3. Supplier's details

Address:	3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113
Telephone:	136 136
E Mail:	productinfo.au@mmm.com
Website:	www.3m.com.au

1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

Skin Sensitizer: Category 1.

2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

Signal word

3M™ ESPE™ RelyX™ Ultimate Base Paste

WARNING!

Symbols

Exclamation mark |

Pictograms



Hazard statements

H317 May cause an allergic skin reaction.

Precautionary statements

Prevention:

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280E Wear protective gloves.
P272 Contaminated work clothing should not be allowed out of the workplace.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
P363 Wash contaminated clothing before reuse.

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other assigned/identified product hazards

None known.

2.4. Other hazards which do not result in classification

May be harmful if swallowed.
Causes mild skin irritation. Toxic to aquatic life with long lasting effects.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
2-Propenoic acid, 2-methyl-, 1,1'-[1-(hydroxymethyl)-1,2-ethanediyl] ester, reaction products with 2-hydroxy-1,3-propanediyl dimethacrylate and phosphorus oxide	1224866-76-5	20 - 30
2,2'-ethylenedioxydiethyl dimethacrylate	109-16-0	10 - 20
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	68909-20-6	5 - 10

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.
Irritant vapours or gases.	During combustion.

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

Hazchem Code: 2Z

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. Acrylates may penetrate commonly-used gloves. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this Safety Data Sheet.

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid.
Specific Physical Form:	Paste
Colour	Tooth
Odour	Slight Acrylic
Odour threshold	<i>No data available.</i>

pH	<i>Not applicable.</i>
Melting point/Freezing point	<i>No data available.</i>
Boiling point/Initial boiling point/Boiling range	<i>No data available.</i>
Flash point	No flash point
Evaporation rate	<i>No data available.</i>
Flammability (solid, gas)	Not classified
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Vapour pressure	<i>No data available.</i>
Vapour density	<i>No data available.</i>
Density	2 - 2.2 g/cm ³
Relative density	2 - 2.2 [Ref Std: WATER=1]
Water solubility	Negligible
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
Viscosity	<i>No data available.</i>
Molecular weight	<i>No data available.</i>
Volatile organic compounds (VOC)	<i>No data available.</i>

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3. Conditions to avoid

Heat.

10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

Substance

Condition

None known.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

This product may have a characteristic odour; however, no adverse health effects are anticipated.

Skin contact

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE2,000 - 5,000 mg/kg
2-Propenoic acid, 2-methyl-, 1,1'-[1-(hydroxymethyl)-1,2-ethanediyl] ester, reaction products with 2-hydroxy-1,3-propanediyl dimethacrylate and phosphorus oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
2-Propenoic acid, 2-methyl-, 1,1'-[1-(hydroxymethyl)-1,2-ethanediyl] ester, reaction products with 2-hydroxy-1,3-propanediyl dimethacrylate and phosphorus oxide	Ingestion	Rat	LD50 > 2,000 mg/kg
2,2'-ethylenedioxydiethyl dimethacrylate	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
2,2'-ethylenedioxydiethyl dimethacrylate	Ingestion	Rat	LD50 10,837 mg/kg
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Ingestion	Rat	LD50 > 5,110 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
2-Propenoic acid, 2-methyl-, 1,1'-[1-(hydroxymethyl)-1,2-ethanediyl] ester, reaction products with 2-hydroxy-1,3-propanediyl dimethacrylate and phosphorus oxide	Rabbit	Minimal irritation
2,2'-ethylenedioxydiethyl dimethacrylate	Guinea pig	Mild irritant

3M™ ESPE™ RelyX™ Ultimate Base Paste

2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Rabbit	No significant irritation
----------------------------------------------------------------------------------------------	--------	---------------------------

Serious Eye Damage/Irritation

Name	Species	Value
Overall product		No significant irritation
2-Propenoic acid, 2-methyl-, 1,1'-[1-(hydroxymethyl)-1,2-ethanediyl] ester, reaction products with 2-hydroxy-1,3-propanediyl dimethacrylate and phosphorus oxide	Rabbit	Corrosive
2,2'-ethylenedioxydiethyl dimethacrylate	Professional judgement	Moderate irritant
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Rabbit	No significant irritation

Skin Sensitisation

Name	Species	Value
2-Propenoic acid, 2-methyl-, 1,1'-[1-(hydroxymethyl)-1,2-ethanediyl] ester, reaction products with 2-hydroxy-1,3-propanediyl dimethacrylate and phosphorus oxide	Guinea pig	Not classified
2,2'-ethylenedioxydiethyl dimethacrylate	Human and animal	Sensitising
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Human and animal	Not classified

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
2-Propenoic acid, 2-methyl-, 1,1'-[1-(hydroxymethyl)-1,2-ethanediyl] ester, reaction products with 2-hydroxy-1,3-propanediyl dimethacrylate and phosphorus oxide	In Vitro	Not mutagenic
2,2'-ethylenedioxydiethyl dimethacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
2,2'-ethylenedioxydiethyl dimethacrylate	Dermal	Mouse	Not carcinogenic
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
2,2'-	Ingestion	Not classified for	Mouse	NOAEL 1	1 generation

3M™ ESPE™ RelyX™ Ultimate Base Paste

ethylenedioxydiethyl dimethacrylate		female reproduction		mg/kg/day	
2,2'-ethylenedioxydiethyl dimethacrylate	Ingestion	Not classified for male reproduction	Mouse	NOAEL 1 mg/kg/day	1 generation
2,2'-ethylenedioxydiethyl dimethacrylate	Ingestion	Not classified for development	Mouse	NOAEL 1 mg/kg/day	1 generation
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
2,2'-ethylenedioxy diethyl dimethacrylate	Dermal	kidney and/or bladder blood	Not classified	Mouse	NOAEL 833 mg/kg/day	78 weeks
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Exposure Levels

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

Interactive Effects

Not determined.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient

classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

GHS Acute 2: Toxic to aquatic life.

Chronic aquatic hazard:

GHS Chronic 2: Toxic to aquatic life with long lasting effects.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
2-Propenoic acid, 2-methyl-, 1,1'-[1-(hydroxymethyl)-1,2-ethanediyl] ester, reaction products with 2-hydroxy-1,3-propanediyl dimethacrylate and phosphorus oxide	1224866-76-5	Green algae	Endpoint not reached	72 hours	EC50	>100 mg/l
2-Propenoic acid, 2-methyl-, 1,1'-[1-(hydroxymethyl)-1,2-ethanediyl] ester, reaction products with 2-hydroxy-1,3-propanediyl dimethacrylate and phosphorus oxide	1224866-76-5	Water flea	Experimental	48 hours	EC50	>100 mg/l
2-Propenoic acid, 2-methyl-, 1,1'-[1-(hydroxymethyl)-1,2-ethanediyl] ester, reaction products with 2-hydroxy-1,3-propanediyl dimethacrylate and phosphorus oxide	1224866-76-5	Green algae	Experimental	72 hours	NOEC	56 mg/l
2,2'-	109-16-0	Green Algae	Experimental	72 hours	EC50	>100 mg/l

3M™ ESPE™ RelyX™ Ultimate Base Paste

ethylenedioxydiethyl dimethacrylate						
2,2'-ethylenedioxydiethyl dimethacrylate	109-16-0	Zebra Fish	Experimental	96 hours	LC50	16.4 mg/l
2,2'-ethylenedioxydiethyl dimethacrylate	109-16-0	Green algae	Experimental	72 hours	NOEC	18.6 mg/l
2,2'-ethylenedioxydiethyl dimethacrylate	109-16-0	Water flea	Experimental	21 days	NOEC	32 mg/l
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl) propyl ester, hydrolysis products with silica	68909-20-6	Algae	Estimated	72 hours	EC50	>100 mg/l

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
2-Propenoic acid, 2-methyl-, 1,1'-[1-(hydroxymethyl)-1,2-ethanediyl] ester, reaction products with 2-hydroxy-1,3-propanediyl dimethacrylate and phosphorus oxide	1224866-76-5	Experimental Biodegradation	28 days	BOD	82 % BOD/ThBOD	OECD 301F - Manometric respirometry
2,2'-ethylenedioxydiethyl dimethacrylate	109-16-0	Experimental Biodegradation	28 days	CO2 evolution	85 % weight	OECD 301B - Modified sturm or CO2
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl) propyl ester, hydrolysis products with silica	68909-20-6	Data not available-insufficient			N/A	

12.3 : Bioaccumulative potential

3M™ ESPE™ RelyX™ Ultimate Base Paste

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
2-Propenoic acid, 2-methyl-, 1,1'-[1-(hydroxymethyl)-1,2-ethanediyl] ester, reaction products with 2-hydroxy-1,3-propanediyl dimethacrylate and phosphorus oxide	1224866-76-5	Experimental Bioconcentration		Log Kow	-0.2	Other methods
2,2'-ethylenedioxydiethyl dimethacrylate	109-16-0	Experimental Bioconcentration		Log Kow	2.3	Other methods
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl) propyl ester, hydrolysis products with silica	68909-20-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility.

SECTION 14: Transport Information**Australian Dangerous Goods Code (ADG) - Road/Rail Transport**

UN No.: UN3077

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. , (TERT-BUTYL PEROXY-3, 5, 5-TRIMETHYLHEXANOATE, (ACETIC ACID, COPPER (2+) SALT, MONOHYDRATE))

Class/Division: 9

Sub Risk: Not applicable.

Packing Group: III

Special Instructions: Not restricted, environmentally hazardous substance exception.

Hazchem Code: 2Z

IERG: 47

International Air Transport Association (IATA) - Air Transport

3M™ ESPE™ RelyX™ Ultimate Base Paste

UN No.: UN3077

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. , (TERT-BUTYL PEROXY-3, 5, 5-TRIMETHYLHEXANOATE, (ACETIC ACID, COPPER (2+) SALT, MONOHYDRATE))

Class/Division: 9

Sub Risk: Not applicable.

Packing Group: III

Special Instructions: Not restricted, as per Special Provision A197, environmentally hazardous substance exception.

International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: UN3077

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. , (TERT-BUTYL PEROXY-3, 5, 5-TRIMETHYLHEXANOATE, (ACETIC ACID, COPPER (2+) SALT, MONOHYDRATE))

Class/Division: 9

Sub Risk: Not applicable.

Packing Group: III

Marine Pollutant: Not applicable.

Special Instructions: Not restricted, as per IMDG code 2.10.2.7, marine pollutant exception.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Australian Inventory Status:

This product is regulated by the Therapeutics Goods Administration and is exempt from compliance with the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

SECTION 16: Other information

Revision information:

Complete document review.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au



Safety Data Sheet

Copyright, 2019, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	29-9002-6	Version number:	3.00
Issue Date:	04/08/2019	Supersedes date:	14/10/2014

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

SECTION 1: Identification

1.1. Product identifier

3M™ ESPE™ RelyX™ Ultimate Catalyst Paste

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Adhesive resin cement.

Restrictions on use

For use by dental professionals only.

1.3. Supplier's details

Address: 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113
Telephone: 136 136
E Mail: productinfo.au@mmm.com
Website: www.3m.com.au

1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 2.

Skin Sensitizer: Category 1.

2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

Signal word

WARNING!

Symbols

Exclamation mark |

Pictograms



Hazard statements

H319 Causes serious eye irritation.
 H317 May cause an allergic skin reaction.

Precautionary statements

Prevention:

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P280A Wear eye/face protection.
 P280E Wear protective gloves.
 P264 Wash thoroughly after handling.
 P272 Contaminated work clothing should not be allowed out of the workplace.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337 + P313 If eye irritation persists: Get medical advice/attention.
 P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
 P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
 P363 Wash contaminated clothing before reuse.
 P321 Specific treatment (see Notes to Physician on this label).

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other assigned/identified product hazards

None known.

2.4. Other hazards which do not result in classification

May be harmful if swallowed.
 Causes mild skin irritation. Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
(1-Methylethylidene)bis(4, 1-phenyleneoxy-3, 1-propanediyl) bismethacrylate	27689-12-9	20 - 30
1,12-dodecane dimethacrylate	72829-09-5	< 5
2-Propenoic acid, 2-methyl-, 3-	68909-20-6	< 5

3M™ ESPE™ RelyX™ Ultimate Catalyst Paste

(trimetoxysilyl)propyl ester, hydrolysis products with silica		
Sodium P-Toluenesulfinate	824-79-3	< 5
Calcium dihydroxide	1305-62-0	< 2

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide.
Carbon dioxide.
Irritant vapours or gases.

Condition

During combustion.
During combustion.
During combustion.

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

Hazchem Code: 2Z

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation

3M™ ESPE™ RelyX™ Ultimate Catalyst Paste

to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. Acrylates may penetrate commonly-used gloves. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Calcium dihydroxide	1305-62-0	ACGIH	TWA:5 mg/m ³	
Calcium dihydroxide	1305-62-0	Australia OELs	TWA(8 hours):5 mg/m ³	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state	Solid.
Specific Physical Form:	Paste
Colour	Tooth
Odour	Slight Acrylic
Odour threshold	<i>No data available.</i>
pH	<i>Not applicable.</i>
Melting point/Freezing point	<i>No data available.</i>
Boiling point/Initial boiling point/Boiling range	<i>No data available.</i>
Flash point	No flash point
Evaporation rate	<i>No data available.</i>
Flammability (solid, gas)	Not classified
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Vapour pressure	<i>No data available.</i>
Vapour density	<i>No data available.</i>
Density	2 - 2.2 g/cm ³
Relative density	2 - 2.2 [Ref Std: WATER=1]
Water solubility	Nil
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
Viscosity	<i>No data available.</i>
Molecular weight	<i>No data available.</i>
Volatile organic compounds (VOC)	<i>No data available.</i>

SECTION 10: Stability and reactivity**10.1 Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3. Conditions to avoid

Heat.

10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products**Substance****Condition**

None known.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects**Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

This product may have a characteristic odour; however, no adverse health effects are anticipated.

Skin contact

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Additional Health Effects:**Carcinogenicity:**

Exposures needed to cause the following health effect(s) are not expected during normal, intended use:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE 2,000 - 5,000 mg/kg
(1-Methylethylidene)bis(4, 1-phenyleneoxy- 3, 1-propanediyl)	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg

3M™ ESPE™ RelyX™ Ultimate Catalyst Paste

bismethacrylate			
(1-Methylethylidene)bis(4, 1-phenyleneoxy- 3, 1-propanediyl) bismethacrylate	Ingestion	Rat	LD50 > 17,600 mg/kg
1,12-dodecane dimethacrylate	Dermal	Professional judgement	LD50 estimated to be 2,000 - 5,000 mg/kg
1,12-dodecane dimethacrylate	Ingestion	similar compounds	LD50 2000-5000 mg/kg
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Calcium dihydroxide	Dermal	Rabbit	LD50 > 2,500 mg/kg
Calcium dihydroxide	Ingestion	Rat	LD50 7,340 mg/kg
Sodium P-Toluenesulfinate	Dermal	Professional judgement	LD50 estimated to be 2,000 - 5,000 mg/kg
Sodium P-Toluenesulfinate	Ingestion	Rat	LD50 3,200 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
(1-Methylethylidene)bis(4, 1-phenyleneoxy- 3, 1-propanediyl) bismethacrylate	Rabbit	No significant irritation
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Rabbit	No significant irritation
Calcium dihydroxide	Human	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
(1-Methylethylidene)bis(4, 1-phenyleneoxy- 3, 1-propanediyl) bismethacrylate	Rabbit	Mild irritant
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Rabbit	No significant irritation
Calcium dihydroxide	Rabbit	Corrosive

Skin Sensitisation

Name	Species	Value
(1-Methylethylidene)bis(4, 1-phenyleneoxy- 3, 1-propanediyl) bismethacrylate	Guinea pig	Not classified
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Human and animal	Not classified

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
------	-------	-------

3M™ ESPE™ RelyX™ Ultimate Catalyst Paste

(1-Methylethylidene)bis(4, 1-phenyleneoxy- 3, 1-propanediyl) bismethacrylate	In Vitro	Not mutagenic
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Calcium dihydroxide	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	LOAEL 2.5 mg/m3	20 minutes

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Exposure Levels

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

Interactive Effects

Not determined.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity**Acute aquatic hazard:**

GHS Acute 1: Very toxic to aquatic life.

Chronic aquatic hazard:

GHS Chronic 2: Toxic to aquatic life with long lasting effects.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
(1-Methylethylidene)bis(4, 1-phenyleneoxy-3, 1-propanediyl) bismethacrylate	27689-12-9	Green algae	Experimental	72 hours	EC50	>100 mg/l
(1-Methylethylidene)bis(4, 1-phenyleneoxy-3, 1-propanediyl) bismethacrylate	27689-12-9	Water flea	Experimental	48 hours	EC50	>100 mg/l
(1-Methylethylidene)bis(4, 1-phenyleneoxy-3, 1-propanediyl) bismethacrylate	27689-12-9	Green algae	Experimental	72 hours	NOEC	>100 mg/l
1,12-dodecane dimethacrylate	72829-09-5	Green Algae	Experimental	72 hours	EC50	17 ug/l
1,12-dodecane dimethacrylate	72829-09-5	Water flea	Experimental	48 hours	EC50	>100 mg/l
1,12-dodecane dimethacrylate	72829-09-5	Green Algae	Experimental	72 hours	Effect Concentration 10%	6.4 ug/l
2-Propenoic acid, 2-methyl-,	68909-20-6	Algae	Estimated	72 hours	EC50	>100 mg/l

3M™ ESPE™ RelyX™ Ultimate Catalyst Paste

3-(trimetoxysilyl) propyl ester, hydrolysis products with silica						
Sodium P-Toluenesulfinate	824-79-3	Fathead minnow	Estimated	96 hours	LC50	>400 mg/l
Sodium P-Toluenesulfinate	824-79-3	Green Algae	Estimated	96 hours	EC50	230 mg/l
Sodium P-Toluenesulfinate	824-79-3	Water flea	Estimated	48 hours	EC50	>400 mg/l
Sodium P-Toluenesulfinate	824-79-3	Green Algae	Estimated	96 hours	NOEC	31 mg/l
Calcium dihydroxide	1305-62-0	Fathead minnow	Estimated	96 hours	LC50	4,630 mg/l
Calcium dihydroxide	1305-62-0	Green Algae	Estimated	72 hours	EC50	>4,000 mg/l
Calcium dihydroxide	1305-62-0	Water flea	Estimated	48 hours	EC50	2,400 mg/l

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
(1-Methylethylidene)bis(4, 1-phenyleneoxy-3, 1-propanediyl) bismethacrylate	27689-12-9	Experimental Biodegradation	28 days	CO2 evolution	7-12 % weight	OECD 301B - Modified sturm or CO2
1,12-dodecane dimethacrylate	72829-09-5	Experimental Biodegradation	28 days	CO2 evolution	97.3 %CO2 evolution/THC O2 evolution	OECD 301B - Modified sturm or CO2
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl) propyl ester, hydrolysis products with silica	68909-20-6	Data not available-insufficient			N/A	
Sodium P-Toluenesulfinate	824-79-3	Experimental Biodegradation	28 days	BOD	91 % BOD/ThBOD	OECD 301C - MITI test (I)
Calcium dihydroxide	1305-62-0	Data not available-insufficient			N/A	

12.3 : Bioaccumulative potential

3M™ ESPE™ RelyX™ Ultimate Catalyst Paste

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
(1-Methylethylidene)bis(4, 1-phenyleneoxy-3, 1-propanediyl) bismethacrylate	27689-12-9	Estimated Bioconcentration		Log Kow	7.61	Estimated: Octanol-water partition coefficient
1,12-dodecane dimethacrylate	72829-09-5	Estimated Bioconcentration		Bioaccumulation factor	6.6	Estimated: Bioconcentration factor
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl) propyl ester, hydrolysis products with silica	68909-20-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Sodium P-Toluenesulfinate	824-79-3	Estimated Bioconcentration		Bioaccumulation factor	3.9	Estimated: Bioconcentration factor
Calcium dihydroxide	1305-62-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes.

SECTION 14: Transport Information**Australian Dangerous Goods Code (ADG) - Road/Rail Transport**

UN No.: UN3077

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. , (2-PROPENOIC ACID, 2-METHYL-,1,12-DODECANEDIYL ESTER)

Class/Division: 9

Sub Risk: Not applicable.

Packing Group: III

Special Instructions: Not restricted, environmentally hazardous substance exception.

Hazchem Code: 2Z

IERG: 47

International Air Transport Association (IATA) - Air Transport

UN No.: UN3077

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. , (2-PROPENOIC ACID, 2-METHYL-,1,12-DODECANEDIYL ESTER)

Class/Division: 9

Sub Risk: Not applicable.

Packing Group: III

Special Instructions: Not restricted, as per Special Provision A197, environmentally hazardous substance exception.

International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: UN3077

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. , (2-PROPENOIC ACID, 2-METHYL-,1,12-DODECANEDIYL ESTER)

Class/Division: 9

Sub Risk: Not applicable.

Packing Group: III

Marine Pollutant: Not applicable.

Special Instructions: Not restricted, as per IMDG code 2.10.2.7, marine pollutant exception.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Australian Inventory Status:

This product is regulated by the Therapeutics Goods Administration and is exempt from compliance with the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

SECTION 16: Other information

Revision information:

Complete document review.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au



Safety Data Sheet

Copyright, 2019, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	29-8286-6	Version number:	3.00
Issue Date:	14/05/2019	Supersedes date:	04/07/2014

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

SECTION 1: Identification

1.1. Product identifier

3M™ ESPE™ Scotchbond™ Universal Etchant

Product Identification Numbers

70-2011-3906-3

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Etching gel

Restrictions on use

For use by dental professionals only.

1.3. Supplier's details

Address: 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113
Telephone: 136 136
E Mail: productinfo.au@mmm.com
Website: www.3m.com.au

1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

Corrosive to metal: Category 1.
Serious Eye Damage/Irritation: Category 1.
Skin Corrosion/Irritation: Category 1.

2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

Signal word

DANGER!

Symbols

Corrosion |

Pictograms



Hazard statements

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

Precautionary statements

Prevention:

P234 Keep only in original container.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P280D Wear protective gloves, protective clothing, and eye/face protection.
P264 Wash thoroughly after handling.

Response:

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTRE or doctor/physician.
P363 Wash contaminated clothing before reuse.
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P321 Specific treatment (see Notes to Physician on this label).
P390 Absorb spillage to prevent material damage.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other assigned/identified product hazards

- May cause chemical gastrointestinal burns.

2.4. Other hazards which do not result in classification

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
Water	7732-18-5	50 - 65
Orthophosphoric acid	7664-38-2	30 - 40
Synthetic amorphous silica, fumed, crystalline free	112945-52-5	5 - 10
Poly(oxy-1,2-ethanediyl),alpha-hydro-omega-hydroxy-ethane-1,2-diol, ethoxylated	25322-68-3	1 - 5
Aluminium oxide	1344-28-1	< 2

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If swallowed

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products**Substance**

Carbon monoxide.
Carbon dioxide.

Condition

During combustion.
During combustion.

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

Hazchem Code: 2R

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Collect as much of the spilled material as possible. Place in a metal container approved for use in transportation by appropriate authorities. The container must be lined with polyethylene plastic or contain a plastic drum liner made of polyethylene. Clean up residue with water. Cover, but do not seal for 48 hours. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid prolonged or repeated skin contact. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Do not get in eyes.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Keep only in original container. Store in a corrosive resistant container with a resistant inner liner. Store away from strong bases.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Silicon dioxide	112945-52-5	Australia OELs	TWA(respirable fraction)(8 hours):2 mg/m ³	
Aluminium oxide	1344-28-1	Australia OELs	TWA(Inspirable dust)(8 hours):10 mg/m ³	
Aluminum, insoluble compounds	1344-28-1	ACGIH	TWA(respirable fraction):1 mg/m ³	A4: Not class. as human carcin
Poly(oxy-1,2-ethanediyl),alpha-hydro-omega-hydroxy-ethane-1,2-diol, ethoxylated	25322-68-3	AIHA	TWA(as aerosol):10 mg/m ³	
Orthophosphoric acid	7664-38-2	ACGIH	TWA: 1 mg/m ³ ; STEL: 3 mg/m ³	
Orthophosphoric acid	7664-38-2	Australia OELs	TWA(8 hours):1 mg/m ³ ;STEL(15 minutes):3 mg/m ³	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG : Chemical Manufacturer's Recommended Guidelines

3M™ ESPE™ Scotchbond™ Universal Etchant

TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling
Sen: Sensitiser
Sk: Absorption through the skin may be a significant source of exposure.

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety glasses with side shields.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Gel
Appearance/Odour	Slight characteristic odour, Blue
Odour threshold	<i>No data available.</i>
pH	< 1
Melting point/Freezing point	<i>Not applicable.</i>
Boiling point/Initial boiling point/Boiling range	<i>No data available.</i>
Flash point	> 100 °C [Test Method:Closed Cup]
Evaporation rate	<i>No data available.</i>
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Vapour pressure	<i>No data available.</i>
Vapour density	<i>No data available.</i>
Density	1.1 g/ml - 1.2 g/ml
Relative density	1.1 - 1.2 [Ref Std:WATER=1]
Water solubility	Complete
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
Viscosity	<i>No data available.</i>
Molecular weight	<i>No data available.</i>
Volatile organic compounds (VOC)	<i>No data available.</i>
Percent volatile	<i>No data available.</i>

VOC less H2O & exempt solvents

No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3. Conditions to avoid

Heat.

10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.5 Incompatible materials

Strong bases.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

This product may have a characteristic odour; however, no adverse health effects are anticipated.

Skin contact

Corrosive (skin burns): Signs/symptoms may include localised redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction.

Eye contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion

Gastrointestinal corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain, nausea, vomiting, and diarrhea; blood in the faeces and/or vomitus may also be seen.

Toxicological Data

3M™ ESPE™ Scotchbond™ Universal Etchant

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Orthophosphoric acid	Dermal	Rabbit	LD50 2,740 mg/kg
Orthophosphoric acid	Ingestion	Rat	LD50 1,530 mg/kg
Synthetic amorphous silica, fumed, crystalline free	Dermal	Rabbit	LD50 > 5,000 mg/kg
Synthetic amorphous silica, fumed, crystalline free	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Synthetic amorphous silica, fumed, crystalline free	Ingestion	Rat	LD50 > 5,110 mg/kg
Poly(oxy-1,2-ethanediyl),alpha-hydro-omega-hydroxy-ethane-1,2-diol, ethoxylated	Dermal	Rabbit	LD50 > 20,000 mg/kg
Poly(oxy-1,2-ethanediyl),alpha-hydro-omega-hydroxy-ethane-1,2-diol, ethoxylated	Ingestion	Rat	LD50 32,770 mg/kg
Aluminium oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminium oxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminium oxide	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Orthophosphoric acid	Rabbit	Corrosive
Synthetic amorphous silica, fumed, crystalline free	Rabbit	No significant irritation
Poly(oxy-1,2-ethanediyl),alpha-hydro-omega-hydroxy-ethane-1,2-diol, ethoxylated	Rabbit	Minimal irritation
Aluminium oxide	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Orthophosphoric acid	official classification	Corrosive
Synthetic amorphous silica, fumed, crystalline free	Rabbit	No significant irritation
Poly(oxy-1,2-ethanediyl),alpha-hydro-omega-hydroxy-ethane-1,2-diol, ethoxylated	Rabbit	Mild irritant
Aluminium oxide	Rabbit	No significant irritation

Skin Sensitisation

Name	Species	Value
Orthophosphoric acid	Human	Not classified
Synthetic amorphous silica, fumed, crystalline free	Human and animal	Not classified
Poly(oxy-1,2-ethanediyl),alpha-hydro-omega-hydroxy-ethane-1,2-diol, ethoxylated	Guinea pig	Not classified

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Orthophosphoric acid	In Vitro	Not mutagenic
Synthetic amorphous silica, fumed, crystalline free	In Vitro	Not mutagenic
Poly(oxy-1,2-ethanediyl),alpha-hydro-omega-hydroxy-ethane-1,2-diol, ethoxylated	In Vitro	Not mutagenic
Poly(oxy-1,2-ethanediyl),alpha-hydro-omega-hydroxy-ethane-1,2-diol, ethoxylated	In vivo	Not mutagenic
Aluminium oxide	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Synthetic amorphous silica, fumed, crystalline free	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Poly(oxy-1,2-ethanediyl),alpha-hydro-omega-hydroxy-ethane-1,2-diol, ethoxylated	Ingestion	Rat	Not carcinogenic
Aluminium oxide	Inhalation	Rat	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Orthophosphoric acid	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
Orthophosphoric acid	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
Orthophosphoric acid	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
Synthetic amorphous silica, fumed, crystalline free	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Synthetic amorphous silica, fumed, crystalline free	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Synthetic amorphous silica, fumed, crystalline free	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Poly(oxy-1,2-ethanediyl),alpha-hydro-omega-hydroxy-ethane-1,2-diol, ethoxylated	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,125 mg/kg/day	during gestation
Poly(oxy-1,2-ethanediyl),alpha-hydro-omega-hydroxy-ethane-1,2-diol, ethoxylated	Ingestion	Not classified for male reproduction	Rat	NOAEL 5699 +/-1341 mg/kg/day	5 days
Poly(oxy-1,2-ethanediyl),alpha-hydro-omega-hydroxy-ethane-1,2-diol, ethoxylated	Not specified.	Not classified for reproduction and/or development		NOEL N/A	
Poly(oxy-1,2-ethanediyl),alpha-hydro-omega-hydroxy-ethane-1,2-diol, ethoxylated	Ingestion	Not classified for development	Mouse	NOAEL 562 mg/animal/day	during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Orthophosphoric acid	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Poly(oxy-1,2-ethanediyl),alpha-hydro-omega-hydroxy-ethane-1,2-diol, ethoxylated	Inhalation	respiratory irritation	Not classified	Rat	NOAEL 1.008 mg/l	2 weeks

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Synthetic amorphous silica, fumed, crystalline free	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Poly(oxy-1,2-ethanediyl),alpha-hydro-omega-hydroxy-ethane-1,2-diol, ethoxylated	Inhalation	respiratory system	Not classified	Rat	NOAEL 1.008 mg/l	2 weeks
Poly(oxy-1,2-ethanediyl),alpha-hydro-omega-hydroxy-ethane-1,2-diol, ethoxylated	Ingestion	kidney and/or bladder heart endocrine system hematopoietic system liver nervous system	Not classified	Rat	NOAEL 5,640 mg/kg/day	13 weeks
Aluminium oxide	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminium oxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Exposure Levels

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

Interactive Effects

Not determined.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

Not acutely toxic to aquatic life by GHS criteria.

Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Orthophosphoric acid	7664-38-2	Green algae	Experimental	72 hours	EC50	>100 mg/l
Orthophosphoric acid	7664-38-2	Water flea	Experimental	48 hours	EC50	>100 mg/l
Orthophosphoric acid	7664-38-2	Green algae	Experimental	72 hours	NOEC	100 mg/l
Synthetic amorphous silica, fumed, crystalline free	112945-52-5	Green Algae	Experimental	72 hours	EC50	>100 mg/l
Synthetic amorphous silica, fumed, crystalline free	112945-52-5	Water flea	Experimental	24 hours	EC50	>100 mg/l
Synthetic amorphous silica, fumed, crystalline free	112945-52-5	Zebra Fish	Experimental	96 hours	LC50	>100 mg/l
Synthetic amorphous silica, fumed, crystalline free	112945-52-5	Green Algae	Experimental	72 hours	NOEC	60 mg/l
Poly(oxy-1,2-ethanediyl), alpha-hydroxy-omega-hydroxy-ethane-1,2-diol, ethoxylated	25322-68-3	Atlantic Salmon	Experimental	96 hours	LC50	>1,000 mg/l
Aluminium oxide	1344-28-1	Fish	Experimental	96 hours	LC50	>100 mg/l
Aluminium oxide	1344-28-1	Green Algae	Experimental	72 hours	EC50	>100 mg/l
Aluminium oxide	1344-28-1	Water flea	Experimental	48 hours	LC50	>100 mg/l

3M™ ESPE™ Scotchbond™ Universal Etchant

Aluminium oxide	1344-28-1	Green Algae	Experimental	72 hours	NOEC	>100 mg/l
-----------------	-----------	-------------	--------------	----------	------	-----------

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Orthophosphoric acid	7664-38-2	Data not available-insufficient			N/A	
Synthetic amorphous silica, fumed, crystalline free	112945-52-5	Data not available-insufficient			N/A	
Poly(oxy-1,2-ethanediyl),alpha-hydro-omega-hydroxy-ethane-1,2-diol, ethoxylated	25322-68-3	Experimental Biodegradation	28 days	BOD	53 % BOD/ThBOD	OECD 301C - MITI test (I)
Aluminium oxide	1344-28-1	Data not available-insufficient			N/A	

12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Orthophosphoric acid	7664-38-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Synthetic amorphous silica, fumed, crystalline free	112945-52-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Poly(oxy-1,2-ethanediyl),alpha-hydro-omega-hydroxy-ethane-1,2-diol, ethoxylated	25322-68-3	Estimated Bioconcentration		Bioaccumulation factor	2.3	Estimated: Bioconcentration factor
Aluminium oxide	1344-28-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility.

SECTION 14: Transport Information

Australian Dangerous Goods Code (ADG) - Road/Rail Transport

UN No.: UN1805

Proper shipping name: PHOSPHORIC ACID SOLUTION

Class/Division: 8

Sub Risk: Not applicable.

Packing Group: III

Special Instructions: Excepted quantity may apply

Hazchem Code: 2R

IERG: 37

International Air Transport Association (IATA) - Air Transport

UN No.: UN1805

Proper shipping name: PHOSPHORIC ACID SOLUTION

Class/Division: 8

Sub Risk: Not applicable.

Packing Group: III

Special Instructions: Excepted Quantity may apply

International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: UN1805

Proper shipping name: PHOSPHORIC ACID SOLUTION

Class/Division: 8

Sub Risk: Not applicable.

Packing Group: III

Marine Pollutant: Not applicable.

Special Instructions: Forbidden due to internal policy

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Australian Inventory Status:

This product is regulated by the Therapeutics Goods Administration and is exempt from compliance with the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

SECTION 16: Other information

Revision information:

Complete document review.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State

regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au