



Safety Data Sheet

Copyright, 2017, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	28-1016-6	Version number:	1.01
Issue Date:	16/10/2017	Supersedes date:	16/11/2016

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

IDENTIFICATION:

1.1. Product identifier

3M™ Semi-Rigid Plastic Repair PN 34240

Product Identification Numbers

60-4550-5240-1

1.2. Recommended use and restrictions on use

Recommended use

Automotive.

For Industrial or Professional use only.

1.3. Supplier's details

Address: 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113
Telephone: 136 136
E Mail: productinfo.au@mmm.com
Website: www.3m.com.au

1.4. Emergency telephone number

Company Emergency Hotline: EMERGENCY: 1800 097 146 (Australia only)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the SDSs for components of this product are:

28-7003-8, 28-7005-3

One or more components of this KIT is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

TRANSPORT INFORMATION

For transportation and storage this KIT and its components are NOT classified as Dangerous Goods

Marine Pollutant:Not applicable.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au



Safety Data Sheet

Copyright, 2017, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	28-7003-8	Version number:	1.01
Issue Date:	11/10/2017	Supersedes date:	16/11/2016

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

SECTION 1: Identification

1.1. Product identifier

3M™ Semi-Rigid Plasic Repair PN 34240 (Part A)

1.2. Recommended use and restrictions on use

Recommended use

Automotive.

For Industrial or Professional use only.

1.3. Supplier's details

Address: 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113
Telephone: 136 136
E Mail: productinfo.au@mmm.com
Website: www.3m.com.au

1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 2.
Skin Corrosion/Irritation: Category 2.
Respiratory Sensitizer: Category 1.
Skin Sensitizer: Category 1.
Specific Target Organ Toxicity (single exposure): Category 3.
Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for

Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

Signal word

DANGER!

Symbols

Exclamation mark | Health Hazard |

Pictograms



Hazard statements

H319	Causes serious eye irritation.
H315	Causes skin irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H372	Causes damage to organs through prolonged or repeated exposure: respiratory system

Precautionary statements

General:

P102	Keep out of reach of children.
P103	Read label before use.
P101	If medical advice is needed, have product container or label at hand.

Prevention:

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P284	Wear respiratory protection.
P280A	Wear eye/face protection.
P280E	Wear protective gloves.
P270	Do not eat, drink or smoke when using this product.
P264	Wash thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.

Response:

P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P304 + P341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
P342 + P311	If experiencing respiratory symptoms: Call a POISON CENTRE or doctor/physician.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P363	Wash contaminated clothing before reuse.

3M™ Semi-Rigid Plastic Repair PN 34240 (Part A)

P321	Specific treatment (see Notes to Physician on this label).
P312	Call a POISON CENTRE or doctor/physician if you feel unwell.
P314	Get medical advice/attention if you feel unwell.

Storage:

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.

Disposal:

P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.
------	--

2.3. Other assigned/identified product hazards

Persons previously sensitised to isocyanates may develop a cross-sensitisation reaction to other isocyanates.

2.4. Other hazards which do not result in classification

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
Castor Oil, Polymer With 1,1'-Methylenebis[4-Isocyanatobenzene]	68424-09-9	30 - 60
P,P'-Methylenebis(Phenyl Isocyanate)	101-68-8	30 - 60
4,4'-Methylenediphenyl diisocyanate, oligomers	25686-28-6	10 - 30
Oxirane, Methyl-, Polymer With Oxirane, Ether With 1,2,3-Propanetriol (3:1), Polymer With 1,1'-Methylenebis[4-Isocyanatobenzene]	59675-67-1	1 - 5
Carbon black	1333-86-4	0.1 - 1
Chromium	7440-47-3	< 0.02

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.
Hydrogen cyanide.	During combustion.
Oxides of nitrogen.	During combustion.
Toxic vapour, gas, particulate.	During combustion.

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Pour isocyanate decontaminant solution (90% water, 8% concentrated ammonia, 2% detergent) on spill and allow to react for 10 minutes. Or pour water on spill and allow to react for more than 30 minutes. Cover with absorbent material. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from acids. Store away from strong bases.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
P,P'-Methylenebis(Phenyl Isocyanate)	101-68-8	ACGIH	TWA:0.005 ppm	
Free isocyanates	101-68-8	Australia OELs	TWA(as NCO)(8 hours):0.02 mg/m ³ ;STEL(as NCO)(15 minutes):0.07 mg/m ³	
Free isocyanates	101-68-8	Manufacturer determined	TWA:0.005 ppm;STEL:0.02 ppm	
P,P'-Methylenebis(Phenyl Isocyanate)	101-68-8	Australia OELs	TWA(8 hours):0.02 mg/m ³ ;STEL(15 minutes):0.07 mg/m ³	
Carbon black	1333-86-4	Australia OELs	TWA(8 hours): 3 mg/m ³	
Carbon black	1333-86-4	ACGIH	TWA(inhalable fraction):3 mg/m ³	A3: Confirmed animal carcinogen.
Chromium	7440-47-3	Australia OELs	TWA(8 hours): 0.5 mg/m ³	
Chromium	7440-47-3	ACGIH	TWA(as Cr):0.5 mg/m ³	A4: Not class. as human carcin

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

Skin/hand protection

3M™ Semi-Rigid Plasic Repair PN 34240 (Part A)

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl rubber.
Nitrile rubber.

if this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Butyl rubber
Apron – Nitrile

Select and use gloves according to AS/NZ 2161.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Viscous.
Appearance/Odour	Low or no detectable odour, weakly aromatic, black.
Odour threshold	<i>No data available.</i>
pH	<i>Not applicable.</i>
Melting point/Freezing point	<i>No data available.</i>
Boiling point/Initial boiling point/Boiling range	≥ 204.4 °C
Flash point	≥ 143.3 °C [<i>Test Method</i> :Tagliabue closed cup]
Evaporation rate	≤ 1 [<i>Details</i> :Gels with exposure to humidity.]
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	<i>Not applicable.</i>
Flammable Limits(UEL)	<i>Not applicable.</i>
Vapour pressure	≤ 0 Pa [<i>@ 20 °C</i>]
Vapour density	≥ 1 [<i>Ref Std</i> :AIR=1]
Density	1 - 1.2 g/ml
Relative density	1 - 1.2 [<i>Ref Std</i> :WATER=1]
Water solubility	Negligible
Solubility- non-water	<i>No data available.</i>
Autoignition temperature	<i>Not applicable.</i>
Decomposition temperature	<i>No data available.</i>
Volatile organic compounds (VOC)	0 g/l [<i>Test Method</i> :calculated SCAQMD rule 443.1]
Volatile organic compounds (VOC)	0 % weight [<i>Test Method</i> :calculated per CARB title 2]
Percent volatile	0 % weight
VOC less H2O & exempt solvents	0 g/l [<i>Test Method</i> :calculated SCAQMD rule 443.1]

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3. Conditions to avoid

None known.

10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.5 Incompatible materials

Water

Strong acids.

Strong bases.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
------------------	------------------

None known.	
-------------	--

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic respiratory reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest. May cause additional health effects (see below).

Skin contact

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Additional Health Effects:

3M™ Semi-Rigid Plasic Repair PN 34240 (Part A)**Prolonged or repeated exposure may cause target organ effects:**

Prolonged or repeated exposure by inhalation may cause:

Respiratory effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and respiratory failure.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Additional information:

Persons previously sensitised to isocyanates may develop a cross-sensitisation reaction to other isocyanates.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE10 - 20 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
P,P'-Methylenebis(Phenyl Isocyanate)	Dermal	Rabbit	LD50 > 5,000 mg/kg
P,P'-Methylenebis(Phenyl Isocyanate)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.368 mg/l
P,P'-Methylenebis(Phenyl Isocyanate)	Ingestion	Rat	LD50 31,600 mg/kg
4,4'-Methylenediphenyl diisocyanate, oligomers	Dermal	Rabbit	LD50 > 5,000 mg/kg
4,4'-Methylenediphenyl diisocyanate, oligomers	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.368 mg/l
4,4'-Methylenediphenyl diisocyanate, oligomers	Ingestion	Rat	LD50 31,600 mg/kg
Carbon black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon black	Ingestion	Rat	LD50 > 8,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
P,P'-Methylenebis(Phenyl Isocyanate)	official classification	Irritant
4,4'-Methylenediphenyl diisocyanate, oligomers	official classification	Irritant
Carbon black	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
P,P'-Methylenebis(Phenyl Isocyanate)	official classification	Severe irritant
4,4'-Methylenediphenyl diisocyanate, oligomers	official classification	Severe irritant
Carbon black	Rabbit	No significant irritation

Skin Sensitisation

Name	Species	Value
P,P'-Methylenebis(Phenyl Isocyanate)	official classification	Sensitising
4,4'-Methylenediphenyl diisocyanate, oligomers	official classification	Sensitising

Respiratory Sensitisation

3M™ Semi-Rigid Plasic Repair PN 34240 (Part A)

Name	Species	Value
P,P'-Methylenebis(Phenyl Isocyanate)	Human	Sensitising
4,4'-Methylenediphenyl diisocyanate, oligomers	Human	Sensitising

Germ Cell Mutagenicity

Name	Route	Value
P,P'-Methylenebis(Phenyl Isocyanate)	In Vitro	Some positive data exist, but the data are not sufficient for classification
4,4'-Methylenediphenyl diisocyanate, oligomers	In Vitro	Some positive data exist, but the data are not sufficient for classification
Carbon black	In Vitro	Not mutagenic
Carbon black	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
P,P'-Methylenebis(Phenyl Isocyanate)	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
4,4'-Methylenediphenyl diisocyanate, oligomers	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Carbon black	Dermal	Mouse	Not carcinogenic
Carbon black	Ingestion	Mouse	Not carcinogenic
Carbon black	Inhalation	Rat	Carcinogenic.

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
P,P'-Methylenebis(Phenyl Isocyanate)	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis
4,4'-Methylenediphenyl diisocyanate, oligomers	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
P,P'-Methylenebis(Phenyl Isocyanate)	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	
4,4'-Methylenediphenyl diisocyanate, oligomers	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
P,P'-Methylenebis(Inhalation	respiratory system	Causes damage to organs through	Rat	LOAEL 0.004 mg/l	13 weeks

3M™ Semi-Rigid Plastic Repair PN 34240 (Part A)

Phenyl Isocyanate)			prolonged or repeated exposure			
4,4'-Methylenediphenyl diisocyanate, oligomers	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
Carbon black	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Exposure Levels

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

Interactive Effects

Not determined.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity**Acute aquatic hazard:**

Not acutely toxic to aquatic life by GHS criteria.

Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Castor Oil, Polymer With 1,1'-Methylenebis[4-Isocyanatobenzene]	68424-09-9		Data not available or insufficient for classification			
P,P'-Methylenebis(Phenyl Isocyanate)	101-68-8	Water flea	Experimental	24 hours	EC50	>100 mg/l
4,4'-Methylenediphenyl diisocyanate, oligomers	25686-28-6	Green algae	Estimated	72 hours	EC50	>1,640 mg/l
4,4'-Methylenediphenyl diisocyanate, oligomers	25686-28-6	Ricefish	Estimated	96 hours	LC50	>3,000 mg/l

3M™ Semi-Rigid Plastic Repair PN 34240 (Part A)

enyl diisocyanate, oligomers						
4,4'-Methylenediphenyl diisocyanate, oligomers	25686-28-6	Water flea	Estimated	24 hours	EC50	>1,000 mg/l
4,4'-Methylenediphenyl diisocyanate, oligomers	25686-28-6	Water flea	Estimated	21 days	NOEC	>=10 mg/l
4,4'-Methylenediphenyl diisocyanate, oligomers	25686-28-6	Green algae	Estimated	72 hours	NOEC	1,640 mg/l
Oxirane, Methyl-, Polymer With Oxirane, Ether With 1,2,3-Propanetriol (3:1), Polymer With 1,1'-Methylenebis[4-Isocyanatobenzene]	59675-67-1		Data not available or insufficient for classification			
Carbon black	1333-86-4		Data not available or insufficient for classification			
Chromium	7440-47-3		Data not available or insufficient for classification			

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Castor Oil, Polymer With 1,1'-Methylenebis[4-Isocyanatobenzene]	68424-09-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
P,P'-Methylenebis(Phenyl Isocyanate)	101-68-8	Estimated Hydrolysis		Hydrolytic half-life	<2 hours (t 1/2)	Other methods
P,P'-Methylenebis(P)	101-68-8	Experimental Biodegradation	28 days	BOD	0 % weight	OECD 301C - MITI test (I)

3M™ Semi-Rigid Plastic Repair PN 34240 (Part A)

henyl Isocyanate)						
4,4'-Methylenediphenyl diisocyanate, oligomers	25686-28-6	Estimated Hydrolysis		Hydrolytic half-life	20 hours (t 1/2)	Other methods
Oxirane, Methyl-, Polymer With Oxirane, Ether With 1,2,3-Propanetriol (3:1), Polymer With 1,1'-Methylenebis[4 - Isocyanatobenzene]	59675-67-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Carbon black	1333-86-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Chromium	7440-47-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Castor Oil, Polymer With 1,1'-Methylenebis[4 - Isocyanatobenzene]	68424-09-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
P,P'-Methylenebis(P henyl Isocyanate)	101-68-8	Experimental BCF-Carp	28 days	Bioaccumulation factor	200	Other methods
4,4'-Methylenediphenyl diisocyanate, oligomers	25686-28-6	Estimated BCF-Carp	28 days	Bioaccumulation factor	200	OECD 305E - Bioaccumulation flow-through fish test
Oxirane, Methyl-, Polymer With Oxirane, Ether With 1,2,3-Propanetriol (3:1), Polymer With 1,1'-	59675-67-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

3M™ Semi-Rigid Plasic Repair PN 34240 (Part A)

Methylenebis[4-Isocyanobenzene]						
Carbon black	1333-86-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Chromium	7440-47-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate uncured product in a permitted waste incineration facility. Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste.

SECTION 14: Transport Information**Australian Dangerous Goods Code (ADG) - Road/Rail Transport**

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

Hazchem Code: Not applicable

IERG: Not applicable.

International Air Transport Association (IATA) - Air Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

Marine Pollutant: Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Australian Inventory Status:

The chemical components contained within this product are listed on the Australian Inventory of Chemical Substances and are in compliance with the requirements of the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

Poison Schedule: This product is intended for Industrial or Professional Use only and therefore is not packaged and labelled in accordance with the requirements of the Standard for the Uniform Scheduling of Medicines and Poisons.

SECTION 16: Other information

Revision information:

Initial issue.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au



Safety Data Sheet

Copyright,2016,3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	28-7005-3	Version number:	1.00
Issue Date:	16/11/2016	Supersedes date:	Initial issue.

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

SECTION 1: Identification

1.1. Product identifier

3M™ Semi-Rigid Plastic Repair PN 34240 - Part B

1.2. Recommended use and restrictions on use

Recommended use

Automotive.

For Industrial or Professional use only.

1.3. Supplier's details

Address: 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113
Telephone: 136 136
E Mail: productinfo.au@mmm.com
Website: www.3m.com.au

1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 2.

Skin Corrosion/Irritation: Category 2.

Skin Sensitizer: Category 1.

2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

Signal word

WARNING!

Symbols

Exclamation mark |

Pictograms



Hazard statements

H319 Causes serious eye irritation.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.

Precautionary statements

General:

P102 Keep out of reach of children.
P103 Read label before use.
P101 If medical advice is needed, have product container or label at hand.

Prevention:

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280A Wear eye/face protection.
P280E Wear protective gloves.
P264 Wash thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 If eye irritation persists: Get medical advice/attention.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P363 Wash contaminated clothing before reuse.
P321 Specific treatment (see Notes to Physician on this label).

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other assigned/identified product hazards

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines.

2.4. Other hazards which do not result in classification

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
------------	---------	-------------

3M™ Semi-Rigid Plastic Repair PN 34240 - Part B

Polyether Polyol	9082-00-2	40 - 70
Propoxylated Trimethylolpropane	25723-16-4	10 - 30
Tetrakis(2-Hydroxypropyl)Ethylenediamine	102-60-3	10 - 30
M-Xylene-Alpha,Alpha'-Diamine	1477-55-0	1 - 5

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.
Oxides of nitrogen.	During combustion.

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from oxidising agents.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
M-Xylene-Alpha,Alpha'-Diamine	1477-55-0	ACGIH	CEIL: 0.1 mg/m3	SKIN
M-Xylene-Alpha,Alpha'-Diamine	1477-55-0	Australia OELs	Peak limit:0.1 mg/m3	SKIN

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl rubber.

Select and use gloves according to AS/NZ 2161.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state	Liquid.
Specific Physical Form:	Viscous.
Appearance/Odour	Slight ammonia like odour, clear.
Odour threshold	<i>No data available.</i>
pH	<i>Not applicable.</i>
Melting point/Freezing point	<i>No data available.</i>
Boiling point/Initial boiling point/Boiling range	>=210 °C
Flash point	>=143.3 °C [<i>Test Method</i> :Tagliabue closed cup]
Evaporation rate	<=1 [<i>Ref Std</i> :WATER=1]
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	<i>Not applicable.</i>
Flammable Limits(UEL)	<i>Not applicable.</i>
Vapour pressure	<i>Not applicable.</i>
Vapour density	>=1 [<i>Ref Std</i> :AIR=1]
Density	1 - 1.1 g/ml
Relative density	1 - 1.1 [<i>Ref Std</i> :WATER=1]
Water solubility	Negligible
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Autoignition temperature	<i>Not applicable.</i>
Decomposition temperature	<i>No data available.</i>
Viscosity	1,400 - 1,800 mPa-s
Volatile organic compounds (VOC)	0 g/l [<i>Test Method</i> :calculated SCAQMD rule 443.1]
Volatile organic compounds (VOC)	0 % weight [<i>Test Method</i> :calculated per CARB title 2]
Percent volatile	0.49 % weight
VOC less H2O & exempt solvents	0 g/l [<i>Test Method</i> :calculated SCAQMD rule 443.1]

SECTION 10: Stability and reactivity**10.1 Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3. Conditions to avoid

None known.

10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.5 Incompatible materials

Strong acids.

Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin contact

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Additional information:

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or

3M™ Semi-Rigid Plastic Repair PN 34240 - Part B

the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Polyether Polyol	Dermal	Rabbit	LD50 > 5,000 mg/kg
Polyether Polyol	Ingestion	Rat	LD50 > 10,000 mg/kg
Propoxylated Trimethylolpropane	Dermal	Rat	LD50 > 2,000 mg/kg
Propoxylated Trimethylolpropane	Ingestion	Rat	LD50 > 2,500 mg/kg
Tetrakis(2-Hydroxypropyl)Ethylenediamine	Dermal	Rabbit	LD50 > 2,000 mg/kg
Tetrakis(2-Hydroxypropyl)Ethylenediamine	Ingestion	Rat	LD50 3,280 mg/kg
M-Xylene-Alpha,Alpha'-Diamine	Dermal	Rabbit	LD50 > 2,000 mg/kg
M-Xylene-Alpha,Alpha'-Diamine	Inhalation-Dust/Mist (4 hours)	Rat	LC50 1.2 mg/l
M-Xylene-Alpha,Alpha'-Diamine	Ingestion	Rat	LD50 980 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Propoxylated Trimethylolpropane	Rabbit	No significant irritation
M-Xylene-Alpha,Alpha'-Diamine	Rat	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
Propoxylated Trimethylolpropane	Rabbit	Mild irritant
M-Xylene-Alpha,Alpha'-Diamine	Rabbit	Corrosive

Skin Sensitisation

Name	Species	Value
M-Xylene-Alpha,Alpha'-Diamine	Guinea pig	Sensitising

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
M-Xylene-Alpha,Alpha'-Diamine	In Vitro	Not mutagenic
M-Xylene-Alpha,Alpha'-Diamine	In vivo	Not mutagenic

Carcinogenicity

For the component/components, either no data are currently available or the data are not sufficient for classification.

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
M-Xylene-Alpha,Alpha'-	Ingestion	Not toxic to female reproduction	Rat	NOAEL 450 mg/kg/day	1 generation

3M™ Semi-Rigid Plastic Repair PN 34240 - Part B

Diamine					
M-Xylene-Alpha,Alpha'-Diamine	Ingestion	Not toxic to male reproduction	Rat	NOAEL 450 mg/kg	1 generation
M-Xylene-Alpha,Alpha'-Diamine	Ingestion	Not toxic to development	Rat	NOAEL 450 mg/kg/day	1 generation

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
M-Xylene-Alpha,Alpha'-Diamine	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Not available	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
M-Xylene-Alpha,Alpha'-Diamine	Ingestion	endocrine system blood bone marrow	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 600 mg/kg/day	28 days

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Exposure Levels

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

Interactive Effects

Not determined.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity**Acute aquatic hazard:**

Not acutely toxic to aquatic life by GHS criteria.

Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
M-Xylene-	1477-55-0	Green Algae	Experimental	72 hours	NOEC	9.8 mg/l

3M™ Semi-Rigid Plastic Repair PN 34240 - Part B

Alpha,Alpha'-Diamine						
M-Xylene-Alpha,Alpha'-Diamine	1477-55-0	Ricefish	Experimental	96 hours	LC50	87.6 mg/l
M-Xylene-Alpha,Alpha'-Diamine	1477-55-0	Water flea	Experimental	48 hours	EC50	15.2 mg/l
M-Xylene-Alpha,Alpha'-Diamine	1477-55-0	Water flea	Experimental	21 days	NOEC	4.7 mg/l
M-Xylene-Alpha,Alpha'-Diamine	1477-55-0	Green Algae	Experimental	72 hours	EC50	28 mg/l
Propoxylated Trimethylolpropane	25723-16-4		Data not available or insufficient for classification			
Polyether Polyol	9082-00-2	Inland Silverside	Estimated	96 hours	LC50	650 mg/l
Tetrakis(2-Hydroxypropyl)Ethylenediamine	102-60-3	Fathead minnow	Experimental	96 hours	LC50	>1,000 mg/l
Tetrakis(2-Hydroxypropyl)Ethylenediamine	102-60-3	Green algae	Estimated	72 hours	EC50	>100 mg/l
Tetrakis(2-Hydroxypropyl)Ethylenediamine	102-60-3	Water flea	Estimated	48 hours	EC50	>500 mg/l

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Tetrakis(2-Hydroxypropyl)Ethylenediamine	102-60-3	Experimental Biodegradation	28 days	BOD	1 % weight	OECD 301C - MITI test (I)
M-Xylene-Alpha,Alpha'-Diamine	1477-55-0	Estimated Photolysis		Photolytic half-life (in air)	5.4 hours (t _{1/2})	Other methods
M-Xylene-Alpha,Alpha'-Diamine	1477-55-0	Experimental Biodegradation	28 days	CO ₂ evolution	49 % weight	OECD 301B - Modified sturm or CO ₂
Propoxylated Trimethylolpropane	25723-16-4	Estimated Biodegradation	28 days	BOD	85 % weight	OECD 301F - Manometric respirometry
Polyether Polyol	9082-00-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.3 : Bioaccumulative potential

3M™ Semi-Rigid Plastic Repair PN 34240 - Part B

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Tetrakis(2-Hydroxypropyl)Ethylendiamine	102-60-3	Experimental Bioconcentration		Log Kow	0.27	Other methods
M-Xylene-Alpha,Alpha'-Diamine	1477-55-0	Experimental BCF-Carp	42 days	Bioaccumulation factor	<2.7	OECD 305E - Bioaccumulation flow-through fish test
Propoxylated Trimethylolpropane	25723-16-4	Estimated BCF - Fathead Mi		Bioaccumulation factor	1.9	Estimated: Bioconcentration factor
Polyether Polyol	9082-00-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate uncured product in a permitted waste incineration facility. Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste.

SECTION 14: Transport Information**Australian Dangerous Goods Code (ADG) - Road/Rail Transport**

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

Hazchem Code: Not applicable

IERG: Not applicable.

International Air Transport Association (IATA) - Air Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

Marine Pollutant: Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Australian Inventory Status:

The chemical components contained within this product are listed on the Australian Inventory of Chemical Substances and are in compliance with the requirements of the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

Poison Schedule: This product is intended for Industrial or Professional Use only and therefore is not packaged and labelled in accordance with the requirements of the Standard for the Uniform Scheduling of Medicines and Poisons.

SECTION 16: Other information

Revision information:

Initial issue.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au