

Safety Data Sheet

Copyright, 2024, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 28-3754-0
 Version number:
 4.03

 Issue Date:
 03/03/2024
 Supersedes date:
 29/02/2024

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

IDENTIFICATION:

1.1. Product identifier

3MTM RelyXTM Unicem 2 Automix Refill (56846, 56847, 56848)

Product Identification Numbers

70-2011-4030-1 70-2011-4031-9 70-2011-4032-7 UU-0104-3510-3 UU-0104-3511-1

UU-0104-3512-9

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Dental Cement

Restrictions on use

For use by dental professionals only.

1.3. Supplier's details

Address: 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113

Telephone: 136 136

E Mail: productinfo.au@mmm.com

Website: www.3m.com.au

1.4. Emergency telephone number

Company Emergency Hotline: EMERGENCY: 1800 097 146 (Australia only)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the SDSs for components of this product are:

28-1333-5, 28-1380-6

One or more components of this KIT is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

TRANSPORT INFORMATION

The Dangerous Goods Classification for the complete Kit is provided below.

Marine Pollutant: Not applicable.

Hazchem Code: 2Z

Australian Dangerous Goods Code (ADG) - Road/Rail Transport

Special Instructions: Not restricted, environmentally hazardous substance exception.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au



Safety Data Sheet

Copyright, 2022, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 28-1380-6
 Version number:
 4.00

 Issue Date:
 10/04/2022
 Supersedes date:
 20/11/2019

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

SECTION 1: Identification

1.1. Product identifier

3MTM RelyXTM Unicem 2 Automix Base Paste

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Cement

Restrictions on use

For use by dental professionals only.

1.3. Supplier's details

Address: 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113

Telephone: 136 136

E Mail: productinfo.au@mmm.com

Website: www.3m.com.au

1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

Skin Sensitizer: Category 1.

2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

Signal word

Warning

Symbols

Exclamation mark |

Pictograms



Hazard statements

H317 May cause an allergic skin reaction.

Precautionary statements

Prevention:

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention. P362 + P364 Take off contaminated clothing and wash it before reuse.

Disposal:

P501 Dispose of contents/container in accordance with applicable

local/regional/national/international regulations.

2.3. Other assigned/identified product hazards

None known.

2.4. Other hazards which do not result in classification

May be harmful if swallowed. Causes mild skin irritation.

Toxic to aquatic life with long lasting effects.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
Glass powder (65997-17-3), surface	None	45 - 55
modified with 2-propenoic acid, 2		
methyl3-(trimethoxysilyl)propyl ester		
(2530-85-0) and phenyltrimethoxy silane		
(2996-92-1), bulk material		
2-Propenoic acid, 2-methyl-, 1,1'-[1-	1224866-76-5	20 - 30
(hydroxymethyl)-1,2-ethanediyl] ester,		
reaction products with 2-hydroxy-1,3-		
propanediyl dimethacrylate and phosphorus		
oxide		
2,2'-ethylenedioxydiethyl dimethacrylate	109-16-0	10 - 20
2-Propenoic acid, 2-methyl-, 3-	68909-20-6	1 - 10

(trimetoxysilyl)propyl ester, hydrolysis		
products with silica		
OXIDE GLASS CHEMICALS (non-	65997-17-3	< 3
fibrous)		
Sodium Persulphate	7775-27-1	< 3
tert-Butyl peroxy-3,5,5-trimethylhexanoate	13122-18-4	< 0.5
Acetic acid, copper(2+) salt, monohydrate	6046-93-1	< 0.1

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eve contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide.

Carbon dioxide.

Irritant vapours or gases.

Condition

During combustion.

During combustion.

During combustion.

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

Hazchem Code: 2Z

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for

information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. Acrylates may penetrate commonly-used gloves. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Do not get in eyes.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
COPPER COMPOUNDS	6046-93-1	ACGIH	TWA(as Cu, fume):0.2	
			mg/m3;TWA(as Cu dust or	
			mist):1 mg/m3	
CERAMIC FIBERS	65997-17-3	ACGIH	TWA(as fiber):0.2 fiber/cc	A2: Suspected human carcin.
CERAMIC FIBERS	65997-17-3	Australia OELs	TWA(as fiber)(8 hours):0.5 fibers/ml	
CONTINUOUS FILAMENT	65997-17-3	ACGIH	TWA(as fiber):1 fiber/cc	A4: Not class. as human
GLASS FIBERS				carcin
CONTINUOUS FILAMENT	65997-17-3	ACGIH	TWA(inhalable fraction):5	A4: Not class. as human
GLASS FIBERS, INHALABLE			mg/m3	carcin
FRACTION				
Glass filaments	65997-17-3	Australia OELs	TWA(as fiber)(8 hours):0.5	
			fibers/ml;TWA(8 hours):0.5	
			fibers/ml	
GLASS WOOL FIBERS	65997-17-3	ACGIH	TWA(as fiber):1 fiber/cc	A3: Confirmed animal
				carcinogen.
ROCK WOOL FIBERS	65997-17-3	ACGIH	TWA(as fiber):1 fiber/cc	A3: Confirmed animal
				carcinogen.
SLAG WOOL FIBERS	65997-17-3	ACGIH	TWA(as fiber):1 fiber/cc	A3: Confirmed animal
				carcinogen.
SPECIAL PURPOSE GLASS	65997-17-3	ACGIH	TWA(as fiber):1 fiber/cc	A3: Confirmed animal
FIBERS				carcinogen.
PERSULFATE COMPOUNDS	7775-27-1	ACGIH	TWA(as persulfate):0.1 mg/m3	

3MTM RelyXTM Unicem 2 Automix Base Paste

Sodium Persulphate	7775_27_1	LAuctralia OFI c	Peak limit:0.01 mg/m3	
30dium i cisuiphate	1113-41-1	Australia OLLS	i cak iiiiit.v.vi iiig/iiij	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

Australia OELs: Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG: Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

information on basic physical and chemical properties	<u></u>	
Physical state	Solid.	
Specific Physical Form:	Paste	
Colour	Tooth	
Odour	Slight Acrylic	
Odour threshold	No data available.	
pH	Not applicable.	
Melting point/Freezing point	No data available.	
Boiling point/Initial boiling point/Boiling range	No data available.	
Flash point	No flash point	
Evaporation rate	No data available.	
Flammability (solid, gas)	Not classified	
Flammable Limits(LEL)	No data available.	
Flammable Limits(UEL)	No data available.	
Vapour pressure	No data available.	
Vapor Density and/or Relative Vapor Density	No data available.	
Density	2 g/cm3 - 2.2 g/cm3	
Relative density	2 - 2.2 [<i>Ref Std</i> :WATER=1]	
Water solubility	Negligible	
Solubility- non-water	No data available.	

Partition coefficient: n-octanol/water	No data available.
Autoignition temperature	No data available.
Decomposition temperature	No data available.
Viscosity/Kinematic Viscosity	No data available.
Volatile organic compounds (VOC)	No data available.
Percent volatile	No data available.
VOC less H2O & exempt solvents	No data available.
Molecular weight	No data available.

Nanoparticles

This material contains nanoparticles.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3. Conditions to avoid

Heat.

10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

Substance

None known.

Condition

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

This product may have a characteristic odour; however, no adverse health effects are anticipated.

Skin contact

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
Glass powder (65997-17-3), surface modified with 2-propenoic acid, 2 methyl3-(trimethoxysilyl)propyl ester (2530-85-0) and phenyltrimethoxy silane (2996-92-1), bulk material	Dermal		LD50 estimated to be > 5,000 mg/kg
Glass powder (65997-17-3), surface modified with 2-propenoic acid, 2 methyl3-(trimethoxysilyl)propyl ester (2530-85-0) and phenyltrimethoxy silane (2996-92-1), bulk material	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
2-Propenoic acid, 2-methyl-, 1,1'-[1- (hydroxymethyl)-1,2-ethanediyl] ester, reaction products with 2- hydroxy-1,3-propanediyl dimethacrylate and phosphorus oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
2-Propenoic acid, 2-methyl-, 1,1'-[1-(hydroxymethyl)-1,2-ethanediyl] ester, reaction products with 2-hydroxy-1,3-propanediyl dimethacrylate and phosphorus oxide	Ingestion	Rat	LD50 > 2,000 mg/kg
2,2'-ethylenedioxydiethyl dimethacrylate	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
2,2'-ethylenedioxydiethyl dimethacrylate	Ingestion	Rat	LD50 10,837 mg/kg
2-Propenoic acid, 2-methyl-, 3- (trimetoxysilyl)propyl ester, hydrolysis products with silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
2-Propenoic acid, 2-methyl-, 3- (trimetoxysilyl)propyl ester, hydrolysis products with silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
2-Propenoic acid, 2-methyl-, 3- (trimetoxysilyl)propyl ester, hydrolysis products with silica	Ingestion	Rat	LD50 > 5,110 mg/kg
OXIDE GLASS CHEMICALS (non-fibrous)	Dermal		LD50 estimated to be > 5,000 mg/kg
OXIDE GLASS CHEMICALS (non-fibrous)	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Sodium Persulphate	Dermal	Rabbit	LD50 > 10,000 mg/kg
Sodium Persulphate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 47.93 mg/l
Sodium Persulphate	Ingestion	Rat	LD50 895 mg/kg
tert-Butyl peroxy-3,5,5-	Dermal	Rat	LD50 > 2,000 mg/kg

3MTM RelyXTM Unicem 2 Automix Base Paste

trimethylhexanoate			
tert-Butyl peroxy-3,5,5-	Inhalation-Dust/Mist	Rat	LC50 > 0.8 mg/l
trimethylhexanoate	(4 hours)		-
tert-Butyl peroxy-3,5,5-	Ingestion	Rat	LD50 12,905 mg/kg
trimethylhexanoate			

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Glass powder (65997-17-3), surface modified with 2-propenoic acid, 2 methyl3- (trimethoxysilyl)propyl ester (2530-85-0) and phenyltrimethoxy silane (2996-92-1), bulk material	Professional judgement	No significant irritation
2-Propenoic acid, 2-methyl-, 1,1'-[1- (hydroxymethyl)-1,2-ethanediyl] ester, reaction products with 2-hydroxy-1,3-propanediyl dimethacrylate and phosphorus oxide	Rabbit	Minimal irritation
2,2'-ethylenedioxydiethyl dimethacrylate	Guinea pig	Mild irritant
2-Propenoic acid, 2-methyl-, 3- (trimetoxysilyl)propyl ester, hydrolysis products with silica	Rabbit	No significant irritation
OXIDE GLASS CHEMICALS (non-fibrous)	Professional judgement	No significant irritation
tert-Butyl peroxy-3,5,5-trimethylhexanoate	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Overall product		No significant irritation
Glass powder (65997-17-3), surface modified with 2-propenoic acid, 2 methyl3- (trimethoxysilyl)propyl ester (2530-85-0) and phenyltrimethoxy silane (2996-92-1), bulk material	Professional judgement	No significant irritation
2-Propenoic acid, 2-methyl-, 1,1'-[1- (hydroxymethyl)-1,2-ethanediyl] ester, reaction products with 2-hydroxy-1,3-propanediyl dimethacrylate and phosphorus oxide	Rabbit	Corrosive
2,2'-ethylenedioxydiethyl dimethacrylate	Professional judgement	Moderate irritant
2-Propenoic acid, 2-methyl-, 3- (trimetoxysilyl)propyl ester, hydrolysis products with silica	Rabbit	No significant irritation
OXIDE GLASS CHEMICALS (non-fibrous)	Professional judgement	No significant irritation
tert-Butyl peroxy-3,5,5-trimethylhexanoate	Rabbit	No significant irritation

Skin Sensitisation

Name	Species	Value	
2-Propenoic acid, 2-methyl-, 1,1'-[1- (hydroxymethyl)-1,2-ethanediyl] ester, reaction products with 2-hydroxy-1,3-propanediyl dimethacrylate and phosphorus oxide	Guinea pig	Not classified	
2,2'-ethylenedioxydiethyl dimethacrylate	Human and animal	Sensitising	
2-Propenoic acid, 2-methyl-, 3- (trimetoxysilyl)propyl ester, hydrolysis products with silica	Human and animal	Not classified	
tert-Butyl peroxy-3,5,5-trimethylhexanoate	Guinea pig	Sensitising	-

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
2-Propenoic acid, 2-methyl-, 1,1'-[1- (hydroxymethyl)-1,2-ethanediyl] ester, reaction products with 2-hydroxy-1,3-propanediyl dimethacrylate and phosphorus oxide	In Vitro	Not mutagenic
2,2'-ethylenedioxydiethyl dimethacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
2-Propenoic acid, 2-methyl-, 3- (trimetoxysilyl)propyl ester, hydrolysis products with silica	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
2,2'-ethylenedioxydiethyl	Dermal	Mouse	Not carcinogenic
dimethacrylate			
2-Propenoic acid, 2-methyl-, 3-	Not specified.	Mouse	Some positive data exist, but the data
(trimetoxysilyl)propyl ester,	_		are not sufficient for classification
hydrolysis products with silica			

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
2,2'- ethylenedioxydiethyl dimethacrylate	Ingestion	Not classified for female reproduction	Mouse	NOAEL 1 mg/kg/day	1 generation
2,2'- ethylenedioxydiethyl dimethacrylate	Ingestion	Not classified for male reproduction	Mouse	NOAEL 1 mg/kg/day	1 generation
2,2'- ethylenedioxydiethyl dimethacrylate	Ingestion	Not classified for development	Mouse	NOAEL 1 mg/kg/day	1 generation
2-Propenoic acid, 2- methyl-, 3- (trimetoxysilyl)propy l ester, hydrolysis products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
2-Propenoic acid, 2- methyl-, 3- (trimetoxysilyl)propy l ester, hydrolysis products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
2-Propenoic acid, 2- methyl-, 3- (trimetoxysilyl)propy l ester, hydrolysis products with silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Organ(s) Duration	Name	Route	Target	Value	Species	Test result	Exposure
							Duration

Page: 9 of 17

2,2'- ethylenedioxy diethyl dimethacrylat	Dermal	kidney and/or bladder blood	Not classified	Mouse	NOAEL 833 mg/kg/day	78 weeks
2-Propenoic acid, 2- methyl-, 3- (trimetoxysily l)propyl ester, hydrolysis products with silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Exposure Levels

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

Interactive Effects

Not determined.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

GHS Acute 2: Toxic to aquatic life.

Chronic aquatic hazard:

GHS Chronic 2: Toxic to aquatic life with long lasting effects.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Glass powder	None		Data not			N/A
(65997-17-3),			available or			
surface			insufficient for			
modified with			classification			
2-propenoic						
acid, 2						
methyl3-						
(trimethoxysily						
l)propyl ester						
(2530-85-0)						
and						
phenyltrimetho						
xy silane						
(2996-92-1),						

bulk material						
2-Propenoic	1224866-76-5	Green algae	Endpoint not	72 hours	EC50	>100 mg/l
acid, 2-methyl-,	122.000 70 0	oreen urgue	reached	7 110 0115	2000	l 100 mg/1
1,1'-[1-			10001100			
(hydroxymethy						
1)-1,2-						
ethanediyl]						
ester, reaction						
products with						
2-hydroxy-1,3-						
propanediyl						
dimethacrylate						
and phosphorus						
oxide						
2-Propenoic	1224866-76-5	Water flea	Experimental	48 hours	EC50	>100 mg/l
acid, 2-methyl-,	1224000-70-3	vv atci iica	Experimental	46 110015	LC30	100 mg/1
1,1'-[1- (hydroxymethy						
1)-1,2-						
ethanediyl]						
ester, reaction						
products with						
2-hydroxy-1,3-						
propanediyl						
dimethacrylate						
and phosphorus oxide						
	1224866-76-5	C	F	70 1	NOEC	56
2-Propenoic	1224800-70-3	Green algae	Experimental	72 hours	NOEC	56 mg/l
acid, 2-methyl-,						
1,1'-[1-						
(hydroxymethy						
1)-1,2-						
ethanediyl]						
ester, reaction products with						
2-hydroxy-1,3-						
propanediyl						
dimethacrylate						
and phosphorus oxide						
	100 16 0	Croon Algon	Exmanimantal	72 hours	EC50	>100 ma/l
2,2'-	109-16-0	Green Algae	Experimental	72 hours	EC50	>100 mg/l
ethylenedioxyd						
iethyl						
dimethacrylate	100 16 0	Zohne Eigh	Europine s :: 4 - 1	06 h	1.050	16 A m a /1
2,2'-	109-16-0	Zebra Fish	Experimental	96 hours	LC50	16.4 mg/l
ethylenedioxyd						
iethyl						
dimethacrylate	100 16 0	C	F	70 1	NOEC	10.6
2,2'-	109-16-0	Green algae	Experimental	72 hours	NOEC	18.6 mg/l
ethylenedioxyd						
iethyl						
dimethacrylate	100.16.0	TT	 p	01.1	NOEC	22 /1
2,2'-	109-16-0	Water flea	Experimental	21 days	NOEC	32 mg/l
ethylenedioxyd						
iethyl			1			

dimethacrylate						
2-Propenoic	68909-20-6	Algae	Estimated	72 hours	EC50	>100 mg/l
acid, 2-methyl-,						
3-						
(trimetoxysilyl)						
propyl ester,						
hydrolysis						
products with						
silica						
OXIDE	65997-17-3	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
GLASS						
CHEMICALS						
(non-fibrous)						
OXIDE	65997-17-3	Water flea	Experimental	72 hours	EC50	>1,000 mg/l
GLASS						
CHEMICALS						
(non-fibrous)						
OXIDE	65997-17-3	Zebra Fish	Experimental	96 hours	LC50	>1,000 mg/l
GLASS						
CHEMICALS						
(non-fibrous)						
OXIDE	65997-17-3	Green algae	Experimental	72 hours	NOEC	>1,000 mg/l
GLASS						
CHEMICALS						
(non-fibrous)						
Sodium	7775-27-1	Algae other	Estimated	72 hours	EC50	320 mg/l
Persulphate						
Sodium	7775-27-1	Copepods	Estimated	48 hours	EC50	21.22 mg/l
Persulphate						
Sodium	7775-27-1	Rainbow trout	Estimated	96 hours	LC50	76.3 mg/l
Persulphate						
Sodium	7775-27-1	Algae other	Estimated	72 hours	NOEC	32 mg/l
Persulphate						
tert-Butyl	13122-18-4	Activated	Experimental	3 hours	NOEC	26.3 mg/l
peroxy-3,5,5-		sludge				
trimethylhexan						
oate						
tert-Butyl	13122-18-4	Green Algae	Experimental		EC50	0.51 mg/l
peroxy-3,5,5-						
trimethylhexan						
oate						
tert-Butyl	13122-18-4	Rainbow trout	Experimental		LC50	7 mg/l
peroxy-3,5,5-						
trimethylhexan						
oate						
tert-Butyl	13122-18-4	Water flea	Experimental		EC50	>100 mg/l
peroxy-3,5,5-						
trimethylhexan						
oate						
tert-Butyl	13122-18-4	Green Algae	Experimental		NOEC	0.125 mg/l
peroxy-3,5,5-						
trimethylhexan						
oate						
Acetic acid,	6046-93-1	Green Algae	Estimated	72 hours	EC50	0.33 mg/l
copper(2+) salt,						
	•	•	•	•	•	

.....

monohydrate						
Acetic acid, copper(2+) salt, monohydrate	6046-93-1	Water flea	Estimated	48 hours	EC50	0.04 mg/l
Acetic acid, copper(2+) salt, monohydrate	6046-93-1	Zebra Fish	Estimated	96 hours	LC50	0.037 mg/l
Acetic acid, copper(2+) salt, monohydrate	6046-93-1	Fathead minnow	Estimated	32 days	EC10	0.019 mg/l
Acetic acid, copper(2+) salt, monohydrate	6046-93-1	Green Algae	Estimated		NOEC	0.069 mg/l
Acetic acid, copper(2+) salt, monohydrate	6046-93-1	Water flea	Estimated	7 days	NOEC	0.01 mg/l
Acetic acid, copper(2+) salt, monohydrate	6046-93-1	Activated sludge	Estimated		EC50	22 mg/l
Acetic acid, copper(2+) salt, monohydrate	6046-93-1	Barley	Estimated	4 days	NOEC	50 mg/kg (Dry Weight)
Acetic acid, copper(2+) salt, monohydrate	6046-93-1	Bobwhite quail	Estimated	14 days	LD50	4,402 mg per kg of bodyweight
Acetic acid, copper(2+) salt, monohydrate	6046-93-1	Redworm	Estimated	56 days	NOEC	31 mg/kg (Dry Weight)
Acetic acid, copper(2+) salt, monohydrate	6046-93-1	Sediment Worm	Estimated	28 days	NOEC	57.5 mg/kg (Dry Weight)
Acetic acid, copper(2+) salt, monohydrate		Soil microbes	Estimated	4 days	NOEC	38 mg/kg (Dry Weight)
Acetic acid, copper(2+) salt, monohydrate	6046-93-1	Springtail	Estimated	28 days	NOEC	87.7 mg/kg (Dry Weight)

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Glass powder	None	Data not	N/A	N/A	N/A	N/A
(65997-17-3),		available-				
surface		insufficient				
modified with						
2-propenoic						
acid, 2						
methyl3-						
(trimethoxysily						
l)propyl ester						
(2530-85-0)						
and						
phenyltrimetho						
xy silane						
(2996-92-1),						

bulk material						
2-Propenoic acid, 2-methyl-, 1,1'-[1- (hydroxymethy l)-1,2- ethanediyl] ester, reaction products with 2-hydroxy-1,3- propanediyl dimethacrylate and phosphorus oxide	1224866-76-5	Experimental Biodegradation	28 days	BOD	82 % BOD/ThOD	OECD 301F - Manometric respirometry
2,2'- ethylenedioxyd iethyl dimethacrylate	109-16-0	Experimental Biodegradation	28 days	CO2 evolution	85 % weight	OECD 301B - Modified sturm or CO2
2-Propenoic acid, 2-methyl-, 3- (trimetoxysilyl) propyl ester, hydrolysis products with silica	68909-20-6	Data not available- insufficient	N/A	N/A	N/A	N/A
OXIDE GLASS CHEMICALS (non-fibrous)	65997-17-3	Data not available- insufficient	N/A	N/A	N/A	N/A
Sodium Persulphate	7775-27-1	Data not available- insufficient	N/A	N/A	N/A	N/A
tert-Butyl peroxy-3,5,5- trimethylhexan oate	13122-18-4	Estimated Biodegradation	28	BOD	14 % BOD/ThOD	OECD 301C - MITI test (I)
Acetic acid, copper(2+) salt, monohydrate	6046-93-1	Analogous Compound Biodegradation	14 days	BOD	74 % BOD/ThOD	OECD 301C - MITI test (I)

12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Glass powder	None	Data not	N/A	N/A	N/A	N/A
(65997-17-3),		available or				
surface		insufficient for				
modified with		classification				
2-propenoic						
acid, 2						
methyl3-						
(trimethoxysily						
l)propyl ester						
(2530-85-0)						
and						

phenyltrimetho						
xy silane						
(2996-92-1),						
bulk material						
	1224966 76 5	E ' / 1		T 17	0.2	NT 4 1 1 4 1
2-Propenoic	1224866-76-5	Experimental		Log Kow	-0.2	Non-standard method
acid, 2-methyl-,		Bioconcentrati				
1,1'-[1-		on				
(hydroxymethy						
1)-1,2-						
ethanediyl]						
ester, reaction						
products with						
2-hydroxy-1,3-						
propanediyl						
dimethacrylate						
and phosphorus						
oxide						
2,2'-	109-16-0	Experimental		Log Kow	2.3	Non-standard method
ethylenedioxyd		Bioconcentrati				
iethyl		on				
dimethacrylate						
2-Propenoic	68909-20-6	Data not	N/A	N/A	N/A	N/A
acid, 2-methyl-,		available or				
3-		insufficient for				
(trimetoxysilyl)		classification				
propyl ester,						
hydrolysis						
products with						
silica						
OXIDE	65997-17-3	Data not	N/A	N/A	N/A	N/A
GLASS		available or				
CHEMICALS		insufficient for				
(non-fibrous)		classification				
Sodium	7775-27-1	Data not	N/A	N/A	N/A	N/A
Persulphate	.,,,,	available or		- "	- "	
F		insufficient for				
		classification				
tert-Butyl	13122-18-4	Estimated		Bioaccumulatio	363	Estimated:
peroxy-3,5,5-		Bioconcentrati		n factor		Bioconcentration factor
trimethylhexan		on				
oate						
Acetic acid,	6046-93-1	Analogous		Log Kow	-0.17	
copper(2+) salt,		Compound		Log Kow	V.1 /	
monohydrate		Bioconcentrati				
mononyurac		on				
	l	IOII	Ĺ			

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes.

SECTION 14: Transport Information

Australian Dangerous Goods Code (ADG) - Road/Rail Transport

UN No.: UN3077

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., (Tert-Butyl Peroxy-

3,5,5-Trimethylhexanoate, Acetic acid, copper(2+) salt, monohydrate)

Class/Division: 9

Sub Risk: Not applicable. **Packing Group:** III

Special Instructions: Not restricted, environmentally hazardous substance exception.

Hazchem Code: 2Z

IERG: 47

International Air Transport Association (IATA) - Air Transport

UN No.: UN3077

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., (Tert-Butyl Peroxy-

3,5,5-Trimethylhexanoate, Acetic acid, copper(2+) salt, monohydrate)

Class/Division: 9

Sub Risk: Not applicable. **Packing Group:** III

Special Instructions: Not restricted, as per Special Provision A197, environmentally hazardous substance exception.

International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: UN3077

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., (Tert-Butyl Peroxy-

3,5,5-Trimethylhexanoate, Acetic acid, copper(2+) salt, monohydrate)

Class/Division: 9

Sub Risk: Not applicable. **Packing Group:** III

Marine Pollutant: Not applicable.

Special Instructions: Forbidden by this mode of transport

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Australian Inventory Status:

This product is regulated by the Therapeutics Goods Administration and is exempt from compliance with the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

SECTION 16: Other information

Revision information:

Complete document review.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to

3MTM RelyXTM Unicem 2 Automix Base Paste

satisfy themselves as to the suitability of the product for their own intended applications. Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au



Safety Data Sheet

Copyright, 2022, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 28-1333-5
 Version number:
 4.00

 Issue Date:
 10/04/2022
 Supersedes date:
 20/11/2019

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

SECTION 1: Identification

1.1. Product identifier

3M[™] RelyX[™] Unicem[™] 2 Automix Catalyst

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Cement

Restrictions on use

For use by dental professionals only.

1.3. Supplier's details

Address: 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113

Telephone: 136 136

E Mail: productinfo.au@mmm.com

Website: www.3m.com.au

1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 2.

Skin Sensitizer: Category 1.

2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

Signal word

Warning

Symbols

Exclamation mark

Pictograms



Hazard statements

H319 Causes serious eve irritation. May cause an allergic skin reaction. H317

Precautionary statements

Prevention:

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

Contaminated work clothing should not be allowed out of the workplace. P272

Wear protective gloves. P280E

Response:

P302 + P352IF ON SKIN: Wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact P305 + P351 + P338

lenses, if present and easy to do. Continue rinsing.

If skin irritation or rash occurs: Get medical advice/attention. P333 + P313

P337 + P313IF eye irritation persists: Get medical advice/attention. P362 + P364Take off contaminated clothing and wash it before reuse.

Disposal:

P501 Dispose of contents/container in accordance with applicable

local/regional/national/international regulations.

2.3. Other assigned/identified product hazards

None known.

2.4. Other hazards which do not result in classification

May be harmful if swallowed.

Causes mild skin irritation.

Very toxic to aquatic life.

Toxic to aquatic life with long lasting effects.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
Glass powder (65997-17-3), surface	None	50 - 70
modified with 2-propenoic acid, 2		
methyl3-(trimethoxysilyl)propyl ester		
(2530-85-0), bulk material		

(1-Methylethylidene)bis(4, 1-phenyleneoxy-	27689-12-9	10 - 30
3, 1-propanediyl) bismethacrylate		
1,12-dodecane dimethycrylate	72829-09-5	< 5
2,4,6(1H,3H,5H)-Pyrimidinetrione, 5-	945012-02-2	< 5
phenyl-1-(phenylmethyl)-, calcium salt (2:1)		
2-Propenoic acid, 2-methyl-, 3-	68909-20-6	< 5
(trimetoxysilyl)propyl ester, hydrolysis		
products with silica		
[(3-methoxypropyl)imino]di-2,1-ethanediyl	93962-71-1	< 2
bismethacrylate		
Calcium dihydroxide	1305-62-0	< 2
Sodium P-Toluenesulfinate	824-79-3	< 2
Titanium dioxide	13463-67-7	< 0.5

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide.
Carbon dioxide.

Irritant vapours or gases.

Condition

During combustion.
During combustion.
During combustion.

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

Hazchem Code: 2Z

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Do not get in eyes. A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

tor the component.				
Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Calcium dihydroxide	1305-62-0	ACGIH	TWA:5 mg/m3	
Calcium dihydroxide	1305-62-0	Australia OELs	TWA(8 hours):5 mg/m3	
Titanium dioxide	13463-67-7	ACGIH	TWA:10 mg/m ³	A4: Not class. as human
				carcin
Titanium dioxide	13463-67-7	Australia OELs	TWA(Inspirable dust)(8	
			hours):10 mg/m3	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

Australia OELs: Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG: Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid.
Specific Physical Form:	Paste
Colour	Tooth
Odour	Slight Acrylic
Odour threshold	No data available.
рН	Not applicable.
Melting point/Freezing point	No data available.
Boiling point/Initial boiling point/Boiling range	No data available.
Flash point	No flash point
Evaporation rate	No data available.
Flammability (solid, gas)	Not classified
Flammable Limits(LEL)	No data available.
Flammable Limits(UEL)	No data available.
Vapour pressure	No data available.
Vapor Density and/or Relative Vapor Density	No data available.
Density	2 g/cm3 - 2.2 g/cm3
Relative density	2 - 2.2 [<i>Ref Std</i> :WATER=1]
Water solubility	Nil
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Autoignition temperature	No data available.
Decomposition temperature	No data available.
Viscosity/Kinematic Viscosity	No data available.
Volatile organic compounds (VOC)	No data available.
Percent volatile	No data available.
VOC less H2O & exempt solvents	No data available.
Molecular weight	No data available.

Nanoparticles

This material contains nanoparticles.

SECTION 10: Stability and reactivity

3MTM RelyXTM UnicemTM 2 Automix Catalyst

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3. Conditions to avoid

Heat

10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

Substance

Condition

None known.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

This product may have a characteristic odour; however, no adverse health effects are anticipated.

Skin contact

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Additional Health Effects:

Carcinogenicity:

Exposures needed to cause the following health effect(s) are not expected during normal, intended use:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
Glass powder (65997-17-3), surface modified with 2-propenoic acid, 2 methyl3-(trimethoxysilyl)propyl ester (2530-85-0), bulk material	Dermal		LD50 estimated to be > 5,000 mg/kg
Glass powder (65997-17-3), surface modified with 2-propenoic acid, 2 methyl3-(trimethoxysilyl)propyl ester (2530-85-0), bulk material	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
(1-Methylethylidene)bis(4, 1- phenyleneoxy- 3, 1-propanediyl) bismethacrylate	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
(1-Methylethylidene)bis(4, 1- phenyleneoxy- 3, 1-propanediyl) bismethacrylate	Ingestion	Rat	LD50 > 17,600 mg/kg
1,12-dodecane dimethycrylate	Dermal	Professional judgement	LD50 estimated to be 2,000 - 5,000 mg/kg
1,12-dodecane dimethycrylate	Ingestion	similar compounds	LD50 2000-5000 mg/kg
2,4,6(1H,3H,5H)-Pyrimidinetrione, 5-phenyl-1-(phenylmethyl)-, calcium salt (2:1)	Dermal	Professional judgement	LD50 estimated to be 2,000 - 5,000 mg/kg
2,4,6(1H,3H,5H)-Pyrimidinetrione, 5-phenyl-1-(phenylmethyl)-, calcium salt (2:1)	Ingestion	Rat	LD50 > 2,000 mg/kg
2-Propenoic acid, 2-methyl-, 3- (trimetoxysilyl)propyl ester, hydrolysis products with silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
2-Propenoic acid, 2-methyl-, 3- (trimetoxysilyl)propyl ester, hydrolysis products with silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
2-Propenoic acid, 2-methyl-, 3- (trimetoxysilyl)propyl ester, hydrolysis products with silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Sodium P-Toluenesulfinate	Dermal	Professional judgement	LD50 estimated to be 2,000 - 5,000 mg/kg
Calcium dihydroxide	Dermal	Rabbit	LD50 > 2,500 mg/kg
Calcium dihydroxide	Ingestion	Rat	LD50 7,340 mg/kg
Sodium P-Toluenesulfinate	Ingestion	Rat	LD50 3,200 mg/kg
[(3-methoxypropyl)imino]di-2,1- ethanediyl bismethacrylate	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
[(3-methoxypropyl)imino]di-2,1- ethanediyl bismethacrylate	Ingestion	Rat	LD50 > 1,600 mg/kg
Titanium dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg

 $\overline{\text{ATE}} = \text{acute toxicity estimate}$

Skin Corrosion/Irritation

Name	Species	Value

D 7 C 1

3MTM RelyXTM UnicemTM 2 Automix Catalyst

Glass powder (65997-17-3), surface modified with	Professional judgement	No significant irritation
2-propenoic acid, 2 methyl3-		
(trimethoxysilyl)propyl ester (2530-85-0), bulk		
material		
(1-Methylethylidene)bis(4, 1-phenyleneoxy- 3, 1-	Rabbit	No significant irritation
propanediyl) bismethacrylate		
2-Propenoic acid, 2-methyl-, 3-	Rabbit	No significant irritation
(trimetoxysilyl)propyl ester, hydrolysis products		
with silica		
Calcium dihydroxide	Human	Corrosive
Titanium dioxide	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Glass powder (65997-17-3), surface modified with 2-propenoic acid, 2 methyl3-	Professional judgement	No significant irritation
(trimethoxysilyl)propyl ester (2530-85-0), bulk material		
(1-Methylethylidene)bis(4, 1-phenyleneoxy- 3, 1-propanediyl) bismethacrylate	Rabbit	Mild irritant
2-Propenoic acid, 2-methyl-, 3- (trimetoxysilyl)propyl ester, hydrolysis products with silica	Rabbit	No significant irritation
Calcium dihydroxide	Rabbit	Corrosive
Titanium dioxide	Rabbit	No significant irritation

Skin Sensitisation

Name	Species	Value
(1-Methylethylidene)bis(4, 1-phenyleneoxy- 3, 1-propanediyl) bismethacrylate	Guinea pig	Not classified
2,4,6(1H,3H,5H)-Pyrimidinetrione, 5-phenyl-1- (phenylmethyl)-, calcium salt (2:1)	Mouse	Not classified
2-Propenoic acid, 2-methyl-, 3- (trimetoxysilyl)propyl ester, hydrolysis products with silica	Human and animal	Not classified
[(3-methoxypropyl)imino]di-2,1-ethanediyl bismethacrylate	Professional judgement	Sensitising
Titanium dioxide	Human and animal	Not classified

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
(1-Methylethylidene)bis(4, 1-phenyleneoxy- 3, 1-	In Vitro	Not mutagenic
propanediyl) bismethacrylate		
2,4,6(1H,3H,5H)-Pyrimidinetrione, 5-phenyl-1-	In Vitro	Not mutagenic
(phenylmethyl)-, calcium salt (2:1)		
2-Propenoic acid, 2-methyl-, 3-	In Vitro	Not mutagenic
(trimetoxysilyl)propyl ester, hydrolysis products		
with silica		
Titanium dioxide	In Vitro	Not mutagenic
Titanium dioxide	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
2-Propenoic acid, 2-methyl-, 3- (trimetoxysilyl)propyl ester,	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
hydrolysis products with silica			are not sufficient for classification
Titanium dioxide	Ingestion	Multiple animal	Not carcinogenic
		species	
Titanium dioxide	Inhalation	Rat	Carcinogenic.

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
2-Propenoic acid, 2- methyl-, 3- (trimetoxysilyl)propy l ester, hydrolysis products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
2-Propenoic acid, 2- methyl-, 3- (trimetoxysilyl)propy l ester, hydrolysis products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
2-Propenoic acid, 2- methyl-, 3- (trimetoxysilyl)propy l ester, hydrolysis products with silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
2,4,6(1H,3H,5 H)- Pyrimidinetrio ne, 5-phenyl- 1- (phenylmethyl)-, calcium salt (2:1)	Ingestion	nervous system	Not classified	Rat	NOAEL 2,000 mg/kg	
Calcium dihydroxide	Inhalation	respiratory irritation	May cause respiratory irritation	Human	LOAEL 2.5 mg/m³	20 minutes

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
2-Propenoic acid, 2- methyl-, 3- (trimetoxysily l)propyl ester, hydrolysis products with silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Titanium dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for	Rat	LOAEL 0.01 mg/l	2 years

			classification			
Titanium	Inhalation	pulmonary	Not classified	Human	NOAEL Not	occupational
dioxide		fibrosis			available	exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Exposure Levels

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

Interactive Effects

Not determined.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

GHS Acute 1: Very toxic to aquatic life.

Chronic aquatic hazard:

GHS Chronic 2: Toxic to aquatic life with long lasting effects.

No product test data available.

Material	CAS Number	Organism	Туре	Exposure	Test endpoint	Test result
Glass powder	None		Data not			N/A
(65997-17-3),			available or			
surface			insufficient for			
modified with			classification			
2-propenoic						
acid, 2						
methyl3-						
(trimethoxysily						
l)propyl ester						
(2530-85-0),						
bulk material						
(1-	27689-12-9	Green algae	Experimental	72 hours	EC50	>100 mg/l
Methylethylide						
ne)bis(4, 1-						
phenyleneoxy-						
3, 1-						
propanediyl)						
bismethacrylate						
(1-	27689-12-9	Water flea	Experimental	48 hours	EC50	>100 mg/l
Methylethylide						
ne)bis(4, 1-						
phenyleneoxy-						
3, 1-						

propanediyl)						
bismethacrylate						
(1-	27689-12-9	Green algae	Experimental	72 hours	NOEC	>100 mg/l
Methylethylide						
ne)bis(4, 1-						
phenyleneoxy-						
3, 1-						
propanediyl)						
bismethacrylate						
1,12-dodecane	72829-09-5	Green Algae	Experimental	72 hours	EC50	17 ug/l
dimethycrylate	1202) 0) 3	Green raigae	Experimental	72 Hours	Leso	17 48/1
1,12-dodecane	72829-09-5	Water flea	Experimental	48 hours	EC50	>100 mg/l
dimethycrylate	12027-07-3	water fied	Experimental	40 Hours	LC30	- 100 mg/1
1,12-dodecane	72829-09-5	Croon Algor	Evenorimental	72 hours	EC10	6.4 ug/l
/	12829-09-3	Green Algae	Experimental	/2 nours	EC10	0.4 ug/1
dimethycrylate	0.45012.02.2		D			27/4
2,4,6(1H,3H,5	945012-02-2		Data not			N/A
H)-			available or			
Pyrimidinetrion			insufficient for			
e, 5-phenyl-1-			classification			
(phenylmethyl)						
-, calcium salt						
(2:1)						
2-Propenoic	68909-20-6	Algae	Estimated	72 hours	EC50	>100 mg/l
acid, 2-methyl-,						
3-						
(trimetoxysilyl)						
propyl ester,						
hydrolysis						
products with						
silica						
[(3-	93962-71-1		Data not			N/A
methoxypropyl			available or			
)imino]di-2,1-			insufficient for			
ethanediyl			classification			
bismethacrylate						
Calcium	1305-62-0	Fathead	Estimated	96 hours	LC50	4,630 mg/l
dihydroxide	1303 02 0	minnow	Estimated) o nours		1,030 mg/1
Calcium	1305-62-0	Green Algae	Estimated	72 hours	EC50	>4,000 mg/l
dihydroxide	1303-02-0	Green Aigae	Estimated	72 Hours	LC30	4,000 mg/1
Calcium	1205 62 0	Water flee	Estimated	10 haura	EC50	2 400 m c/l
	1305-62-0	Water flea	Estimated	48 hours	EC50	2,400 mg/l
dihydroxide	024.70.2	F (1 1	E .: 1	0.6.1	1.050	> 400
Sodium P-	824-79-3	Fathead	Estimated	96 hours	LC50	>400 mg/l
Toluenesulfinat		minnow				
e g ti p	0.2.4. = 0.5			0.51	15050	
Sodium P-	824-79-3	Green Algae	Estimated	96 hours	EC50	230 mg/l
Toluenesulfinat						
e						
Sodium P-	824-79-3	Water flea	Estimated	48 hours	EC50	>400 mg/l
Toluenesulfinat						
e						
Sodium P-	824-79-3	Green Algae	Estimated	96 hours	NOEC	31 mg/l
Toluenesulfinat						
e						
Titanium	13463-67-7	Activated	Experimental	3 hours	NOEC	>=1,000 mg/l
dioxide		sludge				-,
aloniac	<u> </u>	praage	1	<u> </u>		ı

Titanium	13463-67-7	Diatom	Experimental	72 hours	EC50	>10,000 mg/l
dioxide						
Titanium	13463-67-7	Fathead	Experimental	96 hours	LC50	>100 mg/l
dioxide		minnow				
Titanium	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
dioxide						_
Titanium	13463-67-7	Diatom	Experimental	72 hours	NOEC	5,600 mg/l
dioxide						_

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Glass powder (65997-17-3), surface modified with 2-propenoic acid, 2 methyl3- (trimethoxysily 1)propyl ester (2530-85-0), bulk material	None	Data not available-insufficient	N/A	N/A	N/A	N/A
(1- Methylethylide ne)bis(4, 1- phenyleneoxy- 3, 1- propanediyl) bismethacrylate		Experimental Biodegradation	28 days	CO2 evolution	7-12 % weight	OECD 301B - Modified sturm or CO2
1,12-dodecane dimethycrylate	72829-09-5	Experimental Biodegradation	28 days	CO2 evolution	97.3 %CO2 evolution/THC O2 evolution	OECD 301B - Modified sturm or CO2
2,4,6(1H,3H,5 H)- Pyrimidinetrion e, 5-phenyl-1- (phenylmethyl) -, calcium salt (2:1)	945012-02-2	Data not available- insufficient	N/A	N/A	N/A	N/A
2-Propenoic acid, 2-methyl-, 3- (trimetoxysilyl) propyl ester, hydrolysis products with silica	68909-20-6	Data not available- insufficient	N/A	N/A	N/A	N/A
[(3-methoxypropyl)imino]di-2,1-ethanediylbismethacrylate	93962-71-1	Modeled Biodegradation	28 days	BOD	70 % BOD/ThOD	Catalogic [™]
Calcium dihydroxide	1305-62-0	Data not available-	N/A	N/A	N/A	N/A

		insufficient				
Sodium P- Toluenesulfinat		r	28 days			OECD 301C - MITI
e Totuenesummat		Biodegradation			BOD/ThOD	test (I)
Titanium dioxide	13463-67-7	Data not available-	N/A	N/A	N/A	N/A
		insufficient				

12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Glass powder	None	Data not	N/A	N/A	N/A	N/A
(65997-17-3),		available or				
surface		insufficient for				
modified with		classification				
2-propenoic						
acid, 2						
methyl3-						
(trimethoxysily						
l)propyl ester						
(2530-85-0),						
bulk material						
(1-	27689-12-9	Estimated		Log Kow	7.61	Estimated: Octanol-
Methylethylide		Bioconcentrati				water partition
ne)bis(4, 1-		on				coefficient
phenyleneoxy-						
3, 1-						
propanediyl)						
bismethacrylate						
1,12-dodecane	72829-09-5	Estimated		Bioaccumulatio	6.6	Estimated:
dimethycrylate		Bioconcentrati		n factor		Bioconcentration factor
		on				
7 7 7	945012-02-2	Data not	N/A	N/A	N/A	N/A
H)-		available or				
Pyrimidinetrion		insufficient for				
e, 5-phenyl-1-		classification				
(phenylmethyl)						
-, calcium salt						
(2:1)	(0000 20 (D	27/4	27/4	3.7/4	27/4
2-Propenoic	68909-20-6	Data not	N/A	N/A	N/A	N/A
acid, 2-methyl-, 3-		available or				
		insufficient for classification				
(trimetoxysilyl) propyl ester,		classification				
hydrolysis						
products with						
silica						
[(3-	93962-71-1	Modeled		Bioaccumulatio	3.6	Catalogic TM
methoxypropyl	/J/JU4-/1-1 	Bioconcentrati		n factor	J.0	Catalogic
)imino]di-2,1-		on		ii iactoi		
ethanediyl						
bismethacrylate						
[(3-	93962-71-1	Modeled		Log Kow	1.7	ACD/Labs
methoxypropyl	75702 /1 1	Bioconcentrati		Logitow	1.,	ChemSketch TM
21 12						
)imino]di-2,1-		on				

ethanediyl						
bismethacrylate						
Calcium	1305-62-0	Data not	N/A	N/A	N/A	N/A
dihydroxide		available or				
		insufficient for				
		classification				
Sodium P-	824-79-3	Estimated		Bioaccumulatio	3.9	Estimated:
Toluenesulfinat		Bioconcentrati		n factor		Bioconcentration factor
e		on				
Titanium	13463-67-7	Experimental	42 days	Bioaccumulatio	9.6	Non-standard method
dioxide		BCF - Carp		n factor		

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility.

SECTION 14: Transport Information

Australian Dangerous Goods Code (ADG) - Road/Rail Transport

UN No.: UN3077

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., (1,12-Dodecane

Dimetherylate, 2,6-Di-Tert-Butyl-P-Cresol)

Class/Division: 9

Sub Risk: Not applicable. **Packing Group:** III

Special Instructions: Not restricted, environmentally hazardous substance exception.

Hazchem Code: 2Z

IERG: 47

International Air Transport Association (IATA) - Air Transport

UN No.: UN3077

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., (1,12-Dodecane

Dimethcrylate, 2,6-Di-Tert-Butyl-P-Cresol)

Class/Division: 9

Sub Risk: Not applicable. **Packing Group:** III

Special Instructions: Not restricted, as per Special Provision A197, environmentally hazardous substance exception.

International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: UN3077

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., (1,12-Dodecane

Dimetherylate, 2,6-Di-Tert-Butyl-P-Cresol)

Class/Division: 9

Sub Risk: Not applicable.

3MTM RelyXTM UnicemTM 2 Automix Catalyst

Packing Group: III

Marine Pollutant: Not applicable.

Special Instructions: Forbidden by this mode of transport

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Australian Inventory Status:

This product is regulated by the Therapeutics Goods Administration and is exempt from compliance with the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

SECTION 16: Other information

Revision information:

Complete document review.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au