

Safety Data Sheet

Copyright, 2021, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 23-4208-7
 Version number:
 5.00

 Issue Date:
 02/08/2021
 Supersedes date:
 18/11/2016

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

SECTION 1: Identification

1.1. Product identifier

3M[™] Foam Fast 74NF Cylinder Spray Adhesive, Clear

Product Identification Numbers

62-4998-8010-2 62-4998-8030-0

1.2. Recommended use and restrictions on use

Recommended use

Adhesive. Industrial use.

For Industrial or Professional use only.

1.3. Supplier's details

Address: 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113

Telephone: 136 136

E Mail: productinfo.au@mmm.com

Website: www.3m.com.au

1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

Skin Corrosion/Irritation: Category 2. Serious Eye Damage/Irritation: Category 2.

Carcinogenicity: Category 1B.

Specific Target Organ Toxicity (single exposure): Category 2.

2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

Signal word

Danger

Symbols

Exclamation mark | Health Hazard |

Pictograms





Hazard statements

H315 Causes skin irritation. H319 Causes serious eye irritation.

H350 May cause cancer.

H371 May cause damage to organs: cardiovascular system.

Precautionary statements

Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.

P280F Wear respiratory protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a POISON CENTRE or doctor/physician if you feel unwell.

P332 + P313 If skin irritation occurs: Get medical advice/attention.
P337 + P313 IF eye irritation persists: Get medical advice/attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/container in accordance with applicable

local/regional/national/international regulations.

2.3. Other assigned/identified product hazards

None known.

2.4. Other hazards which do not result in classification

May be harmful if swallowed.

May cause drowsiness or dizziness.

Harmful to aquatic life with long lasting effects.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Weight	
Methylene Chloride	75-09-2	40 - 70	
1,1,1,2-Tetrafluoroethane	811-97-2	7 - 13	
Carbon Dioxide	124-38-9	1 - 8	
Dimethyl Ether	115-10-6	1 - 5	

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. Get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

This product contains methylene chloride which can be metabolized to carbon monoxide. Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance	<u>Condition</u>
Aldehydes.	During combustion.
Hydrocarbons.	During combustion.
Formaldehyde	During combustion.
Methane,	During combustion.
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.

Hydrogen Chloride Hydrogen Fluoride Ketones. Toxic vapour, gas, particulate. During combustion.
During combustion.
During combustion.
During combustion.

5.3. Special protective actions for fire-fighters

When fire fighting conditions are severe and total thermal decomposition of the product is possible, wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, tunic and trousers (leggings), bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

Hazchem Code: 2ZE

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid inhalation of thermal decomposition products. For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store away from heat. Store away from oxidising agents.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Dimethyl Ether	115-10-6	AIHA	TWA:1880 mg/m3(1000 ppm)	
Dimethyl Ether	115-10-6	Australia OELs	TWA(8 hours):760	

			mg/m3(400 ppm);STEL(15 minutes):950 mg/m3(500 ppm)	
Carbon Dioxide	124-38-9	ACGIH	TWA:5000 ppm;STEL:30000	
			ppm	
Carbon Dioxide	124-38-9	Australia OELs	TWA(8 hours): 9000 mg/m3	
			(5000 ppm); STEL(15	
			minutes): 54000 mg/m3	
			(30000 ppm)	
Methylene Chloride	75-09-2	ACGIH	TWA:50 ppm	A3: Confirmed animal
				carcinogen.
Methylene Chloride	75-09-2	Australia OELs	TWA(8 hours): 174 mg/m3	SKIN
			(50 ppm)	
1,1,1,2-Tetrafluoroethane	811-97-2	AIHA	TWA:4240 mg/m ³ (1000 ppm)	
1,1,1,2-Tetrafluoroethane	811-97-2	Australia OELs	TWA(8 hours):4240	
			mg/m3(1000 ppm)	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

Australia OELs: Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG: Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

8.2. Exposure controls

8.2.1. Engineering controls

Provide appropriate local exhaust when product is heated. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Fluoroelastomer Polyvinyl alcohol (PVA).

Select and use gloves according to AS/NZ 2161.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part

of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

During heating: Use a positive pressure supplied-air respirator if there is a potential for over exposure from an uncontrolled release, exposure levels are not known, or under any other circumstances where air-purifying respirators may not provide adequate protection.

Half facepiece or full facepiece supplied-air respirator.

Organic vapour respirators may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer. Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

information on basic physical and chemical properties	
Physical state	Liquid.
Colour	Colourless
Odour	Solvent
Odour threshold	No data available.
pH	Not applicable.
Melting point/Freezing point	Not applicable.
Boiling point/Initial boiling point/Boiling range	<=20 °C
Flash point	No flash point
Evaporation rate	No data available.
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	Not applicable.
Flammable Limits(UEL)	Not applicable.
Vapour pressure	1342409.2 Pa [@ 20 °C] [<i>Details</i> :charge pressure.]
Vapor Density and/or Relative Vapor Density	>=1 [<i>Ref Std</i> :AIR=1]
Density	1.21 g/ml
Relative density	1.21 [<i>Ref Std</i> :WATER=1]
Water solubility	Nil
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Autoignition temperature	No data available.
Decomposition temperature	Not applicable.
Viscosity/Kinematic Viscosity	Not applicable.
Volatile organic compounds (VOC)	
Percent volatile	
VOC less H2O & exempt solvents	<=128 g/l [Test Method:calculated SCAQMD rule 443.1]
Molecular weight	No data available.
Solids content	15 - 30 %

Nanoparticles

This material does not contain nanoparticles.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3. Conditions to avoid

Heat.

10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.5 Incompatible materials

Strong oxidising agents.

10.6 Hazardous decomposition products

Substance

Condition

None known.

Dust created by grinding, sanding, or machining may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. May cause additional health effects (see below).

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness. Single exposure, above recommended guidelines, may cause: Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Medical conditions aggravated by exposure:

Can aggravate pre-existing cardiovascular disease.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000
_			mg/kg
Overall product	Ingestion		No data available; calculated ATE2,000 -
			5,000 mg/kg
Methylene Chloride	Dermal	Rat	LD50 > 2,000 mg/kg
Methylene Chloride	Inhalation-Vapour (4	Rat	LC50 63.7 mg/l
	hours)		
Methylene Chloride	Ingestion	Rat	LD50 1,410 mg/kg
1,1,1,2-Tetrafluoroethane	Inhalation-Gas (4	Rat	LC50 > 359,300 ppm
	hours)		
Carbon Dioxide	Inhalation-Gas (4	Rat	LC50 > 53,000 ppm
	hours)		
Dimethyl Ether	Inhalation-Gas (4	Rat	LC50 164,000 ppm
	hours)		

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Methylene Chloride	Rabbit	Irritant
1,1,1,2-Tetrafluoroethane	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Methylene Chloride	Rabbit	Severe irritant
1,1,1,2-Tetrafluoroethane	Rabbit	No significant irritation

Skin Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Methylene Chloride	In vivo	Not mutagenic
Methylene Chloride	In Vitro	Some positive data exist, but the data are not sufficient for classification
Dimethyl Ether	In Vitro	Not mutagenic
Dimethyl Ether	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Methylene Chloride	Inhalation	Multiple animal	Carcinogenic.
		species	
Dimethyl Ether	Inhalation	Rat	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Methylene Chloride	Inhalation	Not classified for female reproduction	Rat	NOAEL 5.2 mg/l	2 generation
Methylene Chloride	Methylene Chloride Inhalation		Rat	NOAEL 5.2 mg/l	2 generation
Methylene Chloride	Inhalation	Not classified for development	Multiple animal species	NOAEL 4.3 mg/l	during gestation
Carbon Dioxide Inhalation		Not classified for male reproduction	Mouse	LOAEL 350,000 ppm	not available
Carbon Dioxide	Inhalation	Not classified for development	Rat	LOAEL 60,000 ppm	24 hours
Dimethyl Ether	Inhalation	Not classified for development	Rat	NOAEL 40,000 ppm	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Methylene Chloride	Dermal	blood	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	4 hours
Methylene Chloride	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	occupational exposure
Methylene Chloride	Inhalation	blood	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Methylene Chloride	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
1,1,1,2- Tetrafluoroeth ane	Inhalation	cardiac sensitization	May cause damage to organs	Dog	NOAEL 40,000 ppm	5 minutes
Dimethyl Ether	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Rat	LOAEL 10,000 ppm	30 minutes
Dimethyl Ether	Inhalation	cardiac sensitization	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL 100,000 ppm	5 minutes

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Methylene Chloride	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 6.95 mg/l	2 years
Methylene Chloride	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.17 mg/l	2 years
Methylene Chloride	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	LOAEL 35 mg/l	8 weeks
Methylene Chloride	Inhalation	heart	Not classified	Human	NOAEL Not available	
Methylene Chloride	Inhalation	immune system	Not classified	Rat	NOAEL 18 mg/l	28 days
Methylene Chloride	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 1,200 mg/kg/day	3 months
Methylene Chloride	Ingestion	blood	Not classified	Rat	NOAEL 249 mg/kg/day	2 years
Methylene Chloride	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,469 mg/kg/day	3 months
Methylene Chloride	Ingestion	eyes	Not classified	Rat	NOAEL 249 mg/kg/day	104 weeks
Carbon Dioxide	Inhalation	heart bone, teeth, nails, and/or hair liver nervous system kidney and/or bladder respiratory system	Not classified	Rat	LOAEL 60,000 ppm	166 days
Dimethyl Ether	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 25,000 ppm	2 years
Dimethyl Ether	Inhalation	liver	Not classified	Rat	NOAEL 20,000 ppm	30 weeks

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Exposure Levels

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

Interactive Effects

Not determined.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be

reflected in this section because an ingredient—is present below the threshold for labelling, an ingredient—is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

GHS Acute 3: Harmful to aquatic life.

Chronic aquatic hazard:

GHS Chronic 3: Harmful to aquatic life with long lasting effects.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Methylene	75-09-2	Fathead	Experimental	96 hours	LC50	193 mg/l
Chloride		minnow				
Methylene	75-09-2	Green Algae	Experimental	72 hours	EC50	242 mg/l
Chloride						
Methylene	75-09-2	Water flea	Experimental	48 hours	LC50	27 mg/l
Chloride			_			
Methylene	75-09-2	Fathead	Experimental	28 days	NOEC	83 mg/l
Chloride		minnow				
Methylene	75-09-2	Green Algae	Experimental	72 hours	EC10	115 mg/l
Chloride						
Methylene	75-09-2	Activated	Experimental	40 minutes	EC50	2,590 mg/l
Chloride		sludge				
1,1,1,2-	811-97-2	Bacteria	Experimental	6 hours	EC50	>730 mg/l
Tetrafluoroetha						
ne						
1,1,1,2-	811-97-2	Rainbow trout	Experimental	96 hours	LC50	450 mg/l
Tetrafluoroetha						
ne						
1,1,1,2-	811-97-2	Water flea	Experimental	48 hours	EC50	980 mg/l
Tetrafluoroetha						
ne						
Carbon	124-38-9	Fish	Experimental	96 hours	LC50	112.2 mg/l
Dioxide						
Carbon	124-38-9	Atlantic	Experimental	43 days	NOEC	26 mg/l
Dioxide		Salmon				
Dimethyl Ether	115-10-6	Bacteria	Experimental		EC10	>1,600 mg/l
Dimethyl Ether	115-10-6	Guppy	Experimental	96 hours	LC50	>4,100 mg/l
Dimethyl Ether	115-10-6	Water flea	Experimental	48 hours	EC50	>4,400 mg/l

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Methylene	75-09-2	Experimental		Photolytic half-	226 days (t 1/2)	
Chloride		Photolysis		life (in air)		
Methylene	75-09-2	Experimental	28 days	BOD	68 %	OECD 301D - Closed
Chloride		Biodegradation			BOD/ThBOD	bottle test
1,1,1,2-	811-97-2	Experimental		Photolytic half-	17.9 years (t	Non-standard method
Tetrafluoroetha		Photolysis		life (in air)	1/2)	
ne						
1,1,1,2-	811-97-2	Experimental	28 days	BOD	3 %	OECD 301D - Closed

Tetrafluoroetha		Biodegradation			BOD/ThBOD	bottle test
ne						
Carbon	124-38-9	Data not			N/A	
Dioxide		available-				
		insufficient				
Dimethyl Ether	115-10-6	Experimental		Photolytic half-	12.4 days (t	Non-standard method
		Photolysis		life (in air)	1/2)	
Dimethyl Ether	115-10-6	Experimental	28 days	BOD	5 % weight	OECD 301D - Closed
		Biodegradation	-			bottle test

12.3: Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Methylene	75-09-2	Experimental	42 days	Bioaccumulatio	≤40	OECD305-
Chloride		BCF-Carp		n factor		Bioconcentration
Methylene	75-09-2	Experimental		Log Kow	1.25	
Chloride		Bioconcentrati				
		on				
1,1,1,2-	811-97-2	Experimental		Log Kow	1.06	Non-standard method
Tetrafluoroetha		Bioconcentrati				
ne		on				
Carbon	124-38-9	Experimental		Log Kow	0.83	Non-standard method
Dioxide		Bioconcentrati				
		on				
Dimethyl Ether	115-10-6	Data not	N/A	N/A	N/A	N/A
		available or				
		insufficient for				
		classification				

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials.

SECTION 14: Transport Information

Australian Dangerous Goods Code (ADG) - Road/Rail Transport

UN No.: UN3500

Proper shipping name: CHEMICAL UNDER PRESSURE, N.O.S., (1,1,1,2-TETRAFLUOROETHANE, CARBON

DIOXIDE)

Class/Division: 2.2
Sub Risk: Not applicable.
Packing Group: Not applicable.

3M[™] Foam Fast 74NF Cylinder Spray Adhesive, Clear

Hazchem Code: 2ZE

IERG: 08

International Air Transport Association (IATA) - Air Transport

UN No.: UN3500

Proper shipping name: CHEMICAL UNDER PRESSURE, N.O.S., (1,1,1,2-TETRAFLUOROETHANE, CARBON

DIOXIDE)

Class/Division: 2.2 Sub Risk: Not applicable. Packing Group: Not applicable.

Special Instructions: Forbidden by this mode of transport

International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: UN3500

Proper shipping name: CHEMICAL UNDER PRESSURE, N.O.S., (1,1,1,2-TETRAFLUOROETHANE, CARBON

DIOXIDE)

Class/Division: 2.2 Sub Risk: Not applicable. Packing Group: Not applicable. Marine Pollutant: Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Australian Inventory Status:

The chemical components contained within this product are listed on the Australian Inventory of Chemical Substances and are in compliance with the requirements of the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

Poison Schedule: This product is intended for Industrial or Professional Use only and therefore is not packaged and labelled in accordance with the requirements of the Standard for the Uniform Scheduling of Medicines and Poisons.

SECTION 16: Other information

Revision information:

Complete document review.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard @ is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au