



Safety Data Sheet

Copyright, 2022, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|------------------------|------------|-------------------------|------------|
| Document group: | 43-2607-0 | Version number: | 2.00 |
| Issue Date: | 28/11/2022 | Supersedes date: | 21/11/2021 |

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

SECTION 1: Identification

1.1. Product identifier

BATH16 Toothbrush Holder with Swab Alcohol

Product Identification Numbers

XA-0067-1337-5

1.2. Recommended use and restrictions on use

Recommended use

Surface cleaning.

For Consumer Use

1.3. Supplier's details

Address: 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113
Telephone: 136 136
E Mail: productinfo.au@mmm.com
Website: www.3m.com.au

1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

Flammable Liquid: Category 2.

Serious Eye Damage/Irritation: Category 2.

Specific Target Organ Toxicity (single exposure): Category 3

2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for

Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

Signal word

Danger

Symbols

Flame | Exclamation mark |

Pictograms



Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

General:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical, ventilating and lighting equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTRE or doctor/physician if you feel unwell.

P337 + P313 IF eye irritation persists: Get medical advice/attention.

P370 + P378 In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/container in accordance with applicable

local/regional/national/international regulations.

2.3. Other assigned/identified product hazards

Repeated exposure may cause skin dryness or cracking.

2.4. Other hazards which do not result in classification

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

| Ingredient | CAS Nbr | % by Weight |
|-------------------|----------------|--------------------|
| Isopropyl Alcohol | 67-63-0 | > 70 |
| Water | 7732-18-5 | < 30 |

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide.
Carbon dioxide.

Condition

During combustion.
During combustion.

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering

for exposed areas of the head.

Hazchem Code: 1Z

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. **WARNING !** A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire extinguishing foam that is resistant to polar solvents. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapour accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from acids. Store away from oxidising agents.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | CAS Nbr | Agency | Limit type | Additional comments |
|-------------------|---------|----------------|--|--------------------------------|
| Isopropyl Alcohol | 67-63-0 | ACGIH | TWA:200 ppm;STEL:400 ppm | A4: Not class. as human carcin |
| Isopropyl Alcohol | 67-63-0 | Australia OELs | TWA(8 hours):983 mg/m ³ (400 ppm);STEL(15 | |

| | | | | |
|--|--|--|---|--|
| | | | minutes):1230 mg/m ³ (500 ppm) | |
|--|--|--|---|--|

ACGIH : American Conference of Governmental Industrial Hygienists
 AIHA : American Industrial Hygiene Association
 Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment
 CMRG : Chemical Manufacturer's Recommended Guidelines
 TWA: Time-Weighted-Average
 STEL: Short Term Exposure Limit
 CEIL: Ceiling
 Sen: Sensitiser
 Sk: Absorption through the skin may be a significant source of exposure.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Nitrile rubber.

Select and use gloves according to AS/NZ 2161.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours

For questions about suitability for a specific application, consult with your respirator manufacturer.

Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--------------------------------|-----------------|
| Physical state | Liquid. |
| Specific Physical Form: | Liquid for wipe |

| | |
|---|---------------------------------|
| Colour | Colorless |
| Odour | Slight Alcohol |
| Odour threshold | No data available. |
| pH | No data available. |
| Melting point/Freezing point | No data available. |
| Boiling point/Initial boiling point/Boiling range | 82 °C |
| Flash point | 18 °C [Test Method: Closed Cup] |
| Evaporation rate | No data available. |
| Flammability (solid, gas) | Not applicable. |
| Flammable Limits(LEL) | 2 % volume |
| Flammable Limits(UEL) | 12.7 % volume |
| Vapour pressure | 3.1 kPa [@ 20 °C] |
| Vapor Density and/or Relative Vapor Density | No data available. |
| Density | 0.875 g/cm ³ |
| Relative density | 0.875 [Ref Std: WATER=1] |
| Water solubility | Complete |
| Solubility- non-water | No data available. |
| Partition coefficient: n-octanol/water | No data available. |
| Autoignition temperature | No data available. |
| Decomposition temperature | No data available. |
| Viscosity/Kinematic Viscosity | No data available. |
| Volatile organic compounds (VOC) | 612.5 g/l |
| Percent volatile | No data available. |
| VOC less H ₂ O & exempt solvents | No data available. |

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3. Conditions to avoid

Not determined

10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.5 Incompatible materials

Strong acids.

Strong oxidising agents.

Aluminium or magnesium powder and high/shear temperature conditions.

Acid aldehydes, Halogenated materials

10.6 Hazardous decomposition products

Substance

None known.

Condition

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be

reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Dermal Defatting Prolonged or repeated exposure may cause: Dermal Defatting: Signs/symptoms may include localized redness, itching, drying and cracking of skin. Dermal Defatting: Signs/symptoms may include localised redness, itching, drying and cracking of skin.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|-------------------|-----------------------------|---------|--|
| Overall product | Dermal | | No data available; calculated ATE >5,000 mg/kg |
| Overall product | Ingestion | | No data available; calculated ATE >5,000 mg/kg |
| Isopropyl Alcohol | Dermal | Rabbit | LD50 12,870 mg/kg |
| Isopropyl Alcohol | Inhalation-Vapour (4 hours) | Rat | LC50 72.6 mg/l |
| Isopropyl Alcohol | Ingestion | Rat | LD50 4,710 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|-------------------|-------------------------|---------------------------|
| Isopropyl Alcohol | Multiple animal species | No significant irritation |

Serious Eye Damage/Irritation

| Name | Species | Value |
|------|---------|-------|
|------|---------|-------|

BATH16 Toothbrush Holder with Swab Alcohol

| | | |
|-------------------|--------|-----------------|
| Isopropyl Alcohol | Rabbit | Severe irritant |
|-------------------|--------|-----------------|

Skin Sensitisation

| Name | Species | Value |
|-------------------|------------|----------------|
| Isopropyl Alcohol | Guinea pig | Not classified |

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

| Name | Route | Value |
|-------------------|----------|---------------|
| Isopropyl Alcohol | In Vitro | Not mutagenic |
| Isopropyl Alcohol | In vivo | Not mutagenic |

Carcinogenicity

| Name | Route | Species | Value |
|-------------------|------------|---------|--|
| Isopropyl Alcohol | Inhalation | Rat | Some positive data exist, but the data are not sufficient for classification |

Reproductive Toxicity**Reproductive and/or Developmental Effects**

| Name | Route | Value | Species | Test result | Exposure Duration |
|-------------------|------------|--|---------|-----------------------|----------------------|
| Isopropyl Alcohol | Ingestion | Not classified for female reproduction | Rat | NOAEL 1,000 mg/kg/day | 2 generation |
| Isopropyl Alcohol | Ingestion | Not classified for male reproduction | Rat | NOAEL 500 mg/kg/day | 2 generation |
| Isopropyl Alcohol | Ingestion | Not classified for development | Rat | NOAEL 400 mg/kg/day | during organogenesis |
| Isopropyl Alcohol | Inhalation | Not classified for development | Rat | LOAEL 9 mg/l | during gestation |

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|-------------------|------------|-----------------------------------|--|------------|---------------------|------------------------|
| Isopropyl Alcohol | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | |
| Isopropyl Alcohol | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | |
| Isopropyl Alcohol | Inhalation | auditory system | Not classified | Guinea pig | NOAEL 13.4 mg/l | 24 hours |
| Isopropyl Alcohol | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | poisoning and/or abuse |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target | Value | Species | Test result | Exposure |
|------|-------|--------|-------|---------|-------------|----------|
|------|-------|--------|-------|---------|-------------|----------|

| | | Organ(s) | | | | Duration |
|-------------------|------------|-----------------------|----------------|-----|---------------------|-----------|
| Isopropyl Alcohol | Inhalation | kidney and/or bladder | Not classified | Rat | NOAEL 12.3 mg/l | 24 months |
| Isopropyl Alcohol | Inhalation | nervous system | Not classified | Rat | NOAEL 12 mg/l | 13 weeks |
| Isopropyl Alcohol | Ingestion | kidney and/or bladder | Not classified | Rat | NOAEL 400 mg/kg/day | 12 weeks |

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Exposure Levels

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

Interactive Effects

Not determined.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity**Acute aquatic hazard:**

Not acutely toxic to aquatic life by GHS criteria.

Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available.

| Material | CAS Number | Organism | Type | Exposure | Test endpoint | Test result |
|-------------------|------------|--------------|--------------|----------|---------------|--------------|
| Isopropyl Alcohol | 67-63-0 | Bacteria | Experimental | 16 hours | LOEC | 1,050 mg/l |
| Isopropyl Alcohol | 67-63-0 | Green algae | Experimental | 72 hours | EC50 | >1,000 mg/l |
| Isopropyl Alcohol | 67-63-0 | Invertebrate | Experimental | 24 hours | LC50 | >10,000 mg/l |
| Isopropyl Alcohol | 67-63-0 | Medaka | Experimental | 96 hours | LC50 | >100 mg/l |
| Isopropyl Alcohol | 67-63-0 | Water flea | Experimental | 48 hours | EC50 | >1,000 mg/l |
| Isopropyl Alcohol | 67-63-0 | Green algae | Experimental | 72 hours | NOEC | 1,000 mg/l |
| Isopropyl Alcohol | 67-63-0 | Water flea | Experimental | 21 days | NOEC | 100 mg/l |

12.2. Persistence and degradability

| Material | CAS Number | Test type | Duration | Study Type | Test result | Protocol |
|-------------------|------------|-----------------------------|----------|------------|--------------|---------------------------|
| Isopropyl Alcohol | 67-63-0 | Experimental Biodegradation | 14 days | BOD | 86 %BOD/ThOD | OECD 301C - MITI test (I) |

12.3 : Bioaccumulative potential

| Material | CAS Number | Test type | Duration | Study Type | Test result | Protocol |
|-------------------|------------|--------------|----------|------------|-------------|----------|
| Isopropyl Alcohol | 67-63-0 | Experimental | | Log Kow | 0.05 | |

| | | | | | | |
|--|--|------------------|--|--|--|--|
| | | Bioconcentration | | | | |
|--|--|------------------|--|--|--|--|

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Dispose of waste product in a permitted industrial waste facility.

SECTION 14: Transport Information

Australian Dangerous Goods Code (ADG) - Road/Rail Transport

UN No.: UN3175

Proper shipping name: SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. , (Isopropyl Alcohol)

Class/Division: 4.1

Sub Risk: Not applicable.

Packing Group: II

Special Instructions: Australian Dangerous Goods Code: Not subject to this code as per Special Provision 216

Hazchem Code: 1Z

IERG: 20

International Air Transport Association (IATA) - Air Transport

UN No.: UN3175

Proper shipping name: SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. , (Isopropyl Alcohol)

Class/Division: 4.1

Sub Risk: Not applicable.

Packing Group: II

Special Instructions: Not restricted, as per Special Provision A46.

International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: UN3175

Proper shipping name: SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. , (Isopropyl Alcohol)

Class/Division: 4.1

Sub Risk: Not applicable.

Packing Group: II

Marine Pollutant: Not applicable.

Special Instructions: Not restricted, as per Special Provision 216.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Australian Inventory Status:

All components of this product are listed on or exempt from the Australian Inventory of Industrial Chemicals (AIIC). Conditions may apply prior to introduction for direct importers of this product, Please contact 3M Australia on 136 136 for further details.

Poison Schedule: This product is not a scheduled poison according to the criteria of the Standard for the Uniform Scheduling of Medicines and Poisons.

SECTION 16: Other information

Revision information:

Initial issue.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au