



Safety Data Sheet

Copyright, 2017, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	07-1089-7	Version number:	5.00
Issue Date:	07/05/2017	Supersedes date:	12/04/2017

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

SECTION 1: Identification

1.1. Product identifier

3M™ Scotchcast™ Soft Cast Standard Colors

Product Identification Numbers

YP-2060-6013-6

1.2. Recommended use and restrictions on use

Recommended use

Casting tape for orthopedic use, Immobilization of upper and lower extremities

1.3. Supplier's details

Address: 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113
Telephone: 136 136
E Mail: productinfo.au@mmm.com
Website: www.3m.com.au

1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

Respiratory Sensitizer: Category 1.

Skin Sensitizer: Category 1.

Specific Target Organ Toxicity (repeated exposure): Category 2.

2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

Signal word

DANGER!

Symbols

Health Hazard |

Pictograms



Hazard statements

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317 May cause an allergic skin reaction.
H373 May cause damage to organs through prolonged or repeated exposure:
respiratory system |

Precautionary statements

Prevention:

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P285 In case of inadequate ventilation wear respiratory protection.
P280E Wear protective gloves.
P272 Contaminated work clothing should not be allowed out of the workplace.

Response:

P304 + P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTRE or doctor/physician.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
P363 Wash contaminated clothing before reuse.
P321 Specific treatment (see Notes to Physician on this label).
P314 Get medical advice/attention if you feel unwell.

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other assigned/identified product hazards

Persons previously sensitised to isocyanates may develop a cross-sensitisation reaction to other isocyanates.

2.4. Other hazards which do not result in classification

May be harmful if swallowed.
Causes mild skin irritation.

SECTION 3: Composition/information on ingredients

This material is a mixture.

3M™ Scotchcast™ Soft Cast Standard Colors

Ingredient	CAS Nbr	% by Weight
Glass yarn	65997-17-3	40 - 70
4,4'-Methylenediphenyl diisocyanate, oligomeric reaction products with a-hydroxy-hydroxypoly(oxy-1,2-ethanediyl)	9048-57-1	15 - 40
2,2'-Dimorpholinodiethyl ether	6425-39-4	1 - 5
4,4'-Diphenylmethane diisocyanate	26447-40-5	1 - 5
BHT - Butylated hydroxytoluene	128-37-0	0.1 - 1

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products**Substance**

Carbon monoxide.
Carbon dioxide.
Hydrogen cyanide.
Oxides of nitrogen.

Condition

During combustion.
During combustion.
During combustion.
During combustion.

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial or professional use only. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Keep container tightly closed. Store away from heat. Store away from strong bases. Store away from oxidising agents. Store away from amines.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
BHT - Butylated hydroxytoluene	128-37-0	Australia OELs	TWA(8 hours):10 mg/m3	
BHT - Butylated hydroxytoluene	128-37-0	ACGIH	TWA(inhalable fraction and vapour):2 mg/m3	A4: Not class. as human carcin
Free isocyanates	26447-40-5	Manufacturer determined	TWA:0.005 ppm;STEL:0.02 ppm	
Free isocyanates	26447-40-5	Australia OELs	TWA(as NCO)(8 hours):0.02 mg/m3;STEL(as NCO)(15 minutes):0.07 mg/m3	
Glass yarn	65997-17-3	Manufacturer determined	TWA(as dust):10 mg/m3	
Glass filaments	65997-17-3	Australia OELs	TWA(8 hours):0.5 fibers/ml;TWA(as fiber)(8 hours):0.5 fibers/ml	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

Gloves providing sufficient protection must be worn while applying the casting tape. E.g. nitrile gloves with a minimum thickness of 0.127 mm (5 mil, 0.005 inch) have proven to provide effective protection. The cast surface should be free of monomer and polymer isocyanate within 30 minutes when proper wetting techniques are used.

if this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Nitrile

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure: Results from air sampling during simulated product application show that vapours of methylenediphenyl-diisocyanate as used in the product are not detectable during use in Health Care facility cast rooms. Detection limits were extremely low and far below international safety recommendations for working with isocyanates. Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection. People with bronchial problems or with isocyanate sensitivity may still respond to low isocyanate concentrations. In general it is recommended to use synthetic casting material in rooms with normal general/dilution ventilation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid.
Specific Physical Form:	Paste imbedded on knit fibreglass.
Appearance/Odour	Liquid resin impregnated on knit fiberglass; slight odour; colour varies.
Odour threshold	<i>No data available.</i>
pH	<i>Not applicable.</i>
Melting point/Freezing point	<i>No data available.</i>
Boiling point/Initial boiling point/Boiling range	<i>No data available.</i>
Flash point	<i>Not applicable.</i>
Evaporation rate	<i>Not applicable.</i>
Flammability (solid, gas)	Not classified
Flammable Limits(LEL)	<i>Not applicable.</i>
Flammable Limits(UEL)	<i>Not applicable.</i>
Vapour pressure	$\leq 186,158.4 \text{ Pa}$ [$@ 55 \text{ }^\circ\text{C}$]
Vapour density	<i>Not applicable.</i>
Density	1.09 g/ml
Relative density	1.09 [<i>Ref Std: WATER=1</i>]
Water solubility	Nil
Solubility- non-water	<i>No data available.</i>

Partition coefficient: n-octanol/water	No data available.
Autoignition temperature	No data available.
Decomposition temperature	No data available.
Viscosity	30 - 1,000,000 mPa-s [@ 23 °C]
Volatile organic compounds (VOC)	No data available.
Percent volatile	Not applicable.
VOC less H2O & exempt solvents	No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3. Conditions to avoid

Heat.
Sparks and/or flames.

10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.5 Incompatible materials

Strong bases.
Amines.
Alcohols.
Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic respiratory reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest. May cause target organ effects after inhalation. May cause additional health effects (see below).

Skin contact

3M™ Scotchcast™ Soft Cast Standard Colors

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:

Respiratory effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and respiratory failure.

Additional information:

Persons previously sensitised to isocyanates may develop a cross-sensitisation reaction to other isocyanates. Results from air sampling for simulated dry and wet product application show that vapours of methylenediphenyl-diisocyanate as used in the product are not detectable during use. Detection limits were extremely low and far below international safety recommendations for working with isocyanates. People with bronchial problems or with isocyanate sensitivity may still respond to low isocyanate concentrations.

Direct contact with the cast surface without the use of gloves should be avoided until curing has completed. The cast surface should be free of monomer and polymer isocyanate within 30 minutes when proper wetting techniques are used.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE 2,000 - 5,000 mg/kg
Glass yarn	Dermal		LD50 estimated to be > 5,000 mg/kg
Glass yarn	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
4,4'-Methylenediphenyl diisocyanate, oligomeric reaction products with a-hydro-w-hydroxypoly(oxy-1,2-ethanediyl)	Dermal		LD50 estimated to be > 5,000 mg/kg
4,4'-Methylenediphenyl diisocyanate, oligomeric reaction products with a-hydro-w-hydroxypoly(oxy-1,2-ethanediyl)	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
4,4'-Diphenylmethane diisocyanate	Dermal	Rabbit	LD50 > 5,000 mg/kg
4,4'-Diphenylmethane diisocyanate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.368 mg/l
4,4'-Diphenylmethane diisocyanate	Ingestion	Rat	LD50 31,600 mg/kg
2,2'-Dimorpholinodiethyl ether	Dermal	Rabbit	LD50 3,030 mg/kg
2,2'-Dimorpholinodiethyl ether	Ingestion	Rat	LD50 2,020 mg/kg
BHT - Butylated hydroxytoluene	Dermal	Rat	LD50 > 2,000 mg/kg
BHT - Butylated hydroxytoluene	Ingestion	Rat	LD50 > 2,930 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

3M™ Scotchcast™ Soft Cast Standard Colors

Name	Species	Value
Glass yarn	Professional judgement	No significant irritation
4,4'-Diphenylmethane diisocyanate	official classification	Irritant
2,2'-Dimorpholinodiethyl ether	Rabbit	Mild irritant
BHT - Butylated hydroxytoluene	Human and animal	Minimal irritation

Serious Eye Damage/Irritation

Name	Species	Value
Glass yarn	Professional judgement	No significant irritation
4,4'-Diphenylmethane diisocyanate	official classification	Severe irritant
2,2'-Dimorpholinodiethyl ether	Rabbit	Severe irritant
BHT - Butylated hydroxytoluene	Rabbit	Mild irritant

Skin Sensitisation

Name	Species	Value
4,4'-Diphenylmethane diisocyanate	official classification	Sensitising
2,2'-Dimorpholinodiethyl ether	Guinea pig	Not classified
BHT - Butylated hydroxytoluene	Human	Not classified

Respiratory Sensitisation

Name	Species	Value
4,4'-Diphenylmethane diisocyanate	Human	Sensitising

Germ Cell Mutagenicity

Name	Route	Value
Glass yarn	In Vitro	Some positive data exist, but the data are not sufficient for classification
4,4'-Diphenylmethane diisocyanate	In Vitro	Some positive data exist, but the data are not sufficient for classification
2,2'-Dimorpholinodiethyl ether	In Vitro	Not mutagenic
2,2'-Dimorpholinodiethyl ether	In vivo	Not mutagenic
BHT - Butylated hydroxytoluene	In Vitro	Not mutagenic
BHT - Butylated hydroxytoluene	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Glass yarn	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
4,4'-Diphenylmethane diisocyanate	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
BHT - Butylated hydroxytoluene	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
4,4'-Diphenylmethane diisocyanate	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis
2,2'-Dimorpholinodiethyl	Ingestion	Not classified for female reproduction	Rat	NOAEL 300 mg/kg/day	prematuring into lactation

3M™ Scotchcast™ Soft Cast Standard Colors

ether					
2,2'-Dimorpholinodiethyl ether	Ingestion	Not classified for male reproduction	Rat	NOAEL 300 mg/kg/day	28 days
2,2'-Dimorpholinodiethyl ether	Ingestion	Not classified for development	Rat	NOAEL 300 mg/kg/day	prematuring into lactation
BHT - Butylated hydroxytoluene	Ingestion	Not classified for female reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
BHT - Butylated hydroxytoluene	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
BHT - Butylated hydroxytoluene	Ingestion	Not classified for development	Rat	NOAEL 100 mg/kg/day	2 generation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
4,4'-Diphenylmethane diisocyanate	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	
2,2'-Dimorpholino diethyl ether	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Glass yarn	Inhalation	respiratory system	Not classified	Human	NOAEL not available	occupational exposure
4,4'-Diphenylmethane diisocyanate	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
2,2'-Dimorpholino diethyl ether	Ingestion	heart endocrine system hematopoietic system liver immune system nervous system kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 300 mg/kg/day	28 days
BHT - Butylated hydroxytoluene	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 250 mg/kg/day	28 days
BHT - Butylated hydroxytoluene	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 500 mg/kg/day	2 generation
BHT - Butylated hydroxytoluene	Ingestion	blood	Not classified	Rat	LOAEL 420 mg/kg/day	40 days

3M™ Scotchcast™ Soft Cast Standard Colors

e						
BHT - Butylated hydroxytoluen e	Ingestion	endocrine system	Not classified	Rat	NOAEL 25 mg/kg/day	2 generation
BHT - Butylated hydroxytoluen e	Ingestion	heart	Not classified	Mouse	NOAEL 3,480 mg/kg/day	10 weeks

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Exposure Levels

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

Interactive Effects

Not determined.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity**Acute aquatic hazard:**

Not acutely toxic to aquatic life by GHS criteria.

Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
4,4'- Diphenylmetha ne diisocyanate	26447-40-5		Data not available or insufficient for classification			
4,4'- Methylenediph enyl diisocyanate, oligomeric reaction products with a-hydro-w- hydroxypoly(o xy-1,2- ethanediyl)	9048-57-1	Water flea	Estimated	24 hours	EC50	>100 mg/l
4,4'- Methylenediph enyl	9048-57-1	Zebra Fish	Estimated	24 hours	LC50	>100 mg/l

3M™ Scotchcast™ Soft Cast Standard Colors

diisocyanate, oligomeric reaction products with a-hydro-w-hydroxypoly(oxy-1,2-ethanediyl)						
BHT - Butylated hydroxytoluene	128-37-0	Green algae	Experimental	72 hours	NOEC	0.4 mg/l
2,2'-Dimorpholinodiethyl ether	6425-39-4		Data not available or insufficient for classification			
Glass yarn	65997-17-3		Data not available or insufficient for classification			

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
BHT - Butylated hydroxytoluene	128-37-0	Experimental Biodegradation	28 days	BOD	4.5 % weight	OECD 301C - MITI test (I)
4,4'-Diphenylmethane diisocyanate	26447-40-5	Experimental Hydrolysis		Hydrolytic half-life	<2 hours (t 1/2)	Other methods
4,4'-Diphenylmethane diisocyanate	26447-40-5	Experimental Biodegradation	28 days	BOD	0 % weight	OECD 301C - MITI test (I)
2,2'-Dimorpholinodiethyl ether	6425-39-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Glass yarn	65997-17-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
4,4'-Methylenediphenyl diisocyanate, oligomeric reaction products with a-hydro-w-hydroxypoly(oxy-1,2-ethanediyl)	9048-57-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
----------	------------	-----------	----------	------------	-------------	----------

3M™ Scotchcast™ Soft Cast Standard Colors

BHT - Butylated hydroxytoluene	128-37-0	Experimental BCF-Carp	56 days	Bioaccumulation factor	1276	OECD 305E - Bioaccumulation flow-through fish test
4,4'-Diphenylmethane diisocyanate	26447-40-5	Experimental BCF-Carp	28 days	Bioaccumulation factor	200	Other methods
2,2'-Dimorpholinod iethyl ether	6425-39-4	Estimated Bioconcentration		Bioaccumulation factor	2	Other methods
Glass yarn	65997-17-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
4,4'-Methylenediphenyl diisocyanate, oligomeric reaction products with a-hydro-w-hydroxypoly(oxy-1,2-ethanediyl)	9048-57-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate uncured product in a permitted waste incineration facility. Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste.

SECTION 14: Transport Information**Australian Dangerous Goods Code (ADG) - Road/Rail Transport**

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

Special Instructions: Not restricted, environmentally hazardous substance exception.

Hazchem Code: Not applicable

IERG: Not applicable.

International Air Transport Association (IATA) - Air Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

Marine Pollutant: Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Australian Inventory Status:

This product is regulated by the Therapeutics Goods Administration and is exempt from compliance with the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

Poison Schedule: This product has not been assessed for poisons scheduling as the product is intended for industrial and professional use only.

SECTION 16: Other information

Revision information:

No revision information is available.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au