



Safety Data Sheet

Copyright, 2016, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	36-3869-9	Version number:	1.00
Issue Date:	12/12/2016	Supersedes date:	Initial issue.

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

SECTION 1: Identification

1.1. Product identifier

3M™ 8964UV Yellow Piezo InkJet Ink

Product Identification Numbers

75-0302-6690-4

1.2. Recommended use and restrictions on use

Recommended use

Ink, For use with Durst 163TS and 163TS-HS

For Industrial or Professional use only.

1.3. Supplier's details

Address: 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113
Telephone: 136 136
E Mail: productinfo.au@mmm.com
Website: www.3m.com.au

1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

Acute Toxicity (oral): Category 4.
Serious Eye Damage/Irritation: Category 2.
Skin Corrosion/Irritation: Category 2.
Skin Sensitizer: Category 1B.
Reproductive Toxicity: Category 2.
Carcinogenicity: Category 1A.

2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

Signal word

DANGER!

Symbols

Exclamation mark | Health Hazard |

Pictograms



Hazard statements

H302	Harmful if swallowed.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H361	Suspected of damaging fertility or the unborn child.
H350	May cause cancer.

Precautionary statements

Prevention:

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280A	Wear eye/face protection.
P280E	Wear protective gloves.
P281	Use personal protective equipment as required.
P270	Do not eat, drink or smoke when using this product.
P264	Wash thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.

Response:

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P363	Wash contaminated clothing before reuse.
P330	Rinse mouth.
P301 + P312	IF SWALLOWED: Call a POISON CENTRE or doctor/physician if you feel unwell.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P321	Specific treatment (see Notes to Physician on this label).

Storage:

P405	Store locked up.
------	------------------

Disposal:

P501

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other assigned/identified product hazards

None known.

2.4. Other hazards which do not result in classification

Very toxic to aquatic life with long lasting effects.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
Isobornyl acrylate	5888-33-5	10 - 30
Isooctyl acrylate	29590-42-9	10 - 30
Tetrahydrofurfuryl acrylate	2399-48-6	10 - 30
Pigment affinic groups	Trade Secret	10 - 30
1,6-Hexanediol diacrylate	13048-33-4	1 - 10
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	75980-60-8	1 - 10
Benzophenone	119-61-9	1 - 10
Nickel, 5,5'-azobis-2,4,6(1H,3H,5H)-pyrimidinetrione complexes	68511-62-6	1 - 10
High molecular weight block copolymer	Trade Secret	1 - 10
Urethane acrylate oligomer	Trade Secret	1 - 10
Melamine	108-78-1	1 - 5
n,n'-Bis(2,2,6,6-tetramethyl-4-piperidinyl)-1,6-hexanediamine, polymers w/morpholine-2,4,6-trichloro-1,3,5-triazine reaction products, methylated	193098-40-7	1 - 5
Camphene	79-92-5	< 0.2

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

Hazchem Code: •3Z

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial or professional use only. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from oxidising agents.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Melamine	108-78-1	AIHA	TWA(inhalable particulates):10 mg/m ³ ;TWA(respirable particles):5 mg/m ³	
Benzophenone	119-61-9	AIHA	TWA: 0.5 mg/m ³	
1,6-Hexanediol diacrylate	13048-33-4	AIHA	TWA:1 mg/m ³ (0.11 ppm)	Dermal Sensitizer
Tetrahydrofurfuryl acrylate	2399-48-6	Manufacturer determined	TWA:0.1 ppm(0.64 mg/m ³);STEL:0.3 ppm(1.91 mg/m ³)	
Isooctyl acrylate	29590-42-9	Manufacturer determined	TWA:5 ppm	
Isooctyl acrylate	29590-42-9	AIHA	TWA:37.5 mg/m ³ (5 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CELL: Ceiling

Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

if this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Select and use gloves according to AS/NZ 2161.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Liquid.
Appearance/Odour	Acrylate odour, yellow colour, liquid
Odour threshold	<i>No data available.</i>
pH	<i>Not applicable.</i>
Melting point/Freezing point	<i>Not applicable.</i>
Boiling point/Initial boiling point/Boiling range	> 93.3 °C
Flash point	> 93.3 °C [Test Method:Closed Cup]
Evaporation rate	<i>No data available.</i>
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Vapour pressure	< 1,333.2 Pa [@ 20 °C]
Vapour density	> 1 [Ref Std:AIR=1]
Density	1.04 g/ml
Relative density	1.04 [Ref Std:WATER=1]
Water solubility	Negligible
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3. Conditions to avoid

Light.

10.4. Possibility of hazardous reactions

Hazardous polymerisation may occur. (Upon depletion of inhibitor or exposure to heat)

10.5 Incompatible materials

Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching. May cause additional health effects (see below).

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

Harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:

Kidney/Bladder effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine, increased blood urea nitrogen (BUN), blood in urine, and painful urination. Dermal effects:

Signs/symptoms may include redness, itching, acne, or bumps on the skin.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE300 - 2,000 mg/kg
Tetrahydrofurfuryl acrylate	Ingestion	Rat	LD50 551 mg/kg
Isooctyl acrylate	Dermal	Rabbit	LD50 > 2,000 mg/kg
Isooctyl acrylate	Ingestion	Rat	LD50 > 5,000 mg/kg
Isobornyl acrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
Isobornyl acrylate	Ingestion	Rat	LD50 4,350 mg/kg
1,6-Hexanediol diacrylate	Dermal	Rabbit	LD50 3,636 mg/kg
1,6-Hexanediol diacrylate	Ingestion	Rat	LD50 > 5,000 mg/kg
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
Benzophenone	Dermal	Rabbit	LD50 3,535 mg/kg
Benzophenone	Ingestion	Rat	LD50 1,900 mg/kg
Nickel, 5,5'-azobis-2,4,6(1H,3H,5H)-pyrimidinetrione complexes	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Nickel, 5,5'-azobis-2,4,6(1H,3H,5H)-pyrimidinetrione complexes	Ingestion	Rat	LD50 5,000 mg/kg
Melamine	Dermal	Rabbit	LD50 > 1,000 mg/kg
Melamine	Ingestion	Rat	LD50 3,161 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Tetrahydrofurfuryl acrylate	Rabbit	Irritant
Isooctyl acrylate	In vitro data	No significant irritation
Isobornyl acrylate	Rabbit	Minimal irritation
1,6-Hexanediol diacrylate	Rabbit	Irritant
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	Rabbit	No significant irritation
Benzophenone	Rabbit	No significant irritation
Nickel, 5,5'-azobis-2,4,6(1H,3H,5H)-pyrimidinetrione complexes	Rabbit	No significant irritation
Melamine	Guinea pig	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Tetrahydrofurfuryl acrylate	Rabbit	Severe irritant
Isooctyl acrylate	similar health hazards	Mild irritant
Isobornyl acrylate	Rabbit	Mild irritant
1,6-Hexanediol diacrylate	Rabbit	Moderate irritant
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	Rabbit	No significant irritation
Benzophenone	Rabbit	Mild irritant
Nickel, 5,5'-azobis-2,4,6(1H,3H,5H)-pyrimidinetrione complexes	Rabbit	No significant irritation
Melamine	Rabbit	No significant irritation
Camphene	Rabbit	Moderate irritant

Skin Sensitisation

Name	Species	Value
Tetrahydrofurfuryl acrylate	Human and animal	Some positive data exist, but the data are not sufficient for classification
Isooctyl acrylate	Mouse	Sensitising
Isobornyl acrylate	Mouse	Sensitising
1,6-Hexanediol diacrylate	Guinea pig	Sensitising
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	Mouse	Sensitising
Benzophenone	Guinea pig	Not sensitizing
Nickel, 5,5'-azobis-2,4,6(1H,3H,5H)-pyrimidinetrione complexes	similar compounds	Sensitising
Melamine	Guinea pig	Not sensitizing

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Tetrahydrofurfuryl acrylate	In Vitro	Not mutagenic
Isooctyl acrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Isobornyl acrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
1,6-Hexanediol diacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	In Vitro	Not mutagenic
Benzophenone	In Vitro	Not mutagenic
Benzophenone	In vivo	Not mutagenic
Melamine	In Vitro	Not mutagenic
Melamine	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Isooctyl acrylate	Dermal	Mouse	Not carcinogenic
1,6-Hexanediol diacrylate	Dermal	Mouse	Not carcinogenic
Benzophenone	Dermal	Multiple animal species	Not carcinogenic
Benzophenone	Ingestion	Multiple animal species	Carcinogenic.
Nickel, 5,5'-azobis-2,4,6(1H,3H,5H)-pyrimidinetrione complexes	Not specified.	similar compounds	Carcinogenic.
Melamine	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Isooctyl acrylate	Dermal	Not toxic to female reproduction	Rat	NOAEL 57 mg/kg/day	prematuring & during gestation
Isooctyl acrylate	Dermal	Not toxic to male reproduction	Rat	NOAEL 57 mg/kg/day	prematuring & during gestation
Isooctyl acrylate	Dermal	Not toxic to development	Rat	NOAEL 57 mg/kg/day	prematuring & during gestation
Isooctyl acrylate	Ingestion	Some positive	Rat	NOAEL	during

		developmental data exist, but the data are not sufficient for classification		1,000 mg/kg/day	organogenesis
1,6-Hexanediol diacrylate	Not specified.	Not toxic to development	Rat	NOAEL 750 mg/kg/day	during organogenesis
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	Ingestion	Toxic to male reproduction	Rat	NOAEL 100 mg/kg/day	90 days
Benzophenone	Ingestion	Not toxic to female reproduction	Rat	NOAEL 100 mg/kg/day	2 generation
Benzophenone	Ingestion	Not toxic to male reproduction	Rat	NOAEL 80 mg/kg/day	2 generation
Benzophenone	Ingestion	Some positive developmental data exist, but the data are not sufficient for classification	Rabbit	NOAEL 25 mg/kg/day	during gestation
Melamine	Ingestion	Not toxic to development	Rat	NOAEL 1,060 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Tetrahydrofurfuryl acrylate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Isooctyl acrylate	Inhalation	respiratory irritation	All data are negative	Human	NOAEL Not available	occupational exposure
Isooctyl acrylate	Ingestion	central nervous system depression	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 5,000 mg/kg	
Isobornyl acrylate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	official classification	NOAEL Not available	
1,6-Hexanediol diacrylate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Isooctyl acrylate	Dermal	heart endocrine system hematopoietic system liver immune system nervous system kidney and/or	All data are negative	Rat	NOAEL 57 mg/kg/day	prematuring & during gestation

3M™ 8964UV Yellow Piezo InkJet Ink

		bladder respiratory system				
Isooctyl acrylate	Ingestion	endocrine system liver kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 600 mg/kg/day	90 days
Isooctyl acrylate	Ingestion	heart bone, teeth, nails, and/or hair hematopoietic system immune system muscles nervous system eyes respiratory system vascular system	All data are negative	Rat	NOAEL 600 mg/kg/day	90 days
1,6-Hexanediol diacrylate	Dermal	skin	May cause damage to organs though prolonged or repeated exposure	Mouse	LOAEL 70 mg/kg/day	80 weeks
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	Ingestion	skin blood liver kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,000 mg/kg/day	90 days
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	Ingestion	nervous system	All data are negative	Rat	NOAEL 1,000 mg/kg/day	90 days
Benzophenone	Ingestion	kidney and/or bladder	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 75 mg/kg/day	14 weeks
Benzophenone	Ingestion	heart hematopoietic system liver immune system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 850 mg/kg/day	14 weeks
Benzophenone	Ingestion	endocrine system bone, teeth, nails, and/or hair nervous system eyes respiratory system	All data are negative	Rat	NOAEL 850 mg/kg/day	14 weeks
Melamine	Ingestion	kidney and/or bladder	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 63 mg/kg/day	13 weeks

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Exposure Levels

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

Interactive Effects

Not determined.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity**Acute aquatic hazard:**

GHS Acute 1: Very toxic to aquatic life.

Chronic aquatic hazard:

GHS Chronic 1: Very toxic to aquatic life with long lasting effects.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Tetrahydrofurfuryl acrylate	2399-48-6		Data not available or insufficient for classification			
n,n'-Bis(2,2,6,6-tetramethyl-4-piperidiny)-1,6-hexanediamine, polymers w/morpholine-2,4,6-trichloro-1,3,5-triazine reaction products, methylated	193098-40-7		Data not available or insufficient for classification			
1,6-Hexanediol diacrylate	13048-33-4	Water flea	Experimental	48 hours	EC50	2.7 mg/l
1,6-Hexanediol diacrylate	13048-33-4	Green algae	Experimental	72 hours	EC50	1.6 mg/l
1,6-Hexanediol diacrylate	13048-33-4	Ricefish	Experimental	96 hours	LC50	0.38 mg/l
1,6-Hexanediol diacrylate	13048-33-4	Green algae	Experimental	72 hours	NOEC	0.27 mg/l
1,6-Hexanediol diacrylate	13048-33-4	Water flea	Experimental	21 days	NOEC	0.14 mg/l
1,6-Hexanediol diacrylate	13048-33-4	Golden Orfe	Experimental	96 hours	LC50	4.6 mg/l

3M™ 8964UV Yellow Piezo InkJet Ink

1,6-Hexanediol diacrylate	13048-33-4	Green algae	Experimental	72 hours	EC50	1.5 mg/l
1,6-Hexanediol diacrylate	13048-33-4	Green algae	Experimental	72 hours	Effect Concentration 10%	0.585 mg/l
Isooctyl acrylate	29590-42-9	Fathead minnow	Experimental	96 hours	LC50	0.67 mg/l
Isooctyl acrylate	29590-42-9	Water flea	Experimental	48 hours	EC50	0.4 mg/l
Isooctyl acrylate	29590-42-9	Green algae	Estimated	72 hours	EC50	0.535 mg/l
Isooctyl acrylate	29590-42-9	Water flea	Experimental	21 days	NOEC	0.065 mg/l
Isooctyl acrylate	29590-42-9	Green algae	Estimated	72 hours	EC50	0.535 mg/l
Benzophenone	119-61-9	Fathead minnow	Experimental	96 hours	LC50	10.89 mg/l
Benzophenone	119-61-9	Green Algae	Experimental	72 hours	EC50	3.5 mg/l
Benzophenone	119-61-9	Water flea	Experimental	21 days	NOEC	0.2 mg/l
Benzophenone	119-61-9	Green Algae	Experimental	72 hours	NOEC	1 mg/l
Benzophenone	119-61-9	Water flea	Experimental	48 hours	EC50	6.8 mg/l
Benzophenone	119-61-9	Green Algae	Experimental	72 hours	EC50	3.5 mg/l
Benzophenone	119-61-9	Fathead minnow	Experimental	7 days	NOEC	2.1 mg/l
Benzophenone	119-61-9	Green Algae	Experimental	72 hours	NOEC	1 mg/l
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	75980-60-8		Data not available or insufficient for classification			
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	75980-60-8	Ricefish	Experimental	48 hours	LC50	6.53 mg/l
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	75980-60-8	Water flea	Experimental	48 hours	EC50	3.53 mg/l
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	75980-60-8	Algae other	Experimental	72 hours	Effect Concentration 10%	1.56 mg/l
Nickel, 5,5'-azobis-2,4,6(1H,3H,5H)-pyrimidinetrione complexes	68511-62-6	Green algae	Experimental	96 hours	EC50	0.017 mg/l
Nickel, 5,5'-azobis-2,4,6(1H,3H,5	68511-62-6	Water flea	Experimental	21 days	EC50	0.25 mg/l

H)-pyrimidinetrione complexes						
Nickel, 5,5'-azobis-2,4,6(1H,3H,5H)-pyrimidinetrione complexes	68511-62-6	Common Carp	Experimental	96 hours	LC50	3.4 mg/l
Nickel, 5,5'-azobis-2,4,6(1H,3H,5H)-pyrimidinetrione complexes	68511-62-6	Water flea	Experimental	48 hours	EC50	0.034 mg/l
Melamine	108-78-1	Water flea	Experimental	21 days	NOEC	18 mg/l
Melamine	108-78-1	Algae	Experimental	96 hours	NOEC	>320 mg/l
Melamine	108-78-1	Water flea	Experimental	48 hours	EC50	48 mg/l
Melamine	108-78-1	Flagfish	Experimental	35 days	NOEC	>1,000 mg/l
Melamine	108-78-1	Guppy	Experimental	96 hours	LC50	>3,000 mg/l
Melamine	108-78-1	Algae	Experimental	96 hours	EC50	940 mg/l
Isobornyl acrylate	5888-33-5	Fathead minnow	Estimated	96 hours	LC50	1.598 mg/l
Isobornyl acrylate	5888-33-5	Water flea	Experimental	48 hours	EC50	1 mg/l
Isobornyl acrylate	5888-33-5	Green algae	Experimental	72 hours	EC50	1.98 mg/l
Isobornyl acrylate	5888-33-5	Water flea	Experimental	21 days	NOEC	0.092 mg/l
Isobornyl acrylate	5888-33-5	Green Algae	Experimental	72 hours	NOEC	0.405 mg/l
Isobornyl acrylate	5888-33-5	Zebra Fish	Experimental	96 hours	LC50	0.704 mg/l
Camphene	79-92-5	Water flea	Experimental	48 hours	LC50	22 mg/l
Camphene	79-92-5	Zebra Fish	Experimental	96 hours	LC50	0.72 mg/l
Camphene	79-92-5	Sheepshead Minnow	Experimental	96 hours	LC50	1.9 mg/l

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Isobornyl acrylate	5888-33-5	Estimated Photolysis		Photolytic half-life (in air)	1.45 days (t _{1/2})	Other methods
Tetrahydrofurfuryl acrylate	2399-48-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
n,n'-Bis(2,2,6,6-tetramethyl-4-piperidiny)-1,6-hexanediamine, polymers	193098-40-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

3M™ 8964UV Yellow Piezo InkJet Ink

w/morpholine-2,4,6-trichloro-1,3,5-triazine reaction products, methylated						
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	75980-60-8	Estimated Biodegradation	28 days	BOD	<20 % weight	OECD 301F - Manometric respirometry
1,6-Hexanediol diacrylate	13048-33-4	Estimated Biodegradation	28 days	BOD	84 % weight	OECD 301F - Manometric respirometry
Isobornyl acrylate	5888-33-5	Experimental Biodegradation	28 days	BOD	73 % weight	OECD 301D - Closed bottle test
Benzophenone	119-61-9	Experimental Biodegradation	14 days	BOD	0 % weight	OECD 301C - MITI test (I)
1,6-Hexanediol diacrylate	13048-33-4	Weight of Evidence Biodegradation	28 days	BOD	60 % weight	Other methods
Isooctyl acrylate	29590-42-9	Estimated Photolysis		Photolytic half-life (in air)	1.45-1.78 days (t 1/2)	Other methods
Isooctyl acrylate	29590-42-9	Experimental Biodegradation	28 days	BOD	93 % weight	OECD 301D - Closed bottle test
Camphene	79-92-5	Experimental Biodegradation	28 days	BOD	1-4 % weight	OECD 301C - MITI test (I)
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	75980-60-8	Experimental Biodegradation	28 days	BOD	<20 % weight	OECD 301F - Manometric respirometry
Tetrahydrofurfuryl acrylate	2399-48-6	Estimated Biodegradation	28 days	BOD	75 % weight	OECD 301C - MITI test (I)
Melamine	108-78-1	Experimental Biodegradation	14 days	BOD	0 % weight	OECD 301C - MITI test (I)
Isobornyl acrylate	5888-33-5	Experimental Biodegradation	28 days	CO2 evolution	57 % weight	OECD 310 CO2 Headspace
1,6-Hexanediol diacrylate	13048-33-4	Experimental Biodegradation	28 days	CO2 evolution	60-70 % weight	OECD 310 CO2 Headspace
Benzophenone	119-61-9	Experimental Biodegradation	28 days	BOD	66-84 % weight	OECD 301F - Manometric respirometry
Nickel, 5,5'-azobis-2,4,6(1H,3H,5H)-pyrimidinetrione complexes	68511-62-6	Estimated Biodegradation	28 days	BOD	29 % weight	OECD 301C - MITI test (I)

12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
n,n'-Bis(2,2,6,6-	193098-40-7	Data not available or	N/A	N/A	N/A	N/A

tetramethyl-4-piperidiny)-1,6-hexanediamine, polymers w/morpholine-2,4,6-trichloro-1,3,5-triazine reaction products, methylated		insufficient for classification				
Tetrahydrofurfuryl acrylate	2399-48-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	75980-60-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
1,6-Hexanediol diacrylate	13048-33-4	Estimated Bioconcentration		Bioaccumulation factor	42	Estimated: Bioconcentration factor
Benzophenone	119-61-9	Experimental BCF-Carp	42 days	Bioaccumulation factor	12	OECD 305E - Bioaccumulation flow-through fish test
Isobornyl acrylate	5888-33-5	Experimental Bioconcentration		Log Kow	2.4	Other methods
Isooctyl acrylate	29590-42-9	Estimated Bioconcentration		Bioaccumulation factor	120-940	Other methods
Camphene	79-92-5	Experimental BCF-Carp	56 days	Bioaccumulation factor	606-1290	OECD 305C-Bioaccum degree fish
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	75980-60-8	Experimental BCF-Carp	56 days	Bioaccumulation factor	<55	Other methods
Tetrahydrofurfuryl acrylate	2399-48-6	Estimated Bioconcentration		Bioaccumulation factor	7.4	Estimated: Bioconcentration factor
Isobornyl acrylate	5888-33-5	Estimated Bioconcentration		Bioaccumulation factor	660	Estimated: Bioconcentration factor
1,6-Hexanediol diacrylate	13048-33-4	Experimental Bioconcentration		Log Kow	2.81	Other methods
Nickel, 5,5'-azobis-2,4,6(1H,3H,5H)-pyrimidinetrione complexes	68511-62-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Benzophenone	119-61-9	Experimental	56 days	Bioaccumulation	<12	Other methods

3M™ 8964UV Yellow Piezo InkJet Ink

		BCF - Other		n factor		
Melamine	108-78-1	Experimental BCF-Carp	42 days	Bioaccumulation factor	<3.8	OECD 305E - Bioaccumulation flow-through fish test
Isobornyl acrylate	5888-33-5	Estimated BCF - Other	56 hours	Bioaccumulation factor	37	OECD 305E - Bioaccumulation flow-through fish test

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes.

SECTION 14: Transport Information**Australian Dangerous Goods Code (ADG) - Road/Rail Transport**

UN No.: UN3082

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Class/Division: 9

Sub Risk: Not applicable.

Packing Group: III

Special Instructions: Australian Dangerous Goods Code: Not subject to this code as per Special Provision AU01

Hazchem Code: •3Z

IERG: 47

International Air Transport Association (IATA) - Air Transport

UN No.: UN3082

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Class/Division: 9

Sub Risk: Not applicable.

Packing Group: III

Special Instructions: Not restricted, as per Special Provision A197, Environmentally Hazardous Substance Exception.

International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: UN3082

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Class/Division: 9

Sub Risk: Not applicable.

Packing Group: III

Marine Pollutant: Not applicable.

Special Instructions: Not restricted, as per IMDG code 2.10.2.7, marine pollutant exception.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Australian Inventory Status:

An ingredient(s) in this product is being introduced under a Certificate (Standard/Limited/Polymer of Low Concern) granted under Section 39 of the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

Poison Schedule: This product is intended for Industrial or Professional Use only and therefore is not packaged and labelled in accordance with the requirements of the Standard for the Uniform Scheduling of Medicines and Poisons.

SECTION 16: Other information

Revision information:

Initial issue.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au