



Safety Data Sheet

Copyright,2021, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	36-3861-6	Version number:	2.00
Issue Date:	08/08/2021	Supersedes date:	12/12/2016

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

SECTION 1: Identification

1.1. Product identifier

3M™ 8966UV Cyan Piezo InkJet Ink

Product Identification Numbers

75-0302-6688-8

1.2. Recommended use and restrictions on use

Recommended use

Ink, For use with Durst 163TS and 163TS-HS, Professional printing ink for use in traffic safety systems.

For Industrial or Professional use only.

1.3. Supplier's details

Address: 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113
Telephone: 136 136
E Mail: productinfo.au@mmm.com
Website: www.3m.com.au

1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

Skin Corrosion/Irritation: Category 2.
Serious Eye Damage/Irritation: Category 1.
Skin Sensitizer: Category 1.
Carcinogenicity: Category 2.
Reproductive Toxicity: Category 1.

2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

Signal word

Danger

Symbols

Corrosion | Exclamation mark | Health Hazard |

Pictograms



Hazard statements

H315	Causes skin irritation.
H318	Causes serious eye damage.
H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer.
H360	May damage fertility or the unborn child.

Precautionary statements

Prevention:

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280F	Wear respiratory protection.

Response:

P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTRE or doctor/physician.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.

Storage:

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.

Disposal:

P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.
------	--

2.3. Other assigned/identified product hazards

- May cause chemical gastrointestinal burns.

2.4. Other hazards which do not result in classification

May be harmful if swallowed.

May cause respiratory irritation.

Very toxic to aquatic life.

Toxic to aquatic life with long lasting effects.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
Isobornyl acrylate	5888-33-5	10 - 30
Isooctyl acrylate	29590-42-9	10 - 30
Tetrahydrofurfuryl acrylate	22399-48-6	15 - 25
2-Propenoic acid, 1,6-hexanediyl ester, polymer with 2-aminoethanol	67906-98-3	7 - 13
2-Propenoic acid, 2-hydroxyethyl ester, polymer with 5-isocyanato-1-(isocyanatomethyl)-1,3,3-trimethylcyclohexane, 2-oxepanone and 2,2'-oxybis[ethanol]	72162-39-1	7 - 13
1,6-Hexanediol diacrylate	13048-33-4	1 - 10
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	75980-60-8	1 - 10
Benzophenone	119-61-9	1 - 10
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper	147-14-8	1 - 5
Acrylic acid	79-10-7	< 0.2
Camphene	79-92-5	< 0.2
Toluene	108-88-3	< 0.2

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If swallowed

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Irritating to the respiratory tract (coughing, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain). Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide.
Carbon dioxide.

Condition

During combustion.
During combustion.

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

Hazchem Code: •3Z

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store away from oxidising agents.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Toluene	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human carcinogen, Ototoxicant
Toluene	108-88-3	Australia OELs	TWA(8 hours):191 mg/m ³ (50 ppm);STEL(15 minutes):574 mg/m ³ (150 ppm)	SKIN
Benzophenone	119-61-9	AIHA	TWA: 0.5 mg/m ³	
1,6-Hexanediol diacrylate	13048-33-4	AIHA	TWA:1 mg/m ³ (0.11 ppm)	Dermal Sensitizer
COPPER COMPOUNDS	147-14-8	ACGIH	TWA(as Cu, fume):0.2 mg/m ³ ;TWA(as Cu dust or mist):1 mg/m ³	
Tetrahydrofurfuryl acrylate	22399-48-6	Manufacturer determined	TWA:0.1 ppm(0.64 mg/m ³);STEL:0.3 ppm(1.91 mg/m ³)	Dermal Sensitizer
Isooctyl acrylate	29590-42-9	AIHA	TWA:37.5 mg/m ³ (5 ppm)	
Acrylic acid	79-10-7	ACGIH	TWA:2 ppm	A4: Not classified as human carcinogen, Danger of cutaneous absorption
Acrylic acid	79-10-7	Australia OELs	TWA(8 hours):5.9 mg/m ³ (2 ppm)	SKIN

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

if this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Select and use gloves according to AS/NZ 2161.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates, including oily mists

For questions about suitability for a specific application, consult with your respirator manufacturer.

Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state	Liquid.
Specific Physical Form:	Liquid.
Colour	Cyan
Odour	Acrylate
Odour threshold	<i>No data available.</i>
pH	<i>Not applicable.</i>
Melting point/Freezing point	<i>Not applicable.</i>
Boiling point/Initial boiling point/Boiling range	> 93.3 °C
Flash point	> 93.3 °C [Test Method: Closed Cup]
Evaporation rate	<i>No data available.</i>
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Vapour pressure	< 1,333.2 Pa [@ 20 °C]
Vapor Density and/or Relative Vapor Density	> 1 [Ref Std: AIR=1]
Density	1.04 g/ml
Relative density	1.04 [Ref Std: WATER=1]
Water solubility	Negligible
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
Viscosity/Kinematic Viscosity	<i>No data available.</i>
Volatile organic compounds (VOC)	<i>No data available.</i>

Percent volatile	No data available.
VOC less H2O & exempt solvents	No data available.

Nanoparticles

This material does not contain nanoparticles.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3. Conditions to avoid

Light.

10.4. Possibility of hazardous reactions

Hazardous polymerisation may occur. (Upon depletion of inhibitor or exposure to heat)

10.5 Incompatible materials

Strong oxidising agents.

10.6 Hazardous decomposition products**Substance****Condition**

None known.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects**Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching. May cause additional health effects (see below).

Eye contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion

May be harmful if swallowed.

Gastrointestinal corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain, nausea, vomiting, and diarrhea; blood in the faeces and/or vomitus may also be seen. May cause additional health effects (see below).

Additional Health Effects:**Prolonged or repeated exposure may cause target organ effects:**

Kidney/Bladder effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine, increased blood urea nitrogen (BUN), blood in urine, and painful urination. Dermal effects: Signs/symptoms may include redness, itching, acne, or bumps on the skin.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE 2,000 - 5,000 mg/kg
Isobornyl acrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
Isobornyl acrylate	Ingestion	Rat	LD50 4,350 mg/kg
Isooctyl acrylate	Dermal	Rabbit	LD50 > 2,000 mg/kg
Isooctyl acrylate	Ingestion	Rat	LD50 > 5,000 mg/kg
Tetrahydrofurfuryl acrylate	Ingestion	Rat	LD50 882 mg/kg
1,6-Hexanediol diacrylate	Dermal	Rabbit	LD50 3,636 mg/kg
1,6-Hexanediol diacrylate	Ingestion	Rat	LD50 > 5,000 mg/kg
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
Benzophenone	Dermal	Rabbit	LD50 3,535 mg/kg
Benzophenone	Ingestion	Rat	LD50 1,900 mg/kg
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper	Dermal		LD50 estimated to be > 5,000 mg/kg
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper	Ingestion	Rat	LD50 10,000 mg/kg
Toluene	Dermal	Rat	LD50 12,000 mg/kg
Toluene	Inhalation-Vapour (4 hours)	Rat	LC50 30 mg/l
Toluene	Ingestion	Rat	LD50 5,550 mg/kg
Acrylic acid	Dermal	Rabbit	LD50 > 2,000 mg/kg
Acrylic acid	Inhalation-Dust/Mist (4 hours)	Rat	LC50 3.8 mg/l
Acrylic acid	Ingestion	Rat	LD50 1,250 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
------	---------	-------

Overall product	Professional judgement	Irritant
Isobornyl acrylate	Rabbit	Minimal irritation
Isooctyl acrylate	In vitro data	No significant irritation
Tetrahydrofurfuryl acrylate	Rabbit	Corrosive
2-Propenoic acid, 1,6-hexanediyl ester, polymer with 2-aminoethanol	similar compounds	Irritant
2-Propenoic acid, 2-hydroxyethyl ester, polymer with 5-isocyanato-1-(isocyanatomethyl)-1,3,3-trimethylcyclohexane, 2-oxepanone and 2,2'-oxybis[ethanol]	similar compounds	Irritant
1,6-Hexanediol diacrylate	Rabbit	Irritant
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	Rabbit	No significant irritation
Benzophenone	Rabbit	No significant irritation
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper	Rabbit	No significant irritation
Toluene	Rabbit	Irritant
Acrylic acid	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
Isobornyl acrylate	Rabbit	Mild irritant
Isooctyl acrylate	similar health hazards	Mild irritant
Tetrahydrofurfuryl acrylate	Rabbit	Corrosive
2-Propenoic acid, 1,6-hexanediyl ester, polymer with 2-aminoethanol	similar compounds	Severe irritant
2-Propenoic acid, 2-hydroxyethyl ester, polymer with 5-isocyanato-1-(isocyanatomethyl)-1,3,3-trimethylcyclohexane, 2-oxepanone and 2,2'-oxybis[ethanol]	similar compounds	Severe irritant
1,6-Hexanediol diacrylate	Rabbit	Moderate irritant
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	Rabbit	No significant irritation
Benzophenone	Rabbit	Mild irritant
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper	Rabbit	No significant irritation
Camphene	Rabbit	Moderate irritant
Toluene	Rabbit	Moderate irritant
Acrylic acid	Rabbit	Corrosive

Skin Sensitisation

Name	Species	Value
Isobornyl acrylate	Mouse	Sensitising
Isooctyl acrylate	Mouse	Sensitising
Tetrahydrofurfuryl acrylate	Professional judgement	Sensitising
2-Propenoic acid, 1,6-hexanediyl ester, polymer with 2-aminoethanol	similar compounds	Sensitising
1,6-Hexanediol diacrylate	Guinea pig	Sensitising
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	Mouse	Sensitising
Benzophenone	Guinea pig	Not classified
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper	Human	Not classified
Toluene	Guinea pig	Not classified
Acrylic acid	Guinea pig	Not classified

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Isobornyl acrylate	In Vitro	Not mutagenic
Isooctyl acrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Tetrahydrofurfuryl acrylate	In Vitro	Not mutagenic
1,6-Hexanediol diacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	In Vitro	Not mutagenic
Benzophenone	In Vitro	Not mutagenic
Benzophenone	In vivo	Not mutagenic
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper	In Vitro	Not mutagenic
Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic
Acrylic acid	In vivo	Not mutagenic
Acrylic acid	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Isooctyl acrylate	Dermal	Mouse	Not carcinogenic
1,6-Hexanediol diacrylate	Dermal	Mouse	Not carcinogenic
Benzophenone	Dermal	Multiple animal species	Not carcinogenic
Benzophenone	Ingestion	Multiple animal species	Carcinogenic.
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper	Ingestion	Mouse	Not carcinogenic
Toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
Acrylic acid	Ingestion	Rat	Not carcinogenic
Acrylic acid	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Isobornyl acrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	31 days
Isobornyl acrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 100 mg/kg/day	premating into lactation
Isobornyl acrylate	Ingestion	Not classified for development	Rat	NOAEL 100 mg/kg/day	premating into lactation
Isooctyl acrylate	Dermal	Not classified for female reproduction	Rat	NOAEL 57 mg/kg/day	premating & during gestation
Isooctyl acrylate	Dermal	Not classified for male reproduction	Rat	NOAEL 57 mg/kg/day	premating & during gestation
Isooctyl acrylate	Dermal	Not classified for development	Rat	NOAEL 57 mg/kg/day	premating & during gestation
Isooctyl acrylate	Ingestion	Not classified for development	Rat	NOAEL 1,000	during organogenesis

				mg/kg/day	
Tetrahydrofurfuryl acrylate	Ingestion	Toxic to female reproduction	Rat	NOAEL 50 mg/kg/day	prematuring into lactation
Tetrahydrofurfuryl acrylate	Dermal	Toxic to male reproduction	Rat	NOAEL 100 mg/kg/day	90 days
Tetrahydrofurfuryl acrylate	Ingestion	Toxic to male reproduction	Rat	NOAEL 35 mg/kg/day	90 days
Tetrahydrofurfuryl acrylate	Inhalation	Toxic to male reproduction	Rat	NOAEL 0.6 mg/l	90 days
Tetrahydrofurfuryl acrylate	Ingestion	Toxic to development	Rat	NOAEL 50 mg/kg/day	prematuring into lactation
1,6-Hexanediol diacrylate	Not specified.	Not classified for development	Rat	NOAEL 750 mg/kg/day	during organogenesis
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	Ingestion	Not classified for development	Rat	NOAEL 150 mg/kg/day	during gestation
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	Ingestion	Toxic to female reproduction	Rat	NOAEL 200 mg/kg/day	prematuring into lactation
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	Ingestion	Toxic to male reproduction	Rat	NOAEL 60 mg/kg/day	85 days
Benzophenone	Ingestion	Not classified for female reproduction	Rat	NOAEL 100 mg/kg/day	2 generation
Benzophenone	Ingestion	Not classified for male reproduction	Rat	NOAEL 80 mg/kg/day	2 generation
Benzophenone	Ingestion	Not classified for development	Rabbit	NOAEL 25 mg/kg/day	during gestation
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	prematuring into lactation
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	42 days
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	prematuring into lactation
Toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse
Acrylic acid	Ingestion	Not classified for female reproduction	Rat	NOAEL 460 mg/kg/day	2 generation
Acrylic acid	Ingestion	Not classified for male reproduction	Rat	NOAEL 460 mg/kg/day	2 generation
Acrylic acid	Inhalation	Not classified for development	Rat	NOAEL 1.1 mg/l	during organogenesis
Acrylic acid	Ingestion	Not classified for development	Rat	NOAEL 53 mg/kg/day	2 generation

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Isooctyl acrylate	Inhalation	respiratory irritation	Not classified	Human	NOAEL Not available	occupational exposure
Isooctyl acrylate	Ingestion	central nervous system depression	Not classified	Rat	NOAEL 5,000 mg/kg	
Tetrahydrofurfuryl acrylate	Inhalation	respiratory irritation	May cause respiratory irritation	Human and animal	NOAEL Not available	
2-Propenoic acid, 1,6-hexanediyl ester, polymer with 2-aminoethanol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
2-Propenoic acid, 2-hydroxyethyl ester, polymer with 5-isocyanato-1-(isocyanatomethyl)-1,3,3-trimethylcyclohexane, 2-oxepanone and 2,2'-oxybis[ethanol]	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
1,6-Hexanediol diacrylate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Acrylic acid	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Isobornyl acrylate	Ingestion	gastrointestinal tract immune system kidney and/or bladder	Not classified	Rat	NOAEL 500 mg/kg/day	31 days

		heart endocrine system hematopoietic system liver nervous system respiratory system				
Isooctyl acrylate	Dermal	heart endocrine system hematopoietic system liver immune system nervous system kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 57 mg/kg/day	prematuring & during gestation
Isooctyl acrylate	Ingestion	endocrine system liver kidney and/or bladder heart bone, teeth, nails, and/or hair hematopoietic system immune system muscles nervous system eyes respiratory system vascular system	Not classified	Rat	NOAEL 600 mg/kg/day	90 days
1,6-Hexanediol diacrylate	Dermal	skin	May cause damage to organs though prolonged or repeated exposure	Mouse	LOAEL 70 mg/kg/day	80 weeks
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	Ingestion	skin blood liver kidney and/or bladder nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
Benzophenone	Ingestion	kidney and/or bladder	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 75 mg/kg/day	14 weeks
Benzophenone	Ingestion	heart hematopoietic system liver immune system endocrine system bone, teeth, nails, and/or hair nervous system eyes respiratory system	Not classified	Rat	NOAEL 850 mg/kg/day	14 weeks
29H,31H-phthalocyanin	Ingestion	endocrine system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

ato(2-)-N29,N30,N31,N32 copper		hematopoietic system respiratory system				
29H,31H-phthalocyanin ato(2-)-N29,N30,N31,N32 copper	Ingestion	kidney and/or bladder	Not classified	Multiple animal species	NOAEL Not available	not available
Toluene	Inhalation	auditory system eyes olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	nervous system	May cause damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
Toluene	Inhalation	heart liver kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
Toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic system vascular system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	liver kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks

Aspiration Hazard

Name	Value
Toluene	Aspiration hazard

Exposure Levels

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

Interactive Effects

Not determined.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity**Acute aquatic hazard:**

GHS Acute 1: Very toxic to aquatic life.

Chronic aquatic hazard:

GHS Chronic 2: Toxic to aquatic life with long lasting effects.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Isobornyl acrylate	5888-33-5	Green algae	Experimental	72 hours	EC50	1.98 mg/l
Isobornyl acrylate	5888-33-5	Zebra Fish	Experimental	96 hours	LC50	0.704 mg/l
Isobornyl acrylate	5888-33-5	Green Algae	Experimental	72 hours	NOEC	0.405 mg/l
Isobornyl acrylate	5888-33-5	Water flea	Experimental	21 days	NOEC	0.092 mg/l
Isooctyl acrylate	29590-42-9	Green algae	Estimated	72 hours	EC50	0.535 mg/l
Isooctyl acrylate	29590-42-9	Activated sludge	Experimental	3 hours	EC50	>1,000 mg/l
Isooctyl acrylate	29590-42-9	Fathead minnow	Experimental	96 hours	LC50	0.67 mg/l
Isooctyl acrylate	29590-42-9	Water flea	Experimental	48 hours	EC50	0.4 mg/l
Isooctyl acrylate	29590-42-9	Water flea	Experimental	21 days	NOEC	0.065 mg/l
Tetrahydrofurfuryl acrylate	22399-48-6	Activated sludge	Experimental	3 hours	EC50	263.7 mg/l
Tetrahydrofurfuryl acrylate	22399-48-6	Green algae	Experimental	72 hours	EC50	3.92 mg/l
Tetrahydrofurfuryl acrylate	22399-48-6	Water flea	Experimental	48 hours	EC50	37.7 mg/l
Tetrahydrofurfuryl acrylate	22399-48-6	Zebra Fish	Experimental	96 hours	LC50	7.32 mg/l
Tetrahydrofurfuryl acrylate	22399-48-6	Green algae	Experimental	72 hours	EC10	2.48 mg/l
2-Propenoic acid, 1,6-hexanediyl ester, polymer	67906-98-3		Data not available or insufficient for classification			N/A

with 2-aminoethanol						
2-Propenoic acid, 2-hydroxyethyl ester, polymer with 5-isocyanato-1-(isocyanatomethyl)-1,3,3-trimethylcyclohexane, 2-oxepanone and 2,2'-oxybis[ethanol]	72162-39-1		Data not available or insufficient for classification			N/A
1,6-Hexanediol diacrylate	13048-33-4	Green Algae	Experimental	72 hours	EC50	2.33 mg/l
1,6-Hexanediol diacrylate	13048-33-4	Medaka	Experimental	96 hours	LC50	0.38 mg/l
1,6-Hexanediol diacrylate	13048-33-4	Water flea	Experimental	48 hours	EC50	2.7 mg/l
1,6-Hexanediol diacrylate	13048-33-4	Green Algae	Experimental	72 hours	NOEC	0.9 mg/l
1,6-Hexanediol diacrylate	13048-33-4	Medaka	Experimental	39 days	NOEC	0.072 mg/l
1,6-Hexanediol diacrylate	13048-33-4	Water flea	Experimental	21 days	NOEC	0.14 mg/l
1,6-Hexanediol diacrylate	13048-33-4	Activated sludge	Experimental	30 minutes	EC50	270 mg/l
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	75980-60-8	Activated sludge	Experimental	3 hours	EC20	>1,000 mg/l
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	75980-60-8	Common Carp	Experimental	96 hours	LC50	1.4 mg/l
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	75980-60-8	Green Algae	Experimental	72 hours	EC50	>2.01 mg/l
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	75980-60-8	Water flea	Experimental	48 hours	EC50	3.53 mg/l
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	75980-60-8	Green algae	Experimental	72 hours	EC10	1.56 mg/l
Benzophenone	119-61-9	Fathead	Experimental	96 hours	LC50	10.89 mg/l

		minnow				
Benzophenone	119-61-9	Green Algae	Experimental	72 hours	EC50	3.5 mg/l
Benzophenone	119-61-9	Water flea	Experimental	48 hours	EC50	6.8 mg/l
Benzophenone	119-61-9	Fathead minnow	Experimental	7 days	NOEC	2.1 mg/l
Benzophenone	119-61-9	Green Algae	Experimental	72 hours	NOEC	1 mg/l
Benzophenone	119-61-9	Water flea	Experimental	21 days	NOEC	0.2 mg/l
29H,31H-phthalocyanina to(2-)-N29,N30,N31,N32 copper	147-14-8	Green algae	Estimated	72 hours	EC50	>100 mg/l
29H,31H-phthalocyanina to(2-)-N29,N30,N31,N32 copper	147-14-8	Water flea	Estimated	48 hours	EC50	>500 mg/l
29H,31H-phthalocyanina to(2-)-N29,N30,N31,N32 copper	147-14-8	Activated sludge	Experimental	30 minutes	EC20	750 mg/l
29H,31H-phthalocyanina to(2-)-N29,N30,N31,N32 copper	147-14-8	Bacteria	Experimental	30 minutes	EC10	>10,000 mg/l
29H,31H-phthalocyanina to(2-)-N29,N30,N31,N32 copper	147-14-8	Rainbow trout	Experimental	96 hours	LC50	355.6 mg/l
29H,31H-phthalocyanina to(2-)-N29,N30,N31,N32 copper	147-14-8	Green algae	Estimated	72 hours	EC10	100 mg/l
29H,31H-phthalocyanina to(2-)-N29,N30,N31,N32 copper	147-14-8	Water flea	Estimated	21 days	NOEC	>=1 mg/l
Acrylic acid	79-10-7	Green algae	Experimental	72 hours	EC50	0.13 mg/l
Acrylic acid	79-10-7	Rainbow trout	Experimental	96 hours	LC50	27 mg/l
Acrylic acid	79-10-7	Water flea	Experimental	48 hours	EC50	95 mg/l
Acrylic acid	79-10-7	Green algae	Experimental	72 hours	EC10	0.03 mg/l
Acrylic acid	79-10-7	Water flea	Experimental	21 days	NOEC	3.8 mg/l
Acrylic acid	79-10-7		Experimental	7 days	LD50	>=98 mg per kg of bodyweight
Acrylic acid	79-10-7		Experimental	48 hours	NOEC	0.9 mg/l
Acrylic acid	79-10-7	Activated sludge	Experimental	30 minutes	NOEC	100 mg/l
Acrylic acid	79-10-7	Redworm	Experimental	14 days	LC50	>1,000 mg/kg (Dry Weight)

Acrylic acid	79-10-7	Soil microbes	Experimental	28 days	NOEC	100 mg/kg (Dry Weight)
Camphene	79-92-5	Activated sludge	Experimental	3 hours	EC10	490.3 mg/l
Camphene	79-92-5	Green Algae	Experimental	72 hours	EC50	1.75 mg/l
Camphene	79-92-5	Sheepshead Minnow	Experimental	96 hours	LC50	1.9 mg/l
Camphene	79-92-5	Water flea	Experimental	48 hours	EC50	0.72 mg/l
Camphene	79-92-5	Zebra Fish	Experimental	96 hours	LC50	0.72 mg/l
Camphene	79-92-5	Green Algae	Experimental	72 hours	NOEC	0.07 mg/l
Toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
Toluene	108-88-3	Grass Shrimp	Experimental	96 hours	LC50	9.5 mg/l
Toluene	108-88-3	Green Algae	Experimental	72 hours	EC50	12.5 mg/l
Toluene	108-88-3	Leopard frog	Experimental	9 days	LC50	0.39 mg/l
Toluene	108-88-3	Pink Salmon	Experimental	96 hours	LC50	6.41 mg/l
Toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
Toluene	108-88-3	Coho Salmon	Experimental	40 days	NOEC	1.39 mg/l
Toluene	108-88-3	Diatom	Experimental	72 hours	NOEC	10 mg/l
Toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l
Toluene	108-88-3	Activated sludge	Experimental	12 hours	IC50	292 mg/l
Toluene	108-88-3	Bacteria	Experimental	16 hours	NOEC	29 mg/l
Toluene	108-88-3	Bacteria	Experimental	24 hours	EC50	84 mg/l
Toluene	108-88-3	Redworm	Experimental	28 days	LC50	>150 mg per kg of bodyweight
Toluene	108-88-3	Soil microbes	Experimental	28 days	NOEC	<26 mg/kg (Dry Weight)

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Isobornyl acrylate	5888-33-5	Experimental Biodegradation	28 days	CO2 evolution	57 % weight	OECD 310 CO2 Headspace
Isooctyl acrylate	29590-42-9	Estimated Photolysis		Photolytic half-life (in air)	1.45-1.78 days (t 1/2)	Non-standard method
Isooctyl acrylate	29590-42-9	Experimental Biodegradation	28 days	BOD	93 % weight	OECD 301D - Closed bottle test
Tetrahydrofurfuryl acrylate	22399-48-6	Experimental Bioconcentration		Log Kow	0.81	Non-standard method
Tetrahydrofurfuryl acrylate	22399-48-6	Experimental Biodegradation	28 days	BOD	77.7 % BOD/ThBOD	OECD 301F - Manometric respirometry
2-Propenoic acid, 1,6-hexanediyl ester, polymer with 2-aminoethanol	67906-98-3	Data not available-insufficient			N/A	
2-Propenoic acid, 2-hydroxyethyl ester, polymer with 5-	72162-39-1	Data not available-insufficient			N/A	

isocyanato-1-(isocyanatomethyl)-1,3,3-trimethylcyclohexane, 2-oxepanone and 2,2'-oxybis[ethanol]						
1,6-Hexanediol diacrylate	13048-33-4	Estimated Photolysis		Photolytic half-life (in air)	1 days (t 1/2)	Episuite™
1,6-Hexanediol diacrylate	13048-33-4	Experimental Biodegradation	28 days	CO2 evolution	60-70 %CO2 evolution/THC O2 evolution	ISO 14593 Inorg C Headspace
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	75980-60-8	Experimental Biodegradation	28 days	BOD	≤10 % BOD/ThBOD	OECD 301F - Manometric respirometry
Benzophenone	119-61-9	Experimental Biodegradation	28 days	BOD	66-84 % weight	OECD 301F - Manometric respirometry
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper	147-14-8	Experimental Biodegradation	28 days	BOD	<1 % weight	OECD 301F - Manometric respirometry
Acrylic acid	79-10-7	Estimated Photolysis		Photolytic half-life (in air)	3.2 days (t 1/2)	
Acrylic acid	79-10-7	Experimental Biodegradation	28 days	Percent degraded	81 % BOD/ThBOD	OECD 301D - Closed bottle test
Acrylic acid	79-10-7	Experimental Biodegradation	3 days	Percent degraded	72.9 %CO2 evolution/THC O2 evolution	
Camphene	79-92-5	Experimental Photolysis		Photolytic half-life (in air)	7.2 hours (t 1/2)	Non-standard method
Camphene	79-92-5	Experimental Biodegradation	28 days	BOD	2 % BOD/ThBOD	OECD 301C - MITI test (I)
Toluene	108-88-3	Experimental Photolysis		Photolytic half-life (in air)	5.2 days (t 1/2)	
Toluene	108-88-3	Experimental Biodegradation	20 days	BOD	80 % BOD/ThBOD	APHA Std Meth Water/Wastewater

12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Isobornyl acrylate	5888-33-5	Estimated BCF - Other	56 hours	Bioaccumulation factor	37	OECD 305E - Bioaccumulation flow-through fish test
Isooctyl acrylate	29590-42-9	Estimated Bioconcentration		Bioaccumulation factor	120-940	Non-standard method
2-Propenoic acid, 1,6-hexanediyl ester, polymer	67906-98-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

with 2-aminoethanol						
2-Propenoic acid, 2-hydroxyethyl ester, polymer with 5-isocyanato-1-(isocyanatomethyl)-1,3,3-trimethylcyclohexane, 2-oxepanone and 2,2'-oxybis[ethanol]	72162-39-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
1,6-Hexanediol diacrylate	13048-33-4	Experimental Bioconcentration		Log Kow	2.81	
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	75980-60-8	Experimental BCF-Carp	56 days	Bioaccumulation factor	≤40	
Benzophenone	119-61-9	Experimental BCF - Other	56 days	Bioaccumulation factor	<12	Non-standard method
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper	147-14-8	Experimental BCF-Carp	42 days	Bioaccumulation factor	<3.6	OECD 305E - Bioaccumulation flow-through fish test
Acrylic acid	79-10-7	Experimental Bioconcentration		Log Kow	0.46	OECD 107 log Kow shke flsk mtd
Camphene	79-92-5	Experimental BCF-Carp	56 days	Bioaccumulation factor	606-1290	OECD 305C-Bioaccum degree fish
Toluene	108-88-3	Experimental BCF - Other	72 hours	Bioaccumulation factor	90	
Toluene	108-88-3	Experimental Bioconcentration		Log Kow	2.73	

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes.

SECTION 14: Transport Information

Australian Dangerous Goods Code (ADG) - Road/Rail Transport

UN No.: UN3082

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. , (ISOBORNYL ACRYLATE, ISOOCYTL ACRYLATE)

Class/Division: 9

Sub Risk: Not applicable.

Packing Group: III

Special Instructions: Australian Dangerous Goods Code: Not subject to this code as per Special Provision AU01

Hazchem Code: •3Z

IERG: 47

International Air Transport Association (IATA) - Air Transport

UN No.: UN3082

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. , (ISOBORNYL ACRYLATE, ISOOCYTL ACRYLATE)

Class/Division: 9

Sub Risk: Not applicable.

Packing Group: III

Special Instructions: Not restricted, as per Special Provision A197, environmentally hazardous substance exception.

International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: UN3082

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. , (ISOBORNYL ACRYLATE, ISOOCYTL ACRYLATE)

Class/Division: 9

Sub Risk: Not applicable.

Packing Group: III

Marine Pollutant: Not applicable.

Special Instructions: Not restricted, as per IMDG code 2.10.2.7, marine pollutant exception.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Australian Inventory Status:

An ingredient(s) in this product is being introduced under a Certificate (Standard/Limited/Polymer of Low Concern) granted under Section 39 of the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

Poison Schedule: This product is intended for Industrial or Professional Use only and therefore is not packaged and labelled in accordance with the requirements of the Standard for the Uniform Scheduling of Medicines and Poisons.

SECTION 16: Other information

Revision information:

Complete document review.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State

regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au