

## **Safety Data Sheet**

Copyright, 2021, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 35-1596-2
 Version number:
 2.00

 Issue Date:
 07/11/2021
 Supersedes date:
 11/04/2017

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

## **IDENTIFICATION:**

#### 1.1. Product identifier

3M(TM) Scotch-Weld(TM) Low Odor Acrylic Adhesive DP8805NS Green

#### **Product Identification Numbers**

62-2852-1446-6

#### 1.2. Recommended use and restrictions on use

#### Recommended use

Adhesive

For Industrial or Professional use only.

#### 1.3. Supplier's details

Address: 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113

**Telephone:** 136 136

E Mail: productinfo.au@mmm.com

Website: www.3m.com.au

## 1.4. Emergency telephone number

Company Emergency Hotline: EMERGENCY: 1800 097 146 (Australia only)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the SDSs for components of this product are:

35-1588-9, 35-1592-1

One or more components of this KIT is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

## TRANSPORT INFORMATION

This KIT and its components are NOT classified as Dangerous Goods.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au



## Safety Data Sheet

Copyright, 2021, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 35-1588-9
 Version number:
 2.00

 Issue Date:
 03/10/2021
 Supersedes date:
 10/04/2017

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

## **SECTION 1: Identification**

#### 1.1. Product identifier

3M™ Scotch-Weld™ Low Odor Acrylic Adhesive DP8805NS and Low Odor Acrylic Adhesive 8805NS Green, Part B

#### 1.2. Recommended use and restrictions on use

#### Recommended use

Adhesive

For Industrial or Professional use only.

### 1.3. Supplier's details

Address: 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113

**Telephone:** 136 136

E Mail: productinfo.au@mmm.com

Website: www.3m.com.au

#### 1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

## **SECTION 2: Hazard identification**

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

#### 2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 2.

Skin Sensitizer: Category 1.

Reproductive Toxicity: Category 1.

## 2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

## Signal word

Danger

#### **Symbols**

Exclamation mark | Health Hazard |

#### **Pictograms**





#### Hazard statements

H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H360 May damage fertility or the unborn child.

## **Precautionary statements**

**Prevention:** 

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280K Wear protective gloves and respiratory protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/attention.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313 IF eve irritation persists: Get medical advice/attention.

P337 + P313 IF eye irritation persists: Get medical advice/attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

**Storage:** 

P405 Store locked up.

Disposal:

P501 Dispose of contents/container in accordance with applicable

local/regional/national/international regulations.

## 2.3. Other assigned/identified product hazards

None known.

### 2.4. Other hazards which do not result in classification

Causes mild skin irritation.

Harmful to aquatic life with long lasting effects.

# **SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
Tetrahydrofurfuryl Methacrylate	2455-24-5	20 - 40
Butadiene-Acrylonitrile Polymer	9003-18-3	1 - 20
Hydroxyethyl Methacrylate	868-77-9	1 - 20
Isobornyl Methacrylate	7534-94-3	1 - 20
Fillers	Trade Secret	1 - 20
Bisphenol A Polyethylene Glycol Diether	41637-38-1	0.1 - 10
Dimethacrylate (polymer)		
Phosphate Esters of PPG Methacrylate	95175-93-2	< 3
Tetrahydrofurfuryl alcohol	97-99-4	< 0.3
Copper Naphthenates	1338-02-9	< 0.1

## **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

#### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

## 4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

## 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

## **Hazardous Decomposition or By-Products**

<b>Substance</b>	<u>Condition</u>
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.
Hydrogen Chloride	During combustion.
Oxides of nitrogen.	During combustion.

### 5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

#### **6.2.** Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

#### 7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidising agents. Store away from amines.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
COPPER COMPOUNDS	1338-02-9	ACGIH	TWA(as Cu, fume):0.2	
			mg/m3;TWA(as Cu dust or	
			mist):1 mg/m3	
Tetrahydrofurfuryl alcohol	97-99-4	AIHA	TWA:2 mg/m3(0.5 ppm)	SKIN
Fillers	Trade	ACGIH	TWA(respirable fraction):2	A4: Not class. as human
	Secret		mg/m3	carcin
Fillers	Trade	Australia OELs	TWA(Inspirable dust)(8	
	Secret		hours):10 mg/m3	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

Australia OELs: Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG: Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

#### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

## 8.2.2. Personal protective equipment (PPE)

## Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

## Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

When only incidental contact is anticipated, alternative glove material(s) may be used. If contact with the glove does occur, remove immediately and replace with a set of new gloves. For incidental contact, gloves made of the following material(s) may be used: Nitrile rubber.

Select and use gloves according to AS/NZ 2161.

### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer. Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

information on basic physical and chemical properties		
Physical state	Liquid.	
Specific Physical Form:	Paste	
Colour	White	
Odour	Acrylate	
Odour threshold	No data available.	
pH	Not applicable.	
Melting point/Freezing point	Not applicable.	

Boiling point/Initial boiling point/Boiling range	> 93.3 °C
Flash point	> 93.3 °C [Test Method:Closed Cup]
Evaporation rate	No data available.
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	No data available.
Flammable Limits(UEL)	No data available.
Vapour pressure	No data available.
Vapor Density and/or Relative Vapor Density	No data available.
Density	1.13 g/ml
Relative density	1.13 [Ref Std:WATER=1]
Water solubility	Nil
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Autoignition temperature	No data available.
Decomposition temperature	No data available.
Viscosity/Kinematic Viscosity	100,000 - 125,000 mPa-s
Volatile organic compounds (VOC)	
Percent volatile	
VOC less H2O & exempt solvents	4.8 g/l [Details: when used as intended with Part A]
VOC less H2O & exempt solvents	612 g/l [Details:as supplied]
VOC less H2O & exempt solvents	0.5 % [Details: when used as intended with Part A]
Molecular weight	Not applicable.

## **Nanoparticles**

This material does not contain nanoparticles.

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

## 10.2 Chemical stability

Stable.

## 10.3. Conditions to avoid

Heat.

Sparks and/or flames.

### 10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

## 10.5 Incompatible materials

Amines.

Strong acids.

Strong bases.

Strong oxidising agents.

## 10.6 Hazardous decomposition products

**Substance Condition** 

None known.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

#### 11.1 Information on Toxicological effects

## Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

#### Skin contact

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching. May cause additional health effects (see below).

#### Eve contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

### Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

### **Additional Health Effects:**

#### Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

#### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity** 

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000
_			mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000
			mg/kg
Tetrahydrofurfuryl Methacrylate	Ingestion	Rat	LD50 4,000 mg/kg
Tetrahydrofurfuryl Methacrylate	Dermal	similar health hazards	LD50 estimated to be 2,000 - 5,000 mg/kg
Hydroxyethyl Methacrylate	Dermal	Rabbit	LD50 > 5,000  mg/kg
Hydroxyethyl Methacrylate	Ingestion	Rat	LD50 5,564 mg/kg
Butadiene-Acrylonitrile Polymer	Dermal	Rabbit	LD50 > 15,000  mg/kg
Butadiene-Acrylonitrile Polymer	Ingestion	Rat	LD50 > 30,000  mg/kg
Isobornyl Methacrylate	Dermal	Rabbit	LD50 > 3,000  mg/kg
Isobornyl Methacrylate	Ingestion	Rat	LD50 > 2,000  mg/kg
Fillers	Dermal		LD50 estimated to be > 5,000 mg/kg
Fillers	Ingestion	Human	LD50 > 15,000 mg/kg
Bisphenol A Polyethylene Glycol	Dermal	Rat	LD50 > 2,000  mg/kg
Diether Dimethacrylate (polymer)			

Bisphenol A Polyethylene Glycol Diether Dimethacrylate (polymer)	Ingestion	Rat	LD50 > 35,000 mg/kg
Phosphate Esters of PPG Methacrylate	Ingestion	Rat	LD50 > 5,000 mg/kg
Phosphate Esters of PPG Methacrylate	Dermal	similar health hazards	LD50 estimated to be > 5,000 mg/kg
Tetrahydrofurfuryl alcohol	Dermal	Professional judgement	LD50 estimated to be 2,000 - 5,000 mg/kg
Tetrahydrofurfuryl alcohol	Inhalation-Vapour (4 hours)	Rat	LC50 > 3.1 mg/l
Tetrahydrofurfuryl alcohol	Ingestion	Rat	LD50 > 2,000 mg/kg
Copper Naphthenates	Dermal	similar compounds	LD50 > 2,000 mg/kg
Copper Naphthenates	Ingestion	similar compounds	LD50 >300, < 2,000 mg/kg

ATE = acute toxicity estimate

## Skin Corrosion/Irritation

Name	Species	Value	
Tetrahydrofurfuryl Methacrylate	Rabbit	No significant irritation	
Hydroxyethyl Methacrylate	Rabbit	Minimal irritation	
Butadiene-Acrylonitrile Polymer	Professional judgement	No significant irritation	
Isobornyl Methacrylate	Rabbit	Mild irritant	
Fillers	Professional judgement	No significant irritation	
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (polymer)	Rabbit	Minimal irritation	
Phosphate Esters of PPG Methacrylate	Not available	Irritant	
Tetrahydrofurfuryl alcohol	Rabbit	No significant irritation	
Copper Naphthenates	Rabbit	No significant irritation	

**Serious Eye Damage/Irritation** 

Name	Species	Value	
Tetrahydrofurfuryl Methacrylate	Rabbit	No significant irritation	
Hydroxyethyl Methacrylate	Rabbit	Moderate irritant	
Butadiene-Acrylonitrile Polymer	Professional judgement	No significant irritation	
Isobornyl Methacrylate	Rabbit	Mild irritant	
Fillers	Professional judgement	No significant irritation	
Bisphenol A Polyethylene Glycol Diether	Rabbit	No significant irritation	
Dimethacrylate (polymer)			
Phosphate Esters of PPG Methacrylate	Not available	Corrosive	
Tetrahydrofurfuryl alcohol	Rabbit	Severe irritant	
Copper Naphthenates	In vitro data	No significant irritation	

## **Skin Sensitisation**

Name	Species	Value	
	a process	, 33-2-5	
Tetrahydrofurfuryl Methacrylate	In vitro data	Sensitising	
Hydroxyethyl Methacrylate	Human and animal	Sensitising	
Isobornyl Methacrylate	Guinea pig	Not classified	
Bisphenol A Polyethylene Glycol Diether	Guinea pig	Not classified	
Dimethacrylate (polymer)			
Tetrahydrofurfuryl alcohol	Mouse	Not classified	
Copper Naphthenates	Guinea pig	Not classified	

## **Respiratory Sensitisation**

For the component/components, either no data are currently available or the data are not sufficient for classification.

## **Germ Cell Mutagenicity**

Name	Route	Value
Tetrahydrofurfuryl Methacrylate	In Vitro	Not mutagenic
Hydroxyethyl Methacrylate	In vivo	Not mutagenic
Hydroxyethyl Methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Bisphenol A Polyethylene Glycol Diether	In Vitro	Not mutagenic
Dimethacrylate (polymer)		
Tetrahydrofurfuryl alcohol	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Fillers	Inhalation	Multiple animal	Not carcinogenic
		species	

## Reproductive Toxicity

Reproductive and/or Developmental Effects

Reproductive and/or Developmental Effects						
Name	Route	Value	Species	Test result	Exposure Duration	
Tetrahydrofurfuryl	Ingestion	Not classified for	Rat	NOAEL 300	29 days	
Methacrylate		male reproduction		mg/kg/day		
Tetrahydrofurfuryl	Ingestion	Toxic to female	Rat	NOAEL 120	premating into	
Methacrylate		reproduction		mg/kg/day	lactation	
Tetrahydrofurfuryl	Ingestion	Toxic to development	Rat	NOAEL 120	premating into	
Methacrylate				mg/kg/day	lactation	
Hydroxyethyl	Ingestion	Not classified for	Rat	NOAEL	premating & during	
Methacrylate		female reproduction		1,000	gestation	
				mg/kg/day		
Hydroxyethyl	Ingestion	Not classified for	Rat	NOAEL	49 days	
Methacrylate		male reproduction		1,000		
				mg/kg/day		
Hydroxyethyl	Ingestion	Not classified for	Rat	NOAEL	premating & during	
Methacrylate		development		1,000	gestation	
				mg/kg/day		
Tetrahydrofurfuryl	Ingestion	Toxic to female	Rat	NOAEL 50	premating into	
alcohol		reproduction		mg/kg/day	lactation	
Tetrahydrofurfuryl	Dermal	Toxic to male	Rat	NOAEL 100	13 weeks	
alcohol		reproduction		mg/kg/day		
Tetrahydrofurfuryl	Ingestion	Toxic to male	Rat	NOAEL 150	47 days	
alcohol		reproduction		mg/kg/day	-	
Tetrahydrofurfuryl	Inhalation	Toxic to male	Rat	NOAEL 0.6	90 days	
alcohol		reproduction		mg/l		
Tetrahydrofurfuryl	Ingestion	Toxic to development	Rat	NOAEL 50	premating into	
alcohol				mg/kg/day	lactation	

# Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Phosphate Esters of PPG Methacrylate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Tetrahydrofur furyl alcohol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for	similar health hazards	NOAEL Not available	

\_\_\_\_\_

	classification		
	***************************************		

**Specific Target Organ Toxicity - repeated exposure** 

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Tetrahydrofur furyl Methacrylate	Ingestion	hematopoietic system   nervous system	Not classified	Rat	NOAEL 300 mg/kg/day	29 days
Fillers	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL NA	occupational exposure
Fillers	Inhalation	pulmonary fibrosis	Not classified	Rat	NOAEL Not available	
Tetrahydrofur furyl alcohol	Inhalation	nervous system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.2 mg/l	90 days
Tetrahydrofur furyl alcohol	Inhalation	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.6 mg/l	90 days
Tetrahydrofur furyl alcohol	Inhalation	eyes	Not classified	Rat	NOAEL 2.1 mg/l	90 days
Tetrahydrofur furyl alcohol	Ingestion	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 69 mg/kg/day	91 days
Tetrahydrofur furyl alcohol	Ingestion	immune system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 150 mg/kg/day	28 days
Tetrahydrofur furyl alcohol	Ingestion	endocrine system   kidney and/or bladder	Not classified	Rat	NOAEL 600 mg/kg/day	28 days
Tetrahydrofur furyl alcohol	Ingestion	liver   eyes	Not classified	Rat	NOAEL 781 mg/kg/day	91 days
Tetrahydrofur furyl alcohol	Ingestion	heart   nervous system	Not classified	Rat	NOAEL 600 mg/kg/day	28 days

### **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

#### **Exposure Levels**

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

#### **Interactive Effects**

Not determined.

# **SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not

## expected to be available for exposure, or the data is considered not relevant to the material as a whole.

## 12.1. Toxicity

Acute aquatic hazard:

GHS Acute 3: Harmful to aquatic life.

**Chronic aquatic hazard:** 

GHS Chronic 3: Harmful to aquatic life with long lasting effects.

No product test data available.

Material	CAS Number	Organism	Туре	Exposure	Test endpoint	Test result
Tetrahydrofurf	2455-24-5	Fathead	Experimental	96 hours	LC50	34.7 mg/l
uryl		minnow				
Methacrylate						
Tetrahydrofurf	2455-24-5	Green algae	Experimental	72 hours	EC50	>100 mg/l
uryl						
Methacrylate						
Tetrahydrofurf	2455-24-5	Green algae	Experimental	72 hours	EC10	100 mg/l
uryl						
Methacrylate						
Tetrahydrofurf	2455-24-5	Water flea	Experimental	21 days	NOEC	37.2 mg/l
uryl						
Methacrylate						
Butadiene-	9003-18-3		Data not			N/A
Acrylonitrile			available or			
Polymer			insufficient for			
			classification			
Fillers	Trade Secret	Water flea	Experimental	48 hours	LC50	>1,100 mg/l
Hydroxyethyl	868-77-9	Turbot	Analogous	96 hours	LC50	833 mg/l
Methacrylate			Compound			
Hydroxyethyl	868-77-9	Fathead	Experimental	96 hours	LC50	227 mg/l
Methacrylate		minnow				
Hydroxyethyl	868-77-9	Green algae	Experimental	72 hours	EC50	710 mg/l
Methacrylate						
Hydroxyethyl	868-77-9	Water flea	Experimental	48 hours	EC50	380 mg/l
Methacrylate						
Hydroxyethyl	868-77-9	Green Algae	Experimental	72 hours	NOEC	160 mg/l
Methacrylate						
Hydroxyethyl	868-77-9	Water flea	Experimental	21 days	NOEC	24.1 mg/l
Methacrylate						
Hydroxyethyl	868-77-9		Experimental	16 hours	EC0	>3,000 mg/l
Methacrylate						, ,
Hydroxyethyl	868-77-9		Experimental	18 hours	LD50	<98 mg per kg of
Methacrylate						bodyweight
Isobornyl	7534-94-3	Green Algae	Experimental	72 hours	EC50	2.3 mg/l
Methacrylate						
Isobornyl	7534-94-3	Water flea	Experimental	48 hours	EC50	1.1 mg/l
Methacrylate			*			
Isobornyl	7534-94-3	Zebra Fish	Experimental	96 hours	LC50	1.8 mg/l
Methacrylate						
Isobornyl	7534-94-3	Green Algae	Experimental	72 hours	EC10	0.751 mg/l
Methacrylate			1			
Isobornyl	7534-94-3	Water flea	Experimental	21 days	NOEC	0.233 mg/l

Page: 11 of 1

Methacrylate						
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (polymer)	41637-38-1	Activated sludge	Estimated	3 hours	EC50	>1,000 mg/l
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (polymer)	41637-38-1	Green Algae	Estimated	72 hours	EL50	>100 mg/l
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (polymer)	41637-38-1	Water flea	Estimated	48 hours	EL50	>100 mg/l
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (polymer)	41637-38-1	Zebra Fish	Estimated	96 hours	LL50	>100 mg/l
Phosphate Esters of PPG Methacrylate	95175-93-2		Data not available or insufficient for classification			N/A
Tetrahydrofurf uryl alcohol	97-99-4	Green Algae	Experimental	72 hours	EC50	>100 mg/l
Tetrahydrofurf uryl alcohol	97-99-4	Medaka	Experimental	96 hours	LC50	>100 mg/l
Tetrahydrofurf uryl alcohol	97-99-4	Water flea	Experimental	48 hours	EC50	>100 mg/l
Tetrahydrofurf uryl alcohol	97-99-4	Green Algae	Experimental	72 hours	NOEC	>100 mg/l
Tetrahydrofurf uryl alcohol	97-99-4	Water flea	Experimental	21 days	NOEC	>100 mg/l
Copper Naphthenates	1338-02-9	Green Algae	Estimated	72 hours	EC50	0.629 mg/l
Copper Naphthenates	1338-02-9	Water flea	Estimated	48 hours	EC50	0.0756 mg/l
Copper Naphthenates	1338-02-9	Zebra Fish	Estimated	96 hours	LC50	0.0702 mg/l
Copper Naphthenates	1338-02-9	Algae or other aquatic plants	Estimated	hours	NOEC	0.132 mg/l
Copper Naphthenates	1338-02-9	Fathead minnow	Estimated	32 days	EC10	0.0354 mg/l
Copper Naphthenates	1338-02-9	Water flea	Estimated	21 days	NOEC	0.0756 mg/l

# 12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Tetrahydrofurf	2455-24-5	Experimental	28 days	BOD	75 %	OECD 301F -
uryl		Biodegradation	-		BOD/ThBOD	Manometric
Methacrylate						respirometry

\_\_\_\_\_

Butadiene-	9003-18-3	Data not			N/A	
Acrylonitrile		available-				
Polymer		insufficient				
Fillers	Trade Secret	Data not			N/A	
		available-				
		insufficient				
Hydroxyethyl	868-77-9	Experimental		Hydrolytic	10.9 days (t	OECD 111 Hydrolysis
Methacrylate		Hydrolysis		half-life (pH 10)	1/2)	func of pH
Hydroxyethyl	868-77-9	Experimental	28 days	BOD	84 %BOD/CO	OECD 301D - Closed
Methacrylate		Biodegradation	-		D	bottle test
Isobornyl	7534-94-3	Estimated		Photolytic half-	1.12 days (t	Non-standard method
Methacrylate		Photolysis		life (in air)	1/2)	
Isobornyl	7534-94-3	Experimental	28 days	CO2 evolution	70 % weight	OECD 310 CO2
Methacrylate		Biodegradation				Headspace
Bisphenol A	41637-38-1	Experimental	28 days	Percent	24 % degraded	Non-standard method
Polyethylene		Biodegradation		degraded		
Glycol Diether						
Dimethacrylate						
(polymer)						
Phosphate	95175-93-2	Data not			N/A	
Esters of PPG		available-				
Methacrylate		insufficient				
Tetrahydrofurf	97-99-4	Experimental	28 days	BOD	92 % weight	OECD 301C - MITI
uryl alcohol		Biodegradation				test (I)
Copper	1338-02-9	Data not			N/A	
Naphthenates		available-				
		insufficient				

# 12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Tetrahydrofurf	2455-24-5	Estimated		Bioaccumulatio	3.42	Estimated:
uryl		Bioconcentrati		n factor		Bioconcentration factor
Methacrylate		on				
Butadiene-	9003-18-3	Data not	N/A	N/A	N/A	N/A
Acrylonitrile		available or				
Polymer		insufficient for				
		classification				
Fillers	Trade Secret	Data not	N/A	N/A	N/A	N/A
		available or				
		insufficient for				
		classification				
Hydroxyethyl	868-77-9	Experimental		Log Kow	0.42	OECD 107 log Kow
Methacrylate		Bioconcentrati				shke flsk mtd
		on				
Isobornyl	7534-94-3	Estimated		Bioaccumulatio	39	Estimated:
Methacrylate		Bioconcentrati		n factor		Bioconcentration factor
		on				
Bisphenol A	41637-38-1	Estimated		Bioaccumulatio	6.6	Non-standard method
Polyethylene		Bioconcentrati		n factor		
Glycol Diether		on				
Dimethacrylate						
(polymer)						
Phosphate	95175-93-2	Data not	N/A	N/A	N/A	N/A

Esters of PPG		available or				
Methacrylate		insufficient for				
		classification				
Tetrahydrofurf	97-99-4	Experimental		Log Kow	-0.11	Non-standard method
uryl alcohol		Bioconcentrati				
		on				
Copper	1338-02-9	Estimated	42 days	Bioaccumulatio	≤27	OECD 305E -
Naphthenates		BCF-Carp	-	n factor		Bioaccumulation flow-
						through fish test

## 12.4. Mobility in soil

Please contact manufacturer for more details

#### 12.5 Other adverse effects

No information available

# **SECTION 13: Disposal considerations**

## 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate uncured product in a permitted waste incineration facility. Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste.

# **SECTION 14: Transport Information**

Australian Dangerous Goods Code (ADG) - Road/Rail Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable. Sub Risk: Not applicable. Packing Group: Not applicable.

Hazchem Code: Not applicable

**IERG:** Not applicable.

International Air Transport Association (IATA) - Air Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable. Sub Risk: Not applicable. Packing Group: Not applicable.

International Maritime Dangerous Goods Code (IMDG)- Marine Transport

**UN No.:** Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable.
Sub Risk: Not applicable.
Packing Group: Not applicable.
Marine Pollutant: Not applicable.

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **Australian Inventory Status:**

The chemical components contained within this product are listed on the Australian Inventory of Chemical Substances and are in compliance with the requirements of the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

**Poison Schedule:** This product is intended for Industrial or Professional Use only and therefore is not packaged and labelled in accordance with the requirements of the Standard for the Uniform Scheduling of Medicines and Poisons.

## **SECTION 16: Other information**

#### **Revision information:**

Complete document review.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au



## Safety Data Sheet

Copyright, 2021, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 35-1592-1
 Version number:
 2.00

 Issue Date:
 29/08/2021
 Supersedes date:
 11/04/2017

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

## **SECTION 1: Identification**

#### 1.1. Product identifier

3M™ Scotch-Weld™ Low Odor Acrylic Adhesive DP8805NS Green, Part A

#### 1.2. Recommended use and restrictions on use

#### Recommended use

Adhesive

For Industrial or Professional use only.

### 1.3. Supplier's details

**Address:** 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113

**Telephone:** 136 136

E Mail: productinfo.au@mmm.com

Website: www.3m.com.au

#### 1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

## **SECTION 2: Hazard identification**

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

#### 2.1. Classification of the substance or mixture

Skin Sensitizer: Category 1B.

#### 2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

#### Signal word

Warning

#### **Symbols**

Exclamation mark |

#### **Pictograms**



### **Hazard statements**

H317 May cause an allergic skin reaction.

### **Precautionary statements**

**Prevention:** 

P272 Contaminated work clothing should not be allowed out of the workplace.

P280E Wear protective gloves.

**Response:** 

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention. P362 + P364 Take off contaminated clothing and wash it before reuse.

Disposal:

P501 Dispose of contents/container in accordance with applicable

local/regional/national/international regulations.

## 2.3. Other assigned/identified product hazards

None known.

## 2.4. Other hazards which do not result in classification

May be harmful if swallowed.

Toxic to aquatic life.

Harmful to aquatic life with long lasting effects.

# **SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	CAS Nbr	% by Weight	
Dibenzoate Propanol	27138-31-4	50 - 80	
Acrylate Polymer	25101-28-4	5 - 30	
Catalyst.	Trade Secret	1 - 20	
Organic Peroxide	13122-18-4	1 - 10	
Acetone	67-64-1	< 3	

## **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

## 3MTM Scotch-WeldTM Low Odor Acrylic Adhesive DP8805NS Green, Part A

#### Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

#### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## **SECTION 5: Fire-fighting measures**

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

#### **Hazardous Decomposition or By-Products**

SubstanceConditionHydrocarbons.During combustion.Carbon monoxide.During combustion.Carbon dioxide.During combustion.

## 5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

#### **6.2.** Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

#### 7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidising agents. Store away from amines.

## **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Acetone	67-64-1	ACGIH	TWA:250 ppm;STEL:500 ppm	A4: Not class. as human
				carcin
Acetone	67-64-1	Australia OELs	TWA(8 hours):1185	
			mg/m3(500 ppm);STEL(15	
			minutes):2375 mg/m3(1000	
			ppm)	ļ

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

Australia OELs: Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG: Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

## 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

## Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective

clothing. When only incidental contact is anticipated, alternative glove material(s) may be used. If contact with the glove does occur, remove immediately and replace with a set of new gloves. For incidental contact, gloves made of nitrile rubber are recommended. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

Select and use gloves according to AS/NZ 2161.

## **Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates Organic vapour respirators may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer. Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

## **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Paste
Colour	Blue
Odour	Hydrocarbon
Odour threshold	No data available.
pH	Not applicable.
Melting point/Freezing point	Not applicable.
Boiling point/Initial boiling point/Boiling range	> 93.3 °C
Flash point	> 93.3 °C [Test Method:Closed Cup]
Evaporation rate	No data available.
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	No data available.
Flammable Limits(UEL)	No data available.
Vapour pressure	No data available.
Vapor Density and/or Relative Vapor Density	No data available.
Density	1.08 g/ml
Relative density	1.08 [Ref Std:WATER=1]
Water solubility	Nil
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Autoignition temperature	No data available.
Decomposition temperature	No data available.
Viscosity/Kinematic Viscosity	20,000 mPa-s
Volatile organic compounds (VOC)	
Percent volatile	No data available.
VOC less H2O & exempt solvents	4.8 g/l [Details: when used as intended with Part B]
VOC less H2O & exempt solvents	0.5 % [Details: when used as intended with Part B]
VOC less H2O & exempt solvents	59.4 g/l [Details: as supplied]
Molecular weight	Not applicable.

### Nanoparticles

This material does not contain nanoparticles.

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

#### 10.2 Chemical stability

Stable.

#### 10.3. Conditions to avoid

Heat.

Sparks and/or flames.

#### 10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.5 Incompatible materials

Amines.

Strong acids.

Strong bases.

Strong oxidising agents.

## 10.6 Hazardous decomposition products

Substance

Condition

None known.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

#### 11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

## Skin contact

Contact with the skin during product use is not expected to result in significant irritation. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

#### **Ingestion**

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

## **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity** 

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000
_			mg/kg
Overall product	Ingestion		No data available; calculated ATE2,000 -
			5,000 mg/kg
Dibenzoate Propanol	Dermal	Rat	LD50 > 2,000  mg/kg
Dibenzoate Propanol	Inhalation-Dust/Mist	Rat	LC50 > 200  mg/l
	(4 hours)		
Dibenzoate Propanol	Ingestion	Rat	LD50 3,295 mg/kg
Acrylate Polymer	Dermal		LD50 estimated to be > 5,000 mg/kg
Acrylate Polymer	Ingestion	Rat	LD50 > 5,000 mg/kg
Catalyst.	Dermal	Professional	LD50 estimated to be 2,000 - 5,000 mg/kg
		judgement	
Catalyst.	Ingestion	Rat	LD50 > 2,000  mg/kg
Organic Peroxide	Dermal	Rat	LD50 > 2,000 mg/kg
Organic Peroxide	Inhalation-Dust/Mist	Rat	LC50 > 0.8 mg/l
	(4 hours)		_
Organic Peroxide	Ingestion	Rat	LD50 12,905 mg/kg
Acetone	Dermal	Rabbit	LD50 > 15,688 mg/kg
Acetone	Inhalation-Vapour (4	Rat	LC50 76 mg/l
	hours)		_
Acetone	Ingestion	Rat	LD50 5,800 mg/kg

ATE = acute toxicity estimate

#### Skin Corrosion/Irritation

Name	Species	Value
Dibenzoate Propanol	Rabbit	No significant irritation
Organic Peroxide	Rabbit	No significant irritation
Acetone	Mouse	Minimal irritation

Serious Eye Damage/Irritation

Name	Species	Value
Dibenzoate Propanol	Rabbit	No significant irritation
Organic Peroxide	Rabbit	No significant irritation
Acetone	Rabbit	Severe irritant

## **Skin Sensitisation**

Name	Species	Value
Dibenzoate Propanol	Guinea pig	Not classified
Catalyst.	Mouse	Not classified
Organic Peroxide	Guinea pig	Sensitising

## **Respiratory Sensitisation**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
------	-------	-------

Page: 7 of 12

Dibenzoate Propanol	In Vitro	Not mutagenic
Catalyst.	In Vitro	Not mutagenic
Acetone	In vivo	Not mutagenic
Acetone	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Acetone	Not specified.	Multiple animal	Not carcinogenic
		species	

## Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	<b>Exposure Duration</b>
Dibenzoate Propanol Ingestion		Not classified for	Rat	NOAEL 500	2 generation
		female reproduction		mg/kg/day	
Dibenzoate Propanol	Ingestion	Not classified for	Rat	NOAEL 400	2 generation
		male reproduction		mg/kg/day	
Dibenzoate Propanol	Ingestion	Not classified for	Rat	NOAEL	during gestation
		development		1,000	
				mg/kg/day	
Acetone	Ingestion	Not classified for	Rat	NOAEL	13 weeks
		male reproduction		1,700	
				mg/kg/day	
Acetone	Inhalation	Not classified for	Rat	NOAEL 5.2	during
		development		mg/l	organogenesis

## Target Organ(s)

**Specific Target Organ Toxicity - single exposure** 

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Catalyst.	Ingestion	nervous system	Not classified	Rat	NOAEL 2,000 mg/kg	
Acetone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Acetone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 hours
Acetone	Inhalation	liver	Not classified	Guinea pig	NOAEL Not available	
Acetone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse

Specific Target Organ Toxicity - reneated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Dibenzoate Propanol	Ingestion	hematopoietic system   liver	Not classified	Rat	NOAEL 2,500 mg/kg/day	90 days
Acetone	Dermal	eyes	Not classified	Guinea pig	NOAEL Not available	3 weeks

Acetone	Inhalation	hematopoietic system	Not classified	Human	NOAEL 3 mg/l	6 weeks
Acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 days
Acetone	Inhalation	kidney and/or bladder	Not classified	Guinea pig	NOAEL 119 mg/l	not available
Acetone	Inhalation	heart   liver	Not classified	Rat	NOAEL 45 mg/l	8 weeks
Acetone	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 900 mg/kg/day	13 weeks
Acetone	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Acetone	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 200 mg/kg/day	13 weeks
Acetone	Ingestion	liver	Not classified	Mouse	NOAEL 3,896 mg/kg/day	14 days
Acetone	Ingestion	eyes	Not classified	Rat	NOAEL 3,400 mg/kg/day	13 weeks
Acetone	Ingestion	respiratory system	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Acetone	Ingestion	muscles	Not classified	Rat	NOAEL 2,500 mg/kg	13 weeks
Acetone	Ingestion	skin   bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 11,298 mg/kg/day	13 weeks

#### **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

#### **Exposure Levels**

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

### **Interactive Effects**

Not determined.

# **SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

## 12.1. Toxicity

#### Acute aquatic hazard:

GHS Acute 2: Toxic to aquatic life.

## Chronic aquatic hazard:

GHS Chronic 3: Harmful to aquatic life with long lasting effects.

No product test data available.

Material	CAS Number	Organism	Туре	Exposure	Test endpoint	Test result
Dibenzoate	27138-31-4	Fathead	Experimental	96 hours	LC50	3.7 mg/l
Propanol		minnow				
Dibenzoate	27138-31-4	Green Algae	Experimental	72 hours	EL50	4.9 mg/l
Propanol			_			_

Dibenzoate	27138-31-4	Water flea	Experimental	48 hours	EL50	19.31 mg/l
Propanol						
Dibenzoate Propanol	27138-31-4	Green Algae	Experimental	72 hours	EC10	0.89 mg/l
Acrylate Polymer	25101-28-4		Data not available or insufficient for classification			N/A
Catalyst.	Trade Secret		Data not available or insufficient for classification			N/A
Organic Peroxide	13122-18-4	Activated sludge	Experimental	3 hours	NOEC	26.3 mg/l
Organic Peroxide	13122-18-4	Green Algae	Experimental		EC50	0.51 mg/l
Organic Peroxide	13122-18-4	Rainbow trout	Experimental		LC50	7 mg/l
Organic Peroxide	13122-18-4	Water flea	Experimental		EC50	>100 mg/l
Organic Peroxide	13122-18-4	Green Algae	Experimental		NOEC	0.125 mg/l
Acetone	67-64-1	Algae other	Experimental	96 hours	EC50	11,493 mg/l
Acetone	67-64-1	Crustecea other	Experimental	24 hours	LC50	2,100 mg/l
Acetone	67-64-1	Rainbow trout	Experimental	96 hours	LC50	5,540 mg/l
Acetone	67-64-1	Water flea	Experimental	21 days	NOEC	1,000 mg/l
Acetone	67-64-1	Bacteria	Experimental	16 hours	NOEC	1,700 mg/l
Acetone	67-64-1	Redworm	Experimental	48 hours	LC50	>100

## 12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Dibenzoate	27138-31-4	Experimental	28 days	CO2 evolution	85 % weight	OECD 301B - Modified
Propanol		Biodegradation				sturm or CO2
Acrylate	25101-28-4	Data not			N/A	
Polymer		available-				
		insufficient				
Catalyst.	Trade Secret	Estimated		Photolytic half-	1.48 days (t	Non-standard method
		Photolysis		life (in air)	1/2)	
Catalyst.	Trade Secret	Experimental	28 days	CO2 evolution	29.1 %CO2	OECD 301B - Modified
		Biodegradation			evolution/THC	sturm or CO2
					O2 evolution	
Organic	13122-18-4	Estimated	28	BOD	14 %	OECD 301C - MITI
Peroxide		Biodegradation			BOD/ThBOD	test (I)
Acetone	67-64-1	Experimental		Photolytic half-	147 days (t 1/2)	
		Photolysis		life (in air)		
Acetone	67-64-1	Experimental	28 days	BOD	78 %	OECD 301D - Closed
		Biodegradation			BOD/ThBOD	bottle test

## 12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Dibenzoate	27138-31-4	Estimated		Bioaccumulatio	8	Estimated:
Propanol		Bioconcentrati		n factor		Bioconcentration factor

\_\_\_\_

		on				
Acrylate Polymer	25101-28-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Catalyst.	Trade Secret	Experimental Bioconcentrati on		Log Kow	2.57	Non-standard method
Organic Peroxide	13122-18-4	Estimated Bioconcentrati on		Bioaccumulatio n factor	363	Estimated: Bioconcentration factor
Acetone	67-64-1	Experimental BCF - Other		Bioaccumulatio n factor	0.65	
Acetone	67-64-1	Experimental Bioconcentrati on		Log Kow	-0.24	

#### 12.4. Mobility in soil

Please contact manufacturer for more details

#### 12.5 Other adverse effects

No information available.

# **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes.

# **SECTION 14: Transport Information**

Australian Dangerous Goods Code (ADG) - Road/Rail Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable. Sub Risk: Not applicable. Packing Group: Not applicable.

Hazchem Code: Not applicable

**IERG:** Not applicable.

International Air Transport Association (IATA) - Air Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable.
Sub Risk: Not applicable.
Packing Group: Not applicable.

International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable.
Sub Risk: Not applicable.
Packing Group: Not applicable.
Marine Pollutant: Not applicable.

# **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **Australian Inventory Status:**

An ingredient(s) in this product is being introduced under the no unreasonable risk non-cosmetic (<100 Kg) exemption provisions specified in Section 21(4) of the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

**Poison Schedule:** This product is intended for Industrial or Professional Use only and therefore is not packaged and labelled in accordance with the requirements of the Standard for the Uniform Scheduling of Medicines and Poisons.

## **SECTION 16: Other information**

#### **Revision information:**

Complete document review.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au