



## Safety Data Sheet

Copyright, 2017, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	35-2668-8	<b>Version number:</b>	1.00
<b>Issue Date:</b>	28/11/2017	<b>Supersedes date:</b>	Initial issue.

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

### SECTION 1: Identification

#### 1.1. Product identifier

3M Accessory Products, Air Tool Lubricant

#### Product Identification Numbers

60-4402-4214-1

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Tool Lubricant

For Industrial or Professional use only.

#### 1.3. Supplier's details

**Address:** 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113  
**Telephone:** 136 136  
**E Mail:** productinfo.au@mmm.com  
**Website:** www.3m.com.au

#### 1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

### SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

#### 2.1. Classification of the substance or mixture

Skin Sensitizer: Category 1B.

Specific Target Organ Toxicity (single exposure): Category 3.

#### 2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product

label.

**Signal word**

WARNING!

**Symbols**

Not applicable.

**Pictograms**

Not applicable

**Hazard statements**

H317 May cause an allergic skin reaction.  
 H336 May cause drowsiness or dizziness.

**Precautionary statements**

**Prevention:**

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
 P271 Use only outdoors or in a well-ventilated area.  
 P280E Wear protective gloves.  
 P272 Contaminated work clothing should not be allowed out of the workplace.

**Response:**

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
 P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.  
 P363 Wash contaminated clothing before reuse.  
 P321 Specific treatment (see Notes to Physician on this label).  
 P312 Call a POISON CENTRE or doctor/physician if you feel unwell.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
 P405 Store locked up.

**Disposal:**

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**2.3. Other assigned/identified product hazards**

None known.

**2.4. Other hazards which do not result in classification**

Causes mild skin irritation. May cause long lasting harmful effects to aquatic life.

**SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
C10-13-iso-Alkanes	64742-54-7	50 - 65
Alkanes, C18-28, chloro	85535-86-0	10 - 20
Chlorinated Paraffin Wax	63449-39-8	10 - 20
Mineral Oil	64742-58-1	5 - 15
Lubricant	64742-53-6	1 - 10

### 3M Accessory Products, Air Tool Lubricant

Sulphide Additive	68425-15-0	1 - 10
C10-13-iso-Alkanes	64742-65-0	0.5 - 5
Additive	68584-23-6	0.1 - 0.5

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

In case of fire: Use a carbon dioxide or dry chemical extinguisher to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### Hazardous Decomposition or By-Products

#### Substance

Carbon monoxide.

Carbon dioxide.

#### Condition

During combustion.

During combustion.

### 5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

**Hazchem Code:** •3Z

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

For industrial or professional use only. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

**7.2. Conditions for safe storage including any incompatibilities**

Store in a well-ventilated place. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidising agents.

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Paraffin oil	64742-53-6	Australia OELs	TWA(as mist)(8 hours):5 mg/m3	
MINERAL OILS, HIGHLY-REFINED OILS	64742-54-7	ACGIH	TWA(inhalable fraction):5 mg/m3	A4: Not class. as human carcin
Paraffin oil	64742-54-7	Australia OELs	TWA(as mist)(8 hours):5 mg/m3	
MINERAL OILS, HIGHLY-REFINED OILS	64742-58-1	ACGIH	TWA(inhalable fraction):5 mg/m3	A4: Not class. as human carcin
Paraffin oil	64742-65-0	Australia OELs	TWA(as mist)(8 hours):5 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

**8.2. Exposure controls****8.2.1. Engineering controls**

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure

Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

if this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Select and use gloves according to AS/NZ 2161.

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Appearance/Odour	Mild petroleum odour, clear light amber liquid.
Odour threshold	No data available.
pH	No data available.
Melting point/Freezing point	Not applicable.
Boiling point/Initial boiling point/Boiling range	230 °C
Flash point	138 °C [Test Method:Pensky-Martens Closed Cup]
Evaporation rate	No data available.
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	No data available.
Flammable Limits(UEL)	No data available.
Vapour pressure	No data available.
Vapour density	No data available.
Density	No data available.

Relative density	0.88 [ @ 20 °C ] [Ref Std: WATER=1]
Water solubility	Nil
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Autoignition temperature	No data available.
Decomposition temperature	No data available.
Viscosity	35.4 mm <sup>2</sup> /sec [ @ 40 °C ] [Test Method: Tested per ASTM protocol] [Details: 10 wt. D-445]
Viscosity	6.1 mm <sup>2</sup> /sec [ @ 100 °C ] [Test Method: Tested per ASTM protocol] [Details: 10 wt. D-445]
Volatile organic compounds (VOC)	0.18 lb/gal
Percent volatile	2.2 %
VOC less H <sub>2</sub> O & exempt solvents	21.98 g/l

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material is considered to be non reactive under normal use conditions

### 10.2 Chemical stability

Stable.

### 10.3. Conditions to avoid

Sparks and/or flames.

### 10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.5 Incompatible materials

Strong oxidising agents.

Reducing agents.

Strong acids.

### 10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
------------------	------------------

None known.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1 Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

### 3M Accessory Products, Air Tool Lubricant

May cause additional health effects (see below).

#### Skin contact

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

#### Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

#### Additional Health Effects:

##### Single exposure may cause target organ effects:

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
C10-13-iso-Alkanes	Dermal	Rabbit	LD50 > 5,000 mg/kg
C10-13-iso-Alkanes	Ingestion	Rat	LD50 > 5,000 mg/kg
Chlorinated Paraffin Wax	Dermal	Rabbit	LD50 > 13,000 mg/kg
Chlorinated Paraffin Wax	Ingestion	Rat	LD50 > 11,700 mg/kg
Lubricant	Dermal	Rabbit	LD50 > 2,000 mg/kg
Lubricant	Inhalation-Dust/Mist (4 hours)	Rat	LC50 2.2 mg/l
Lubricant	Ingestion	Rat	LD50 > 5,000 mg/kg
C10-13-iso-Alkanes	Dermal	Rabbit	LD50 > 5,000 mg/kg
C10-13-iso-Alkanes	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 4 mg/l
C10-13-iso-Alkanes	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

#### Skin Corrosion/Irritation

Name	Species	Value
C10-13-iso-Alkanes	Rabbit	Minimal irritation
Chlorinated Paraffin Wax	Rabbit	No significant irritation
Lubricant	Rabbit	Mild irritant

#### Serious Eye Damage/Irritation

Name	Species	Value
C10-13-iso-Alkanes	Rabbit	Mild irritant
Chlorinated Paraffin Wax	Rabbit	No significant irritation
Lubricant	Rabbit	Mild irritant

#### Skin Sensitisation

**3M Accessory Products, Air Tool Lubricant**

Name	Species	Value
C10-13-iso-Alkanes	Guinea pig	Not classified
Lubricant	Guinea pig	Not classified

**Respiratory Sensitisation**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
C10-13-iso-Alkanes	In Vitro	Some positive data exist, but the data are not sufficient for classification
Lubricant	In Vitro	Some positive data exist, but the data are not sufficient for classification
Lubricant	In vivo	Some positive data exist, but the data are not sufficient for classification

**Carcinogenicity**

Name	Route	Species	Value
C10-13-iso-Alkanes	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Lubricant	Dermal	Mouse	Not carcinogenic

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Lubricant	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	prematuring & during gestation
Lubricant	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	prematuring & during gestation
Lubricant	Dermal	Not classified for development	Rat	NOAEL 2,000 mg/kg/day	during gestation
Lubricant	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	prematuring & during gestation
Lubricant	Dermal	Not classified for male reproduction	Rabbit	NOAEL 1,000 mg/kg/day	28 days

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
C10-13-iso-Alkanes	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
C10-13-iso-Alkanes	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**



**3M Accessory Products, Air Tool Lubricant**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
C10-13-iso-Alkanes	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.21 mg/l	28 days

**Aspiration Hazard**

Name	Value
Lubricant	Aspiration hazard

**Exposure Levels**

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

**Interactive Effects**

Not determined.

**SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

**12.1. Toxicity****Acute aquatic hazard:**

Not acutely toxic to aquatic life by GHS criteria.

**Chronic aquatic hazard:**

GHS Chronic 4: May cause long lasting harmful effects to aquatic organisms.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
C10-13-iso-Alkanes	64742-54-7	Water flea	Estimated	48 hours	Effect Level 50%	>100 mg/l
C10-13-iso-Alkanes	64742-54-7	Green algae	Estimated	72 hours	Effect Level 50%	>100 mg/l
C10-13-iso-Alkanes	64742-54-7	Fathead minnow	Experimental	96 hours	Lethal Level 50%	>100 mg/l
C10-13-iso-Alkanes	64742-54-7	Water flea	Estimated	21 days	No obs Effect Level	>100 mg/l
C10-13-iso-Alkanes	64742-54-7	Green algae	Estimated	72 hours	No obs Effect Level	>100 mg/l
Alkanes, C18-28, chloro	85535-86-0	Water flea	Estimated	24 hours	EC50	102 mg/l
Alkanes, C18-28, chloro	85535-86-0	Rainbow trout	Estimated	96 hours	LC50	>300 mg/l
Chlorinated Paraffin Wax	63449-39-8	Rainbow trout	Experimental	96 hours	LC50	>300 mg/l
Chlorinated Paraffin Wax	63449-39-8	Water flea	Experimental	24 hours	EC50	102 mg/l
Mineral Oil	64742-58-1		Data not available or insufficient for			

**3M Accessory Products, Air Tool Lubricant**

			classification			
Lubricant	64742-53-6	Green algae	Estimated	96 hours	EC50	>100 mg/l
Lubricant	64742-53-6	Water flea	Experimental	48 hours	EC50	>100 mg/l
Sulphide Additive	68425-15-0	Green algae	Experimental	72 hours	EC50	>100 mg/l
Sulphide Additive	68425-15-0	Water flea	Experimental	48 hours	EC50	>100 mg/l
Sulphide Additive	68425-15-0	Zebra Fish	Endpoint not reached	96 hours	Lethal Level 50%	>100 mg/l
Sulphide Additive	68425-15-0	Green algae	Experimental	72 hours	NOEC	100 mg/l
C10-13-iso-Alkanes	64742-65-0	Water flea	Estimated	48 hours	EC50	>100 mg/l
C10-13-iso-Alkanes	64742-65-0	Green algae	Estimated	96 hours	EC50	>100 mg/l
C10-13-iso-Alkanes	64742-65-0	Rainbow trout	Experimental	96 hours	LC50	>100 mg/l
C10-13-iso-Alkanes	64742-65-0	Water flea	Experimental	21 days	NOEC	100 mg/l
Additive	68584-23-6	Water flea	Estimated	48 hours	EC50	>100 mg/l
Additive	68584-23-6	Green algae	Estimated	72 hours	EC50	>100 mg/l
Additive	68584-23-6	Green algae	Estimated	72 hours	NOEC	>100 mg/l

**12.2. Persistence and degradability**

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
C10-13-iso-Alkanes	64742-54-7	Experimental Biodegradation	28 days	BOD	31 % weight	OECD 301F - Manometric respirometry
Alkanes, C18-28, chloro	85535-86-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Chlorinated Paraffin Wax	63449-39-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Mineral Oil	64742-58-1	Experimental Biodegradation	28 days		9.1 % weight	Other methods
Lubricant	64742-53-6	Experimental Biodegradation	28 days	BOD	42 % weight	OECD 301F - Manometric respirometry
Sulphide Additive	68425-15-0	Experimental Bioconcentration		Log Kow	>6.2	Other methods
Sulphide Additive	68425-15-0	Experimental Biodegradation	28 days	BOD	0 % BOD/ThBOD	OECD 301F - Manometric respirometry
C10-13-iso-Alkanes	64742-65-0	Experimental Biodegradation	28 days	CO2 evolution	23 % weight	Other methods
Additive	68584-23-6	Estimated Biodegradation	28 days	BOD	8.0 % BOD/ThBOD	OECD 301D - Closed bottle test

**12.3 : Bioaccumulative potential**

**3M Accessory Products, Air Tool Lubricant**

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
C10-13-iso-Alkanes	64742-54-7	Estimated Bioconcentration		Bioaccumulation factor	7.5	Estimated: Bioconcentration factor
Alkanes, C18-28, chloro	85535-86-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Chlorinated Paraffin Wax	63449-39-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Mineral Oil	64742-58-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Lubricant	64742-53-6	Estimated Bioconcentration		Log Kow	5.07	Other methods
C10-13-iso-Alkanes	64742-65-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Additive	68584-23-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

**12.4. Mobility in soil**

Please contact manufacturer for more details

**12.5 Other adverse effects**

No information available.

**SECTION 13: Disposal considerations****13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes.

**SECTION 14: Transport Information****Australian Dangerous Goods Code (ADG) - Road/Rail Transport**

UN No.: UN3082

**Proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. , ( Chlorinated Paraffin Waxes and Triphenyl Phosphate )

**Class/Division:** 9

**Sub Risk:** Not applicable.

**Packing Group:** III

**Special Instructions:** Australian Dangerous Goods Code: Not subject to this code as per Special Provision AU01

**Hazchem Code:** •3Z

## 3M Accessory Products, Air Tool Lubricant

**IERG:** 47

### **International Air Transport Association (IATA) - Air Transport**

**UN No.:** UN3082

**Proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. , ( Chlorinated Paraffin Waxes and Triphenyl Phosphate )

**Class/Division:** 9

**Sub Risk:** Not applicable.

**Packing Group:** III

**Special Instructions:** Not restricted, as per Special Provision A197, environmentally hazardous substance exception.

### **International Maritime Dangerous Goods Code (IMDG)- Marine Transport**

**UN No.:** UN3082

**Proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. , ( Chlorinated Paraffin Waxes and Triphenyl Phosphate )

**Class/Division:** 9

**Sub Risk:** Not applicable.

**Packing Group:** III

**Marine Pollutant:** Not applicable.

**Special Instructions:** Not restricted, as per IMDG code 2.10.2.7, marine pollutant exception.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **Australian Inventory Status:**

An ingredient(s) in this product is being introduced under the no unreasonable risk non-cosmetic (<100 Kg) exemption provisions specified in Section 21(4) of the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

**Poison Schedule:** This product has not been assessed for poisons scheduling as the product is intended for industrial and professional use only.

## SECTION 16: Other information

#### **Revision information:**

Initial issue.

**DISCLAIMER:** The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

**3M Australia SDSs are available at [www.3m.com.au](http://www.3m.com.au)**