



Safety Data Sheet

Copyright, 2022, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	31-5887-0	Version number:	3.00
Issue Date:	20/03/2022	Supersedes date:	30/07/2019

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

SECTION 1: Identification

1.1. Product identifier

3M™ Premium Liquid Wax, 06005, 06006, 06008

Product Identification Numbers

60-4550-7151-8 60-4550-7198-9

1.2. Recommended use and restrictions on use

Recommended use

Automotive Wax

For Industrial or Professional use only.

1.3. Supplier's details

Address: 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113
Telephone: 136 136
E Mail: productinfo.au@mmm.com
Website: www.3m.com.au

1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

Flammable Liquid: Category 4.

Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product

label.

Signal word

Danger

Symbols

Health Hazard |

Pictograms



Hazard statements

H227 Combustible Liquid
 H372 Causes damage to organs through prolonged or repeated exposure: respiratory system.

Precautionary statements

General:

P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P260 Do not breathe dust/fume/gas/mist/vapours/spray.
 P264 Wash thoroughly after handling.
 P270 Do not eat, drink or smoke when using this product.

Response:

P314 Get medical advice/attention if you feel unwell.
 P370 + P378 In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage:

P403 Store in a well-ventilated place.

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other assigned/identified product hazards

None known.

2.4. Other hazards which do not result in classification

Causes mild skin irritation.
 Harmful to aquatic life with long lasting effects.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
------------	---------	-------------

Water	7732-18-5	50 - 70
Hydrotreated Light Petroleum Distillates	64742-47-8	10 - 30
Kaolin	1332-58-7	7 - 13
Poly (Dimethylsiloxane)	63148-62-9	3 - 7
2-Butoxyethanol	111-76-2	1 - 5
Ammonia, aqueous solution	1336-21-6	< 0.5
Glycerin	56-81-5	1 - 5
Morpholine	110-91-8	< 1
2-Propenoic acid, homopolymer	9003-01-4	< 0.5
1,2-Benzisothiazolin-3-One	2634-33-5	< 0.05

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye contact

No need for first aid is anticipated.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Hydrocarbons.
Carbon monoxide.
Carbon dioxide.
Ammonia
Oxides of nitrogen.

Condition

During combustion.
During combustion.
During combustion.
During combustion.
During combustion.

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. **WARNING !** A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

This product is classified as a C1 COMBUSTIBLE LIQUID. For more information please refer to AS 1940

7.1. Precautions for safe handling

Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Protect from sunlight. Store away from heat. Store away from acids. Store away from oxidising agents.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Morpholine	110-91-8	ACGIH	TWA:20 ppm	A4: Not classified as human carcinogen, Danger of cutaneous absorption
Morpholine	110-91-8	Australia OELs	TWA(8 hours): 71mg/m ³ (20 ppm)	SKIN
2-Butoxyethanol	111-76-2	ACGIH	TWA:20 ppm	A3: Confirmed animal carcinogen.
2-Butoxyethanol	111-76-2	Australia OELs	TWA(8 hours):96.9 mg/m ³ (20 ppm);STEL(15 minutes):242 mg/m ³ (50 ppm)	SKIN
Kaolin	1332-58-7	ACGIH	TWA(respirable fraction):2	A4: Not class. as human

			mg/m3	carcin
Kaolin	1332-58-7	Australia OELs	TWA(Inspirable dust)(8 hours):10 mg/m3	
CAS NO SEQ117921	56-81-5	ACGIH	TWA(inhalable particulates):10 mg/m3	
CAS NO SEQ117922	56-81-5	ACGIH	TWA(respirable particles):3 mg/m3	
Glycerin	56-81-5	Australia OELs	TWA(Inspirable dust)(8 hours):10 mg/m3	
Kerosine (petroleum)	64742-47-8	ACGIH	TWA(as total hydrocarbon vapour, non-aerosol):200 mg/m3	A3: Confirmed animal carcin., SKIN

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

Select and use gloves according to AS/NZ 2161.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Paste
Colour	Light Green-Yellow
Odour	Mild Odour
Odour threshold	<i>No data available.</i>
pH	9
Melting point/Freezing point	<i>Not applicable.</i>
Boiling point/Initial boiling point/Boiling range	<i>No data available.</i>
Flash point	62.8 °C [<i>Test Method: Closed Cup</i>]
Evaporation rate	<i>No data available.</i>
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Vapour pressure	<i>No data available.</i>
Vapor Density and/or Relative Vapor Density	<i>No data available.</i>
Density	1 g/ml
Relative density	1 [<i>Ref Std: WATER=1</i>]
Water solubility	<i>No data available.</i>
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
Viscosity/Kinematic Viscosity	8,000 mPa-s
Volatile organic compounds (VOC)	2.3 % weight [<i>Test Method: calculated per CARB title 2</i>]
Volatile organic compounds (VOC)	203 g/l [<i>Test Method: calculated SCAQMD rule 443.1</i>]
Percent volatile	80.9 % weight
VOC less H2O & exempt solvents	516 g/l [<i>Test Method: calculated SCAQMD rule 443.1</i>]
Molecular weight	<i>No data available.</i>

Nanoparticles

This material does not contain nanoparticles.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3. Conditions to avoid

Heat.

Sparks and/or flames.

Light.

10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.5 Incompatible materials

Strong oxidising agents.
Strong acids.

10.6 Hazardous decomposition products

Substance

Condition

None known.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:

Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum, and changes in lung function tests.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg

Hydrotreated Light Petroleum Distillates	Dermal	Rabbit	LD50 > 3,160 mg/kg
Hydrotreated Light Petroleum Distillates	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 3 mg/l
Hydrotreated Light Petroleum Distillates	Ingestion	Rat	LD50 > 5,000 mg/kg
Kaolin	Dermal		LD50 estimated to be > 5,000 mg/kg
Kaolin	Ingestion	Human	LD50 > 15,000 mg/kg
Poly (Dimethylsiloxane)	Dermal	Rabbit	LD50 > 19,400 mg/kg
Poly (Dimethylsiloxane)	Ingestion	Rat	LD50 > 17,000 mg/kg
Glycerin	Dermal	Rabbit	LD50 estimated to be > 5,000 mg/kg
Glycerin	Ingestion	Rat	LD50 > 5,000 mg/kg
2-Butoxyethanol	Dermal	Guinea pig	LD50 > 2,000 mg/kg
2-Butoxyethanol	Inhalation-Vapour (4 hours)	Guinea pig	LC50 > 2.6 mg/l
2-Butoxyethanol	Ingestion	Guinea pig	LD50 1,200 mg/kg
Morpholine	Dermal	Rabbit	LD50 310 mg/kg
Morpholine	Inhalation-Vapour	Rat	LC50 estimated to be 10 - 20 mg/l
Morpholine	Ingestion	Rat	LD50 1,050 mg/kg
Ammonia, aqueous solution	Ingestion	Rat	LD50 350 mg/kg
2-Propenoic acid, homopolymer	Dermal	Rabbit	LD50 > 3,000 mg/kg
2-Propenoic acid, homopolymer	Ingestion	Rat	LD50 > 2,500 mg/kg
1,2-Benzisothiazolin-3-One	Dermal	Rat	LD50 > 2,000 mg/kg
1,2-Benzisothiazolin-3-One	Ingestion	Rat	LD50 454 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Hydrotreated Light Petroleum Distillates	Rabbit	Mild irritant
Kaolin	Professional judgement	No significant irritation
Poly (Dimethylsiloxane)	Rabbit	No significant irritation
Glycerin	Rabbit	No significant irritation
2-Butoxyethanol	Rabbit	Irritant
Morpholine	official classification	Corrosive
Ammonia, aqueous solution	Rabbit	Corrosive
1,2-Benzisothiazolin-3-One	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Hydrotreated Light Petroleum Distillates	Rabbit	Mild irritant
Kaolin	Professional judgement	No significant irritation
Poly (Dimethylsiloxane)	Rabbit	No significant irritation
Glycerin	Rabbit	No significant irritation
2-Butoxyethanol	Rabbit	Severe irritant
Morpholine	Rabbit	Corrosive
Ammonia, aqueous solution	Rabbit	Corrosive
1,2-Benzisothiazolin-3-One	Rabbit	Corrosive

Skin Sensitisation

Name	Species	Value
Hydrotreated Light Petroleum Distillates	Guinea pig	Not classified
Glycerin	Guinea pig	Not classified
2-Butoxyethanol	Guinea pig	Not classified
Morpholine	Guinea pig	Not classified

1,2-Benzisothiazolin-3-One	Guinea pig	Sensitising
----------------------------	------------	-------------

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Hydrotreated Light Petroleum Distillates	In Vitro	Not mutagenic
2-Butoxyethanol	In Vitro	Some positive data exist, but the data are not sufficient for classification
Morpholine	In Vitro	Some positive data exist, but the data are not sufficient for classification
Morpholine	In vivo	Some positive data exist, but the data are not sufficient for classification
1,2-Benzisothiazolin-3-One	In vivo	Not mutagenic
1,2-Benzisothiazolin-3-One	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Hydrotreated Light Petroleum Distillates	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Kaolin	Inhalation	Multiple animal species	Not carcinogenic
Glycerin	Ingestion	Mouse	Some positive data exist, but the data are not sufficient for classification
2-Butoxyethanol	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Morpholine	Ingestion	Multiple animal species	Not carcinogenic
Morpholine	Inhalation	Rat	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Glycerin	Ingestion	Not classified for female reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
Glycerin	Ingestion	Not classified for male reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
Glycerin	Ingestion	Not classified for development	Rat	NOAEL 2,000 mg/kg/day	2 generation
2-Butoxyethanol	Dermal	Not classified for development	Rat	NOAEL 1,760 mg/kg/day	during gestation
2-Butoxyethanol	Ingestion	Not classified for development	Rat	NOAEL 100 mg/kg/day	during organogenesis
2-Butoxyethanol	Inhalation	Not classified for development	Multiple animal species	NOAEL 0.48 mg/l	during organogenesis
1,2-Benzisothiazolin-3-One	Ingestion	Not classified for female reproduction	Rat	NOAEL 112 mg/kg/day	2 generation
1,2-Benzisothiazolin-3-One	Ingestion	Not classified for male reproduction	Rat	NOAEL 112 mg/kg/day	2 generation
1,2-Benzisothiazolin-	Ingestion	Not classified for	Rat	NOAEL 112	2 generation

3-One		development		mg/kg/day	
-------	--	-------------	--	-----------	--

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Hydrotreated Light Petroleum Distillates	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Hydrotreated Light Petroleum Distillates	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Hydrotreated Light Petroleum Distillates	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
2-Butoxyethanol	Dermal	endocrine system	Not classified	Rabbit	NOAEL 902 mg/kg	6 hours
2-Butoxyethanol	Dermal	liver	Not classified	Rabbit	LOAEL 72 mg/kg	not available
2-Butoxyethanol	Dermal	kidney and/or bladder	Not classified	Rabbit	LOAEL 451 mg/kg	6 hours
2-Butoxyethanol	Dermal	blood	Not classified	Multiple animal species	NOAEL Not available	
2-Butoxyethanol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
2-Butoxyethanol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
2-Butoxyethanol	Inhalation	blood	Not classified	Multiple animal species	NOAEL Not available	
2-Butoxyethanol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
2-Butoxyethanol	Ingestion	blood	Not classified	Multiple animal species	NOAEL Not available	
2-Butoxyethanol	Ingestion	kidney and/or bladder	Not classified	Human	NOAEL Not available	poisoning and/or abuse
Morpholine	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Ammonia, aqueous solution	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL not available	

1,2-Benzisothiazolin-3-One	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
----------------------------	------------	------------------------	--	------------------------	---------------------	--

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Kaolin	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL NA	occupational exposure
Kaolin	Inhalation	pulmonary fibrosis	Not classified	Rat	NOAEL Not available	
Glycerin	Inhalation	respiratory system heart liver kidney and/or bladder	Not classified	Rat	NOAEL 3.91 mg/l	14 days
Glycerin	Ingestion	endocrine system hematopoietic system liver kidney and/or bladder	Not classified	Rat	NOAEL 10,000 mg/kg/day	2 years
2-Butoxyethanol	Dermal	blood	Not classified	Multiple animal species	NOAEL Not available	not available
2-Butoxyethanol	Dermal	endocrine system	Not classified	Rabbit	NOAEL 150 mg/kg/day	90 days
2-Butoxyethanol	Inhalation	liver	Not classified	Rat	NOAEL 2.4 mg/l	14 weeks
2-Butoxyethanol	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 0.15 mg/l	14 weeks
2-Butoxyethanol	Inhalation	blood	Not classified	Rat	LOAEL 0.15 mg/l	6 months
2-Butoxyethanol	Inhalation	endocrine system	Not classified	Dog	LOAEL 1.9 mg/l	8 days
2-Butoxyethanol	Ingestion	blood	Not classified	Rat	LOAEL 69 mg/kg/day	13 weeks
2-Butoxyethanol	Ingestion	kidney and/or bladder	Not classified	Multiple animal species	NOAEL Not available	not available
Morpholine	Dermal	liver kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Guinea pig	LOAEL 900 mg/kg/day	13 days
Morpholine	Dermal	hematopoietic system	Not classified	Guinea pig	NOAEL 900 mg/kg/day	13 days
Morpholine	Inhalation	eyes	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure

Morpholine	Inhalation	respiratory system	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 0.09 mg/l	13 weeks
Morpholine	Inhalation	liver kidney and/or bladder	Not classified	Rat	LOAEL 64 mg/l	5 days
Morpholine	Inhalation	heart endocrine system	Not classified	Rat	NOAEL 0.9 mg/l	13 weeks
Morpholine	Inhalation	gastrointestinal tract nervous system	Not classified	Rat	NOAEL 0.53 mg/l	104 weeks
Morpholine	Ingestion	kidney and/or bladder	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 160 mg/kg/day	30 days
Morpholine	Ingestion	liver respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 160 mg/kg/day	30 days
Morpholine	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 800 mg/kg/day	30 days
Morpholine	Ingestion	endocrine system	Not classified	Rat	NOAEL 323 mg/kg/day	4 weeks
1,2-Benzisothiazolin-3-One	Ingestion	liver hematopoietic system eyes kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 322 mg/kg/day	90 days
1,2-Benzisothiazolin-3-One	Ingestion	heart endocrine system nervous system	Not classified	Rat	NOAEL 150 mg/kg/day	28 days

Aspiration Hazard

Name	Value
Hydrotreated Light Petroleum Distillates	Aspiration hazard

Exposure Levels

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

Interactive Effects

Not determined.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

GHS Acute 3: Harmful to aquatic life.

Chronic aquatic hazard:

GHS Chronic 3: Harmful to aquatic life with long lasting effects.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Hydrotreated Light Petroleum Distillates	64742-47-8	Green Algae	Estimated	72 hours	EC50	1 mg/l
Hydrotreated Light Petroleum Distillates	64742-47-8	Rainbow trout	Estimated	96 hours	LL50	2 mg/l
Hydrotreated Light Petroleum Distillates	64742-47-8	Water flea	Estimated	48 hours	EL50	1.4 mg/l
Hydrotreated Light Petroleum Distillates	64742-47-8	Green Algae	Estimated	72 hours	NOEL	1 mg/l
Hydrotreated Light Petroleum Distillates	64742-47-8	Water flea	Estimated	21 days	NOEL	0.48 mg/l
Kaolin	1332-58-7	Water flea	Experimental	48 hours	LC50	>1,100 mg/l
Poly (Dimethylsiloxane)	63148-62-9		Data not available or insufficient for classification			N/A
2-Butoxyethanol	111-76-2	Activated sludge	Experimental	16 hours	IC50	>1,000 mg/l
2-Butoxyethanol	111-76-2	Eastern oyster	Experimental	96 hours	LC50	89.4 mg/l
2-Butoxyethanol	111-76-2	Green Algae	Experimental	72 hours	EC50	1,840 mg/l
2-Butoxyethanol	111-76-2	Rainbow trout	Experimental	96 hours	LC50	1,474 mg/l
2-Butoxyethanol	111-76-2	Water flea	Experimental	48 hours	EC50	1,550 mg/l
2-Butoxyethanol	111-76-2	Green Algae	Experimental	72 hours	EC10	679 mg/l
2-Butoxyethanol	111-76-2	Water flea	Experimental	21 days	NOEC	100 mg/l
Ammonia, aqueous solution	1336-21-6	Algae or other aquatic plants	Estimated	72 hours	IC50	21.5 mg/l
Ammonia, aqueous solution	1336-21-6	Fish other	Estimated	96 hours	LC50	3.5 mg/l
Ammonia, aqueous	1336-21-6	Grass Shrimp	Estimated	48 hours	EC50	20 mg/l

solution						
Ammonia, aqueous solution	1336-21-6	Algae or other aquatic plants	Estimated	72 hours	NOEC	1.5 mg/l
Ammonia, aqueous solution	1336-21-6	Bluegill	Estimated	32 days	NOEC	4.1 mg/l
Ammonia, aqueous solution	1336-21-6	Water flea	Estimated	21 days	NOEC	49.2 mg/l
Glycerin	56-81-5	Bacteria	Experimental	16 hours	NOEC	10,000 mg/l
Glycerin	56-81-5	Rainbow trout	Experimental	96 hours	LC50	54,000 mg/l
Glycerin	56-81-5	Water flea	Experimental	48 hours	LC50	1,955 mg/l
Morpholine	110-91-8	Activated sludge	Experimental	30 minutes	EC20	>1,000 mg/l
Morpholine	110-91-8	Fish other	Experimental	96 hours	LC50	100 mg/l
Morpholine	110-91-8	Green algae	Experimental	96 hours	EC50	28 mg/l
Morpholine	110-91-8	Rainbow trout	Experimental	96 hours	LC50	180 mg/l
Morpholine	110-91-8	Water flea	Experimental	48 hours	EC50	45 mg/l
Morpholine	110-91-8	Green algae	Experimental	96 hours	NOEC	10 mg/l
Morpholine	110-91-8	Water flea	Experimental	21 days	NOEC	5 mg/l
2-Propenoic acid, homopolymer	9003-01-4	Green Algae	Estimated	72 hours	EC50	0.75 mg/l
2-Propenoic acid, homopolymer	9003-01-4	Rainbow trout	Estimated	96 hours	LC50	27 mg/l
2-Propenoic acid, homopolymer	9003-01-4	Water flea	Estimated	48 hours	EC50	47 mg/l
2-Propenoic acid, homopolymer	9003-01-4	Activated sludge	Experimental		EC50	>100 mg/l
2-Propenoic acid, homopolymer	9003-01-4	Green algae	Estimated	72 hours	NOEC	0.03 mg/l
1,2-Benzisothiazolin-3-One	2634-33-5	Green algae	Experimental	72 hours	EC50	0.11 mg/l
1,2-Benzisothiazolin-3-One	2634-33-5	Pacific oyster	Experimental	48 hours	EC50	0.062 mg/l
1,2-Benzisothiazolin-3-One	2634-33-5	Rainbow trout	Experimental	96 hours	LC50	1.6 mg/l
1,2-Benzisothiazolin-3-One	2634-33-5	Water flea	Experimental	48 hours	EC50	2.9 mg/l
1,2-Benzisothiazolin-3-One	2634-33-5	Green algae	Experimental	72 hours	NOEC	0.0403 mg/l
1,2-Benzisothiazolin-3-One	2634-33-5	Bobwhite quail	Experimental	14 days	LD50	617 mg per kg of bodyweight

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Hydrotreated Light Petroleum Distillates	64742-47-8	Data not available-insufficient			N/A	
Kaolin	1332-58-7	Data not available-insufficient			N/A	
Poly (Dimethylsiloxane)	63148-62-9	Data not available-insufficient			N/A	
2-Butoxyethanol	111-76-2	Experimental Biodegradation	28 days	CO2 evolution	90.4 % weight	OECD 301B - Modified sturm or CO2
Ammonia, aqueous solution	1336-21-6	Data not available-insufficient			N/A	
Glycerin	56-81-5	Experimental Biodegradation	14 days	BOD	63 % BOD/ThBOD	OECD 301C - MITI test (I)
Morpholine	110-91-8	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	93 % weight	OECD 301E - Modif. OECD Screen
2-Propenoic acid, homopolymer	9003-01-4	Experimental Biodegradation	28 days	BOD	87.4 % BOD/ThBOD	OECD 301F - Manometric respirometry
1,2-Benzisothiazolin-3-One	2634-33-5	Experimental Biodegradation	28 days	BOD	0 % BOD/ThBOD	OECD 301C - MITI test (I)

12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Hydrotreated Light Petroleum Distillates	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Kaolin	1332-58-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Poly (Dimethylsiloxane)	63148-62-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
2-Butoxyethanol	111-76-2	Experimental Bioconcentration		Log Kow	0.81	Non-standard method
Ammonia, aqueous solution	1336-21-6	Estimated Bioconcentration		Log Kow	-1.14	Non-standard method
Glycerin	56-81-5	Experimental Bioconcentration		Log Kow	-1.76	Non-standard method

Morpholine	110-91-8	Experimental BCF-Carp	42 days	Bioaccumulation factor	<2.8	OECD 305C-Bioaccum degree fish
2-Propenoic acid, homopolymer	9003-01-4	Experimental Bioconcentration		Log Kow	0.23	Non-standard method
1,2-Benzisothiazolin-3-One	2634-33-5	Experimental BCF - Bluegill	56 days	Bioaccumulation factor	6.62	similar to OECD 305
1,2-Benzisothiazolin-3-One	2634-33-5	Experimental Bioconcentration		Log Kow	1.45	OECD 107 log Kow shke flask mtd

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes.

SECTION 14: Transport Information

Australian Dangerous Goods Code (ADG) - Road/Rail Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

Hazchem Code: Not applicable

IERG: Not applicable.

International Air Transport Association (IATA) - Air Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

Marine Pollutant: Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Australian Inventory Status:

All components of this product are listed on or exempt from the Australian Inventory of Industrial Chemicals (AIIC). Conditions may apply prior to introduction for direct importers of this product, Please contact 3M Australia on 136 136 for further details.

Poison Schedule: This product is intended for Industrial or Professional Use only and therefore is not packaged and labelled in accordance with the requirements of the Standard for the Uniform Scheduling of Medicines and Poisons.

SECTION 16: Other information

Revision information:

Complete document review.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au