



Safety Data Sheet

Copyright, 2024, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group: 16-3092-0 **Version number:** 15.03
Issue Date: 2024/10/28 **Supersedes Date:** 2022/11/11

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3M™ Marine Adhesive Sealant 5200, White, PN 05203, PN 05206, PN 06500

Product Identification Numbers

60-4100-0946-2	60-4100-0947-0	60-4100-0967-8	60-4300-5026-4	60-4300-5027-2
60-4300-5028-0	60-9800-3622-6	60-9800-4298-4	60-9800-4299-2	60-9800-4300-8
60-9800-4301-6	60-9801-0556-7	60-9801-0843-9	62-5225-5236-3	62-5239-5230-7
62-6500-5230-1	70-0064-1000-8	FS-9100-3614-4	LB-T000-0006-0	UU-0036-4221-0
UU-0036-4223-6	XD-0055-2983-4	XS-0414-1675-0		

1.2. Recommended use and restrictions on use

Intended Use

Marine Adhesive Sealant

Specific Use

Polyurethane Adhesive for Marine Applications.

Restrictions on use

Not applicable

1.3. Supplier's details

Company: 3M Canada Company
Division: Industrial Adhesives and Tapes Division
Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1
Telephone: (800) 364-3577
Website: www.3M.ca

1.4. Emergency telephone number

Medical Emergency Telephone: 1-800-3M HELPS / 1800 364 3577

SECTION 2: Hazard identification

The following product identification number(s) are sold in the consumer market place:
60410009470; 60980108439, XS041416750

2.1. Classification of the substance or mixture

Acute Toxicity (inhalation): Category 4.
Respiratory Sensitizer: Category 1A.
Skin Sensitizer: Category 1A.
Reproductive Toxicity: Category 1B.
Carcinogenicity: Category 1B.

2.2. Label elements

Signal word

Danger

Symbols

Exclamation mark | Health Hazard |

Pictograms



Hazard statements

May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. Harmful if inhaled. May damage fertility or the unborn child. May cause cancer.

Precautionary statements

General:

Keep out of reach of children.

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. In case of inadequate ventilation wear respiratory protection. Wear protective gloves. Contaminated work clothing must not be allowed out of the workplace.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTRE or doctor/physician. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF exposed or concerned: Get medical advice/attention.

Storage:

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
------------	------------	---------	-------------

Urethane Polymer	68611-34-7	30 - 60	Poly[oxy(methyl-1,2-ethanediyl)], .alpha.,.alpha.',.alpha."-1,2,3-propanetriyltris[.omega.-hydroxy-, polymer with 1,3-diisocyanatomethylbenzene and .alpha.-hydro-.omega.-hydroxypoly[oxy(methyl-1,2-ethanediyl)], isocyanate-terminated
Talc	14807-96-6	15 - 40	Talc (Mg3H2(SiO3)4)
Titanium Dioxide	13463-67-7	5 - 10	Titanium oxide (TiO2)
Carbitol Acetate	112-15-2	1 - 5	Ethanol, 2-(2-ethoxyethoxy)-, acetate
Fumed Silica	112945-52-5	0.5 - 5	Fumed amorphous silica, crystalline-free
Zinc Oxide	1314-13-2	< 2.5	Zinc oxide (ZnO)
Alkyl Isocyanate Silane	85702-90-5	0.5 - 1.5 Trade Secret *	2,9,11,13-Tetraazanonadecanethioic acid, 19-isocyanato-11-(6-isocyanatohexyl)-10,12-dioxo-, S-[3-(trimethoxysilyl)propyl] ester
Toluene Diisocyanate	26471-62-5	0.1 - 1 Trade Secret *	Benzene, 1,3-diisocyanatomethyl-
Toluene	108-88-3	0 - 0.75	No Data Available
Heptane	142-82-5	< 0.23	Heptane
(Gamma-Mercaptopropyl)trimethoxysilane	4420-74-0	< 0.19	1-Propanethiol, 3-(trimethoxysilyl)-
Hexamethylene Diisocyanate	822-06-0	< 0.015	Hexane, 1,6-diisocyanato-

*The actual concentration of this ingredient has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic respiratory reaction (difficulty breathing, wheezing, cough, and tightness of chest). Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a carbon dioxide or dry chemical extinguisher to extinguish.

5.2. Unsuitable extinguishing media

None Determined

5.3. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Isocyanates
Carbon monoxide
Carbon dioxide
Hydrogen Cyanide
Irritant Vapours or Gases
Oxides of Nitrogen
Oxides of Sulfur

Condition

During Combustion
During Combustion
During Combustion
During Combustion
During Combustion
During Combustion
During Combustion

5.4. Special protection actions for fire-fighters

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Pour isocyanate decontaminant solution (90% water, 8% concentrated ammonia, 2% detergent) on spill and allow to react for 10 minutes. Or pour water on spill and allow to react for more than 30 minutes. Cover with absorbent material. Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Keep cool. Protect from sunlight. Store away from heat. Store away from amines.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Toluene	108-88-3	ACGIH	TWA:20 ppm	
Zinc Oxide	1314-13-2	ACGIH	TWA(respirable fraction):2 mg/m ³ ;STEL(respirable fraction):10 mg/m ³	
Titanium Dioxide	13463-67-7	ACGIH	TWA(Respirable nanoscale particles):0.2 mg/m ³ ;TWA(Respirable finescale particles):2.5 mg/m ³	
Heptane	142-82-5	ACGIH	TWA:400 ppm;STEL:500 ppm	
Talc	14807-96-6	ACGIH	TWA(respirable fraction):2 mg/m ³	
Toluene Diisocyanate	26471-62-5	ACGIH	TWA(inhalable fraction and vapour):0.001 ppm;STEL(inhalable fraction and vapour):0.005 ppm	Dermal/Respiratory Sensitizer
Hexamethylene Diisocyanate	822-06-0	ACGIH	TWA:0.005 ppm	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates
 Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Specific Physical Form:	Paste
Colour	White
Odour	Mild Urethane
Odour threshold	No Data Available
pH	No Data Available
Melting point/Freezing point	No Data Available
Boiling point	No Data Available
Flash Point	No flash point
Evaporation rate	No Data Available
Flammability	Not Applicable
Flammable Limits(LEL)	No Data Available
Flammable Limits(UEL)	No Data Available
Vapour Pressure	No Data Available
Vapour Density and/or Relative Vapour Density	No Data Available
Density	1.36 g/ml
Relative density	1.36 [Ref Std: WATER=1]
Water solubility	No Data Available
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	Not Applicable
Decomposition temperature	No Data Available
Kinematic Viscosity	220,588 mm ² /sec
Volatile Organic Compounds	No Data Available
Percent volatile	2.9 % weight
VOC Less H ₂ O & Exempt Solvents	40 g/l [Test Method: tested per EPA method 24]
Molecular weight	No Data Available

Particle Characteristics	Not Applicable
--------------------------	----------------

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Reaction with water, alcohols, and amines is not hazardous if container can vent to the atmosphere to prevent pressure buildup.

Amines
Alcohols
Water

10.6. Hazardous decomposition products**Substance****Condition**

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects**Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Harmful if inhaled. Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic Respiratory Reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest. May cause additional health effects (see below).

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea. May cause additional health effects (see below).

Additional Health Effects:**Reproductive/Developmental Toxicity:**

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

<u>Ingredient</u>	<u>CAS No.</u>	<u>Class Description</u>	<u>Regulation</u>
Titanium dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Toluene Diisocyanate	26471-62-5	Anticipated human carcinogen	National Toxicology Program Carcinogens
Toluene diisocyanates	26471-62-5	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Additional Information:

Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >10 - =20 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Talc	Dermal		LD50 estimated to be > 5,000 mg/kg
Talc	Ingestion		LD50 estimated to be > 5,000 mg/kg
Titanium Dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium Dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium Dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
Fumed Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Fumed Silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Fumed Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Zinc Oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Zinc Oxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.7 mg/l
Zinc Oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
Carbitol Acetate	Dermal	Rabbit	LD50 15,000 mg/kg
Carbitol Acetate	Ingestion	Rat	LD50 11,000 mg/kg
Toluene	Dermal	Rat	LD50 12,000 mg/kg
Toluene	Inhalation-Vapor (4 hours)	Rat	LC50 30 mg/l
Toluene	Ingestion	Rat	LD50 5,550 mg/kg
Toluene Diisocyanate	Inhalation-Vapor (4 hours)	Mouse	LC50 0.12 mg/l
Toluene Diisocyanate	Dermal	Rabbit	LD50 > 9,400 mg/kg
Toluene Diisocyanate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.35 mg/l
Toluene Diisocyanate	Ingestion	Rat	LD50 > 5,000 mg/kg
Heptane	Dermal	similar compounds	LD50 > 2,000 mg/kg
Heptane	Inhalation-Vapor (4 hours)	similar compounds	LC50 > 33.5 mg/l
Heptane	Ingestion	similar compounds	LD50 > 5,000 mg/kg
(Gamma-Mercaptopropyl)trimethoxysilane	Dermal	Rabbit	LD50 2,270 mg/kg
(Gamma-Mercaptopropyl)trimethoxysilane	Ingestion	Rat	LD50 770 mg/kg
Hexamethylene Diisocyanate	Dermal	Rat	LD50 > 7,000 mg/kg
Hexamethylene Diisocyanate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.124 mg/l
Hexamethylene Diisocyanate	Inhalation-Vapor (4 hours)	Rat	LC50 0.124 mg/l
Hexamethylene Diisocyanate	Ingestion	Rat	LD50 746 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Talc	Rabbit	No significant irritation
Titanium Dioxide	Rabbit	No significant irritation
Fumed Silica	Rabbit	No significant irritation
Zinc Oxide	Human and animal	No significant irritation
Carbitol Acetate	Human and animal	Minimal irritation
Toluene	Rabbit	Irritant
Toluene Diisocyanate	Rabbit	Irritant
Heptane	Professional judgement	Mild irritant
(Gamma-Mercaptopropyl)trimethoxysilane	Rabbit	No significant irritation
Hexamethylene Diisocyanate	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
Talc	Rabbit	No significant irritation
Titanium Dioxide	Rabbit	No significant irritation
Fumed Silica	Rabbit	No significant irritation
Zinc Oxide	Rabbit	Mild irritant
Carbitol Acetate	Rabbit	Severe irritant
Toluene	Rabbit	Moderate irritant
Toluene Diisocyanate	Rabbit	Corrosive
Heptane	similar compounds	Mild irritant
(Gamma-Mercaptopropyl)trimethoxysilane	Rabbit	No significant irritation
Hexamethylene Diisocyanate	Rabbit	Corrosive

Skin Sensitization

Name	Species	Value
Titanium Dioxide	Human and animal	Not classified
Fumed Silica	Human and animal	Not classified
Zinc Oxide	Guinea pig	Not classified
Carbitol Acetate	Human and animal	Not classified
Toluene	Guinea pig	Not classified
Toluene Diisocyanate	Human and animal	Sensitizing
Heptane	similar compounds	Not classified
(Gamma-Mercaptopropyl)trimethoxysilane	Guinea pig	Sensitizing
Hexamethylene Diisocyanate	Multiple animal species	Sensitizing

Respiratory Sensitization

Name	Species	Value
Talc	Human	Not classified
Toluene Diisocyanate	Human	Sensitizing
Hexamethylene Diisocyanate	Human and animal	Sensitizing

Germ Cell Mutagenicity

Name	Route	Value
Talc	In Vitro	Not mutagenic
Talc	In vivo	Not mutagenic
Titanium Dioxide	In Vitro	Not mutagenic
Titanium Dioxide	In vivo	Not mutagenic
Fumed Silica	In Vitro	Not mutagenic
Zinc Oxide	In Vitro	Some positive data exist, but the data are not sufficient for classification
Zinc Oxide	In vivo	Some positive data exist, but the data are not sufficient for classification
Carbitol Acetate	In Vitro	Not mutagenic
Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic
Toluene Diisocyanate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Heptane	In Vitro	Not mutagenic
(Gamma-Mercaptopropyl)trimethoxysilane	In Vitro	Not mutagenic
Hexamethylene Diisocyanate	In Vitro	Not mutagenic
Hexamethylene Diisocyanate	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Talc	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Titanium Dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium Dioxide	Inhalation	Rat	Carcinogenic
Fumed Silica	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene Diisocyanate	Inhalation	Human and animal	Not carcinogenic
Toluene Diisocyanate	Ingestion	Multiple animal species	Carcinogenic
Hexamethylene Diisocyanate	Inhalation	Rat	Not carcinogenic

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Talc	Ingestion	Not classified for development	Rat	NOAEL 1,600 mg/kg	during organogenesis

Fumed Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Fumed Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Fumed Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Zinc Oxide	Ingestion	Not classified for reproduction and/or development	Multiple animal species	NOAEL 125 mg/kg/day	premating & during gestation
Toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse
Toluene Diisocyanate	Inhalation	Not classified for female reproduction	Rat	NOAEL 0.002 mg/l	2 generation
Toluene Diisocyanate	Inhalation	Not classified for male reproduction	Rat	NOAEL 0.002 mg/l	2 generation
Toluene Diisocyanate	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis
Hexamethylene Diisocyanate	Inhalation	Not classified for female reproduction	Rat	NOAEL 0.002 mg/l	7 weeks
Hexamethylene Diisocyanate	Inhalation	Not classified for development	Rat	NOAEL 0.002 mg/l	7 weeks
Hexamethylene Diisocyanate	Inhalation	Not classified for male reproduction	Rat	NOAEL 0.014 mg/l	4 weeks

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Carbitol Acetate	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	not applicable
Carbitol Acetate	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	not applicable
Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Toluene Diisocyanate	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	occupational exposure
Heptane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Heptane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Heptane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Hexamethylene Diisocyanate	Inhalation	respiratory irritation	May cause respiratory irritation	Human and animal	NOAEL Not available	
Hexamethylene Diisocyanate	Inhalation	blood	Not classified	Human	NOAEL Not available	occupational exposure

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Talc	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Talc	Inhalation	pulmonary fibrosis respiratory system	Not classified	Rat	NOAEL 18 mg/m3	113 weeks
Titanium Dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium Dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Fumed Silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Zinc Oxide	Ingestion	nervous system	Not classified	Rat	NOAEL 600 mg/kg/day	10 days
Zinc Oxide	Ingestion	endocrine system hematopoietic system kidney and/or bladder	Not classified	Other	NOAEL 500 mg/kg/day	6 months
Carbitol Acetate	Inhalation	respiratory system liver immune system kidney and/or bladder	Not classified	Rat	NOAEL 0.48 mg/l	2 weeks
Toluene	Inhalation	auditory system nervous system eyes olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
Toluene	Inhalation	heart liver kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
Toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic system vascular system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	liver kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks
Toluene Diisocyanate	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL 0 mg/l	occupational exposure
Heptane	Inhalation	nervous system	Not classified	Rat	NOAEL 6.15 mg/l	30 weeks
Heptane	Inhalation	peripheral nervous system	Not classified	Rat	NOAEL 12.5 mg/l	16 weeks

Heptane	Inhalation	hematopoietic system kidney and/or bladder	Not classified	Rat	NOAEL 12.2 mg/l	26 weeks
Hexamethylene Diisocyanate	Inhalation	liver kidney and/or bladder	Not classified	Rat	NOAEL 0.002 mg/l	3 weeks
Hexamethylene Diisocyanate	Inhalation	endocrine system	Not classified	Rat	NOAEL 0.0014 mg/l	4 weeks
Hexamethylene Diisocyanate	Inhalation	blood	Not classified	Rat	NOAEL 0.0012 mg/l	2 years
Hexamethylene Diisocyanate	Inhalation	nervous system	Not classified	Rat	NOAEL 0.002 mg/l	7 weeks
Hexamethylene Diisocyanate	Inhalation	heart	Not classified	Rat	NOAEL 0.001 mg/l	90 days

Aspiration Hazard

Name	Value
Toluene	Aspiration hazard
Heptane	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 2 **Flammability:** 1 **Instability:** 1 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document group:	16-3092-0	Version number:	15.03
Issue Date:	2024/10/28	Supersedes Date:	2022/11/11

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca