

# **Safety Data Sheet**

Copyright,2020, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	19-9370-8	Version number:	1.01
Issue Date:	2020/10/16	Supercedes Date:	2019/10/11

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

# **SECTION 1: Identification**

#### 1.1. Product identifier

3M<sup>™</sup> Abrasive Products, 314D, Grades P80 - P400 Utility Cloth

#### **Product Identification Numbers**

ion Numbers			
60-4401-0658-5	60-4401-0659-3	60-4401-0660-1	60-4401-0661-9
60-4401-0663-5	60-4401-0664-3	60-4401-0665-0	60-4401-0666-8
60-4401-0671-8	60-4401-0672-6	60-4401-0673-4	60-4401-0674-2
60-4401-0676-7	60-4401-0677-5	60-4401-0678-3	60-4401-0679-1
60-4401-0681-7	60-4401-0682-5	60-4401-0683-3	60-4401-0684-1
60-4401-0686-6	60-4401-0689-0	60-4401-0690-8	60-4401-0691-6
60-4401-0693-2	60-4401-0694-0	60-4401-0695-7	60-4401-0696-5
60-4401-0698-1	60-4401-0699-9	60-4401-0700-5	60-4401-0701-3
60-4401-0703-9	60-4401-0704-7	60-4401-0705-4	60-4401-0708-8
60-4401-0710-4	60-4401-0711-2	60-4401-0712-0	60-4401-0713-8
60-4401-0715-3	60-4401-0716-1	60-4401-0717-9	60-4401-4244-0
60-4401-4246-5	60-4401-4247-3	60-4401-8823-7	60-4401-8824-5
60-4402-9580-0	60-4403-5289-0	60-4403-5290-8	60-4403-5291-6
60-4403-5293-2	60-4403-5294-0	60-4403-5295-7	60-4403-5296-5
60-4403-5298-1	60-4403-5302-1	60-4403-5303-9	60-4403-5304-7
60-4403-5306-2	60-4403-5307-0	60-4403-5308-8	60-4403-5309-6
60-4403-5311-2	60-4403-5312-0	60-4403-5313-8	60-4403-5314-6
60-4403-5316-1	60-4403-5317-9	60-4403-5318-7	60-4403-5321-1
60-4403-5323-7	60-4403-5324-5	60-4403-5325-2	60-4403-5326-0
60-4403-5328-6	60-4403-5329-4	60-4403-5330-2	60-4403-5331-0
60-4403-5333-6	60-4403-5334-4	60-4403-5335-1	60-4403-5336-9
60-4403-5340-1	60-4403-5341-9	60-4403-5342-7	60-4403-5343-5
60-4403-5345-0	60-4403-5346-8	60-4403-5347-6	60-4403-5348-4
60-4403-5354-2	60-4403-5355-9	60-4403-5356-7	60-4403-5357-5
DC-2729-2626-2	IX-1101-5641-7	IX-1101-5642-5	IX-1101-5643-3
IX-1101-5645-8	IX-1101-5653-2	IX-1101-5654-0	IX-1101-5655-7
	$\begin{array}{c} 60-4401-0658-5\\ 60-4401-0663-5\\ 60-4401-0671-8\\ 60-4401-0671-8\\ 60-4401-0681-7\\ 60-4401-0681-7\\ 60-4401-0693-2\\ 60-4401-0698-1\\ 60-4401-0703-9\\ 60-4401-0710-4\\ 60-4401-0715-3\\ 60-4401-0715-3\\ 60-4401-29580-0\\ 60-4403-5293-2\\ 60-4403-5298-1\\ 60-4403-5298-1\\ 60-4403-5306-2\\ 60-4403-5316-1\\ 60-4403-5328-6\\ 60-4403-5328-6\\ 60-4403-5333-6\\ 60-4403-5333-6\\ 60-4403-5345-0\\ 60-4403-5345-0\\ 60-4403-5354-2\\ DC-2729-2626-2\end{array}$	60-4401-0658-5 $60-4401-0659-3$ $60-4401-0663-5$ $60-4401-0664-3$ $60-4401-0671-8$ $60-4401-0672-6$ $60-4401-067-7$ $60-4401-0677-5$ $60-4401-0681-7$ $60-4401-0682-5$ $60-4401-0686-6$ $60-4401-0689-0$ $60-4401-0693-2$ $60-4401-0694-0$ $60-4401-0698-1$ $60-4401-0699-9$ $60-4401-0703-9$ $60-4401-0704-7$ $60-4401-0710-4$ $60-4401-0711-2$ $60-4401-0715-3$ $60-4401-0716-1$ $60-4401-0715-3$ $60-4401-0716-1$ $60-4402-9580-0$ $60-4403-5294-0$ $60-4403-5298-1$ $60-4403-5302-1$ $60-4403-5311-2$ $60-4403-5312-0$ $60-4403-5316-1$ $60-4403-5312-0$ $60-4403-5328-6$ $60-4403-5328-5$ $60-4403-533-6$ $60-4403-5328-4$ $60-4403-533-6$ $60-4403-5334-4$ $60-4403-5345-0$ $60-4403-5346-8$ $60-4403-5345-2$ $60-4403-5346-8$ $60-4403-5345-2$ $60-4403-5355-9$ $DC-2729-2626-2$ $IX-1101-5641-7$	60-4401-0658-5 $60-4401-0659-3$ $60-4401-0660-1$ $60-4401-0663-5$ $60-4401-0664-3$ $60-4401-0665-0$ $60-4401-0671-8$ $60-4401-0672-6$ $60-4401-0673-4$ $60-4401-067-7$ $60-4401-0677-5$ $60-4401-0678-3$ $60-4401-0681-7$ $60-4401-0682-5$ $60-4401-0683-3$ $60-4401-0685-2$ $60-4401-0682-5$ $60-4401-0690-8$ $60-4401-0693-2$ $60-4401-0694-0$ $60-4401-0695-7$ $60-4401-0698-1$ $60-4401-0704-7$ $60-4401-0705-4$ $60-4401-0703-9$ $60-4401-0714-7$ $60-4401-0712-0$ $60-4401-0715-3$ $60-4401-0716-1$ $60-4401-0712-0$ $60-4401-0715-3$ $60-4401-247-3$ $60-4401-2823-7$ $60-4402-9580-0$ $60-4403-5294-0$ $60-4403-5295-7$ $60-4403-5293-2$ $60-4403-5302-1$ $60-4403-5303-9$ $60-4403-5316-1$ $60-4403-5312-0$ $60-4403-5313-8$ $60-4403-5316-1$ $60-4403-5312-0$ $60-4403-5313-8$ $60-4403-5323-7$ $60-4403-532-5$ $60-4403-533-5$ $60-4403-533-7$ </th

### 1.2. Recommended use and restrictions on use

Intended Use Abrasive Product

**Restrictions on use** Not applicable

## 1.3. Supplier's details

Company:	3M Canada Company	
<b>Division:</b>	Abrasive Systems Division	
Address:	1840 Oxford Street East, Post Office Box 5757, London, Ontario	N6A 4T1
Telephone:	(800) 364-3577	
Website:	www.3M.ca	

## 1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

# **SECTION 2: Hazard identification**

# 2.1. Classification of the substance or mixture

Not classified according to the Canadian Hazardous Products Regulation.

**2.2. Label elements Signal word** Not applicable.

**Symbols** Not applicable.

**Pictograms** Not applicable.

2.3. Other hazards

None known.

94% of the mixture consists of ingredients of unknown acute oral toxicity.

# **SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Cloth Backing	Mixture	25 - 65	Not Applicable
Aluminum Oxide Mineral (non-	1344-28-1	20 - 45	Aluminum oxide (non-fibrous)
fibrous)			
Cured Resin	Mixture	15 - 35	Not Applicable
Filler	471-34-1	0 - 20	Carbonic acid calcium salt (1:1)
Filler	1318-74-7	0.5 - 2	Kaolinite (Al2(Si2O7).2H2O)
Carbon Black	1333-86-4	0.1 - 0.5	Carbon black
Titanium Dioxide	13463-67-7	0.3 - 0.5	Titanium oxide (TiO2)

Carbon black is inextricably bound in this product. Exposure to carbon black is not expected during product use

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

Inhalation:

#### 3M<sup>™</sup> Abrasive Products, 314D, Grades P80 - P400 Utility Cloth

Remove person to fresh air. If you feel unwell, get medical attention.

#### **Skin Contact:**

Wash with soap and water. If signs/symptoms develop, get medical attention.

#### **Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### If Swallowed:

No need for first aid is anticipated.

#### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

# **4.3. Indication of any immediate medical attention and special treatment required**

# Not applicable

# **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

## 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

#### Hazardous Decomposition or By-Products

<u>Substance</u> Carbon monoxide Carbon dioxide <u>Condition</u> During Combustion During Combustion

# 5.3. Special protective actions for fire-fighters

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

# **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Observe precautions from other sections.

#### **6.2.** Environmental precautions

Not applicable.

6.3. Methods and material for containment and cleaning up

Not applicable.

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Avoid breathing of dust created by sanding, grinding or machining. Combustible dust may form by action of this product on another material (substrate). Dust generated from the substrate during use of this product may be explosive if in sufficient concentration with an ignition source. Dust deposits should not be allowed to accumulate on surfaces because of the potential for secondary explosions.

#### 7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

#### **Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	<b>Additional Comments</b>
Aluminum, insoluble compounds	1318-74-7	ACGIH	TWA(respirable fraction):1 mg/m3	
Carbon Black	1333-86-4	ACGIH	TWA(inhalable fraction):3 mg/m3	
Aluminum, insoluble compounds	1344-28-1	ACGIH	TWA(respirable fraction):1 mg/m3	
Titanium Dioxide	13463-67-7		TWA:10 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

## 8.2. Exposure controls

## 8.2.1. Engineering controls

Provide appropriate local exhaust ventilation for sanding, grinding or machining. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Provide local exhaust at process emission sources to control exposure near the source and to prevent the escape of dust into the work area. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

## 8.2.2. Personal protective equipment (PPE)

## Eye/face protection

To minimize the risk of injury to face and eyes, always wear eye and face protection when working at sanding or grinding operations or when near such operations. Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Safety Glasses with side shields

## **Skin/hand protection**

Wear appropriate gloves to minimize risk of injury to skin from contact with dust or physical abrasion from grinding or sanding.

# **Respiratory protection**

Assess exposure concentrations of all materials involved in the work process. Consider material being abraded when determining the appropriate respiratory protection. Select and use appropriate respirators to prevent inhalation overexposure. An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

formation on basic physical and chemical properties		
Physical state	Solid	
Colour	Red	
Odour	Slight Polymeric	
Odour threshold	Not Applicable	
рН	Not Applicable	
Melting point/Freezing point	Not Applicable	
Boiling point	Not Applicable	
Flash Point	Not Applicable	
Evaporation rate	Not Applicable	
Flammability (solid, gas)	Not Classified	
Flammable Limits(LEL)	Not Applicable	
Flammable Limits(UEL)	Not Applicable	
Vapour Pressure	Not Applicable	
Viscosity/Kinematic Viscosity Viscosity/Kinematic	Not Applicable	
Viscosity		
Density	Not Applicable	
Relative density	Not Applicable	
Water solubility	Not Applicable	
Solubility- non-water	Not Applicable	
Partition coefficient: n-octanol/ water	Not Applicable	
Autoignition temperature	Not Applicable	
Decomposition temperature	Not Applicable	
Viscosity/Kinematic Viscosity	Not Applicable	
Volatile Organic Compounds	No Data Available	
Percent volatile	No Data Available	
VOC Less H2O & Exempt Solvents		

## Nanoparticles

This material contains nanoparticles.

# **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

# 10.2. Chemical stability

Stable.

**10.3. Possibility of hazardous reactions** Hazardous polymerization will not occur.

# **10.4. Conditions to avoid** None known.

**10.5. Incompatible materials** None known.

10.6. Hazardous decomposition products <u>Substance</u>

**Condition** 

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

## 11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

## Inhalation:

Dust from grinding, sanding or machining may cause irritation of the respiratory system. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

#### **Skin Contact:**

Mechanical Skin irritation: Signs/symptoms may include abrasion, redness, pain, and itching.

#### **Eye Contact:**

Mechanical eye irritation: Signs/symptoms may include pain, redness, tearing and corneal abrasion. Dust created by grinding, sanding, or machining may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

#### Ingestion:

No health effects are expected.

#### **Carcinogenicity:**

Ingredient	CAS No.	Class Description	Regulation
Carbon Black	1333-86-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Titanium Dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

#### **Additional Information:**

This document covers only the 3M product. For complete assessment, when determining the degree of hazard, the material being abraded must also be considered. This product contains titanium dioxide. Cancer of the lungs has been observed in rats that inhaled high levels of titanium dioxide. No exposure to inhaled titanium dioxide is expected during the normal handling and use of this product. Titanium dioxide was not detected when air sampling was conducted during simulated use of similar products containing titanium dioxide. Therefore, the health effects associated with titanium dioxide are not expected during the normal use of this product.

#### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### **Acute Toxicity**

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Aluminum Oxide Mineral (non-fibrous)	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminum Oxide Mineral (non-fibrous)	Inhalation- Dust/Mist	Rat	LC50 > 2.3 mg/l

# 3M<sup>TM</sup> Abrasive Products, 314D, Grades P80 - P400 Utility Cloth

	(4 hours)		
Aluminum Oxide Mineral (non-fibrous)	Ingestion	Rat	LD50 > 5,000 mg/kg
Filler	Dermal	Rat	LD50 > 2,000 mg/kg
Filler	Inhalation-	Rat	LC50 3 mg/l
	Dust/Mist		-
	(4 hours)		
Filler	Ingestion	Rat	LD50 6,450 mg/kg
Filler	Dermal		LD50 estimated to be $> 5,000 \text{ mg/kg}$
Filler	Ingestion	Human	LD50 > 15,000 mg/kg
Titanium Dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium Dioxide	Inhalation-	Rat	LC50 > 6.82  mg/l
	Dust/Mist		
	(4 hours)		
Titanium Dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
Carbon Black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon Black	Ingestion	Rat	LD50 > 8,000 mg/kg

ATE = acute toxicity estimate

# Skin Corrosion/Irritation

Name	Species	Value
Aluminum Oxide Mineral (non-fibrous)	Rabbit	No significant irritation
Filler	Rabbit	No significant irritation
Filler	Professio	No significant irritation
	nal	
	judgeme	
	nt	
Titanium Dioxide	Rabbit	No significant irritation
Carbon Black	Rabbit	No significant irritation

# Serious Eye Damage/Irritation

Name	Species	Value
Aluminum Oxide Mineral (non-fibrous)	Rabbit	No significant irritation
Filler	Rabbit	No significant irritation
Filler	Professio	No significant irritation
	nal	
	judgeme	
	nt	
Titanium Dioxide	Rabbit	No significant irritation
Carbon Black	Rabbit	No significant irritation

#### **Skin Sensitization**

Name	Species	Value
Titanium Dioxide	Human	Not classified
	and	
	animal	

# **Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

# Germ Cell Mutagenicity

Name	Route	Value
Aluminum Oxide Mineral (non-fibrous)	In Vitro	Not mutagenic
Titanium Dioxide	In Vitro	Not mutagenic
Titanium Dioxide	In vivo	Not mutagenic
Carbon Black	In Vitro	Not mutagenic
Carbon Black	In vivo	Some positive data exist, but the data are not
		sufficient for classification

# Carcinogenicity

# 3M<sup>TM</sup> Abrasive Products, 314D, Grades P80 - P400 Utility Cloth

Name	Route	Species	Value
Aluminum Oxide Mineral (non-fibrous)	Inhalation	Rat	Not carcinogenic
Filler	Inhalation	Multiple	Not carcinogenic
		animal	
		species	
Titanium Dioxide	Ingestion	Multiple	Not carcinogenic
		animal	
		species	
Titanium Dioxide	Inhalation	Rat	Carcinogenic
Carbon Black	Dermal	Mouse	Not carcinogenic
Carbon Black	Ingestion	Mouse	Not carcinogenic
Carbon Black	Inhalation	Rat	Carcinogenic

# **Reproductive Toxicity**

# **Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Filler	Ingestion	Not classified for development	Rat	NOAEL 625 mg/kg/day	premating & during gestation

# Target Organ(s)

## Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Filler	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.812 mg/l	90 minutes

# Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Aluminum Oxide Mineral (non-fibrous)	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminum Oxide Mineral (non-fibrous)	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Filler	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Filler	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL NA	occupational exposure
Filler	Inhalation	pulmonary fibrosis	Not classified	Rat	NOAEL Not available	
Titanium Dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium Dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Carbon Black	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure

#### **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

# Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

No data available.

# **SECTION 13: Disposal considerations**

# 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Prior to disposal, consult all applicable authorities and regulations to insure proper classification. The substrate that was abraded must be considered as a factor in the disposal method for this product. Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product may be placed in a landfill properly designed for industrial waste.

# **SECTION 14: Transport Information**

Not regulated per U.S. DOT, IATA or IMO.

These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling, or marking requirements. The original 3M package is certified for Canadian ground shipment only. If you are shipping by air or ocean, the package may not meet applicable regulatory requirements.

# **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## **Global inventory status**

Contact 3M for more information.

# **SECTION 16: Other information**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 0 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

# HMIS Hazard ClassificationHealth:0Flammability:1Physical Hazard:0Personal Protection:X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

## 3M<sup>™</sup> Abrasive Products, 314D, Grades P80 - P400 Utility Cloth

Document group:	19-9370-8	Version number:	1.01
Issue Date:	2020/10/16	Supercedes Date:	2019/10/11

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

## 3M Canada SDSs are available at www.3M.ca