

Safety Data Sheet

Copyright, 2024, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 18-3703-8
 Version number:
 14.00

 Issue Date:
 2024/01/05
 Supercedes Date:
 2023/02/09

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3MTM Process Colour 886I Orange

Product Identification Numbers

42-0019-9657-0 75-0300-4995-3 75-0301-1090-4 LR-0000-0151-9

1.2. Recommended use and restrictions on use

Intended Use

Ink

Restrictions on use

Not applicable

1.3. Supplier's details

Company: 3M Canada Company

Division: Transportation Safety Division

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

Telephone: (800) 364-3577 **Website:** www.3M.ca

1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Flammable Liquid: Category 3.

Serious Eye Damage/Irritation: Category 1.

Skin Sensitizer: Category 1.

Reproductive Toxicity: Category 1B. Carcinogenicity: Category 1A.

2.2. Label elements

Signal word

Danger

Symbols

Flame Corrosion | Exclamation mark | Health Hazard |





Hazard statements

Flammable liquid and vapour.

Causes serious eye damage. May cause an allergic skin reaction. May damage fertility or the unborn child. May cause cancer.

Precautionary statements

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Use non-sparking tools. Take action to prevent static discharges. Keep container tightly closed. Use explosion-proof electrical/ventilating/lighting equipment. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear protective gloves and eye/face protection. Contaminated work clothing must not be allowed out of the workplace.

Response:

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTRE or doctor/physician. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage:

Store in a well-ventilated place. Keep cool. Store locked up.

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

None known.

16% of the mixture consists of ingredients of unknown acute oral toxicity.

16% of the mixture consists of ingredients of unknown acute dermal toxicity.

66% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Dipropylene glycol methyl ether	88917-22-0	30 - 60	Propanol, 1(or 2)-(2-
acetate			methoxymethylethoxy)-, acetate (9CI)
2-Propenoic acid, 2-methyl-,	28262-63-7	10 - 30	2-Propenoic acid, 2-methyl-, polymer with
polymer with butyl 2-methyl-2-			butyl 2-methyl-2-propenoate and methyl 2-
propenoate and methyl 2-			methyl-2-propenoate

methyl-2-propenoate			
Acrylic polymers	Trade Secret	10 - 30	Not Applicable
1-Methoxy-2-propyl acetate	108-65-6	3 - 7	2-Propanol, 1-methoxy-, acetate
Cyclohexanone	108-94-1	3 - 7 Trade Secret *	Cyclohexanone
Vinyl polymer	Trade Secret	1 - 5	Not Applicable
Organic pigment	Trade Secret	0.5 - 2	Not Applicable
Nickel, 5,5'-azobis-2,4,6, (1H,3H,5H)-pyrimidinetrione	68511-62-6	0.1 - 1.0 Trade Secret *	Nickel, 5,5'-azobis-2,4,6(1H,3H,5H)- pyrimidinetrione complexes
complexes			pyrimameurone complexes
Xylene	1330-20-7	< 0.9	Dimethylbenzene
"2,3,4,5-tetrachloro-6-cyanobenzoic acid, methyl ester, reaction products with 2-methyl-1,3-benzenediamine and sodium methoxide"	106276-79-3	< 0.7	Benzoic acid, 2,3,4,5-tetrachloro-6-cyano-, methyl ester, reaction products with 2-methyl-1,3-benzenediamine and sodium methoxide
"3-dodecyl-1-(2,2,6,6- tetramethyl-4-piperidinyl) -2,5- pyrrolidinedione "	79720-19-7	< 0.6	2,5-Pyrrolidinedione, 3-dodecyl-1-(2,2,6,6-tetramethyl-4-piperidinyl)-
N-Butyl methacrylate	97-88-1	< 0.4	2-Propenoic acid, 2-methyl-, butyl ester
Ethylbenzene	100-41-4	< 0.3	Benzene, ethyl-
(3',4'-epoxycyclohexylmethyl) 3,4- epoxycyclohexanecarboxylate	2386-87-0	< 0.2	7-Oxabicyclo[4.1.0]heptane-3-carboxylic acid, 7-oxabicyclo[4.1.0]hept-3-ylmethyl ester
m-Xylene	108-38-3	< 0.2	No Data Available
Toluene	108-88-3	0.0 - 0.13	No Data Available
p-Xylene	106-42-3	< 0.07	No Data Available
o-Xylene	95-47-6	< 0.05	No Data Available
Nickel salts of naphthenic acids	61788-71-4	< 0.02	Naphthenic acids, nickel salts

Vinyl polymer is a non-hazardous Trade Secret material according to WHMIS criteria. Organic pigment is a non-hazardous Trade Secret material according to WHMIS criteria. Acrylic polymers is a non-hazardous Trade Secret material according to WHMIS criteria.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing,

^{*}The actual concentration of this ingredient has been withheld as a trade secret.

3MTM Process Colour 886I Orange

ulcerations, and significantly impaired or loss of vision).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode. Exposure to extreme heat can give rise to thermal decomposition.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Hydrocarbons	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Chloride	During Combustion
Hydrogen Fluoride	During Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire extinguishing foam that is resistant to polar solvents. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not breathe thermal decomposition products. For industrial or professional use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot

 $\mathbf{p} = \mathbf{A} \cdot \mathbf{c}$

surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (gloves, respirators, etc.) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Ethylbenzene	100-41-4	ACGIH	TWA:20 ppm	
p-Xylene	106-42-3	ACGIH	TWA:20 ppm	
m-Xylene	108-38-3	ACGIH	TWA:20 ppm	
1-Methoxy-2-propyl acetate	108-65-6	AIHA	TWA:50 ppm	
Toluene	108-88-3	ACGIH	TWA:20 ppm	
Cyclohexanone	108-94-1	ACGIH	TWA:20 ppm;STEL:50 ppm	Danger of cutaneous absorption
Xylene	1330-20-7	ACGIH	TWA:20 ppm	
o-Xylene	95-47-6	ACGIH	TWA:20 ppm	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

For those situations where the material might be exposed to extreme overheating due to misuse or equipment failure, use with appropriate local exhaust ventilation sufficient to maintain levels of thermal decomposition products below their exposure guidelines. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

For those situations where the material might be exposed to extreme overheating due to misuse or equipment failure, use a positive pressure supplied-air respirator.

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

information on basic physical and chemical properties		
Physical state	Liquid	
Specific Physical Form:	Liquid	
Colour	Orange	
Odour	Sweet Ether	
Odour threshold	No Data Available	
pH	Not Applicable	
Melting point/Freezing point	Not Applicable	
Boiling point	>=140 °C	
Flash Point	42.2 °C [Test Method: Tagliabue Closed Cup]	
Evaporation rate	<=0.4 [<i>Ref Std</i> :BUOAC=1]	
Flammability (solid, gas)	Not Applicable	
Flammable Limits(LEL)	1.1 % volume	
Flammable Limits(UEL)	8.6 % volume	
Vapour Pressure	<=493.3 Pa [@ 20 °C]	
Vapour Density and/or Relative Vapour Density	No Data Available	
Density	0.95 g/ml	
Relative density	0.95 [Ref Std:WATER=1]	
Water solubility	No Data Available	
Solubility- non-water	No Data Available	
Partition coefficient: n-octanol/ water	No Data Available	
Autoignition temperature	No Data Available	
Decomposition temperature	No Data Available	
Viscosity/Kinematic Viscosity	1,000 - 1,200 mPa-s [Details:DTM-300 (# 3 @ 30 rmp)]	
Volatile Organic Compounds	600 - 800 g/l [Details: As Packaged.]	
Percent volatile	65 - 75 %	
VOC Less H2O & Exempt Solvents	No Data Available	

Page: 6 of 21

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Sparks and/or flames

10.5. Incompatible materials

Strong acids

Strong oxidizing agents

10.6. Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

Extreme heat arising from situations such as misuse or equipment failure can generate hydrogen fluoride as a decomposition product.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching. May cause additional health effects (see below).

Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea. May cause additional health effects (see below).

Additional Health Effects:

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
Nickel Compounds (except alloys)	61788-71-4	Known To Be Human Carcinogen.	National Toxicology Program Carcinogens
Nickel Compounds (except alloys)	68511-62-6	Known To Be Human Carcinogen.	National Toxicology Program Carcinogens
Nickel compounds	61788-71-4	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
Nickel compounds	68511-62-6	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
Butyl methacrylate	97-88-1	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Ethylbenzene	100-41-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation- Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Dipropylene glycol methyl ether acetate	Dermal	Rat	LD50 > 2,000 mg/kg
Dipropylene glycol methyl ether acetate	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 5.7 mg/l
Dipropylene glycol methyl ether acetate	Ingestion	Rat	LD50 > 5,000 mg/kg
2-Propenoic acid, 2-methyl-, polymer with butyl 2-methyl-2- propenoate and methyl 2-methyl-2-propenoate	Dermal		LD50 estimated to be > 5,000 mg/kg
2-Propenoic acid, 2-methyl-, polymer with butyl 2-methyl-2- propenoate and methyl 2-methyl-2-propenoate	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Cyclohexanone	Dermal	Rabbit	LD50 >794, <3160 mg/kg
Cyclohexanone	Inhalation- Vapor (4 hours)	Rat	LC50 > 6.2 mg/l
Cyclohexanone	Ingestion	Rat	LD50 1,296 mg/kg
1-Methoxy-2-propyl acetate	Dermal	Rabbit	LD50 > 5,000 mg/kg
1-Methoxy-2-propyl acetate	Inhalation- Vapor (4 hours)	Rat	LC50 > 28.8 mg/l
1-Methoxy-2-propyl acetate	Ingestion	Rat	LD50 8,532 mg/kg
Vinyl polymer	Dermal	Rabbit	LD50 > 8,000 mg/kg
Vinyl polymer	Ingestion	Rat	LD50 > 8,000 mg/kg
Organic pigment	Dermal	Rat	LD50 > 2,000 mg/kg
Organic pigment	Ingestion	Rat	LD50 > 5,000 mg/kg
Xylene	Dermal	Rabbit	LD50 > 4,200 mg/kg
Xylene	Inhalation- Vapor (4 hours)	Rat	LC50 29 mg/l
Xylene	Ingestion	Rat	LD50 3,523 mg/kg
"2,3,4,5-tetrachloro-6-cyanobenzoic acid, methyl ester, reaction products with 2-methyl-1,3-benzenediamine and sodium methoxide"	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 1.04 mg/l
"2,3,4,5-tetrachloro-6-cyanobenzoic acid, methyl ester, reaction products with 2-methyl-1,3-benzenediamine and sodium	Ingestion	Rat	LD50 > 5,000 mg/kg

methoxide "		1	
"2,3,4,5-tetrachloro-6-cyanobenzoic acid, methyl ester, reaction	Dermal	similar	LD50 estimated to be > 5,000 mg/kg
products with 2-methyl-1,3-benzenediamine and sodium	Dermai	health	LD50 estimated to be > 5,000 mg/kg
methoxide "		hazards	
"3-dodecyl-1-(2,2,6,6-tetramethyl-4-piperidinyl) -2,5-	Dermal	Rabbit	LD50 > 2,000 mg/kg
pvrrolidinedione "	Deliliai	Kabbit	LD30 > 2,000 Hig/kg
"3-dodecyl-1-(2,2,6,6-tetramethyl-4-piperidinyl) -2,5-	Inhalation-	Rat	LC50 > 5 mg/l
pyrrolidinedione "	Dust/Mist	Rat	EC30 > 3 mg/1
pyrronumeurone	(4 hours)		
"3-dodecyl-1-(2,2,6,6-tetramethyl-4-piperidinyl) -2,5-	Ingestion	Rat	LD50 > 2,000 mg/kg
pyrrolidinedione "			
Nickel, 5,5'-azobis-2,4,6, (1H,3H,5H)-pyrimidinetrione	Dermal	Professio	LD50 estimated to be > 5,000 mg/kg
complexes		nal	, , , , , , , , , , , , , , , , , , , ,
		judgeme	
		nt	
Nickel, 5,5'-azobis-2,4,6, (1H,3H,5H)-pyrimidinetrione	Inhalation-	Rat	LC50 > 5.222 mg/l
complexes	Dust/Mist		
	(4 hours)		
Nickel, 5,5'-azobis-2,4,6, (1H,3H,5H)-pyrimidinetrione	Ingestion	Rat	LD50 > 5,000 mg/kg
complexes	ļ		
Ethylbenzene	Dermal	Rabbit	LD50 15,433 mg/kg
Ethylbenzene	Inhalation-	Rat	LC50 17.4 mg/l
	Vapor (4		
	hours)		
Ethylbenzene	Ingestion	Rat	LD50 4,769 mg/kg
N-Butyl methacrylate	Dermal	Rabbit	LD50 > 2,000 mg/kg
N-Butyl methacrylate	Inhalation-	Rat	LC50 > 27 mg/l
	Dust/Mist		
	(4 hours)		
N-Butyl methacrylate	Ingestion	Rat	LD50 > 2,000 mg/kg
(3',4'-epoxycyclohexylmethyl) 3,4-epoxycyclohexanecarboxylate	Dermal	Rat	LD50 > 2,000 mg/kg
(3',4'-epoxycyclohexylmethyl) 3,4-epoxycyclohexanecarboxylate	Inhalation-	Rat	LC50 > 5.19 mg/l
	Dust/Mist		
(21.41	(4 hours)	D-4	LD50 5 000 //
(3',4'-epoxycyclohexylmethyl) 3,4-epoxycyclohexanecarboxylate	Ingestion Dermal	Rat Rabbit	LD50 5,000 mg/kg
m-Xylene		1	LD50 > 4,200 mg/kg
m-Xylene	Inhalation-	Rat	LC50 29 mg/l
	Vapor (4 hours)		
m-Xylene	Ingestion	Rat	LD50 3,523 mg/kg
Toluene	Dermal	Rat	LD50 5,325 Hg/kg LD50 12,000 mg/kg
Toluene	Inhalation-	Rat	LC50 30 mg/l
TOTACHE	Vapor (4	Nat	LC30 30 Hig/I
	hours)		
Toluene	Ingestion	Rat	LD50 5,550 mg/kg
p-Xylene	Dermal	Rabbit	LD50 > 4,200 mg/kg
p-Xylene	Inhalation-	Rat	LC50 29 mg/l
p rijiono	Vapor (4	Tut	2000 27 mg/1
	hours)		
p-Xylene	Ingestion	Rat	LD50 3,523 mg/kg
o-Xylene	Dermal	Rabbit	LD50 > 4,200 mg/kg
o-Xylene	Inhalation-	Rat	LC50 29 mg/l
7 - 7	Vapor (4		
	hours)		
o-Xylene	Ingestion	Rat	LD50 3,523 mg/kg
Nickel salts of naphthenic acids	Ingestion	Rat	LD50 419 mg/kg
ATE = aguta taviaity agtimata	-0		

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Skiii Cultusiuii/II I itatiuii			
Name	Species	Value	
Dipropylene glycol methyl ether acetate	Rabbit	No significant irritation	
Cyclohexanone	Rabbit	Irritant	
1-Methoxy-2-propyl acetate	Rabbit	No significant irritation	
Vinyl polymer	Professio	No significant irritation	
	nal		

Page: 9 of 21

	judgeme	
	nt	
Organic pigment	Rabbit	No significant irritation
Xylene	Rabbit	Mild irritant
"2,3,4,5-tetrachloro-6-cyanobenzoic acid, methyl ester, reaction products with 2-	Rabbit	No significant irritation
methyl-1,3-benzenediamine and sodium methoxide "		
"3-dodecyl-1-(2,2,6,6-tetramethyl-4-piperidinyl) -2,5-pyrrolidinedione	Rabbit	Corrosive
Nickel, 5,5'-azobis-2,4,6, (1H,3H,5H)-pyrimidinetrione complexes	Rabbit	No significant irritation
Ethylbenzene	Rabbit	Mild irritant
N-Butyl methacrylate	Rabbit	Irritant
(3',4'-epoxycyclohexylmethyl) 3,4-epoxycyclohexanecarboxylate	Rabbit	Minimal irritation
m-Xylene	Rabbit	Mild irritant
Toluene	Rabbit	Irritant
p-Xylene	Rabbit	Mild irritant
o-Xylene	Rabbit	Mild irritant
Nickel salts of naphthenic acids	Professio	Minimal irritation
	nal	
	judgeme	
	nt	

Serious Eye Damage/Irritation

Name	Species	Value
Dipropylene glycol methyl ether acetate	Rabbit	No significant irritation
Cyclohexanone	In vitro	Corrosive
	data	
1-Methoxy-2-propyl acetate	Rabbit	Mild irritant
Vinyl polymer	Professio	No significant irritation
	nal	
	judgeme	
	nt	
Organic pigment	Rabbit	No significant irritation
Xylene	Rabbit	Mild irritant
"2,3,4,5-tetrachloro-6-cyanobenzoic acid, methyl ester, reaction products with 2-	Rabbit	No significant irritation
methyl-1,3-benzenediamine and sodium methoxide "		
"3-dodecyl-1-(2,2,6,6-tetramethyl-4-piperidinyl) -2,5-pyrrolidinedione	Rabbit	Corrosive
Nickel, 5,5'-azobis-2,4,6, (1H,3H,5H)-pyrimidinetrione complexes	Rabbit	No significant irritation
Ethylbenzene	Rabbit	Moderate irritant
N-Butyl methacrylate	Rabbit	Mild irritant
(3',4'-epoxycyclohexylmethyl) 3,4-epoxycyclohexanecarboxylate	Rabbit	Mild irritant
m-Xylene	Rabbit	Mild irritant
Toluene	Rabbit	Moderate irritant
p-Xylene	Rabbit	Mild irritant
o-Xylene	Rabbit	Mild irritant
Nickel salts of naphthenic acids	Professio	Mild irritant
-	nal	
	judgeme	
	nt	

Skin Sensitization

Skin Sensitization		
Name	Species	Value
Dipropylene glycol methyl ether acetate	Guinea	Not classified
	pig	
Cyclohexanone	Guinea	Not classified
	pig	
1-Methoxy-2-propyl acetate	Guinea	Not classified
	pig	
Organic pigment	Mouse	Not classified
"2,3,4,5-tetrachloro-6-cyanobenzoic acid, methyl ester, reaction products with 2-	Mouse	Not classified
methyl-1,3-benzenediamine and sodium methoxide "		
Nickel, 5,5'-azobis-2,4,6, (1H,3H,5H)-pyrimidinetrione complexes	similar	Sensitizing
	compoun	
	ds	
Ethylbenzene	Human	Not classified
N-Butyl methacrylate	Guinea	Sensitizing

Page: 10 of 21

3MTM Process Colour 886I Orange

	pig	
(3',4'-epoxycyclohexylmethyl) 3,4-epoxycyclohexanecarboxylate	Guinea	Sensitizing
	pig	
Toluene	Guinea	Not classified
	pig	
Nickel salts of naphthenic acids	similar	Sensitizing
	compoun	
	ds	

Respiratory Sensitization

Name	Species	Value
Nickel salts of naphthenic acids	Professio nal judgeme nt	Sensitizing

Germ Cell Mutagenicity

Name	Route	Value
Dipropylene glycol methyl ether acetate	In Vitro	Not mutagenic
Dipropylene glycol methyl ether acetate	In vivo	Not mutagenic
Cyclohexanone	In vivo	Not mutagenic
Cyclohexanone	In Vitro	Some positive data exist, but the data are not sufficient for classification
1-Methoxy-2-propyl acetate	In Vitro	Not mutagenic
Organic pigment	In Vitro	Not mutagenic
Xylene	In Vitro	Not mutagenic
Xylene	In vivo	Not mutagenic
"2,3,4,5-tetrachloro-6-cyanobenzoic acid, methyl ester, reaction products with 2-methyl-1,3-benzenediamine and sodium methoxide"	In Vitro	Not mutagenic
"3-dodecyl-1-(2,2,6,6-tetramethyl-4-piperidinyl) -2,5-pyrrolidinedione	In Vitro	Not mutagenic
Nickel, 5,5'-azobis-2,4,6, (1H,3H,5H)-pyrimidinetrione complexes	In Vitro	Not mutagenic
Ethylbenzene	In vivo	Not mutagenic
Ethylbenzene	In Vitro	Some positive data exist, but the data are not sufficient for classification
N-Butyl methacrylate	In Vitro	Not mutagenic
N-Butyl methacrylate	In vivo	Not mutagenic
(3',4'-epoxycyclohexylmethyl) 3,4-epoxycyclohexanecarboxylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
(3',4'-epoxycyclohexylmethyl) 3,4-epoxycyclohexanecarboxylate	In vivo	Some positive data exist, but the data are not sufficient for classification
m-Xylene	In Vitro	Not mutagenic
m-Xylene	In vivo	Not mutagenic
Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic
p-Xylene	In Vitro	Not mutagenic
p-Xylene	In vivo	Not mutagenic
o-Xylene	In Vitro	Not mutagenic
o-Xylene	In vivo	Not mutagenic
Nickel salts of naphthenic acids	In Vitro	Some positive data exist, but the data are not sufficient for classification
Nickel salts of naphthenic acids	In vivo	Mutagenic

Carcinogenicity

Name	Route	Species	Value
Cyclohexanone	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Xylene	Dermal	Rat	Not carcinogenic
Xylene	Ingestion	Multiple animal species	Not carcinogenic
Xylene	Inhalation	Human	Some positive data exist, but the data are not

Page: 11 of 21

			sufficient for classification
Nickel, 5,5'-azobis-2,4,6, (1H,3H,5H)-pyrimidinetrione complexes	Not Specified	similar compoun ds	Carcinogenic
Ethylbenzene	Inhalation	Multiple animal species	Carcinogenic
N-Butyl methacrylate	Inhalation	Multiple animal species	Carcinogenic
(3',4'-epoxycyclohexylmethyl) 3,4-epoxycyclohexanecarboxylate	Dermal	Mouse	Not carcinogenic
m-Xylene	Dermal	Rat	Not carcinogenic
m-Xylene	Ingestion	Multiple animal species	Not carcinogenic
m-Xylene	Inhalation	Human	Some positive data exist, but the data are not sufficient for classification
Toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
p-Xylene	Dermal	Rat	Not carcinogenic
p-Xylene	Ingestion	Multiple animal species	Not carcinogenic
p-Xylene	Inhalation	Human	Some positive data exist, but the data are not sufficient for classification
o-Xylene	Dermal	Rat	Not carcinogenic
o-Xylene	Ingestion	Multiple animal species	Not carcinogenic
o-Xylene	Inhalation	Human	Some positive data exist, but the data are not sufficient for classification
Nickel salts of naphthenic acids	Inhalation	similar compoun ds	Carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Cyclohexanone	Inhalation	Not classified for female reproduction	Rat	NOAEL 4 mg/l	2 generation
Cyclohexanone	Inhalation	Not classified for male reproduction	Rat	NOAEL 2 mg/l	2 generation
Cyclohexanone	Ingestion	Not classified for development	Mouse	LOAEL 1,100 mg/kg/day	during organogenesi s
Cyclohexanone	Inhalation	Not classified for development	Rat	NOAEL 2 mg/l	2 generation
1-Methoxy-2-propyl acetate	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
1-Methoxy-2-propyl acetate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
1-Methoxy-2-propyl acetate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
1-Methoxy-2-propyl acetate	Inhalation	Not classified for development	Rat	NOAEL 21.6 mg/l	during organogenesi s
Organic pigment	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000	premating

Page: 12 of 21

Organic pigment	Ingestion	Not classified for male reproduction	Rat	mg/kg/day NOAEL 1,000	into lactation 28 days
Organic pigment	Ingestion	Not classified for development	Rat	mg/kg/day NOAEL 1,000	premating
		_		mg/kg/day	into lactation
Xylene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Xylene	Ingestion	Not classified for development	Mouse	NOAEL Not available	during organogenesi s
Xylene	Inhalation	Not classified for development	Multiple animal species	NOAEL Not available	during gestation
Nickel, 5,5'-azobis-2,4,6, (1H,3H,5H)- pyrimidinetrione complexes	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation
Ethylbenzene	Inhalation	Not classified for development	Rat	NOAEL 4.3 mg/l	premating & during gestation
N-Butyl methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	44 days
N-Butyl methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 300 mg/kg/day	premating & during gestation
N-Butyl methacrylate	Ingestion	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during gestation
N-Butyl methacrylate	Inhalation	Not classified for development	Rat	NOAEL 1.8 mg/l	during gestation
(3',4'-epoxycyclohexylmethyl) 3,4- epoxycyclohexanecarboxylate	Ingestion	Not classified for development	Rat	NOAEL 125 mg/kg/day	during gestation
m-Xylene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
m-Xylene	Ingestion	Not classified for development	Mouse	NOAEL Not available	during organogenesi s
m-Xylene	Inhalation	Not classified for development	Multiple animal species	NOAEL Not available	during gestation
Toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse
p-Xylene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
p-Xylene	Ingestion	Not classified for development	Mouse	NOAEL Not available	during organogenesi s
p-Xylene	Inhalation	Not classified for development	Multiple animal species	NOAEL Not available	during gestation
o-Xylene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
o-Xylene	Ingestion	Not classified for development	Mouse	NOAEL Not available	during organogenesi s
o-Xylene	Inhalation	Not classified for development	Multiple animal species	NOAEL Not available	during gestation
Nickel salts of naphthenic acids	Ingestion	Toxic to development	similar compoun ds	NOAEL not available	2 generation

Lactation

Name	Route	Species	Value
Xylene	Ingestion	Mouse	Not classified for effects on or via lactation
m-Xylene	Ingestion	Mouse	Not classified for effects on or via lactation
p-Xylene	Ingestion	Mouse	Not classified for effects on or via lactation
o-Xylene	Ingestion	Mouse	Not classified for effects on or via lactation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Cyclohexanone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Guinea pig	LOAEL 16.1 mg/l	6 hours
Cyclohexanone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Cyclohexanone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professio nal judgeme nt	NOAEL Not available	
1-Methoxy-2-propyl acetate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
1-Methoxy-2-propyl acetate	Ingestion	central nervous system depression	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL not available	
Xylene	Inhalation	auditory system	Causes damage to organs	Rat	LOAEL 6.3 mg/l	8 hours
Xylene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Xylene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Xylene	Inhalation	eyes	Not classified	Rat	NOAEL 3.5 mg/l	not available
Xylene	Inhalation	liver	Not classified	Multiple animal species	NOAEL Not available	
Xylene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	
Xylene	Ingestion	eyes	Not classified	Rat	NOAEL 250 mg/kg	not applicable
"3-dodecyl-1-(2,2,6,6- tetramethyl-4-piperidinyl) - 2,5-pyrrolidinedione "	Inhalation	respiratory irritation	May cause respiratory irritation	similar health hazards	NOAEL Not available	
Ethylbenzene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Ethylbenzene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	
Ethylbenzene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professio nal judgeme nt	NOAEL Not available	
N-Butyl methacrylate	Inhalation	respiratory irritation	May cause respiratory irritation		NOAEL Not available	
m-Xylene	Inhalation	auditory system	Causes damage to organs	Rat	LOAEL 6.3 mg/l	8 hours
m-Xylene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
m-Xylene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
m-Xylene	Inhalation	eyes	Not classified	Rat	NOAEL 3.5 mg/l	not available

m-Xylene	Inhalation	liver	Not classified	Multiple animal species	NOAEL Not available	
m-Xylene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	
m-Xylene	Ingestion	eyes	Not classified	Rat	NOAEL 250 mg/kg	not applicable
Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
p-Xylene	Inhalation	auditory system	Causes damage to organs	Rat	LOAEL 6.3 mg/l	8 hours
p-Xylene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
p-Xylene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
p-Xylene	Inhalation	eyes	Not classified	Rat	NOAEL 3.5 mg/l	not available
p-Xylene	Inhalation	liver	Not classified	Multiple animal species	NOAEL Not available	
p-Xylene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	
p-Xylene	Ingestion	eyes	Not classified	Rat	NOAEL 250 mg/kg	not applicable
o-Xylene	Inhalation	auditory system	Causes damage to organs	Rat	LOAEL 6.3 mg/l	8 hours
o-Xylene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
o-Xylene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
o-Xylene	Inhalation	eyes	Not classified	Rat	NOAEL 3.5 mg/l	not available
o-Xylene	Inhalation	liver	Not classified	Multiple animal species	NOAEL Not available	
o-Xylene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	
o-Xylene	Ingestion	eyes	Not classified	Rat	NOAEL 250 mg/kg	not applicable

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Dipropylene glycol methyl ether acetate	Ingestion	liver heart endocrine system hematopoietic system kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	4 weeks
Cyclohexanone	Inhalation	liver kidney and/or bladder	Not classified	Rabbit	NOAEL 0.76 mg/l	50 days
Cyclohexanone	Ingestion	liver	Not classified	Mouse	NOAEL 4,800 mg/kg/day	90 days
1-Methoxy-2-propyl acetate	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 16.2 mg/l	9 days

Page: 15 of 21

1-Methoxy-2-propyl acetate	Inhalation	olfactory system	Not classified	Mouse	LOAEL 1.62 mg/l	9 days
1-Methoxy-2-propyl acetate	Inhalation	blood	Not classified	Multiple animal species	NOAEL 16.2 mg/l	9 days
1-Methoxy-2-propyl acetate	Ingestion	endocrine system	Not classified	Rat	NOAEL 1,000 mg/kg/day	44 days
Organic pigment	Ingestion	heart endocrine system gastrointestinal tract hematopoietic system liver immune system nervous system kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Xylene	Inhalation	nervous system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.4 mg/l	4 weeks
Xylene	Inhalation	auditory system	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 7.8 mg/l	5 days
Xylene	Inhalation	liver	Not classified	Multiple animal species	NOAEL Not available	
Xylene	Inhalation	heart endocrine system gastrointestinal tract hematopoietic system muscles kidney and/or bladder respiratory system	Not classified	Multiple animal species	NOAEL 3.5 mg/l	13 weeks
Xylene	Ingestion	auditory system	Not classified	Rat	NOAEL 900 mg/kg/day	2 weeks
Xylene	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,500 mg/kg/day	90 days
Xylene	Ingestion	liver	Not classified	Multiple animal species	NOAEL Not available	
Xylene	Ingestion	heart skin endocrine system bone, teeth, nails, and/or hair hematopoietic system immune system nervous system respiratory system	Not classified	Mouse	NOAEL 1,000 mg/kg/day	103 weeks
Nickel, 5,5'-azobis-2,4,6, (1H,3H,5H)- pyrimidinetrione complexes	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Ethylbenzene	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	2 years
Ethylbenzene	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 1.1 mg/l	103 weeks
Ethylbenzene	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 3.4 mg/l	28 days
Ethylbenzene	Inhalation	auditory system	Not classified	Rat	NOAEL 2.4 mg/l	5 days
Ethylbenzene	Inhalation	endocrine system	Not classified	Mouse	NOAEL 3.3 mg/l	103 weeks
Ethylbenzene	Inhalation	gastrointestinal tract	Not classified	Rat	NOAEL 3.3	2 years

					mg/l	
Ethylbenzene	Inhalation	bone, teeth, nails, and/or hair muscles	Not classified	Multiple animal species	NOAEL 4.2 mg/l	90 days
Ethylbenzene	Inhalation	heart immune system respiratory system	Not classified	Multiple animal species	NOAEL 3.3 mg/l	2 years
Ethylbenzene	Ingestion	liver kidney and/or bladder	Not classified	Rat	NOAEL 680 mg/kg/day	6 months
N-Butyl methacrylate	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 11 mg/l	28 days
N-Butyl methacrylate	Inhalation	olfactory system	Not classified	Rat	NOAEL 1.8 mg/l	28 days
N-Butyl methacrylate	Inhalation	heart endocrine system hematopoietic system liver nervous system respiratory system	Not classified	Rat	NOAEL 11 mg/l	28 days
N-Butyl methacrylate	Ingestion	olfactory system	Not classified	Rat	NOAEL 60 mg/kg/day	90 days
N-Butyl methacrylate	Ingestion	endocrine system hematopoietic system liver nervous system kidney and/or bladder heart immune system	Not classified	Rat	NOAEL 360 mg/kg/day	90 days
(3',4'- epoxycyclohexylmethyl) 3,4- epoxycyclohexanecarboxyl ate	Ingestion	olfactory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 50 mg/kg/day	91 days
(3',4'- epoxycyclohexylmethyl) 3,4- epoxycyclohexanecarboxyl ate	Ingestion	liver kidney and/or bladder heart skin endocrine system gastrointestinal tract hematopoietic system immune system nervous system eyes respiratory system vascular system	Not classified	Rat	NOAEL 500 mg/kg/day	91 days
m-Xylene	Inhalation	nervous system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.4 mg/l	4 weeks
m-Xylene	Inhalation	auditory system	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 7.8 mg/l	5 days
m-Xylene	Inhalation	liver	Not classified	Multiple animal species	NOAEL Not available	
m-Xylene	Inhalation	heart endocrine system gastrointestinal tract hematopoietic system muscles kidney and/or bladder respiratory system	Not classified	Multiple animal species	NOAEL 3.5 mg/l	13 weeks
m-Xylene	Ingestion	auditory system	Not classified	Rat	NOAEL 900 mg/kg/day	2 weeks
m-Xylene	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,500 mg/kg/day	90 days
m-Xylene	Ingestion	liver	Not classified	Multiple animal species	NOAEL Not available	
m-Xylene	Ingestion	heart skin	Not classified	Mouse	NOAEL	103 weeks

Page: 17 of 21

p-Xylene p-Xylene	Ingestion Ingestion	kidney and/or bladder respiratory system auditory system kidney and/or	Not classified Not classified	Rat Rat	NOAEL 900 mg/kg/day NOAEL	2 weeks
p-Xylene p-Xylene	Inhalation Inhalation	heart endocrine system gastrointestinal tract hematopoietic system muscles	Not classified Not classified	Multiple animal species Multiple animal species	NOAEL Not available NOAEL 3.5 mg/l	13 weeks
p-Xylene	Inhalation	auditory system	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 7.8 mg/l	5 days
p-Xylene	Inhalation	nervous system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.4 mg/l	4 weeks
Toluene	Ingestion	immune system	Not classified	Mouse	mg/kg/day NOAEL 105 mg/kg/day	4 weeks
Toluene	Ingestion	system endocrine system	Not classified	Mouse	mg/kg/day NOAEL 105	28 days
Toluene	Ingestion	bladder hematopoietic	Not classified	animal species Mouse	2,500 mg/kg/day NOAEL 600	14 days
Toluene	Ingestion Ingestion	heart liver kidney and/or	Not classified Not classified	Rat Multiple	NOAEL 2,500 mg/kg/day NOAEL	13 weeks
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	hematopoietic system vascular system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	available NOAEL 1.1 mg/l	8 weeks
Toluene	Inhalation	immune system	Not classified	Mouse	mg/l NOAEL Not	20 days
Toluene	Inhalation	and/or bladder endocrine system	Not classified	Rat	mg/l NOAEL 1.1	4 weeks
Toluene	Inhalation Inhalation	respiratory system heart liver kidney	Some positive data exist, but the data are not sufficient for classification Not classified	Rat Rat	LOAEL 2.3 mg/l	15 months 15 weeks
Toluene	Inhalation	auditory system nervous system eyes olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
T. I.		bone, teeth, nails, and/or hair hematopoietic system immune system nervous system respiratory system		W.	mg/kg/day	

Page: 18 of 21

p-Xylene	Ingestion	heart skin endocrine system bone, teeth, nails, and/or hair hematopoietic system immune system nervous system respiratory system	Not classified	Mouse	NOAEL 1,000 mg/kg/day	103 weeks
o-Xylene	Inhalation	nervous system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.4 mg/l	4 weeks
o-Xylene	Inhalation	auditory system	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 7.8 mg/l	5 days
o-Xylene	Inhalation	liver	Not classified	Multiple animal species	NOAEL Not available	
o-Xylene	Inhalation	heart endocrine system gastrointestinal tract hematopoietic system muscles kidney and/or bladder respiratory system	Not classified	Multiple animal species	NOAEL 3.5 mg/l	13 weeks
o-Xylene	Ingestion	auditory system	Not classified	Rat	NOAEL 900 mg/kg/day	2 weeks
o-Xylene	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,500 mg/kg/day	90 days
o-Xylene	Ingestion	liver	Not classified	Multiple animal species	NOAEL Not available	
o-Xylene	Ingestion	heart skin endocrine system bone, teeth, nails, and/or hair hematopoietic system immune system nervous system respiratory system	Not classified	Mouse	NOAEL 1,000 mg/kg/day	103 weeks
Nickel salts of naphthenic acids	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	similar compoun ds	NOAEL not available	13 weeks

Aspiration Hazard

110 11 11 11 11 11 11 11 11 11 11 11 11					
Name	Value				
Xylene	Aspiration hazard				
Ethylbenzene	Aspiration hazard				
m-Xylene	Aspiration hazard				
Toluene	Aspiration hazard				
p-Xylene	Aspiration hazard				
o-Xylene	Aspiration hazard				

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

Page: 19 of 21

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 3 Flammability: 2 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document group:	18-3703-8	Version number:	14.00
Issue Date:	2024/01/05	Supercedes Date:	2023/02/09

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca

Page: 20 of 21

3M TM Process Colour 886I Orange		