

## **Safety Data Sheet**

Copyright, 2024, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 11-0058-5
 Version number:
 19.00

 Issue Date:
 2024/06/10
 Supercedes Date:
 2021/11/30

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

## **SECTION 1: Identification**

#### 1.1. Product identifier

3M<sup>TM</sup> Hot Melt Adhesive 3764-AE, 3764-PG, 3764-TC, 3764-Q, 3764-B

#### **Product Identification Numbers**

62-3764-7230-4	62-3764-7231-2	62-3764-7232-0	62-3764-7233-8	62-3764-7234-6
62-3764-7235-3	62-3764-7236-1	62-3764-8530-6	62-3764-9030-6	62-3764-9130-4
62-3764-9132-0	62-3764-9135-3	62-3764-9136-1	62-3764-9230-2	62-3764-9231-0
62-3764-9232-8	62-3764-9330-0	62-3764-9333-4	62-3764-9335-9	62-3764-9336-7
62-3764-9337-5	62-3764-9338-3	62-3764-9339-1	62-3764-9395-3	62-3764-9399-5
62-3764-9530-5	62-3764-9531-3	62-3764-9536-2	62-3764-9537-0	62-3764-9830-9
62-3764-9835-8	62-3764-9836-6	62-3764-9930-7	CR-1808-0501-0	JS-3000-5041-1
IS-3000-5044-5	IS-3000-5059-3	IS-3000-5070-0		

## 1.2. Recommended use and restrictions on use

#### **Intended Use**

Adhesive

## Specific Use

hot-melt adhesive

## Restrictions on use

Not applicable

### 1.3. Supplier's details

**Company:** 3M Canada Company

**Division:** Industrial Adhesives and Tapes Division

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

**Telephone:** (800) 364-3577 **Website:** www.3M.ca

## 1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

## **SECTION 2: Hazard identification**

#### 2.1. Classification of the substance or mixture

Carcinogenicity: Category 2.

### 2.2. Label elements

### Signal word

Warning

## **Symbols**

Health Hazard

## **Pictograms**



### **Hazard statements**

Suspected of causing cancer.

## **Precautionary statements**

## **Prevention:**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves.

### **Response:**

IF exposed or concerned: Get medical advice/attention.

## Storage:

Store locked up.

## Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

## 2.3. Other hazards

May cause thermal burns.

# **SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Ethylene-Vinyl Acetate	24937-78-8	50 - 70	Acetic acid ethenyl ester, polymer with
Copolymer			ethene
Naptha (Petroleum), Llight	68132-00-3	30 - 50	Naphtha (petroleum), light steam-cracked,
Steam-Cracked, Debenzenized,			debenzenized, polymers, hydrogenated
Polymers, Hydrogenated			
Hydrocarbon Resin	69430-35-9	20 - 40	Hydrocarbons, C6-20, polymers,
			hydrogenated
Polyethylene Polymer	9006-26-2	1 - 10	2,5-Furandione, polymer with ethene
Polyolefin Wax	8002-74-2	1 - 5	Paraffin waxes and Hydrocarbon waxes
Antioxidant	6683-19-8	< 2	Benzenepropanoic acid, 3,5-bis(1,1-

Page: 2 of 12

			dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester
Vinyl Acetate	108-05-4	<= 0.13	Acetic acid ethenyl ester
Maleic Anhydride	108-31-6	< 0.01	2,5-Furandione

## **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you are concerned, get medical advice.

#### **Skin Contact:**

Immediately flush skin with large amounts of cold water for at least 15 minutes. DO NOT ATTEMPT TO REMOVE MOLTEN MATERIAL. Cover affected area with a clean dressing. Get immediate medical attention.

#### **Eye Contact:**

Immediately flush eyes with large amounts of water for at least 15 minutes. DO NOT ATTEMPT TO REMOVE MOLTEN MATERIAL. Get immediate medical attention.

#### If Swallowed:

Rinse mouth. If you are concerned, get medical advice.

#### 4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## **SECTION 5: Fire-fighting measures**

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

## **Hazardous Decomposition or By-Products**

Substance
Carbon monoxide
Carbon dioxide
Irritant Vapours or Gases

### Condition

During Combustion
During Combustion
During Combustion

### 5.3. Special protective actions for fire-fighters

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA). Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. Observe precautions from other sections.

## 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Avoid skin contact with hot material. For industrial or professional use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Use personal protective equipment (gloves, respirators, etc.) as required.

### 7.2. Conditions for safe storage including any incompatibilities

Store away from heat.

## **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

## Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Vinyl Acetate	108-05-4	ACGIH	TWA:10 ppm;STEL:15 ppm	
Maleic Anhydride	108-31-6	ACGIH	TWA(inhalable fraction and vapor): 0.01 mg/m3	Dermal/Respiratory Sensitizer
Polyolefin Wax	8002-74-2	ACGIH	TWA(as fume):2 mg/m3	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

## 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

### Eye/face protection

None required.

#### Skin/hand protection

No chemical protective gloves are required.

### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## Thermal hazards

Wear heat insulating gloves - Wear heat insulating gloves, indirect vented goggles, and a full face shield when handling hot material to prevent thermal burns.

## **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

Information on basic physical and chemical properti				
Physical state	Solid			
Specific Physical Form:	Waxy Solid			
Colour	White			
Odour	Odourless			
Odour threshold	No Data Available			
pH	Not Applicable			
Melting point/Freezing point	No Data Available			
Boiling point	Not Applicable			
Flash Point	267.8 °C [Test Method:Cleveland Open Cup]			
	[Details:CONDITIONS: ASTM D-92-72]			
Evaporation rate	Not Applicable			
Flammability	Not Applicable			
Flammable Limits(LEL)	Not Applicable			
Flammable Limits(UEL)	Not Applicable			
Vapour Pressure	No Data Available			
Vapour Density and/or Relative Vapour Density	No Data Available			
Density	0.95 g/cm3			
Relative density	0.95 [Ref Std:WATER=1]			
Water solubility	Nil			
Solubility- non-water	No Data Available			
Partition coefficient: n-octanol/ water	No Data Available			
Autoignition temperature	No Data Available			
Decomposition temperature	No Data Available			
Kinematic Viscosity	Not Applicable			
Volatile Organic Compounds	0 g/l [Test Method:calculated SCAQMD rule 443.1]			
Percent volatile	0 % weight			
VOC Less H2O & Exempt Solvents	0 g/l [Test Method:calculated SCAQMD rule 443.1]			
Molecular weight	No Data Available			
Solids Content	100 %			

Particle Characteristics	Not Applicable

# **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

## 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

#### 10.4. Conditions to avoid

None known.

### 10.5. Incompatible materials

None known.

### 10.6. Hazardous decomposition products

**Substance** None known. **Condition** 

Refer to section 5.2 for hazardous decomposition products during combustion.

## **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

May cause additional health effects (see below).

#### **Skin Contact:**

During heating: Thermal Burns: Signs/symptoms may include intense pain, redness and swelling, and tissue destruction.

#### **Eve Contact:**

During heating: Thermal Burns: Signs/symptoms may include severe pain, redness and swelling, and tissue destruction.

#### **Ingestion:**

May cause additional health effects (see below).

### **Additional Health Effects:**

## Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
Vinyl acetate	108-05-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

#### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

### **Acute Toxicity**

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg

Ethylene-Vinyl Acetate Copolymer	Dermal		LD50 estimated to be > 5,000 mg/kg
Ethylene-Vinyl Acetate Copolymer	Ingestion	Rat	LD50 > 1,000 mg/kg
Naptha (Petroleum), Llight Steam-Cracked, Debenzenized, Polymers, Hydrogenated	Dermal		LD50 estimated to be > 5,000 mg/kg
Naptha (Petroleum), Llight Steam-Cracked, Debenzenized, Polymers, Hydrogenated	Ingestion		LD50 estimated to be > 5,000 mg/kg
Hydrocarbon Resin	Dermal	Professio nal judgeme nt	LD50 estimated to be > 5,000 mg/kg
Hydrocarbon Resin	Ingestion	Professio nal judgeme nt	LD50 7,000 mg/kg
Polyethylene Polymer	Dermal	Rabbit	LD50 > 7,940 mg/kg
Polyethylene Polymer	Ingestion	Rat	LD50 > 10,000 mg/kg
Polyolefin Wax	Dermal	Rat	LD50 > 5,000 mg/kg
Polyolefin Wax	Ingestion	Rat	LD50 > 5,000  mg/kg
Antioxidant	Dermal	Rabbit	LD50 > 3,160 mg/kg
Antioxidant	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 1.95 mg/l
Antioxidant	Ingestion	Rat	LD50 > 10,250 mg/kg
Vinyl Acetate	Dermal	Rabbit	LD50 2,320 mg/kg
Vinyl Acetate	Inhalation- Vapor (4 hours)	Rat	LC50 11.3 mg/l
Vinyl Acetate	Ingestion	Rat	LD50 2,920 mg/kg
Maleic Anhydride	Dermal	Rabbit	LD50 2,620 mg/kg
Maleic Anhydride	Ingestion	Rat	LD50 1,030 mg/kg

ATE = acute toxicity estimate

## Skin Corrosion/Irritation

Name	Species	Value
Ethylene-Vinyl Acetate Copolymer	Professio nal judgeme nt	No significant irritation
Hydrocarbon Resin	Professio nal judgeme nt	No significant irritation
Naptha (Petroleum), Llight Steam-Cracked, Debenzenized, Polymers, Hydrogenated	Professio nal judgeme nt	No significant irritation
Polyethylene Polymer	Rabbit	No significant irritation
Polyolefin Wax	Rabbit	No significant irritation
Antioxidant	Rabbit	No significant irritation
Vinyl Acetate	Rabbit	Minimal irritation
Maleic Anhydride	Human and animal	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
Ethylene-Vinyl Acetate Copolymer	Professio nal judgeme nt	No significant irritation
Naptha (Petroleum), Llight Steam-Cracked, Debenzenized, Polymers, Hydrogenated	Professio nal judgeme	No significant irritation

Page: 7 of 12

	nt	
Polyethylene Polymer	Rabbit	Mild irritant
Polyolefin Wax	Rabbit	No significant irritation
Antioxidant	Rabbit	Mild irritant
Vinyl Acetate	Rabbit	Mild irritant
Maleic Anhydride	Rabbit	Corrosive

## **Skin Sensitization**

Name	Species	Value
Polyolefin Wax	Guinea	Not classified
	pig	
Antioxidant	Human	Not classified
	and	
	animal	
Vinyl Acetate	Guinea	Not classified
	pig	
Maleic Anhydride	Multiple	Sensitizing
	animal	
	species	

**Respiratory Sensitization** 

Name	Species	Value
Maleic Anhydride	Human	Sensitizing

**Germ Cell Mutagenicity** 

Name	Route	Value
Hydrocarbon Resin	In Vitro	Not mutagenic
Polyolefin Wax	In Vitro	Not mutagenic
Antioxidant	In Vitro	Not mutagenic
Antioxidant	In vivo	Not mutagenic
Vinyl Acetate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Vinyl Acetate	In vivo	Some positive data exist, but the data are not sufficient for classification
Maleic Anhydride	In vivo	Not mutagenic
Maleic Anhydride	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

caremogenety			
Name	Route	Species	Value
Polyolefin Wax	Ingestion	Rat	Not carcinogenic
Antioxidant	Ingestion	Multiple animal species	Not carcinogenic
Vinyl Acetate	Ingestion	Multiple animal species	Carcinogenic
Vinyl Acetate	Inhalation	Rat	Carcinogenic

## **Reproductive Toxicity**

Reproductive and/or Developmental Effects

reproductive and/or Developmental Effects							
Name	Route	Value	Species	Test result	Exposure		
					Duration		
Antioxidant	Ingestion	Not classified for female reproduction	Rat	NOAEL 688	2 generation		
				mg/kg/day			
Antioxidant	Ingestion	Not classified for male reproduction	Rat	NOAEL 688	2 generation		
		_		mg/kg/day			
Antioxidant	Ingestion	Not classified for development	Multiple	NOAEL 1,000	during		
		_	animal	mg/kg/day	organogenesi		
			species		S		

Page: 8 of 12

Vinyl Acetate	Ingestion	Not classified for female reproduction	Rat	NOAEL 140	2 generation
				mg/kg/day	
Vinyl Acetate	Ingestion	Not classified for male reproduction	Rat	NOAEL 140	2 generation
				mg/kg/day	
Vinyl Acetate	Ingestion	Not classified for development	Rat	NOAEL 700	2 generation
				mg/kg/day	
Vinyl Acetate	Inhalation	Not classified for development	Rat	NOAEL 0.7	during
				mg/l	organogenesi
					S
Maleic Anhydride	Ingestion	Not classified for female reproduction	Rat	NOAEL 55	2 generation
-		_		mg/kg/day	
Maleic Anhydride	Ingestion	Not classified for male reproduction	Rat	NOAEL 55	2 generation
		•		mg/kg/day	
Maleic Anhydride	Ingestion	Not classified for development	Rat	NOAEL 140	during
_		•		mg/kg/day	organogenesi
					S

## Target Organ(s)

**Specific Target Organ Toxicity - single exposure** 

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Vinyl Acetate	Inhalation	respiratory irritation	May cause respiratory irritation	Human and animal	NOAEL Not available	
Vinyl Acetate	Inhalation	central nervous system depression	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Maleic Anhydride	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure** 

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Ethylene-Vinyl Acetate Copolymer	Ingestion	liver	Not classified	Rat	NOAEL 4,000 mg/kg/day	90 days
Polyolefin Wax	Ingestion	heart	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 15 mg/kg/day	90 days
Polyolefin Wax	Ingestion	hematopoietic system   liver   immune system   skin   endocrine system   bone, teeth, nails, and/or hair   muscles   nervous system   eyes   kidney and/or bladder   respiratory system   vascular system	Not classified	Rat	NOAEL 1,500 mg/kg/day	90 days
Antioxidant	Ingestion	endocrine system	Not classified	Rat	NOAEL 450 mg/kg/day	2 years
Antioxidant	Ingestion	liver	Not classified	Dog	NOAEL 302 mg/kg/day	90 days
Antioxidant	Ingestion	hematopoietic system   nervous system   kidney and/or bladder	Not classified	Rat	NOAEL 2,500 mg/kg/day	90 days
Antioxidant	Ingestion	auditory system   eyes	Not classified	Dog	NOAEL 302 mg/kg/day	90 days
Vinyl Acetate	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL 0.2 mg/l	104 weeks
Vinyl Acetate	Inhalation	heart	Not classified	Rat	NOAEL 2.1	104 weeks

		hematopoietic system   liver   kidney and/or bladder			mg/l	
Vinyl Acetate	Inhalation	endocrine system	Not classified	Rat	NOAEL 0.07 mg/l	120 days
Vinyl Acetate	Inhalation	immune system	Not classified	Multiple animal species	NOAEL 3.5 mg/l	3 months
Vinyl Acetate	Inhalation	nervous system	Not classified	Multiple animal species	NOAEL 2.1 mg/l	104 weeks
Vinyl Acetate	Inhalation	gastrointestinal tract	Not classified	Mouse	NOAEL 3.5 mg/l	3 months
Vinyl Acetate	Ingestion	liver	Not classified	Rat	LOAEL 684 mg/kg/day	3 months
Vinyl Acetate	Ingestion	hematopoietic system   nervous system   kidney and/or bladder	Not classified	Rat	NOAEL 235 mg/kg/day	104 weeks
Vinyl Acetate	Ingestion	immune system   respiratory system	Not classified	Mouse	NOAEL 950 mg/kg/day	3 months
Vinyl Acetate	Ingestion	heart	Not classified	Rat	NOAEL 235 mg/kg/day	104 weeks
Maleic Anhydride	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.0011 mg/l	6 months
Maleic Anhydride	Inhalation	endocrine system   hematopoietic system   nervous system   kidney and/or bladder   heart   liver   eyes	Not classified	Rat	NOAEL 0.0098 mg/l	6 months
Maleic Anhydride	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 55 mg/kg/day	80 days
Maleic Anhydride	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 250 mg/kg/day	183 days
Maleic Anhydride	Ingestion	heart   nervous system	Not classified	Rat	NOAEL 600 mg/kg/day	183 days
Maleic Anhydride	Ingestion	gastrointestinal tract	Not classified	Rat	NOAEL 150 mg/kg/day	80 days
Maleic Anhydride	Ingestion	hematopoietic system	Not classified	Dog	NOAEL 60 mg/kg/day	90 days
Maleic Anhydride	Ingestion	skin   endocrine system   immune system   eyes   respiratory system	Not classified	Rat	NOAEL 150 mg/kg/day	80 days

## **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

No data available.

# **SECTION 13: Disposal considerations**

## 13.1. Disposal methods

\_\_\_\_\_

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

## **SECTION 14: Transport Information**

Not regulated per U.S. DOT, IATA or IMO.

These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling, or marking requirements. The original 3M package is certified for Canadian ground shipment only. If you are shipping by air or ocean, the package may not meet applicable regulatory requirements.

## **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

## **SECTION 16: Other information**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 0 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document group:	11-0058-5	Version number:	19.00
Issue Date:	2024/06/10	Supercedes Date:	2021/11/30

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca