

Safety Data Sheet

Copyright, 2022, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 11-0345-6
 Version number:
 11.00

 Issue Date:
 2022/04/07
 Supercedes Date:
 2021/12/24

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3MTM Thinner CGS-60

Product Identification Numbers

75-3465-0421-2 75-3465-5334-2 75-3465-5335-9 75-3466-2540-5 75-3470-5116-3

1.2. Recommended use and restrictions on use

Intended Use

Solvent

Restrictions on use

Not applicable

1.3. Supplier's details

Company: 3M Canada Company

Division: Commercial Solutions Division

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

Telephone: (800) 364-3577 **Website:** www.3M.ca

1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Flammable Liquid: Category 4.

Serious Eye Damage/Irritation: Category 2A.

Skin Corrosion/Irritation: Category 2. Aspiration Hazard: Category 1. Carcinogenicity: Category 2.

Specific Target Organ Toxicity (single exposure): Category 3.

2.2. Label elements

Signal word

Danger

Symbols

Exclamation mark | Health Hazard







Hazard statements

Combustible liquid.

Causes serious eye irritation. Causes skin irritation. May be fatal if swallowed and enters airways. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of causing cancer.

Precautionary statements

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves and eye/face protection. Wash exposed skin thoroughly after handling.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Do NOT induce vomiting. IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician. IF exposed or concerned: Get medical advice/attention. In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

| Ingredient | C.A.S. No. | % by Wt | Common Name |
|-----------------|------------|------------------------|--|
| HEAVY AROMATIC | 64742-94-5 | 30 - 60 Trade Secret * | Solvent naphtha, petroleum, heavy |
| SOLVENT NAPHTHA | | | arom.aromatic streams. It consists |
| (PETROLEUM) | | | predominantly of aromatic hydrocarbons |
| | | | having carbon numbers predominantly in |
| | | | the range of C9 through C16 and boiling in |
| | | | the range of approximately 165.degree.C to |
| | | | 290.degree.C (330.degr |

| ISOPHORONE | 78-59-1 | 30 - 60 Trade Secret * | 2-Cyclohexen-1-one, 3,5,5-trimethyl- |
|------------|---------|------------------------|--------------------------------------|

^{*}The actual concentration of this ingredient has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Remove person to fresh air. If you feel unwell, get medical attention.

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eve Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Irritating to the respiratory tract (coughing, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain). Aspiration pneumonitis (coughing, gasping, choking, burning of the mouth, and difficulty breathing). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance Condition Carbon monoxide **During Combustion** Carbon dioxide **During Combustion**

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial or professional use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Protect from sunlight. Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|------------|------------|--------|------------|----------------------------|
| ISOPHORONE | 78-59-1 | ACGIH | CEIL:5 ppm | |

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Physical state | Liquid | | | |
|---|----------------------------------|--|--|--|
| Specific Physical Form: | Liquid | | | |
| | | | | |
| Colour | Colourless | | | |
| Odour | Solvent | | | |
| Odour threshold | No Data Available | | | |
| рН | Not Applicable | | | |
| Melting point/Freezing point | Not Applicable | | | |
| Boiling point | > 182.2 °C | | | |
| Flash Point | 62.2 °C [Test Method:Closed Cup] | | | |
| Evaporation rate | No Data Available | | | |
| Flammability (solid, gas) | Not Applicable | | | |
| Flammable Limits(LEL) | 1.1 % | | | |
| Flammable Limits(UEL) | 5.8 % | | | |
| Vapour Pressure | < 133.3 Pa [@ 20 °C] | | | |
| Vapour Density and/or Relative Vapour Density | > 1 [<i>Ref Std</i> :AIR=1] | | | |
| Density | 0.91 g/ml | | | |
| Relative density | 0.91 [Ref Std:WATER=1] | | | |
| Water solubility | Slight (less than 10%) | | | |
| Solubility- non-water | No Data Available | | | |
| Partition coefficient: n-octanol/ water | No Data Available | | | |
| Autoignition temperature | > 237.8 °C | | | |
| Decomposition temperature | No Data Available | | | |
| Viscosity/Kinematic Viscosity | No Data Available | | | |
| Volatile Organic Compounds | 910 g/l | | | |
| Percent volatile | 100 % | | | |
| VOC Less H2O & Exempt Solvents | 910 g/l | | | |
| Molecular weight | No Data Available | | | |

SECTION 10: Stability and reactivity

10.1. Reactivity

Page: 5 of 10

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

Sparks and/or flames

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin Contact:

May be harmful in contact with skin. Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. May cause additional health effects (see below).

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

May be harmful if swallowed. Chemical (Aspiration) Pneumonitis: Signs/symptoms may include coughing, gasping, choking, burning of the mouth, difficulty breathing, bluish coloured skin (cyanosis), and may be fatal. Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

| Ingredient | CAS No. | Class Description | Regulation |
|------------|---------|-------------------------------|---|
| Isophorone | 78-59-1 | Grp. 2B: Possible human carc. | International Agency for Research on Cancer |

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|--|-------------|---------|---|
| Overall product | Dermal | | No data available; calculated ATE >2,000 - =5,000 |
| | | | mg/kg |
| Overall product | Ingestion | | No data available; calculated ATE >2,000 - =5,000 |
| | | | mg/kg |
| ISOPHORONE | Dermal | Rat | LD50 1,700 mg/kg |
| ISOPHORONE | Inhalation- | Rat | LC50 7 mg/l |
| | Dust/Mist | | |
| | (4 hours) | | |
| ISOPHORONE | Ingestion | Rat | LD50 1,500 mg/kg |
| HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM) | Dermal | Rabbit | LD50 > 2,000 mg/kg |
| HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM) | Ingestion | Rat | LD50 > 5,000 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|--|---------|--------------------|
| ISOPHORONE | Rabbit | Minimal irritation |
| HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM) | Rabbit | Irritant |

Serious Eve Damage/Irritation

| Scrious Lyc Damage/Hittation | | |
|--|---------|-----------------|
| Name | Species | Value |
| ISOPHORONE | Rabbit | Severe irritant |
| HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM) | Rabbit | Mild irritant |

Skin Sensitization

| Name | Species | Value |
|--|---------|----------------|
| ISOPHORONE | Guinea | Not classified |
| | pig | |
| HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM) | Guinea | Not classified |
| | pig | |

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

| Name | Route | Value |
|------------|----------|---------------|
| ISOPHORONE | In Vitro | Not mutagenic |

Carcinogenicity

| Name | Route | Species | Value |
|------------|-----------|----------|--------------|
| ISOPHORONE | Ingestion | Multiple | Carcinogenic |
| | | animal | |

| | | species | |
|--|--------|---------|--|
| HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM) | Dermal | Mouse | Some positive data exist, but the data are not sufficient for classification |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Na | ame | Route | Value | Species | Test result | Exposure Duration |
|----|----------|------------|--------------------------------|--------------------|--------------------|------------------------|
| IS | OPHORONE | Inhalation | Not classified for development | Multiple animal | NOAEL 0.66 mg/l | during organogenesi |
| | | | | species | | s |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|---|------------|--------------------------------------|--|-----------------------------------|------------------------|----------------------|
| ISOPHORONE Dermal central nervous system depression | | May cause drowsiness or dizziness | Rabbit | LOAEL 500 mg/kg | 6 hours | |
| ISOPHORONE | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | |
| ISOPHORONE | Inhalation | respiratory irritation | May cause respiratory irritation | Human | NOAEL Not available | |
| HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM) | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human and animal | NOAEL Not available | |
| HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM) | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Professio nal judgeme nt | NOAEL Not available | |
| HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM) | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Professio nal judgeme nt | NOAEL Not available | |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|------------|------------|--------------------------|--|---------|------------------------|----------------------|
| ISOPHORONE | Inhalation | kidney and/or bladder | Not classified | Rat | NOAEL 2.8 mg/l | 14 days |
| ISOPHORONE | Inhalation | hematopoietic system | Not classified | Rat | NOAEL 0.208 mg/l | 28 days |
| ISOPHORONE | Ingestion | liver | Some positive data exist, but the data are not sufficient for classification | Mouse | NOAEL 250 mg/kg/day | 2 years |
| ISOPHORONE | Ingestion | kidney and/or bladder | Not classified | Rat | LOAEL 500 mg/kg/day | 2 years |

Aspiration Hazard

| Name | Value | | |
|--|-------------------|--|--|
| HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM) | Aspiration hazard | | |

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

As a disposal alternative, utilize an acceptable permitted waste disposal facility. Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 2 Flammability: 2 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

| Document group: | 11-0345-6 | Version number: | 11.00 |
|-----------------|------------|------------------|------------|
| Issue Date: | 2022/04/07 | Supercedes Date: | 2021/12/24 |

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

Page: 9 of 10

| M™ Thinner CGS-60 | | | |
|---------------------------|-----------------|--|--|
| | | | |
| | | | |
| M Canada SDSs are availab | le at www.3M.ca | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |