



Safety Data Sheet

Copyright,2022, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|------------------------|------------|-------------------------|------------|
| Document group: | 11-2403-1 | Version number: | 15.06 |
| Issue Date: | 2022/06/09 | Supersedes Date: | 2021/12/03 |

SECTION 1: Identification

1.1. Product identifier

3M(TM) Scotch-Weld(TM) Epoxy Adhesive DP100NS Translucent

Product Identification Numbers

62-3265-1430-4 62-3265-1431-2 62-3265-1435-3 62-3265-1436-1 62-3265-3530-9
62-3265-3830-3 H0-0016-1676-4 HB-0045-6085-8 HB-0045-6108-8 XI-0039-9042-5

1.2. Recommended use and restrictions on use

Recommended use

Structural adhesive

1.3. Supplier's details

Company: 3M Canada Company
Division: Industrial Adhesives and Tapes Division
Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

Telephone: (800) 364-3577
E Mail:

1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS) or Article Information Sheet (AIS) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:

11-2401-5, 11-2402-3

Transport in accordance with applicable regulations.

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE,

COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca



Safety Data Sheet

Copyright,2022, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|------------------------|------------|-------------------------|------------|
| Document group: | 11-2402-3 | Version number: | 15.01 |
| Issue Date: | 2022/11/08 | Supersedes Date: | 2022/06/09 |

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3M™ Scotch-Weld™ Epoxy Adhesive DP100NS Translucent, Part A

Product Identification Numbers

LA-D100-2250-2 LA-D100-0015-3 LA-D100-0015-4 LA-D100-0309-9 DP-100

1.2. Recommended use and restrictions on use

Intended Use

Structural adhesive

Specific Use

Accelerator for 2-part epoxy adhesive

Restrictions on use

Not applicable

1.3. Supplier's details

| | |
|-------------------|--|
| Company: | 3M Canada Company |
| Division: | Industrial Adhesives and Tapes Division |
| Address: | 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1 |
| Telephone: | (800) 364-3577 |
| Website: | www.3M.ca |

1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 2A.

Skin Corrosion/Irritation: Category 2.

Skin Sensitizer: Category 1B.

2.2. Label elements

Signal word

Warning

Symbols

Exclamation mark |

Pictograms



Hazard statements

Causes serious eye irritation. Causes skin irritation. May cause an allergic skin reaction.

Precautionary statements

Prevention:

Avoid breathing dust/fume/gas/mist/vapours/spray. Wear protective gloves and eye/face protection. Wash exposed skin thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

None known.

2% of the mixture consists of ingredients of unknown acute oral toxicity.

3% of the mixture consists of ingredients of unknown acute dermal toxicity.

SECTION 3: Composition/information on ingredients

This material is a mixture.

| Ingredient | C.A.S. No. | % by Wt | Common Name |
|---|------------|------------------------|---|
| Polypropyleneglycoltrimercaptanether | 72244-98-5 | 60 - 80 Trade Secret * | Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-hydro-.omega.-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether |
| Hydrogenated Terphenyl | 61788-32-7 | 5 - 20 | Terphenyl, hydrogenated |
| 2,4,6-Tris((dimethylamino)methyl)phenol | 90-72-2 | 5 - 10 Trade Secret * | Phenol, 2,4,6-tris[(dimethylamino)methyl]- |
| Amorphous Silica | 67762-90-7 | 1 - 5 | Siloxanes and Silicones, di-Me, reaction products with silica |
| Polyphenyls, partially hydrogenated | 68956-74-1 | < 3 | Polyphenyls, quater- and higher, partially hydrogenated |

| | | | |
|----------------------------------|------------|--------------------------|--------------------------------------|
| bis[(Dimethylamino)methyl]Phenol | 71074-89-0 | 0.1 - 1.5 Trade Secret * | Phenol, bis[(dimethylamino)methyl]- |
| Terphenyl | 26140-60-3 | 0.1 - 1 | Terphenyl |
| Organosilane | 4420-74-0 | < 0.5 | 1-Propanethiol, 3-(trimethoxysilyl)- |

*The actual concentration of this ingredient has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide
Carbon dioxide
Hydrogen Sulfide
Oxides of Nitrogen
Oxides of Sulfur

Condition

During Combustion
During Combustion
During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA). Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for

information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|------------------------|------------|--------|--------------------------|---------------------|
| Terphenyl | 26140-60-3 | ACGIH | CEIL:5 mg/m ³ | |
| Hydrogenated Terphenyl | 61788-32-7 | ACGIH | TWA:0.5 ppm | |

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--|--|
| Physical state | Liquid |
| Specific Physical Form: | Viscous |
| Colour | Light Amber |
| Odour | Strong Mercaptan |
| Odour threshold | No Data Available |
| pH | Not Applicable |
| Melting point/Freezing point | Not Applicable |
| Boiling point | Not Applicable |
| Flash Point | >=149 °C [Test Method:Estimated] |
| Evaporation rate | Not Applicable |
| Flammability (solid, gas) | Not Applicable |
| Flammable Limits(LEL) | Not Applicable |
| Flammable Limits(UEL) | Not Applicable |
| Vapour Pressure | <=2.7 Pa [@ 20 °C] |
| Vapour Density and/or Relative Vapour Density | Not Applicable |
| Density | 1.15 g/ml |
| Relative density | 1.15 [Ref Std:WATER=1] |
| Water solubility | Negligible |
| Solubility- non-water | No Data Available |
| Partition coefficient: n-octanol/ water | No Data Available |
| Autoignition temperature | No Data Available |
| Decomposition temperature | No Data Available |
| Viscosity/Kinematic Viscosity | 50,000 - 85,000 mPa-s |
| Volatile Organic Compounds | No Data Available |
| Percent volatile | No Data Available |
| VOC Less H2O & Exempt Solvents | 0 g/l [Test Method:calculated SCAQMD rule 443.1] [Details:when used as intended with Part B] |

| | |
|--------------------------------|---|
| VOC Less H2O & Exempt Solvents | 5 g/l [<i>Test Method</i> :calculated SCAQMD rule 443.1] [<i>Details</i> :as supplied] |
| VOC Less H2O & Exempt Solvents | 0 % [<i>Test Method</i> :calculated per CARB title 2] [<i>Details</i> :when used as intended with Part B] |
| Molecular weight | No Data Available |

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

10.5. Incompatible materials

Strong oxidizing agents

Strong acids

10.6. Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the

cornea, and impaired vision.

Ingestion:

May be harmful if swallowed. Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|---|--------------------------------|---------|---|
| Overall product | Dermal | | No data available; calculated ATE >5,000 mg/kg |
| Overall product | Ingestion | | No data available; calculated ATE >2,000 - =5,000 mg/kg |
| Polypropyleneglycoltrimercaptanether | Dermal | Rabbit | LD50 > 10,200 mg/kg |
| Polypropyleneglycoltrimercaptanether | Ingestion | Rat | LD50 2,600 mg/kg |
| Hydrogenated Terphenyl | Dermal | Rabbit | LD50 > 2,000 mg/kg |
| Hydrogenated Terphenyl | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 4.7 mg/l |
| Hydrogenated Terphenyl | Ingestion | Rat | LD50 > 10,000 mg/kg |
| 2,4,6-Tris((dimethylamino)methyl)phenol | Dermal | Rat | LD50 1,280 mg/kg |
| 2,4,6-Tris((dimethylamino)methyl)phenol | Ingestion | Rat | LD50 1,000 mg/kg |
| Amorphous Silica | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| Amorphous Silica | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 0.691 mg/l |
| Amorphous Silica | Ingestion | Rat | LD50 > 5,110 mg/kg |
| bis[(Dimethylamino)methyl]Phenol | Ingestion | | LD50 estimated to be 300 - 2,000 mg/kg |
| Terphenyl | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| Terphenyl | Inhalation-Dust/Mist (4 hours) | Rat | LD50 > 3.8 mg/l |
| Terphenyl | Ingestion | Rat | LD50 2,304 mg/kg |
| Organosilane | Dermal | Rabbit | LD50 2,270 mg/kg |
| Organosilane | Ingestion | Rat | LD50 770 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|---|-------------------|---------------------------|
| Overall product | In vitro data | Irritant |
| Polypropyleneglycoltrimercaptanether | Rabbit | No significant irritation |
| Hydrogenated Terphenyl | Rabbit | No significant irritation |
| 2,4,6-Tris((dimethylamino)methyl)phenol | Rabbit | Corrosive |
| Amorphous Silica | Rabbit | No significant irritation |
| bis[(Dimethylamino)methyl]Phenol | similar compounds | Corrosive |
| Terphenyl | Rabbit | No significant irritation |
| Organosilane | Rabbit | No significant irritation |

Serious Eye Damage/Irritation

| Name | Species | Value |
|---|---------------|---------------------------|
| Overall product | In vitro data | Severe irritant |
| Polypropyleneglycoltrimercaptanether | Rabbit | Mild irritant |
| Hydrogenated Terphenyl | Rabbit | No significant irritation |
| 2,4,6-Tris((dimethylamino)methyl)phenol | Rabbit | Corrosive |

3M™ Scotch-Weld™ Epoxy Adhesive DP100NS Translucent, Part A

| | | |
|----------------------------------|-------------------|---------------------------|
| Amorphous Silica | Rabbit | No significant irritation |
| bis[(Dimethylamino)methyl]Phenol | similar compounds | Corrosive |
| Terphenyl | Rabbit | No significant irritation |
| Organosilane | Rabbit | No significant irritation |

Skin Sensitization

| Name | Species | Value |
|---|------------------|----------------|
| Polypropyleneglycoltrimercaptanether | Mouse | Sensitizing |
| Hydrogenated Terphenyl | Human | Not classified |
| 2,4,6-Tris((dimethylamino)methyl)phenol | Guinea pig | Not classified |
| Amorphous Silica | Human and animal | Not classified |
| Organosilane | Guinea pig | Sensitizing |

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

| Name | Route | Value |
|---|----------|---------------|
| Polypropyleneglycoltrimercaptanether | In Vitro | Not mutagenic |
| Hydrogenated Terphenyl | In Vitro | Not mutagenic |
| Hydrogenated Terphenyl | In vivo | Not mutagenic |
| 2,4,6-Tris((dimethylamino)methyl)phenol | In Vitro | Not mutagenic |
| Amorphous Silica | In Vitro | Not mutagenic |
| Terphenyl | In Vitro | Not mutagenic |
| Terphenyl | In vivo | Not mutagenic |
| Organosilane | In Vitro | Not mutagenic |

Carcinogenicity

| Name | Route | Species | Value |
|------------------|---------------|---------|--|
| Amorphous Silica | Not Specified | Mouse | Some positive data exist, but the data are not sufficient for classification |

Reproductive Toxicity**Reproductive and/or Developmental Effects**

| Name | Route | Value | Species | Test result | Exposure Duration |
|------------------------|-----------|--|---------|-----------------------|----------------------|
| Hydrogenated Terphenyl | Ingestion | Not classified for female reproduction | Rat | NOAEL 81 mg/kg/day | 2 generation |
| Hydrogenated Terphenyl | Ingestion | Not classified for male reproduction | Rat | NOAEL 62 mg/kg/day | 2 generation |
| Hydrogenated Terphenyl | Ingestion | Not classified for development | Rat | NOAEL 500 mg/kg/day | during organogenesis |
| Amorphous Silica | Ingestion | Not classified for female reproduction | Rat | NOAEL 509 mg/kg/day | 1 generation |
| Amorphous Silica | Ingestion | Not classified for male reproduction | Rat | NOAEL 497 mg/kg/day | 1 generation |
| Amorphous Silica | Ingestion | Not classified for development | Rat | NOAEL 1,350 mg/kg/day | during organogenesis |

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

3M™ Scotch-Weld™ Epoxy Adhesive DP100NS Translucent, Part A

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|---------------------------------------|------------|------------------------|--|---------|---------------------|-------------------|
| 2,4,6-Tris(dimethylamino)methylphenol | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | | NOAEL Not available | |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|---------------------------------------|------------|--|--|---------|-----------------------|-----------------------|
| Polypropyleneglycoltrimer captanether | Ingestion | hematopoietic system | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 75 mg/kg/day | 90 days |
| Polypropyleneglycoltrimer captanether | Ingestion | liver | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 250 mg/kg/day | 90 days |
| Polypropyleneglycoltrimer captanether | Ingestion | endocrine system heart skin immune system nervous system eyes kidney and/or bladder respiratory system vascular system | Not classified | Rat | NOAEL 1,000 mg/kg/day | 90 days |
| Hydrogenated Terphenyl | Dermal | skin | Not classified | Rabbit | NOAEL 500 mg/kg/day | 3 weeks |
| Hydrogenated Terphenyl | Dermal | hematopoietic system | Not classified | Rabbit | NOAEL 2,000 mg/kg/day | 3 weeks |
| Hydrogenated Terphenyl | Inhalation | liver hematopoietic system eyes | Not classified | Rat | NOAEL 0.5 mg/l | 13 weeks |
| Hydrogenated Terphenyl | Ingestion | hematopoietic system kidney and/or bladder liver eyes respiratory system | Not classified | Rat | NOAEL 120 mg/kg/day | 14 weeks |
| 2,4,6-Tris(dimethylamino)methylphenol | Dermal | skin liver nervous system auditory system hematopoietic system eyes | Not classified | Rat | NOAEL 125 mg/kg/day | 28 days |
| Amorphous Silica | Inhalation | respiratory system silicosis | Not classified | Human | NOAEL Not available | occupational exposure |

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals

(chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 2 Flammability: 1 Instability: 1 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

| | | | |
|------------------------|------------|-------------------------|------------|
| Document group: | 11-2402-3 | Version number: | 15.01 |
| Issue Date: | 2022/11/08 | Supersedes Date: | 2022/06/09 |

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca



Safety Data Sheet

Copyright, 2021, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|------------------------|------------|-------------------------|------------|
| Document group: | 11-2401-5 | Version number: | 17.00 |
| Issue Date: | 2021/09/30 | Supersedes Date: | 2021/09/17 |

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3M™ Scotch-Weld™ Epoxy Adhesive DP100NS Translucent, Part B

1.2. Recommended use and restrictions on use

Intended Use

Structural adhesive

Restrictions on use

Not applicable

1.3. Supplier's details

| | |
|-------------------|--|
| Company: | 3M Canada Company |
| Division: | Industrial Adhesives and Tapes Division |
| Address: | 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1 |
| Telephone: | (800) 364-3577 |
| Website: | www.3M.ca |

1.4. Emergency telephone number

Medical Emergency Telephone: 1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 1.

Skin Sensitizer: Category 1.

Reproductive Toxicity: Category 1B.

Germ Cell Mutagenicity: Category 2.

2.2. Label elements

Signal word

Danger

Symbols

Corrosion | Exclamation mark | Health Hazard |

Pictograms



Hazard statements

Causes serious eye damage. May cause an allergic skin reaction. May damage fertility or the unborn child. Suspected of causing genetic defects.

Precautionary statements

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear protective gloves and eye/face protection. Contaminated work clothing must not be allowed out of the workplace.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN: Wash with plenty of soap and water. Immediately call a POISON CENTRE or doctor/physician. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF exposed or concerned: Get medical advice/attention.

Storage:

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

| Ingredient | C.A.S. No. | % by Wt | Common Name |
|------------------|------------|-------------------------|---|
| Epoxy Resin 1 | 25068-38-6 | 80 - 100 Trade Secret * | Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane |
| Epoxy Resin 2 | 30499-70-8 | 5 - 10 Trade Secret * | 1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-, polymer with (chloromethyl)oxirane |
| Amorphous Silica | 67762-90-7 | 1 - 5 | Siloxanes and Silicones, di-Me, reaction products with silica |

*The actual concentration of this ingredient has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Aldehydes
Carbon monoxide
Carbon dioxide
Hydrogen Chloride
Ketones

Condition

During Combustion
During Combustion
During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with

applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this SDS.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|--|
| Physical state | Liquid |
| Specific Physical Form: | Viscous |
| Colour | Light Straw |
| Odour | Epoxy |
| Odour threshold | No Data Available |
| pH | Not Applicable |
| Melting point/Freezing point | No Data Available |
| Boiling point | Not Applicable |
| Flash Point | >=240 °C [Test Method: Closed Cup] [Details: Estimated] |
| Evaporation rate | Not Applicable |
| Flammability (solid, gas) | Not Applicable |
| Flammable Limits(LEL) | Not Applicable |
| Flammable Limits(UEL) | Not Applicable |
| Vapour Pressure | <=4 Pa [@ 25 °C] |
| Vapour Density and/or Relative Vapour Density | Not Applicable |
| Density | 1.18 g/ml |
| Relative density | 1.18 [Ref Std: WATER=1] |
| Water solubility | Insoluble |
| Solubility- non-water | No Data Available |
| Partition coefficient: n-octanol/ water | No Data Available |
| Autoignition temperature | No Data Available |
| Decomposition temperature | No Data Available |
| Viscosity/Kinematic Viscosity | 90,000 - 150,000 mPa-s [@ 23 °C] [Details: MITS data] |
| Volatile Organic Compounds | |
| Percent volatile | |
| VOC Less H2O & Exempt Solvents | 0 g/l [Test Method: calculated SCAQMD rule 443.1] [Details: when used as intended with Part A] |
| VOC Less H2O & Exempt Solvents | 0 g/l [Test Method: calculated SCAQMD rule 443.1] [Details: as supplied] |
| VOC Less H2O & Exempt Solvents | 0 % [Test Method: calculated per CARB title 2] [Details: when used as intended with Part A] |
| Molecular weight | No Data Available |

Nanoparticles

This material contains nanoparticles.

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

10.5. Incompatible materials

Strong acids
Strong oxidizing agents

10.6. Hazardous decomposition products

| <u>Substance</u> | <u>Condition</u> |
|------------------|------------------|
| None known. | |

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching. May cause additional health effects (see below).

Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea. May cause additional health effects (see below).

Additional Health Effects:

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Genotoxicity:

Genotoxicity and Mutagenicity: May interact with genetic material and possibly alter gene expression.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or

the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|------------------|--------------------------------|---------|--|
| Overall product | Ingestion | | No data available; calculated ATE >5,000 mg/kg |
| Epoxy Resin 1 | Dermal | Rat | LD50 > 1,600 mg/kg |
| Epoxy Resin 1 | Ingestion | Rat | LD50 > 1,000 mg/kg |
| Epoxy Resin 2 | Dermal | Rat | LD50 > 3,170 mg/kg |
| Epoxy Resin 2 | Ingestion | Rat | LD50 3,398 mg/kg |
| Amorphous Silica | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| Amorphous Silica | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 0.691 mg/l |
| Amorphous Silica | Ingestion | Rat | LD50 > 5,110 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|------------------|---------------|---------------------------|
| Epoxy Resin 1 | Rabbit | Mild irritant |
| Epoxy Resin 2 | In vitro data | Irritant |
| Amorphous Silica | Rabbit | No significant irritation |

Serious Eye Damage/Irritation

| Name | Species | Value |
|------------------|---------|---------------------------|
| Epoxy Resin 1 | Rabbit | Moderate irritant |
| Epoxy Resin 2 | Rabbit | Corrosive |
| Amorphous Silica | Rabbit | No significant irritation |

Skin Sensitization

| Name | Species | Value |
|------------------|-------------------|----------------|
| Epoxy Resin 1 | Human and animal | Sensitizing |
| Epoxy Resin 2 | similar compounds | Sensitizing |
| Amorphous Silica | Human and animal | Not classified |

Respiratory Sensitization

| Name | Species | Value |
|---------------|---------|----------------|
| Epoxy Resin 1 | Human | Not classified |

Germ Cell Mutagenicity

| Name | Route | Value |
|------------------|----------|--|
| Epoxy Resin 1 | In vivo | Not mutagenic |
| Epoxy Resin 1 | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Epoxy Resin 2 | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Epoxy Resin 2 | In vivo | Mutagenic |
| Amorphous Silica | In Vitro | Not mutagenic |

Carcinogenicity

| Name | Route | Species | Value |
|---------------|--------|---------|--|
| Epoxy Resin 1 | Dermal | Mouse | Some positive data exist, but the data are not |

3M™ Scotch-Weld™ Epoxy Adhesive DP100NS Translucent, Part B

| | | | |
|------------------|---------------|-------|--|
| | | | sufficient for classification |
| Amorphous Silica | Not Specified | Mouse | Some positive data exist, but the data are not sufficient for classification |

Reproductive Toxicity
Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test result | Exposure Duration |
|------------------|-----------|--|---------|-----------------------|----------------------------|
| Epoxy Resin 1 | Ingestion | Not classified for female reproduction | Rat | NOAEL 750 mg/kg/day | 2 generation |
| Epoxy Resin 1 | Ingestion | Not classified for male reproduction | Rat | NOAEL 750 mg/kg/day | 2 generation |
| Epoxy Resin 1 | Dermal | Not classified for development | Rabbit | NOAEL 300 mg/kg/day | during organogenesis |
| Epoxy Resin 1 | Ingestion | Not classified for development | Rat | NOAEL 750 mg/kg/day | 2 generation |
| Epoxy Resin 2 | Ingestion | Not classified for female reproduction | Rat | NOAEL 100 mg/kg/day | prematuring into lactation |
| Epoxy Resin 2 | Ingestion | Not classified for development | Rat | NOAEL 100 mg/kg/day | prematuring into lactation |
| Epoxy Resin 2 | Ingestion | Toxic to male reproduction | Rat | NOAEL 100 mg/kg/day | 14 days |
| Amorphous Silica | Ingestion | Not classified for female reproduction | Rat | NOAEL 509 mg/kg/day | 1 generation |
| Amorphous Silica | Ingestion | Not classified for male reproduction | Rat | NOAEL 497 mg/kg/day | 1 generation |
| Amorphous Silica | Ingestion | Not classified for development | Rat | NOAEL 1,350 mg/kg/day | during organogenesis |

Target Organ(s)
Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|---------------|------------|------------------------|--|------------------------|---------------------|-------------------|
| Epoxy Resin 2 | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | similar health hazards | NOAEL Not available | |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|---------------|-----------|---|----------------|---------|-----------------------|-------------------|
| Epoxy Resin 1 | Dermal | liver | Not classified | Rat | NOAEL 1,000 mg/kg/day | 2 years |
| Epoxy Resin 1 | Dermal | nervous system | Not classified | Rat | NOAEL 1,000 mg/kg/day | 13 weeks |
| Epoxy Resin 1 | Ingestion | auditory system heart endocrine system hematopoietic system liver eyes kidney and/or bladder | Not classified | Rat | NOAEL 1,000 mg/kg/day | 28 days |
| Epoxy Resin 2 | Ingestion | heart skin endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system liver immune system | Not classified | Rat | NOAEL 300 mg/kg/day | 43 days |

| | | | | | | |
|------------------|------------|--|----------------|-------|---------------------|-----------------------|
| | | muscles nervous system eyes kidney and/or bladder respiratory system vascular system | | | | |
| Amorphous Silica | Inhalation | respiratory system silicosis | Not classified | Human | NOAEL Not available | occupational exposure |

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 3 **Flammability:** 1 **Instability:** 1 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

| | | | |
|------------------------|------------|-------------------------|------------|
| Document group: | 11-2401-5 | Version number: | 17.00 |
| Issue Date: | 2021/09/30 | Supersedes Date: | 2021/09/17 |

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca