

### Safety Data Sheet

Copyright, 2022, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| Document group: | 11-2673-9  | Version number:  | 23.01      |
|-----------------|------------|------------------|------------|
| Issue Date:     | 2022/12/30 | Supercedes Date: | 2022/10/26 |

# **SECTION 1: Identification**

## 1.1. Product identifier

3M<sup>TM</sup> Scotch-Weld<sup>TM</sup> Epoxy Adhesive 460 Off-White

#### **Product Identification Numbers**

62-3593-6430-4 XF-0038-7117-5

## 1.2. Recommended use and restrictions on use

#### Recommended use

Structural adhesive

#### 1.3. Supplier's details

**Company:** 3M Canada Company

**Division:** Industrial Adhesives and Tapes Division

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

**Telephone:** (800) 364-3577

E Mail:

#### 1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS) or Article Information Sheet (AIS) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:

22-0525-0, 22-0534-2

Transport in accordance with applicable regulations.

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit

for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca

Page: 2 of 2



# Safety Data Sheet

Copyright, 2024, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 22-0534-2
 Version number:
 13.01

 Issue Date:
 2024/02/05
 Supercedes Date:
 2022/10/26

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

# **SECTION 1: Identification**

#### 1.1. Product identifier

3M<sup>TM</sup> Scotch-Weld<sup>TM</sup> Epoxy Adhesive 460 Off-White, Part A

**Product Identification Numbers** 

LA-D100-0281-6 62-3693-8530-7 62-3693-9530-6 XI-0038-5432-4

## 1.2. Recommended use and restrictions on use

#### **Intended Use**

Structural adhesive

### Restrictions on use

Not applicable

#### 1.3. Supplier's details

**Company:** 3M Canada Company

**Division:** Industrial Adhesives and Tapes Division

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

**Telephone:** (800) 364-3577 **Website:** www.3M.ca

# 1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

# **SECTION 2: Hazard identification**

## 2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 1. Skin Corrosion/Irritation: Category 1B. Skin Sensitizer: Category 1.

#### 2.2. Label elements

#### Signal word

Danger

## **Symbols**

Corrosion Exclamation mark

#### **Pictograms**



#### Hazard statements

Causes severe skin burns and eye damage. May cause an allergic skin reaction.

### **Precautionary statements**

#### **Prevention:**

Do not breathe dust/fume/gas/mist/vapours/spray. Wear protective gloves, protective clothing, and eye/face protection. Wash exposed skin thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

#### **Response:**

IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTRE or doctor/physician. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

#### Storage:

Store locked up.

## Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

#### 2.3. Other hazards

May cause chemical gastrointestinal burns.

# **SECTION 3: Composition/information on ingredients**

This material is a mixture.

| Ingredient                   | C.A.S. No.   | % by Wt                | Common Name                                |
|------------------------------|--------------|------------------------|--|
| Modified Epoxy Resin         | Trade Secret | 40 - 70                | Not Applicable                             |
| 4,7,10-Trioxatridecane-1,13- | 4246-51-9    | 30 - 60 Trade Secret * | 1-Propanamine, 3,3'-[oxybis(2,1-           |
| Diamine                      |              |                        | ethanediyloxy)]bis-                        |
| 2,4,6-tris((Dimethylamino)-  | 90-72-2      | 1 - 5 Trade Secret *   | Phenol, 2,4,6-tris[(dimethylamino)methyl]- |
| Methyl)Phenol                |              |                        |  |
| Amorphous Silica             | 67762-90-7   | 1 - 5                  | Siloxanes and Silicones, di-Me, reaction   |
|                              |              |                        | products with silica                       |

Modified Epoxy Resin is a non-hazardous Trade Secret material according to WHMIS criteria.

# **SECTION 4: First aid measures**

<sup>\*</sup>The actual concentration of this ingredient has been withheld as a trade secret.

#### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

#### **Skin Contact:**

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

#### **Eye Contact:**

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

#### If Swallowed:

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Skin burns (localized redness, swelling, itching, intense pain, blistering, and tissue destruction). Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision).

#### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

#### **Hazardous Decomposition or By-Products**

| <b>Substance</b>   | <u>Condition</u>  |
|--------------------|-------------------|
| Aldehydes          | During Combustion |
| Carbon monoxide    | During Combustion |
| Carbon dioxide     | During Combustion |
| Hydrogen Chloride  | During Combustion |
| Oxides of Nitrogen | During Combustion |

## 5.3. Special protective actions for fire-fighters

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA). Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

# **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

#### **6.2.** Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

\_\_\_\_\_

#### 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

For industrial or professional use only. Not for consumer sale or use. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

### 7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from strong bases. Store away from oxidizing agents. Store away from amines.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this SDS.

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

## Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

**Indirect Vented Goggles** 

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl Rubber

Nitrile Rubber

Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Butyl rubber

\_\_\_\_\_

Apron - Nitrile

Apron - polymer laminate

# **Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

# **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

| Physical state                                | Liquid   |  |
|---|--|--|
| Specific Physical Form:                       | viscous liquid   |  |
|   |  |  |
| Colour  | Amber  |  |
| Odour   | Very Mild Odour, Pungent Odour                               |  |
| Odour threshold                               | No Data Available  |  |
| рН  | Not Applicable   |  |
| Melting point/Freezing point                  | Not Applicable   |  |
| Boiling point                                 | >=171 °C   |  |
| Flash Point                                   | 171.1 °C [Test Method:Closed Cup]                            |  |
| Evaporation rate                              | No Data Available  |  |
| Flammability (solid, gas)                     | Not Applicable   |  |
| Flammable Limits(LEL)                         | No Data Available  |  |
| Flammable Limits(UEL)                         | No Data Available  |  |
| Vapour Pressure                               | <=400 Pa [@ 20 °C ]  |  |
| Vapour Density and/or Relative Vapour Density | 3.72 [ <i>Ref Std</i> :AIR=1]                                |  |
| Density                                       | 1.09 g/ml  |  |
| Relative density                              | 1.09 [ <i>Ref Std</i> :WATER=1]                              |  |
| Water solubility                              | Slight (less than 10%)                                       |  |
| Solubility- non-water                         | No Data Available  |  |
| Partition coefficient: n-octanol/ water       | No Data Available  |  |
| Autoignition temperature                      | No Data Available  |  |
| Decomposition temperature                     | No Data Available  |  |
| Viscosity/Kinematic Viscosity                 | 8,000 - 16,000 mPa-s [@ 23 °C ] [Test Method: Brookfield]    |  |
| Volatile Organic Compounds                    | No Data Available  |  |
| Percent volatile                              | No Data Available  |  |
| VOC Less H2O & Exempt Solvents                |  |  |
|   | [Details: when used as intended with Part B]                 |  |
| VOC Less H2O & Exempt Solvents                | 0 g/l [Test Method:calculated SCAQMD rule 443.1] [Details:as |  |
|   | supplied]  |  |
| Molecular weight                              | No Data Available  |  |

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

## 10.2. Chemical stability

## 3M<sup>TM</sup> Scotch-Weld<sup>TM</sup> Epoxy Adhesive 460 Off-White, Part A

Stable.

#### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

#### 10.4. Conditions to avoid

None known.

# 10.5. Incompatible materials

Amines

Alcohols

Strong bases

Strong acids

Strong oxidizing agents

### 10.6. Hazardous decomposition products

### **Substance**

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

#### 11.1. Information on Toxicological effects

### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### **Inhalation:**

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

## **Skin Contact:**

Corrosive (Skin Burns): Signs/symptoms may include localized redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### **Eve Contact:**

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

#### **Ingestion:**

Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen.

#### **Additional Information:**

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

#### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity** 

| Name                                     | Route       | Species | Value  |
|--|-------------|---------|--|
| Overall product                          | Dermal      |         | No data available; calculated ATE >5,000 mg/kg |
| Overall product                          | Ingestion   |         | No data available; calculated ATE >5,000 mg/kg |
| 4,7,10-Trioxatridecane-1,13-Diamine      | Dermal      | Rabbit  | LD50 2,525 mg/kg                               |
| 4,7,10-Trioxatridecane-1,13-Diamine      | Ingestion   | Rat     | LD50 2,850 mg/kg                               |
| Amorphous Silica                         | Dermal      | Rabbit  | LD50 > 5,000 mg/kg                             |
| Amorphous Silica                         | Inhalation- | Rat     | LC50 > 0.691 mg/l                              |
|  | Dust/Mist   |         |  |
|  | (4 hours)   |         |  |
| Amorphous Silica                         | Ingestion   | Rat     | LD50 > 5,110 mg/kg                             |
| 2,4,6-tris((Dimethylamino)-Methyl)Phenol | Dermal      | Rat     | LD50 1,280 mg/kg                               |
| 2,4,6-tris((Dimethylamino)-Methyl)Phenol | Ingestion   | Rat     | LD50 1,000 mg/kg                               |

ATE = acute toxicity estimate

#### Skin Corrosion/Irritation

| JAME COTTOSION/TITIMATON                 |          |                           |  |
|--|----------|---------------------------|--|
| Name                                     | Species  | Value                     |  |
|  |          |                           |  |
| Overall product                          | In vitro | Corrosive                 |  |
|  | data     |                           |  |
| 4,7,10-Trioxatridecane-1,13-Diamine      | Rabbit   | Corrosive                 |  |
| Amorphous Silica                         | Rabbit   | No significant irritation |  |
| 2,4,6-tris((Dimethylamino)-Methyl)Phenol | Rabbit   | Corrosive                 |  |

Serious Eve Damage/Irritation

| Name                                     | Species | Value                     |
|--|---------|---------------------------|
| 4,7,10-Trioxatridecane-1,13-Diamine      | Rabbit  | Corrosive                 |
| Amorphous Silica                         | Rabbit  | No significant irritation |
| 2,4,6-tris((Dimethylamino)-Methyl)Phenol | Rabbit  | Corrosive                 |

## **Skin Sensitization**

| Name                                     | Species   | Value          |
|--|-----------|----------------|
| 4,7,10-Trioxatridecane-1,13-Diamine      | Professio | Sensitizing    |
|  | nal       |                |
|  | judgeme   |                |
|  | nt        |                |
| Amorphous Silica                         | Human     | Not classified |
|  | and       |                |
|  | animal    |                |
| 2,4,6-tris((Dimethylamino)-Methyl)Phenol | Guinea    | Not classified |
|  | pig       |                |

# **Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

| Name                                     | Route    | Value         |
|--|----------|---------------|
| Overall product                          | In Vitro | Not mutagenic |
| 4,7,10-Trioxatridecane-1,13-Diamine      | In Vitro | Not mutagenic |
| Amorphous Silica                         | In Vitro | Not mutagenic |
| 2,4,6-tris((Dimethylamino)-Methyl)Phenol | In Vitro | Not mutagenic |

Carcinogenicity

| Name             | Route     | Species | Value  |
|------------------|-----------|---------|--|
| Amorphous Silica | Not       | Mouse   | Some positive data exist, but the data are not |
|                  | Specified |         | sufficient for classification                  |

Page: 7 of 10

# Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name                                | Route     | Value                                  | Species | Test result              | Exposure<br>Duration        |
|-------------------------------------|-----------|--|---------|--------------------------|-----------------------------|
| 4,7,10-Trioxatridecane-1,13-Diamine | Ingestion | Not classified for female reproduction | Rat     | NOAEL 600<br>mg/kg/day   | premating into lactation    |
| 4,7,10-Trioxatridecane-1,13-Diamine | Ingestion | Not classified for male reproduction   | Rat     | NOAEL 600<br>mg/kg/day   | 59 days                     |
| 4,7,10-Trioxatridecane-1,13-Diamine | Ingestion | Not classified for development         | Rat     | NOAEL 600<br>mg/kg/day   | premating into lactation    |
| Amorphous Silica                    | Ingestion | Not classified for female reproduction | Rat     | NOAEL 509<br>mg/kg/day   | 1 generation                |
| Amorphous Silica                    | Ingestion | Not classified for male reproduction   | Rat     | NOAEL 497<br>mg/kg/day   | 1 generation                |
| Amorphous Silica                    | Ingestion | Not classified for development         | Rat     | NOAEL 1,350<br>mg/kg/day | during<br>organogenesi<br>s |

# Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name   | Route      | Target Organ(s)        | Value  | Species                      | Test result            | Exposure<br>Duration |
|--|------------|------------------------|--|------------------------------|------------------------|----------------------|
| 4,7,10-Trioxatridecane-<br>1,13-Diamine          | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | similar<br>health<br>hazards | NOAEL Not<br>available |                      |
| 2,4,6-<br>tris((Dimethylamino)-<br>Methyl)Phenol | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification |                              | NOAEL Not available    |                      |

Specific Target Organ Toxicity - repeated exposure

| Name   | Route      | Target Organ(s)   | Value          | Species | Test result            | Exposure<br>Duration  |
|--|------------|---|----------------|---------|------------------------|-----------------------|
| 4,7,10-Trioxatridecane-<br>1,13-Diamine          | Ingestion  | gastrointestinal tract   heart   endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   liver   immune system   muscles   nervous system   eyes   kidney and/or bladder   respiratory system   vascular system | Not classified | Rat     | NOAEL 600<br>mg/kg/day | 59 days               |
| Amorphous Silica                                 | Inhalation | respiratory system  <br>silicosis   | Not classified | Human   | NOAEL Not available    | occupational exposure |
| 2,4,6-<br>tris((Dimethylamino)-<br>Methyl)Phenol | Dermal     | skin   liver   nervous<br>system   auditory<br>system  <br>hematopoietic<br>system   eyes   | Not classified | Rat     | NOAEL 125<br>mg/kg/day | 28 days               |

## **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

Daga, Q of 10

No data available.

# **SECTION 13: Disposal considerations**

## 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

# **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

# **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

# **SECTION 16: Other information**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 3 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

| Document group: | 22-0534-2  | Version number:  | 13.01      |
|-----------------|------------|------------------|------------|
| Issue Date:     | 2024/02/05 | Supercedes Date: | 2022/10/26 |

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR

PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca



# Safety Data Sheet

Copyright, 2024, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document group:** 22-0525-0 Version number: 6.01 **Issue Date:** 2024/02/05 **Supercedes Date:** 2022/07/21

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

# **SECTION 1: Identification**

#### 1.1. Product identifier

3M<sup>TM</sup> Scotch-Weld<sup>TM</sup> Epoxy Adhesive 460 Off-White, Part B

**Product Identification Numbers** 

62-3593-8530-9 62-3593-9530-8 62-3593-9532-4 XI-0038-5433-2

#### 1.2. Recommended use and restrictions on use

#### **Intended Use**

Structural adhesive

### Restrictions on use

Not applicable

#### 1.3. Supplier's details

3M Canada Company Company:

Industrial Adhesives and Tapes Division **Division:** 

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

**Telephone:** (800) 364-3577 Website: www.3M.ca

# 1.4. Emergency telephone number

Medical Emergency Telephone: 1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

# **SECTION 2: Hazard identification**

### 2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 2B.

Skin Sensitizer: Category 1.

## 2.2. Label elements

Signal word

Warning

**Symbols** 

## 3M™ Scotch-Weld™ Epoxy Adhesive 460 Off-White, Part B

Exclamation mark

## **Pictograms**



#### Hazard statements

Causes eye irritation. May cause an allergic skin reaction.

### **Precautionary statements**

#### **Prevention:**

Avoid breathing dust/fume/gas/mist/vapours/spray. Wear protective gloves. Wash exposed skin thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

## **Response:**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

#### Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

#### 2.3. Other hazards

None known.

# **SECTION 3: Composition/information on ingredients**

This material is a mixture.

| Ingredient      | C.A.S. No.   | % by Wt                 | Common Name                            |
|-----------------|--------------|-------------------------|--|
| Epoxy Resin     | 25068-38-6   | 80 - 100 Trade Secret * | Phenol, 4,4'-(1-methylethylidene)bis-, |
|                 |              |                         | polymer with (chloromethyl)oxirane     |
| Acrylic Polymer | Trade Secret | 1 - 20                  | Not Applicable                         |

Acrylic Polymer is a non-hazardous Trade Secret material according to WHMIS criteria.

# **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

#### **Skin Contact**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

# **Eye Contact:**

<sup>\*</sup>The actual concentration of this ingredient has been withheld as a trade secret.

## 3M<sup>™</sup> Scotch-Weld<sup>™</sup> Epoxy Adhesive 460 Off-White, Part B

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

#### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

## **Hazardous Decomposition or By-Products**

| Substance                 | <u>Condition</u>  |
|---------------------------|-------------------|
| Aldehydes                 | During Combustion |
| Carbon monoxide           | During Combustion |
| Carbon dioxide            | During Combustion |
| Hydrogen Chloride         | During Combustion |
| Irritant Vapours or Gases | During Combustion |

#### 5.3. Special protective actions for fire-fighters

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA). Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

# **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

## **6.2.** Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

## 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

For industrial or professional use only. Not for consumer sale or use. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

#### 7.2. Conditions for safe storage including any incompatibilities

Store away from oxidizing agents.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this SDS.

#### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

#### 8.2.2. Personal protective equipment (PPE)

## Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

**Indirect Vented Goggles** 

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

# **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

| Physical state L | Liquid |
|------------------|--------|
|------------------|--------|

Page: 4 of 9

| Specific Physical Form:                       | Paste  |  |  |  |
|---|--|--|--|--|
| Colour  | White  |  |  |  |
| Odour   | Very Mild Odour  |  |  |  |
| Odour threshold                               | No Data Available  |  |  |  |
| рН  | Not Applicable   |  |  |  |
| Melting point/Freezing point                  | No Data Available  |  |  |  |
| Boiling point                                 | >=260 °C   |  |  |  |
| Flash Point                                   | 248.9 °C [Test Method:Closed Cup]                            |  |  |  |
| Evaporation rate                              | Not Applicable   |  |  |  |
| Flammability (solid, gas)                     | Not Applicable   |  |  |  |
| Flammable Limits(LEL)                         | Not Applicable   |  |  |  |
| Flammable Limits(UEL)                         | Not Applicable   |  |  |  |
| Vapour Pressure                               | Not Applicable   |  |  |  |
| Vapour Density and/or Relative Vapour Density | Not Applicable   |  |  |  |
| Density                                       | 1.14 g/ml  |  |  |  |
| Relative density                              | 1.14 [ <i>Ref Std</i> :WATER=1]                              |  |  |  |
| Water solubility                              | Nil  |  |  |  |
| Solubility- non-water                         | No Data Available  |  |  |  |
| Partition coefficient: n-octanol/ water       | No Data Available  |  |  |  |
| Autoignition temperature                      | No Data Available  |  |  |  |
| Decomposition temperature                     | No Data Available  |  |  |  |
| Viscosity/Kinematic Viscosity                 | 20,000 - 50,000 mPa-s [@ 23 °C ]                             |  |  |  |
| Volatile Organic Compounds                    | No Data Available  |  |  |  |
| Percent volatile                              | No Data Available  |  |  |  |
| VOC Less H2O & Exempt Solvents                | 0 g/l [Test Method:calculated SCAQMD rule 443.1]             |  |  |  |
|   | [Details: when used as intended with Part A]                 |  |  |  |
| VOC Less H2O & Exempt Solvents                | 5 g/l [Test Method:calculated SCAQMD rule 443.1] [Details:as |  |  |  |
|   | supplied]  |  |  |  |
| VOC Less H2O & Exempt Solvents                | 0 % [Test Method:calculated SCAQMD rule 443.1]               |  |  |  |
|   | [Details: when used as intended with Part A]                 |  |  |  |
| Molecular weight                              | No Data Available  |  |  |  |

# **SECTION 10: Stability and reactivity**

# 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

# 10.2. Chemical stability

Stable.

## 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

#### 10.4. Conditions to avoid

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

# 10.5. Incompatible materials

Strong oxidizing agents

# 10.6. Hazardous decomposition products

<u>Substance</u> <u>Condition</u>

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

## 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

#### **Skin Contact:**

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### **Eve Contact:**

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

#### **Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

## **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity** 

| ricate Tokicity |           |         |  |
|-----------------|-----------|---------|--|
| Name            | Route     | Species | Value  |
| Overall product | Ingestion |         | No data available; calculated ATE >5,000 mg/kg |
| Epoxy Resin     | Dermal    | Rat     | LD50 > 1,600 mg/kg                             |
| Epoxy Resin     | Ingestion | Rat     | LD50 > 1,000 mg/kg                             |
| Acrylic Polymer | Dermal    | Rabbit  | LD50 > 5,000 mg/kg                             |
| Acrylic Polymer | Ingestion | Rat     | LD50 > 5,000 mg/kg                             |

ATE = acute toxicity estimate

#### Skin Corrosion/Irritation

| Name            | Species                           | Value              |
|-----------------|-----------------------------------|--------------------|
| Epoxy Resin     | Rabbit                            | Mild irritant      |
| Acrylic Polymer | Professio<br>nal<br>judgeme<br>nt | Minimal irritation |

Serious Eve Damage/Irritation

| Name | Species | Value |
|------|---------|-------|
|      |         |       |

Page: 6 of 9

# 3M<sup>TM</sup> Scotch-Weld<sup>TM</sup> Epoxy Adhesive 460 Off-White, Part B

| Epoxy Resin     | Rabbit    | Moderate irritant |
|-----------------|-----------|-------------------|
| Acrylic Polymer | Professio | Mild irritant     |
|                 | nal       |                   |
|                 | judgeme   |                   |
|                 | nt        |                   |

## **Skin Sensitization**

| Name        | Species | Value       |
|-------------|---------|-------------|
| Epoxy Resin | Human   | Sensitizing |
|             | and     |             |
|             | animal  |             |

**Respiratory Sensitization** 

| Name        | Species | Value          |
|-------------|---------|----------------|
| Epoxy Resin | Human   | Not classified |

Germ Cell Mutagenicity

| Name        | Route    | Value  |
|-------------|----------|--|
| Epoxy Resin | In vivo  | Not mutagenic  |
| Epoxy Resin | In Vitro | Some positive data exist, but the data are not sufficient for classification |

Carcinogenicity

| Name        | Route  | Species | Value  |
|-------------|--------|---------|--|
| Epoxy Resin | Dermal | Mouse   | Some positive data exist, but the data are not |
|             |        |         | sufficient for classification                  |

# **Reproductive Toxicity**

Reproductive and/or Developmental Effects

| Name        | Route     | Value                                  | Species | Test result            | Exposure<br>Duration        |
|-------------|-----------|--|---------|------------------------|-----------------------------|
| Epoxy Resin | Ingestion | Not classified for female reproduction | Rat     | NOAEL 750<br>mg/kg/day | 2 generation                |
| Epoxy Resin | Ingestion | Not classified for male reproduction   | Rat     | NOAEL 750<br>mg/kg/day | 2 generation                |
| Epoxy Resin | Dermal    | Not classified for development         | Rabbit  | NOAEL 300<br>mg/kg/day | during<br>organogenesi<br>s |
| Epoxy Resin | Ingestion | Not classified for development         | Rat     | NOAEL 750<br>mg/kg/day | 2 generation                |

# Target Organ(s)

# **Specific Target Organ Toxicity - single exposure**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

| Name        | Route     | Target Organ(s)   | Value          | Species | Test result                 | Exposure<br>Duration |
|-------------|-----------|---|----------------|---------|-----------------------------|----------------------|
| Epoxy Resin | Dermal    | liver   | Not classified | Rat     | NOAEL<br>1,000<br>mg/kg/day | 2 years              |
| Epoxy Resin | Dermal    | nervous system  | Not classified | Rat     | NOAEL<br>1,000<br>mg/kg/day | 13 weeks             |
| Epoxy Resin | Ingestion | auditory system  <br>heart   endocrine<br>system  <br>hematopoietic | Not classified | Rat     | NOAEL<br>1,000<br>mg/kg/day | 28 days              |

Page: 7 of 9

| system   liver   eyes  <br>kidney and/or<br>bladder |  |  |
|---|--|--|

#### **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

3M<sup>™</sup> Scotch-Weld<sup>™</sup> Epoxy Adhesive 460 Off-White, Part B

No data available.

# **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

# **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

# **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

# **SECTION 16: Other information**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to

\_\_\_\_\_

address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

| Document group: | 22-0525-0  | Version number:  | 6.01       |
|-----------------|------------|------------------|------------|
| Issue Date:     | 2024/02/05 | Supercedes Date: | 2022/07/21 |

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca