

#### **Safety Data Sheet**

Copyright, 2022, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	10-5608-4	Version number:	14.01
Issue Date:	2022/09/30	Supercedes Date:	2022/06/27

## **SECTION 1: Identification**

#### 1.1. Product identifier

3M<sup>TM</sup> Scotchcast<sup>TM</sup> Multi-Mold Resin Splice Kit 85-12 (Scotchcast<sup>TM</sup> 2104)

#### **Product Identification Numbers**

78-8025-2927-7 80-6100-7711-9 80-6112-1839-9

#### 1.2. Recommended use and restrictions on use

#### Recommended use

Electrical, Electrical Splice and Insulation

#### 1.3. Supplier's details

**Company:** 3M Canada Company **Division:** Electrical Markets Division

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

**Telephone:** (800) 364-3577

E Mail:

#### 1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS) or Article Information Sheet (AIS) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:

25-0742-4, 25-1043-6

Transport in accordance with applicable regulations.

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit

	3M <sup>TM</sup> Scotchcast <sup>TM</sup>	Multi-Mold Resin	Splice Kit 85-12	(Scotchcast <sup>TM</sup> 2104)
--	---	------------------	------------------	---------------------------------

for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca

Page: 2 of 2



## Safety Data Sheet

Copyright, 2022, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 25-1043-6
 Version number:
 5.02

 Issue Date:
 2022/06/26
 Supercedes Date:
 2020/10/21

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

## **SECTION 1: Identification**

#### 1.1. Product identifier

3M(TM) Scotchcast(TM) Electrical Insulating Resin 2104, Part B

**Product Identification Numbers** 

LH-A100-0575-2 LH-A100-0575-3 LH-A100-0575-4 LH-A100-0575-5 LH-A100-0575-6

LH-A100-1638-6 80-6116-1276-5

### 1.2. Recommended use and restrictions on use

## **Intended Use**

Electrical

#### Specific Use

Part B of two part electrical resin

#### Restrictions on use

Not applicable

## 1.3. Supplier's details

Company: 3M Canada Company
Division: Electrical Markets Division

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

**Telephone:** (800) 364-3577 **Website:** www.3M.ca

#### 1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

## **SECTION 2: Hazard identification**

### 2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 1.

#### 2.2. Label elements

Signal word

### 3M(TM) Scotchcast(TM) Electrical Insulating Resin 2104, Part B

Danger

**Symbols** 

Corrosion

**Pictograms** 



#### **Hazard statements**

Causes serious eye damage.

## **Precautionary statements**

#### **Prevention:**

Wear eye/face protection.

### **Response:**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTRE or doctor/physician.

#### 2.3. Other hazards

None known.

# **SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
POLYPROPYLENE GLYCOL GLYCEROL TRIETHER	25791-96-2		Poly[oxy(methyl-1,2-ethanediyl)], .alpha.,.alpha.',.alpha."-1,2,3-propanetriyltris[.omegahydroxy-
N,N-DI(2- HYDROXYPROPYL) ANILINE	3077-13-2	10 - 30 Trade Secret *	2-Propanol, 1,1'-(phenylimino)bis-
PHTHALIC ACID, DI-C11-14-BRANCHED ALKYL ESTERS, C13-RICH		5 - 20	1,2-Benzenedicarboxylic acid, di-C11-14- branched alkyl esters, C13-rich
DIPROPYLENE GLYCOL	25265-71-8	1 - 10	Propanol, oxybis-

<sup>\*</sup>The actual concentration of this ingredient has been withheld as a trade secret.

## **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin Contact:** 

Wash with soap and water. If signs/symptoms develop, get medical attention.

#### 3M(TM) Scotchcast(TM) Electrical Insulating Resin 2104, Part B

#### **Eye Contact:**

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision).

## 4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

## **SECTION 5: Fire-fighting measures**

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

## 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

## **Hazardous Decomposition or By-Products**

<b>Substance</b>	<u>Condition</u>
Aldehydes	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Oxides of Nitrogen	During Combustion

#### 5.3. Special protective actions for fire-fighters

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA). Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### **6.2.** Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

For industrial or professional use only. Not for consumer sale or use. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment.

#### 7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this SDS.

#### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

#### 8.2.2. Personal protective equipment (PPE)

### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

**Indirect Vented Goggles** 

#### Skin/hand protection

No chemical protective gloves are required.

### **Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

# **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state	Liquid	
Colour	Light Amber	
Odour	Glycol	
Odour threshold	No Data Available	
pH	No Data Available	
Melting point/Freezing point	No Data Available	
Boiling point	>= 110 °C	
Flash Point	>= 110 °C [Test Method:Closed Cup]	
Evaporation rate	No Data Available	
Flammability (solid, gas)	Not Applicable	

Page: 4 of 9

Flammable Limits(LEL)	No Data Available		
Flammable Limits(UEL)	No Data Available		
Vapour Density and/or Relative Vapour Density	No Data Available		
Density 1 g/ml			
Relative density	1 [Ref Std:WATER=1]		
Water solubility	Slight (less than 10%)		
Solubility- non-water	No Data Available		
Partition coefficient: n-octanol/ water	No Data Available		
Autoignition temperature	No Data Available		
Decomposition temperature	No Data Available		
Viscosity/Kinematic Viscosity	450 mPa-s - 750 mPa-s		
Volatile Organic Compounds	No Data Available		
Percent volatile	No Data Available		
VOC Less H2O & Exempt Solvents	No Data Available		
Average particle size	No Data Available		
Bulk density	No Data Available		
Molecular weight	No Data Available		
Softening point	No Data Available		

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

### 10.2. Chemical stability

Stable.

#### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

#### 10.4. Conditions to avoid

None known.

#### 10.5. Incompatible materials

None known.

No Data Available

### 10.6. Hazardous decomposition products

Substance
None known.

**Condition** 

Refer to section 5.2 for hazardous decomposition products during combustion.

## **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

## Signs and Symptoms of Exposure

## Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

#### **Skin Contact:**

No known health effects.

#### **Eye Contact:**

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

#### **Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

### Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
POLYPROPYLENE GLYCOL GLYCEROL TRIETHER	Dermal	Rat	LD50 > 2,000 mg/kg
POLYPROPYLENE GLYCOL GLYCEROL TRIETHER	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 50 mg/l
POLYPROPYLENE GLYCOL GLYCEROL TRIETHER	Ingestion	Rat	LD50 4,600 mg/kg
N,N-DI(2-HYDROXYPROPYL) ANILINE	Dermal	Rabbit	LD50 > 2,000 mg/kg
N,N-DI(2-HYDROXYPROPYL) ANILINE	Ingestion	Rat	LD50 3,800 mg/kg
DIPROPYLENE GLYCOL	Dermal	Rabbit	LD50 > 5,010 mg/kg
DIPROPYLENE GLYCOL	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 2.34 mg/l
DIPROPYLENE GLYCOL	Ingestion	Rat	LD50 > 14,800 mg/kg

ATE = acute toxicity estimate

#### Skin Corrosion/Irritation

Name	Species	Value
POLYPROPYLENE GLYCOL GLYCEROL TRIETHER	Rabbit	No significant irritation
N,N-DI(2-HYDROXYPROPYL) ANILINE	Professio	Minimal irritation
	nal	
	judgeme	
	nt	
DIPROPYLENE GLYCOL	Rabbit	No significant irritation

Serious Eve Damage/Irritation

Species	Value
Rabbit	Mild irritant
Professio	Corrosive
nal	
judgeme	
nt	
Rabbit	No significant irritation
	Rabbit Professio nal judgeme nt

#### **Skin Sensitization**

Name	Species	Value
DIPROPYLENE GLYCOL	Guinea	Not classified
	pig	

### **Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity** 

Name	Route	Value
DIPROPYLENE GLYCOL	In Vitro	Not mutagenic
DIPROPYLENE GLYCOL	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
DIPROPYLENE GLYCOL	Ingestion	Multiple	Not carcinogenic
		animal	
		species	

### Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
DIPROPYLENE GLYCOL	Ingestion	Not classified for development	Rat	NOAEL 5,000 mg/kg/day	during organogenesi s

### Target Organ(s)

### Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
DIPROPYLENE GLYCOL	Ingestion	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 470 mg/kg/day	105 weeks
DIPROPYLENE GLYCOL	Ingestion	heart	Not classified	Rat	NOAEL 470 mg/kg/day	105 weeks
DIPROPYLENE GLYCOL	Ingestion	endocrine system   liver	Not classified	Rat	NOAEL 3,040 mg/kg/day	105 weeks
DIPROPYLENE GLYCOL	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 115 mg/kg/day	105 weeks
DIPROPYLENE GLYCOL	Ingestion	skin   bone, teeth, nails, and/or hair   hematopoietic system   immune system   nervous system   vascular system	Not classified	Rat	NOAEL 3,040 mg/kg/day	105 weeks

## **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

## **SECTION 12: Ecological information**

No data available.

## **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product—that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

## **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

## **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## Global inventory status

Contact 3M for more information. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

## **SECTION 16: Other information**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 3 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

### **HMIS Hazard Classification**

**Health:** 3 Flammability: 1 Physical Hazard: 0 Personal Protection: X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV

### 3M(TM) Scotchcast(TM) Electrical Insulating Resin 2104, Part B

program. HMIS® is a registered mark of the American Coatings Association (ACA).

Document group:	25-1043-6	Version number:	5.02
Issue Date:	2022/06/26	Supercedes Date:	2020/10/21

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca



## Safety Data Sheet

Copyright, 2022, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 25-0742-4
 Version number:
 6.00

 Issue Date:
 2022/06/26
 Supercedes Date:
 2020/10/16

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

## **SECTION 1: Identification**

#### 1.1. Product identifier

3M(TM) Scotchcast(TM) Electrical Insulating Resin 2104, Part A

**Product Identification Numbers** 

LH-A100-0574-7 LH-A100-0574-8 LH-A100-0574-9 LH-A100-0575-0 LH-A100-0575-1

LH-A100-1638-5 80-6116-1275-7

#### 1.2. Recommended use and restrictions on use

## **Intended Use**

Electrical

#### Specific Use

Part A of two part electrical resin

#### Restrictions on use

Not applicable

## 1.3. Supplier's details

Company: 3M Canada Company
Division: Electrical Markets Division

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

**Telephone:** (800) 364-3577 **Website:** www.3M.ca

#### 1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

## **SECTION 2: Hazard identification**

## 2.1. Classification of the substance or mixture

Acute Toxicity (inhalation): Category 3. Serious Eye Damage/Irritation: Category 2A. Skin Corrosion/Irritation: Category 2.

Respiratory Sensitizer: Category 1.

## 3M(TM) Scotchcast(TM) Electrical Insulating Resin 2104, Part A

Skin Sensitizer: Category 1A.

Specific Target Organ Toxicity (single exposure): Category 3. Specific Target Organ Toxicity (repeated exposure): Category 1.

#### 2.2. Label elements

#### Signal word

Danger

#### **Symbols**

Skull and crossbones | Exclamation mark | Health Hazard |

#### **Pictograms**



#### Hazard statements

Toxic if inhaled. Causes serious eye irritation. Causes skin irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause respiratory irritation.

Causes damage to organs through prolonged or repeated exposure: respiratory system

#### **Precautionary statements**

#### **Prevention:**

Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. In case of inadequate ventilation wear respiratory protection. Wear protective gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash exposed skin thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

#### Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTRE or doctor/physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

#### Storage:

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

#### Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

#### 2.3. Other hazards

None known.

# **SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
PHTHALIC ACID, DI-C11-14-	68515-47-9	35 - 50	1,2-Benzenedicarboxylic acid, di-C11-14-

Page: 2 of 11

BRANCHED ALKYL ESTERS,			branched alkyl esters, C13-rich
C13-RICH			-
POLYMETHYLENE	9016-87-9	< 35	Isocyanic acid,
POLYPHENYLENE			polymethylenepolyphenylene ester
ISOCYANATE			
1,3-BUTADIENE,	69102-90-5	15 - 25	1,3-Butadiene, homopolymer, hydroxy-
HOMOPOLYMER,			terminated
HYDROXY-TERMINATED			
P,P'-	101-68-8	< 20	Benzene, 1,1'-methylenebis[4-isocyanato-
METHYLENEBIS(PHENYL			
ISOCYANATE)			
1,1'-	26447-40-5	< 10	Benzene, 1,1'-methylenebis[isocyanato-
METHYLENEBIS(ISOCYANA			
TOBENZENE)			
PHENYL ISOCYANATE	103-71-9	< 0.5	Benzene, isocyanato-
C.I. SOLVENT YELLOW 3	97-56-3	< 0.02	Benzenamine, 2-methyl-4-[(2-
			methylphenyl)azo]-

Polymethylene Polyphenylene Isocyanate is a hazardous Trade Secret material according to WHMIS criteria. Refer to Section 15 for further information.

P,P'-Methylenebis(Phenyl Isocyanate) is a hazardous Trade Secret material according to WHMIS criteria. Refer to Section 15 for further information.

1,1'-Methylenebis(Isocyanatobenzene) is a hazardous Trade Secret material according to WHMIS criteria. Refer to Section 15 for further information.

PHENYL ISOCYANATE is a hazardous Trade Secret material according to WHMIS criteria. Refer to Section 15 for further information.

## **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

### Inhalation:

Remove person to fresh air. Get medical attention.

#### **Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### **Eve Contact:**

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

## 4.2. Most important symptoms and effects, both acute and delayed

Toxic if inhaled. Irritating to the respiratory tract (coughing, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain). Allergic respiratory reaction (difficulty breathing, wheezing, cough, and tightness of chest). Allergic skin reaction (redness, swelling, blistering, and itching). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

### 4.3. Indication of any immediate medical attention and special treatment required Not applicable

## **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

#### **Hazardous Decomposition or By-Products**

<b>Substance</b>	<u>Condition</u>
Isocyanates	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Cyanide	During Combustion
Oxides of Nitrogen	During Combustion

#### 5.3. Special protective actions for fire-fighters

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA). Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

#### 6.2. Environmental precautions

Avoid release to the environment.

## 6.3. Methods and material for containment and cleaning up

Contain spill. Pour isocyanate decontaminant solution (90% water, 8% concentrated ammonia, 2% detergent) on spill and allow to react for 10 minutes. Or pour water on spill and allow to react for more than 30 minutes. Cover with absorbent material. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

For industrial or professional use only. Not for consumer sale or use. Do not use in a confined area with minimal air exchange. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

## 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from amines.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

Occupational exposure limits

## 3M(TM) Scotchcast(TM) Electrical Insulating Resin 2104, Part A

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
P,P'-	101-68-8	ACGIH	TWA:0.005 ppm	
METHYLENEBIS(PHENYL				
ISOCYANATE)				
PHENYL ISOCYANATE	103-71-9	ACGIH	TWA:0.005 ppm;STEL:0.015	Dermal/Respiratory
			ppm	Sensitizer

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

#### 8.2. Exposure controls

#### **8.2.1.** Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

#### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

**Indirect Vented Goggles** 

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Fluoroelastomer

Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

# **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

	 J	
Physical state		Liquid

Specific Physical Form:	Resin
Colour	Dark Green
Odour	Isocvanate
Odour threshold	No Data Available
pH	No Data Available
Melting point/Freezing point	No Data Available
Boiling point	>= 110 °C
Flash Point	110 °C [Test Method:Closed Cup]
Evaporation rate	No Data Available
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	No Data Available
Flammable Limits(UEL)	No Data Available
Vapour Pressure	No Data Available
Vapour Density and/or Relative Vapour Density	No Data Available
Density	1.04 g/ml
Relative density	1.04 [Ref Std:WATER=1]
Water solubility	Slight (less than 10%)
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Viscosity/Kinematic Viscosity	1,400 mPa-s - 2,000 mPa-s
Volatile Organic Compounds	No Data Available
Percent volatile as Text	Negligible
VOC Less H2O & Exempt Solvents	No Data Available
Average particle size	No Data Available
Bulk density	No Data Available
Molecular weight	No Data Available
Softening point	No Data Available

# **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

## 10.2. Chemical stability

Stable.

## 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

## 10.4. Conditions to avoid

Not determined

## 10.5. Incompatible materials

Amines

Alcohols

Water

Not Applicable

# 10.6. Hazardous decomposition products

Substance

**Condition** 

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

## **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

## 11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### **Inhalation:**

Toxic if inhaled. Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic Respiratory Reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest. May cause additional health effects (see below).

#### **Skin Contact:**

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### **Eve Contact:**

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

#### **Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

### **Additional Health Effects:**

#### Prolonged or repeated exposure may cause target organ effects:

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

#### Carcinogenicity:

Ingredient	CAS No.	Class Description	Regulation
o-Aminoazotoluene	97-56-3	Anticipated human carcinogen	National Toxicology Program Carcinogens
ortho-Aminoazotoluene	97-56-3	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

#### **Additional Information:**

Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

## **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### **Acute Toxicity**

Name	Route	Species	Value
------	-------	---------	-------

Overall product	Inhalation- Vapor(4 hr)		No data available; calculated ATE >2 -=10 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
POLYMETHYLENE POLYPHENYLENE ISOCYANATE	Dermal	Rabbit	LD50 > 5,000 mg/kg
POLYMETHYLENE POLYPHENYLENE ISOCYANATE	Inhalation-	Rat	LC50 0.368 mg/l
	Dust/Mist		
	(4 hours)		
POLYMETHYLENE POLYPHENYLENE ISOCYANATE	Ingestion	Rat	LD50 31,600 mg/kg
1,3-BUTADIENE, HOMOPOLYMER, HYDROXY-	Dermal		LD50 estimated to be > 5,000 mg/kg
TERMINATED			
1,3-BUTADIENE, HOMOPOLYMER, HYDROXY-	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
TERMINATED			
P,P'-METHYLENEBIS(PHENYL ISOCYANATE)	Dermal	Rabbit	LD50 > 5,000 mg/kg
P,P'-METHYLENEBIS(PHENYL ISOCYANATE)	Inhalation-	Rat	LC50 0.368 mg/l
	Dust/Mist		
	(4 hours)		
P,P'-METHYLENEBIS(PHENYL ISOCYANATE)	Ingestion	Rat	LD50 31,600 mg/kg
1,1'-METHYLENEBIS(ISOCYANATOBENZENE)	Dermal	Rabbit	LD50 > 5,000 mg/kg
1,1'-METHYLENEBIS(ISOCYANATOBENZENE)	Inhalation-	Rat	LC50 0.368 mg/l
	Dust/Mist		
	(4 hours)		
1,1'-METHYLENEBIS(ISOCYANATOBENZENE)	Ingestion	Rat	LD50 31,600 mg/kg
PHENYL ISOCYANATE	Dermal	Rat	LD50 > 5,000 mg/kg
PHENYL ISOCYANATE	Inhalation-	Rat	LC50 0.022 mg/l
	Vapor (4		
	hours)		
PHENYL ISOCYANATE	Ingestion	Rat	LD50 887 mg/kg

ATE = acute toxicity estimate

## Skin Corrosion/Irritation

Name	Species	Value
POLYMETHYLENE POLYPHENYLENE ISOCYANATE	official classifica tion	Irritant
P,P'-METHYLENEBIS(PHENYL ISOCYANATE)	official classifica tion	Irritant
1,1'-METHYLENEBIS(ISOCYANATOBENZENE)	official classifica tion	Irritant
PHENYL ISOCYANATE	Rabbit	Corrosive

**Serious Eye Damage/Irritation** 

Name	Species	Value
POLYMETHYLENE POLYPHENYLENE ISOCYANATE	official	Severe irritant
	classifica	
	tion	
P,P'-METHYLENEBIS(PHENYL ISOCYANATE)	official	Severe irritant
	classifica	
	tion	
1,1'-METHYLENEBIS(ISOCYANATOBENZENE)	official	Severe irritant
	classifica	
	tion	
PHENYL ISOCYANATE	Rabbit	Corrosive

## **Skin Sensitization**

Name	Species	Value
POLYMETHYLENE POLYPHENYLENE ISOCYANATE	official	Sensitizing
	classifica	
	tion	
P,P'-METHYLENEBIS(PHENYL ISOCYANATE)	official	Sensitizing
	classifica	
	tion	

Page: 8 of 11

## 3M(TM) Scotchcast(TM) Electrical Insulating Resin 2104, Part A

1,1'-METHYLENEBIS(ISOCYANATOBENZENE)	official classifica tion	Sensitizing
PHENYL ISOCYANATE	Guinea pig	Sensitizing

**Respiratory Sensitization** 

Name	Species	Value
POLYMETHYLENE POLYPHENYLENE ISOCYANATE	Human	Sensitizing
P,P'-METHYLENEBIS(PHENYL ISOCYANATE)	Human	Sensitizing
1,1'-METHYLENEBIS(ISOCYANATOBENZENE)	Human	Sensitizing
PHENYL ISOCYANATE	similar	Sensitizing
	compoun	
	ds	

**Germ Cell Mutagenicity** 

Name	Route	Value
POLYMETHYLENE POLYPHENYLENE ISOCYANATE	In Vitro	Some positive data exist, but the data are not sufficient for classification
P,P'-METHYLENEBIS(PHENYL ISOCYANATE)	In Vitro	Some positive data exist, but the data are not sufficient for classification
1,1'-METHYLENEBIS(ISOCYANATOBENZENE)	In Vitro	Some positive data exist, but the data are not sufficient for classification
PHENYL ISOCYANATE	In vivo	Not mutagenic
PHENYL ISOCYANATE	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
POLYMETHYLENE POLYPHENYLENE ISOCYANATE	Inhalation	Rat	Some positive data exist, but the data are not
			sufficient for classification
P,P'-METHYLENEBIS(PHENYL ISOCYANATE)	Inhalation	Rat	Some positive data exist, but the data are not
			sufficient for classification
1,1'-METHYLENEBIS(ISOCYANATOBENZENE)	Inhalation	Rat	Some positive data exist, but the data are not
			sufficient for classification

## **Reproductive Toxicity**

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
POLYMETHYLENE POLYPHENYLENE ISOCYANATE	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesi s
P,P'-METHYLENEBIS(PHENYL ISOCYANATE)	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesi s
1,1'- METHYLENEBIS(ISOCYANATOBENZE NE)	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesi s
PHENYL ISOCYANATE	Ingestion	Not classified for development	Mouse	NOAEL 9.8 mg/kg/day	during gestation

## Target Organ(s)

Specific Target Organ Toxicity - single exposure

Specific Target Organ Toxicity - single exposure							
Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration	
POLYMETHYLENE	Inhalation	respiratory irritation	May cause respiratory irritation	official	NOAEL Not		
POLYPHENYLENE				classifica	available		
ISOCYANATE				tion			

Page: 9 of 11

P,P'- METHYLENEBIS(PHEN	Inhalation	respiratory irritation	May cause respiratory irritation	official classifica	NOAEL Not available	
YL ISOCYANATE)				tion	avaliable	
1,1'- METHYLENEBIS(ISOCY ANATOBENZENE)	Inhalation	respiratory irritation	May cause respiratory irritation	official classifica tion	NOAEL Not available	
PHENYL ISOCYANATE	Inhalation	respiratory irritation	May cause respiratory irritation	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
POLYMETHYLENE POLYPHENYLENE ISOCYANATE	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
P,P'- METHYLENEBIS(PHEN YL ISOCYANATE)	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
1,1'- METHYLENEBIS(ISOCY ANATOBENZENE)	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
PHENYL ISOCYANATE	Inhalation	respiratory system   hematopoietic system   liver   immune system   nervous system   eyes   kidney and/or bladder	Not classified	Rat	NOAEL 0.00279 mg/l	4 weeks

#### **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

## **SECTION 12: Ecological information**

No data available.

# **SECTION 13: Disposal considerations**

#### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

# **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

## **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Global inventory status

Contact 3M for more information. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

**Trade Secret Information:** 

HMIRA Registry Number: Filing date: Claim status: Date of decision:

10750 09/12/2016 Claim for exemption has been

filed.

## **SECTION 16: Other information**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

#### **HMIS Hazard Classification**

**Health:** \*3 Flammability: 1 Physical Hazard: 0 Personal Protection: X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

Document group:	25-0742-4	Version number:	6.00
Issue Date:	2022/06/26	Supercedes Date:	2020/10/16

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

#### 3M Canada SDSs are available at www.3M.ca