

# Safety Data Sheet

Copyright, 2024, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 10-8191-8
 Version number:
 11.01

 Issue Date:
 2024/08/19
 Supercedes Date:
 2024/07/31

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

# **SECTION 1: Identification**

### 1.1. Product identifier

3M(TM) GLASS POLISHING COMPOUND PN60150

#### **Product Identification Numbers**

41-2009-0270-2 60-0900-0596-2 60-9800-1020-5 60-9800-1124-5 DC-2729-9171-2 DN-9999-8130-6 GC-8007-5266-6 HB-0040-6477-8 HC-0006-0070-6 IA-2601-0229-7 IA-2601-0421-0 J3-0103-8055-1 JC-2200-7571-0 JC-2200-9561-9

### 1.2. Recommended use and restrictions on use

### **Intended Use**

Abrasive Product

### **Specific Use**

Glass Polishing. For industrial/occupational use only. Not for consumer sale or use.

### Restrictions on use

Not applicable

# 1.3. Supplier's details

**Company:** 3M Canada Company **Division:** Abrasive Systems Division

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

**Telephone:** (800) 364-3577 **Website:** www.3M.ca

### 1.4. Emergency telephone number

Medical Emergency Telephone: 1-800-3M HELPS / 1800 364 3577

# **SECTION 2: Hazard identification**

## 2.1. Classification of the substance or mixture

Not classified according to the Canadian Hazardous Products Regulation.

### 2.2. Label elements

Signal word

Not applicable.

### **Symbols**

Not applicable.

### **Pictograms**

Not applicable.

### 2.3. Other hazards

None known.

# **SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Water	7732-18-5	70 - 80	Water
Cerium Oxide (CeO2)	1306-38-3	15 - 30	Cerium oxide (CeO2)
Lanthanum Trioxide	1312-81-8	< 5	Lanthanum oxide (La2O3)
(Hydroxyethyl)Cellulose	9004-62-0	< 2	Cellulose, 2-hydroxyethyl ether

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

#### **Skin Contact:**

If exposed, wash with soap and water. If signs/symptoms develop, get medical attention.

#### **Eve Contact**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

### If Swallowed:

Do not induce vomiting. Rinse mouth. If you feel unwell, get medical attention.

# 4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

# 5.1. Suitable extinguishing media

Material will not burn. Use a fire fighting agent suitable for the surrounding fire.

# 5.2. Unsuitable extinguishing media

None Determined

## 5.3. Special hazards arising from the substance or mixture

None inherent in this product.

# **Hazardous Decomposition or By-Products**

\_\_\_\_\_\_

**Substance** 

Condition

None known.

**During Combustion** 

### 5.4. Special protection actions for fire-fighters

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

# **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Observe precautions from other sections.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Avoid breathing of dust created by sanding, grinding or machining. Avoid release to the environment.

# 7.2. Conditions for safe storage including any incompatibilities

Keep from freezing.

# **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this SDS.

### 8.2. Exposure controls

# 8.2.1. Engineering controls

Provide appropriate local exhaust ventilation for sanding, grinding or machining. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

# Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

### Skin/hand protection

No chemical protective gloves are required.

# **Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

# **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

The state of basic physical and chemical properties	T · · · 1				
Physical state	Liquid				
Specific Physical Form:	Dispersion				
Colour	White				
Odour	Slight Solvent				
Odour threshold No Data Available					
pH	6 - 9				
Melting point/Freezing point	Not Applicable				
Boiling point	100 ℃				
Flash Point	No flash point				
Evaporation rate	No Data Available				
Flammability	Not Applicable				
Flammable Limits(LEL)	Not Applicable				
Flammable Limits(UEL)	Not Applicable				
Vapour Pressure	2,306.5 Pa [@ 20 °C ]				
Vapour Density and/or Relative Vapour Density	No Data Available				
Density	1.17 - 1.3 g/cm3				
Relative density	1.17 - 1.3				
Water solubility	Moderate				
Solubility- non-water	No Data Available				
Partition coefficient: n-octanol/ water	No Data Available				
Autoignition temperature	Not Applicable				
Decomposition temperature	No Data Available				
Kinematic Viscosity	No Data Available				
Volatile Organic Compounds 0.0013 % [Details:Calculated]					
Percent volatile 78 % [Details: Calculated including water]					
VOC Less H2O & Exempt Solvents	0.036 g/l [Details: Calculated]				
Molecular weight	No Data Available				

Particle Characteristics	Not Applicable

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

### 10.2. Chemical stability

Stable.

## 10.3. Possibility of hazardous reactions

Page: 4 of 8

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

None known.

### 10.5. Incompatible materials

None known.

# 10.6. Hazardous decomposition products

**Substance** 

None known.

**Condition** 

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

# 11.1. Information on Toxicological effects

### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

## **Inhalation:**

Dust from grinding, sanding or machining may cause irritation of the respiratory system. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

### **Skin Contact:**

Contact with the skin during product use is not expected to result in significant irritation.

### **Eye Contact:**

Dust created by grinding, sanding, or machining may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

### **Ingestion:**

No known health effects.

### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

# **Acute Toxicity**

reute I oxiety			
Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Lanthanum Trioxide	Dermal	Professio nal judgeme nt	LD50 estimated to be > 5,000 mg/kg
Lanthanum Trioxide	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 5.3 mg/l
Lanthanum Trioxide	Ingestion	Rat	LD50 > 10,000 mg/kg

Page: 5 of 8

(Hydroxyethyl)Cellulose	Dermal		LD50 estimated to be > 5,000 mg/kg	
(Hydroxyethyl)Cellulose	Ingestion	Rat	LD50 > 5,000  mg/kg	

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

Name	Species	Value
Lanthanum Trioxide	Rabbit	No significant irritation
(Hydroxyethyl)Cellulose	Human and animal	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Lanthanum Trioxide	Rabbit	Mild irritant
(Hydroxyethyl)Cellulose	Rabbit	No significant irritation

### Skin Sensitization

Name	Species	Value
Lanthanum Trioxide	Guinea	Not classified
	pig	

### **Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

### Germ Cell Mutagenicity

For the component/components, either no data are currently available or the data are not sufficient for classification.

### Carcinogenicity

For the component/components, either no data are currently available or the data are not sufficient for classification.

### Reproductive Toxicity

### Reproductive and/or Developmental Effects

For the component/components, either no data are currently available or the data are not sufficient for classification.

## Target Organ(s)

## **Specific Target Organ Toxicity - single exposure**

For the component/components, either no data are currently available or the data are not sufficient for classification.

# Specific Target Organ Toxicity - repeated exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

### **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

No data available.

# **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Prior to disposal, consult all applicable authorities and regulations to insure proper classification. Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty and clean product containers may be disposed as non-hazardous waste. Consult your specific regulations and service providers to determine available options and requirements.

# **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

## **SECTION 16: Other information**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 0 Flammability: 0 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document group:	10-8191-8	Version number:	11.01
Issue Date:	2024/08/19	Supercedes Date:	2024/07/31

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE. COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

Page: 7 of 8

3M(TM) GLASS POLISHING COMPOUND PN60150
3M Canada SDSs are available at www.3M.ca