

Safety Data Sheet

Document group:	26-5715-3	Version number:	1.03
Issue Date:	2022/03/30	Supercedes Date:	2021/10/27

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

Standard Abrasives[™] Products, Buff & Blend High Strength HS A-MED, MED-Type F, CRS: Cross Buffs, Wheels, Discs, Rolls, Type 27 Discs, Quick Change

Product Identification Numbers

Product Identification	Numbers			
44-0009-5423-8	66-0000-0108-2	66-0000-0115-7	66-0000-0117-3	66-0000-0118-1
66-0000-0120-7	66-0000-0121-5	66-0000-0608-1	66-0000-0610-7	66-0000-0612-3
66-0000-0619-8	66-0000-0638-8	66-0000-0643-8	66-0000-0700-6	66-0000-0706-3
66-0000-0717-0	66-0000-0726-1	66-0000-0771-7	66-0000-0772-5	66-0000-0829-3
66-0000-0831-9	66-0000-0896-2	66-0000-2757-4	66-0000-2758-2	66-0000-2759-0
66-0000-2772-3	66-0000-2773-1	66-0000-3423-2	66-0000-3430-7	66-0000-3433-1
66-0000-3435-6	66-0000-3436-4	66-0000-3466-1	66-0000-3469-5	66-0000-3470-3
66-0000-3471-1	66-0000-3474-5	66-0000-3476-0	66-0000-3540-3	66-0000-3541-1
66-0000-3542-9	66-0000-3543-7	66-0000-3544-5	66-0000-3545-2	66-0000-3546-0
66-0000-3547-8	66-0000-3549-4	66-0000-3552-8	66-0000-3555-1	66-0000-3557-7
66-0000-3558-5	66-0000-3559-3	66-0000-3560-1	66-0000-3562-7	66-0000-3563-5
66-0000-3565-0	66-0000-3567-6	66-0000-3568-4	66-0000-3569-2	66-0000-3571-8
66-0000-3572-6	66-0000-3573-4	66-0000-3575-9	66-0000-3576-7	66-0000-3581-7
66-0000-3582-5	66-0000-3584-1	66-0000-3585-8	66-0000-3586-6	66-0000-3588-2
66-0000-3590-8	66-0000-3591-6	66-0000-3593-2	66-0000-3594-0	66-0000-3597-3
66-0000-3598-1	66-0000-3599-9	66-0000-4743-2	66-0000-4746-5	66-0000-4750-7
66-0000-4753-1	66-0000-4754-9	66-0000-4757-2	66-0000-4758-0	66-0000-4761-4
66-0000-4762-2	66-0000-4766-3	66-0000-4783-8	66-0000-4785-3	66-0000-4787-9
66-0000-5267-1	66-0000-7811-4	66-0000-7812-2	66-0000-7813-0	66-0000-7814-8
66-0000-7819-7	66-0000-7820-5	66-0000-7822-1	66-0000-7823-9	66-0000-7824-7
66-0000-7825-4	66-0000-7826-2	66-0000-7898-1	66-0000-7961-7	66-0000-7962-5
66-0000-7963-3	66-0000-7964-1	66-0000-7965-8	66-0000-7966-6	66-0000-7967-4
66-0000-7968-2	66-0000-8059-9	66-0000-8175-3	66-0000-8176-1	66-0000-8178-7
66-0000-9873-2	66-0001-0014-0	66-0001-0041-3	66-0001-0055-3	66-0001-0056-1
66-0001-0931-5	66-0001-0932-3	66-0001-0948-9	66-0001-0995-0	66-0001-2993-3
66-0001-2994-1	66-0001-3040-2	66-0001-3171-5	66-0001-3253-1	66-0001-3323-2
66-0001-3354-7	66-0001-3374-5	66-0001-3375-2	66-0001-3376-0	66-0001-3377-8
66-0001-3378-6	66-0001-3379-4	66-0001-3383-6	66-0001-3384-4	66-0001-3385-1
66-0001-3386-9	66-0001-3387-7	66-0001-3388-5	66-0001-3390-1	66-0001-3391-9
66-0001-3392-7	66-0001-3393-5	66-0001-3394-3	66-0001-3395-0	66-0001-3409-9
66-0001-3410-7	66-0001-3411-5	66-0001-3412-3	66-0001-3413-1	66-0001-3414-9
66-0001-3415-6	66-0001-3416-4	66-0001-3417-2	66-0001-3423-0	66-0001-3498-2
66-0001-3519-5	66-0001-3522-9	66-0001-3581-5	66-0001-3607-8	66-0001-3608-6
66-0001-3609-4	66-0001-3612-8	66-0001-3638-3	66-0001-3686-2	66-0001-3687-0
66-0001-3795-1	66-0001-3819-9	66-0001-3822-3	66-0001-3907-2	66-0001-3918-9
66-0001-3969-2	66-0001-3972-6	66-0002-0395-1	66-0002-0396-9	66-0002-0397-7
66-0002-0398-5	66-0002-0399-3	66-0002-0400-9	66-0002-0401-7	66-0002-0402-5

66-0002-0403-3	66-0002-0407-4	66-0002-0408-2	66-0002-0409-0	66-0002-0410-8
66-0002-0411-6	66-0002-0412-4	66-0002-0413-2	66-0002-2744-8	66-0002-2745-5
66-0002-2764-6	66-0002-2781-0	66-0002-2799-2	66-0002-2811-5	66-0002-3189-5
66-0002-3190-3	66-0002-3191-1	66-0002-3192-9	66-0002-3193-7	66-0002-3194-5
66-0002-3195-2	66-0002-3226-5	HB-0045-6042-9	HB-0046-5691-2	HB-0046-8144-9

1.2. Recommended use and restrictions on use

Intended Use

Abrasive Product

Restrictions on use

Not applicable

1.3. Supplier's details

Company:	Standard Abrasives
Division:	Abrasive Systems Division
Address:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)
Website:	www.3m.com

1.4. Emergency telephone number

1-888-3M HELPS (1-888-364-3577)

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Not classified according to the Canadian Hazardous Products Regulation.

2.2. Label elements

Signal word

Not applicable.

Symbols Not applicable.

Pictograms Not applicable.

2.3. Other hazards

None known.

59% of the mixture consists of ingredients of unknown acute oral toxicity.59% of the mixture consists of ingredients of unknown acute dermal toxicity.60% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Aluminum Oxide Mineral (non-	1344-28-1	35 - 75	Aluminum oxide (non-fibrous)
fibrous)			
Cured Resin	Mixture	15 - 60	Not Applicable

Standard Abrasives[™] Products, Buff & Blend High Strength HS A-MED, MED-Type F, CRS: Cross Buffs, Wheels, Discs, Rolls, Type 27 Discs, Quick Change

Fiberglass Plate (Type 27 Discs)	Mixture	<= 20	Not Applicable
Nylon Fiber	Mixture	< 20	Not Applicable
Attachment Button	Mixture	<= 5	Not Applicable
Fiberglass Core (Wheels)	Mixture	<= 5	Not Applicable
Metal Eyelet (Cross Buffs)	Mixture	<= 5	Not Applicable
Titanium Dioxide	13463-67-7	0.25 - 3.5	Titanium oxide (TiO2)
Cured Resin (Attachment	Mixture	< 3	Not Applicable
Button)			
Filler	1317-65-3	0.5 - 2	Limestonests primarily of calcium
			carbonate.
Silica	7631-86-9	0.4 - 2	Silica
Iron Oxide (Fe2O3)	1309-37-1	< 1.5	Iron oxide (Fe2O3)
Quartz Silica	14808-60-7	< 0.2	Quartz (SiO2)

Cured Resin is a non-hazardous Trade Secret material according to WHMIS criteria. Nylon Fiber is a non-hazardous Trade Secret material according to WHMIS criteria. Fiberglass Core (Wheels) is a non-hazardous Trade Secret material according to WHMIS criteria. Metal Evelet (Cross Buffs) is a non-hazardous Trade Secret material according to WHMIS criteria. Attachment Button is a non-hazardous Trade Secret material according to WHMIS criteria. Cured Resin (Attachment Button) is a non-hazardous Trade Secret material according to WHMIS criteria. Fiberglass Plate (Type 27 Discs) is a non-hazardous Trade Secret material according to WHMIS criteria.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

No need for first aid is anticipated.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance Carbon monoxide Condition **During Combustion** Carbon dioxide

During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Observe precautions from other sections.

6.2. Environmental precautions

Not applicable.

6.3. Methods and material for containment and cleaning up

Not applicable.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing of dust created by sanding, grinding or machining. Damaged product can break apart during use and cause serious injury to face or eyes. Check product for damage such as cracks or nicks prior to use. Replace if damaged. Always wear eye and face protection when working at sanding or grinding operations or when near such operations. Combustible dust may form by action of this product on another material (substrate). Dust generated from the substrate during use of this product may be explosive if in sufficient concentration with an ignition source. Dust deposits should not be allowed to accumulate on surfaces because of the potential for secondary explosions.

7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Iron Oxide (Fe2O3)	1309-37-1	ACGIH	TWA(respirable fraction):5	
			mg/m3	
CAS NO SEQ117921	1317-65-3	ACGIH	TWA(inhalable	
			particulates):10 mg/m3	
CAS NO SEQ117922	1317-65-3	ACGIH	TWA(respirable particles):3	
			mg/m3	
Aluminum, insoluble compounds	1344-28-1	ACGIH	TWA(respirable fraction):1	
			mg/m3	
CAS NO SEQ117921	1344-28-1	ACGIH	TWA(inhalable	
			particulates):10 mg/m3	
CAS NO SEQ117922	1344-28-1	ACGIH	TWA(respirable particles):3	
			mg/m3	
Titanium Dioxide	13463-67-7	ACGIH	TWA:10 mg/m3	
Quartz Silica	14808-60-7	ACGIH	TWA(respirable	
			fraction):0.025 mg/m3	
CAS NO SEQ117921	7631-86-9	ACGIH	TWA(inhalable	
			particulates):10 mg/m3	
CAS NO SEQ117922	7631-86-9	ACGIH	TWA(respirable particles):3	

			mg/m3		
ACGIH : American Conference of Government	ntal Industrial H	Iygienists			
AIHA : American Industrial Hygiene Associat	AIHA : American Industrial Hygiene Association				
CMRG : Chemical Manufacturer's Recommended Guidelines					
TWA: Time-Weighted-Average					
STEL: Short Term Exposure Limit					
CEIL: Ceiling	1				

8.2. Exposure controls

8.2.1. Engineering controls

Provide appropriate local exhaust ventilation for sanding, grinding or machining. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Warning: Excessive operating speed or generation of extreme heat may result in harmful emissions. Use local exhaust ventilation. Provide local exhaust at process emission sources to control exposure near the source and to prevent the escape of dust into the work area. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

8.2.2. Personal protective equipment (PPE)

Eye/face protection

To minimize the risk of injury to face and eyes, always wear eye and face protection when working at sanding or grinding operations or when near such operations. Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Safety Glasses with side shields

Skin/hand protection

Wear appropriate gloves to minimize risk of injury to skin from contact with dust or physical abrasion from grinding or sanding.

Respiratory protection

Assess exposure concentrations of all materials involved in the work process. Consider material being abraded when determining the appropriate respiratory protection. Select and use appropriate respirators to prevent inhalation overexposure.

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid		
Colour	Gold, Red		
Odour	Slight Polymeric		
Odour threshold	Not Applicable		
рН	Not Applicable		
Melting point/Freezing point	Not Applicable		
Boiling point	Not Applicable		
Flash Point	Not Applicable		
Evaporation rate	Not Applicable		

Standard Abrasives™ Products, Buff & Blend High Strength HS A-MED, MED-Type F, CRS: Cross Buffs, Wheels, Discs, Rolls, Type 27 Discs, Quick Change

Flammability (solid, gas)	Not Classified
Flammable Limits(LEL)	Not Applicable
Flammable Limits(UEL)	Not Applicable
Vapour Pressure	Not Applicable
Vapour Density and/or Relative Vapour Density	Not Applicable
Density	Not Applicable
Relative density	Not Applicable
Water solubility	Not Applicable
Solubility- non-water	Not Applicable
Partition coefficient: n-octanol/ water	Not Applicable
Autoignition temperature	Not Applicable
Decomposition temperature	Not Applicable
Viscosity/Kinematic Viscosity	Not Applicable
Volatile Organic Compounds	No Data Available
Percent volatile	No Data Available
VOC Less H2O & Exempt Solvents	No Data Available

Nanoparticles

This material contains nanoparticles.

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Dust from grinding, sanding or machining may cause irritation of the respiratory system. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Mechanical Skin irritation: Signs/symptoms may include abrasion, redness, pain, and itching.

Eye Contact:

Mechanical eye irritation: Signs/symptoms may include pain, redness, tearing and corneal abrasion. Dust created by grinding, sanding, or machining may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

No known health effects.

Carcinogenicity:

Ingredient	CAS No.	Class Description	Regulation
SILICA, CRYSTALLINE (RESPIRABLE SIZE)	14808-60-7	Known human carcinogen	National Toxicology Program Carcinogens
Silica dust, crystalline, in the form of quartz or cristobalite	14808-60-7	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
Titanium dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Additional Information:

This document covers only the 3M product. For complete assessment, when determining the degree of hazard, the material being abraded must also be considered. This product contains titanium dioxide and quartz (crystalline) silica. Cancer of the lungs has been associated with inhalation of high levels of titanium dioxide in animal studies, and occupational exposure to inhaled quartz silica has been associated with silicosis and lung cancer. No exposure to titanium dioxide or quartz silica is expected during the normal handling and use of this product. Titanium dioxide and quartz silica were not detected when air sampling was conducted during simulated use of similar products containing these substances. Therefore, the health effects associated with titanium dioxide and quartz (crystalline) silica are not expected during the normal use of this product.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation- Dust/Mist(4 hr)		No data available; calculated ATE >12.5 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Aluminum Oxide Mineral (non-fibrous)	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminum Oxide Mineral (non-fibrous)	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminum Oxide Mineral (non-fibrous)	Ingestion	Rat	LD50 > 5,000 mg/kg
Titanium Dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium Dioxide	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium Dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Silica	Inhalation- Dust/Mist	Rat	LC50 > 0.691 mg/l

Standard Abrasives[™] Products, Buff & Blend High Strength HS A-MED, MED-Type F, CRS: Cross Buffs, Wheels, Discs, Rolls, Type 27 Discs, Quick Change

	(4 hours)		
Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Filler	Dermal	Rat	LD50 > 2,000 mg/kg
Filler	Inhalation- Dust/Mist (4 hours)	Rat	LC50 3 mg/l
Filler	Ingestion	Rat	LD50 6,450 mg/kg
Iron Oxide (Fe2O3)	Dermal	Not available	LD50 3,100 mg/kg
Iron Oxide (Fe2O3)	Ingestion	Not available	LD50 3,700 mg/kg
Quartz Silica	Dermal		LD50 estimated to be > 5,000 mg/kg
Quartz Silica	Ingestion		LD50 estimated to be > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Aluminum Oxide Mineral (non-fibrous)	Rabbit	No significant irritation
Titanium Dioxide	Rabbit	No significant irritation
Silica	Rabbit	No significant irritation
Filler	Rabbit	No significant irritation
Iron Oxide (Fe2O3)	Rabbit	No significant irritation
Quartz Silica	Professio	No significant irritation
	nal	
	judgeme	
	nt	

Serious Eye Damage/Irritation

Name	Species	Value
Aluminum Oxide Mineral (non-fibrous)	Rabbit	No significant irritation
Titanium Dioxide	Rabbit	No significant irritation
Silica	Rabbit	No significant irritation
Filler	Rabbit	No significant irritation
Iron Oxide (Fe2O3)	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
Titanium Dioxide	Human	Not classified
	and	
	animal	
Silica	Human	Not classified
	and	
	animal	
Iron Oxide (Fe2O3)	Human	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Aluminum Oxide Mineral (non-fibrous)	In Vitro	Not mutagenic
Titanium Dioxide	In Vitro	Not mutagenic
Titanium Dioxide	In vivo	Not mutagenic
Silica	In Vitro	Not mutagenic
Iron Oxide (Fe2O3)	In Vitro	Not mutagenic
Quartz Silica	In Vitro	Some positive data exist, but the data are not sufficient for classification
Quartz Silica	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Aluminum Oxide Mineral (non-fibrous)	Inhalation	Rat	Not carcinogenic
Titanium Dioxide	Ingestion	Multiple	Not carcinogenic
		animal	
		species	
Titanium Dioxide	Inhalation	Rat	Carcinogenic
Silica	Not	Mouse	Some positive data exist, but the data are not
	Specified		sufficient for classification
Iron Oxide (Fe2O3)	Inhalation	Human	Some positive data exist, but the data are not
			sufficient for classification
Quartz Silica	Inhalation	Human	Carcinogenic
		and	
		animal	

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesi s
Filler	Ingestion	Not classified for development	Rat	NOAEL 625 mg/kg/day	premating & during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Filler	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.812 mg/l	90 minutes

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Aluminum Oxide Mineral (non-fibrous)	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminum Oxide Mineral (non-fibrous)	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Titanium Dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium Dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Filler	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Iron Oxide (Fe2O3)	Inhalation	pulmonary fibrosis pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure
Quartz Silica	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Standard Abrasives™ Products, Buff & Blend High Strength HS A-MED, MED-Type F, CRS: Cross Buffs, Wheels, Discs, Rolls, Type 27 Discs, Quick Change

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Prior to disposal, consult all applicable authorities and regulations to insure proper classification. The substrate that was abraded must be considered as a factor in the disposal method for this product. Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product may be placed in a landfill properly designed for industrial waste.

SECTION 14: Transport Information

Not regulated per U.S. DOT, IATA or IMO.

These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. The manufacturer's transportation classifications are based on product formulation, packaging, the manufacturer's policies and the manufacturer's understanding of applicable current regulations. The manufacturer does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling, or marking requirements. The original Standard Abrasives package is certified for U.S. ground shipment only. If you are shipping by air or ocean, the package may not meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 0 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document group:	26-5715-3	Version number:	1.03
Issue Date:	2022/03/30	Supercedes Date:	2021/10/27

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

Standard Abrasives Canada SDSs are available at www.3m.ca