



Safety Data Sheet

Copyright,2020, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|------------------------|------------|-------------------------|------------|
| Document group: | 25-8181-7 | Version number: | 4.03 |
| Issue Date: | 2020/10/21 | Supersedes Date: | 2019/07/30 |

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3M(TM) METAL PRIMER P592, CLEAR

Product Identification Numbers

62-5271-0250-3 62-5271-0255-2 DE-2729-2805-7

1.2. Recommended use and restrictions on use

Intended Use

Industrial use

Restrictions on use

Not applicable

1.3. Supplier's details

| | |
|-------------------|--|
| Company: | 3M Canada Company |
| Division: | Industrial Adhesives and Tapes Division |
| Address: | 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1 |
| Telephone: | (800) 364-3577 |
| Website: | www.3M.ca |

1.4. Emergency telephone number

Medical Emergency Telephone: 1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Flammable Liquid: Category 2.

Serious Eye Damage/Irritation: Category 2A.

Skin Sensitizer: Category 1.

Specific Target Organ Toxicity (single exposure): Category 3.

Specific Target Organ Toxicity (repeated exposure): Category 2.

2.2. Label elements

Signal word

3M(TM) METAL PRIMER P592, CLEAR

Danger

Symbols

Flame | Exclamation mark | Health Hazard |

Pictograms



Hazard statements

Highly flammable liquid and vapour.

Causes serious eye irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure: respiratory system |

Precautionary statements

Prevention:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Use non-sparking tools. Take action to prevent static discharges. Keep container tightly closed. Use explosion-proof electrical/ventilating/lighting equipment. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves and eye/face protection. Wash exposed skin thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell. In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage:

Store in a well-ventilated place. Keep cool. Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

| Ingredient | C.A.S. No. | % by Wt | Common Name |
|--|------------|-------------------------|---|
| Ethyl Alcohol | 64-17-5 | 80 - 100 Trade Secret * | Ethanol |
| 1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]- | 1760-24-3 | 1 - 5 Trade Secret * | 1,2-Ethanediamine, N-[3-(trimethoxysilyl)propyl]- |

*The actual concentration of this ingredient has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

| <u>Substance</u> | <u>Condition</u> |
|------------------|-------------------|
| Carbon monoxide | During Combustion |
| Carbon dioxide | During Combustion |

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools.

Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire extinguishing foam that is resistant to polar solvents. Working from around the

3M(TM) METAL PRIMER P592, CLEAR

edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial or professional use only. Not for consumer sale or use. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|---------------|------------|--------|---------------|---------------------|
| Ethyl Alcohol | 64-17-5 | ACGIH | STEL:1000 ppm | |

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

3M(TM) METAL PRIMER P592, CLEAR

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|--|
| Physical state | Liquid |
| Colour | Colourless |
| Odour | Alcohol |
| Odour threshold | No Data Available |
| pH | No Data Available |
| Melting point/Freezing point | -114.5 °C |
| Boiling point | 78 °C |
| Flash Point | 12 °C [Test Method: Closed Cup] |
| Evaporation rate | No Data Available |
| Flammability (solid, gas) | Not Applicable |
| Flammable Limits(LEL) | 3 % volume |
| Flammable Limits(UEL) | 19 % volume |
| Vapour Pressure | 5.9 kPa |
| Viscosity/Kinematic Viscosity Viscosity/Kinematic Viscosity | No Data Available |
| Viscosity | |
| Density | 0.79 g/ml |
| Relative density | 0.79 [Ref Std: WATER=1] |
| Water solubility | 1 g/l [@ 20 °C] |
| Solubility- non-water | No Data Available |
| Partition coefficient: n-octanol/ water | No Data Available |
| Autoignition temperature | >=200 °C |
| Decomposition temperature | No Data Available |
| Viscosity/Kinematic Viscosity | No Data Available |
| Volatile Organic Compounds | 781 g/l [Test Method: calculated SCAQMD rule 443.1] [Details: Material VOC] |
| Percent volatile | |
| VOC Less H2O & Exempt Solvents | 98.9 % [Test Method: calculated per CARB title 2] |
| Molecular weight | No Data Available |

Nanoparticles

This material does not contain nanoparticles.

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Sparks and/or flames

Heat

10.5. Incompatible materials

Strong acids

Strong oxidizing agents

10.6. Hazardous decomposition products

| <u>Substance</u> | <u>Condition</u> |
|------------------|------------------|
|------------------|------------------|

| | |
|-------------|--|
| None known. | |
|-------------|--|

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

3M(TM) METAL PRIMER P592, CLEAR

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea. May cause additional health effects (see below).

Additional Health Effects:**Single exposure may cause target organ effects:**

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Prolonged or repeated exposure may cause target organ effects:

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

Additional Information:

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines. This product contains ethanol. Alcoholic beverages and ethanol in alcoholic beverages have been classified by the International Agency for Research on Cancer as carcinogenic to humans. There are also data associating human consumption of alcoholic beverages with developmental toxicity and liver toxicity. Exposure to ethanol during the foreseeable use of this product is not expected to cause cancer, developmental toxicity, or liver toxicity.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|--|--------------------------------|---------|--|
| Overall product | Ingestion | | No data available; calculated ATE >5,000 mg/kg |
| Ethyl Alcohol | Dermal | Rabbit | LD50 > 15,800 mg/kg |
| Ethyl Alcohol | Inhalation-Vapor (4 hours) | Rat | LC50 124.7 mg/l |
| Ethyl Alcohol | Ingestion | Rat | LD50 17,800 mg/kg |
| 1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]- | Dermal | Rabbit | LD50 > 2,000 mg/kg |
| 1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]- | Inhalation-Dust/Mist (4 hours) | Rat | LC50 >1.49, <2.44 mg/l |
| 1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]- | Ingestion | Rat | LD50 1,897 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|--|---------|---------------------------|
| Ethyl Alcohol | Rabbit | No significant irritation |
| 1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]- | Rabbit | Mild irritant |

Serious Eye Damage/Irritation

| Name | Species | Value |
|--|---------|-----------------|
| Ethyl Alcohol | Rabbit | Severe irritant |
| 1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]- | Rabbit | Corrosive |

Skin Sensitization

| Name | Species | Value |
|--|-------------------------|----------------|
| Ethyl Alcohol | Human | Not classified |
| 1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]- | Multiple animal species | Sensitizing |

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

3M(TM) METAL PRIMER P592, CLEAR**Germ Cell Mutagenicity**

| Name | Route | Value |
|---------------|----------|--|
| Ethyl Alcohol | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Ethyl Alcohol | In vivo | Some positive data exist, but the data are not sufficient for classification |

Carcinogenicity

| Name | Route | Species | Value |
|---------------|-----------|-------------------------|--|
| Ethyl Alcohol | Ingestion | Multiple animal species | Some positive data exist, but the data are not sufficient for classification |

Reproductive Toxicity**Reproductive and/or Developmental Effects**

| Name | Route | Value | Species | Test result | Exposure Duration |
|---------------|------------|--------------------------------|---------|-----------------------|--------------------------------|
| Ethyl Alcohol | Inhalation | Not classified for development | Rat | NOAEL 38 mg/l | during gestation |
| Ethyl Alcohol | Ingestion | Not classified for development | Rat | NOAEL 5,200 mg/kg/day | prematuring & during gestation |

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|---------------|------------|-----------------------------------|--|-------------------------|---------------------|-------------------|
| Ethyl Alcohol | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human | LOAEL 2.6 mg/l | 30 minutes |
| Ethyl Alcohol | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human | LOAEL 9.4 mg/l | not available |
| Ethyl Alcohol | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Multiple animal species | NOAEL not available | |
| Ethyl Alcohol | Ingestion | kidney and/or bladder | Not classified | Dog | NOAEL 3,000 mg/kg | |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|--|------------|--------------------------------------|--|---------|-----------------------|-------------------|
| Ethyl Alcohol | Inhalation | liver | Some positive data exist, but the data are not sufficient for classification | Rabbit | LOAEL 124 mg/l | 365 days |
| Ethyl Alcohol | Inhalation | hematopoietic system immune system | Not classified | Rat | NOAEL 25 mg/l | 14 days |
| Ethyl Alcohol | Ingestion | liver | Some positive data exist, but the data are not sufficient for classification | Rat | LOAEL 8,000 mg/kg/day | 4 months |
| Ethyl Alcohol | Ingestion | kidney and/or bladder | Not classified | Dog | NOAEL 3,000 mg/kg/day | 7 days |
| 1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]- | Inhalation | respiratory system | May cause damage to organs though prolonged or repeated exposure | Rat | NOAEL 0.015 mg/l | 90 days |

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 2 Flammability: 3 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address

3M(TM) METAL PRIMER P592, CLEAR

the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: 2 Flammability: 3 Physical Hazard: 0 Personal Protection: J

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

| | | | |
|------------------------|------------|-------------------------|------------|
| Document group: | 25-8181-7 | Version number: | 4.03 |
| Issue Date: | 2020/10/21 | Supersedes Date: | 2019/07/30 |

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca