

Safety Data Sheet

Copyright, 2024, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 25-8829-1
 Version number:
 6.00

 Issue Date:
 2024/09/13
 Supercedes Date:
 2023/02/10

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3M[™] Polyurethane Multi-Purpose Adhesive 5010 Cream

Product Identification Numbers

62-5281-5230-9 62-5281-5235-8 62-5281-8530-9 62-5281-8532-5 HB-0040-9066-6

HB-0041-0134-9 HB-0041-5893-5

1.2. Recommended use and restrictions on use

Intended Use

Industrial use

Specific Use

Adhesive

Restrictions on use

Not applicable

1.3. Supplier's details

Company: 3M Canada Company

Division: Industrial Adhesives and Tapes Division

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

Telephone: (800) 364-3577 **Website:** www.3M.ca

1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1800 364 3577

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 2A.

Skin Corrosion/Irritation: Category 2. Respiratory Sensitizer: Category 1. Skin Sensitizer: Category 1A. Reproductive Toxicity: Category 1B.

Page: 1 of 11

3M[™] Polyurethane Multi-Purpose Adhesive 5010 Cream

Specific Target Organ Toxicity (single exposure): Category 3. Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Exclamation mark | Health Hazard |

Pictograms





Hazard statements

Causes serious eye irritation. Causes skin irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause respiratory irritation. May damage fertility or the unborn child.

Causes damage to organs through prolonged or repeated exposure: respiratory system

Precautionary statements

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. In case of inadequate ventilation wear respiratory protection. Wear protective gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash exposed skin thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTRE or doctor/physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF exposed or concerned: Get medical advice/attention.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Urethane Polymer	Trade Secret	50 - 70	Not Applicable

Page: 2 of 11

1,1'-	26447-40-5	10 - 30 Trade Secret *	Benzene, 1,1'-methylenebis[isocyanato-
Methylenebis(isocyanatobenzen			
e)			
Amorphous Silica	67762-90-7	5 - 10	Siloxanes and Silicones, di-Me, reaction
			products with silica
Diisodecyl Phthalate	68515-49-1	1 - 5 Trade Secret *	1,2-Benzenedicarboxylic acid, di-C9-11-
			branched alkyl esters, C10-rich
2,2'-Dimorpholinodiethyl Ether	6425-39-4	0.1 - 2.5	Morpholine, 4,4'-(oxydi-2,1-ethanediyl)bis-
Diphenylmethane-2,2'-	2536-05-2	0.5 - 1.5 Trade Secret *	Benzene, 1,1'-methylenebis[2-isocyanato-
diisocyanate			

Urethane polymer is a non-hazardous Trade Secret material according to WHMIS criteria.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eve Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Irritating to the respiratory tract (coughing, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain). Allergic respiratory reaction (difficulty breathing, wheezing, cough, and tightness of chest). Allergic skin reaction (redness, swelling, blistering, and itching). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Unsuitable extinguishing media

None Determined

5.3. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance Condition **During Combustion** Isocvanates Carbon monoxide **During Combustion During Combustion** Carbon dioxide

^{*}The actual concentration of this ingredient has been withheld as a trade secret.

3M[™] Polyurethane Multi-Purpose Adhesive 5010 Cream

Hydrogen Cyanide Oxides of Nitrogen Oxides of Sulfur During Combustion During Combustion During Combustion

5.4. Special protection actions for fire-fighters

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA). Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Pour isocyanate decontaminant solution (90% water, 8% concentrated ammonia, 2% detergent) on spill and allow to react for 10 minutes. Or pour water on spill and allow to react for more than 30 minutes. Cover with absorbent material. Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial or professional use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from heat. Store away from amines.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this SDS.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl Rubber

Nitrile Rubber

Polyvinyl Chloride

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Butyl rubber

Apron – Nitrile

Apron - PVC

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid			
Specific Physical Form:	Paste			
Colour	Colourless			
Odour	Slight Urethane			
Odour threshold	No Data Available			
pH	Not Applicable			
Melting point/Freezing point	Not Applicable			
Boiling point	>=200 °C			
Flash Point	No flash point			
Evaporation rate	No Data Available			
Flammability	Not Applicable			
Flammable Limits(LEL)	Not Applicable			
Flammable Limits(UEL)	Not Applicable			
Vapour Pressure	Not Applicable			
Vapour Density and/or Relative Vapour Density	Not Applicable			
Density	1.05 g/cm3			
Relative density	1.05 [Ref Std:WATER=1]			
Water solubility	Slight (less than 10%)			

Dagge 5 of 1

Solubility- non-water	No Data Available		
Partition coefficient: n-octanol/ water	No Data Available		
Autoignition temperature	No Data Available		
Decomposition temperature	No Data Available		
Kinematic Viscosity	380,952 mm2/sec		
Volatile Organic Compounds	0 g/l [Details:EU VOC content]		
Percent volatile	0 %		
VOC Less H2O & Exempt Solvents 0 g/l [Test Method:calculated SCAQMD rule 443.1			
Molecular weight	No Data Available		

Particle Characteristics	Not Applicable
i ai ticle Characteristics	ινοι Αρριισμοίε

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Alcohols

Amines

Water

10.6. Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic Respiratory Reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and

tightness of chest. May cause additional health effects (see below).

Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea. May cause additional health effects (see below).

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Additional Information:

Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation- Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
1,1'-Methylenebis(isocyanatobenzene)	Dermal	Rabbit	LD50 > 5,000 mg/kg
1,1'-Methylenebis(isocyanatobenzene)	Inhalation- Dust/Mist (4 hours)	Rat	LC50 0.368 mg/l
1,1'-Methylenebis(isocyanatobenzene)	Ingestion	Rat	LD50 31,600 mg/kg
Amorphous Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Amorphous Silica	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Amorphous Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Diisodecyl Phthalate	Dermal	Rabbit	LD50 > 3,160 mg/kg
Diisodecyl Phthalate	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 12.5 mg/l
Diisodecyl Phthalate	Ingestion	Rat	LD50 > 9,700 mg/kg
2,2'-Dimorpholinodiethyl Ether	Dermal	Rabbit	LD50 3,030 mg/kg
2,2'-Dimorpholinodiethyl Ether	Ingestion	Rat	LD50 2,020 mg/kg
Diphenylmethane-2,2'-diisocyanate	Dermal	Rabbit	LD50 > 5,000 mg/kg
Diphenylmethane-2,2'-diisocyanate	Inhalation- Dust/Mist (4 hours)	Rat	LC50 0.368 mg/l
Diphenylmethane-2,2'-diisocyanate	Ingestion	Rat	LD50 31,600 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
1,1'-Methylenebis(isocyanatobenzene)	official	Irritant
	classifica	
	tion	
Amorphous Silica	Rabbit	No significant irritation
Diisodecyl Phthalate	Rabbit	Minimal irritation
2,2'-Dimorpholinodiethyl Ether	Rabbit	Mild irritant
Diphenylmethane-2,2'-diisocyanate	official	Irritant
	classifica	
	tion	

Serious Eye Damage/Irritation

Name	Species	Value
1,1'-Methylenebis(isocyanatobenzene)	official classifica tion	Severe irritant
Amorphous Silica	Rabbit	No significant irritation
Diisodecyl Phthalate	Rabbit	Mild irritant
2,2'-Dimorpholinodiethyl Ether	Rabbit	Severe irritant
Diphenylmethane-2,2'-diisocyanate	official	Severe irritant
	classifica	
	tion	

Skin Sensitization

SKIII SCHSICIZATION		
Name	Species	Value
1,1'-Methylenebis(isocyanatobenzene)	Mouse	Sensitizing
Amorphous Silica	Human	Not classified
	and	
	animal	
Diisodecyl Phthalate	Guinea	Not classified
	pig	
2,2'-Dimorpholinodiethyl Ether	Guinea	Not classified
	pig	
Diphenylmethane-2,2'-diisocyanate	Mouse	Sensitizing

Respiratory Sensitization

p			
Name	Species	Value	
1,1'-Methylenebis(isocyanatobenzene)	Human	Sensitizing	
Diphenylmethane-2,2'-diisocyanate	Human	Sensitizing	

Germ Cell Mutagenicity

Name	Route	Value
1,1'-Methylenebis(isocyanatobenzene)	In Vitro	Some positive data exist, but the data are not sufficient for classification
Amorphous Silica	In Vitro	Not mutagenic
Diisodecyl Phthalate	In Vitro	Not mutagenic
Diisodecyl Phthalate	In vivo	Not mutagenic
2,2'-Dimorpholinodiethyl Ether	In Vitro	Not mutagenic
2,2'-Dimorpholinodiethyl Ether	In vivo	Not mutagenic
Diphenylmethane-2,2'-diisocyanate	In Vitro	Some positive data exist, but the data are not
		sufficient for classification

Carcinogenicity

caremogeneity				
Name	Route	Species	Value	
1,1'-Methylenebis(isocyanatobenzene)	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification	
Amorphous Silica	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification	

Page: 8 of 11

Diphenylmethane-2,2'-diisocyanate	Inhalation	Rat	Some positive data exist, but the data are not
			sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
1,1'-Methylenebis(isocyanatobenzene)	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesi s
Amorphous Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Amorphous Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Amorphous Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesi s
Diisodecyl Phthalate	Ingestion	Not classified for female reproduction	Rat	NOAEL 927 mg/kg/day	2 generation
Diisodecyl Phthalate	Ingestion	Not classified for male reproduction	Rat	NOAEL 929 mg/kg/day	2 generation
Diisodecyl Phthalate	Ingestion	Toxic to development	Rat	NOAEL 38 mg/kg/day	2 generation
2,2'-Dimorpholinodiethyl Ether	Ingestion	Not classified for female reproduction	Rat	NOAEL 300 mg/kg/day	premating into lactation
2,2'-Dimorpholinodiethyl Ether	Ingestion	Not classified for male reproduction	Rat	NOAEL 300 mg/kg/day	28 days
2,2'-Dimorpholinodiethyl Ether	Ingestion	Not classified for development	Rat	NOAEL 300 mg/kg/day	premating into lactation
Diphenylmethane-2,2'-diisocyanate	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesi s

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
1,1'- Methylenebis(isocyanatobe nzene)	Inhalation	respiratory irritation	May cause respiratory irritation	official classifica tion	NOAEL Not available	
2,2'-Dimorpholinodiethyl Ether	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Diphenylmethane-2,2'-diisocyanate	Inhalation	respiratory irritation	May cause respiratory irritation	official classifica tion	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
1,1'- Methylenebis(isocyanatobe nzene)	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
Amorphous Silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Diisodecyl Phthalate	Inhalation	respiratory system hematopoietic system liver	Not classified	Rat	NOAEL 0.5 mg/l	2 weeks
Diisodecyl Phthalate	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 0.5 mg/l	2 generation
Diisodecyl Phthalate	Ingestion	endocrine system	Not classified	Rat	NOAEL 686 mg/kg/day	90 days
Diisodecyl Phthalate	Ingestion	liver kidney and/or	Not classified	Rat	NOAEL 500	90 days

Page: 9 of 11

		bladder heart			mg/kg/day	
Diisodecyl Phthalate	Ingestion	hematopoietic	Not classified	Dog	NOAEL 320	90 days
		system			mg/kg/day	
2,2'-Dimorpholinodiethyl Ether	Ingestion	heart endocrine system hematopoietic system liver immune system nervous system kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 300 mg/kg/day	28 days
Diphenylmethane-2,2'- diisocyanate	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Page: 10 of 11

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 2 Flammability: 1 Instability: 1 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document group:	25-8829-1	Version number:	6.00
Issue Date:	2024/09/13	Supercedes Date:	2023/02/10

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca

Page: 11 of 11