



## Safety Data Sheet

Copyright, 2022, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	27-4694-9	<b>Version number:</b>	10.02
<b>Issue Date:</b>	2022/11/13	<b>Supersedes Date:</b>	2020/10/28

## SECTION 1: Identification

### 1.1. Product identifier

3M™ Semi-Rigid Parts/SMC/Fiberglass Repair Adhesive-3 Minute PN 08237

#### Product Identification Numbers

LB-K100-0747-2      41-9103-0513-9      60-4550-5031-4      HB-0044-0435-4      XS-0414-1917-6

### 1.2. Recommended use and restrictions on use

#### Recommended use

Automotive

### 1.3. Supplier's details

**Company:** 3M Canada Company  
**Division:** Automotive Aftermarket  
**Address:** 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

**Telephone:** (800) 364-3577

**E Mail:**

### 1.4. Emergency telephone number

Medical Emergency Telephone: 1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

**This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS) or Article Information Sheet (AIS) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:**

27-4720-2, 27-4348-2

Transport in accordance with applicable regulations.

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit

for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

**3M Canada SDSs are available at [www.3M.ca](http://www.3M.ca)**



## Safety Data Sheet

Copyright,2022, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	27-4720-2	<b>Version number:</b>	5.02
<b>Issue Date:</b>	2022/11/13	<b>Supersedes Date:</b>	2020/10/21

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Semi-Rigid Parts/SMC/Fiberglass Repair Adhesive-3 Minute PN 08237 Part B

#### Product Identification Numbers

LB-K100-0745-5      LB-K100-0911-0

#### 1.2. Recommended use and restrictions on use

##### Intended Use

Automotive

##### Specific Use

Repair Adhesive

##### Restrictions on use

Not applicable

#### 1.3. Supplier's details

<b>Company:</b>	3M Canada Company
<b>Division:</b>	Automotive Aftermarket
<b>Address:</b>	1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1
<b>Telephone:</b>	(800) 364-3577
<b>Website:</b>	www.3M.ca

#### 1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

Reproductive Toxicity: Category 2.

Carcinogenicity: Category 2.

Specific Target Organ Toxicity (repeated exposure): Category 1.

#### 2.2. Label elements

**Signal word**

Danger

**Symbols**

Health Hazard |

**Pictograms**



**Hazard statements**

Suspected of damaging fertility or the unborn child. Suspected of causing cancer.

Causes damage to organs through prolonged or repeated exposure: respiratory system |

**Precautionary statements**

**Prevention:**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Wear protective gloves. Do not eat, drink or smoke when using this product. Wash exposed skin thoroughly after handling.

**Response:**

Get medical advice/attention if you feel unwell.

**Storage:**

Store locked up.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**2.3. Other hazards**

None known.

2% of the mixture consists of ingredients of unknown acute oral toxicity.

2% of the mixture consists of ingredients of unknown acute dermal toxicity.

**SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Polyether Polyol	Trade Secret	30 - 60	Not Applicable
Polyol	Trade Secret	15 - 40	Not Applicable
Talc	14807-96-6	15 - 40 Trade Secret *	Talc (Mg3H2(SiO3)4)
Urethane Prepolymer	Trade Secret	3 - 7	Not Applicable
Clay	71011-24-0	1 - 5	Quaternary ammonium compounds, benzyl(hydrogenated tallow alkyl)dimethyl, chlorides, compds. with bentonite
Polypropylene Glycol Glycerol	25791-96-2	1 - 5	Poly[oxy(methyl-1,2-

Triether			ethanediyl)], .alpha.,.alpha.',.alpha."-1,2,3-propanetriyltris[.omega.-hydroxy-
Carbon Black	1333-86-4	0.1 - 1 Trade Secret *	Carbon black
Piperazine	110-85-0	0.1 - 1 Trade Secret *	Piperazine

Polyether Polyol is a non-hazardous Trade Secret material according to WHMIS criteria.

Polyol is a non-hazardous Trade Secret material according to WHMIS criteria.

Urethane Prepolymer is a non-hazardous Trade Secret material according to WHMIS criteria.

\*The actual concentration of this ingredient has been withheld as a trade secret.

## **SECTION 4: First aid measures**

### **4.1. Description of first aid measures**

**Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin Contact:**

Wash with soap and water. If signs/symptoms develop, get medical attention.

**Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

**If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

### **4.2. Most important symptoms and effects, both acute and delayed**

Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

### **4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

## **SECTION 5: Fire-fighting measures**

### **5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### **5.2. Special hazards arising from the substance or mixture**

None inherent in this product.

### **Hazardous Decomposition or By-Products**

**Substance**

Hydrocarbons  
Carbon monoxide  
Carbon dioxide  
Oxides of Nitrogen

**Condition**

During Combustion  
During Combustion  
During Combustion  
During Combustion

### **5.3. Special protective actions for fire-fighters**

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA). Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## **SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**

Contain spill. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

For industrial or professional use only. Not for consumer sale or use. Do not use in a confined area with minimal air exchange. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

**7.2. Conditions for safe storage including any incompatibilities**

Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from acids. Store away from strong bases. Store away from oxidizing agents.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

<b>Ingredient</b>	<b>C.A.S. No.</b>	<b>Agency</b>	<b>Limit type</b>	<b>Additional Comments</b>
Piperazine	110-85-0	ACGIH	TWA(as piperazine, inhalable fraction & vapor):0.03 ppm	Dermal/Respiratory Sensitizer
Carbon Black	1333-86-4	ACGIH	TWA(inhalable fraction):3 mg/m3	
Talc	14807-96-6	ACGIH	TWA(respirable fraction):2 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

**8.2. Exposure controls**

**8.2.1. Engineering controls**

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

**8.2.2. Personal protective equipment (PPE)****Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

**Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl Rubber

Neoprene

Nitrile Rubber

**Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

<b>Physical state</b>	Liquid
<b>Specific Physical Form:</b>	Viscous
<b>Colour</b>	Black
<b>Odour</b>	Slight Ammoniacal
<b>Odour threshold</b>	<i>No Data Available</i>
<b>pH</b>	<i>Not Applicable</i>
<b>Melting point/Freezing point</b>	<i>Not Applicable</i>
<b>Boiling point</b>	<i>No Data Available</i>
<b>Flash Point</b>	> 94 °C [Test Method: Closed Cup]
<b>Evaporation rate</b>	< 1 [Ref Std: ETHER=1]
<b>Flammability (solid, gas)</b>	Not Applicable
<b>Flammable Limits(LEL)</b>	<i>No Data Available</i>
<b>Flammable Limits(UEL)</b>	<i>No Data Available</i>
<b>Vapour Pressure</b>	<= 13.3 Pa
<b>Vapour Density and/or Relative Vapour Density</b>	>= 1 [Ref Std: AIR=1]
<b>Density</b>	1.2 g/ml
<b>Relative density</b>	1 - 1.2 [Ref Std: WATER=1]
<b>Water solubility</b>	<i>No Data Available</i>
<b>Solubility- non-water</b>	Negligible %

Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Viscosity/Kinematic Viscosity	No Data Available
Volatile Organic Compounds	5 g/l [Test Method:calculated SCAQMD rule 443.1]
Volatile Organic Compounds	0.4 % weight [Test Method:calculated per CARB title 2]
Percent volatile	0.38 % weight
VOC Less H2O & Exempt Solvents	5 g/l [Test Method:calculated SCAQMD rule 443.1]

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

High shear and high temperature conditions

### 10.5. Incompatible materials

Strong acids

Strong bases

Strong oxidizing agents

Alcohols

Water

### 10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
Aldehydes	Not Specified
Hydrogen Cyanide	Not Specified

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).



**Skin Contact:**

Contact with the skin during product use is not expected to result in significant irritation.

**Eye Contact:**

Contact with the eyes during product use is not expected to result in significant irritation.

**Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea. May cause additional health effects (see below).

**Additional Health Effects:**

**Prolonged or repeated exposure may cause target organ effects:**

Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum, and changes in lung function tests.

**Reproductive/Developmental Toxicity:**

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

**Carcinogenicity:**

Contains a chemical or chemicals which can cause cancer.

<b>Ingredient</b>	<b>CAS No.</b>	<b>Class Description</b>	<b>Regulation</b>
Talc-based body powder (perineal use of)	14807-96-6	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Talc containing asbestiform fibres	14807-96-6	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
Carbon black	1333-86-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

<b>Name</b>	<b>Route</b>	<b>Species</b>	<b>Value</b>
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Polyether Polyol	Dermal	Rat	LD50 > 2,000 mg/kg
Polyether Polyol	Ingestion	Rat	LD50 > 2,500 mg/kg
Talc	Dermal		LD50 estimated to be > 5,000 mg/kg
Talc	Ingestion		LD50 estimated to be > 5,000 mg/kg
Polyol	Dermal	similar compounds	LD50 > 2,000 mg/kg
Polyol	Inhalation-Dust/Mist (4 hours)	similar compounds	LC50 > 3.2 mg/l
Polyol	Ingestion	similar compounds	LD50 > 5,000 mg/kg
Urethane Prepolymer	Dermal		LD50 estimated to be > 5,000 mg/kg
Urethane Prepolymer	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Polypropylene Glycol Glycerol Triether	Dermal	Rat	LD50 > 2,000 mg/kg
Polypropylene Glycol Glycerol Triether	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 50 mg/l
Polypropylene Glycol Glycerol Triether	Ingestion	Rat	LD50 4,600 mg/kg
Piperazine	Ingestion	Rat	LD50 2,300 mg/kg
Carbon Black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon Black	Ingestion	Rat	LD50 > 8,000 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Polyether Polyol	Rabbit	No significant irritation
Talc	Rabbit	No significant irritation
Polyol	similar compounds	Minimal irritation
Polypropylene Glycol Glycerol Triether	Rabbit	No significant irritation
Piperazine	Rabbit	Corrosive
Carbon Black	Rabbit	No significant irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
Polyether Polyol	Rabbit	Mild irritant
Talc	Rabbit	No significant irritation
Polyol	similar compounds	Mild irritant
Polypropylene Glycol Glycerol Triether	Rabbit	Mild irritant
Piperazine	similar health hazards	Corrosive
Carbon Black	Rabbit	No significant irritation

**Skin Sensitization**

Name	Species	Value
Polyol	similar compounds	Not classified
Piperazine	Human and animal	Sensitizing

**Respiratory Sensitization**

Name	Species	Value
Talc	Human	Not classified
Piperazine	Human	Sensitizing

**Germ Cell Mutagenicity**

Name	Route	Value
Talc	In Vitro	Not mutagenic
Talc	In vivo	Not mutagenic
Polyol	In Vitro	Not mutagenic
Piperazine	In vivo	Not mutagenic
Piperazine	In Vitro	Some positive data exist, but the data are not sufficient for classification
Carbon Black	In Vitro	Not mutagenic
Carbon Black	In vivo	Some positive data exist, but the data are not sufficient for classification

**Carcinogenicity**

Name	Route	Species	Value
Talc	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Carbon Black	Dermal	Mouse	Not carcinogenic
Carbon Black	Ingestion	Mouse	Not carcinogenic
Carbon Black	Inhalation	Rat	Carcinogenic

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Talc	Ingestion	Not classified for development	Rat	NOAEL 1,600 mg/kg	during organogenesis
Piperazine	Ingestion	Toxic to female reproduction	Rat	NOAEL 125 mg/kg/day	2 generation
Piperazine	Ingestion	Toxic to male reproduction	Rat	NOAEL 125 mg/kg/day	2 generation
Piperazine	Ingestion	Toxic to development	Rabbit	NOAEL 94 mg/kg/day	during organogenesis

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Piperazine	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL not available	
Piperazine	Ingestion	nervous system	Causes damage to organs	Human and animal	NOAEL not available	therapeutic use

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Talc	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Talc	Inhalation	pulmonary fibrosis   respiratory system	Not classified	Rat	NOAEL 18 mg/m <sup>3</sup>	113 weeks
Piperazine	Ingestion	hematopoietic system   eyes   kidney and/or bladder	Not classified	Rat	NOAEL 1,250 mg/kg/day	90 days
Carbon Black	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information**

No data available.

**SECTION 13: Disposal considerations****13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste

incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

## SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

## SECTION 16: Other information

**National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.**

**Health: 1 Flammability: 1 Instability: 0 Special Hazards: None**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

<b>Document group:</b>	27-4720-2	<b>Version number:</b>	5.02
<b>Issue Date:</b>	2022/11/13	<b>Supersedes Date:</b>	2020/10/21

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at [www.3M.ca](http://www.3M.ca)



## Safety Data Sheet

Copyright, 2023, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	27-4348-2	<b>Version number:</b>	12.00
<b>Issue Date:</b>	2023/04/27	<b>Supersedes Date:</b>	2022/11/11

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Semi-Rigid Parts Repair Adhesive-3 PN 08237 Part A

#### Product Identification Numbers

LB-K100-0907-8      LB-K100-0736-4

#### 1.2. Recommended use and restrictions on use

##### Intended Use

Automotive

##### Specific Use

Repair Adhesive

##### Restrictions on use

Not applicable

#### 1.3. Supplier's details

<b>Company:</b>	3M Canada Company
<b>Division:</b>	Automotive Aftermarket
<b>Address:</b>	1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1
<b>Telephone:</b>	(800) 364-3577
<b>Website:</b>	www.3M.ca

#### 1.4. Emergency telephone number

Medical Emergency Telephone: 1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 2A.

Skin Corrosion/Irritation: Category 2.

Respiratory Sensitizer: Category 1.

Skin Sensitizer: Category 1.

Specific Target Organ Toxicity (single exposure): Category 3.

Specific Target Organ Toxicity (repeated exposure): Category 1.

## 2.2. Label elements

### Signal word

Danger

### Symbols

Exclamation mark | Health Hazard |

### Pictograms



### Hazard statements

Causes serious eye irritation. Causes skin irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause respiratory irritation.

Causes damage to organs through prolonged or repeated exposure: respiratory system |

### Precautionary statements

#### Prevention:

Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. In case of inadequate ventilation wear respiratory protection. Wear protective gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash exposed skin thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

#### Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTRE or doctor/physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Call a POISON centre or doctor/physician if you feel unwell.

#### Storage:

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

#### Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

## 2.3. Other hazards

None known.

40% of the mixture consists of ingredients of unknown acute inhalation toxicity.

## SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Urethane Prepolymer	Trade Secret	30 - 60	Not Applicable

Methylene Phenylene Isocyanate	101-68-8	15 - 40 Trade Secret *	Benzene, 1,1'-methylenebis[4-isocyanato-
4,4'-Diisocyanatodiphenylmethane Polymer	25686-28-6	10 - 30 Trade Secret *	Benzene, 1,1'-methylenebis[4-isocyanato-, homopolymer
Aluminum Silicate	Trade Secret	7 - 13	Not Applicable
Talc	14807-96-6	7 - 13 Trade Secret *	Talc (Mg3H2(SiO3)4)
Thickening Agent	Trade Secret	1 - 5	Not Applicable

Aluminum Silicate is a non-hazardous Trade Secret material according to WHMIS criteria.  
 Urethane Prepolymer is a non-hazardous Trade Secret material according to WHMIS criteria.  
 Thickening agent is a non-hazardous Trade Secret material according to WHMIS criteria.

\*The actual concentration of this ingredient has been withheld as a trade secret.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

**Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye Contact:**

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

**If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Irritating to the respiratory tract (coughing, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain). Allergic respiratory reaction (difficulty breathing, wheezing, cough, and tightness of chest). Allergic skin reaction (redness, swelling, blistering, and itching). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

DO NOT USE WATER In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### Hazardous Decomposition or By-Products

**Substance**

Carbon monoxide  
 Carbon dioxide  
 Hydrogen Cyanide  
 Oxides of Nitrogen

**Condition**

During Combustion  
 During Combustion  
 During Combustion  
 During Combustion

### 5.3. Special protective actions for fire-fighters

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Pour isocyanate decontaminant solution (90% water, 8% concentrated ammonia, 2% detergent) on spill and allow to react for 10 minutes. Or pour water on spill and allow to react for more than 30 minutes. Cover with absorbent material. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

For industrial or professional use only. Not for consumer sale or use. Do not use in a confined area with minimal air exchange. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed to prevent loss of stabilizing materials. Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from heat. Store away from acids. Store away from strong bases.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Methylene Phenylene Isocyanate	101-68-8	ACGIH	TWA:0.005 ppm	
Talc	14807-96-6	ACGIH	TWA(respirable fraction):2 mg/m <sup>3</sup>	
Aluminum Silicate	Trade Secret	ACGIH	TWA(respirable fraction):1 mg/m <sup>3</sup>	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

### 8.2. Exposure controls



**8.2.1. Engineering controls**

Provide ventilated enclosure for curing. Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

**8.2.2. Personal protective equipment (PPE)****Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields  
Indirect Vented Goggles

**Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

**Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

<b>Physical state</b>	Liquid
<b>Colour</b>	White
<b>Odour</b>	Slight Isocyanate
<b>Odour threshold</b>	<i>No Data Available</i>
<b>pH</b>	<i>Not Applicable</i>
<b>Melting point/Freezing point</b>	<i>Not Applicable</i>
<b>Boiling point</b>	<i>No Data Available</i>
<b>Flash Point</b>	> 195 °C [Test Method:Closed Cup]
<b>Evaporation rate</b>	< 1 [Ref Std:ETHER=1]
<b>Flammability (solid, gas)</b>	Not Applicable
<b>Flammable Limits(LEL)</b>	<i>No Data Available</i>
<b>Flammable Limits(UEL)</b>	<i>No Data Available</i>
<b>Vapour Pressure</b>	1.3 Pa [Details:@ 25 C for product]
<b>Vapour Density and/or Relative Vapour Density</b>	< 1 [Ref Std:AIR=1]

Density	1.3 kg/l
Relative density	1.288 [Ref Std: WATER=1]
Water solubility	No Data Available
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Viscosity/Kinematic Viscosity	No Data Available
Volatile Organic Compounds	0 g/l [Test Method:calculated SCAQMD rule 443.1]
Volatile Organic Compounds	0 % weight [Test Method:calculated per CARB title 2]
Percent volatile	0 % weight
VOC Less H2O & Exempt Solvents	0 g/l [Test Method:calculated SCAQMD rule 443.1]

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization may occur.

### 10.4. Conditions to avoid

Heat  
Sparks and/or flames

### 10.5. Incompatible materials

Strong acids  
Strong bases  
Water

### 10.6. Hazardous decomposition products

#### Substance

#### Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### **Inhalation:**

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose

and throat pain. Allergic Respiratory Reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest. May cause additional health effects (see below).

#### Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

#### Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

#### Additional Health Effects:

##### Prolonged or repeated exposure may cause target organ effects:

Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum, and changes in lung function tests. Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

#### Carcinogenicity:

Ingredient	CAS No.	Class Description	Regulation
Talc-based body powder (perineal use of)	14807-96-6	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Talc containing asbestiform fibres	14807-96-6	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer

#### Additional Information:

Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

Name	Route	Species	Value
Overall product	Inhalation-Dust/Mist(4 hr)		No data available; calculated ATE >12.5 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Methylene Phenylene Isocyanate	Dermal	Rabbit	LD50 > 5,000 mg/kg
Methylene Phenylene Isocyanate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.368 mg/l
Methylene Phenylene Isocyanate	Ingestion	Rat	LD50 31,600 mg/kg
Urethane Prepolymer	Dermal		LD50 estimated to be > 5,000 mg/kg
Urethane Prepolymer	Ingestion	Rat	LD50 > 5,000 mg/kg
4,4'-Diisocyanatodiphenylmethane Polymer	Dermal	Rabbit	LD50 > 5,000 mg/kg
4,4'-Diisocyanatodiphenylmethane Polymer	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.368 mg/l
4,4'-Diisocyanatodiphenylmethane Polymer	Ingestion	Rat	LD50 31,600 mg/kg
Aluminum Silicate	Dermal	Rabbit	LD50 > 2,000 mg/kg
Aluminum Silicate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 4.57 mg/l
Aluminum Silicate	Ingestion	Rat	LD50 > 5,000 mg/kg
Talc	Dermal		LD50 estimated to be > 5,000 mg/kg

Talc	Ingestion		LD50 estimated to be > 5,000 mg/kg
Thickening Agent	Dermal	Rabbit	LD50 > 5,000 mg/kg
Thickening Agent	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Thickening Agent	Ingestion	Rat	LD50 > 5,110 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Methylene Phenylene Isocyanate	official classification	Irritant
4,4'-Diisocyanatodiphenylmethane Polymer	official classification	Irritant
Aluminum Silicate	Rabbit	No significant irritation
Talc	Rabbit	No significant irritation
Thickening Agent	Rabbit	No significant irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
Methylene Phenylene Isocyanate	official classification	Severe irritant
4,4'-Diisocyanatodiphenylmethane Polymer	official classification	Severe irritant
Aluminum Silicate	Rabbit	Mild irritant
Talc	Rabbit	No significant irritation
Thickening Agent	Rabbit	No significant irritation

**Skin Sensitization**

Name	Species	Value
Methylene Phenylene Isocyanate	official classification	Sensitizing
4,4'-Diisocyanatodiphenylmethane Polymer	official classification	Sensitizing
Thickening Agent	Human and animal	Not classified

**Respiratory Sensitization**

Name	Species	Value
Methylene Phenylene Isocyanate	Human	Sensitizing
4,4'-Diisocyanatodiphenylmethane Polymer	Human	Sensitizing
Talc	Human	Not classified

**Germ Cell Mutagenicity**

Name	Route	Value
Methylene Phenylene Isocyanate	In Vitro	Some positive data exist, but the data are not sufficient for classification
4,4'-Diisocyanatodiphenylmethane Polymer	In Vitro	Some positive data exist, but the data are not sufficient for classification
Talc	In Vitro	Not mutagenic
Talc	In vivo	Not mutagenic
Thickening Agent	In Vitro	Not mutagenic

**Carcinogenicity**

Name	Route	Species	Value
Methylene Phenylene Isocyanate	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
4,4'-Diisocyanatodiphenylmethane Polymer	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Talc	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Thickening Agent	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Methylene Phenylene Isocyanate	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis
4,4'-Diisocyanatodiphenylmethane Polymer	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis
Talc	Ingestion	Not classified for development	Rat	NOAEL 1,600 mg/kg	during organogenesis
Thickening Agent	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Thickening Agent	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Thickening Agent	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Methylene Phenylene Isocyanate	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	
4,4'-Diisocyanatodiphenylmethane Polymer	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Methylene Phenylene Isocyanate	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
4,4'-Diisocyanatodiphenylmethane Polymer	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
Talc	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Talc	Inhalation	pulmonary fibrosis   respiratory system	Not classified	Rat	NOAEL 18 mg/m <sup>3</sup>	113 weeks
Thickening Agent	Inhalation	respiratory system   silicosis	Not classified	Human	NOAEL Not available	occupational exposure

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

## SECTION 12: Ecological information

No data available.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

## SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Industrial Safety and Health Law. Certain restrictions may apply. Contact the selling division for additional information. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

## SECTION 16: Other information

**National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.**

**Health:** 2 **Flammability:** 1 **Instability:** 1 **Special Hazards:** Reacts with Water

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar

emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

<b>Document group:</b>	27-4348-2	<b>Version number:</b>	12.00
<b>Issue Date:</b>	2023/04/27	<b>Supersedes Date:</b>	2022/11/11

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

**3M Canada SDSs are available at [www.3M.ca](http://www.3M.ca)**