

Safety Data Sheet

Copyright, 2023, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| Document group: | 29-7796-5 | Version number: | 4.00 |
|-----------------|------------|------------------|------------|
| Issue Date: | 2023/01/19 | Supercedes Date: | 2022/03/11 |

SECTION 1: Identification

1.1. Product identifier

3MTM Three Conductor In-line Splice, 5751 (2131 Resin)

Product Identification Numbers

70-2013-7512-1 78-8126-9836-9 80-6114-6828-3

1.2. Recommended use and restrictions on use

Recommended use

Electrical

1.3. Supplier's details

Company: 3M Canada Company **Division:** Electrical Markets Division

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

Telephone: (800) 364-3577

E Mail:

1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS) or Article Information Sheet (AIS) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:

26-2852-7, 28-7650-6, 28-7666-2, 34-7684-3

Transport in accordance with applicable regulations.

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit

for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca

Page: 2 of 2



Safety Data Sheet

Copyright, 2022, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 26-2852-7
 Version number:
 7.06

 Issue Date:
 2022/06/24
 Supercedes Date:
 2021/06/23

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3MTM Cable Preparation Kit CC-2 (Can)

Product Identification Numbers

LH-A100-0663-9 GBCDMS00141 78-8061-7605-9 78-8127-6979-8 80-6105-9299-2 80-6112-0013-2 80-6114-2769-3 CE-1007-3253-2 CE-1007-4524-5 JE-1900-3038-5 UU-0109-3612-6 UU-0109-3614-2 UU-0114-6788-1 UU-0115-6093-3 UU-0117-4166-5

1.2. Recommended use and restrictions on use

Intended Use

Electrical, SOLVENT SOAKED PADS FOR CLEANING CABLE

Restrictions on use

Not applicable

1.3. Supplier's details

Company: 3M Canada Company **Division:** Electrical Markets Division

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

Telephone: (800) 364-3577 **Website:** www.3M.ca

1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Flammable Liquid: Category 4. Skin Sensitizer: Category 1B.

2.2. Label elements

Signal word

Warning

Symbols

Exclamation mark

Pictograms



Hazard statements

Combustible liquid.

May cause an allergic skin reaction.

Precautionary statements

Prevention:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear protective gloves and eye/face protection. Contaminated work clothing must not be allowed out of the workplace.

Response:

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage:

Store in a well-ventilated place.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

| Ingredient | C.A.S. No. | % by Wt | Common Name |
|---------------------|------------|---------|--|
| HYDROTREATED HEAVY | 64742-48-9 | 50 - 70 | Naphtha, petroleum, hydrotreated heavy |
| NAPHTHA (PETROLEUM) | | | |
| Cotton Pads | None | 25 - 40 | Not Applicable |
| D-LIMONENE | 5989-27-5 | 5 - 20 | Cyclohexene, 1-methyl-4-(1- |
| | | | methylethenyl)-, (R)- |

Cotton Pads is a non-hazardous Trade Secret material according to WHMIS criteria.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

3M[™] Cable Preparation Kit CC-2 (Can)

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eve Contact:

No need for first aid is anticipated.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

5.3. Special protective actions for fire-fighters

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA). Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial or professional use only. Not for consumer sale or use. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|------------|------------|--------|-------------------------|----------------------------|
| D-LIMONENE | 5989-27-5 | AIHA | TWA:165.5 mg/m3(30 ppm) | |

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Fluoroelastomer

Nitrile Rubber

Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Nitrile Apron – polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Physical state | Solid (Lint-free cloths soaked with liquid) | | |
|--|---|--|--|
| Specific Physical Form: | Cloth pads soaked in liquid in can or bag | | |
| | | | |
| Colour | White | | |
| Odour | Citrus | | |
| Odour threshold | No Data Available | | |
| рН | 7 | | |
| Melting point/Freezing point | No Data Available | | |
| Boiling point | 193.3 °C - 248.9 °C | | |
| Flash Point | 62.2 °C [Test Method:Closed Cup] | | |
| Evaporation rate | No Data Available | | |
| Flammability (solid, gas) | Not Classified | | |
| Flammable Limits(LEL) | No Data Available | | |
| Flammable Limits(UEL) | No Data Available | | |
| Pour Pressure < 133.3 Pa [@ 25 °C] | | | |
| Vapour Density and/or Relative Vapour Density | > 1 [<i>Ref Std:</i> AIR=1] | | |
| Density | 0.76 g/ml | | |
| Relative density | 0.76 [Ref Std:WATER=1] | | |
| Water solubility Nil | | | |
| Solubility- non-water | No Data Available | | |
| Partition coefficient: n-octanol/ water | No Data Available | | |
| Autoignition temperature | No Data Available | | |
| Decomposition temperature No Data Available | | | |
| Viscosity/Kinematic Viscosity 1.5 mPa-s | | | |
| Tolatile Organic Compounds Approximately 740 % | | | |
| Percent volatile | No Data Available | | |
| VOC Less H2O & Exempt Solvents 760 g/l | | | |
| Molecular weight | No Data Available | | |

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Sparks and/or flames

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

SubstanceConditionCarbon monoxideNot SpecifiedCarbon dioxideNot Specified

SECTION 11: Toxicological information

D. . . . 5 . . C . . O

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

May be harmful if inhaled.

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eve Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

Physical Blockage: Signs/symptoms may include cramping, abdominal pain, and constipation. Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|--|-----------------------------------|---------|--|
| Overall product | Inhalation- Vapor(4 hr) | | No data available; calculated ATE >20 - =50 mg/l |
| Overall product | Ingestion | | No data available; calculated ATE >5,000 mg/kg |
| HYDROTREATED HEAVY NAPHTHA (PETROLEUM) | Inhalation- Vapor | | LC50 estimated to be 20 - 50 mg/l |
| HYDROTREATED HEAVY NAPHTHA (PETROLEUM) | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| HYDROTREATED HEAVY NAPHTHA (PETROLEUM) | Ingestion | Rat | LD50 > 5,000 mg/kg |
| D-LIMONENE | Inhalation- Vapor (4 hours) | Mouse | LC50 > 3.14 mg/l |
| D-LIMONENE | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| D-LIMONENE | Ingestion | Rat | LD50 4,400 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|--|---------|--------------------|
| HYDROTREATED HEAVY NAPHTHA (PETROLEUM) | Rabbit | Minimal irritation |
| D-LIMONENE | Rabbit | Mild irritant |

Serious Eve Damage/Irritation

| Name | Species | Value |
|--|---------|---------------|
| HYDROTREATED HEAVY NAPHTHA (PETROLEUM) | Rabbit | Mild irritant |
| D-LIMONENE | Rabbit | Mild irritant |

Skin Sensitization

| Name | Species | Value |
|--|---------|----------------|
| HYDROTREATED HEAVY NAPHTHA (PETROLEUM) | Guinea | Not classified |
| | pig | |
| D-LIMONENE | Mouse | Sensitizing |

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

| Name | | Value |
|--|----------|---------------|
| | | |
| HYDROTREATED HEAVY NAPHTHA (PETROLEUM) | | Not mutagenic |
| HYDROTREATED HEAVY NAPHTHA (PETROLEUM) | | Not mutagenic |
| D-LIMONENE | In Vitro | Not mutagenic |
| D-LIMONENE | In vivo | Not mutagenic |

Carcinogenicity

| Name | Route | Species | Value |
|--|-----------|-----------|--|
| HYDROTREATED HEAVY NAPHTHA (PETROLEUM) | Not | Not | Not carcinogenic |
| | Specified | available | - |
| D-LIMONENE | Ingestion | Rat | Some positive data exist, but the data are not |
| | _ | | sufficient for classification |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test result | Exposure Duration |
|---|------------------|--|-------------------------------|------------------------|------------------------------|
| HYDROTREATED HEAVY NAPHTHA (PETROLEUM) | Not Specified | Not classified for female reproduction | Not available | NOAEL NA | 1 generation |
| HYDROTREATED HEAVY NAPHTHA (PETROLEUM) | Not Specified | Not classified for male reproduction | Not available | NOAEL NA | 28 days |
| HYDROTREATED HEAVY NAPHTHA (PETROLEUM) | Not Specified | Not classified for development | Not applicabl e | NOAEL NA | during gestation |
| D-LIMONENE | Ingestion | Not classified for female reproduction | Rat | NOAEL 750 mg/kg/day | premating & during gestation |
| D-LIMONENE | Ingestion | Not classified for development | Multiple animal species | NOAEL 591 mg/kg/day | during organogenesi s |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|------------|-----------|-----------------|----------------|---------|------------------------|----------------------|
| D-LIMONENE | Ingestion | nervous system | Not classified | | NOAEL Not available | |
| | | | | | avanable | |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|------------|-----------|--|----------------|---------|-----------------------------|----------------------|
| D-LIMONENE | Ingestion | kidney and/or bladder | Not classified | Rat | LOAEL 75 mg/kg/day | 103 weeks |
| D-LIMONENE | Ingestion | liver | Not classified | Mouse | NOAEL 1,000 mg/kg/day | 103 weeks |
| D-LIMONENE | Ingestion | heart endocrine system bone, teeth, nails, and/or hair | Not classified | Rat | NOAEL 600 mg/kg/day | 103 weeks |

| hematopoietic system immune system muscles | | |
|--|--|--|
| nervous system | | |

Aspiration Hazard

3M[™] Cable Preparation Kit CC-2 (Can)

| Name | Value |
|--|-------------------|
| HYDROTREATED HEAVY NAPHTHA (PETROLEUM) | Aspiration hazard |
| D-LIMONENE | Aspiration hazard |

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

respiratory system

Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

Page: 8 of 9

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 2 Flammability: 2 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: 2 Flammability: 2 Physical Hazard: 0 Personal Protection: X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

| Document group: | 26-2852-7 | Version number: | 7.06 |
|-----------------|------------|------------------|------------|
| Issue Date: | 2022/06/24 | Supercedes Date: | 2021/06/23 |

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca

Page: 9 of 9



Safety Data Sheet

Copyright, 2022, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 28-7650-6
 Version number:
 5.02

 Issue Date:
 2022/03/11
 Supercedes Date:
 2020/10/16

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3MTM ScotchcastTM Flame-Retardant Compound 2131 (Part A)

Product Identification Numbers

| LH-A024-2131-A | LH-A027-2131-A | LH-A063-2131-A | LH-A065-2131-A | LH-A100-1638-7 |
|----------------|----------------|----------------|----------------|----------------|
| LH-A125-2131-A | LH-A179-2131-A | LH-A184-2131-A | LH-A194-2131-A | GBCDMS00148 |
| GBCDMS00150 | 80-6114-2633-1 | 80-6114-6840-8 | 80-6116-1242-7 | |

1.2. Recommended use and restrictions on use

Intended Use

Electrical

Specific Use

Part A of two part electrical resin

Restrictions on use

Not applicable

1.3. Supplier's details

Company: 3M Canada Company **Division:** Electrical Markets Division

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

Telephone: (800) 364-3577 **Website:** www.3M.ca

1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 2A.

Skin Corrosion/Irritation: Category 2. Respiratory Sensitizer: Category 1.

3M™ Scotchcast™ Flame-Retardant Compound 2131 (Part A)

Skin Sensitizer: Category 1.

Specific Target Organ Toxicity (single exposure): Category 3. Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Exclamation mark | Health Hazard |

Pictograms





Hazard statements

Causes serious eye irritation. Causes skin irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause respiratory irritation.

Causes damage to organs through prolonged or repeated exposure: respiratory system

Precautionary statements

Prevention:

Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. In case of inadequate ventilation wear respiratory protection. Wear protective gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash exposed skin thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTRE or doctor/physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

| Ingredient | C.A.S. No. | % by Wt | Common Name |
|------------|-------------|---------|--|
| POLYETHER- | 154517-54-1 | 35 - 45 | Poly[oxy(methyl-1,2-ethanediyl)], .alpha |

Page: 2 of 11

| HYDROCARBON- URETHANE POLYMER | | | hydroomegahydroxy-, polymers with hydroxy-terminated polybutadiene and 1,1'-methylenebis[isocyanatobenzene] |
|---|------------|------------------------|---|
| P,P'- METHYLENEBIS(PHENYL ISOCYANATE) | 101-68-8 | 15 - 40 Trade Secret * | Benzene, 1,1'-methylenebis[4-isocyanato- |
| DIUNDECYL PHTHALATE | 3648-20-2 | < 15 | 1,2-Benzenedicarboxylic acid, diundecyl ester |
| DIUNDECYL PHTHALATE, BRANCHED AND LINEAR | 85507-79-5 | < 15 | 1,2-Benzenedicarboxylic acid, diundecyl ester, branched and linear |
| BENZENE, 1,1'- METHYLENEBIS[ISOCYANA TO-, HOMOPOLYMER | 39310-05-9 | 5 - 13 Trade Secret * | Benzene, 1,1'-methylenebis[isocyanato-, homopolymer |
| 1,1'- METHYLENEBIS(ISOCYANA TOBENZENE) | 26447-40-5 | 1 - 5 Trade Secret * | Benzene, 1,1'-methylenebis[isocyanato- |
| 1,1,3-TRIS(3-TERT-BUTYL-4- HYDROXY-6- METHYLPHENYL)BUTANE | 1843-03-4 | 0.1 - 1 Trade Secret * | No Data Available |

^{*}The actual concentration of this ingredient has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Irritating to the respiratory tract (coughing, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain). Allergic respiratory reaction (difficulty breathing, wheezing, cough, and tightness of chest). Allergic skin reaction (redness, swelling, blistering, and itching). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide Carbon dioxide Hydrogen Cyanide Oxides of Nitrogen Condition

During Combustion During Combustion During Combustion During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA). Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Pour isocyanate decontaminant solution (90% water, 8% concentrated ammonia, 2% detergent) on spill and allow to react for 10 minutes. Or pour water on spill and allow to react for more than 30 minutes. Cover with absorbent material. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial or professional use only. Not for consumer sale or use. Do not use in a confined area with minimal air exchange. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Protect from sunlight. Store away from heat. Store away from strong bases. Store away from areas where product may come into contact with food or pharmaceuticals. Store in a dry place.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

3M™ Scotchcast™ Flame-Retardant Compound 2131 (Part A)

| P,P'- | 101-68-8 | ACGIH | TWA:0.005 ppm | |
|---------------------|----------|-------|---------------|--|
| METHYLENEBIS(PHENYL | | | | |
| ISOCYANATE) | | | | |

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eve/face protection to prevent contact based on the results of an exposure assessment. The following eve/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| mormation on basic physical and encinical properties | | | | |
|--|-------------------------------------|--|--|--|
| Physical state | Liquid | | | |
| Colour | Light Straw | | | |
| Odour | Pungent Odour | | | |
| Odour threshold | No Data Available | | | |
| pH | Not Applicable | | | |
| Melting point/Freezing point | Not Applicable | | | |
| Boiling point | >=148.9 °C | | | |
| Flash Point | >=148.9 °C [Test Method:Closed Cup] | | | |

Page: 5 of 11

| Evaporation rate | No Data Available |
|---|------------------------|
| Flammability (solid, gas) | Not Applicable |
| Flammable Limits(LEL) | No Data Available |
| Flammable Limits(UEL) | No Data Available |
| Vapour Pressure | No Data Available |
| Vapour Density and/or Relative Vapour Density | No Data Available |
| Density | No Data Available |
| Relative density | 1.08 [Ref Std:WATER=1] |
| Water solubility | Nil |
| Solubility- non-water | No Data Available |
| Partition coefficient: n-octanol/ water | No Data Available |
| Autoignition temperature | No Data Available |
| Decomposition temperature | No Data Available |
| Viscosity/Kinematic Viscosity | 700 - 900 mPa-s |
| Volatile Organic Compounds | No Data Available |
| Percent volatile | No Data Available |
| VOC Less H2O & Exempt Solvents | 10.5 g/l |
| Average particle size | No Data Available |
| Bulk density | No Data Available |
| Molecular weight | No Data Available |
| Softening point | No Data Available |

Nanoparticles

This material does not contain nanoparticles.

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization may occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong bases

Alcohols

Water

10.6. Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

D 6 C 11

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic Respiratory Reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest. May cause additional health effects (see below).

Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eve Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

Additional Information:

Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|--|---------------------------------------|---------|--|
| Overall product | Ingestion | | No data available; calculated ATE >5,000 mg/kg |
| POLYETHER-HYDROCARBON-URETHANE POLYMER | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| POLYETHER-HYDROCARBON-URETHANE POLYMER | Ingestion | | LD50 estimated to be 2,000 - 5,000 mg/kg |
| P,P'-METHYLENEBIS(PHENYL ISOCYANATE) | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| P,P'-METHYLENEBIS(PHENYL ISOCYANATE) | Inhalation- Dust/Mist (4 hours) | Rat | LC50 0.368 mg/l |
| P,P'-METHYLENEBIS(PHENYL ISOCYANATE) | Ingestion | Rat | LD50 31,600 mg/kg |
| DIUNDECYL PHTHALATE | Dermal | Rabbit | LD50 > 7,900 mg/kg |
| DIUNDECYL PHTHALATE | Ingestion | Rat | LD50 > 15,000 mg/kg |
| DIUNDECYL PHTHALATE, BRANCHED AND LINEAR | Dermal | Rat | LD50 > 2,000 mg/kg |
| DIUNDECYL PHTHALATE, BRANCHED AND LINEAR | Ingestion | Rat | LD50 > 15,800 mg/kg |
| BENZENE, 1,1'-METHYLENEBIS[ISOCYANATO-, | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| HOMOPOLYMER | | | |
| BENZENE, 1,1'-METHYLENEBIS[ISOCYANATO-, | Inhalation- | Rat | LC50 0.368 mg/l |
| HOMOPOLYMER | Dust/Mist | | |

| | (4 hours) | | |
|---|-------------|--------|--------------------|
| BENZENE, 1,1'-METHYLENEBIS[ISOCYANATO-, | Ingestion | Rat | LD50 31,600 mg/kg |
| HOMOPOLYMER | | | |
| 1,1'-METHYLENEBIS(ISOCYANATOBENZENE) | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| 1,1'-METHYLENEBIS(ISOCYANATOBENZENE) | Inhalation- | Rat | LC50 0.368 mg/l |
| | Dust/Mist | | |
| | (4 hours) | | |
| 1,1'-METHYLENEBIS(ISOCYANATOBENZENE) | Ingestion | Rat | LD50 31,600 mg/kg |
| 1,1,3-TRIS(3-TERT-BUTYL-4-HYDROXY-6- | Dermal | Rat | LD50 > 2,000 mg/kg |
| METHYLPHENYL)BUTANE | | | |
| 1,1,3-TRIS(3-TERT-BUTYL-4-HYDROXY-6- | Ingestion | Rat | LD50 > 5,000 mg/kg |
| METHYLPHENYL)BUTANE | | | |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|---|------------|---------------------------|
| D DI A CETTATA EMEDICADATEMATA (COCALAMATE) | 00 : 1 | T. St. A |
| P,P'-METHYLENEBIS(PHENYL ISOCYANATE) | official | Irritant |
| | classifica | |
| | tion | |
| DIUNDECYL PHTHALATE, BRANCHED AND LINEAR | Rabbit | No significant irritation |
| BENZENE, 1,1'-METHYLENEBIS[ISOCYANATO-, HOMOPOLYMER | official | Irritant |
| | classifica | |
| | tion | |
| 1,1'-METHYLENEBIS(ISOCYANATOBENZENE) | official | Irritant |
| | classifica | |
| | tion | |
| 1,1,3-TRIS(3-TERT-BUTYL-4-HYDROXY-6-METHYLPHENYL)BUTANE | In vitro | No significant irritation |
| | data | |

Serious Eye Damage/Irritation

| Name | Species | Value |
|---|--------------------------------|---------------------------|
| P,P'-METHYLENEBIS(PHENYL ISOCYANATE) | official classifica tion | Severe irritant |
| DIUNDECYL PHTHALATE, BRANCHED AND LINEAR | Rabbit | Mild irritant |
| BENZENE, 1,1'-METHYLENEBIS[ISOCYANATO-, HOMOPOLYMER | official classifica tion | Severe irritant |
| 1,1'-METHYLENEBIS(ISOCYANATOBENZENE) | official classifica tion | Severe irritant |
| 1,1,3-TRIS(3-TERT-BUTYL-4-HYDROXY-6-METHYLPHENYL)BUTANE | In vitro data | No significant irritation |

Skin Sensitization

| SKIII SCHSILIZATION | | |
|---|------------|----------------|
| Name | Species | Value |
| P,P'-METHYLENEBIS(PHENYL ISOCYANATE) | official | Sensitizing |
| | classifica | |
| | tion | |
| DIUNDECYL PHTHALATE, BRANCHED AND LINEAR | Human | Not classified |
| BENZENE, 1,1'-METHYLENEBIS[ISOCYANATO-, HOMOPOLYMER | official | Sensitizing |
| | classifica | |
| | tion | |
| 1,1'-METHYLENEBIS(ISOCYANATOBENZENE) | official | Sensitizing |
| | classifica | |
| | tion | |
| 1,1,3-TRIS(3-TERT-BUTYL-4-HYDROXY-6-METHYLPHENYL)BUTANE | Mouse | Sensitizing |

Respiratory Sensitization

| Name | Species | Value |
|--------------------------------------|---------|-------------|
| P,P'-METHYLENEBIS(PHENYL ISOCYANATE) | Human | Sensitizing |

Page: 8 of 11

| BENZENE, 1,1'-METHYLENEBIS[ISOCYANATO-, HOMOPOLYMER | Human | Sensitizing |
|---|-------|-------------|
| 1,1'-METHYLENEBIS(ISOCYANATOBENZENE) | Human | Sensitizing |

Germ Cell Mutagenicity

| Name | Route | Value |
|---|----------|--|
| | | |
| P,P'-METHYLENEBIS(PHENYL ISOCYANATE) | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| DIUNDECYL PHTHALATE, BRANCHED AND LINEAR | In Vitro | Not mutagenic |
| BENZENE, 1,1'-METHYLENEBIS[ISOCYANATO-, HOMOPOLYMER | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| 1,1'-METHYLENEBIS(ISOCYANATOBENZENE) | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| 1,1,3-TRIS(3-TERT-BUTYL-4-HYDROXY-6-METHYLPHENYL)BUTANE | In Vitro | Not mutagenic |

Carcinogenicity

| Name | Route | Species | Value |
|--|------------|---------|--|
| P,P'-METHYLENEBIS(PHENYL ISOCYANATE) | Inhalation | Rat | Some positive data exist, but the data are not sufficient for classification |
| BENZENE, 1,1'-METHYLENEBIS[ISOCYANATO-, HOMOPOLYMER | Inhalation | Rat | Some positive data exist, but the data are not sufficient for classification |
| 1,1'-METHYLENEBIS(ISOCYANATOBENZENE) | Inhalation | Rat | Some positive data exist, but the data are not sufficient for classification |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test result | Exposure |
|------------------------------|------------|--------------------------------------|---------|-------------|--------------|
| | | | | | Duration |
| P,P'-METHYLENEBIS(PHENYL | Inhalation | Not classified for development | Rat | NOAEL 0.004 | during |
| ISOCYANATE) | | | | mg/l | organogenesi |
| | | | | | S |
| DIUNDECYL PHTHALATE, | Ingestion | Not classified for male reproduction | Rat | NOAEL 2,100 | 21 days |
| BRANCHED AND LINEAR | | | | mg/kg/day | |
| DIUNDECYL PHTHALATE, | Ingestion | Not classified for development | Rat | NOAEL 1,000 | during |
| BRANCHED AND LINEAR | | | | mg/kg/day | gestation |
| BENZENE, 1,1'- | Inhalation | Not classified for development | Rat | NOAEL 0.004 | during |
| METHYLENEBIS[ISOCYANATO-, | | | | mg/l | organogenesi |
| HOMOPOLYMER | | | | | S |
| 1,1'- | Inhalation | Not classified for development | Rat | NOAEL 0.004 | during |
| METHYLENEBIS(ISOCYANATOBENZE | | - | | mg/l | organogenesi |
| NE) | | | | | s |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|--|------------|------------------------|----------------------------------|--------------------------------|------------------------|----------------------|
| P,P'- METHYLENEBIS(PHEN YL ISOCYANATE) | Inhalation | respiratory irritation | May cause respiratory irritation | official classifica tion | NOAEL Not available | |
| BENZENE, 1,1'- METHYLENEBIS[ISOCY ANATO-, HOMOPOLYMER | Inhalation | respiratory irritation | May cause respiratory irritation | official classifica tion | NOAEL Not available | |
| 1,1'- METHYLENEBIS(ISOCY ANATOBENZENE) | Inhalation | respiratory irritation | May cause respiratory irritation | official classifica tion | NOAEL Not available | |

Specific Target Organ Toxicity - repeated exposure

| Specific Target Organ | TOXICITY - I | cpcatca exposure | | | | |
|-----------------------|--------------|--------------------|---------------------------------|---------|-------------|----------------------|
| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
| P,P'- | Inhalation | respiratory system | Causes damage to organs through | Rat | LOAEL | 13 weeks |
| METHYLENEBIS(PHEN | | | prolonged or repeated exposure | | 0.004 mg/l | |

| YL ISOCYANATE) | | | | | | |
|---|------------|--|--|-----|-----------------------------|----------|
| DIUNDECYL PHTHALATE, BRANCHED AND LINEAR | Ingestion | liver | Not classified | Rat | NOAEL 2,100 mg/kg/day | 21 days |
| BENZENE, 1,1'- METHYLENEBIS[ISOCY ANATO-, HOMOPOLYMER | Inhalation | respiratory system | Causes damage to organs through prolonged or repeated exposure | Rat | LOAEL 0.004 mg/l | 13 weeks |
| 1,1'- METHYLENEBIS(ISOCY ANATOBENZENE) | Inhalation | respiratory system | Causes damage to organs through prolonged or repeated exposure | Rat | LOAEL 0.004 mg/l | 13 weeks |
| 1,1,3-TRIS(3-TERT- BUTYL-4-HYDROXY-6- METHYLPHENYL)BUT ANE | Ingestion | endocrine system hematopoietic system liver eyes | Not classified | Rat | NOAEL 392 mg/kg/day | 13 weeks |

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: *3 Flammability: 1 Physical Hazard: 0 **Personal Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

| Document group: | 28-7650-6 | Version number: | 5.02 |
|-----------------|------------|------------------|------------|
| Issue Date: | 2022/03/11 | Supercedes Date: | 2020/10/16 |

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE. COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca



Safety Data Sheet

Copyright, 2022, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 28-7666-2
 Version number:
 5.00

 Issue Date:
 2022/11/11
 Supercedes Date:
 2020/10/09

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3MTM ScotchcastTM Flame Retardant Resin 2131 (PART B)

Product Identification Numbers

80-6114-6841-6 80-6116-1288-0

1.2. Recommended use and restrictions on use

Intended Use

Electrical

Specific Use

Part B of two part electrical resin

Restrictions on use

Not applicable

1.3. Supplier's details

Company: 3M Canada Company **Division:** Electrical Markets Division

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

Telephone: (800) 364-3577 **Website:** www.3M.ca

1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 1.

Carcinogenicity: Category 2.

2.2. Label elements

Signal word

Danger

Symbols

Corrosion Health Hazard







Hazard statements

Causes serious eye damage. Suspected of causing cancer.

Precautionary statements

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves and eye/face protection.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTRE or doctor/physician.

Storage:

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

None known.

4% of the mixture consists of ingredients of unknown acute oral toxicity.

12% of the mixture consists of ingredients of unknown acute dermal toxicity.

95% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

This material is a mixture.

| Ingredient | C.A.S. No. | % by Wt | Common Name |
|---|------------|---------|--|
| HOMOPOLYMER | 69102-90-5 | 20 - 30 | 1,3-Butadiene, homopolymer, hydroxy-terminated |
| Bis(pentabromo Phenyl)ethane | 84852-53-9 | 22 - 25 | Benzene, 1,1'-(1,2-ethanediyl)bis[2,3,4,5,6-pentabromo- |
| DIUNDECYL PHTHALATE, BRANCHED AND LINEAR | 85507-79-5 | 10 - 20 | 1,2-Benzenedicarboxylic acid, diundecyl ester, branched and linear |
| ALUMINUM POTASSIUM SODIUM SILICATE | 12736-96-8 | 1 - 10 | Silicic acid, aluminum potassium sodium salt |
| ANTIMONY PENTAOXIDE | 1314-60-9 | 5 - 10 | Antimony oxide (Sb2O5) |
| CASTOR OIL | 8001-79-4 | 1 - 10 | Castor oil |
| N,N-DI(2- | 3077-13-2 | 4 - 10 | 2-Propanol, 1,1'-(phenylimino)bis- |

Page: 2 of 11

| HYDROXYPROPYL) | | | |
|--------------------------------|------------|--------|---|
| ANILINE | | | |
| POLYPROPYLENE ETHER | 25322-69-4 | 5 - 10 | Poly[oxy(methyl-1,2-ethanediyl)], .alpha |
| DIOL | | | hydroomegahydroxy- |
| DIPROPYLENE GLYCOL | 25265-71-8 | 3 - 6 | Propanol, oxybis- |
| Carbon Black | 1333-86-4 | < 2 | Carbon black |
| Silanamine, 1,1,1-trimethyl-N- | 68909-20-6 | <= 1 | Silanamine, 1,1,1-trimethyl-N- |
| (trimethylsilyl)-, hydrolysis | | | (trimethylsilyl)-, hydrolysis products with |
| products with silica | | | silica |
| TRIETHYLENEDIAMINE | 280-57-9 | <= 1 | 1,4-Diazabicyclo[2.2.2]octane |

Carbon Black is a hazardous Trade Secret material according to WHMIS criteria. Refer to Section 15 for further

N,N-DI(2-HYDROXYPROPYL) ANILINE is a hazardous Trade Secret material according to WHMIS criteria. Refer to Section 15 for further information.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Wash with soap and water. If you are concerned, get medical advice.

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

| Substance | <u>Condition</u> |
|--------------------|-------------------|
| Carbon monoxide | During Combustion |
| Carbon dioxide | During Combustion |
| Oxides of Nitrogen | During Combustion |
| Oxides of Antimony | During Combustion |

5.3. Special protective actions for fire-fighters

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA). Wear full protective

clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Keep container tightly closed. Keep cool. Store away from heat. Store in a dry place.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|---------------------|------------|--------|---------------------------|---------------------|
| Carbon Black | 1333-86-4 | ACGIH | TWA(inhalable fraction):3 | |
| | | | mg/m3 | |
| POLYPROPYLENE ETHER | 25322-69-4 | AIHA | TWA(as aerosol):10 mg/m3 | |
| DIOL | | | | |

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use with appropriate local exhaust ventilation. Provide appropriate local exhaust ventilation on open containers.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

Skin/hand protection

No chemical protective gloves are required.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Physical state | Liquid |
|---|-------------------------------------|
| Colour | Black |
| Odour | Pungent Odour |
| Odour threshold | No Data Available |
| pH | Not Applicable |
| Melting point/Freezing point | Not Applicable |
| Boiling point > 143.3 °C | |
| Flash Point | > 143.3 °C [Test Method:Closed Cup] |
| Evaporation rate | No Data Available |
| Flammability (solid, gas) | Not Applicable |
| Flammable Limits(LEL) | No Data Available |
| Flammable Limits(UEL) | No Data Available |
| Vapour Pressure | < 186,158.4 Pa [@ 55 °C] |
| Vapour Density and/or Relative Vapour Density | No Data Available |
| Density | No Data Available |
| Relative density | 1.29 [<i>Ref Std</i> :WATER=1] |
| Water solubility | Nil |
| Solubility- non-water | No Data Available |
| Partition coefficient: n-octanol/ water No Data Available | |
| Autoignition temperature | No Data Available |
| Decomposition temperature No Data Available | |
| iscosity/Kinematic Viscosity 5,500 mPa-s | |
| Volatile Organic Compounds No Data Available | |
| Percent volatile | No Data Available |
| VOC Less H2O & Exempt Solvents | 12.9 g/l |
| Molecular weight | No Data Available |

SECTION 10: Stability and reactivity

D 5 0 1

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

Eve Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Additional Health Effects:

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

| Ingredient CAS No. Class Description Regulation |
|---|
|---|

3MTM ScotchcastTM Flame Retardant Resin 2131 (PART B)

| Carbon black | 1333-86-4 | Grp. 2B: Possible human carc. | International Agency for Research on Cancer |
|--------------|-----------|-------------------------------|---|

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|--|---------------------------------------|---------|--|
| Overall product | Dermal | | No data available; calculated ATE >5,000 mg/kg |
| Overall product | Inhalation- Dust/Mist(4 hr) | | No data available; calculated ATE >12.5 mg/l |
| Overall product | Ingestion | | No data available; calculated ATE >5,000 mg/kg |
| HOMOPOLYMER | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| HOMOPOLYMER | Ingestion | | LD50 estimated to be 2,000 - 5,000 mg/kg |
| DIUNDECYL PHTHALATE, BRANCHED AND LINEAR | Dermal | Rat | LD50 > 2,000 mg/kg |
| DIUNDECYL PHTHALATE, BRANCHED AND LINEAR | Ingestion | Rat | LD50 > 15,800 mg/kg |
| POLYPROPYLENE ETHER DIOL | Dermal | Rabbit | LD50 > 10,000 mg/kg |
| POLYPROPYLENE ETHER DIOL | Ingestion | Rat | LD50 > 2,000 mg/kg |
| N,N-DI(2-HYDROXYPROPYL) ANILINE | Dermal | Rabbit | LD50 > 2,000 mg/kg |
| N,N-DI(2-HYDROXYPROPYL) ANILINE | Ingestion | Rat | LD50 3,800 mg/kg |
| CASTOR OIL | Dermal | | LD50 estimated to be > 5,000 |
| CASTOR OIL | Ingestion | | LD50 estimated to be > 5,000 |
| DIPROPYLENE GLYCOL | Dermal | Rabbit | LD50 > 5,010 mg/kg |
| DIPROPYLENE GLYCOL | Inhalation- Dust/Mist (4 hours) | Rat | LC50 > 2.34 mg/l |
| DIPROPYLENE GLYCOL | Ingestion | Rat | LD50 > 14,800 mg/kg |
| Carbon Black | Dermal | Rabbit | LD50 > 3,000 mg/kg |
| Carbon Black | Ingestion | Rat | LD50 > 8,000 mg/kg |
| Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| TRIETHYLENEDIAMINE | Dermal | Rabbit | LD50 > 3,200 mg/kg |
| Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica | Inhalation- Dust/Mist (4 hours) | Rat | LC50 > 0.691 mg/l |
| Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica | Ingestion | Rat | LD50 > 5,110 mg/kg |
| TRIETHYLENEDIAMINE | Inhalation- Dust/Mist (4 hours) | Rat | LC50 > 5.05 mg/l |
| TRIETHYLENEDIAMINE | Ingestion | Rat | LD50 1,870 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|--|-----------|---------------------------|
| | | |
| DIUNDECYL PHTHALATE, BRANCHED AND LINEAR | Rabbit | No significant irritation |
| POLYPROPYLENE ETHER DIOL | Rabbit | No significant irritation |
| N,N-DI(2-HYDROXYPROPYL) ANILINE | Professio | Minimal irritation |
| | nal | |
| | judgeme | |
| | nt | |
| CASTOR OIL | Human | Minimal irritation |
| DIPROPYLENE GLYCOL | Rabbit | No significant irritation |
| Carbon Black | Rabbit | No significant irritation |
| Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica | Rabbit | No significant irritation |
| TRIETHYLENEDIAMINE | Rabbit | Mild irritant |

Serious Eye Damage/Irritation

| Name | Species | Value |
|------|---------|-------|
| | | |

| DIUNDECYL PHTHALATE, BRANCHED AND LINEAR | Rabbit | Mild irritant |
|--|-----------|---------------------------|
| POLYPROPYLENE ETHER DIOL | Rabbit | No significant irritation |
| N,N-DI(2-HYDROXYPROPYL) ANILINE | Professio | Corrosive |
| | nal | |
| | judgeme | |
| | nt | |
| CASTOR OIL | Rabbit | Mild irritant |
| DIPROPYLENE GLYCOL | Rabbit | No significant irritation |
| Carbon Black | Rabbit | No significant irritation |
| Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica | Rabbit | No significant irritation |
| TRIETHYLENEDIAMINE | Rabbit | Corrosive |

Skin Sensitization

| Name | Species | Value |
|--|---------|----------------|
| DIUNDECYL PHTHALATE, BRANCHED AND LINEAR | Human | Not classified |
| CASTOR OIL | Human | Not classified |
| DIPROPYLENE GLYCOL | Guinea | Not classified |
| | pig | |
| Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica | Human | Not classified |
| | and | |
| | animal | |

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

| N Serial Centification of the | I D 4 | X7 1 |
|---|----------|--|
| Name | Route | Value |
| | | |
| DIUNDECYL PHTHALATE, BRANCHED AND LINEAR | In Vitro | Not mutagenic |
| CASTOR OIL | In Vitro | Not mutagenic |
| CASTOR OIL | In vivo | Not mutagenic |
| DIPROPYLENE GLYCOL | In Vitro | Not mutagenic |
| DIPROPYLENE GLYCOL | In vivo | Not mutagenic |
| Carbon Black | In Vitro | Not mutagenic |
| Carbon Black | In vivo | Some positive data exist, but the data are not |
| | | sufficient for classification |
| Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with | In Vitro | Not mutagenic |
| silica | | |

Carcinogenicity

| Name | Route | Species | Value |
|---|------------|----------|--|
| DIPROPYLENE GLYCOL | Ingestion | Multiple | Not carcinogenic |
| | | animal | |
| | | species | |
| Carbon Black | Dermal | Mouse | Not carcinogenic |
| Carbon Black | Ingestion | Mouse | Not carcinogenic |
| Carbon Black | Inhalation | Rat | Carcinogenic |
| Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis | Not | Mouse | Some positive data exist, but the data are not |
| products with silica | Specified | | sufficient for classification |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test result | Exposure Duration |
|---|-----------|--|---------|--------------------------|-----------------------------|
| DIUNDECYL PHTHALATE, BRANCHED AND LINEAR | Ingestion | Not classified for male reproduction | Rat | NOAEL 2,100 mg/kg/day | 21 days |
| DIUNDECYL PHTHALATE, BRANCHED AND LINEAR | Ingestion | Not classified for development | Rat | NOAEL 1,000 mg/kg/day | during gestation |
| DIPROPYLENE GLYCOL | Ingestion | Not classified for development | Rat | NOAEL 5,000 mg/kg/day | during organogenesi s |
| Silanamine, 1,1,1-trimethyl-N- | Ingestion | Not classified for female reproduction | Rat | NOAEL 509 | 1 generation |

Page: 8 of 11

3MTM ScotchcastTM Flame Retardant Resin 2131 (PART B)

| (trimethylsilyl)-, hydrolysis products with silica | | | | mg/kg/day | |
|---|-----------|--------------------------------------|-----|--------------------------|-----------------------------|
| Silanamine, 1,1,1-trimethyl-N- (trimethylsilyl)-, hydrolysis products with silica | Ingestion | Not classified for male reproduction | Rat | NOAEL 497 mg/kg/day | 1 generation |
| Silanamine, 1,1,1-trimethyl-N- (trimethylsilyl)-, hydrolysis products with silica | Ingestion | Not classified for development | Rat | NOAEL 1,350 mg/kg/day | during organogenesi s |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|--|------------|--|--|---------|------------------------------|-----------------------|
| DIUNDECYL PHTHALATE, BRANCHED AND LINEAR | Ingestion | liver | Not classified | Rat | NOAEL 2,100 mg/kg/day | 21 days |
| CASTOR OIL | Ingestion | heart hematopoietic system liver | Not classified | Rat | NOAEL 4,800 mg/kg/day | 13 weeks |
| CASTOR OIL | Ingestion | kidney and/or bladder | Not classified | Mouse | NOAEL 13,000 mg/kg/day | 13 weeks |
| DIPROPYLENE GLYCOL | Ingestion | respiratory system | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 470 mg/kg/day | 105 weeks |
| DIPROPYLENE GLYCOL | Ingestion | heart | Not classified | Rat | NOAEL 470 mg/kg/day | 105 weeks |
| DIPROPYLENE GLYCOL | Ingestion | endocrine system liver | Not classified | Rat | NOAEL 3,040 mg/kg/day | 105 weeks |
| DIPROPYLENE GLYCOL | Ingestion | kidney and/or bladder | Not classified | Rat | NOAEL 115 mg/kg/day | 105 weeks |
| DIPROPYLENE GLYCOL | Ingestion | skin bone, teeth, nails, and/or hair hematopoietic system immune system nervous system vascular system | Not classified | Rat | NOAEL 3,040 mg/kg/day | 105 weeks |
| Carbon Black | Inhalation | pneumoconiosis | Not classified | Human | NOAEL Not available | occupational exposure |
| Silanamine, 1,1,1- trimethyl-N- (trimethylsilyl)-, hydrolysis products with silica | Inhalation | respiratory system silicosis | Not classified | Human | NOAEL Not available | occupational exposure |

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Trade Secret Information:

HMIRA Registry Number: Filing date: Claim status: Date of decision: 04/11/2016 Claim for exemption has been 14/10/2022 10587 granted.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 3 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: *3 Flammability: 1 **Physical Hazard:** 0 **Personal Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV

3MTM ScotchcastTM Flame Retardant Resin 2131 (PART B)

program. HMIS® is a registered mark of the American Coatings Association (ACA).

| Document group: | 28-7666-2 | Version number: | 5.00 |
|-----------------|------------|------------------|------------|
| Issue Date: | 2022/11/11 | Supercedes Date: | 2020/10/09 |

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca

D 11 c 11



Article Information Sheet

Copyright, 2023, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

This Article Information Sheet is provided as a courtesy in response to a customer request. A Safety Data Sheet (SDS) has not been prepared for these product(s) because they are articles. Articles are not subject to the Hazardous Products Act or Regulations. As defined in the act: "Article" means any article that is formed to a specific shape or design during manufacture, the intended use of which when in that form is dependent in whole or in part on its shape or design, and that, when being installed, if the intended use of the article requires it to be installed, and under normal conditions of use, will not release or otherwise cause an individual to be exposed to a hazardous product.

Document group: 34-7684-3 **Version number:** 1.03

Issue Date: 2023/01/12 **Supercedes Date:** 2020/10/16

SECTION 1: Identification

1.1. Product identifier

Black EPDM Tubing (on plastic core)

Product Identification Numbers

78-8125-9775-1

1.2. Recommended use and restrictions on use

Intended Use

Electrical

Restrictions on use

Not applicable

1.3. Supplier's details

Company: 3M Canada Company **Division:** Electrical Markets Division

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

Telephone: (800) 364-3577 **Website:** www.3M.ca

1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

SECTION 2: Hazard identification

This product is exempt from hazard classification according to the Hazardous Products Act because it meets the manufactured article exemption.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt | Common Name |
|-----------------------------|------------|---------|-------------------|
| Black EPDM Tubing Composite | None | 100 | No Data Available |

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

No need for first aid is anticipated.

Skin Contact:

No need for first aid is anticipated.

Eye Contact:

No need for first aid is anticipated.

If Swallowed:

No need for first aid is anticipated.

SECTION 5: Fire-fighting measures

In case of fire: Use a carbon dioxide or dry chemical extinguisher to extinguish.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Not applicable.

6.2. Environmental precautions

Not applicable.

6.3. Methods and material for containment and cleaning up

Not applicable.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

This product is considered to be an article which does not release or otherwise result in exposure to a hazardous chemical under normal use conditions.

7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

SECTION 8: Exposure controls/personal protection

This product is considered to be an article which does not release or otherwise result in exposure to a hazardous chemical under normal use conditions. No engineering controls or personal protective equipment (PPE) are necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| DI I I I | 0.11 |
|---|-------------------|
| Physical state | Solid |
| Colour | Black |
| Odour | Rubber |
| Odour threshold | Not Applicable |
| pH | Not Applicable |
| Melting point/Freezing point | No Data Available |
| Boiling point | Not Applicable |
| Flash Point | No flash point |
| Evaporation rate | Not Applicable |
| Flammability (solid, gas) | Not Classified |
| Flammable Limits(LEL) | Not Applicable |
| Flammable Limits(UEL) | Not Applicable |
| Vapour Density and/or Relative Vapour Density | Not Applicable |
| Density | No Data Available |
| Relative density | No Data Available |
| Water solubility | Not Applicable |
| Solubility- non-water | Not Applicable |
| Partition coefficient: n-octanol/ water | Not Applicable |
| Autoignition temperature | Not Applicable |
| Decomposition temperature | No Data Available |
| Viscosity/Kinematic Viscosity | Not Applicable |
| Volatile Organic Compounds | No Data Available |
| Percent volatile | No Data Available |
| VOC Less H2O & Exempt Solvents | No Data Available |
| Molecular weight | Not Applicable |
| L | • |

SECTION 10: Stability and reactivity

This material is considered to be non reactive under normal use conditions.

SECTION 11: Toxicological information

Inhalation:

No health effects are expected

Skin Contact:

No health effects are expected

Eye Contact:

No health effects are expected

Ingestion:

No health effects are expected

Additional Information:

This product, when used under reasonable conditions and in accordance with the directions for use, should not present a health hazard. However, use or processing of the product in a manner not in accordance with the product's directions for use may affect the performance of the product and may present potential health and safety hazards.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

Dispose of contents/container in accordance with the local/regional/national/international regulations.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

This product is an article as defined by CEPA and is exempt from DSL inventory listing.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 0 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

| Document group: | 34-7684-3 | Version number: | 1.03 |
|-----------------|------------|------------------|------------|
| Issue Date: | 2023/01/12 | Supercedes Date: | 2020/10/16 |

The information in this Article Information Sheet (AIS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca