

# Safety Data Sheet

Copyright,2024, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	28-4707-7	Version number:	6.01
Issue Date:	2024/10/04	Supercedes Date:	2024/05/15

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

#### **1.1. Product identifier** 3M<sup>TM</sup> Fire Barrier Putty Sleeves

 Product Identification Numbers

 98-0400-5594-3
 98-0400-5596-8
 98-0400-5597-6

## 1.2. Recommended use and restrictions on use

**Intended Use** Passive fire protection in industrial applications

**Restrictions on use** Not applicable

#### 1.3. Supplier's details

Company:	3M Canada Company	
Division:	Industrial Specialties Division	
Address:	1840 Oxford Street East, Post Office Box 5757, London, Ontario	N6A 4T1
Telephone:	(800) 364-3577	
Website:	www.3M.ca	

#### 1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1800 364 3577

# **SECTION 2: Hazard identification**

## 2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 1. Skin Corrosion/Irritation: Category 2. Reproductive Toxicity: Category 2. Carcinogenicity: Category 2. Germ Cell Mutagenicity: Category 2. Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements Signal word Danger

Symbols

Corrosion | Exclamation mark | Health Hazard |

## Pictograms



#### Hazard statements

Causes serious eye damage. Causes skin irritation. Suspected of damaging fertility or the unborn child. Suspected of causing cancer. Suspected of causing genetic defects.

Causes damage to organs through prolonged or repeated exposure: kidney/urinary tract |

## Precautionary statements General:

Keep out of reach of children.

## **Prevention:**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Wear protective gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash exposed skin thoroughly after handling.

#### **Response:**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN: Wash with plenty of soap and water. Immediately call a POISON CENTRE or doctor/physician. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF exposed or concerned: Get medical advice/attention.

#### Storage:

Store locked up.

#### **Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

#### 2.3. Other hazards

None known.

4% of the mixture consists of ingredients of unknown acute oral toxicity.

# **SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Sodium Silicate	1344-09-8	10 - 30 Trade Secret *	Silicic acid, sodium salt
Zinc Borate 2335	138265-88-0		Boron zinc hydroxide oxide (B12Zn4(OH)14O15)
Petrolatum	8009-03-8	10 - 20	Petrolatum
Polyisobutylene	9003-27-4	10 - 20	1-Propene, 2-methyl-, homopolymer

Styrene-Butadiene Polymer	9003-55-8	10 - 20	Benzene, ethenyl-, polymer with 1,3- butadiene
Melamine Phosphate	41583-09-9	5 - 10 Trade Secret *	1,3,5-Triazine-2,4,6-triamine, phosphate
Oxide Glass Chemicals	65997-17-3	1 - 10	Glass, oxide, chemicals
Butadiene-Styrene-Meta- Divinylbenzene Polymer	26471-45-4	1 - 5	Benzene, 1,3-diethenyl-, polymer with 1,3- butadiene and ethenylbenzene
Alpha-Methylstyrene- Isoamylene-Piperylene Polymer	62258-49-5	< 3	Benzene, (1-methylethenyl)-, polymer with 2-methyl-2-butene and 1,3-pentadiene
Bisphenol A Diglycidyl Ether- Bisphenol A Copolymer	25036-25-3	< 3	No Data Available
Fatty Acids, C14-18 and C16- C18-Unsatd.	67701-06-8	< 3	No Data Available
Rayon Fiber	None	< 3	Not Applicable
Regenerated Cellulose	68442-85-3	< 3	Cellulose, regeneratedng this with carbon disulfide, dissolving this in a dilute alkali solution and extruding into an acid to form a continuous vicose tube.
Synthetic amorphous silica, fumed, crystalline-free	112945-52-5	< 3	Fumed amorphous silica, crystalline-free
Water	7732-18-5	< 3	Water

Rayon Fiber is a non-hazardous Trade Secret material according to WHMIS criteria.

\*The actual concentration of this ingredient has been withheld as a trade secret.

# **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

#### **Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### **Eve Contact:**

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

#### 4.3. Indication of any immediate medical attention and special treatment required Not applicable

# **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

## 5.2. Unsuitable extinguishing media

None Determined

## 5.3. Special hazards arising from the substance or mixture

None inherent in this product.

## Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Aldehydes	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Chloride	During Combustion

## 5.4. Special protection actions for fire-fighters

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA). Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

## **6.2.** Environmental precautions

Avoid release to the environment.

## 6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Use personal protective equipment (gloves, respirators, etc.) as required.

#### 7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### **Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	<b>Additional Comments</b>
Oxide Glass Chemicals	65997-17-3	Manufacturer	TWA(as non-fibrous,	
		determined	respirable)(8 hours):3	
			mg/m3;TWA(as non-fibrous,	
			inhalable fraction)(8 hours):10	
			mg/m3	

MINERAL OILS, HIGHLY-	8009-03-8	ACGIH	TWA(inhalable fraction):5	
REFINED OILS			mg/m3	
ACGIH : American Conference of Governmental Industrial Hygienists				

ACOTI : American Conference of Governmentar Industrial Hygienist AIHA : American Industrial Hygiene Association CMRG : Chemical Manufacturer's Recommended Guidelines TWA: Time-Weighted-Average STEL: Short Term Exposure Limit CEIL: Ceiling

## 8.2. Exposure controls

## 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

## 8.2.2. Personal protective equipment (PPE)

## **Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Full Face Shield Indirect Vented Goggles

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

#### **Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

# **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state	Solid			
Specific Physical Form:	Putty	Putty		
Colour	Red			
Odour	Odourless			
Odour threshold	No Data Available			
рН	No Data Available			
Melting point/Freezing point	Not Applicable			
Boiling point	Not Applicable			
Flash Point	Flash point > 93 °C (200 °F)			
Evaporation rate	Not Applicable			

Flammability	Not Applicable			
Flammable Limits(LEL)	Not Applicable			
Flammable Limits(UEL)	Not Applicable			
Vapour Pressure	Not Applicable			
Vapour Density and/or Relative Vapour Density	Not Applicable			
Density	1.25 g/cm3			
Relative density	1.25 [ <i>Ref Std</i> :WATER=1]			
Water solubility	No Data Available			
Solubility- non-water	No Data Available			
Partition coefficient: n-octanol/ water	No Data Available			
Autoignition temperature	Not Applicable			
Decomposition temperature	No Data Available			
Kinematic Viscosity	No Data Available			
Volatile Organic Compounds	< 1 % weight			
Percent volatile	No Data Available			
VOC Less H2O & Exempt Solvents	< 1 g/l			
Molecular weight	No Data Available			

**Particle Characteristics** 

Not Applicable

# **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

### 10.2. Chemical stability

Stable.

## 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

#### 10.4. Conditions to avoid

None known.

## **10.5. Incompatible materials**

None known.

### 10.6. Hazardous decomposition products

Substance

**Condition** 

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

## **11.1. Information on Toxicological effects**

### Signs and Symptoms of Exposure

#### Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

### **Skin Contact:**

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

## **Eye Contact:**

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

## Ingestion:

May be harmful if swallowed. Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea. May cause additional health effects (see below).

## Additional Health Effects:

## Prolonged or repeated exposure may cause target organ effects:

Kidney/Bladder Effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine, increased blood urea nitrogen (BUN), blood in urine, and painful urination.

## **Reproductive/Developmental Toxicity:**

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

#### Genotoxicity:

Genotoxicity and Mutagenicity: May interact with genetic material and possibly alter gene expression.

#### **Carcinogenicity:**

Contains a chemical or chemicals which can cause cancer.

### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

## Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation- Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
Zinc Borate 2335	Dermal	Rabbit	LD50 > 5,000 mg/kg
Zinc Borate 2335	Inhalation- Dust/Mist	Rat	LC50 > 4.95 mg/l
Zinc Borate 2335	Ingestion	Rat	LD50 > 5,000 mg/kg
Sodium Silicate	Dermal	Rabbit	LD50 > 4,640 mg/kg
Sodium Silicate	Ingestion	Rat	LD50 500 mg/kg
Petrolatum	Dermal		LD50 estimated to be > 5,000 mg/kg
Petrolatum	Ingestion	Rat	LD50 > 5,000 mg/kg
Styrene-Butadiene Polymer	Dermal	Rabbit	LD50 > 2,000 mg/kg
Styrene-Butadiene Polymer	Ingestion	Rat	LD50 > 5,000 mg/kg
Polyisobutylene	Dermal		LD50 estimated to be > 5,000 mg/kg
Polyisobutylene	Ingestion	Rat	LD50 > 2,000 mg/kg
Melamine Phosphate	Dermal	Professio	LD50 estimated to be > 5,000 mg/kg

		nal	
		judgeme nt	
Melamine Phosphate	Ingestion	Rat	LD50 > 2,000 mg/kg
Melamine Phosphate	Inhalation-	similar	LC50 > 5.19 mg/l
	Dust/Mist (4 hours)	compoun ds	
Oxide Glass Chemicals	Dermal		LD50 estimated to be $> 5,000 \text{ mg/kg}$
Oxide Glass Chemicals	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Butadiene-Styrene-Meta-Divinylbenzene Polymer	Dermal		LD50 estimated to be > 5,000 mg/kg
Butadiene-Styrene-Meta-Divinylbenzene Polymer	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Synthetic amorphous silica, fumed, crystalline-free	Dermal	Rabbit	LD50 > 5,000 mg/kg
Synthetic amorphous silica, fumed, crystalline-free	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Synthetic amorphous silica, fumed, crystalline-free	Ingestion	Rat	LD50 > 5,110 mg/kg
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer	Dermal	Rat	LD50 > 1,600 mg/kg
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer	Ingestion	Rat	LD50 > 1,000 mg/kg
Alpha-Methylstyrene-Isoamylene-Piperylene Polymer	Dermal		LD50 estimated to be > 5,000 mg/kg
Alpha-Methylstyrene-Isoamylene-Piperylene Polymer	Ingestion	Rat	LD50 > 40,000 mg/kg
Fatty Acids, C14-18 and C16-C18-Unsatd.	Ingestion	Rat	LD50 > 2,000 mg/kg
Fatty Acids, C14-18 and C16-C18-Unsatd.	Dermal	similar compoun ds	LD50 > 2,000 mg/kg

ATE = acute toxicity estimate

## Skin Corrosion/Irritation

Name	Species	Value
Zinc Borate 2335	Rabbit	No significant irritation
Sodium Silicate	Rabbit	Corrosive
Styrene-Butadiene Polymer	Professio	No significant irritation
	nal	
	judgeme	
	nt	
Polyisobutylene	Rabbit	No significant irritation
Melamine Phosphate	In vitro	No significant irritation
	data	
Oxide Glass Chemicals	Professio	No significant irritation
	nal	
	judgeme	
	nt	
Butadiene-Styrene-Meta-Divinylbenzene Polymer	Professio	Minimal irritation
	nal	
	judgeme	
	nt	
Synthetic amorphous silica, fumed, crystalline-free	Rabbit	No significant irritation
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer	Rabbit	No significant irritation
Fatty Acids, C14-18 and C16-C18-Unsatd.	similar	No significant irritation
	compoun	
	ds	

# Serious Eye Damage/Irritation

Name	Species	Value
Zinc Borate 2335	Rabbit	Severe irritant
Sodium Silicate	In vitro	Corrosive
	data	
Polyisobutylene	Rabbit	No significant irritation
Melamine Phosphate	Rabbit	Mild irritant
Oxide Glass Chemicals	Professio	No significant irritation
	nal	
	judgeme	
	nt	

Synthetic amorphous silica, fumed, crystalline-free	Rabbit	No significant irritation
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer	Rabbit	Mild irritant
Fatty Acids, C14-18 and C16-C18-Unsatd.	similar	Mild irritant
	compoun	
	ds	

## **Skin Sensitization**

Name	Species	Value
Zinc Borate 2335	Guinea	Not classified
	pig	
Sodium Silicate	Mouse	Not classified
Melamine Phosphate	similar	Not classified
	compoun	
	ds	
Synthetic amorphous silica, fumed, crystalline-free	Human	Not classified
	and	
	animal	
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer	Guinea	Not classified
	pig	
Fatty Acids, C14-18 and C16-C18-Unsatd.	similar	Not classified
	compoun	
	ds	

## **Respiratory Sensitization**

Name	Species	Value
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer	Human	Not classified

## Germ Cell Mutagenicity

Name	Route	Value
Zinc Borate 2335	In Vitro	Some positive data exist, but the data are not
		sufficient for classification
Zinc Borate 2335	In vivo	Mutagenic
Sodium Silicate	In Vitro	Not mutagenic
Sodium Silicate	In vivo	Not mutagenic
Melamine Phosphate	In Vitro	Not mutagenic
Oxide Glass Chemicals	In Vitro	Some positive data exist, but the data are not
		sufficient for classification
Synthetic amorphous silica, fumed, crystalline-free	In Vitro	Not mutagenic
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer	In vivo	Not mutagenic
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer	In Vitro	Some positive data exist, but the data are not
		sufficient for classification
Fatty Acids, C14-18 and C16-C18-Unsatd.	In Vitro	Not mutagenic

## Carcinogenicity

Name	Route	Species	Value
Melamine Phosphate	Ingestion	similar	Carcinogenic
		compoun	
		ds	
Oxide Glass Chemicals	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Synthetic amorphous silica, fumed, crystalline-free	Not	Mouse	Some positive data exist, but the data are not
	Specified		sufficient for classification
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer	Dermal	Mouse	Some positive data exist, but the data are not
			sufficient for classification

## **Reproductive Toxicity**

## **Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
------	-------	-------	---------	-------------	----------------------

Zinc Borate 2335	Ingestion	Toxic to male reproduction	Rat	NOAEL 100 mg/kg/day	92 days
Zinc Borate 2335	Ingestion	Toxic to development	Rat	LOAEL 100 mg/kg/day	during gestation
Sodium Silicate	Ingestion	Not classified for development	Mouse	NOAEL 200 mg/kg/day	during gestation
Melamine Phosphate	Ingestion	Toxic to male reproduction	similar compoun ds	NOAEL Not available	2 generation
Synthetic amorphous silica, fumed, crystalline-free	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Synthetic amorphous silica, fumed, crystalline-free	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Synthetic amorphous silica, fumed, crystalline-free	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesi s
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesi s
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation

## Target Organ(s)

## Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Zinc Borate 2335	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Sodium Silicate	Inhalation	respiratory irritation	May cause respiratory irritation	official classifica tion	NOAEL Not available	

## Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Zinc Borate 2335	Inhalation	immune system   respiratory system   heart   endocrine system   hematopoietic system   liver   nervous system   kidney and/or bladder	Not classified	Rat	NOAEL 0.15 mg/l	2 weeks
Zinc Borate 2335	Ingestion	endocrine system   liver   kidney and/or bladder   heart   skin   bone, teeth, nails, and/or hair   hematopoietic system   immune system   nervous system   nervous system   eyes   respiratory system   vascular system	Not classified	Rat	NOAEL 375 mg/kg/day	92 days
Sodium Silicate	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Dog	LOAEL 2,400 mg/kg/day	4 weeks
Sodium Silicate	Ingestion	endocrine system   blood	Not classified	Rat	NOAEL 804 mg/kg/day	3 months

Sodium Silicate	Ingestion	heart   liver	Not classified	Rat	NOAEL 1,259 mg/kg/day	8 weeks
Melamine Phosphate	Ingestion	kidney and/or bladder	Causes damage to organs through prolonged or repeated exposure	similar compoun ds	NOAEL Not available	90 days
Oxide Glass Chemicals	Inhalation	respiratory system	Not classified	Human	NOAEL not available	occupational exposure
Synthetic amorphous silica, fumed, crystalline- free	Inhalation	respiratory system   silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer	Ingestion	auditory system   heart   endocrine system   hematopoietic system   liver   eyes   kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

## Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

## **SECTION 12: Ecological information**

No data available.

# **SECTION 13: Disposal considerations**

## 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

# **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

# **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **Global inventory status**

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

# **SECTION 16: Other information**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 3 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document group:	28-4707-7	Version number:	6.01
Issue Date:	2024/10/04	Supercedes Date:	2024/05/15

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

## 3M Canada SDSs are available at www.3M.ca