



Safety Data Sheet

Copyright, 2020, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	20-7254-4	Version number:	11.01
Issue Date:	2020/10/21	Supersedes Date:	2019/02/05

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3M™ Screen Printing UV Ink Series 9827 Red

Product Identification Numbers

75-3470-6901-7 75-3472-5662-2

1.2. Recommended use and restrictions on use

Intended Use

Ink

Specific Use

Screen Printing Ink

Restrictions on use

Not applicable

1.3. Supplier's details

Company:	3M Canada Company
Division:	Commercial Solutions Division
Address:	1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1
Telephone:	(800) 364-3577
Website:	www.3M.ca

1.4. Emergency telephone number

Medical Emergency Telephone: 1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 2A.

Skin Sensitizer: Category 1A.

Reproductive Toxicity: Category 1B.

Carcinogenicity: Category 2.

Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements**Signal word**

Danger

Symbols

Exclamation mark | Health Hazard |

Pictograms**Hazard statements**

Causes serious eye irritation. May cause an allergic skin reaction. May damage fertility or the unborn child. Suspected of causing cancer.

Causes damage to organs through prolonged or repeated exposure: respiratory system |

Precautionary statements**Prevention:**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Wear protective gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash exposed skin thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF exposed or concerned: Get medical advice/attention.

Storage:

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

None known.

10% of the mixture consists of ingredients of unknown acute oral toxicity.

10% of the mixture consists of ingredients of unknown acute dermal toxicity.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
PHENOXY ETHYL ACRYLATE	48145-04-6	15 - 40 Trade Secret *	2-Propenoic acid, 2-phenoxyethyl ester

VINYLCAPROLACTAM	2235-00-9	10 - 30 Trade Secret *	2H-Azepin-2-one, 1-ethenylhexahydro-; Vinylcaprolactam
3,6-BIS(4-CHLOROPHENYL)-2,5-DIHYDROPYRROLO(3,4-C)PYRROLE-1,4-DIONE	84632-65-5	10 - 20	Pyrrolo[3,4-c]pyrrole-1,4-dione, 3,6-bis(4-chlorophenyl)-2,5-dihydro-
METHACRYLATE POLYMER	Trade Secret	10 - 20	Not Applicable
ALIPHATIC URETHANE ACRYLATE	Trade Secret	7 - 13	Not Applicable
1-BUTANONE, 2-(DIMETHYLAMINO)-1-[4-(4-MORPHOLINYL)PHENYL]-2-(PHENYLMETHYL)-	119313-12-1	1 - 5	1-Butanone, 2-(dimethylamino)-1-[4-(4-morpholinyl)phenyl]-2-(phenylmethyl)-
1-PROPANONE, 2-METHYL-1-[4-(METHYLTHIO)PHENYL]-2-(4-MORPHOLINYL)-	71868-10-5	1 - 5 Trade Secret *	2-Methyl-4'-(methylthio)-2-morpholinopropiophenone
ACRYLATE ESTER	7328-17-8	1 - 5 Trade Secret *	2-Propenoic acid, 2-(2-ethoxyethoxy)ethyl ester; Carbitol acrylate
Synthetic Amorphous Silica, Fumed, Crystalline Free	112945-52-5	1 - 5	Fumed amorphous silica, crystalline-free
.ALPHA.,.ALPHA.',.ALPHA."-1,2,3-PROPANETRIYLTRIS[POLYPROPYLENE GLYCOL ACRYLATE]	52408-84-1	0.1 - 1.0 Trade Secret *	glycerol, propoxylated, esters with Acrylic acid; Propoxylated glycerol triacrylate
Ethylbenzene	100-41-4	0.1 - 1.0 Trade Secret *	Benzene, ethyl-
OCTAMETHYLCYCLOTETRA-SILOXANE	556-67-2	0.1 - 1.0 Trade Secret *	Octamethylcyclotetrasiloxane
TMPEOTA	28961-43-5	< 1.0	Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2-propenyl)oxy]-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1)

ALIPHATIC URETHANE ACRYLATE is a non-hazardous Trade Secret material according to WHMIS criteria.
METHACRYLATE POLYMER is a non-hazardous Trade Secret material according to WHMIS criteria.

*The actual concentration of this ingredient has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Formaldehyde

Carbon monoxide

Carbon dioxide

Condition

During Combustion

During Combustion

During Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Protect from sunlight. Store away from heat. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Ethylbenzene	100-41-4	ACGIH	TWA:20 ppm	
VINYLCAPROLACTAM	2235-00-9	Manufacturer determined	TWA:0.1 ppm(0.57 mg/m ³)	
OCTAMETHYLCYCLOTETRA SILOXANE	556-67-2	AIHA	TWA:10 ppm	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls**8.2.1. Engineering controls**

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)**Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Specific Physical Form:	Liquid
Colour	Red
Odour	Mild Acrylic, Sweet Acrylic
Odour threshold	No Data Available
pH	Not Applicable
Melting point/Freezing point	Not Applicable
Boiling point	> 148.9 °C
Flash Point	> 93.3 °C [Test Method:Pensky-Martens Closed Cup]
Evaporation rate	< 1 [Ref Std:BUOAC=1]
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	No Data Available
Flammable Limits(UEL)	No Data Available
Vapour Pressure	< 160 Pa [@ 20 °C]
Viscosity/Kinematic Viscosity Viscosity/Kinematic Viscosity	No Data Available
Density	Approximately 1.3 g/ml
Relative density	Approximately 1.3 [Ref Std:WATER=1]
Water solubility	Negligible
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Viscosity/Kinematic Viscosity	No Data Available
Volatile Organic Compounds	7 g/l
Percent volatile	1 - 5 % weight
VOC Less H2O & Exempt Solvents	7 g/l

Nanoparticles

This material contains nanoparticles.

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization may occur. Upon loss of initiator or with exposure to heat.

10.4. Conditions to avoid

Sparks and/or flames

Heat

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products**Substance****Condition**

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects**Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

May be harmful if swallowed. Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea. May cause additional health effects (see below).

Additional Health Effects:**Prolonged or repeated exposure may cause target organ effects:**

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

<u>Ingredient</u>	<u>CAS No.</u>	<u>Class Description</u>	<u>Regulation</u>
Ethylbenzene	100-41-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Additional Information:

Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE 2,000 - 5,000 mg/kg
PHENOXY ETHYL ACRYLATE	Dermal	Rat	LD50 > 2,000 mg/kg
PHENOXY ETHYL ACRYLATE	Ingestion	Rat	LD50 > 5,000 mg/kg
METHACRYLATE POLYMER	Dermal		LD50 estimated to be > 5,000 mg/kg
METHACRYLATE POLYMER	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
VINYLCAPROLACTAM	Dermal	Rabbit	LD50 1,700 mg/kg
VINYLCAPROLACTAM	Ingestion	Rat	LD50 1,049 mg/kg
3,6-BIS(4-CHLOROPHENYL)-2,5-DIHYDROPYRROLO(3,4-C)PYRROLE-1,4-DIONE	Dermal	Rat	LD50 > 2,000 mg/kg
3,6-BIS(4-CHLOROPHENYL)-2,5-DIHYDROPYRROLO(3,4-C)PYRROLE-1,4-DIONE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.25 mg/l
3,6-BIS(4-CHLOROPHENYL)-2,5-DIHYDROPYRROLO(3,4-C)PYRROLE-1,4-DIONE	Ingestion	Rat	LD50 > 5,000 mg/kg
Synthetic Amorphous Silica, Fumed, Crystalline Free	Dermal	Rabbit	LD50 > 5,000 mg/kg
Synthetic Amorphous Silica, Fumed, Crystalline Free	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Synthetic Amorphous Silica, Fumed, Crystalline Free	Ingestion	Rat	LD50 > 5,110 mg/kg
ACRYLATE ESTER	Dermal		LD50 estimated to be 1,000 - 2,000 mg/kg
ACRYLATE ESTER	Ingestion	Rat	LD50 1,860 mg/kg
1-BUTANONE, 2-(DIMETHYLAMINO)-1-[4-(4-MORPHOLINYL)PHENYL]-2-(PHENYLMETHYL)-	Dermal	Rat	LD50 > 2,000 mg/kg
1-BUTANONE, 2-(DIMETHYLAMINO)-1-[4-(4-MORPHOLINYL)PHENYL]-2-(PHENYLMETHYL)-	Ingestion	Rat	LD50 > 5,000 mg/kg
1-PROPANONE, 2-METHYL-1-[4-(METHYLTHIO)PHENYL]-2-(4-MORPHOLINYL)-	Dermal	Rat	LD50 > 2,000 mg/kg
1-PROPANONE, 2-METHYL-1-[4-(METHYLTHIO)PHENYL]-2-(4-MORPHOLINYL)-	Ingestion	Rat	LD50 967 mg/kg
TMPEOTA	Dermal	Rabbit	LD50 > 13,000 mg/kg
TMPEOTA	Ingestion	Rat	LD50 > 2,000 mg/kg
.ALPHA.,.ALPHA.',.ALPHA."-1,2,3-PROPANETRIYLTRIS[POLYPROPYLENE GLYCOL ACRYLATE]	Dermal	Rabbit	LD50 > 2,000 mg/kg
.ALPHA.,.ALPHA.',.ALPHA."-1,2,3-PROPANETRIYLTRIS[POLYPROPYLENE GLYCOL ACRYLATE]	Ingestion	Rat	LD50 > 2,000 mg/kg
OCTAMETHYLCYCLOTETRASIOXANE	Dermal	Rat	LD50 > 2,400 mg/kg
OCTAMETHYLCYCLOTETRASIOXANE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 36 mg/l
OCTAMETHYLCYCLOTETRASIOXANE	Ingestion	Rat	LD50 > 5,000 mg/kg
Ethylbenzene	Dermal	Rabbit	LD50 15,433 mg/kg
Ethylbenzene	Inhalation-Vapor (4 hours)	Rat	LC50 17.4 mg/l
Ethylbenzene	Ingestion	Rat	LD50 4,769 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
PHENOXY ETHYL ACRYLATE	Rabbit	No significant irritation
VINYLCAPROLACTAM	Rabbit	Minimal irritation
3,6-BIS(4-CHLOROPHENYL)-2,5-DIHYDROPYRROLO(3,4-C)PYRROLE-	Rabbit	No significant irritation

3M™ Screen Printing UV Ink Series 9827 Red

1,4-DIONE		
Synthetic Amorphous Silica, Fumed, Crystalline Free	Rabbit	No significant irritation
ACRYLATE ESTER	Rabbit	Irritant
1-BUTANONE, 2-(DIMETHYLAMINO)-1-[4-(4-MORPHOLINYL)PHENYL]-2-(PHENYLMETHYL)-	Rabbit	No significant irritation
1-PROPANONE, 2-METHYL-1-[4-(METHYLTHIO)PHENYL]-2-(4-MORPHOLINYL)-	Rabbit	No significant irritation
TMPEOTA	Rabbit	Minimal irritation
.ALPHA.,.ALPHA.',.ALPHA."-1,2,3-PROPANETRIYLTRIS[POLYPROPYLENE GLYCOL ACRYLATE]	Rabbit	Minimal irritation
OCTAMETHYLCYCLOTETRASILOXANE	Rabbit	Minimal irritation
Ethylbenzene	Rabbit	Mild irritant

Serious Eye Damage/Irritation

Name	Species	Value
PHENOXY ETHYL ACRYLATE	Rabbit	No significant irritation
VINYLCAPROLACTAM	Rabbit	Severe irritant
3,6-BIS(4-CHLOROPHENYL)-2,5-DIHYDROPYRROLO(3,4-C)PYRROLE-1,4-DIONE	Rabbit	No significant irritation
Synthetic Amorphous Silica, Fumed, Crystalline Free	Rabbit	No significant irritation
ACRYLATE ESTER	Rabbit	Severe irritant
1-BUTANONE, 2-(DIMETHYLAMINO)-1-[4-(4-MORPHOLINYL)PHENYL]-2-(PHENYLMETHYL)-	Rabbit	No significant irritation
1-PROPANONE, 2-METHYL-1-[4-(METHYLTHIO)PHENYL]-2-(4-MORPHOLINYL)-	Rabbit	No significant irritation
TMPEOTA	Rabbit	Severe irritant
.ALPHA.,.ALPHA.',.ALPHA."-1,2,3-PROPANETRIYLTRIS[POLYPROPYLENE GLYCOL ACRYLATE]	Rabbit	Severe irritant
OCTAMETHYLCYCLOTETRASILOXANE	Rabbit	No significant irritation
Ethylbenzene	Rabbit	Moderate irritant

Skin Sensitization

Name	Species	Value
PHENOXY ETHYL ACRYLATE	Guinea pig	Sensitizing
VINYLCAPROLACTAM	Mouse	Sensitizing
Synthetic Amorphous Silica, Fumed, Crystalline Free	Human and animal	Not classified
ACRYLATE ESTER	Guinea pig	Sensitizing
1-BUTANONE, 2-(DIMETHYLAMINO)-1-[4-(4-MORPHOLINYL)PHENYL]-2-(PHENYLMETHYL)-	Guinea pig	Not classified
TMPEOTA	Guinea pig	Sensitizing
.ALPHA.,.ALPHA.',.ALPHA."-1,2,3-PROPANETRIYLTRIS[POLYPROPYLENE GLYCOL ACRYLATE]	Mouse	Sensitizing
OCTAMETHYLCYCLOTETRASILOXANE	Human and animal	Not classified
Ethylbenzene	Human	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
VINYLCAPROLACTAM	In Vitro	Not mutagenic
Synthetic Amorphous Silica, Fumed, Crystalline Free	In Vitro	Not mutagenic
1-BUTANONE, 2-(DIMETHYLAMINO)-1-[4-(4-MORPHOLINYL)PHENYL]-2-(PHENYLMETHYL)-	In Vitro	Not mutagenic
1-BUTANONE, 2-(DIMETHYLAMINO)-1-[4-(4-	In vivo	Not mutagenic

3M™ Screen Printing UV Ink Series 9827 Red

MORPHOLINYL)PHENYL]-2-(PHENYLMETHYL)-OCTAMETHYLCYCLOTETRASILOXANE	In Vitro	Some positive data exist, but the data are not sufficient for classification
Ethylbenzene	In vivo	Not mutagenic
Ethylbenzene	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Synthetic Amorphous Silica, Fumed, Crystalline Free	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Ethylbenzene	Inhalation	Multiple animal species	Carcinogenic

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
PHENOXY ETHYL ACRYLATE	Ingestion	Not classified for male reproduction	Rat	NOAEL 800 mg/kg/day	43 days
PHENOXY ETHYL ACRYLATE	Ingestion	Toxic to female reproduction	Rat	NOAEL 300 mg/kg/day	premating into lactation
PHENOXY ETHYL ACRYLATE	Ingestion	Toxic to development	Rat	NOAEL 300 mg/kg/day	premating into lactation
Synthetic Amorphous Silica, Fumed, Crystalline Free	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Synthetic Amorphous Silica, Fumed, Crystalline Free	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Synthetic Amorphous Silica, Fumed, Crystalline Free	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
1-BUTANONE, 2-(DIMETHYLAMINO)-1-[4-(4-MORPHOLINYL)PHENYL]-2-(PHENYLMETHYL)-	Ingestion	Not classified for female reproduction	Rat	NOAEL 300 mg/kg/day	1 generation
1-BUTANONE, 2-(DIMETHYLAMINO)-1-[4-(4-MORPHOLINYL)PHENYL]-2-(PHENYLMETHYL)-	Ingestion	Not classified for male reproduction	Rat	NOAEL 300 mg/kg/day	1 generation
1-BUTANONE, 2-(DIMETHYLAMINO)-1-[4-(4-MORPHOLINYL)PHENYL]-2-(PHENYLMETHYL)-	Ingestion	Toxic to development	Rat	NOAEL 30 mg/kg/day	1 generation
1-PROPANONE, 2-METHYL-1-[4-(METHYLTHIO)PHENYL]-2-(4-MORPHOLINYL)-	Ingestion	Toxic to female reproduction	Rat	LOAEL 40 mg/kg/day	1 generation
1-PROPANONE, 2-METHYL-1-[4-(METHYLTHIO)PHENYL]-2-(4-MORPHOLINYL)-	Ingestion	Toxic to development	Rat	LOAEL 40 mg/kg/day	1 generation
OCTAMETHYLCYCLOTETRASILOXANE	Inhalation	Not classified for male reproduction	Rat	NOAEL 8.5 mg/l	2 generation
OCTAMETHYLCYCLOTETRASILOXANE	Ingestion	Toxic to female reproduction	Rabbit	NOAEL 50 mg/kg/day	during organogenesis
OCTAMETHYLCYCLOTETRASILOXANE	Inhalation	Toxic to female reproduction	Rat	NOAEL 3.6 mg/l	2 generation
Ethylbenzene	Inhalation	Not classified for development	Rat	NOAEL 4.3 mg/l	premating & during gestation

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
VINYLCAPROLACTAM	Inhalation	respiratory irritation	Some positive data exist, but the	Rat	NOAEL Not	

3M™ Screen Printing UV Ink Series 9827 Red

			data are not sufficient for classification		available	
Ethylbenzene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Ethylbenzene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	
Ethylbenzene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
VINYLCAPROLACTAM	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 0.001 mg/l	28 days
VINYLCAPROLACTAM	Inhalation	blood liver kidney and/or bladder eyes	Not classified	Rat	NOAEL 0.18 mg/l	90 days
VINYLCAPROLACTAM	Ingestion	liver	Not classified	Rat	NOAEL 260 mg/kg/day	3 months
Synthetic Amorphous Silica, Fumed, Crystalline Free	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
1-BUTANONE, 2-(DIMETHYLAMINO)-1-[4-(4-MORPHOLINYL)PHENYL]-2-(PHENYLMETHYL)-	Ingestion	endocrine system hematopoietic system liver kidney and/or bladder	Not classified	Rat	NOAEL 500 mg/kg/day	28 days
1-PROPANONE, 2-METHYL-1-[4-(METHYLTHIO)PHENYL]-2-(4-MORPHOLINYL)-	Ingestion	peripheral nervous system eyes	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 75 mg/kg/day	90 days
OCTAMETHYLCYCLOTRISILOXANE	Dermal	hematopoietic system	Not classified	Rabbit	NOAEL 960 mg/kg/day	3 weeks
OCTAMETHYLCYCLOTRISILOXANE	Inhalation	liver	Not classified	Rat	NOAEL 8.5 mg/l	13 weeks
OCTAMETHYLCYCLOTRISILOXANE	Inhalation	endocrine system immune system kidney and/or bladder	Not classified	Rat	NOAEL 8.5 mg/l	2 generation
OCTAMETHYLCYCLOTRISILOXANE	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 8.5 mg/l	13 weeks
OCTAMETHYLCYCLOTRISILOXANE	Ingestion	liver	Not classified	Rat	NOAEL 1,600 mg/kg/day	2 weeks
Ethylbenzene	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	2 years
Ethylbenzene	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 1.1 mg/l	103 weeks
Ethylbenzene	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 3.4 mg/l	28 days
Ethylbenzene	Inhalation	auditory system	Not classified	Rat	NOAEL 2.4 mg/l	5 days
Ethylbenzene	Inhalation	endocrine system	Not classified	Mouse	NOAEL 3.3 mg/l	103 weeks
Ethylbenzene	Inhalation	gastrointestinal tract	Not classified	Rat	NOAEL 3.3 mg/l	2 years
Ethylbenzene	Inhalation	bone, teeth, nails, and/or hair muscles	Not classified	Multiple animal species	NOAEL 4.2 mg/l	90 days
Ethylbenzene	Inhalation	heart immune	Not classified	Multiple	NOAEL 3.3	2 years

3M™ Screen Printing UV Ink Series 9827 Red

		system respiratory system		animal species	mg/l	
Ethylbenzene	Ingestion	liver kidney and/or bladder	Not classified	Rat	NOAEL 680 mg/kg/day	6 months

Aspiration Hazard

Name	Value
Ethylbenzene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Global inventory status**

Contact 3M for more information. The components of this product are in compliance with the chemical notification requirements of TSCA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 2 Flammability: 1 Instability: 1 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar

emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document group:	20-7254-4	Version number:	11.01
Issue Date:	2020/10/21	Supercedes Date:	2019/02/05

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca