



## Safety Data Sheet

Copyright, 2024, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	42-2325-1	<b>Version number:</b>	5.01
<b>Issue Date:</b>	2024/08/09	<b>Supersedes Date:</b>	2024/05/01

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Scotch-Weld™ Low Odor Acrylic Adhesive 8725NS, Black, Part B

#### Product Identification Numbers

62-2874-8530-4      62-2874-9530-3

#### 1.2. Recommended use and restrictions on use

##### Intended Use

Adhesive

##### Restrictions on use

Not applicable

#### 1.3. Supplier's details

<b>Company:</b>	3M Canada Company
<b>Division:</b>	Industrial Adhesives and Tapes Division
<b>Address:</b>	1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1
<b>Telephone:</b>	(800) 364-3577
<b>Website:</b>	www.3M.ca

#### 1.4. Emergency telephone number

Medical Emergency Telephone: 1-800-3M HELPS / 1800 364 3577

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 1.

Skin Corrosion/Irritation: Category 2.

Skin Sensitizer: Category 1.

#### 2.2. Label elements

##### Signal word

Danger

##### Symbols

Corrosion | Exclamation mark |

#### Pictograms



#### Hazard statements

Causes serious eye damage. Causes skin irritation. May cause an allergic skin reaction.

#### Precautionary statements

##### Prevention:

Avoid breathing dust/fume/gas/mist/vapours/spray. Wear protective gloves and eye/face protection. Wash exposed skin thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

##### Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN: Wash with plenty of soap and water. Immediately call a POISON CENTRE or doctor/physician. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

##### Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

#### 2.3. Other hazards

None known.

14% of the mixture consists of ingredients of unknown acute oral toxicity.  
17% of the mixture consists of ingredients of unknown acute dermal toxicity.  
68% of the mixture consists of ingredients of unknown acute inhalation toxicity.

## SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Hydroxyethyl Methacrylate	868-77-9	22.6 - 50	2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester
Butadiene-Acrylonitrile Polymer	9003-18-3	1 - 15	2-Propenenitrile, polymer with 1,3-butadiene
Cyclohexyl methacrylate	101-43-9	4.9 - 15	No Data Available
Polymeric Methacrylate	Trade Secret	1 - 15	Not Applicable
Lauryl methacrylate	142-90-5	3 - 10.5	No Data Available
Acrylic Copolymer	Trade Secret	<= 10	Not Applicable
Fillers	Trade Secret	1 - 10	Not Applicable
Amorphous silica	67762-90-7	1 - 5	Siloxanes and Silicones, di-Me, reaction products with silica
Hexadecyl methacrylate	2495-27-4	0.1 - 5	No Data Available
Myristyl methacrylate	2549-53-3	1 - 5	No Data Available
Phosphate Esters of PPG	95175-93-2	0.5 - 5 Trade Secret *	No Data Available

Methacrylate			
Urethane Acrylate Oligomer	Trade Secret	0.1 - 5	Not Applicable
Benzyltributylammonium Chloride	23616-79-7	0.1 - 3	Benzenemethanaminium, N,N,N-tributyl-, chloride
Hydroxypropyl methacrylate	27813-02-1	0.35 - 1.75	2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol
4-Methoxyphenol	150-76-5	< 1	4-Methoxyphenol
Carbon Black	1333-86-4	< 1	Carbon black
Copper Naphthenates	1338-02-9	< 0.25	No Data Available
Methyl Methacrylate	80-62-6	0 - 0.15	2-Propenoic acid, 2-methyl-, methyl ester

Urethane Acrylate Oligomer is a non-hazardous Trade Secret material according to WHMIS criteria.

Acrylic Copolymer is a non-hazardous Trade Secret material according to WHMIS criteria.

Fillers is a non-hazardous Trade Secret material according to WHMIS criteria.

Polymeric Methacrylate is a non-hazardous Trade Secret material according to WHMIS criteria.

Carbon black is inextricably bound in this product. Exposure to carbon black is not expected during product use

\*The actual concentration of this ingredient has been withheld as a trade secret.

## **SECTION 4: First aid measures**

### **4.1. Description of first aid measures**

#### **Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

#### **Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### **Eye Contact:**

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

#### **If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

### **4.2. Most important symptoms and effects, both acute and delayed**

Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision).

### **4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

## **SECTION 5: Fire-fighting measures**

### **5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### **5.2. Unsuitable extinguishing media**

None Determined

### **5.3. Special hazards arising from the substance or mixture**

Exposure to extreme heat can give rise to thermal decomposition.

**Hazardous Decomposition or By-Products****Substance**

Carbon monoxide  
Carbon dioxide  
Hydrogen Chloride  
Hydrogen Fluoride  
Oxides of Nitrogen

**Condition**

During Combustion  
During Combustion  
During Combustion  
During Combustion  
During Combustion

**5.4. Special protection actions for fire-fighters**

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA). Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

Do not breathe thermal decomposition products. For industrial or professional use only. Not for consumer sale or use. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

**7.2. Conditions for safe storage including any incompatibilities**

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents. Store away from amines.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Carbon Black	1333-86-4	ACGIH	TWA(inhalable fraction):3	

			mg/m3	
COPPER COMPOUNDS	1338-02-9	ACGIH	TWA(as Cu, fume):0.2 mg/m3;TWA(as Cu dust or mist):1 mg/m3	
4-Methoxyphenol	150-76-5	ACGIH	TWA:5 mg/m3	
Methyl Methacrylate	80-62-6	ACGIH	TWA:50 ppm;STEL:100 ppm	Dermal Sensitizer

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

## 8.2. Exposure controls

### 8.2.1. Engineering controls

For those situations where the material might be exposed to extreme overheating due to misuse or equipment failure, use with appropriate local exhaust ventilation sufficient to maintain levels of thermal decomposition products below their exposure guidelines. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

For those situations where the material might be exposed to extreme overheating due to misuse or equipment failure, use a positive pressure supplied-air respirator.

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

**9.1. Information on basic physical and chemical properties**

<b>Physical state</b>	Liquid
<b>Specific Physical Form:</b>	Paste
<b>Colour</b>	Black
<b>Odour</b>	Mild Acrylate
<b>Odour threshold</b>	<i>No Data Available</i>
<b>pH</b>	<i>Not Applicable</i>
<b>Melting point/Freezing point</b>	<i>Not Applicable</i>
<b>Boiling point</b>	<i>No Data Available</i>
<b>Flash Point</b>	> 93.3 °C [Test Method: Closed Cup]
<b>Evaporation rate</b>	<i>No Data Available</i>
<b>Flammability</b>	Not Applicable
<b>Flammable Limits(LEL)</b>	<i>No Data Available</i>
<b>Flammable Limits(UEL)</b>	<i>No Data Available</i>
<b>Vapour Pressure</b>	<i>No Data Available</i>
<b>Vapour Density and/or Relative Vapour Density</b>	<i>No Data Available</i>
<b>Density</b>	1.04 g/ml
<b>Relative density</b>	1.04 [Ref Std: WATER=1]
<b>Water solubility</b>	Nil
<b>Solubility- non-water</b>	<i>No Data Available</i>
<b>Partition coefficient: n-octanol/ water</b>	<i>No Data Available</i>
<b>Autoignition temperature</b>	<i>No Data Available</i>
<b>Decomposition temperature</b>	<i>No Data Available</i>
<b>Kinematic Viscosity</b>	38,462 mm <sup>2</sup> /sec
<b>Volatile Organic Compounds</b>	<i>No Data Available</i>
<b>Percent volatile</b>	<i>No Data Available</i>
<b>VOC Less H<sub>2</sub>O &amp; Exempt Solvents</b>	<=10 g/l [Test Method: calculated SCAQMD rule 443.1] [Details: when used as intended with Part A]
<b>VOC Less H<sub>2</sub>O &amp; Exempt Solvents</b>	<=575 g/l [Test Method: calculated SCAQMD rule 443.1] [Details: as supplied]
<b>VOC Less H<sub>2</sub>O &amp; Exempt Solvents</b>	<=1 % [Test Method: calculated SCAQMD rule 443.1] [Details: when used as intended with Part A]
<b>Molecular weight</b>	<i>Not Applicable</i>

<b>Particle Characteristics</b>	<i>Not Applicable</i>
---------------------------------	-----------------------

**SECTION 10: Stability and reactivity****10.1. Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

**10.2. Chemical stability**

Stable.

**10.3. Possibility of hazardous reactions**

Hazardous polymerization will not occur.

**10.4. Conditions to avoid**

Heat  
Sparks and/or flames

**10.5. Incompatible materials**

Amines  
 Strong acids  
 Strong bases  
 Strong oxidizing agents

**10.6. Hazardous decomposition products****Substance****Condition**

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

Extreme heat arising from situations such as misuse or equipment failure can generate hydrogen fluoride as a decomposition product.

**SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

**11.1. Information on Toxicological effects****Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

**Inhalation:**

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

**Skin Contact:**

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.  
 Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

**Eye Contact:**

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

**Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

**Carcinogenicity:**

<b><u>Ingredient</u></b>	<b><u>CAS No.</u></b>	<b><u>Class Description</u></b>	<b><u>Regulation</u></b>
Carbon black	1333-86-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

<b><u>Name</u></b>	<b><u>Route</u></b>	<b><u>Species</u></b>	<b><u>Value</u></b>
--------------------	---------------------	-----------------------	---------------------

**3M™ Scotch-Weld™ Low Odor Acrylic Adhesive 8725NS, Black, Part B**

Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Hydroxyethyl Methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
Hydroxyethyl Methacrylate	Ingestion	Rat	LD50 5,564 mg/kg
Cyclohexyl methacrylate	Dermal	Rat	LD50 > 2,000 mg/kg
Cyclohexyl methacrylate	Ingestion	Rat	LD50 12,900 mg/kg
Cyclohexyl methacrylate	Inhalation-Vapor	similar compounds	LC50 estimated to be 20 - 50 mg/l
Lauryl methacrylate	Ingestion	Rat	LD50 > 5,000 mg/kg
Lauryl methacrylate	Dermal	similar compounds	LD50 > 3,000 mg/kg
Butadiene-Acrylonitrile Polymer	Dermal	Rabbit	LD50 > 15,000 mg/kg
Butadiene-Acrylonitrile Polymer	Ingestion	Rat	LD50 > 30,000 mg/kg
Fillers	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.07 mg/l
Fillers	Dermal	similar compounds	LD50 > 5,000 mg/kg
Fillers	Ingestion	similar compounds	LD50 > 5,000 mg/kg
Amorphous silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Amorphous silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Amorphous silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Myristyl methacrylate	Dermal	Rabbit	LD50 > 3,000 mg/kg
Myristyl methacrylate	Ingestion	Rat	LD50 > 5,000 mg/kg
Benzyltributylammonium Chloride	Ingestion	Not available	LD50 500 mg/kg
Phosphate Esters of PPG Methacrylate	Ingestion	Rat	LD50 > 5,000 mg/kg
Phosphate Esters of PPG Methacrylate	Dermal	similar health hazards	LD50 estimated to be > 5,000 mg/kg
Hydroxypropyl methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
Hydroxypropyl methacrylate	Ingestion	Rat	LD50 > 11,200 mg/kg
Hexadecyl methacrylate	Dermal	Rabbit	LD50 > 3,000 mg/kg
Hexadecyl methacrylate	Ingestion	Rat	LD50 > 5,000 mg/kg
Carbon Black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon Black	Ingestion	Rat	LD50 > 8,000 mg/kg
Methyl Methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
Methyl Methacrylate	Inhalation-Vapor (4 hours)	Rat	LC50 29.8 mg/l
Methyl Methacrylate	Ingestion	Rat	LD50 7,900 mg/kg
Copper Naphthenates	Dermal	similar compounds	LD50 > 2,000 mg/kg
Copper Naphthenates	Ingestion	similar compounds	LD50 >300, <2,000 mg/kg
4-Methoxyphenol	Dermal	Rat	LD50 > 2,000 mg/kg
4-Methoxyphenol	Ingestion	Rat	LD50 1,630 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Hydroxyethyl Methacrylate	Rabbit	Minimal irritation
Cyclohexyl methacrylate	Rabbit	Minimal irritation



Lauryl methacrylate	similar compounds	Minimal irritation
Butadiene-Acrylonitrile Polymer	Professional judgement	No significant irritation
Fillers	Rabbit	No significant irritation
Amorphous silica	Rabbit	No significant irritation
Myristyl methacrylate	Rabbit	Minimal irritation
Benzyltributylammonium Chloride	Guinea pig	Corrosive
Phosphate Esters of PPG Methacrylate	Not available	Irritant
Hydroxypropyl methacrylate	Rabbit	Minimal irritation
Hexadecyl methacrylate	Rabbit	Minimal irritation
Carbon Black	Rabbit	No significant irritation
Methyl Methacrylate	Rabbit	Irritant
Copper Naphthenates	Rabbit	No significant irritation
4-Methoxyphenol	Rabbit	Mild irritant

### Serious Eye Damage/Irritation

Name	Species	Value
Hydroxyethyl Methacrylate	Rabbit	Moderate irritant
Cyclohexyl methacrylate	In vitro data	Severe irritant
Lauryl methacrylate	similar compounds	No significant irritation
Butadiene-Acrylonitrile Polymer	Professional judgement	No significant irritation
Fillers	Rabbit	No significant irritation
Amorphous silica	Rabbit	No significant irritation
Myristyl methacrylate	Rabbit	No significant irritation
Benzyltributylammonium Chloride	similar health hazards	Corrosive
Phosphate Esters of PPG Methacrylate	Not available	Corrosive
Hydroxypropyl methacrylate	Rabbit	Moderate irritant
Hexadecyl methacrylate	Rabbit	No significant irritation
Carbon Black	Rabbit	No significant irritation
Methyl Methacrylate	Rabbit	Mild irritant
Copper Naphthenates	In vitro data	No significant irritation
4-Methoxyphenol	Rabbit	Severe irritant

### Skin Sensitization

Name	Species	Value
Hydroxyethyl Methacrylate	Human and animal	Sensitizing
Cyclohexyl methacrylate	Mouse	Sensitizing
Lauryl methacrylate	Guinea pig	Not classified
Amorphous silica	Human and animal	Not classified
Myristyl methacrylate	Professional judgement	Some positive data exist, but the data are not sufficient for classification

**3M™ Scotch-Weld™ Low Odor Acrylic Adhesive 8725NS, Black, Part B**

Hydroxypropyl methacrylate	Human and animal	Sensitizing
Hexadecyl methacrylate	Mouse	Some positive data exist, but the data are not sufficient for classification
Methyl Methacrylate	Human and animal	Sensitizing
Copper Naphthenates	Guinea pig	Not classified
4-Methoxyphenol	Guinea pig	Sensitizing

**Respiratory Sensitization**

Name	Species	Value
Methyl Methacrylate	Human	Not classified

**Germ Cell Mutagenicity**

Name	Route	Value
Hydroxyethyl Methacrylate	In vivo	Not mutagenic
Hydroxyethyl Methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Cyclohexyl methacrylate	In Vitro	Not mutagenic
Lauryl methacrylate	In Vitro	Not mutagenic
Lauryl methacrylate	In vivo	Not mutagenic
Amorphous silica	In Vitro	Not mutagenic
Myristyl methacrylate	In Vitro	Not mutagenic
Hydroxypropyl methacrylate	In vivo	Not mutagenic
Hydroxypropyl methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Carbon Black	In Vitro	Not mutagenic
Carbon Black	In vivo	Some positive data exist, but the data are not sufficient for classification
Methyl Methacrylate	In vivo	Not mutagenic
Methyl Methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
4-Methoxyphenol	In vivo	Not mutagenic
4-Methoxyphenol	In Vitro	Some positive data exist, but the data are not sufficient for classification

**Carcinogenicity**

Name	Route	Species	Value
Amorphous silica	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Carbon Black	Dermal	Mouse	Not carcinogenic
Carbon Black	Ingestion	Mouse	Not carcinogenic
Carbon Black	Inhalation	Rat	Carcinogenic
Methyl Methacrylate	Ingestion	Rat	Not carcinogenic
Methyl Methacrylate	Inhalation	Human and animal	Not carcinogenic
4-Methoxyphenol	Dermal	Multiple animal species	Not carcinogenic
4-Methoxyphenol	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure
------	-------	-------	---------	-------------	----------

					<b>Duration</b>
Hydroxyethyl Methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
Hydroxyethyl Methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	49 days
Hydroxyethyl Methacrylate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
Cyclohexyl methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
Cyclohexyl methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	15 weeks
Cyclohexyl methacrylate	Ingestion	Not classified for development	Rabbit	NOAEL 500 mg/kg/day	during gestation
Lauryl methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
Lauryl methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	6 weeks
Lauryl methacrylate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
Amorphous silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Amorphous silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Amorphous silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Hydroxypropyl methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
Hydroxypropyl methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	49 days
Hydroxypropyl methacrylate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation
Methyl Methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 400 mg/kg/day	2 generation
Methyl Methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 400 mg/kg/day	2 generation
Methyl Methacrylate	Ingestion	Not classified for development	Rabbit	NOAEL 450 mg/kg/day	during gestation
Methyl Methacrylate	Inhalation	Not classified for development	Rat	NOAEL 8.3 mg/l	during organogenesis
4-Methoxyphenol	Ingestion	Not classified for female reproduction	Rat	NOAEL 300 mg/kg/day	premating into lactation
4-Methoxyphenol	Ingestion	Not classified for male reproduction	Rat	NOAEL 300 mg/kg/day	28 days
4-Methoxyphenol	Ingestion	Not classified for development	Rat	NOAEL 200 mg/kg/day	during gestation

## Target Organ(s)

### Specific Target Organ Toxicity - single exposure

<b>Name</b>	<b>Route</b>	<b>Target Organ(s)</b>	<b>Value</b>	<b>Species</b>	<b>Test result</b>	<b>Exposure Duration</b>
Cyclohexyl methacrylate	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	
Lauryl methacrylate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Professional judgement	NOAEL Not available	
Myristyl methacrylate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Professional judgement	NOAEL not available	

**3M™ Scotch-Weld™ Low Odor Acrylic Adhesive 8725NS, Black, Part B**

Benzyltributylammonium Chloride	Inhalation	respiratory irritation	May cause respiratory irritation	similar health hazards	NOAEL Not available	
Phosphate Esters of PPG Methacrylate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Hydroxypropyl methacrylate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Methyl Methacrylate	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	occupational exposure
4-Methoxyphenol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Cyclohexyl methacrylate	Ingestion	endocrine system   hematopoietic system   liver   kidney and/or bladder   nervous system   eyes	Not classified	Rat	NOAEL 1,000 mg/kg/day	15 weeks
Lauryl methacrylate	Ingestion	hematopoietic system   liver   kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	6 weeks
Fillers	Inhalation	pneumoconiosis	Not classified	similar compounds	NOAEL not available	occupational exposure
Amorphous silica	Inhalation	respiratory system   silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Hydroxypropyl methacrylate	Inhalation	blood	Not classified	Rat	NOAEL 0.5 mg/l	21 days
Hydroxypropyl methacrylate	Ingestion	hematopoietic system   heart   endocrine system   liver   immune system   nervous system   kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	41 days
Carbon Black	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure
Methyl Methacrylate	Dermal	peripheral nervous system	Not classified	Human	NOAEL Not available	occupational exposure
Methyl Methacrylate	Inhalation	olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Methyl Methacrylate	Inhalation	kidney and/or bladder	Not classified	Multiple animal species	NOAEL Not available	14 weeks
Methyl Methacrylate	Inhalation	liver	Not classified	Mouse	NOAEL 12.3 mg/l	14 weeks
Methyl Methacrylate	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Methyl Methacrylate	Ingestion	kidney and/or bladder   heart   skin   endocrine system   gastrointestinal tract   hematopoietic system   liver   muscles   nervous system   respiratory system	Not classified	Rat	NOAEL 90.3 mg/kg/day	2 years
4-Methoxyphenol	Ingestion	gastrointestinal tract	Not classified	Rat	LOAEL 300 mg/kg/day	28 days
4-Methoxyphenol	Ingestion	liver   immune	Not classified	Rat	NOAEL 300	28 days

		system			mg/kg/day	
4-Methoxyphenol	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 300 mg/kg/day	28 days
4-Methoxyphenol	Ingestion	heart   endocrine system   hematopoietic system   nervous system   respiratory system	Not classified	Rat	NOAEL 300 mg/kg/day	28 days

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.**

**SECTION 12: Ecological information**

No data available.

**SECTION 13: Disposal considerations****13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

**SECTION 14: Transport Information**

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Global inventory status**

Contact 3M for more information.

**SECTION 16: Other information**

**National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.**

**Health: 3 Flammability: 1 Instability: 0 Special Hazards: None**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

<b>Document group:</b>	42-2325-1	<b>Version number:</b>	5.01
<b>Issue Date:</b>	2024/08/09	<b>Supersedes Date:</b>	2024/05/01

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

**3M Canada SDSs are available at [www.3M.ca](http://www.3M.ca)**