

# **Safety Data Sheet**

Copyright,2020, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	06-1170-7	Version number:	14.01
Issue Date:	2020/10/09	Supercedes Date:	2018/01/24

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

# **SECTION 1: Identification**

1.1. Product identifier

3M<sup>TM</sup> Abrasive Products, Trizact<sup>TM</sup> 217EA A6, A16

### 1.2. Recommended use and restrictions on use

Intended Use Abrasive Product

**Restrictions on use** Not applicable

# 1.3. Supplier's details

Company:	3M Canada Company	
Division:	Abrasive Systems Division	
Address:	1840 Oxford Street East, Post Office Box 5757, London, Ontario	N6A 4T1
Telephone:	(800) 364-3577	
Website:	www.3M.ca	

### 1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

# **SECTION 2: Hazard identification**

### 2.1. Classification of the substance or mixture

Not classified according to the Canadian Hazardous Products Regulation.

**2.2. Label elements Signal word** Not applicable.

**Symbols** Not applicable.

**Pictograms** Not applicable.

# 2.3. Other hazards

None known.

31% of the mixture consists of ingredients of unknown acute oral toxicity.

# **SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Aluminum Oxide Mineral (non-	1344-28-1	30 - 40	Aluminum oxide (non-fibrous)
fibrous)			
Cloth Backing	Mixture	25 - 35	Not Applicable
Cured Resin	Mixture	25 - 35	Not Applicable
Inorganic Fluoride	14075-53-7	< 1.5	Borate(1-), tetrafluoro-, potassium
Titanium Dioxide	13463-67-7	< 1.5	Titanium oxide (TiO2)

# **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

### **Skin Contact:**

Wash with soap and water. If signs/symptoms develop, get medical attention.

### Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

# 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

# **4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

# **SECTION 5: Fire-fighting measures**

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

# 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

# Hazardous Decomposition or By-Products

<u>Substance</u> Carbon monoxide Carbon dioxide <u>Condition</u> During Combustion During Combustion

### 5.3. Special protective actions for fire-fighters

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

# **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Observe precautions from other sections.

### **6.2.** Environmental precautions

Not applicable.

### 6.3. Methods and material for containment and cleaning up

Not applicable.

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

For industrial or professional use only. Not for consumer sale or use. Avoid breathing of dust created by sanding, grinding or machining. Damaged product can break apart during use and cause serious injury to face or eyes. Check product for damage such as cracks or nicks prior to use. Replace if damaged. Always wear eye and face protection when working at sanding or grinding operations or when near such operations. Combustible dust may form by action of this product on another material (substrate). Dust generated from the substrate during use of this product may be explosive if in sufficient concentration with an ignition source. Dust deposits should not be allowed to accumulate on surfaces because of the potential for secondary explosions.

### 7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

# **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### **Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

C.A.S. No.	Agency	Limit type	Additional Comments
1344-28-1	ACGIH	TWA(respirable fraction):1	
		mg/m3	
13463-67-7	ACGIH	TWA:10 mg/m3	
	1344-28-1	1344-28-1 ACGIH	1344-28-1 ACGIH TWA(respirable fraction):1   mg/m3 TWA

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

### **8.2.** Exposure controls

### 8.2.1. Engineering controls

Provide appropriate local exhaust ventilation for sanding, grinding or machining. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Provide local exhaust at process emission sources to control exposure near the source and to prevent the escape of dust into the work area. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

### **8.2.2.** Personal protective equipment (PPE)

### Eye/face protection

To minimize the risk of injury to face and eyes, always wear eye and face protection when working at sanding or grinding operations or when near such operations. Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Safety Glasses with side shields

### **Skin/hand protection**

Wear appropriate gloves to minimize risk of injury to skin from contact with dust or physical abrasion from grinding or sanding.

### **Respiratory protection**

Assess exposure concentrations of all materials involved in the work process. Consider material being abraded when determining the appropriate respiratory protection. Select and use appropriate respirators to prevent inhalation overexposure. An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state	Solid
Colour	White-Tan
Odour	Slight Polymeric
Odour threshold	Not Applicable
рН	Not Applicable
Melting point/Freezing point	Not Applicable
Boiling point	Not Applicable
Flash Point	Not Applicable
Evaporation rate	Not Applicable
Flammability (solid, gas)	Not Classified
Flammable Limits(LEL)	Not Applicable
Flammable Limits(UEL)	Not Applicable
Vapour Pressure	Not Applicable
Viscosity/Kinematic Viscosity Viscosity/Kinematic	Not Applicable
Viscosity	
Relative density	Not Applicable
Water solubility	Not Applicable
Solubility- non-water	Not Applicable
Partition coefficient: n-octanol/ water	Not Applicable
Autoignition temperature	Not Applicable
Decomposition temperature	Not Applicable
Viscosity/Kinematic Viscosity	Not Applicable
Volatile Organic Compounds	
Percent volatile	
VOC Less H2O & Exempt Solvents	

### Nanoparticles

This material contains nanoparticles.

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

**10.2.** Chemical stability Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

**10.4. Conditions to avoid** None known.

**10.5. Incompatible materials** None known.

10.6. Hazardous decomposition products <u>Substance</u>

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

### Based on test data and/or information on the components, this material may produce the following health effects:

### Inhalation:

Dust from grinding, sanding or machining may cause irritation of the respiratory system. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

### **Skin Contact:**

Mechanical Skin irritation: Signs/symptoms may include abrasion, redness, pain, and itching. Allergic Skin Reaction (non-photo induced) in sensitive people: Signs/symptoms may include redness, swelling, blistering, and itching.

### Eye Contact:

Mechanical eye irritation: Signs/symptoms may include pain, redness, tearing and corneal abrasion. Dust created by grinding, sanding, or machining may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

### **Ingestion:**

Physical Blockage: Signs/symptoms may include cramping, abdominal pain, and constipation.

### **Carcinogenicity:**

### 3M<sup>TM</sup> Abrasive Products, Trizact<sup>TM</sup> 217EA A6, A16

Ingredient	CAS No.	Class Description	Regulation
Titanium Dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

### **Additional Information:**

This document covers only the 3M product. For complete assessment, when determining the degree of hazard, the material being abraded must also be considered. This product contains titanium dioxide. Cancer of the lungs has been observed in rats that inhaled high levels of titanium dioxide. No exposure to inhaled titanium dioxide is expected during the normal handling and use of this product. Titanium dioxide was not detected when air sampling was conducted during simulated use of similar products containing titanium dioxide. Therefore, the health effects associated with titanium dioxide are not expected during the normal use of this product.

### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

### **Acute Toxicity**

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Aluminum Oxide Mineral (non-fibrous)	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminum Oxide Mineral (non-fibrous)	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminum Oxide Mineral (non-fibrous)	Ingestion	Rat	LD50 > 5,000 mg/kg
Titanium Dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium Dioxide	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium Dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
Inorganic Fluoride	Dermal		LD50 estimated to be > 5,000 mg/kg
Inorganic Fluoride	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 5.3 mg/l
Inorganic Fluoride	Ingestion	Rat	LD50 5,854 mg/kg

ATE = acute toxicity estimate

#### **Skin Corrosion/Irritation**

Name	Species	Value
Aluminum Oxide Mineral (non-fibrous)	Rabbit	No significant irritation
Titanium Dioxide	Rabbit	No significant irritation
Inorganic Fluoride	Rabbit	No significant irritation

#### Serious Eye Damage/Irritation

Name	Species	Value
Aluminum Oxide Mineral (non-fibrous)	Rabbit	No significant irritation
Titanium Dioxide	Rabbit	No significant irritation
Inorganic Fluoride	Rabbit	No significant irritation

#### **Skin Sensitization**

Name	Species	Value
Titanium Dioxide	Human	Not classified
	and	
	animal	

### **Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

### Germ Cell Mutagenicity

Name	Route	Value

### 3M<sup>™</sup> Abrasive Products, Trizact<sup>™</sup> 217EA A6, A16

Aluminum Oxide Mineral (non-fibrous)	In Vitro	Not mutagenic
Titanium Dioxide	In Vitro	Not mutagenic
Titanium Dioxide	In vivo	Not mutagenic

# Carcinogenicity

Name	Route	Species	Value
Aluminum Oxide Mineral (non-fibrous)	Inhalation	Rat	Not carcinogenic
Titanium Dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium Dioxide	Inhalation	Rat	Carcinogenic

### **Reproductive Toxicity**

### **Reproductive and/or Developmental Effects**

For the component/components, either no data are currently available or the data are not sufficient for classification.

### Target Organ(s)

### Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Aluminum Oxide Mineral (non-fibrous)	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminum Oxide Mineral (non-fibrous)	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Titanium Dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium Dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure

### Specific Target Organ Toxicity - repeated exposure

### **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

# Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

No data available.

# **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

The substrate that was abraded must be considered as a factor in the disposal method for this product. Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. As a disposal alternative, utilize an acceptable permitted waste disposal facility.

# **SECTION 14: Transport Information**

Not regulated per U.S. DOT, IATA or IMO.

These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling, or marking requirements. The original 3M package is certified for Canadian ground shipment only. If you are shipping by air or ocean, the package may not meet applicable regulatory requirements.

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### **Global inventory status**

All applicable chemical ingredients in this material are listed on the European Inventory of Existing Chemical Substances (EINECS), or are exempt polymers whose monomers are listed on EINECS. Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory.

# **SECTION 16: Other information**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 0 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

# HMIS Hazard ClassificationHealth:0Flammability:1Physical Hazard:0Personal Protection:X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

### 3М<sup>тм</sup> Abrasive Products, Trizact<sup>тм</sup> 217EA A6, A16

Document group:	06-1170-7	Version number:	14.01
Issue Date:	2020/10/09	Supercedes Date:	2018/01/24

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

# 3M Canada SDSs are available at www.3M.ca